

# **MySQL 8.0 Error Message Reference**

---

## Abstract

This is the MySQL 8.0 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 8.0. This document accompanies [Error Messages and Common Problems](#), in [MySQL 8.0 Reference Manual](#).

For help with using MySQL, please visit the [MySQL Forums](#), where you can discuss your issues with other MySQL users.

Document generated on: 2025-05-16 (revision: 82027)

---

---

## Table of Contents

Preface and Legal Notices .....	v
1 MySQL Error Reference .....	1
2 Server Error Message Reference .....	3
3 Client Error Message Reference .....	645
4 Global Error Message Reference .....	653
Index .....	663



---

# Preface and Legal Notices

This is the MySQL 8.0 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 8.0.

## Legal Notices

Copyright © 1997, 2025, Oracle and/or its affiliates.

### License Restrictions

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

### Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

### Restricted Rights Notice

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

### Hazardous Applications Notice

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

### Trademark Notice

Oracle, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

### **Third-Party Content, Products, and Services Disclaimer**

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

### **Use of This Documentation**

This documentation is NOT distributed under a GPL license. Use of this documentation is subject to the following terms:

You may create a printed copy of this documentation solely for your own personal use. Conversion to other formats is allowed as long as the actual content is not altered or edited in any way. You shall not publish or distribute this documentation in any form or on any media, except if you distribute the documentation in a manner similar to how Oracle disseminates it (that is, electronically for download on a Web site with the software) or on a CD-ROM or similar medium, provided however that the documentation is disseminated together with the software on the same medium. Any other use, such as any dissemination of printed copies or use of this documentation, in whole or in part, in another publication, requires the prior written consent from an authorized representative of Oracle. Oracle and/or its affiliates reserve any and all rights to this documentation not expressly granted above.

## **Documentation Accessibility**

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

## **Access to Oracle Support for Accessibility**

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

---

# Chapter 1 MySQL Error Reference

This document provides a reference for the various types of error messages in MySQL:

- Error messages produced only by the server: [Chapter 2, \*Server Error Message Reference\*](#)

On the server side, error messages may occur during the startup and shutdown processes, as a result of issues that occur during SQL statement execution, and so forth.

- The MySQL server writes some error messages to its error log. These indicate issues of interest to database administrators or that require DBA action.
- The server sends other error messages to client programs. These indicate issues pertaining only to a particular client. The MySQL client library takes errors received from the server and makes them available to the host client program.
- Error messages that originate only from within the MySQL client library: [Chapter 3, \*Client Error Message Reference\*](#)

Client-side error messages are generated from within the MySQL client library, usually involving problems communicating with the server.

- Error messages that are shared between the server and the client library: [Chapter 4, \*Global Error Message Reference\*](#)

Some “global” error messages are shared in the sense that they can be produced by the MySQL server or by MySQL client programs.

For a description of the types of error information MySQL provides and how to obtain information about them, see [Error Messages and Common Problems](#), in [MySQL 8.0 Reference Manual](#).

---



---

## Chapter 2 Server Error Message Reference

The MySQL server writes some error messages to its error log, and sends others to client programs.

Example server-side error messages written to the error log:

```
2018-10-28T13:01:32.735983Z 0 [Note] [MY-010303] [Server] Skipping
generation of SSL certificates as options related to SSL are specified.

2018-10-02T03:20:39.410387Z 768 [ERROR] [MY-010045] [Server] Event Scheduler:
[evtuser@localhost][myschema.e_daily] Unknown database 'mydb'
```

Example server-side error message sent to client programs, as displayed by the `mysql` client:

```
mysql> SELECT * FROM no_such_table;
ERROR 1146 (42S02): Table 'test.no_such_table' doesn't exist
```

Each server error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#).

In addition to the errors in the following list, the server can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: [1002](#); Symbol: [ER\\_NO](#); SQLSTATE: [HY000](#)

Message: NO

Used in the construction of other messages.

- Error number: [1003](#); Symbol: [ER\\_YES](#); SQLSTATE: [HY000](#)

Message: YES

Used in the construction of other messages.

Extended [EXPLAIN](#) format generates Note messages. [ER\\_YES](#) is used in the [Code](#) column for these messages in subsequent [SHOW WARNINGS](#) output.

- Error number: [1004](#); Symbol: [ER\\_CANT\\_CREATE\\_FILE](#); SQLSTATE: [HY000](#)

Message: Can't create file '%s' (errno: %d - %s)

Occurs for failure to create or copy a file needed for some operation.

Possible causes: Permissions problem for source file; destination file already exists but is not writeable.

- Error number: [1005](#); Symbol: [ER\\_CANT\\_CREATE\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Can't create table '%s' (errno: %d - %s)

[InnoDB](#) reports this error when a table cannot be created. If the error message refers to error 150, table creation failed because a [foreign key constraint](#) was not correctly formed. If the error message refers to error -1, table creation probably failed because the table includes a column name that matched the name of an internal [InnoDB](#) table.

- Error number: [1006](#); Symbol: [ER\\_CANT\\_CREATE\\_DB](#); SQLSTATE: [HY000](#)

Message: Can't create database '%s' (errno: %d - %s)

- 
- Error number: [1007](#); Symbol: [ER\\_DB\\_CREATE\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Can't create database '%s'; database exists  
An attempt to create a database failed because the database already exists.  
Drop the database first if you really want to replace an existing database, or add an [IF NOT EXISTS](#) clause to the [CREATE DATABASE](#) statement if to retain an existing database without having the statement produce an error.
  - Error number: [1008](#); Symbol: [ER\\_DB\\_DROP\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Can't drop database '%s'; database doesn't exist
  - Error number: [1010](#); Symbol: [ER\\_DB\\_DROP\\_RMDIR](#); SQLSTATE: [HY000](#)  
Message: Error dropping database (can't rmdir '%s', errno: %d - %s)
  - Error number: [1012](#); Symbol: [ER\\_CANT\\_FIND\\_SYSTEM\\_REC](#); SQLSTATE: [HY000](#)  
Message: Can't read record in system table  
Returned by [InnoDB](#) for attempts to access [InnoDB INFORMATION\\_SCHEMA](#) tables when [InnoDB](#) is unavailable.
  - Error number: [1013](#); Symbol: [ER\\_CANT\\_GET\\_STAT](#); SQLSTATE: [HY000](#)  
Message: Can't get status of '%s' (errno: %d - %s)
  - Error number: [1015](#); Symbol: [ER\\_CANT\\_LOCK](#); SQLSTATE: [HY000](#)  
Message: Can't lock file (errno: %d - %s)
  - Error number: [1016](#); Symbol: [ER\\_CANT\\_OPEN\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Can't open file: '%s' (errno: %d - %s)  
[InnoDB](#) reports this error when the table from the [InnoDB data files](#) cannot be found.
  - Error number: [1017](#); Symbol: [ER\\_FILE\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: Can't find file: '%s' (errno: %d - %s)
  - Error number: [1018](#); Symbol: [ER\\_CANT\\_READ\\_DIR](#); SQLSTATE: [HY000](#)  
Message: Can't read dir of '%s' (errno: %d - %s)
  - Error number: [1020](#); Symbol: [ER\\_CHECKREAD](#); SQLSTATE: [HY000](#)  
Message: Record has changed since last read in table '%s'
  - Error number: [1022](#); Symbol: [ER\\_DUP\\_KEY](#); SQLSTATE: [23000](#)  
Message: Can't write; duplicate key in table '%s'
  - Error number: [1024](#); Symbol: [ER\\_ERROR\\_ON\\_READ](#); SQLSTATE: [HY000](#)  
Message: Error reading file '%s' (errno: %d - %s)
  - Error number: [1025](#); Symbol: [ER\\_ERROR\\_ON\\_RENAME](#); SQLSTATE: [HY000](#)

---

Message: Error on rename of '%s' to '%s' (errno: %d - %s)

- Error number: 1026; Symbol: [ER\\_ERROR\\_ON\\_WRITE](#); SQLSTATE: [HY000](#)

Message: Error writing file '%s' (errno: %d - %s)

- Error number: 1027; Symbol: [ER\\_FILE\\_USED](#); SQLSTATE: [HY000](#)

Message: '%s' is locked against change

- Error number: 1028; Symbol: [ER\\_FILSORT\\_ABORT](#); SQLSTATE: [HY000](#)

Message: Sort aborted

[ER\\_FILSORT\\_ABORT](#) was removed after 8.0.18.

- Error number: 1030; Symbol: [ER\\_GET\\_ERRNO](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' from storage engine

Check the %d value to see what the OS error means. For example, 28 indicates that you have run out of disk space.

- Error number: 1031; Symbol: [ER\\_ILLEGAL HA](#); SQLSTATE: [HY000](#)

Message: Table storage engine for '%s' doesn't have this option

- Error number: 1032; Symbol: [ER\\_KEY\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Can't find record in '%s'

- Error number: 1033; Symbol: [ER\\_NOT FORM FILE](#); SQLSTATE: [HY000](#)

Message: Incorrect information in file: '%s'

- Error number: 1034; Symbol: [ER\\_NOT KEYFILE](#); SQLSTATE: [HY000](#)

Message: Incorrect key file for table '%s'; try to repair it

- Error number: 1035; Symbol: [ER\\_OLD KEYFILE](#); SQLSTATE: [HY000](#)

Message: Old key file for table '%s'; repair it!

- Error number: 1036; Symbol: [ER\\_OPEN AS READONLY](#); SQLSTATE: [HY000](#)

Message: Table '%s' is read only

- Error number: 1037; Symbol: [ER\\_OUTOFMEMORY](#); SQLSTATE: [HY001](#)

Message: Out of memory; restart server and try again (needed %d bytes)

- Error number: 1038; Symbol: [ER\\_OUT\\_OF\\_SORTMEMORY](#); SQLSTATE: [HY001](#)

Message: Out of sort memory, consider increasing server sort buffer size

- Error number: 1040; Symbol: [ER\\_CON\\_COUNT\\_ERROR](#); SQLSTATE: [08004](#)

Message: Too many connections

- Error number: 1041; Symbol: ER\_OUT\_OF\_RESOURCES; SQLSTATE: HY000

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

- Error number: 1042; Symbol: ER\_BAD\_HOST\_ERROR; SQLSTATE: 08S01

Message: Can't get hostname for your address

- Error number: 1043; Symbol: ER\_HANDSHAKE\_ERROR; SQLSTATE: 08S01

Message: Bad handshake

- Error number: 1044; Symbol: ER\_DBACCESS\_DENIED\_ERROR; SQLSTATE: 42000

Message: Access denied for user '%s'@'%s' to database '%s'

- Error number: 1045; Symbol: ER\_ACCESS\_DENIED\_ERROR; SQLSTATE: 28000

Message: Access denied for user '%s'@'%s' (using password: %s)

- Error number: 1046; Symbol: ER\_NO\_DB\_ERROR; SQLSTATE: 3D000

Message: No database selected

- Error number: 1047; Symbol: ER\_UNKNOWN\_COM\_ERROR; SQLSTATE: 08S01

Message: Unknown command

- Error number: 1048; Symbol: ER\_BAD\_NULL\_ERROR; SQLSTATE: 23000

Message: Column '%s' cannot be null

- Error number: 1049; Symbol: ER\_BAD\_DB\_ERROR; SQLSTATE: 42000

Message: Unknown database '%s'

- Error number: 1050; Symbol: ER\_TABLE\_EXISTS\_ERROR; SQLSTATE: 42S01

Message: Table '%s' already exists

- Error number: 1051; Symbol: ER\_BAD\_TABLE\_ERROR; SQLSTATE: 42S02

Message: Unknown table '%s'

- Error number: 1052; Symbol: ER\_NON\_UNIQ\_ERROR; SQLSTATE: 23000

Message: Column '%s' in %s is ambiguous

```
%s = column name
%s = location of column (for example, "field list")
```

Likely cause: A column appears in a query without appropriate qualification, such as in a select list or ON clause.

Examples:

```
mysql> SELECT i FROM t INNER JOIN t AS t2;
ERROR 1052 (23000): Column 'i' in field list is ambiguous

mysql> SELECT * FROM t LEFT JOIN t AS t2 ON i = i;
```

---

```
ERROR 1052 (23000): Column 'i' in on clause is ambiguous
```

Resolution:

- Qualify the column with the appropriate table name:

```
mysql> SELECT t2.i FROM t INNER JOIN t AS t2;
```

- Modify the query to avoid the need for qualification:

```
mysql> SELECT * FROM t LEFT JOIN t AS t2 USING (i);
```

- Error number: [1053](#); Symbol: [ER\\_SERVER\\_SHUTDOWN](#); SQLSTATE: [08S01](#)

Message: Server shutdown in progress

- Error number: [1054](#); Symbol: [ER\\_BAD\\_FIELD\\_ERROR](#); SQLSTATE: [42S22](#)

Message: Unknown column '%s' in '%s'

- Error number: [1055](#); Symbol: [ER\\_WRONG\\_FIELD\\_WITH\\_GROUP](#); SQLSTATE: [42000](#)

Message: '%s' isn't in GROUP BY

- Error number: [1056](#); Symbol: [ER\\_WRONG\\_GROUP\\_FIELD](#); SQLSTATE: [42000](#)

Message: Can't group on '%s'

- Error number: [1057](#); Symbol: [ER\\_WRONG\\_SUM\\_SELECT](#); SQLSTATE: [42000](#)

Message: Statement has sum functions and columns in same statement

- Error number: [1058](#); Symbol: [ER\\_WRONG\\_VALUE\\_COUNT](#); SQLSTATE: [21S01](#)

Message: Column count doesn't match value count

- Error number: [1059](#); Symbol: [ER\\_TOO\\_LONG\\_IDENT](#); SQLSTATE: [42000](#)

Message: Identifier name '%s' is too long

- Error number: [1060](#); Symbol: [ER\\_DUP\\_FIELDNAME](#); SQLSTATE: [42S21](#)

Message: Duplicate column name '%s'

- Error number: [1061](#); Symbol: [ER\\_DUP\\_KEYNAME](#); SQLSTATE: [42000](#)

Message: Duplicate key name '%s'

- Error number: [1062](#); Symbol: [ER\\_DUP\\_ENTRY](#); SQLSTATE: [23000](#)

Message: Duplicate entry '%s' for key %d

The message returned with this error uses the format string for [ER\\_DUP\\_ENTRY\\_WITH\\_KEY\\_NAME](#).

- Error number: [1063](#); Symbol: [ER\\_WRONG\\_FIELD\\_SPEC](#); SQLSTATE: [42000](#)

Message: Incorrect column specifier for column '%s'

- Error number: [1064](#); Symbol: [ER\\_PARSE\\_ERROR](#); SQLSTATE: [42000](#)

Message: %s near '%s' at line %d

- 
- Error number: [1065](#); Symbol: [ER\\_EMPTY\\_QUERY](#); SQLSTATE: [42000](#)  
Message: Query was empty
  - Error number: [1066](#); Symbol: [ER\\_NONUNIQ\\_TABLE](#); SQLSTATE: [42000](#)  
Message: Not unique table/alias: '%s'
  - Error number: [1067](#); Symbol: [ER\\_INVALID\\_DEFAULT](#); SQLSTATE: [42000](#)  
Message: Invalid default value for '%s'
  - Error number: [1068](#); Symbol: [ER\\_MULTIPLE\\_PRI\\_KEY](#); SQLSTATE: [42000](#)  
Message: Multiple primary key defined
  - Error number: [1069](#); Symbol: [ER\\_TOO\\_MANY\\_KEYS](#); SQLSTATE: [42000](#)  
Message: Too many keys specified; max %d keys allowed
  - Error number: [1070](#); Symbol: [ER\\_TOO\\_MANY\\_KEY\\_PARTS](#); SQLSTATE: [42000](#)  
Message: Too many key parts specified; max %d parts allowed
  - Error number: [1071](#); Symbol: [ER\\_TOO\\_LONG\\_KEY](#); SQLSTATE: [42000](#)  
Message: Specified key was too long; max key length is %d bytes
  - Error number: [1072](#); Symbol: [ER\\_KEY\\_COLUMN\\_DOES\\_NOT\\_EXISTS](#); SQLSTATE: [42000](#)  
Message: Key column '%s' doesn't exist in table
  - Error number: [1073](#); Symbol: [ER\\_BLOB\\_USED\\_AS\\_KEY](#); SQLSTATE: [42000](#)  
Message: BLOB column '%s' can't be used in key specification with the used table type
  - Error number: [1074](#); Symbol: [ER\\_TOO\\_BIG\\_FIELDLENGTH](#); SQLSTATE: [42000](#)  
Message: Column length too big for column '%s' (max = %lu); use BLOB or TEXT instead
  - Error number: [1075](#); Symbol: [ER\\_WRONG\\_AUTO\\_KEY](#); SQLSTATE: [42000](#)  
Message: Incorrect table definition; there can be only one auto column and it must be defined as a key
  - Error number: [1076](#); Symbol: [ER\\_READY](#); SQLSTATE: [HY000](#)  
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d
  - Error number: [1077](#); Symbol: [ER\\_NORMAL\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: %s: Normal shutdown  
[ER\\_NORMAL\\_SHUTDOWN](#) was removed after 8.0.4.
  - Error number: [1079](#); Symbol: [ER\\_SHUTDOWN\\_COMPLETE](#); SQLSTATE: [HY000](#)  
Message: %s: Shutdown complete
  - Error number: [1080](#); Symbol: [ER\\_FORCING\\_CLOSE](#); SQLSTATE: [08S01](#)  
Message: %s: Forcing close of thread %ld user: '%s'

- 
- Error number: [1081](#); Symbol: [ER\\_IPSOCK\\_ERROR](#); SQLSTATE: [08S01](#)  
Message: Can't create IP socket
  - Error number: [1082](#); Symbol: [ER\\_NO\\_SUCH\\_INDEX](#); SQLSTATE: [42S12](#)  
Message: Table '%s' has no index like the one used in CREATE INDEX; recreate the table
  - Error number: [1083](#); Symbol: [ER\\_WRONG\\_FIELD\\_TERMINATORS](#); SQLSTATE: [42000](#)  
Message: Field separator argument is not what is expected; check the manual
  - Error number: [1084](#); Symbol: [ER\\_BLOBS\\_AND\\_NO\\_TERMINATED](#); SQLSTATE: [42000](#)  
Message: You can't use fixed rowlength with BLOBs; please use 'fields terminated by'
  - Error number: [1085](#); Symbol: [ER\\_TEXTFILE\\_NOT\\_READABLE](#); SQLSTATE: [HY000](#)  
Message: The file '%s' must be in the database directory or be readable by all
  - Error number: [1086](#); Symbol: [ER\\_FILE\\_EXISTS\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: File '%s' already exists
  - Error number: [1087](#); Symbol: [ER\\_LOAD\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Records: %ld Deleted: %ld Skipped: %ld Warnings: %ld
  - Error number: [1088](#); Symbol: [ER\\_ALTER\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Records: %ld Duplicates: %ld
  - Error number: [1089](#); Symbol: [ER\\_WRONG\\_SUB\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Incorrect prefix key; the used key part isn't a string, the used length is longer than the key part, or the storage engine doesn't support unique prefix keys
  - Error number: [1090](#); Symbol: [ER\\_CANT\\_REMOVE\\_ALL\\_FIELDS](#); SQLSTATE: [42000](#)  
Message: You can't delete all columns with ALTER TABLE; use DROP TABLE instead
  - Error number: [1091](#); Symbol: [ER\\_CANT\\_DROP\\_FIELD\\_OR\\_KEY](#); SQLSTATE: [42000](#)  
Message: Can't DROP '%s'; check that column/key exists
  - Error number: [1092](#); Symbol: [ER\\_INSERT\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Records: %ld Duplicates: %ld Warnings: %ld
  - Error number: [1093](#); Symbol: [ER\\_UPDATE\\_TABLE\\_USED](#); SQLSTATE: [HY000](#)  
Message: You can't specify target table '%s' for update in FROM clause  
  
This error occurs for attempts to select from and modify the same table within a single statement. If the select attempt occurs within a derived table, you can avoid this error by setting the [derived\\_merge](#) flag of the [optimizer\\_switch](#) system variable to force the subquery to be materialized into a temporary table, which effectively causes it to be a different table from the one modified. See [Optimizing Derived Tables, View References, and Common Table Expressions with Merging or Materialization](#).
  - Error number: [1094](#); Symbol: [ER\\_NO\\_SUCH\\_THREAD](#); SQLSTATE: [HY000](#)
-

- 
- Message: Unknown thread id: %lu
- Error number: 1095; Symbol: `ER_KILL_DENIED_ERROR`; SQLSTATE: HY000  
Message: You are not owner of thread %lu
  - Error number: 1096; Symbol: `ER_NO_TABLES_USED`; SQLSTATE: HY000  
Message: No tables used
  - Error number: 1097; Symbol: `ER_TOO_BIG_SET`; SQLSTATE: HY000  
Message: Too many strings for column %s and SET
  - Error number: 1098; Symbol: `ER_NO_UNIQUE_LOGFILE`; SQLSTATE: HY000  
Message: Can't generate a unique log-filename %s.(1-999)
  - Error number: 1099; Symbol: `ER_TABLE_NOT_LOCKED_FOR_WRITE`; SQLSTATE: HY000  
Message: Table '%s' was locked with a READ lock and can't be updated
  - Error number: 1100; Symbol: `ER_TABLE_NOT_LOCKED`; SQLSTATE: HY000  
Message: Table '%s' was not locked with LOCK TABLES
  - Error number: 1101; Symbol: `ER_BLOB_CANT_HAVE_DEFAULT`; SQLSTATE: 42000  
Message: BLOB, TEXT, GEOMETRY or JSON column '%s' can't have a default value
  - Error number: 1102; Symbol: `ER_WRONG_DB_NAME`; SQLSTATE: 42000  
Message: Incorrect database name '%s'
  - Error number: 1103; Symbol: `ER_WRONG_TABLE_NAME`; SQLSTATE: 42000  
Message: Incorrect table name '%s'
  - Error number: 1104; Symbol: `ER_TOO_BIG_SELECT`; SQLSTATE: 42000  
Message: The SELECT would examine more than MAX\_JOIN\_SIZE rows; check your WHERE and use SET SQL\_BIG\_SELECTS=1 or SET MAX\_JOIN\_SIZE=# if the SELECT is okay
  - Error number: 1105; Symbol: `ER_UNKNOWN_ERROR`; SQLSTATE: HY000  
Message: Unknown error
  - Error number: 1106; Symbol: `ER_UNKNOWN_PROCEDURE`; SQLSTATE: 42000  
Message: Unknown procedure '%s'
  - Error number: 1107; Symbol: `ER_WRONG_PARAMCOUNT_TO_PROCEDURE`; SQLSTATE: 42000  
Message: Incorrect parameter count to procedure '%s'
  - Error number: 1108; Symbol: `ER_WRONG_PARAMETERS_TO_PROCEDURE`; SQLSTATE: HY000  
Message: Incorrect parameters to procedure '%s'
  - Error number: 1109; Symbol: `ER_UNKNOWN_TABLE`; SQLSTATE: 42S02



---

Message: Unknown table '%s' in %s

- Error number: 1110; Symbol: `ER_FIELD_SPECIFIED_TWICE`; SQLSTATE: 42000

Message: Column '%s' specified twice

- Error number: 1111; Symbol: `ER_INVALID_GROUP_FUNC_USE`; SQLSTATE: HY000

Message: Invalid use of group function

- Error number: 1112; Symbol: `ER_UNSUPPORTED_EXTENSION`; SQLSTATE: 42000

Message: Table '%s' uses an extension that doesn't exist in this MySQL version

- Error number: 1113; Symbol: `ER_TABLE_MUST_HAVE_COLUMNS`; SQLSTATE: 42000

Message: A table must have at least 1 column

- Error number: 1114; Symbol: `ER_RECORD_FILE_FULL`; SQLSTATE: HY000

Message: The table '%s' is full

`InnoDB` reports this error when the system tablespace runs out of free space. Reconfigure the system tablespace to add a new data file.

- Error number: 1115; Symbol: `ER_UNKNOWN_CHARACTER_SET`; SQLSTATE: 42000

Message: Unknown character set: '%s'

- Error number: 1116; Symbol: `ER_TOO_MANY_TABLES`; SQLSTATE: HY000

Message: Too many tables; MySQL can only use %d tables in a join

- Error number: 1117; Symbol: `ER_TOO_MANY_FIELDS`; SQLSTATE: HY000

Message: Too many columns

- Error number: 1118; Symbol: `ER_TOO_BIG_ROWSIZE`; SQLSTATE: 42000

Message: Row size too large. The maximum row size for the used table type, not counting BLOBs, is %ld. This includes storage overhead, check the manual. You have to change some columns to TEXT or BLOBs

- Error number: 1119; Symbol: `ER_STACK_OVERRUN`; SQLSTATE: HY000

Message: Thread stack overrun: Used: %ld of a %ld stack. Use 'mysqld --thread\_stack=#' to specify a bigger stack if needed

- Error number: 1120; Symbol: `ER_WRONG_OUTER_JOIN`; SQLSTATE: 42000

Message: Cross dependency found in OUTER JOIN; examine your ON conditions

`ER_WRONG_OUTER_JOIN` was removed after 8.0.0.

- Error number: 1120; Symbol: `ER_WRONG_OUTER_JOIN_UNUSED`; SQLSTATE: 42000

Message: Cross dependency found in OUTER JOIN; examine your ON conditions

`ER_WRONG_OUTER_JOIN_UNUSED` was added in 8.0.1.

- 
- Error number: [1121](#); Symbol: [ER\\_NULL\\_COLUMN\\_IN\\_INDEX](#); SQLSTATE: [42000](#)  
Message: Table handler doesn't support NULL in given index. Please change column '%s' to be NOT NULL or use another handler
  - Error number: [1122](#); Symbol: [ER\\_CANT\\_FIND\\_UDF](#); SQLSTATE: [HY000](#)  
Message: Can't load function '%s'
  - Error number: [1123](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_UDF](#); SQLSTATE: [HY000](#)  
Message: Can't initialize function '%s'; %s
  - Error number: [1124](#); Symbol: [ER\\_UDF\\_NO\\_PATHS](#); SQLSTATE: [HY000](#)  
Message: No paths allowed for shared library
  - Error number: [1125](#); Symbol: [ER\\_UDF\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Function '%s' already exists
  - Error number: [1126](#); Symbol: [ER\\_CANT\\_OPEN\\_LIBRARY](#); SQLSTATE: [HY000](#)  
Message: Can't open shared library '%s' (errno: %d %s)
  - Error number: [1127](#); Symbol: [ER\\_CANT\\_FIND\\_DL\\_ENTRY](#); SQLSTATE: [HY000](#)  
Message: Can't find symbol '%s' in library
  - Error number: [1128](#); Symbol: [ER\\_FUNCTION\\_NOT\\_DEFINED](#); SQLSTATE: [HY000](#)  
Message: Function '%s' is not defined
  - Error number: [1129](#); Symbol: [ER\\_HOST\\_IS\\_BLOCKED](#); SQLSTATE: [HY000](#)  
Message: Host '%s' is blocked because of many connection errors; unblock with 'mysqladmin flush-hosts'
  - Error number: [1130](#); Symbol: [ER\\_HOST\\_NOT\\_PRIVILEGED](#); SQLSTATE: [HY000](#)  
Message: Host '%s' is not allowed to connect to this MySQL server
  - Error number: [1131](#); Symbol: [ER\\_PASSWORD\\_ANONYMOUS\\_USER](#); SQLSTATE: [42000](#)  
Message: You are using MySQL as an anonymous user and anonymous users are not allowed to change passwords
  - Error number: [1132](#); Symbol: [ER\\_PASSWORD\\_NOT\\_ALLOWED](#); SQLSTATE: [42000](#)  
Message: You must have privileges to update tables in the mysql database to be able to change passwords for others
  - Error number: [1133](#); Symbol: [ER\\_PASSWORD\\_NO\\_MATCH](#); SQLSTATE: [42000](#)  
Message: Can't find any matching row in the user table
  - Error number: [1134](#); Symbol: [ER\\_UPDATE\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Rows matched: %ld Changed: %ld Warnings: %ld

- 
- Error number: [1135](#); Symbol: [ER\\_CANT\\_CREATE\\_THREAD](#); SQLSTATE: [HY000](#)  
Message: Can't create a new thread (errno %d); if you are not out of available memory, you can consult the manual for a possible OS-dependent bug
  - Error number: [1136](#); Symbol: [ER\\_WRONG\\_VALUE\\_COUNT\\_ON\\_ROW](#); SQLSTATE: [21S01](#)  
Message: Column count doesn't match value count at row %ld
  - Error number: [1137](#); Symbol: [ER\\_CANT\\_REOPEN\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Can't reopen table: '%s'
  - Error number: [1138](#); Symbol: [ER\\_INVALID\\_USE\\_OF\\_NULL](#); SQLSTATE: [22004](#)  
Message: Invalid use of NULL value
  - Error number: [1139](#); Symbol: [ER\\_REGEX\\_ERROR](#); SQLSTATE: [42000](#)  
Message: Got error '%s' from regexp
  - Error number: [1140](#); Symbol: [ER\\_MIX\\_OF\\_GROUP\\_FUNC\\_AND\\_FIELDS](#); SQLSTATE: [42000](#)  
Message: Mixing of GROUP columns (MIN(),MAX(),COUNT(),...) with no GROUP columns is illegal if there is no GROUP BY clause
  - Error number: [1141](#); Symbol: [ER\\_NONEXISTING\\_GRANT](#); SQLSTATE: [42000](#)  
Message: There is no such grant defined for user '%s' on host '%s'
  - Error number: [1142](#); Symbol: [ER\\_TABLEACCESS\\_DENIED\\_ERROR](#); SQLSTATE: [42000](#)  
Message: %s command denied to user '%s'@'%s' for table '%s'
  - Error number: [1143](#); Symbol: [ER\\_COLUMNACCESS\\_DENIED\\_ERROR](#); SQLSTATE: [42000](#)  
Message: %s command denied to user '%s'@'%s' for column '%s' in table '%s'
  - Error number: [1144](#); Symbol: [ER\\_ILLEGAL\\_GRANT\\_FOR\\_TABLE](#); SQLSTATE: [42000](#)  
Message: Illegal GRANT/REVOKE command; please consult the manual to see which privileges can be used
  - Error number: [1145](#); Symbol: [ER\\_GRANT\\_WRONG\\_HOST\\_OR\\_USER](#); SQLSTATE: [42000](#)  
Message: The host or user argument to GRANT is too long
  - Error number: [1146](#); Symbol: [ER\\_NO\\_SUCH\\_TABLE](#); SQLSTATE: [42S02](#)  
Message: Table '%s.%s' doesn't exist
  - Error number: [1147](#); Symbol: [ER\\_NONEXISTING\\_TABLE\\_GRANT](#); SQLSTATE: [42000](#)  
Message: There is no such grant defined for user '%s' on host '%s' on table '%s'
  - Error number: [1148](#); Symbol: [ER\\_NOT\\_ALLOWED\\_COMMAND](#); SQLSTATE: [42000](#)  
Message: The used command is not allowed with this MySQL version
  - Error number: [1149](#); Symbol: [ER\\_SYNTAX\\_ERROR](#); SQLSTATE: [42000](#)

---

Message: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use

- Error number: [1152](#); Symbol: [ER\\_ABORTING\\_CONNECTION](#); SQLSTATE: [08S01](#)

Message: Aborted connection %ld to db: '%s' user: '%s' (%s)

- Error number: [1153](#); Symbol: [ER\\_NET\\_PACKET\\_TOO\\_LARGE](#); SQLSTATE: [08S01](#)

Message: Got a packet bigger than 'max\_allowed\_packet' bytes

- Error number: [1154](#); Symbol: [ER\\_NET\\_READ\\_ERROR\\_FROM\\_PIPE](#); SQLSTATE: [08S01](#)

Message: Got a read error from the connection pipe

- Error number: [1155](#); Symbol: [ER\\_NET\\_FCNTL\\_ERROR](#); SQLSTATE: [08S01](#)

Message: Got an error from fcntl()

- Error number: [1156](#); Symbol: [ER\\_NET\\_PACKETS\\_OUT\\_OF\\_ORDER](#); SQLSTATE: [08S01](#)

Message: Got packets out of order

- Error number: [1157](#); Symbol: [ER\\_NET\\_UNCOMPRESS\\_ERROR](#); SQLSTATE: [08S01](#)

Message: Couldn't uncompress communication packet

- Error number: [1158](#); Symbol: [ER\\_NET\\_READ\\_ERROR](#); SQLSTATE: [08S01](#)

Message: Got an error reading communication packets

- Error number: [1159](#); Symbol: [ER\\_NET\\_READ\\_INTERRUPTED](#); SQLSTATE: [08S01](#)

Message: Got timeout reading communication packets

- Error number: [1160](#); Symbol: [ER\\_NET\\_ERROR\\_ON\\_WRITE](#); SQLSTATE: [08S01](#)

Message: Got an error writing communication packets

- Error number: [1161](#); Symbol: [ER\\_NET\\_WRITE\\_INTERRUPTED](#); SQLSTATE: [08S01](#)

Message: Got timeout writing communication packets

- Error number: [1162](#); Symbol: [ER\\_TOO\\_LONG\\_STRING](#); SQLSTATE: [42000](#)

Message: Result string is longer than 'max\_allowed\_packet' bytes

- Error number: [1163](#); Symbol: [ER\\_TABLE\\_CANT\\_HANDLE\\_BLOB](#); SQLSTATE: [42000](#)

Message: The used table type doesn't support BLOB/TEXT columns

- Error number: [1164](#); Symbol: [ER\\_TABLE\\_CANT\\_HANDLE\\_AUTO\\_INCREMENT](#); SQLSTATE: [42000](#)

Message: The used table type doesn't support AUTO\_INCREMENT columns

- Error number: [1166](#); Symbol: [ER\\_WRONG\\_COLUMN\\_NAME](#); SQLSTATE: [42000](#)

Message: Incorrect column name '%s'

- 
- Error number: [1167](#); Symbol: [ER\\_WRONG\\_KEY\\_COLUMN](#); SQLSTATE: [42000](#)  
Message: The used storage engine can't index column '%s'
  - Error number: [1168](#); Symbol: [ER\\_WRONG\\_MRG\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Unable to open underlying table which is differently defined or of non-MyISAM type or doesn't exist
  - Error number: [1169](#); Symbol: [ER\\_DUP\\_UNIQUE](#); SQLSTATE: [23000](#)  
Message: Can't write, because of unique constraint, to table '%s'
  - Error number: [1170](#); Symbol: [ER\\_BLOB\\_KEY\\_WITHOUT\\_LENGTH](#); SQLSTATE: [42000](#)  
Message: BLOB/TEXT column '%s' used in key specification without a key length
  - Error number: [1171](#); Symbol: [ER\\_PRIMARY\\_CANT\\_HAVE\\_NULL](#); SQLSTATE: [42000](#)  
Message: All parts of a PRIMARY KEY must be NOT NULL; if you need NULL in a key, use UNIQUE instead
  - Error number: [1172](#); Symbol: [ER\\_TOO\\_MANY\\_ROWS](#); SQLSTATE: [42000](#)  
Message: Result consisted of more than one row
  - Error number: [1173](#); Symbol: [ER\\_REQUIRES\\_PRIMARY\\_KEY](#); SQLSTATE: [42000](#)  
Message: This table type requires a primary key
  - Error number: [1175](#); Symbol: [ER\\_UPDATE\\_WITHOUT\\_KEY\\_IN\\_SAFE\\_MODE](#); SQLSTATE: [HY000](#)  
Message: You are using safe update mode and you tried to update a table without a WHERE that uses a KEY column. %s
  - Error number: [1176](#); Symbol: [ER\\_KEY\\_DOES\\_NOT\\_EXISTS](#); SQLSTATE: [42000](#)  
Message: Key '%s' doesn't exist in table '%s'
  - Error number: [1177](#); Symbol: [ER\\_CHECK\\_NO\\_SUCH\\_TABLE](#); SQLSTATE: [42000](#)  
Message: Can't open table
  - Error number: [1178](#); Symbol: [ER\\_CHECK\\_NOT\\_IMPLEMENTED](#); SQLSTATE: [42000](#)  
Message: The storage engine for the table doesn't support %s
  - Error number: [1179](#); Symbol: [ER\\_CANT\\_DO\\_THIS\\_DURING\\_AN\\_TRANSACTION](#); SQLSTATE: [25000](#)  
Message: You are not allowed to execute this command in a transaction
  - Error number: [1180](#); Symbol: [ER\\_ERROR\\_DURING\\_COMMIT](#); SQLSTATE: [HY000](#)  
Message: Got error %d - '%s' during COMMIT
  - Error number: [1181](#); Symbol: [ER\\_ERROR\\_DURING\\_ROLLBACK](#); SQLSTATE: [HY000](#)  
Message: Got error %d - '%s' during ROLLBACK
  - Error number: [1182](#); Symbol: [ER\\_ERROR\\_DURING\\_FLUSH\\_LOGS](#); SQLSTATE: [HY000](#)

---

Message: Got error %d during FLUSH\_LOGS

- Error number: 1184; Symbol: `ER_NEW_ABORTING_CONNECTION`; SQLSTATE: 08S01

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s)

- Error number: 1188; Symbol: `ER_MASTER`; SQLSTATE: HY000

Message: Error from master: '%s'

`ER_MASTER` was removed after 8.0.32.

- Error number: 1188; Symbol: `ER_SOURCE`; SQLSTATE: HY000

Message: Error from source: '%s'

`ER_SOURCE` was added in 8.0.33.

- Error number: 1189; Symbol: `ER_MASTER_NET_READ`; SQLSTATE: 08S01

Message: Net error reading from master

`ER_MASTER_NET_READ` was removed after 8.0.32.

- Error number: 1189; Symbol: `ER_SOURCE_NET_READ`; SQLSTATE: 08S01

Message: Net error reading from source

`ER_SOURCE_NET_READ` was added in 8.0.33.

- Error number: 1190; Symbol: `ER_MASTER_NET_WRITE`; SQLSTATE: 08S01

Message: Net error writing to master

`ER_MASTER_NET_WRITE` was removed after 8.0.32.

- Error number: 1190; Symbol: `ER_SOURCE_NET_WRITE`; SQLSTATE: 08S01

Message: Net error writing to source

`ER_SOURCE_NET_WRITE` was added in 8.0.33.

- Error number: 1191; Symbol: `ER_FT_MATCHING_KEY_NOT_FOUND`; SQLSTATE: HY000

Message: Can't find FULLTEXT index matching the column list

- Error number: 1192; Symbol: `ER_LOCK_OR_ACTIVE_TRANSACTION`; SQLSTATE: HY000

Message: Can't execute the given command because you have active locked tables or an active transaction

- Error number: 1193; Symbol: `ER_UNKNOWN_SYSTEM_VARIABLE`; SQLSTATE: HY000

Message: Unknown system variable '%s'

- Error number: 1194; Symbol: `ER_CRASHED_ON_USAGE`; SQLSTATE: HY000

Message: Table '%s' is marked as crashed and should be repaired

- 
- Error number: [1195](#); Symbol: [ER\\_CRASHED\\_ON\\_REPAIR](#); SQLSTATE: [HY000](#)  
Message: Table '%s' is marked as crashed and last (automatic?) repair failed
  - Error number: [1196](#); Symbol: [ER\\_WARNING\\_NOT\\_COMPLETE\\_ROLLBACK](#); SQLSTATE: [HY000](#)  
Message: Some non-transactional changed tables couldn't be rolled back
  - Error number: [1197](#); Symbol: [ER\\_TRANS\\_CACHE\\_FULL](#); SQLSTATE: [HY000](#)  
Message: Multi-statement transaction required more than 'max\_binlog\_cache\_size' bytes of storage; increase this mysqld variable and try again
  - Error number: [1199](#); Symbol: [ER\\_SLAVE\\_NOT\\_RUNNING](#); SQLSTATE: [HY000](#)  
Message: This operation requires a running slave; configure slave and do START SLAVE  
[ER\\_SLAVE\\_NOT\\_RUNNING](#) was removed after 8.0.32.
  - Error number: [1199](#); Symbol: [ER\\_REPLICA\\_NOT\\_RUNNING](#); SQLSTATE: [HY000](#)  
Message: This operation requires a running replica; configure replica and do START REPLICA  
[ER\\_REPLICA\\_NOT\\_RUNNING](#) was added in 8.0.33.
  - Error number: [1200](#); Symbol: [ER\\_BAD\\_SLAVE](#); SQLSTATE: [HY000](#)  
Message: The server is not configured as slave; fix in config file or with CHANGE MASTER TO  
[ER\\_BAD\\_SLAVE](#) was removed after 8.0.32.
  - Error number: [1200](#); Symbol: [ER\\_BAD\\_REPLICA](#); SQLSTATE: [HY000](#)  
Message: The server is not configured as replica; fix in config file or with CHANGE REPLICATION SOURCE TO  
[ER\\_BAD\\_REPLICA](#) was added in 8.0.33.
  - Error number: [1201](#); Symbol: [ER\\_MASTER\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Could not initialize master info structure; more error messages can be found in the MySQL error log  
[ER\\_MASTER\\_INFO](#) was removed after 8.0.32.
  - Error number: [1201](#); Symbol: [ER\\_CONNECTION\\_METADATA](#); SQLSTATE: [HY000](#)  
Message: Could not initialize connection metadata structure; more error messages can be found in the MySQL error log  
[ER\\_CONNECTION\\_METADATA](#) was added in 8.0.33.
  - Error number: [1202](#); Symbol: [ER\\_SLAVE\\_THREAD](#); SQLSTATE: [HY000](#)  
Message: Could not create slave thread; check system resources  
[ER\\_SLAVE\\_THREAD](#) was removed after 8.0.32.
  - Error number: [1202](#); Symbol: [ER\\_REPLICA\\_THREAD](#); SQLSTATE: [HY000](#)

---

Message: Could not create replica thread; check system resources

[ER\\_REPLICA\\_THREAD](#) was added in 8.0.33.

- Error number: [1203](#); Symbol: [ER\\_TOO\\_MANY\\_USER\\_CONNECTIONS](#); SQLSTATE: [42000](#)

Message: User %s already has more than 'max\_user\_connections' active connections

- Error number: [1204](#); Symbol: [ER\\_SET\\_CONSTANTS\\_ONLY](#); SQLSTATE: [HY000](#)

Message: You may only use constant expressions with SET

- Error number: [1205](#); Symbol: [ER\\_LOCK\\_WAIT\\_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: Lock wait timeout exceeded; try restarting transaction

[InnoDB](#) reports this error when lock wait timeout expires. The statement that waited too long was [rolled back](#) (not the entire [transaction](#)). You can increase the value of the [innodb\\_lock\\_wait\\_timeout](#) configuration option if SQL statements should wait longer for other transactions to complete, or decrease it if too many long-running transactions are causing [locking](#) problems and reducing [concurrency](#) on a busy system.

- Error number: [1206](#); Symbol: [ER\\_LOCK\\_TABLE\\_FULL](#); SQLSTATE: [HY000](#)

Message: The total number of locks exceeds the lock table size

[InnoDB](#) reports this error when the total number of locks exceeds the amount of memory devoted to managing locks. To avoid this error, increase the value of [innodb\\_buffer\\_pool\\_size](#). Within an individual application, a workaround may be to break a large operation into smaller pieces. For example, if the error occurs for a large [INSERT](#), perform several smaller [INSERT](#) operations.

- Error number: [1207](#); Symbol: [ER\\_READ\\_ONLY\\_TRANSACTION](#); SQLSTATE: [25000](#)

Message: Update locks cannot be acquired during a READ UNCOMMITTED transaction

- Error number: [1210](#); Symbol: [ER\\_WRONG\\_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: Incorrect arguments to %s

- Error number: [1211](#); Symbol: [ER\\_NO\\_PERMISSION\\_TO\\_CREATE\\_USER](#); SQLSTATE: [42000](#)

Message: '%s'@'%s' is not allowed to create new users

- Error number: [1213](#); Symbol: [ER\\_LOCK\\_DEADLOCK](#); SQLSTATE: [40001](#)

Message: Deadlock found when trying to get lock; try restarting transaction

[InnoDB](#) reports this error when a [transaction](#) encounters a [deadlock](#) and is automatically [rolled back](#) so that your application can take corrective action. To recover from this error, run all the operations in this transaction again. A deadlock occurs when requests for locks arrive in inconsistent order between transactions. The transaction that was rolled back released all its locks, and the other transaction can now get all the locks it requested. Thus, when you re-run the transaction that was rolled back, it might have to wait for other transactions to complete, but typically the deadlock does not recur. If you encounter frequent deadlocks, make the sequence of locking operations ([LOCK TABLES](#), [SELECT ... FOR UPDATE](#), and so on) consistent between the different transactions or applications that experience the issue. See [Deadlocks in InnoDB](#) for details.

- Error number: [1214](#); Symbol: [ER\\_TABLE\\_CANT\\_HANDLE\\_FT](#); SQLSTATE: [HY000](#)



---

Message: The used table type doesn't support FULLTEXT indexes

- Error number: 1215; Symbol: `ER_CANNOT_ADD_FOREIGN`; SQLSTATE: `HY000`

Message: Cannot add foreign key constraint

- Error number: 1216; Symbol: `ER_NO_REFERENCED_ROW`; SQLSTATE: `23000`

Message: Cannot add or update a child row: a foreign key constraint fails

`InnoDB` reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.

- Error number: 1217; Symbol: `ER_ROW_IS_REFERENCED`; SQLSTATE: `23000`

Message: Cannot delete or update a parent row: a foreign key constraint fails

`InnoDB` reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.

- Error number: 1218; Symbol: `ER_CONNECT_TO_MASTER`; SQLSTATE: `08S01`

Message: Error connecting to master: %s

`ER_CONNECT_TO_MASTER` was removed after 8.0.32.

- Error number: 1218; Symbol: `ER_CONNECT_TO_SOURCE`; SQLSTATE: `08S01`

Message: Error connecting to source: %s

`ER_CONNECT_TO_SOURCE` was added in 8.0.33.

- Error number: 1220; Symbol: `ER_ERROR_WHEN_EXECUTING_COMMAND`; SQLSTATE: `HY000`

Message: Error when executing command %s: %s

- Error number: 1221; Symbol: `ER_WRONG_USAGE`; SQLSTATE: `HY000`

Message: Incorrect usage of %s and %s

- Error number: 1222; Symbol: `ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT`; SQLSTATE: `21000`

Message: The used SELECT statements have a different number of columns

- Error number: 1223; Symbol: `ER_CANT_UPDATE_WITH_READLOCK`; SQLSTATE: `HY000`

Message: Can't execute the query because you have a conflicting read lock

- Error number: 1224; Symbol: `ER_MIXING_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: Mixing of transactional and non-transactional tables is disabled

- Error number: 1225; Symbol: `ER_DUP_ARGUMENT`; SQLSTATE: `HY000`

Message: Option '%s' used twice in statement

- Error number: 1226; Symbol: `ER_USER_LIMIT_REACHED`; SQLSTATE: `42000`

Message: User '%s' has exceeded the '%s' resource (current value: %ld)

- 
- Error number: [1227](#); Symbol: [ER\\_SPECIFIC\\_ACCESS\\_DENIED\\_ERROR](#); SQLSTATE: [42000](#)  
Message: Access denied; you need (at least one of) the %s privilege(s) for this operation
  - Error number: [1228](#); Symbol: [ER\\_LOCAL\\_VARIABLE](#); SQLSTATE: [HY000](#)  
Message: Variable '%s' is a SESSION variable and can't be used with SET GLOBAL
  - Error number: [1229](#); Symbol: [ER\\_GLOBAL\\_VARIABLE](#); SQLSTATE: [HY000](#)  
Message: Variable '%s' is a GLOBAL variable and should be set with SET GLOBAL
  - Error number: [1230](#); Symbol: [ER\\_NO\\_DEFAULT](#); SQLSTATE: [42000](#)  
Message: Variable '%s' doesn't have a default value
  - Error number: [1231](#); Symbol: [ER\\_WRONG\\_VALUE\\_FOR\\_VAR](#); SQLSTATE: [42000](#)  
Message: Variable '%s' can't be set to the value of '%s'
  - Error number: [1232](#); Symbol: [ER\\_WRONG\\_TYPE\\_FOR\\_VAR](#); SQLSTATE: [42000](#)  
Message: Incorrect argument type to variable '%s'
  - Error number: [1233](#); Symbol: [ER\\_VAR\\_CANT\\_BE\\_READ](#); SQLSTATE: [HY000](#)  
Message: Variable '%s' can only be set, not read
  - Error number: [1234](#); Symbol: [ER\\_CANT\\_USE\\_OPTION\\_HERE](#); SQLSTATE: [42000](#)  
Message: Incorrect usage/placement of '%s'
  - Error number: [1235](#); Symbol: [ER\\_NOT\\_SUPPORTED\\_YET](#); SQLSTATE: [42000](#)  
Message: This version of MySQL doesn't yet support '%s'
  - Error number: [1236](#); Symbol: [ER\\_MASTER\\_FATAL\\_ERROR\\_READING\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Got fatal error %d from master when reading data from binary log: '%s'  
[ER\\_MASTER\\_FATAL\\_ERROR\\_READING\\_BINLOG](#) was removed after 8.0.32.
  - Error number: [1236](#); Symbol: [ER\\_SOURCE\\_FATAL\\_ERROR\\_READING\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Got fatal error %d from source when reading data from binary log: '%s'  
[ER\\_SOURCE\\_FATAL\\_ERROR\\_READING\\_BINLOG](#) was added in 8.0.33.
  - Error number: [1237](#); Symbol: [ER\\_SLAVE\\_IGNORED\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Slave SQL thread ignored the query because of replicate-\*-table rules  
[ER\\_SLAVE\\_IGNORED\\_TABLE](#) was removed after 8.0.32.
  - Error number: [1237](#); Symbol: [ER\\_REPLICA\\_IGNORED\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Replica SQL thread ignored the query because of replicate-\*-table rules  
[ER\\_REPLICA\\_IGNORED\\_TABLE](#) was added in 8.0.33.

- 
- Error number: [1238](#); Symbol: [ER\\_INCORRECT\\_GLOBAL\\_LOCAL\\_VAR](#); SQLSTATE: [HY000](#)  
Message: Variable '%s' is a %s variable
  - Error number: [1239](#); Symbol: [ER\\_WRONG\\_FK\\_DEF](#); SQLSTATE: [42000](#)  
Message: Incorrect foreign key definition for '%s': %s
  - Error number: [1240](#); Symbol: [ER\\_KEY\\_REF\\_DO\\_NOT\\_MATCH\\_TABLE\\_REF](#); SQLSTATE: [HY000](#)  
Message: Key reference and table reference don't match
  - Error number: [1241](#); Symbol: [ER\\_OPERAND\\_COLUMNS](#); SQLSTATE: [21000](#)  
Message: Operand should contain %d column(s)
  - Error number: [1242](#); Symbol: [ER\\_SUBQUERY\\_NO\\_1\\_ROW](#); SQLSTATE: [21000](#)  
Message: Subquery returns more than 1 row
  - Error number: [1243](#); Symbol: [ER\\_UNKNOWN\\_STMT\\_HANDLER](#); SQLSTATE: [HY000](#)  
Message: Unknown prepared statement handler (%.\*s) given to %s
  - Error number: [1244](#); Symbol: [ER\\_CORRUPT\\_HELP\\_DB](#); SQLSTATE: [HY000](#)  
Message: Help database is corrupt or does not exist
  - Error number: [1246](#); Symbol: [ER\\_AUTO\\_CONVERT](#); SQLSTATE: [HY000](#)  
Message: Converting column '%s' from %s to %s
  - Error number: [1247](#); Symbol: [ER\\_ILLEGAL\\_REFERENCE](#); SQLSTATE: [42S22](#)  
Message: Reference '%s' not supported (%s)
  - Error number: [1248](#); Symbol: [ER\\_DERIVED\\_MUST\\_HAVE\\_ALIAS](#); SQLSTATE: [42000](#)  
Message: Every derived table must have its own alias
  - Error number: [1249](#); Symbol: [ER\\_SELECT\\_REDUCED](#); SQLSTATE: [01000](#)  
Message: Select %u was reduced during optimization
  - Error number: [1250](#); Symbol: [ER\\_TABLENAME\\_NOT\\_ALLOWED\\_HERE](#); SQLSTATE: [42000](#)  
Message: Table '%s' from one of the SELECTs cannot be used in %s
  - Error number: [1251](#); Symbol: [ER\\_NOT\\_SUPPORTED\\_AUTH\\_MODE](#); SQLSTATE: [08004](#)  
Message: Client does not support authentication protocol requested by server; consider upgrading MySQL client
  - Error number: [1252](#); Symbol: [ER\\_SPATIAL\\_CANT\\_HAVE\\_NULL](#); SQLSTATE: [42000](#)  
Message: All parts of a SPATIAL index must be NOT NULL
  - Error number: [1253](#); Symbol: [ER\\_COLLATION\\_CHARSET\\_MISMATCH](#); SQLSTATE: [42000](#)  
Message: COLLATION '%s' is not valid for CHARACTER SET '%s'

- 
- Error number: [1256](#); Symbol: [ER\\_TOO\\_BIG\\_FOR\\_UNCOMPRESS](#); SQLSTATE: [HY000](#)  
Message: Uncompressed data size too large; the maximum size is %d (probably, length of uncompressed data was corrupted)
  - Error number: [1257](#); Symbol: [ER\\_ZLIB\\_Z\\_MEM\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: ZLIB: Not enough memory
  - Error number: [1258](#); Symbol: [ER\\_ZLIB\\_Z\\_BUF\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: ZLIB: Not enough room in the output buffer (probably, length of uncompressed data was corrupted)
  - Error number: [1259](#); Symbol: [ER\\_ZLIB\\_Z\\_DATA\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: ZLIB: Input data corrupted
  - Error number: [1260](#); Symbol: [ER\\_CUT\\_VALUE\\_GROUP\\_CONCAT](#); SQLSTATE: [HY000](#)  
Message: Row %u was cut by GROUP\_CONCAT()
  - Error number: [1261](#); Symbol: [ER\\_WARN\\_TOO\\_FEW\\_RECORDS](#); SQLSTATE: [01000](#)  
Message: Row %ld doesn't contain data for all columns
  - Error number: [1262](#); Symbol: [ER\\_WARN\\_TOO\\_MANY\\_RECORDS](#); SQLSTATE: [01000](#)  
Message: Row %ld was truncated; it contained more data than there were input columns
  - Error number: [1263](#); Symbol: [ER\\_WARN\\_NULL\\_TO\\_NOTNULL](#); SQLSTATE: [22004](#)  
Message: Column set to default value; NULL supplied to NOT NULL column '%s' at row %ld
  - Error number: [1264](#); Symbol: [ER\\_WARN\\_DATA\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [22003](#)  
Message: Out of range value for column '%s' at row %ld
  - Error number: [1265](#); Symbol: [WARN\\_DATA\\_TRUNCATED](#); SQLSTATE: [01000](#)  
Message: Data truncated for column '%s' at row %ld
  - Error number: [1266](#); Symbol: [ER\\_WARN\\_USING\\_OTHER\\_HANDLER](#); SQLSTATE: [HY000](#)  
Message: Using storage engine %s for table '%s'
  - Error number: [1267](#); Symbol: [ER\\_CANT\\_AGGREGATE\\_2COLLATIONS](#); SQLSTATE: [HY000](#)  
Message: Illegal mix of collations (%s,%s) and (%s,%s) for operation '%s'
  - Error number: [1269](#); Symbol: [ER\\_REVOKE\\_GRANTS](#); SQLSTATE: [HY000](#)  
Message: Can't revoke all privileges for one or more of the requested users
  - Error number: [1270](#); Symbol: [ER\\_CANT\\_AGGREGATE\\_3COLLATIONS](#); SQLSTATE: [HY000](#)  
Message: Illegal mix of collations (%s,%s), (%s,%s), (%s,%s) for operation '%s'
  - Error number: [1271](#); Symbol: [ER\\_CANT\\_AGGREGATE\\_NCOLLATIONS](#); SQLSTATE: [HY000](#)

---

Message: Illegal mix of collations for operation '%s'

- Error number: [1272](#); Symbol: [ER\\_VARIABLE\\_IS\\_NOT\\_STRUCT](#); SQLSTATE: [HY000](#)

Message: Variable '%s' is not a variable component (can't be used as XXXX.variable\_name)

- Error number: [1273](#); Symbol: [ER\\_UNKNOWN\\_COLLATION](#); SQLSTATE: [HY000](#)

Message: Unknown collation: '%s'

- Error number: [1274](#); Symbol: [ER\\_SLAVE\\_IGNORED\\_SSL\\_PARAMS](#); SQLSTATE: [HY000](#)

Message: SSL parameters in CHANGE MASTER are ignored because this MySQL slave was compiled without SSL support; they can be used later if MySQL slave with SSL is started

[ER\\_SLAVE\\_IGNORED\\_SSL\\_PARAMS](#) was removed after 8.0.32.

- Error number: [1274](#); Symbol: [ER\\_REPLICA\\_IGNORED\\_SSL\\_PARAMS](#); SQLSTATE: [HY000](#)

Message: SSL parameters in CHANGE REPLICATION SOURCE are ignored because this MySQL replica was compiled without SSL support; they can be used later if MySQL replica with SSL is started

[ER\\_REPLICA\\_IGNORED\\_SSL\\_PARAMS](#) was added in 8.0.33.

- Error number: [1275](#); Symbol: [ER\\_SERVER\\_IS\\_IN\\_SECURE\\_AUTH\\_MODE](#); SQLSTATE: [HY000](#)

Message: Server is running in --secure-auth mode, but '%s'@'%s' has a password in the old format; please change the password to the new format

[ER\\_SERVER\\_IS\\_IN\\_SECURE\\_AUTH\\_MODE](#) was removed after 8.0.15.

- Error number: [1276](#); Symbol: [ER\\_WARN\\_FIELD\\_RESOLVED](#); SQLSTATE: [HY000](#)

Message: Field or reference '%s%s%s%s%s' of SELECT #%d was resolved in SELECT #%d

- Error number: [1277](#); Symbol: [ER\\_BAD\\_SLAVE\\_UNTIL\\_COND](#); SQLSTATE: [HY000](#)

Message: Incorrect parameter or combination of parameters for START SLAVE UNTIL

[ER\\_BAD\\_SLAVE\\_UNTIL\\_COND](#) was removed after 8.0.32.

- Error number: [1277](#); Symbol: [ER\\_BAD\\_REPLICA\\_UNTIL\\_COND](#); SQLSTATE: [HY000](#)

Message: Incorrect parameter or combination of parameters for START REPLICA UNTIL

[ER\\_BAD\\_REPLICA\\_UNTIL\\_COND](#) was added in 8.0.33.

- Error number: [1278](#); Symbol: [ER\\_MISSING\\_SKIP\\_SLAVE](#); SQLSTATE: [HY000](#)

Message: It is recommended to use --skip-replica-start when doing step-by-step replication with START SLAVE UNTIL; otherwise, you will get problems if you get an unexpected slave's mysqld restart

[ER\\_MISSING\\_SKIP\\_SLAVE](#) was removed after 8.0.32.

- Error number: [1278](#); Symbol: [ER\\_MISSING\\_SKIP\\_REPLICA](#); SQLSTATE: [HY000](#)

Message: It is recommended to use --skip-replica-start when doing step-by-step replication with START REPLICA UNTIL; otherwise, you will get problems if you get an unexpected replica's mysqld restart

---

`ER_MISSING_SKIP_REPLICA` was added in 8.0.33.

- Error number: `1279`; Symbol: `ER_UNTIL_COND_IGNORED`; SQLSTATE: `HY000`  
Message: SQL thread is not to be started so UNTIL options are ignored
- Error number: `1280`; Symbol: `ER_WRONG_NAME_FOR_INDEX`; SQLSTATE: `42000`  
Message: Incorrect index name '%s'
- Error number: `1281`; Symbol: `ER_WRONG_NAME_FOR_CATALOG`; SQLSTATE: `42000`  
Message: Incorrect catalog name '%s'
- Error number: `1282`; Symbol: `ER_WARN_QC_RESIZE`; SQLSTATE: `HY000`  
Message: Query cache failed to set size %lu; new query cache size is %lu  
`ER_WARN_QC_RESIZE` was removed after 8.0.2.
- Error number: `1283`; Symbol: `ER_BAD_FT_COLUMN`; SQLSTATE: `HY000`  
Message: Column '%s' cannot be part of FULLTEXT index
- Error number: `1284`; Symbol: `ER_UNKNOWN_KEY_CACHE`; SQLSTATE: `HY000`  
Message: Unknown key cache '%s'
- Error number: `1285`; Symbol: `ER_WARN_HOSTNAME_WONT_WORK`; SQLSTATE: `HY000`  
Message: MySQL is started in --skip-name-resolve mode; you must restart it without this switch for this grant to work
- Error number: `1286`; Symbol: `ER_UNKNOWN_STORAGE_ENGINE`; SQLSTATE: `42000`  
Message: Unknown storage engine '%s'
- Error number: `1287`; Symbol: `ER_WARN_DEPRECATED_SYNTAX`; SQLSTATE: `HY000`  
Message: '%s' is deprecated and will be removed in a future release. Please use %s instead
- Error number: `1288`; Symbol: `ER_NON_UPDATABLE_TABLE`; SQLSTATE: `HY000`  
Message: The target table %s of the %s is not updatable
- Error number: `1289`; Symbol: `ER_FEATURE_DISABLED`; SQLSTATE: `HY000`  
Message: The '%s' feature is disabled; you need MySQL built with '%s' to have it working
- Error number: `1290`; Symbol: `ER_OPTION_PREVENTS_STATEMENT`; SQLSTATE: `HY000`  
Message: The MySQL server is running with the %s option so it cannot execute this statement
- Error number: `1291`; Symbol: `ER_DUPLICATED_VALUE_IN_TYPE`; SQLSTATE: `HY000`  
Message: Column '%s' has duplicated value '%s' in %s
- Error number: `1292`; Symbol: `ER_TRUNCATED_WRONG_VALUE`; SQLSTATE: `22007`  
Message: Truncated incorrect %s value: '%s'

- 
- Error number: [1294](#); Symbol: [ER\\_INVALID\\_ON\\_UPDATE](#); SQLSTATE: [HY000](#)  
Message: Invalid ON UPDATE clause for '%s' column
  - Error number: [1295](#); Symbol: [ER\\_UNSUPPORTED\\_PS](#); SQLSTATE: [HY000](#)  
Message: This command is not supported in the prepared statement protocol yet
  - Error number: [1296](#); Symbol: [ER\\_GET\\_ERRMSG](#); SQLSTATE: [HY000](#)  
Message: Got error %d '%s' from %s
  - Error number: [1297](#); Symbol: [ER\\_GET\\_TEMPORARY\\_ERRMSG](#); SQLSTATE: [HY000](#)  
Message: Got temporary error %d '%s' from %s
  - Error number: [1298](#); Symbol: [ER\\_UNKNOWN\\_TIME\\_ZONE](#); SQLSTATE: [HY000](#)  
Message: Unknown or incorrect time zone: '%s'
  - Error number: [1299](#); Symbol: [ER\\_WARN\\_INVALID\\_TIMESTAMP](#); SQLSTATE: [HY000](#)  
Message: Invalid TIMESTAMP value in column '%s' at row %ld
  - Error number: [1300](#); Symbol: [ER\\_INVALID\\_CHARACTER\\_STRING](#); SQLSTATE: [HY000](#)  
Message: Invalid %s character string: '%s'
  - Error number: [1301](#); Symbol: [ER\\_WARN\\_ALLOWED\\_PACKET\\_OVERFLOWED](#); SQLSTATE: [HY000](#)  
Message: Result of %s() was larger than max\_allowed\_packet (%ld) - truncated
  - Error number: [1302](#); Symbol: [ER\\_CONFLICTING\\_DECLARATIONS](#); SQLSTATE: [HY000](#)  
Message: Conflicting declarations: '%s%s' and '%s%s'
  - Error number: [1303](#); Symbol: [ER\\_SP\\_NO\\_RECURSIVE\\_CREATE](#); SQLSTATE: [2F003](#)  
Message: Can't create a %s from within another stored routine
  - Error number: [1304](#); Symbol: [ER\\_SP\\_ALREADY\\_EXISTS](#); SQLSTATE: [42000](#)  
Message: %s %s already exists
  - Error number: [1305](#); Symbol: [ER\\_SP\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [42000](#)  
Message: %s %s does not exist
  - Error number: [1306](#); Symbol: [ER\\_SP\\_DROP\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to DROP %s %s
  - Error number: [1307](#); Symbol: [ER\\_SP\\_STORE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to CREATE %s %s
  - Error number: [1308](#); Symbol: [ER\\_SP\\_LILABEL\\_MISMATCH](#); SQLSTATE: [42000](#)  
Message: %s with no matching label: %s
  - Error number: [1309](#); Symbol: [ER\\_SP\\_LABEL\\_REDEFINE](#); SQLSTATE: [42000](#)

---

Message: Redefining label %s

- Error number: 1310; Symbol: `ER_SP_LABEL_MISMATCH`; SQLSTATE: 42000

Message: End-label %s without match

- Error number: 1311; Symbol: `ER_SP_UNINIT_VAR`; SQLSTATE: 01000

Message: Referring to uninitialized variable %s

- Error number: 1312; Symbol: `ER_SP_BADSELECT`; SQLSTATE: 0A000

Message: PROCEDURE %s can't return a result set in the given context

- Error number: 1313; Symbol: `ER_SP_BADRETURN`; SQLSTATE: 42000

Message: RETURN is only allowed in a FUNCTION

- Error number: 1314; Symbol: `ER_SP_BADSTATEMENT`; SQLSTATE: 0A000

Message: %s is not allowed in stored procedures

- Error number: 1315; Symbol: `ER_UPDATE_LOG_DEPRECATED_IGNORED`; SQLSTATE: 42000

Message: The update log is deprecated and replaced by the binary log; SET SQL\_LOG\_UPDATE has been ignored.

- Error number: 1316; Symbol: `ER_UPDATE_LOG_DEPRECATED_TRANSLATED`; SQLSTATE: 42000

Message: The update log is deprecated and replaced by the binary log; SET SQL\_LOG\_UPDATE has been translated to SET SQL\_LOG\_BIN.

- Error number: 1317; Symbol: `ER_QUERY_INTERRUPTED`; SQLSTATE: 70100

Message: Query execution was interrupted

- Error number: 1318; Symbol: `ER_SP_WRONG_NO_OF_ARGS`; SQLSTATE: 42000

Message: Incorrect number of arguments for %s %s; expected %u, got %u

- Error number: 1319; Symbol: `ER_SP_COND_MISMATCH`; SQLSTATE: 42000

Message: Undefined CONDITION: %s

- Error number: 1320; Symbol: `ER_SP_NORETURN`; SQLSTATE: 42000

Message: No RETURN found in FUNCTION %s

- Error number: 1321; Symbol: `ER_SP_NORETURNEND`; SQLSTATE: 2F005

Message: FUNCTION %s ended without RETURN

- Error number: 1322; Symbol: `ER_SP_BAD_CURSOR_QUERY`; SQLSTATE: 42000

Message: Cursor statement must be a SELECT

- Error number: 1323; Symbol: `ER_SP_BAD_CURSOR_SELECT`; SQLSTATE: 42000

Message: Cursor SELECT must not have INTO



- 
- Error number: 1324; Symbol: ER\_SP\_CURSOR\_MISMATCH; SQLSTATE: 42000  
Message: Undefined CURSOR: %s
  - Error number: 1325; Symbol: ER\_SP\_CURSOR\_ALREADY\_OPEN; SQLSTATE: 24000  
Message: Cursor is already open
  - Error number: 1326; Symbol: ER\_SP\_CURSOR\_NOT\_OPEN; SQLSTATE: 24000  
Message: Cursor is not open
  - Error number: 1327; Symbol: ER\_SP\_UNDECLARED\_VAR; SQLSTATE: 42000  
Message: Undeclared variable: %s
  - Error number: 1328; Symbol: ER\_SP\_WRONG\_NO\_OF\_FETCH\_ARGS; SQLSTATE: HY000  
Message: Incorrect number of FETCH variables
  - Error number: 1329; Symbol: ER\_SP\_FETCH\_NO\_DATA; SQLSTATE: 02000  
Message: No data - zero rows fetched, selected, or processed
  - Error number: 1330; Symbol: ER\_SP\_DUP\_PARAM; SQLSTATE: 42000  
Message: Duplicate parameter: %s
  - Error number: 1331; Symbol: ER\_SP\_DUP\_VAR; SQLSTATE: 42000  
Message: Duplicate variable: %s
  - Error number: 1332; Symbol: ER\_SP\_DUP\_COND; SQLSTATE: 42000  
Message: Duplicate condition: %s
  - Error number: 1333; Symbol: ER\_SP\_DUP\_CURS; SQLSTATE: 42000  
Message: Duplicate cursor: %s
  - Error number: 1334; Symbol: ER\_SP\_CANT\_ALTER; SQLSTATE: HY000  
Message: Failed to ALTER %s %s
  - Error number: 1335; Symbol: ER\_SP\_SUBSELECT\_NYI; SQLSTATE: 0A000  
Message: Subquery value not supported
  - Error number: 1336; Symbol: ER\_STMT\_NOT\_ALLOWED\_IN\_SF\_OR\_TRG; SQLSTATE: 0A000  
Message: %s is not allowed in stored function or trigger
  - Error number: 1337; Symbol: ER\_SP\_VARCOND\_AFTER\_CURSHNDLR; SQLSTATE: 42000  
Message: Variable or condition declaration after cursor or handler declaration
  - Error number: 1338; Symbol: ER\_SP\_CURSOR\_AFTER\_HANDLER; SQLSTATE: 42000  
Message: Cursor declaration after handler declaration

- 
- Error number: [1339](#); Symbol: [ER\\_SP\\_CASE\\_NOT\\_FOUND](#); SQLSTATE: [20000](#)  
Message: Case not found for CASE statement
  - Error number: [1340](#); Symbol: [ER\\_FPARSER\\_TOO\\_BIG\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Configuration file '%s' is too big
  - Error number: [1341](#); Symbol: [ER\\_FPARSER\\_BAD\\_HEADER](#); SQLSTATE: [HY000](#)  
Message: Malformed file type header in file '%s'
  - Error number: [1342](#); Symbol: [ER\\_FPARSER\\_EOF\\_IN\\_COMMENT](#); SQLSTATE: [HY000](#)  
Message: Unexpected end of file while parsing comment '%s'
  - Error number: [1343](#); Symbol: [ER\\_FPARSER\\_ERROR\\_IN\\_PARAMETER](#); SQLSTATE: [HY000](#)  
Message: Error while parsing parameter '%s' (line: '%s')
  - Error number: [1344](#); Symbol: [ER\\_FPARSER\\_EOF\\_IN\\_UNKNOWN\\_PARAMETER](#); SQLSTATE: [HY000](#)  
Message: Unexpected end of file while skipping unknown parameter '%s'
  - Error number: [1345](#); Symbol: [ER\\_VIEW\\_NO\\_EXPLAIN](#); SQLSTATE: [HY000](#)  
Message: EXPLAIN/SHOW can not be issued; lacking privileges for underlying table
  - Error number: [1347](#); Symbol: [ER\\_WRONG\\_OBJECT](#); SQLSTATE: [HY000](#)  
Message: '%s.%s' is not %s  
  
The named object is incorrect for the type of operation attempted on it. It must be an object of the named type. Example: [HANDLER OPEN](#) requires a base table, not a view. It fails if attempted on an [INFORMATION\\_SCHEMA](#) table that is implemented as a view on data dictionary tables.
  - Error number: [1348](#); Symbol: [ER\\_NONUPDATEABLE\\_COLUMN](#); SQLSTATE: [HY000](#)  
Message: Column '%s' is not updatable
  - Error number: [1350](#); Symbol: [ER\\_VIEW\\_SELECT\\_CLAUSE](#); SQLSTATE: [HY000](#)  
Message: View's SELECT contains a '%s' clause
  - Error number: [1351](#); Symbol: [ER\\_VIEW\\_SELECT\\_VARIABLE](#); SQLSTATE: [HY000](#)  
Message: View's SELECT contains a variable or parameter
  - Error number: [1352](#); Symbol: [ER\\_VIEW\\_SELECT\\_TMPTABLE](#); SQLSTATE: [HY000](#)  
Message: View's SELECT refers to a temporary table '%s'
  - Error number: [1353](#); Symbol: [ER\\_VIEW\\_WRONG\\_LIST](#); SQLSTATE: [HY000](#)  
Message: In definition of view, derived table or common table expression, SELECT list and column names list have different column counts
  - Error number: [1354](#); Symbol: [ER\\_WARN\\_VIEW\\_MERGE](#); SQLSTATE: [HY000](#)  
Message: View merge algorithm can't be used here for now (assumed undefined algorithm)

- 
- Error number: [1355](#); Symbol: [ER\\_WARN\\_VIEW\\_WITHOUT\\_KEY](#); SQLSTATE: [HY000](#)  
Message: View being updated does not have complete key of underlying table in it
  - Error number: [1356](#); Symbol: [ER\\_VIEW\\_INVALID](#); SQLSTATE: [HY000](#)  
Message: View '%s.%s' references invalid table(s) or column(s) or function(s) or definer invoker of view lack rights to use them
  - Error number: [1357](#); Symbol: [ER\\_SP\\_NO\\_DROP\\_SP](#); SQLSTATE: [HY000](#)  
Message: Can't drop or alter a %s from within another stored routine
  - Error number: [1359](#); Symbol: [ER\\_TRG\\_ALREADY\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Trigger already exists
  - Error number: [1360](#); Symbol: [ER\\_TRG\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: Trigger does not exist
  - Error number: [1361](#); Symbol: [ER\\_TRG\\_ON\\_VIEW\\_OR\\_TEMP\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Trigger's '%s' is view or temporary table
  - Error number: [1362](#); Symbol: [ER\\_TRG\\_CANT\\_CHANGE\\_ROW](#); SQLSTATE: [HY000](#)  
Message: Updating of %s row is not allowed in %strigger
  - Error number: [1363](#); Symbol: [ER\\_TRG\\_NO\\_SUCH\\_ROW\\_IN\\_TRG](#); SQLSTATE: [HY000](#)  
Message: There is no %s row in %s trigger
  - Error number: [1364](#); Symbol: [ER\\_NO\\_DEFAULT\\_FOR\\_FIELD](#); SQLSTATE: [HY000](#)  
Message: Field '%s' doesn't have a default value
  - Error number: [1365](#); Symbol: [ER\\_DIVISION\\_BY\\_ZERO](#); SQLSTATE: [22012](#)  
Message: Division by 0
  - Error number: [1366](#); Symbol: [ER\\_TRUNCATED\\_WRONG\\_VALUE\\_FOR\\_FIELD](#); SQLSTATE: [HY000](#)  
Message: Incorrect %s value: '%s' for column '%s' at row %ld
  - Error number: [1367](#); Symbol: [ER\\_ILLEGAL\\_VALUE\\_FOR\\_TYPE](#); SQLSTATE: [22007](#)  
Message: Illegal %s '%s' value found during parsing
  - Error number: [1368](#); Symbol: [ER\\_VIEW\\_NONUPD\\_CHECK](#); SQLSTATE: [HY000](#)  
Message: CHECK OPTION on non-updatable view '%s.%s'
  - Error number: [1369](#); Symbol: [ER\\_VIEW\\_CHECK\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: CHECK OPTION failed '%s.%s'
  - Error number: [1370](#); Symbol: [ER\\_PROCACCESS\\_DENIED\\_ERROR](#); SQLSTATE: [42000](#)  
Message: %s command denied to user '%s'@'%s' for routine '%s'

- 
- Error number: 1371; Symbol: ER\_RELAY\_LOG\_FAIL; SQLSTATE: HY000  
Message: Failed purging old relay logs: %s
  - Error number: 1373; Symbol: ER\_UNKNOWN\_TARGET\_BINLOG; SQLSTATE: HY000  
Message: Target log not found in binlog index
  - Error number: 1374; Symbol: ER\_IO\_ERR\_LOG\_INDEX\_READ; SQLSTATE: HY000  
Message: I/O error reading log index file
  - Error number: 1375; Symbol: ER\_BINLOG\_PURGE\_PROHIBITED; SQLSTATE: HY000  
Message: Server configuration does not permit binlog purge
  - Error number: 1376; Symbol: ER\_FSEEK\_FAIL; SQLSTATE: HY000  
Message: Failed on fseek()
  - Error number: 1377; Symbol: ER\_BINLOG\_PURGE\_FATAL\_ERR; SQLSTATE: HY000  
Message: Fatal error during log purge
  - Error number: 1378; Symbol: ER\_LOG\_IN\_USE; SQLSTATE: HY000  
Message: A purgeable log is in use, will not purge
  - Error number: 1379; Symbol: ER\_LOG\_PURGE\_UNKNOWN\_ERR; SQLSTATE: HY000  
Message: Unknown error during log purge
  - Error number: 1380; Symbol: ER\_RELAY\_LOG\_INIT; SQLSTATE: HY000  
Message: Failed initializing relay log position: %s
  - Error number: 1381; Symbol: ER\_NO\_BINARY\_LOGGING; SQLSTATE: HY000  
Message: You are not using binary logging
  - Error number: 1382; Symbol: ER\_RESERVED\_SYNTAX; SQLSTATE: HY000  
Message: The '%s' syntax is reserved for purposes internal to the MySQL server
  - Error number: 1390; Symbol: ER\_PS\_MANY\_PARAM; SQLSTATE: HY000  
Message: Prepared statement contains too many placeholders
  - Error number: 1391; Symbol: ER\_KEY\_PART\_0; SQLSTATE: HY000  
Message: Key part '%s' length cannot be 0
  - Error number: 1392; Symbol: ER\_VIEW\_CHECKSUM; SQLSTATE: HY000  
Message: View text checksum failed
  - Error number: 1393; Symbol: ER\_VIEW\_MULTIUPDATE; SQLSTATE: HY000  
Message: Can not modify more than one base table through a join view '%s.%s'

- 
- Error number: [1394](#); Symbol: [ER\\_VIEW\\_NO\\_INSERT\\_FIELD\\_LIST](#); SQLSTATE: [HY000](#)  
Message: Can not insert into join view '%s.%s' without fields list
  - Error number: [1395](#); Symbol: [ER\\_VIEW\\_DELETE\\_MERGE\\_VIEW](#); SQLSTATE: [HY000](#)  
Message: Can not delete from join view '%s.%s'
  - Error number: [1396](#); Symbol: [ER\\_CANNOT\\_USER](#); SQLSTATE: [HY000](#)  
Message: Operation %s failed for %s
  - Error number: [1397](#); Symbol: [ER\\_XAER\\_NOTA](#); SQLSTATE: [XAE04](#)  
Message: XAER\_NOTA: Unknown XID
  - Error number: [1398](#); Symbol: [ER\\_XAER\\_INVAL](#); SQLSTATE: [XAE05](#)  
Message: XAER\_INVAL: Invalid arguments (or unsupported command)
  - Error number: [1399](#); Symbol: [ER\\_XAER\\_RMFAIL](#); SQLSTATE: [XAE07](#)  
Message: XAER\_RMFAIL: The command cannot be executed when global transaction is in the %s state
  - Error number: [1400](#); Symbol: [ER\\_XAER\\_OUTSIDE](#); SQLSTATE: [XAE09](#)  
Message: XAER\_OUTSIDE: Some work is done outside global transaction
  - Error number: [1401](#); Symbol: [ER\\_XAER\\_RMERR](#); SQLSTATE: [XAE03](#)  
Message: XAER\_RMERR: Fatal error occurred in the transaction branch - check your data for consistency
  - Error number: [1402](#); Symbol: [ER\\_XA\\_RBROLLBACK](#); SQLSTATE: [XA100](#)  
Message: XA\_RBROLLBACK: Transaction branch was rolled back
  - Error number: [1403](#); Symbol: [ER\\_NONEXISTING\\_PROC\\_GRANT](#); SQLSTATE: [42000](#)  
Message: There is no such grant defined for user '%s' on host '%s' on routine '%s'
  - Error number: [1404](#); Symbol: [ER\\_PROC\\_AUTO\\_GRANT\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to grant EXECUTE and ALTER ROUTINE privileges
  - Error number: [1405](#); Symbol: [ER\\_PROC\\_AUTO\\_REVOKE\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to revoke all privileges to dropped routine
  - Error number: [1406](#); Symbol: [ER\\_DATA\\_TOO\\_LONG](#); SQLSTATE: [22001](#)  
Message: Data too long for column '%s' at row %ld
  - Error number: [1407](#); Symbol: [ER\\_SP\\_BAD\\_SQLSTATE](#); SQLSTATE: [42000](#)  
Message: Bad SQLSTATE: '%s'
  - Error number: [1408](#); Symbol: [ER\\_STARTUP](#); SQLSTATE: [HY000](#)  
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s

- 
- Error number: 1409; Symbol: `ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR`; SQLSTATE: `HY000`  
Message: Can't load value from file with fixed size rows to variable
  - Error number: 1410; Symbol: `ER_CANT_CREATE_USER_WITH_GRANT`; SQLSTATE: `42000`  
Message: You are not allowed to create a user with GRANT
  - Error number: 1411; Symbol: `ER_WRONG_VALUE_FOR_TYPE`; SQLSTATE: `HY000`  
Message: Incorrect %s value: '%s' for function %s
  - Error number: 1412; Symbol: `ER_TABLE_DEF_CHANGED`; SQLSTATE: `HY000`  
Message: Table definition has changed, please retry transaction
  - Error number: 1413; Symbol: `ER_SP_DUP_HANDLER`; SQLSTATE: `42000`  
Message: Duplicate handler declared in the same block
  - Error number: 1414; Symbol: `ER_SP_NOT_VAR_ARG`; SQLSTATE: `42000`  
Message: OUT or INOUT argument %d for routine %s is not a variable or NEW pseudo-variable in BEFORE trigger
  - Error number: 1415; Symbol: `ER_SP_NO_RETSET`; SQLSTATE: `0A000`  
Message: Not allowed to return a result set from a %s
  - Error number: 1416; Symbol: `ER_CANT_CREATE_GEOMETRY_OBJECT`; SQLSTATE: `22003`  
Message: Cannot get geometry object from data you send to the GEOMETRY field
  - Error number: 1418; Symbol: `ER_BINLOG_UNSAFE_ROUTINE`; SQLSTATE: `HY000`  
Message: This function has none of DETERMINISTIC, NO SQL, or READS SQL DATA in its declaration and binary logging is enabled (you \*might\* want to use the less safe log\_bin\_trust\_function\_creators variable)
  - Error number: 1419; Symbol: `ER_BINLOG_CREATE_ROUTINE_NEED_SUPER`; SQLSTATE: `HY000`  
Message: You do not have the SUPER privilege and binary logging is enabled (you \*might\* want to use the less safe log\_bin\_trust\_function\_creators variable)
  - Error number: 1421; Symbol: `ER_STMT_HAS_NO_OPEN_CURSOR`; SQLSTATE: `HY000`  
Message: The statement (%lu) has no open cursor.
  - Error number: 1422; Symbol: `ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG`; SQLSTATE: `HY000`  
Message: Explicit or implicit commit is not allowed in stored function or trigger.
  - Error number: 1423; Symbol: `ER_NO_DEFAULT_FOR_VIEW_FIELD`; SQLSTATE: `HY000`  
Message: Field of view '%s.%s' underlying table doesn't have a default value
  - Error number: 1424; Symbol: `ER_SP_NO_RECURSION`; SQLSTATE: `HY000`  
Message: Recursive stored functions and triggers are not allowed.

- 
- Error number: 1425; Symbol: ER\_TOO\_BIG\_SCALE; SQLSTATE: 42000  
Message: Too big scale %d specified for column '%s'. Maximum is %lu.
  - Error number: 1426; Symbol: ER\_TOO\_BIG\_PRECISION; SQLSTATE: 42000  
Message: Too-big precision %d specified for '%s'. Maximum is %lu.
  - Error number: 1427; Symbol: ER\_M\_BIGGER\_THAN\_D; SQLSTATE: 42000  
Message: For float(M,D), double(M,D) or decimal(M,D), M must be >= D (column '%s').
  - Error number: 1428; Symbol: ER\_WRONG\_LOCK\_OF\_SYSTEM\_TABLE; SQLSTATE: HY000  
Message: You can't combine write-locking of system tables with other tables or lock types
  - Error number: 1429; Symbol: ER\_CONNECT\_TO\_FOREIGN\_DATA\_SOURCE; SQLSTATE: HY000  
Message: Unable to connect to foreign data source: %s
  - Error number: 1430; Symbol: ER\_QUERY\_ON\_FOREIGN\_DATA\_SOURCE; SQLSTATE: HY000  
Message: There was a problem processing the query on the foreign data source. Data source error: %s
  - Error number: 1431; Symbol: ER\_FOREIGN\_DATA\_SOURCE\_DOESNT\_EXIST; SQLSTATE: HY000  
Message: The foreign data source you are trying to reference does not exist. Data source error: %s
  - Error number: 1432; Symbol: ER\_FOREIGN\_DATA\_STRING\_INVALID\_CANT\_CREATE; SQLSTATE: HY000  
Message: Can't create federated table. The data source connection string '%s' is not in the correct format
  - Error number: 1433; Symbol: ER\_FOREIGN\_DATA\_STRING\_INVALID; SQLSTATE: HY000  
Message: The data source connection string '%s' is not in the correct format
  - Error number: 1435; Symbol: ER\_TRG\_IN\_WRONG\_SCHEMA; SQLSTATE: HY000  
Message: Trigger in wrong schema
  - Error number: 1436; Symbol: ER\_STACK\_OVERRUN\_NEED\_MORE; SQLSTATE: HY000  
Message: Thread stack overrun: %ld bytes used of a %ld byte stack, and %ld bytes needed. Use 'mysqld --thread\_stack=#' to specify a bigger stack.
  - Error number: 1437; Symbol: ER\_TOO\_LONG\_BODY; SQLSTATE: 42000  
Message: Routine body for '%s' is too long
  - Error number: 1438; Symbol: ER\_WARN\_CANT\_DROP\_DEFAULT\_KEYCACHE; SQLSTATE: HY000  
Message: Cannot drop default keycache
  - Error number: 1439; Symbol: ER\_TOO\_BIG\_DISPLAYWIDTH; SQLSTATE: 42000  
Message: Display width out of range for column '%s' (max = %lu)
  - Error number: 1440; Symbol: ER\_XAER\_DUPID; SQLSTATE: XAE08

---

Message: XAER\_DUPID: The XID already exists

- Error number: 1441; Symbol: `ER_DATETIME_FUNCTION_OVERFLOW`; SQLSTATE: 22008

Message: Datetime function: %s field overflow

- Error number: 1442; Symbol: `ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG`; SQLSTATE: HY000

Message: Can't update table '%s' in stored function/trigger because it is already used by statement which invoked this stored function/trigger.

- Error number: 1443; Symbol: `ER_VIEW_PREVENT_UPDATE`; SQLSTATE: HY000

Message: The definition of table '%s' prevents operation %s on table '%s'.

- Error number: 1444; Symbol: `ER_PS_NO_RECURSION`; SQLSTATE: HY000

Message: The prepared statement contains a stored routine call that refers to that same statement. It's not allowed to execute a prepared statement in such a recursive manner

- Error number: 1445; Symbol: `ER_SP_CANT_SET_AUTOCOMMIT`; SQLSTATE: HY000

Message: Not allowed to set autocommit from a stored function or trigger

- Error number: 1447; Symbol: `ER_VIEW_FRM_NO_USER`; SQLSTATE: HY000

Message: View '%s'.'%s' has no definer information (old table format). Current user is used as definer. Please recreate the view!

- Error number: 1448; Symbol: `ER_VIEW_OTHER_USER`; SQLSTATE: HY000

Message: You need the SUPER privilege for creation view with '%s'@'%s' definer

- Error number: 1449; Symbol: `ER_NO_SUCH_USER`; SQLSTATE: HY000

Message: The user specified as a definer ('%s'@'%s') does not exist

- Error number: 1450; Symbol: `ER_FORBID_SCHEMA_CHANGE`; SQLSTATE: HY000

Message: Changing schema from '%s' to '%s' is not allowed.

- Error number: 1451; Symbol: `ER_ROW_IS_REFERENCED_2`; SQLSTATE: 23000

Message: Cannot delete or update a parent row: a foreign key constraint fails (%s)

[InnoDB](#) reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.

- Error number: 1452; Symbol: `ER_NO_REFERENCED_ROW_2`; SQLSTATE: 23000

Message: Cannot add or update a child row: a foreign key constraint fails (%s)

[InnoDB](#) reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.

- Error number: 1453; Symbol: `ER_SP_BAD_VAR_SHADOW`; SQLSTATE: 42000

Message: Variable '%s' must be quoted with `...`, or renamed



- 
- Error number: [1454](#); Symbol: [ER\\_TRG\\_NO\\_DEFINER](#); SQLSTATE: [HY000](#)  
Message: No definer attribute for trigger '%s'. '%s'. It's disallowed to create trigger without definer.
  - Error number: [1455](#); Symbol: [ER\\_OLD\\_FILE\\_FORMAT](#); SQLSTATE: [HY000](#)  
Message: '%s' has an old format, you should re-create the '%s' object(s)
  - Error number: [1456](#); Symbol: [ER\\_SP\\_RECURSION\\_LIMIT](#); SQLSTATE: [HY000](#)  
Message: Recursive limit %d (as set by the max\_sp\_recursion\_depth variable) was exceeded for routine %s
  - Error number: [1458](#); Symbol: [ER\\_SP\\_WRONG\\_NAME](#); SQLSTATE: [42000](#)  
Message: Incorrect routine name '%s'
  - Error number: [1459](#); Symbol: [ER\\_TABLE\\_NEEDS\\_UPGRADE](#); SQLSTATE: [HY000](#)  
Message: Table upgrade required. Please do "REPAIR TABLE `%s`" or dump/reload to fix it!
  - Error number: [1460](#); Symbol: [ER\\_SP\\_NO\\_AGGREGATE](#); SQLSTATE: [42000](#)  
Message: AGGREGATE is not supported for stored functions
  - Error number: [1461](#); Symbol: [ER\\_MAX\\_PREPARED\\_STMT\\_COUNT\\_REACHED](#); SQLSTATE: [42000](#)  
Message: Can't create more than max\_prepared\_stmt\_count statements (current value: %lu)
  - Error number: [1462](#); Symbol: [ER\\_VIEW\\_RECURSIVE](#); SQLSTATE: [HY000](#)  
Message: `%s`.`%s` contains view recursion
  - Error number: [1463](#); Symbol: [ER\\_NON\\_GROUPING\\_FIELD\\_USED](#); SQLSTATE: [42000](#)  
Message: Non-grouping field '%s' is used in %s clause
  - Error number: [1464](#); Symbol: [ER\\_TABLE\\_CANT\\_HANDLE\\_SPKEYS](#); SQLSTATE: [HY000](#)  
Message: The used table type doesn't support SPATIAL indexes
  - Error number: [1465](#); Symbol: [ER\\_NO\\_TRIGGERS\\_ON\\_SYSTEM\\_SCHEMA](#); SQLSTATE: [HY000](#)  
Message: Triggers can not be created on system tables
  - Error number: [1466](#); Symbol: [ER\\_REMOVED\\_SPACES](#); SQLSTATE: [HY000](#)  
Message: Leading spaces are removed from name '%s'
  - Error number: [1467](#); Symbol: [ER\\_AUTOINC\\_READ\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to read auto-increment value from storage engine
  - Error number: [1468](#); Symbol: [ER\\_USERNAME](#); SQLSTATE: [HY000](#)  
Message: user name
  - Error number: [1469](#); Symbol: [ER\\_HOSTNAME](#); SQLSTATE: [HY000](#)  
Message: host name

- 
- Error number: 1470; Symbol: `ER_WRONG_STRING_LENGTH`; SQLSTATE: HY000  
Message: String '%s' is too long for %s (should be no longer than %d)
  - Error number: 1471; Symbol: `ER_NON_INSERTABLE_TABLE`; SQLSTATE: HY000  
Message: The target table %s of the %s is not insertable-into
  - Error number: 1472; Symbol: `ER_ADMIN_WRONG_MRG_TABLE`; SQLSTATE: HY000  
Message: Table '%s' is differently defined or of non-MyISAM type or doesn't exist
  - Error number: 1473; Symbol: `ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT`; SQLSTATE: HY000  
Message: Too high level of nesting for select
  - Error number: 1474; Symbol: `ER_NAME_BECOMES_EMPTY`; SQLSTATE: HY000  
Message: Name '%s' has become "
  - Error number: 1475; Symbol: `ER_AMBIGUOUS_FIELD_TERM`; SQLSTATE: HY000  
Message: First character of the FIELDS TERMINATED string is ambiguous; please use non-optional and non-empty FIELDS ENCLOSED BY
  - Error number: 1476; Symbol: `ER_FOREIGN_SERVER_EXISTS`; SQLSTATE: HY000  
Message: The foreign server, %s, you are trying to create already exists.
  - Error number: 1477; Symbol: `ER_FOREIGN_SERVER_DOESNT_EXIST`; SQLSTATE: HY000  
Message: The foreign server name you are trying to reference does not exist. Data source error: %s
  - Error number: 1478; Symbol: `ER_ILLEGAL_HA_CREATE_OPTION`; SQLSTATE: HY000  
Message: Table storage engine '%s' does not support the create option '%s'
  - Error number: 1479; Symbol: `ER_PARTITION_REQUIRES_VALUES_ERROR`; SQLSTATE: HY000  
Message: Syntax error: %s PARTITIONING requires definition of VALUES %s for each partition
  - Error number: 1480; Symbol: `ER_PARTITION_WRONG_VALUES_ERROR`; SQLSTATE: HY000  
Message: Only %s PARTITIONING can use VALUES %s in partition definition
  - Error number: 1481; Symbol: `ER_PARTITION_MAXVALUE_ERROR`; SQLSTATE: HY000  
Message: MAXVALUE can only be used in last partition definition
  - Error number: 1484; Symbol: `ER_PARTITION_WRONG_NO_PART_ERROR`; SQLSTATE: HY000  
Message: Wrong number of partitions defined, mismatch with previous setting
  - Error number: 1485; Symbol: `ER_PARTITION_WRONG_NO_SUBPART_ERROR`; SQLSTATE: HY000  
Message: Wrong number of subpartitions defined, mismatch with previous setting
  - Error number: 1486; Symbol: `ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR`; SQLSTATE: HY000  
Message: Constant, random or timezone-dependent expressions in (sub)partitioning function are not allowed

- 
- Error number: 1488; Symbol: `ER_FIELD_NOT_FOUND_PART_ERROR`; SQLSTATE: HY000  
Message: Field in list of fields for partition function not found in table
  - Error number: 1490; Symbol: `ER_INCONSISTENT_PARTITION_INFO_ERROR`; SQLSTATE: HY000  
Message: The partition info in the frm file is not consistent with what can be written into the frm file
  - Error number: 1491; Symbol: `ER_PARTITION_FUNC_NOT_ALLOWED_ERROR`; SQLSTATE: HY000  
Message: The %s function returns the wrong type
  - Error number: 1492; Symbol: `ER_PARTITIONS_MUST_BE_DEFINED_ERROR`; SQLSTATE: HY000  
Message: For %s partitions each partition must be defined
  - Error number: 1493; Symbol: `ER_RANGE_NOT_INCREASING_ERROR`; SQLSTATE: HY000  
Message: VALUES LESS THAN value must be strictly increasing for each partition
  - Error number: 1494; Symbol: `ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR`; SQLSTATE: HY000  
Message: VALUES value must be of same type as partition function
  - Error number: 1495; Symbol: `ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR`; SQLSTATE: HY000  
Message: Multiple definition of same constant in list partitioning
  - Error number: 1496; Symbol: `ER_PARTITION_ENTRY_ERROR`; SQLSTATE: HY000  
Message: Partitioning can not be used stand-alone in query
  - Error number: 1497; Symbol: `ER_MIX_HANDLER_ERROR`; SQLSTATE: HY000  
Message: The mix of handlers in the partitions is not allowed in this version of MySQL
  - Error number: 1498; Symbol: `ER_PARTITION_NOT_DEFINED_ERROR`; SQLSTATE: HY000  
Message: For the partitioned engine it is necessary to define all %s
  - Error number: 1499; Symbol: `ER_TOO_MANY_PARTITIONS_ERROR`; SQLSTATE: HY000  
Message: Too many partitions (including subpartitions) were defined
  - Error number: 1500; Symbol: `ER_SUBPARTITION_ERROR`; SQLSTATE: HY000  
Message: It is only possible to mix RANGE/LIST partitioning with HASH/KEY partitioning for subpartitioning
  - Error number: 1501; Symbol: `ER_CANT_CREATE_HANDLER_FILE`; SQLSTATE: HY000  
Message: Failed to create specific handler file
  - Error number: 1502; Symbol: `ER_BLOB_FIELD_IN_PART_FUNC_ERROR`; SQLSTATE: HY000  
Message: A BLOB field is not allowed in partition function
  - Error number: 1503; Symbol: `ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF`; SQLSTATE: HY000

---

Message: A %s must include all columns in the table's partitioning function (prefixed columns are not considered).

- Error number: 1504; Symbol: `ER_NO_PARTS_ERROR`; SQLSTATE: `HY000`

Message: Number of %s = 0 is not an allowed value

- Error number: 1505; Symbol: `ER_PARTITION_MGMT_ON_NONPARTITIONED`; SQLSTATE: `HY000`

Message: Partition management on a not partitioned table is not possible

- Error number: 1506; Symbol: `ER_FOREIGN_KEY_ON_PARTITIONED`; SQLSTATE: `HY000`

Message: Foreign keys are not yet supported in conjunction with partitioning

- Error number: 1507; Symbol: `ER_DROP_PARTITION_NON_EXISTENT`; SQLSTATE: `HY000`

Message: Error in list of partitions to %s

- Error number: 1508; Symbol: `ER_DROP_LAST_PARTITION`; SQLSTATE: `HY000`

Message: Cannot remove all partitions, use DROP TABLE instead

- Error number: 1509; Symbol: `ER_COALESCE_ONLY_ON_HASH_PARTITION`; SQLSTATE: `HY000`

Message: COALESCE PARTITION can only be used on HASH/KEY partitions

- Error number: 1510; Symbol: `ER_REORG_HASH_ONLY_ON_SAME_NO`; SQLSTATE: `HY000`

Message: REORGANIZE PARTITION can only be used to reorganize partitions not to change their numbers

- Error number: 1511; Symbol: `ER_REORG_NO_PARAM_ERROR`; SQLSTATE: `HY000`

Message: REORGANIZE PARTITION without parameters can only be used on auto-partitioned tables using HASH PARTITIONS

- Error number: 1512; Symbol: `ER_ONLY_ON_RANGE_LIST_PARTITION`; SQLSTATE: `HY000`

Message: %s PARTITION can only be used on RANGE/LIST partitions

- Error number: 1513; Symbol: `ER_ADD_PARTITION_SUBPART_ERROR`; SQLSTATE: `HY000`

Message: Trying to Add partition(s) with wrong number of subpartitions

- Error number: 1514; Symbol: `ER_ADD_PARTITION_NO_NEW_PARTITION`; SQLSTATE: `HY000`

Message: At least one partition must be added

- Error number: 1515; Symbol: `ER_COALESCE_PARTITION_NO_PARTITION`; SQLSTATE: `HY000`

Message: At least one partition must be coalesced

- Error number: 1516; Symbol: `ER_REORG_PARTITION_NOT_EXIST`; SQLSTATE: `HY000`

Message: More partitions to reorganize than there are partitions

- Error number: 1517; Symbol: `ER_SAME_NAME_PARTITION`; SQLSTATE: `HY000`

Message: Duplicate partition name %s

- 
- Error number: [1518](#); Symbol: [ER\\_NO\\_BINLOG\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: It is not allowed to shut off binlog on this command
  - Error number: [1519](#); Symbol: [ER\\_CONSECUTIVE\\_REORG\\_PARTITIONS](#); SQLSTATE: [HY000](#)  
Message: When reorganizing a set of partitions they must be in consecutive order
  - Error number: [1520](#); Symbol: [ER\\_REORG\\_OUTSIDE\\_RANGE](#); SQLSTATE: [HY000](#)  
Message: Reorganize of range partitions cannot change total ranges except for last partition where it can extend the range
  - Error number: [1521](#); Symbol: [ER\\_PARTITION\\_FUNCTION\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Partition function not supported in this version for this handler
  - Error number: [1523](#); Symbol: [ER\\_LIMITED\\_PART\\_RANGE](#); SQLSTATE: [HY000](#)  
Message: The %s handler only supports 32 bit integers in VALUES
  - Error number: [1524](#); Symbol: [ER\\_PLUGIN\\_IS\\_NOT\\_LOADED](#); SQLSTATE: [HY000](#)  
Message: Plugin '%s' is not loaded
  - Error number: [1525](#); Symbol: [ER\\_WRONG\\_VALUE](#); SQLSTATE: [HY000](#)  
Message: Incorrect %s value: '%s'
  - Error number: [1526](#); Symbol: [ER\\_NO\\_PARTITION\\_FOR\\_GIVEN\\_VALUE](#); SQLSTATE: [HY000](#)  
Message: Table has no partition for value %s
  - Error number: [1527](#); Symbol: [ER\\_FILEGROUP\\_OPTION\\_ONLY\\_ONCE](#); SQLSTATE: [HY000](#)  
Message: It is not allowed to specify %s more than once
  - Error number: [1528](#); Symbol: [ER\\_CREATE\\_FILEGROUP\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to create %s
  - Error number: [1529](#); Symbol: [ER\\_DROP\\_FILEGROUP\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to drop %s
  - Error number: [1530](#); Symbol: [ER\\_TABLESPACE\\_AUTO\\_EXTEND\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The handler doesn't support autoextend of tablespaces
  - Error number: [1531](#); Symbol: [ER\\_WRONG\\_SIZE\\_NUMBER](#); SQLSTATE: [HY000](#)  
Message: A size parameter was incorrectly specified, either number or on the form 10M
  - Error number: [1532](#); Symbol: [ER\\_SIZE\\_OVERFLOW\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The size number was correct but we don't allow the digit part to be more than 2 billion
  - Error number: [1533](#); Symbol: [ER\\_ALTER\\_FILEGROUP\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to alter: %s

- 
- Error number: 1534; Symbol: `ER_BINLOG_ROW_LOGGING_FAILED`; SQLSTATE: HY000  
Message: Writing one row to the row-based binary log failed
  - Error number: 1537; Symbol: `ER_EVENT_ALREADY_EXISTS`; SQLSTATE: HY000  
Message: Event '%s' already exists
  - Error number: 1539; Symbol: `ER_EVENT_DOES_NOT_EXIST`; SQLSTATE: HY000  
Message: Unknown event '%s'
  - Error number: 1542; Symbol: `ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG`; SQLSTATE: HY000  
Message: INTERVAL is either not positive or too big
  - Error number: 1543; Symbol: `ER_EVENT_ENDS_BEFORE_STARTS`; SQLSTATE: HY000  
Message: ENDS is either invalid or before STARTS
  - Error number: 1544; Symbol: `ER_EVENT_EXEC_TIME_IN_THE_PAST`; SQLSTATE: HY000  
Message: Event execution time is in the past. Event has been disabled
  - Error number: 1551; Symbol: `ER_EVENT_SAME_NAME`; SQLSTATE: HY000  
Message: Same old and new event name
  - Error number: 1553; Symbol: `ER_DROP_INDEX_FK`; SQLSTATE: HY000  
Message: Cannot drop index '%s': needed in a foreign key constraint  
  
`InnoDB` reports this error when you attempt to drop the last index that can enforce a particular referential constraint.  
  
For optimal performance with DML statements, `InnoDB` requires an index to exist on [foreign key](#) columns, so that `UPDATE` and `DELETE` operations on a [parent table](#) can easily check whether corresponding rows exist in the [child table](#). MySQL creates or drops such indexes automatically when needed, as a side-effect of `CREATE TABLE`, `CREATE INDEX`, and `ALTER TABLE` statements.  
  
When you drop an index, `InnoDB` checks if the index is used for checking a foreign key constraint. It is still OK to drop the index if there is another index that can be used to enforce the same constraint. `InnoDB` prevents you from dropping the last index that can enforce a particular referential constraint.
  - Error number: 1554; Symbol: `ER_WARN_DEPRECATED_SYNTAX_WITH_VER`; SQLSTATE: HY000  
Message: The syntax '%s' is deprecated and will be removed in MySQL %. Please use %s instead
  - Error number: 1556; Symbol: `ER_CANT_LOCK_LOG_TABLE`; SQLSTATE: HY000  
Message: You can't use locks with log tables.
  - Error number: 1557; Symbol: `ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED`; SQLSTATE: 23000  
Message: Upholding foreign key constraints for table '%s', entry '%s', key %d would lead to a duplicate entry
  - Error number: 1558; Symbol: `ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE`; SQLSTATE: HY000

---

Message: The column count of mysql.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

- Error number: 1559; Symbol: ER\_TEMP\_TABLE\_PREVENTS\_SWITCH\_OUT\_OF\_RBR; SQLSTATE: HY000

Message: Cannot switch out of the row-based binary log format when the session has open temporary tables

ER\_TEMP\_TABLE\_PREVENTS\_SWITCH\_OUT\_OF\_RBR was removed after 8.0.12.

- Error number: 1560; Symbol: ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT; SQLSTATE: HY000

Message: Cannot change the binary logging format inside a stored function or trigger

- Error number: 1562; Symbol: ER\_PARTITION\_NO\_TEMPORARY; SQLSTATE: HY000

Message: Cannot create temporary table with partitions

- Error number: 1563; Symbol: ER\_PARTITION\_CONST\_DOMAIN\_ERROR; SQLSTATE: HY000

Message: Partition constant is out of partition function domain

- Error number: 1564; Symbol: ER\_PARTITION\_FUNCTION\_IS\_NOT\_ALLOWED; SQLSTATE: HY000

Message: This partition function is not allowed

- Error number: 1565; Symbol: ER\_DDL\_LOG\_ERROR; SQLSTATE: HY000

Message: Error in DDL log

ER\_DDL\_LOG\_ERROR was removed after 8.0.1.

- Error number: 1566; Symbol: ER\_NULL\_IN\_VALUES\_LESS\_THAN; SQLSTATE: HY000

Message: Not allowed to use NULL value in VALUES LESS THAN

- Error number: 1567; Symbol: ER\_WRONG\_PARTITION\_NAME; SQLSTATE: HY000

Message: Incorrect partition name

- Error number: 1568; Symbol: ER\_CANT\_CHANGE\_TX\_CHARACTERISTICS; SQLSTATE: 25001

Message: Transaction characteristics can't be changed while a transaction is in progress

- Error number: 1569; Symbol: ER\_DUP\_ENTRY\_AUTOINCREMENT\_CASE; SQLSTATE: HY000

Message: ALTER TABLE causes auto\_increment resequencing, resulting in duplicate entry '%s' for key '%s'

- Error number: 1571; Symbol: ER\_EVENT\_SET\_VAR\_ERROR; SQLSTATE: HY000

Message: Error during starting/stopping of the scheduler. Error code %u

- Error number: 1572; Symbol: ER\_PARTITION\_MERGE\_ERROR; SQLSTATE: HY000

Message: Engine cannot be used in partitioned tables

- 
- Error number: [1575](#); Symbol: [ER\\_BASE64\\_DECODE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Decoding of base64 string failed
  - Error number: [1576](#); Symbol: [ER\\_EVENT\\_RECURSION\\_FORBIDDEN](#); SQLSTATE: [HY000](#)  
Message: Recursion of EVENT DDL statements is forbidden when body is present
  - Error number: [1578](#); Symbol: [ER\\_ONLY\\_INTEGERS\\_ALLOWED](#); SQLSTATE: [HY000](#)  
Message: Only integers allowed as number here
  - Error number: [1579](#); Symbol: [ER\\_UNSUPPORTED\\_LOG\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: This storage engine cannot be used for log tables
  - Error number: [1580](#); Symbol: [ER\\_BAD\\_LOG\\_STATEMENT](#); SQLSTATE: [HY000](#)  
Message: You cannot '%s' a log table if logging is enabled
  - Error number: [1581](#); Symbol: [ER\\_CANT\\_RENAME\\_LOG\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot rename '%s'. When logging enabled, rename to/from log table must rename two tables: the log table to an archive table and another table back to '%s'
  - Error number: [1582](#); Symbol: [ER\\_WRONG\\_PARAMCOUNT\\_TO\\_NATIVE\\_FCT](#); SQLSTATE: [42000](#)  
Message: Incorrect parameter count in the call to native function '%s'
  - Error number: [1583](#); Symbol: [ER\\_WRONG\\_PARAMETERS\\_TO\\_NATIVE\\_FCT](#); SQLSTATE: [42000](#)  
Message: Incorrect parameters in the call to native function '%s'
  - Error number: [1584](#); Symbol: [ER\\_WRONG\\_PARAMETERS\\_TO\\_STORED\\_FCT](#); SQLSTATE: [42000](#)  
Message: Incorrect parameters in the call to stored function %s
  - Error number: [1585](#); Symbol: [ER\\_NATIVE\\_FCT\\_NAME\\_COLLISION](#); SQLSTATE: [HY000](#)  
Message: This function '%s' has the same name as a native function
  - Error number: [1586](#); Symbol: [ER\\_DUP\\_ENTRY\\_WITH\\_KEY\\_NAME](#); SQLSTATE: [23000](#)  
Message: Duplicate entry '%s' for key '%s'  
The format string for this error is also used with [ER\\_DUP\\_ENTRY](#).
  - Error number: [1587](#); Symbol: [ER\\_BINLOG\\_PURGE\\_EMFILE](#); SQLSTATE: [HY000](#)  
Message: Too many files opened, please execute the command again
  - Error number: [1588](#); Symbol: [ER\\_EVENT\\_CANNOT\\_CREATE\\_IN\\_THE\\_PAST](#); SQLSTATE: [HY000](#)  
Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was dropped immediately after creation.
  - Error number: [1589](#); Symbol: [ER\\_EVENT\\_CANNOT\\_ALTER\\_IN\\_THE\\_PAST](#); SQLSTATE: [HY000](#)  
Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was not changed. Specify a time in the future.



- 
- Error number: [1591](#); Symbol: [ER\\_NO\\_PARTITION\\_FOR\\_GIVEN\\_VALUE\\_SILENT](#); SQLSTATE: [HY000](#)  
Message: Table has no partition for some existing values
  - Error number: [1592](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_STATEMENT](#); SQLSTATE: [HY000](#)  
Message: Unsafe statement written to the binary log using statement format since BINLOG\_FORMAT = STATEMENT. %s
  - Error number: [1593](#); Symbol: [ER\\_BINLOG\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Fatal error: %s  
[ER\\_BINLOG\\_FATAL\\_ERROR](#) was added in 8.0.11.
  - Error number: [1598](#); Symbol: [ER\\_BINLOG\\_LOGGING\\_IMPOSSIBLE](#); SQLSTATE: [HY000](#)  
Message: Binary logging not possible. Message: %s
  - Error number: [1599](#); Symbol: [ER\\_VIEW\\_NO\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: View `%s`.`%s` has no creation context
  - Error number: [1600](#); Symbol: [ER\\_VIEW\\_INVALID\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: Creation context of view `%s`.`%s` is invalid
  - Error number: [1602](#); Symbol: [ER\\_TRG\\_CORRUPTED\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Corrupted TRG file for table `%s`.`%s`
  - Error number: [1603](#); Symbol: [ER\\_TRG\\_NO\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: Triggers for table `%s`.`%s` have no creation context
  - Error number: [1604](#); Symbol: [ER\\_TRG\\_INVALID\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: Trigger creation context of table `%s`.`%s` is invalid
  - Error number: [1605](#); Symbol: [ER\\_EVENT\\_INVALID\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: Creation context of event `%s`.`%s` is invalid
  - Error number: [1606](#); Symbol: [ER\\_TRG\\_CANT\\_OPEN\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot open table for trigger `%s`.`%s`
  - Error number: [1609](#); Symbol: [ER\\_NO\\_FORMAT\\_DESCRIPTION\\_EVENT\\_BEFORE\\_BINLOG\\_STATEMENT](#); SQLSTATE: [HY000](#)  
Message: The BINLOG statement of type `%s` was not preceded by a format description BINLOG statement.
  - Error number: [1610](#); Symbol: [ER\\_SLAVE\\_CORRUPT\\_EVENT](#); SQLSTATE: [HY000](#)  
Message: Corrupted replication event was detected  
[ER\\_SLAVE\\_CORRUPT\\_EVENT](#) was removed after 8.0.32.
  - Error number: [1610](#); Symbol: [ER\\_REPLICA\\_CORRUPT\\_EVENT](#); SQLSTATE: [HY000](#)

---

Message: Corrupted replication event was detected

[ER\\_REPLICA\\_CORRUPT\\_EVENT](#) was added in 8.0.33.

- Error number: [1612](#); Symbol: [ER\\_LOG\\_PURGE\\_NO\\_FILE](#); SQLSTATE: [HY000](#)

Message: Being purged log %s was not found

- Error number: [1613](#); Symbol: [ER\\_XA\\_RBTIMEOUT](#); SQLSTATE: [XA106](#)

Message: XA\_RBTIMEOUT: Transaction branch was rolled back: took too long

- Error number: [1614](#); Symbol: [ER\\_XA\\_RBDEADLOCK](#); SQLSTATE: [XA102](#)

Message: XA\_RBDEADLOCK: Transaction branch was rolled back: deadlock was detected

- Error number: [1615](#); Symbol: [ER\\_NEED\\_REPREPARE](#); SQLSTATE: [HY000](#)

Message: Prepared statement needs to be re-prepared

- Error number: [1617](#); Symbol: [WARN\\_NO\\_MASTER\\_INFO](#); SQLSTATE: [HY000](#)

Message: The master info structure does not exist

[WARN\\_NO\\_MASTER\\_INFO](#) was removed after 8.0.32.

- Error number: [1617](#); Symbol: [WARN\\_NO\\_CONNECTION\\_METADATA](#); SQLSTATE: [HY000](#)

Message: The connection metadata structure does not exist

[WARN\\_NO\\_CONNECTION\\_METADATA](#) was added in 8.0.33.

- Error number: [1618](#); Symbol: [WARN\\_OPTION\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: <%s> option ignored

- Error number: [1619](#); Symbol: [ER\\_PLUGIN\\_DELETE\\_BUILTIN](#); SQLSTATE: [HY000](#)

Message: Built-in plugins cannot be deleted

- Error number: [1620](#); Symbol: [WARN\\_PLUGIN\\_BUSY](#); SQLSTATE: [HY000](#)

Message: Plugin is busy and will be uninstalled on shutdown

- Error number: [1621](#); Symbol: [ER\\_VARIABLE\\_IS\\_READONLY](#); SQLSTATE: [HY000](#)

Message: %s variable '%s' is read-only. Use SET %s to assign the value

- Error number: [1622](#); Symbol: [ER\\_WARN\\_ENGINE\\_TRANSACTION\\_ROLLBACK](#); SQLSTATE: [HY000](#)

Message: Storage engine %s does not support rollback for this statement. Transaction rolled back and must be restarted

- Error number: [1624](#); Symbol: [ER\\_SLAVE\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)

Message: The requested value for the heartbeat period is either negative or exceeds the maximum allowed (%s seconds).

[ER\\_SLAVE\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE](#) was removed after 8.0.32.

- 
- Error number: [1624](#); Symbol: [ER\\_REPLICA\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)  
Message: The requested value for the heartbeat period is either negative or exceeds the maximum allowed (%s seconds).  
[ER\\_REPLICA\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE](#) was added in 8.0.33.
  - Error number: [1625](#); Symbol: [ER\\_NDB\\_REPLICATION\\_SCHEMA\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Bad schema for mysql.ndb\_replication table. Message: %s
  - Error number: [1626](#); Symbol: [ER\\_CONFLICT\\_FN\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error in parsing conflict function. Message: %s
  - Error number: [1627](#); Symbol: [ER\\_EXCEPTIONS\\_WRITE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Write to exceptions table failed. Message: %s
  - Error number: [1628](#); Symbol: [ER\\_TOO\\_LONG\\_TABLE\\_COMMENT](#); SQLSTATE: [HY000](#)  
Message: Comment for table '%s' is too long (max = %lu)
  - Error number: [1629](#); Symbol: [ER\\_TOO\\_LONG\\_FIELD\\_COMMENT](#); SQLSTATE: [HY000](#)  
Message: Comment for field '%s' is too long (max = %lu)
  - Error number: [1630](#); Symbol: [ER\\_FUNC\\_INEXISTENT\\_NAME\\_COLLISION](#); SQLSTATE: [42000](#)  
Message: FUNCTION %s does not exist. Check the 'Function Name Parsing and Resolution' section in the Reference Manual
  - Error number: [1631](#); Symbol: [ER\\_DATABASE\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Database
  - Error number: [1632](#); Symbol: [ER\\_TABLE\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Table
  - Error number: [1633](#); Symbol: [ER\\_PARTITION\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Partition
  - Error number: [1634](#); Symbol: [ER\\_SUBPARTITION\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Subpartition
  - Error number: [1635](#); Symbol: [ER\\_TEMPORARY\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Temporary
  - Error number: [1636](#); Symbol: [ER\\_RENAMED\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Renamed
  - Error number: [1637](#); Symbol: [ER\\_TOO\\_MANY\\_CONCURRENT\\_TRXS](#); SQLSTATE: [HY000](#)  
Message: Too many active concurrent transactions

- 
- Error number: 1638; Symbol: `WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED`; SQLSTATE: `HY000`  
Message: Non-ASCII separator arguments are not fully supported
  - Error number: 1639; Symbol: `ER_DEBUG_SYNC_TIMEOUT`; SQLSTATE: `HY000`  
Message: debug sync point wait timed out
  - Error number: 1640; Symbol: `ER_DEBUG_SYNC_HIT_LIMIT`; SQLSTATE: `HY000`  
Message: debug sync point hit limit reached
  - Error number: 1641; Symbol: `ER_DUP_SIGNAL_SET`; SQLSTATE: `42000`  
Message: Duplicate condition information item '%s'
  - Error number: 1642; Symbol: `ER_SIGNAL_WARN`; SQLSTATE: `01000`  
Message: Unhandled user-defined warning condition
  - Error number: 1643; Symbol: `ER_SIGNAL_NOT_FOUND`; SQLSTATE: `02000`  
Message: Unhandled user-defined not found condition
  - Error number: 1644; Symbol: `ER_SIGNAL_EXCEPTION`; SQLSTATE: `HY000`  
Message: Unhandled user-defined exception condition
  - Error number: 1645; Symbol: `ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER`; SQLSTATE: `0K000`  
Message: RESIGNAL when handler not active
  - Error number: 1646; Symbol: `ER_SIGNAL_BAD_CONDITION_TYPE`; SQLSTATE: `HY000`  
Message: SIGNAL/RESIGNAL can only use a CONDITION defined with SQLSTATE
  - Error number: 1647; Symbol: `WARN_COND_ITEM_TRUNCATED`; SQLSTATE: `HY000`  
Message: Data truncated for condition item '%s'
  - Error number: 1648; Symbol: `ER_COND_ITEM_TOO_LONG`; SQLSTATE: `HY000`  
Message: Data too long for condition item '%s'
  - Error number: 1649; Symbol: `ER_UNKNOWN_LOCALE`; SQLSTATE: `HY000`  
Message: Unknown locale: '%s'
  - Error number: 1650; Symbol: `ER_SLAVE_IGNORE_SERVER_IDS`; SQLSTATE: `HY000`  
Message: The requested server id %d clashes with the slave startup option --replicate-same-server-id  
`ER_SLAVE_IGNORE_SERVER_IDS` was removed after 8.0.32.
  - Error number: 1650; Symbol: `ER_REPLICA_IGNORE_SERVER_IDS`; SQLSTATE: `HY000`  
Message: The requested server id %d clashes with the replica startup option --replicate-same-server-id  
`ER_REPLICA_IGNORE_SERVER_IDS` was added in 8.0.33.

- 
- Error number: [1651](#); Symbol: [ER\\_QUERY\\_CACHE\\_DISABLED](#); SQLSTATE: [HY000](#)  
Message: Query cache is disabled; restart the server with query\_cache\_type=1 to enable it  
[ER\\_QUERY\\_CACHE\\_DISABLED](#) was removed after 8.0.2.
  - Error number: [1652](#); Symbol: [ER\\_SAME\\_NAME\\_PARTITION\\_FIELD](#); SQLSTATE: [HY000](#)  
Message: Duplicate partition field name '%s'
  - Error number: [1653](#); Symbol: [ER\\_PARTITION\\_COLUMN\\_LIST\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Inconsistency in usage of column lists for partitioning
  - Error number: [1654](#); Symbol: [ER\\_WRONG\\_TYPE\\_COLUMN\\_VALUE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Partition column values of incorrect type
  - Error number: [1655](#); Symbol: [ER\\_TOO\\_MANY\\_PARTITION\\_FUNC\\_FIELDS\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Too many fields in '%s'
  - Error number: [1656](#); Symbol: [ER\\_MAXVALUE\\_IN\\_VALUES\\_IN](#); SQLSTATE: [HY000](#)  
Message: Cannot use MAXVALUE as value in VALUES IN
  - Error number: [1657](#); Symbol: [ER\\_TOO\\_MANY\\_VALUES\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Cannot have more than one value for this type of %s partitioning
  - Error number: [1658](#); Symbol: [ER\\_ROW\\_SINGLE\\_PARTITION\\_FIELD\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Row expressions in VALUES IN only allowed for multi-field column partitioning
  - Error number: [1659](#); Symbol: [ER\\_FIELD\\_TYPE\\_NOT\\_ALLOWED\\_AS\\_PARTITION\\_FIELD](#); SQLSTATE: [HY000](#)  
Message: Field '%s' is of a not allowed type for this type of partitioning
  - Error number: [1660](#); Symbol: [ER\\_PARTITION\\_FIELDS\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
Message: The total length of the partitioning fields is too large
  - Error number: [1661](#); Symbol: [ER\\_BINLOG\\_ROW\\_ENGINE\\_AND\\_STMT\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Cannot execute statement: impossible to write to binary log since both row-incapable engines and statement-incapable engines are involved.
  - Error number: [1662](#); Symbol: [ER\\_BINLOG\\_ROW\\_MODE\\_AND\\_STMT\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Cannot execute statement: impossible to write to binary log since BINLOG\_FORMAT = ROW and at least one table uses a storage engine limited to statement-based logging.
  - Error number: [1663](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_AND\\_STMT\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Cannot execute statement: impossible to write to binary log since statement is unsafe, storage engine is limited to statement-based logging, and BINLOG\_FORMAT = MIXED. %s
  - Error number: [1664](#); Symbol: [ER\\_BINLOG\\_ROW\\_INJECTION\\_AND\\_STMT\\_ENGINE](#); SQLSTATE: [HY000](#)

---

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and at least one table uses a storage engine limited to statement-based logging.

- Error number: 1665; Symbol: `ER_BINLOG_STMT_MODE_AND_ROW_ENGINE`; SQLSTATE: `HY000`

Message: Cannot execute statement: impossible to write to binary log since `BINLOG_FORMAT = STATEMENT` and at least one table uses a storage engine limited to row-based logging. %s

- Error number: 1666; Symbol: `ER_BINLOG_ROW_INJECTION_AND_STMT_MODE`; SQLSTATE: `HY000`

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and `BINLOG_FORMAT = STATEMENT`.

- Error number: 1667; Symbol: `ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE`; SQLSTATE: `HY000`

Message: Cannot execute statement: impossible to write to binary log since more than one engine is involved and at least one engine is self-logging.

- Error number: 1668; Symbol: `ER_BINLOG_UNSAFE_LIMIT`; SQLSTATE: `HY000`

Message: The statement is unsafe because it uses a `LIMIT` clause. This is unsafe because the set of rows included cannot be predicted.

- Error number: 1670; Symbol: `ER_BINLOG_UNSAFE_SYSTEM_TABLE`; SQLSTATE: `HY000`

Message: The statement is unsafe because it uses the general log, slow query log, or `performance_schema` table(s). This is unsafe because system tables may differ on replicas.

- Error number: 1671; Symbol: `ER_BINLOG_UNSAFE_AUTOINC_COLUMNS`; SQLSTATE: `HY000`

Message: Statement is unsafe because it invokes a trigger or a stored function that inserts into an `AUTO_INCREMENT` column. Inserted values cannot be logged correctly.

- Error number: 1672; Symbol: `ER_BINLOG_UNSAFE_UDF`; SQLSTATE: `HY000`

Message: Statement is unsafe because it uses a UDF which may not return the same value on the replica.

- Error number: 1673; Symbol: `ER_BINLOG_UNSAFE_SYSTEM_VARIABLE`; SQLSTATE: `HY000`

Message: Statement is unsafe because it uses a system variable that may have a different value on the replica.

- Error number: 1674; Symbol: `ER_BINLOG_UNSAFE_SYSTEM_FUNCTION`; SQLSTATE: `HY000`

Message: Statement is unsafe because it uses a system function that may return a different value on the replica.

- Error number: 1675; Symbol: `ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS`; SQLSTATE: `HY000`

Message: Statement is unsafe because it accesses a non-transactional table after accessing a transactional table within the same transaction.

- Error number: 1676; Symbol: `ER_MESSAGE_AND_STATEMENT`; SQLSTATE: `HY000`

Message: %s Statement: %s

- 
- Error number: [1677](#); Symbol: [ER\\_SLAVE\\_CONVERSION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'  
[ER\\_SLAVE\\_CONVERSION\\_FAILED](#) was removed after 8.0.4.
  - Error number: [1678](#); Symbol: [ER\\_SLAVE\\_CANT\\_CREATE\\_CONVERSION](#); SQLSTATE: [HY000](#)  
Message: Can't create conversion table for table '%s.%s'  
[ER\\_SLAVE\\_CANT\\_CREATE\\_CONVERSION](#) was removed after 8.0.32.
  - Error number: [1678](#); Symbol: [ER\\_REPLICA\\_CANT\\_CREATE\\_CONVERSION](#); SQLSTATE: [HY000](#)  
Message: Can't create conversion table for table '%s.%s'  
[ER\\_REPLICA\\_CANT\\_CREATE\\_CONVERSION](#) was added in 8.0.33.
  - Error number: [1679](#); Symbol: [ER\\_INSIDE\\_TRANSACTION\\_PREVENTS\\_SWITCH\\_BINLOG\\_FORMAT](#); SQLSTATE: [HY000](#)  
Message: Cannot modify @@session.binlog\_format inside a transaction
  - Error number: [1680](#); Symbol: [ER\\_PATH\\_LENGTH](#); SQLSTATE: [HY000](#)  
Message: The path specified for %s is too long.
  - Error number: [1681](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_SYNTAX\\_NO\\_REPLACEMENT](#); SQLSTATE: [HY000](#)  
Message: '%s' is deprecated and will be removed in a future release.
  - Error number: [1682](#); Symbol: [ER\\_WRONG\\_NATIVE\\_TABLE\\_STRUCTURE](#); SQLSTATE: [HY000](#)  
Message: Native table '%s'.'%s' has the wrong structure
  - Error number: [1683](#); Symbol: [ER\\_WRONG\\_PERFSCHEMA\\_USAGE](#); SQLSTATE: [HY000](#)  
Message: Invalid performance\_schema usage.
  - Error number: [1684](#); Symbol: [ER\\_WARN\\_I\\_S\\_SKIPPED\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Table '%s'.'%s' was skipped since its definition is being modified by concurrent DDL statement
  - Error number: [1685](#); Symbol: [ER\\_INSIDE\\_TRANSACTION\\_PREVENTS\\_SWITCH\\_BINLOG\\_DIRECT](#); SQLSTATE: [HY000](#)  
Message: Cannot modify @@session.binlog\_direct\_non\_transactional\_updates inside a transaction
  - Error number: [1686](#); Symbol: [ER\\_STORED\\_FUNCTION\\_PREVENTS\\_SWITCH\\_BINLOG\\_DIRECT](#); SQLSTATE: [HY000](#)  
Message: Cannot change the binlog direct flag inside a stored function or trigger
  - Error number: [1687](#); Symbol: [ER\\_SPATIAL\\_MUST\\_HAVE\\_GEOM\\_COL](#); SQLSTATE: [42000](#)  
Message: A SPATIAL index may only contain a geometrical type column
  - Error number: [1688](#); Symbol: [ER\\_TOO\\_LONG\\_INDEX\\_COMMENT](#); SQLSTATE: [HY000](#)

---

Message: Comment for index '%s' is too long (max = %lu)

- Error number: 1689; Symbol: `ER_LOCK_ABORTED`; SQLSTATE: `HY000`

Message: Wait on a lock was aborted due to a pending exclusive lock

- Error number: 1690; Symbol: `ER_DATA_OUT_OF_RANGE`; SQLSTATE: `22003`

Message: %s value is out of range in '%s'

- Error number: 1691; Symbol: `ER_WRONG_SPVAR_TYPE_IN_LIMIT`; SQLSTATE: `HY000`

Message: A variable of a non-integer based type in LIMIT clause

`ER_WRONG_SPVAR_TYPE_IN_LIMIT` was removed after 8.0.21.

- Error number: 1692; Symbol: `ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE`; SQLSTATE: `HY000`

Message: Mixing self-logging and non-self-logging engines in a statement is unsafe.

- Error number: 1693; Symbol: `ER_BINLOG_UNSAFE_MIXED_STATEMENT`; SQLSTATE: `HY000`

Message: Statement accesses nontransactional table as well as transactional or temporary table, and writes to any of them.

- Error number: 1694; Symbol: `ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG_BIN`; SQLSTATE: `HY000`

Message: Cannot modify @@session.sql\_log\_bin inside a transaction

- Error number: 1695; Symbol: `ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN`; SQLSTATE: `HY000`

Message: Cannot change the sql\_log\_bin inside a stored function or trigger

- Error number: 1696; Symbol: `ER_FAILED_READ_FROM_PAR_FILE`; SQLSTATE: `HY000`

Message: Failed to read from the .par file

- Error number: 1697; Symbol: `ER_VALUES_IS_NOT_INT_TYPE_ERROR`; SQLSTATE: `HY000`

Message: VALUES value for partition '%s' must have type INT

- Error number: 1698; Symbol: `ER_ACCESS_DENIED_NO_PASSWORD_ERROR`; SQLSTATE: `28000`

Message: Access denied for user '%s'@'%s'

- Error number: 1699; Symbol: `ER_SET_PASSWORD_AUTH_PLUGIN`; SQLSTATE: `HY000`

Message: SET PASSWORD has no significance for users authenticating via plugins

`ER_SET_PASSWORD_AUTH_PLUGIN` was removed after 8.0.28.

- Error number: 1701; Symbol: `ER_TRUNCATE_ILLEGAL_FK`; SQLSTATE: `42000`

Message: Cannot truncate a table referenced in a foreign key constraint (%s)

- Error number: 1702; Symbol: `ER_PLUGIN_IS_PERMANENT`; SQLSTATE: `HY000`



---

Message: Plugin '%s' is force\_plus\_permanent and can not be unloaded

- Error number: 1703; Symbol: `ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN`; SQLSTATE: `HY000`

Message: The requested value for the heartbeat period is less than 1 millisecond. The value is reset to 0, meaning that heartbeating will effectively be disabled.

`ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN` was removed after 8.0.32.

- Error number: 1703; Symbol: `ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN`; SQLSTATE: `HY000`

Message: The requested value for the heartbeat period is less than 1 millisecond. The value is reset to 0, meaning that heartbeating will effectively be disabled.

`ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN` was added in 8.0.33.

- Error number: 1704; Symbol: `ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX`; SQLSTATE: `HY000`

Message: The requested value for the heartbeat period exceeds the value of `replica\_net\_timeout` seconds. A sensible value for the period should be less than the timeout.

`ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX` was removed after 8.0.32.

- Error number: 1704; Symbol: `ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX`; SQLSTATE: `HY000`

Message: The requested value for the heartbeat period exceeds the value of `replica\_net\_timeout` seconds. A sensible value for the period should be less than the timeout.

`ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX` was added in 8.0.33.

- Error number: 1705; Symbol: `ER_STMT_CACHE_FULL`; SQLSTATE: `HY000`

Message: Multi-row statements required more than 'max\_binlog\_stmt\_cache\_size' bytes of storage; increase this mysqld variable and try again

- Error number: 1706; Symbol: `ER_MULTI_UPDATE_KEY_CONFLICT`; SQLSTATE: `HY000`

Message: Primary key/partition key update is not allowed since the table is updated both as '%s' and '%s'.

- Error number: 1707; Symbol: `ER_TABLE_NEEDS_REBUILD`; SQLSTATE: `HY000`

Message: Table rebuild required. Please do "ALTER TABLE `%s` FORCE" or dump/reload to fix it!

- Error number: 1708; Symbol: `WARN_OPTION_BELOW_LIMIT`; SQLSTATE: `HY000`

Message: The value of '%s' should be no less than the value of '%s'

- Error number: 1709; Symbol: `ER_INDEX_COLUMN_TOO_LONG`; SQLSTATE: `HY000`

Message: Index column size too large. The maximum column size is %lu bytes.

- Error number: 1710; Symbol: `ER_ERROR_IN_TRIGGER_BODY`; SQLSTATE: `HY000`

---

Message: Trigger '%s' has an error in its body: '%s'

- Error number: 1711; Symbol: [ER\\_ERROR\\_IN\\_UNKNOWN\\_TRIGGER\\_BODY](#); SQLSTATE: [HY000](#)

Message: Unknown trigger has an error in its body: '%s'

- Error number: 1712; Symbol: [ER\\_INDEX\\_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Index %s is corrupted

- Error number: 1713; Symbol: [ER\\_UNDO\\_RECORD\\_TOO\\_BIG](#); SQLSTATE: [HY000](#)

Message: Undo log record is too big.

- Error number: 1714; Symbol: [ER\\_BINLOG\\_UNSAFE\\_INSERT\\_IGNORE\\_SELECT](#); SQLSTATE: [HY000](#)

Message: INSERT IGNORE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: 1715; Symbol: [ER\\_BINLOG\\_UNSAFE\\_INSERT\\_SELECT\\_UPDATE](#); SQLSTATE: [HY000](#)

Message: INSERT... SELECT... ON DUPLICATE KEY UPDATE is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are updated. This order cannot be predicted and may differ on source and the replica.

- Error number: 1716; Symbol: [ER\\_BINLOG\\_UNSAFE\\_REPLACE\\_SELECT](#); SQLSTATE: [HY000](#)

Message: REPLACE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on source and the replica.

- Error number: 1717; Symbol: [ER\\_BINLOG\\_UNSAFE\\_CREATE\\_IGNORE\\_SELECT](#); SQLSTATE: [HY000](#)

Message: CREATE... IGNORE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: 1718; Symbol: [ER\\_BINLOG\\_UNSAFE\\_CREATE\\_REPLACE\\_SELECT](#); SQLSTATE: [HY000](#)

Message: CREATE... REPLACE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on source and the replica.

- Error number: 1719; Symbol: [ER\\_BINLOG\\_UNSAFE\\_UPDATE\\_IGNORE](#); SQLSTATE: [HY000](#)

Message: UPDATE IGNORE is unsafe because the order in which rows are updated determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: 1720; Symbol: [ER\\_PLUGIN\\_NO\\_UNINSTALL](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is marked as not dynamically uninstallable. You have to stop the server to uninstall it.

- Error number: 1721; Symbol: [ER\\_PLUGIN\\_NO\\_INSTALL](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.

- 
- Error number: [1722](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_WRITE\\_AUTOINC\\_SELECT](#); SQLSTATE: [HY000](#)  
Message: Statements writing to a table with an auto-increment column after selecting from another table are unsafe because the order in which rows are retrieved determines what (if any) rows will be written. This order cannot be predicted and may differ on source and the replica.
  - Error number: [1723](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_CREATE\\_SELECT\\_AUTOINC](#); SQLSTATE: [HY000](#)  
Message: CREATE TABLE... SELECT... on a table with an auto-increment column is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are inserted. This order cannot be predicted and may differ on source and the replica.
  - Error number: [1724](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_INSERT\\_TWO\\_KEYS](#); SQLSTATE: [HY000](#)  
Message: INSERT... ON DUPLICATE KEY UPDATE on a table with more than one UNIQUE KEY is unsafe
  - Error number: [1725](#); Symbol: [ER\\_TABLE\\_IN\\_FK\\_CHECK](#); SQLSTATE: [HY000](#)  
Message: Table is being used in foreign key check.
  - Error number: [1726](#); Symbol: [ER\\_UNSUPPORTED\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Storage engine '%s' does not support system tables. [%s.%s]
  - Error number: [1727](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_AUTOINC\\_NOT\\_FIRST](#); SQLSTATE: [HY000](#)  
Message: INSERT into autoincrement field which is not the first part in the composed primary key is unsafe.
  - Error number: [1728](#); Symbol: [ER\\_CANNOT\\_LOAD\\_FROM\\_TABLE\\_V2](#); SQLSTATE: [HY000](#)  
Message: Cannot load from %s.%s. The table is probably corrupted
  - Error number: [1729](#); Symbol: [ER\\_MASTER\\_DELAY\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)  
Message: The requested value %s for the master delay exceeds the maximum %u  
[ER\\_MASTER\\_DELAY\\_VALUE\\_OUT\\_OF\\_RANGE](#) was removed after 8.0.32.
  - Error number: [1729](#); Symbol: [ER\\_SOURCE\\_DELAY\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)  
Message: The requested value %s for the source delay exceeds the maximum %u  
[ER\\_SOURCE\\_DELAY\\_VALUE\\_OUT\\_OF\\_RANGE](#) was added in 8.0.33.
  - Error number: [1730](#); Symbol: [ER\\_ONLY\\_FD\\_AND\\_RBR\\_EVENTS\\_ALLOWED\\_IN\\_BINLOG\\_STATEMENT](#); SQLSTATE: [HY000](#)  
Message: Only Format\_description\_log\_event and row events are allowed in BINLOG statements (but %s was provided)
  - Error number: [1731](#); Symbol: [ER\\_PARTITION\\_EXCHANGE\\_DIFFERENT\\_OPTION](#); SQLSTATE: [HY000](#)  
Message: Non matching attribute '%s' between partition and table
  - Error number: [1732](#); Symbol: [ER\\_PARTITION\\_EXCHANGE\\_PART\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Table to exchange with partition is partitioned: '%s'

- 
- Error number: [1733](#); Symbol: [ER\\_PARTITION\\_EXCHANGE\\_TEMP\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Table to exchange with partition is temporary: '%s'
  - Error number: [1734](#); Symbol: [ER\\_PARTITION\\_INSTEAD\\_OF\\_SUBPARTITION](#); SQLSTATE: [HY000](#)  
Message: Subpartitioned table, use subpartition instead of partition
  - Error number: [1735](#); Symbol: [ER\\_UNKNOWN\\_PARTITION](#); SQLSTATE: [HY000](#)  
Message: Unknown partition '%s' in table '%s'
  - Error number: [1736](#); Symbol: [ER\\_TABLES\\_DIFFERENT\\_METADATA](#); SQLSTATE: [HY000](#)  
Message: Tables have different definitions
  - Error number: [1737](#); Symbol: [ER\\_ROW\\_DOES\\_NOT\\_MATCH\\_PARTITION](#); SQLSTATE: [HY000](#)  
Message: Found a row that does not match the partition
  - Error number: [1738](#); Symbol: [ER\\_BINLOG\\_CACHE\\_SIZE\\_GREATER\\_THAN\\_MAX](#); SQLSTATE: [HY000](#)  
Message: Option binlog\_cache\_size (%lu) is greater than max\_binlog\_cache\_size (%lu); setting binlog\_cache\_size equal to max\_binlog\_cache\_size.
  - Error number: [1739](#); Symbol: [ER\\_WARN\\_INDEX\\_NOT\\_APPLICABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot use %s access on index '%s' due to type or collation conversion on field '%s'
  - Error number: [1740](#); Symbol: [ER\\_PARTITION\\_EXCHANGE\\_FOREIGN\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Table to exchange with partition has foreign key references: '%s'
  - Error number: [1742](#); Symbol: [ER\\_RPL\\_INFO\\_DATA\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
Message: Data for column '%s' too long
  - Error number: [1745](#); Symbol: [ER\\_BINLOG\\_STMT\\_CACHE\\_SIZE\\_GREATER\\_THAN\\_MAX](#); SQLSTATE: [HY000](#)  
Message: Option binlog\_stmt\_cache\_size (%lu) is greater than max\_binlog\_stmt\_cache\_size (%lu); setting binlog\_stmt\_cache\_size equal to max\_binlog\_stmt\_cache\_size.
  - Error number: [1746](#); Symbol: [ER\\_CANT\\_UPDATE\\_TABLE\\_IN\\_CREATE\\_TABLE\\_SELECT](#); SQLSTATE: [HY000](#)  
Message: Can't update table '%s' while '%s' is being created.
  - Error number: [1747](#); Symbol: [ER\\_PARTITION\\_CLAUSE\\_ON\\_NONPARTITIONED](#); SQLSTATE: [HY000](#)  
Message: PARTITION () clause on non partitioned table
  - Error number: [1748](#); Symbol: [ER\\_ROW\\_DOES\\_NOT\\_MATCH\\_GIVEN\\_PARTITION\\_SET](#); SQLSTATE: [HY000](#)  
Message: Found a row not matching the given partition set
  - Error number: [1750](#); Symbol: [ER\\_CHANGE\\_RPL\\_INFO\\_REPOSITORY\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Failure while changing the type of replication repository: %s.

- 
- Error number: 1751; Symbol: `ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATED_TEMP_TABLE`; SQLSTATE: HY000  
Message: The creation of some temporary tables could not be rolled back.
  - Error number: 1752; Symbol: `ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPED_TEMP_TABLE`; SQLSTATE: HY000  
Message: Some temporary tables were dropped, but these operations could not be rolled back.
  - Error number: 1753; Symbol: `ER_MTS_FEATURE_IS_NOT_SUPPORTED`; SQLSTATE: HY000  
Message: %s is not supported in multi-threaded slave mode. %s  
`ER_MTS_FEATURE_IS_NOT_SUPPORTED` was removed after 8.0.32.
  - Error number: 1753; Symbol: `ER_MTA_FEATURE_IS_NOT_SUPPORTED`; SQLSTATE: HY000  
Message: %s is not supported in multi-threaded replica mode. %s  
`ER_MTA_FEATURE_IS_NOT_SUPPORTED` was added in 8.0.33.
  - Error number: 1754; Symbol: `ER_MTS_UPDATED_DBS_GREATER_MAX`; SQLSTATE: HY000  
Message: The number of modified databases exceeds the maximum %d; the database names will not be included in the replication event metadata.  
`ER_MTS_UPDATED_DBS_GREATER_MAX` was removed after 8.0.32.
  - Error number: 1754; Symbol: `ER_MTA_UPDATED_DBS_GREATER_MAX`; SQLSTATE: HY000  
Message: The number of modified databases exceeds the maximum %d; the database names will not be included in the replication event metadata.  
`ER_MTA_UPDATED_DBS_GREATER_MAX` was added in 8.0.33.
  - Error number: 1755; Symbol: `ER_MTS_CANT_PARALLEL`; SQLSTATE: HY000  
Message: Cannot execute the current event group in the parallel mode. Encountered event %s, relay-log name %s, position %s which prevents execution of this event group in parallel mode. Reason: %s.  
`ER_MTS_CANT_PARALLEL` was removed after 8.0.32.
  - Error number: 1755; Symbol: `ER_MTA_CANT_PARALLEL`; SQLSTATE: HY000  
Message: Cannot execute the current event group in the parallel mode. Encountered event %s, relay-log name %s, position %s which prevents execution of this event group in parallel mode. Reason: %s.  
`ER_MTA_CANT_PARALLEL` was added in 8.0.33.
  - Error number: 1756; Symbol: `ER_MTS_INCONSISTENT_DATA`; SQLSTATE: HY000  
Message: %s  
`ER_MTS_INCONSISTENT_DATA` was removed after 8.0.32.
  - Error number: 1756; Symbol: `ER_MTA_INCONSISTENT_DATA`; SQLSTATE: HY000  
Message: %s
-

---

`ER_MTA_INCONSISTENT_DATA` was added in 8.0.33.

- Error number: `1757`; Symbol: `ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING`; SQLSTATE: `HY000`

Message: FULLTEXT index is not supported for partitioned tables.

- Error number: `1758`; Symbol: `ER_DA_INVALID_CONDITION_NUMBER`; SQLSTATE: `35000`

Message: Invalid condition number

- Error number: `1759`; Symbol: `ER_INSECURE_PLAIN_TEXT`; SQLSTATE: `HY000`

Message: Sending passwords in plain text without SSL/TLS is extremely insecure.

- Error number: `1760`; Symbol: `ER_INSECURE_CHANGE_MASTER`; SQLSTATE: `HY000`

Message: Storing MySQL user name or password information in the master info repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START SLAVE; see the 'START SLAVE Syntax' in the MySQL Manual for more information.

`ER_INSECURE_CHANGE_MASTER` was removed after 8.0.32.

- Error number: `1760`; Symbol: `ER_INSECURE_CHANGE_SOURCE`; SQLSTATE: `HY000`

Message: Storing MySQL user name or password information in the connection metadata repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START REPLICA; see the 'START REPLICA Syntax' in the MySQL Manual for more information.

`ER_INSECURE_CHANGE_SOURCE` was added in 8.0.33.

- Error number: `1761`; Symbol: `ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO`; SQLSTATE: `23000`

Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in table '%s', key '%s'

- Error number: `1762`; Symbol: `ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO`; SQLSTATE: `23000`

Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in a child table

- Error number: `1763`; Symbol: `ER_SQLTHREAD_WITH_SECURE_SLAVE`; SQLSTATE: `HY000`

Message: Setting authentication options is not possible when only the Slave SQL Thread is being started.

`ER_SQLTHREAD_WITH_SECURE_SLAVE` was removed after 8.0.32.

- Error number: `1763`; Symbol: `ER_SQLTHREAD_WITH_SECURE_REPLICA`; SQLSTATE: `HY000`

Message: Setting authentication options is not possible when only the Replica SQL Thread is being started.

`ER_SQLTHREAD_WITH_SECURE_REPLICA` was added in 8.0.33.

- Error number: `1764`; Symbol: `ER_TABLE_HAS_NO_FT`; SQLSTATE: `HY000`

---

Message: The table does not have FULLTEXT index to support this query

- Error number: 1765; Symbol: `ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER`; SQLSTATE: HY000

Message: The system variable %s cannot be set in stored functions or triggers.

- Error number: 1766; Symbol: `ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION`; SQLSTATE: HY000

Message: The system variable %s cannot be set when there is an ongoing transaction.

- Error number: 1769; Symbol: `ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION`; SQLSTATE: HY000

Message: The statement 'SET %s' cannot invoke a stored function.

- Error number: 1770; Symbol: `ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_NON_NULL`; SQLSTATE: HY000

Message: The system variable @@SESSION.GTID\_NEXT cannot be 'AUTOMATIC' when @@SESSION.GTID\_NEXT\_LIST is non-NULL.

- Error number: 1772; Symbol: `ER_MALFORMED_GTID_SET_SPECIFICATION`; SQLSTATE: HY000

Message: Malformed GTID set specification '%s'.

- Error number: 1773; Symbol: `ER_MALFORMED_GTID_SET_ENCODING`; SQLSTATE: HY000

Message: Malformed GTID set encoding.

- Error number: 1774; Symbol: `ER_MALFORMED_GTID_SPECIFICATION`; SQLSTATE: HY000

Message: Malformed GTID specification '%s'.

- Error number: 1775; Symbol: `ER_GNO_EXHAUSTED`; SQLSTATE: HY000

Message: Impossible to generate GTID: the integer component reached the maximum value. Restart the server with a new server\_uuid.

- Error number: 1776; Symbol: `ER_BAD_SLAVE_AUTO_POSITION`; SQLSTATE: HY000

Message: Parameters MASTER\_LOG\_FILE, MASTER\_LOG\_POS, RELAY\_LOG\_FILE and RELAY\_LOG\_POS cannot be set when MASTER\_AUTO\_POSITION is active.

`ER_BAD_SLAVE_AUTO_POSITION` was removed after 8.0.32.

- Error number: 1776; Symbol: `ER_BAD_REPLICA_AUTO_POSITION`; SQLSTATE: HY000

Message: Parameters SOURCE\_LOG\_FILE, SOURCE\_LOG\_POS, RELAY\_LOG\_FILE and RELAY\_LOG\_POS cannot be set when SOURCE\_AUTO\_POSITION is active.

`ER_BAD_REPLICA_AUTO_POSITION` was added in 8.0.33.

- Error number: 1777; Symbol: `ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF`; SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO SOURCE\_AUTO\_POSITION = 1 cannot be executed because @@GLOBAL.GTID\_MODE = OFF.

- 
- Error number: 1778; Symbol: `ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_NEXT_IS_SET`; SQLSTATE: HY000  
  
Message: Cannot execute statements with implicit commit inside a transaction when @@SESSION.GTID\_NEXT == 'UUID:NUMBER'.
  - Error number: 1779; Symbol: `ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON`; SQLSTATE: HY000  
  
Message: GTID\_MODE = ON requires ENFORCE\_GTID\_CONSISTENCY = ON.
  - Error number: 1781; Symbol: `ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_OFF`; SQLSTATE: HY000  
  
Message: @@SESSION.GTID\_NEXT cannot be set to UUID:NUMBER when @@GLOBAL.GTID\_MODE = OFF.
  - Error number: 1782; Symbol: `ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_IS_ON`; SQLSTATE: HY000  
  
Message: @@SESSION.GTID\_NEXT cannot be set to ANONYMOUS when @@GLOBAL.GTID\_MODE = ON.
  - Error number: 1783; Symbol: `ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_OFF`; SQLSTATE: HY000  
  
Message: @@SESSION.GTID\_NEXT\_LIST cannot be set to a non-NULL value when @@GLOBAL.GTID\_MODE = OFF.
  - Error number: 1785; Symbol: `ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE`; SQLSTATE: HY000  
  
Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.
  - Error number: 1786; Symbol: `ER_GTID_UNSAFE_CREATE_SELECT`; SQLSTATE: HY000  
  
Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.
  - Error number: 1787; Symbol: `ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN_TRANSACTION`; SQLSTATE: HY000  
  
Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE can only be executed outside transactional context. These statements are also not allowed in a function or trigger because functions and triggers are also considered to be multi-statement transactions.  
  
`ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN_TRANSACTION` was removed after 8.0.12.
  - Error number: 1788; Symbol: `ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME`; SQLSTATE: HY000  
  
Message: The value of @@GLOBAL.GTID\_MODE can only be changed one step at a time: OFF <-> OFF\_PERMISSIVE <-> ON\_PERMISSIVE <-> ON. Also note that this value must be stepped up or down simultaneously on all servers. See the Manual for instructions.



- 
- Error number: [1789](#); Symbol: [ER\\_MASTER\\_HAS\\_PURGED\\_REQUIRED\\_GTIDS](#); SQLSTATE: [HY000](#)  
Message: Cannot replicate because the master purged required binary logs. Replicate the missing transactions from elsewhere, or provision a new slave from backup. Consider increasing the master's binary log expiration period. %s  
[ER\\_MASTER\\_HAS\\_PURGED\\_REQUIRED\\_GTIDS](#) was removed after 8.0.32.
  - Error number: [1789](#); Symbol: [ER\\_SOURCE\\_HAS\\_PURGED\\_REQUIRED\\_GTIDS](#); SQLSTATE: [HY000](#)  
Message: Cannot replicate because the source purged required binary logs. Replicate the missing transactions from elsewhere, or provision a new replica from backup. Consider increasing the source's binary log expiration period. %s  
[ER\\_SOURCE\\_HAS\\_PURGED\\_REQUIRED\\_GTIDS](#) was added in 8.0.33.
  - Error number: [1790](#); Symbol: [ER\\_CANT\\_SET\\_GTID\\_NEXT\\_WHEN\\_OWNING\\_GTID](#); SQLSTATE: [HY000](#)  
Message: @@SESSION.GTID\_NEXT cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.
  - Error number: [1791](#); Symbol: [ER\\_UNKNOWN\\_EXPLAIN\\_FORMAT](#); SQLSTATE: [HY000](#)  
Message: Unknown EXPLAIN format name: '%s'
  - Error number: [1792](#); Symbol: [ER\\_CANT\\_EXECUTE\\_IN\\_READ\\_ONLY\\_TRANSACTION](#); SQLSTATE: [25006](#)  
Message: Cannot execute statement in a READ ONLY transaction.
  - Error number: [1793](#); Symbol: [ER\\_TOO\\_LONG\\_TABLE\\_PARTITION\\_COMMENT](#); SQLSTATE: [HY000](#)  
Message: Comment for table partition '%s' is too long (max = %lu)
  - Error number: [1794](#); Symbol: [ER\\_SLAVE\\_CONFIGURATION](#); SQLSTATE: [HY000](#)  
Message: Slave is not configured or failed to initialize properly. You must at least set --server-id to enable either a master or a slave. Additional error messages can be found in the MySQL error log.  
[ER\\_SLAVE\\_CONFIGURATION](#) was removed after 8.0.32.
  - Error number: [1794](#); Symbol: [ER\\_REPLICA\\_CONFIGURATION](#); SQLSTATE: [HY000](#)  
Message: Replica is not configured or failed to initialize properly. You must at least set --server-id to enable either a source or a replica. Additional error messages can be found in the MySQL error log.  
[ER\\_REPLICA\\_CONFIGURATION](#) was added in 8.0.33.
  - Error number: [1795](#); Symbol: [ER\\_INNODB\\_FT\\_LIMIT](#); SQLSTATE: [HY000](#)  
Message: InnoDB presently supports one FULLTEXT index creation at a time
  - Error number: [1796](#); Symbol: [ER\\_INNODB\\_NO\\_FT\\_TEMP\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot create FULLTEXT index on temporary InnoDB table
  - Error number: [1797](#); Symbol: [ER\\_INNODB\\_FT\\_WRONG\\_DOCID\\_COLUMN](#); SQLSTATE: [HY000](#)  
Message: Column '%s' is of wrong type for an InnoDB FULLTEXT index

- 
- Error number: [1798](#); Symbol: [ER\\_INNODB\\_FT\\_WRONG\\_DOCID\\_INDEX](#); SQLSTATE: [HY000](#)  
Message: Index '%s' is of wrong type for an InnoDB FULLTEXT index
  - Error number: [1799](#); Symbol: [ER\\_INNODB\\_ONLINE\\_LOG\\_TOO\\_BIG](#); SQLSTATE: [HY000](#)  
Message: Creating index '%s' required more than 'innodb\_online\_alter\_log\_max\_size' bytes of modification log. Please try again.
  - Error number: [1800](#); Symbol: [ER\\_UNKNOWN\\_ALTER\\_ALGORITHM](#); SQLSTATE: [HY000](#)  
Message: Unknown ALGORITHM '%s'
  - Error number: [1801](#); Symbol: [ER\\_UNKNOWN\\_ALTER\\_LOCK](#); SQLSTATE: [HY000](#)  
Message: Unknown LOCK type '%s'
  - Error number: [1802](#); Symbol: [ER\\_MTS\\_CHANGE\\_MASTER\\_CANT\\_RUN\\_WITH\\_GAPS](#); SQLSTATE: [HY000](#)  
Message: CHANGE MASTER cannot be executed when the slave was stopped with an error or killed in MTS mode. Consider using RESET SLAVE or START SLAVE UNTIL.  
[ER\\_MTS\\_CHANGE\\_MASTER\\_CANT\\_RUN\\_WITH\\_GAPS](#) was removed after 8.0.32.
  - Error number: [1802](#); Symbol: [ER\\_MTA\\_CHANGE\\_SOURCE\\_CANT\\_RUN\\_WITH\\_GAPS](#); SQLSTATE: [HY000](#)  
Message: CHANGE REPLICATION SOURCE cannot be executed when the replica was stopped with an error or killed in MTA mode. Consider using RESET REPLICA or START REPLICA UNTIL.  
[ER\\_MTA\\_CHANGE\\_SOURCE\\_CANT\\_RUN\\_WITH\\_GAPS](#) was added in 8.0.33.
  - Error number: [1803](#); Symbol: [ER\\_MTS\\_RECOVERY\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Cannot recover after SLAVE errored out in parallel execution mode. Additional error messages can be found in the MySQL error log.  
[ER\\_MTS\\_RECOVERY\\_FAILURE](#) was removed after 8.0.32.
  - Error number: [1803](#); Symbol: [ER\\_MTA\\_RECOVERY\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Cannot recover after REPLICA errored out in parallel execution mode. Additional error messages can be found in the MySQL error log.  
[ER\\_MTA\\_RECOVERY\\_FAILURE](#) was added in 8.0.33.
  - Error number: [1804](#); Symbol: [ER\\_MTS\\_RESET\\_WORKERS](#); SQLSTATE: [HY000](#)  
Message: Cannot clean up worker info tables. Additional error messages can be found in the MySQL error log.  
[ER\\_MTS\\_RESET\\_WORKERS](#) was removed after 8.0.32.
  - Error number: [1804](#); Symbol: [ER\\_MTA\\_RESET\\_WORKERS](#); SQLSTATE: [HY000](#)  
Message: Cannot clean up worker info tables. Additional error messages can be found in the MySQL error log.  
[ER\\_MTA\\_RESET\\_WORKERS](#) was added in 8.0.33.
  - Error number: [1805](#); Symbol: [ER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_CORRUPTED\\_V2](#); SQLSTATE: [HY000](#)

---

Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted

- Error number: 1806; Symbol: [ER\\_SLAVE\\_SILENT\\_RETRY\\_TRANSACTION](#); SQLSTATE: HY000

Message: Slave must silently retry current transaction

[ER\\_SLAVE\\_SILENT\\_RETRY\\_TRANSACTION](#) was removed after 8.0.32.

- Error number: 1806; Symbol: [ER\\_REPLICA\\_SILENT\\_RETRY\\_TRANSACTION](#); SQLSTATE: HY000

Message: Replica must silently retry current transaction

[ER\\_REPLICA\\_SILENT\\_RETRY\\_TRANSACTION](#) was added in 8.0.33.

- Error number: 1807; Symbol: [ER\\_DISCARD\\_FK\\_CHECKS\\_RUNNING](#); SQLSTATE: HY000

Message: There is a foreign key check running on table '%s'. Cannot discard the table.

- Error number: 1808; Symbol: [ER\\_TABLE\\_SCHEMA\\_MISMATCH](#); SQLSTATE: HY000

Message: Schema mismatch (%s)

- Error number: 1809; Symbol: [ER\\_TABLE\\_IN\\_SYSTEM\\_TABLESPACE](#); SQLSTATE: HY000

Message: Table '%s' in system tablespace

- Error number: 1810; Symbol: [ER\\_IO\\_READ\\_ERROR](#); SQLSTATE: HY000

Message: IO Read error: (%lu, %s) %s

- Error number: 1811; Symbol: [ER\\_IO\\_WRITE\\_ERROR](#); SQLSTATE: HY000

Message: IO Write error: (%lu, %s) %s

- Error number: 1812; Symbol: [ER\\_TABLESPACE\\_MISSING](#); SQLSTATE: HY000

Message: Tablespace is missing for table %s.

- Error number: 1813; Symbol: [ER\\_TABLESPACE\\_EXISTS](#); SQLSTATE: HY000

Message: Tablespace '%s' exists.

- Error number: 1814; Symbol: [ER\\_TABLESPACE\\_DISCARDED](#); SQLSTATE: HY000

Message: Tablespace has been discarded for table '%s'

- Error number: 1815; Symbol: [ER\\_INTERNAL\\_ERROR](#); SQLSTATE: HY000

Message: Internal error: %s

- Error number: 1816; Symbol: [ER\\_INNODB\\_IMPORT\\_ERROR](#); SQLSTATE: HY000

Message: ALTER TABLE %s IMPORT TABLESPACE failed with error %lu : '%s'

- Error number: 1817; Symbol: [ER\\_INNODB\\_INDEX\\_CORRUPT](#); SQLSTATE: HY000

Message: Index corrupt: %s

- Error number: 1818; Symbol: [ER\\_INVALID\\_YEAR\\_COLUMN\\_LENGTH](#); SQLSTATE: HY000

---

Message: Invalid display width. Use YEAR instead.

- Error number: 1819; Symbol: `ER_NOT_VALID_PASSWORD`; SQLSTATE: `HY000`

Message: Your password does not satisfy the current policy requirements

- Error number: 1820; Symbol: `ER_MUST_CHANGE_PASSWORD`; SQLSTATE: `HY000`

Message: You must reset your password using ALTER USER statement before executing this statement.

- Error number: 1821; Symbol: `ER_FK_NO_INDEX_CHILD`; SQLSTATE: `HY000`

Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the foreign table '%s'

- Error number: 1822; Symbol: `ER_FK_NO_INDEX_PARENT`; SQLSTATE: `HY000`

Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the referenced table '%s'

- Error number: 1823; Symbol: `ER_FK_FAIL_ADD_SYSTEM`; SQLSTATE: `HY000`

Message: Failed to add the foreign key constraint '%s' to system tables

- Error number: 1824; Symbol: `ER_FK_CANNOT_OPEN_PARENT`; SQLSTATE: `HY000`

Message: Failed to open the referenced table '%s'

- Error number: 1825; Symbol: `ER_FK_INCORRECT_OPTION`; SQLSTATE: `HY000`

Message: Failed to add the foreign key constraint on table '%s'. Incorrect options in FOREIGN KEY constraint '%s'

- Error number: 1826; Symbol: `ER_FK_DUP_NAME`; SQLSTATE: `HY000`

Message: Duplicate foreign key constraint name '%s'

- Error number: 1827; Symbol: `ER_PASSWORD_FORMAT`; SQLSTATE: `HY000`

Message: The password hash doesn't have the expected format.

- Error number: 1828; Symbol: `ER_FK_COLUMN_CANNOT_DROP`; SQLSTATE: `HY000`

Message: Cannot drop column '%s': needed in a foreign key constraint '%s'

- Error number: 1829; Symbol: `ER_FK_COLUMN_CANNOT_DROP_CHILD`; SQLSTATE: `HY000`

Message: Cannot drop column '%s': needed in a foreign key constraint '%s' of table '%s'

- Error number: 1830; Symbol: `ER_FK_COLUMN_NOT_NULL`; SQLSTATE: `HY000`

Message: Column '%s' cannot be NOT NULL: needed in a foreign key constraint '%s' SET NULL

- Error number: 1831; Symbol: `ER_DUP_INDEX`; SQLSTATE: `HY000`

Message: Duplicate index '%s' defined on the table '%s.%s'. This is deprecated and will be disallowed in a future release.

- 
- Error number: [1832](#); Symbol: [ER\\_FK\\_COLUMN\\_CANNOT\\_CHANGE](#); SQLSTATE: [HY000](#)  
Message: Cannot change column '%s': used in a foreign key constraint '%s'
  - Error number: [1833](#); Symbol: [ER\\_FK\\_COLUMN\\_CANNOT\\_CHANGE\\_CHILD](#); SQLSTATE: [HY000](#)  
Message: Cannot change column '%s': used in a foreign key constraint '%s' of table '%s'
  - Error number: [1835](#); Symbol: [ER\\_MALFORMED\\_PACKET](#); SQLSTATE: [HY000](#)  
Message: Malformed communication packet.
  - Error number: [1836](#); Symbol: [ER\\_READ\\_ONLY\\_MODE](#); SQLSTATE: [HY000](#)  
Message: Running in read-only mode
  - Error number: [1837](#); Symbol: [ER\\_GTID\\_NEXT\\_TYPE\\_UNDEFINED\\_GROUP](#); SQLSTATE: [HY000](#)  
Message: When @@SESSION.GTID\_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID\_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID\_NEXT is '%s'.  
[ER\\_GTID\\_NEXT\\_TYPE\\_UNDEFINED\\_GROUP](#) was removed after 8.0.4.
  - Error number: [1837](#); Symbol: [ER\\_GTID\\_NEXT\\_TYPE\\_UNDEFINED\\_GTID](#); SQLSTATE: [HY000](#)  
Message: When @@SESSION.GTID\_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID\_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID\_NEXT is '%s'.  
[ER\\_GTID\\_NEXT\\_TYPE\\_UNDEFINED\\_GTID](#) was added in 8.0.11.
  - Error number: [1838](#); Symbol: [ER\\_VARIABLE\\_NOT\\_SETTABLE\\_IN\\_SP](#); SQLSTATE: [HY000](#)  
Message: The system variable %s cannot be set in stored procedures.
  - Error number: [1840](#); Symbol: [ER\\_CANT\\_SET\\_GTID\\_PURGED\\_WHEN\\_GTID\\_EXECUTED\\_IS\\_NOT\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: @@GLOBAL.GTID\_PURGED can only be set when @@GLOBAL.GTID\_EXECUTED is empty.
  - Error number: [1841](#); Symbol: [ER\\_CANT\\_SET\\_GTID\\_PURGED\\_WHEN\\_OWNED\\_GTIDS\\_IS\\_NOT\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: @@GLOBAL.GTID\_PURGED can only be set when there are no ongoing transactions (not even in other clients).
  - Error number: [1842](#); Symbol: [ER\\_GTID\\_PURGED\\_WAS\\_CHANGED](#); SQLSTATE: [HY000](#)  
Message: @@GLOBAL.GTID\_PURGED was changed from '%s' to '%s'.
  - Error number: [1843](#); Symbol: [ER\\_GTID\\_EXECUTED\\_WAS\\_CHANGED](#); SQLSTATE: [HY000](#)  
Message: @@GLOBAL.GTID\_EXECUTED was changed from '%s' to '%s'.
  - Error number: [1844](#); Symbol: [ER\\_BINLOG\\_STMT\\_MODE\\_AND\\_NO\\_REPL\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: Cannot execute statement: impossible to write to binary log since BINLOG\_FORMAT = STATEMENT, and both replicated and non replicated tables are written to.

- 
- Error number: 1845; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTED; SQLSTATE: 0A000  
Message: %s is not supported for this operation. Try %s.
  - Error number: 1846; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTED\_REASON; SQLSTATE: 0A000  
Message: %s is not supported. Reason: %s. Try %s.
  - Error number: 1847; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTED\_REASON\_COPY; SQLSTATE: HY000  
Message: COPY algorithm requires a lock
  - Error number: 1848; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTED\_REASON\_PARTITION; SQLSTATE: HY000  
Message: Partition specific operations do not yet support LOCK/ALGORITHM
  - Error number: 1849; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTED\_REASON\_FK\_RENAME; SQLSTATE: HY000  
Message: Columns participating in a foreign key are renamed
  - Error number: 1850; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTED\_REASON\_COLUMN\_TYPE; SQLSTATE: HY000  
Message: Cannot change column type INPLACE
  - Error number: 1851; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTED\_REASON\_FK\_CHECK; SQLSTATE: HY000  
Message: Adding foreign keys needs foreign\_key\_checks=OFF
  - Error number: 1853; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTED\_REASON\_NOPK; SQLSTATE: HY000  
Message: Dropping a primary key is not allowed without also adding a new primary key
  - Error number: 1854; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTED\_REASON\_AUTOINC; SQLSTATE: HY000  
Message: Adding an auto-increment column requires a lock
  - Error number: 1855; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTED\_REASON\_HIDDEN\_FTS; SQLSTATE: HY000  
Message: Cannot replace hidden FTS\_DOC\_ID with a user-visible one
  - Error number: 1856; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTED\_REASON\_CHANGE\_FTS; SQLSTATE: HY000  
Message: Cannot drop or rename FTS\_DOC\_ID
  - Error number: 1857; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTED\_REASON\_FTS; SQLSTATE: HY000  
Message: Fulltext index creation requires a lock
  - Error number: 1858; Symbol: ER\_SQL\_SLAVE\_SKIP\_COUNTER\_NOT\_SETTABLE\_IN\_GTID\_MODE; SQLSTATE: HY000

---

Message: sql\_slave\_skip\_counter can not be set when the server is running with @@GLOBAL.GTID\_MODE = ON. Instead, for each transaction that you want to skip, generate an empty transaction with the same GTID as the transaction

[ER\\_SQL\\_SLAVE\\_SKIP\\_COUNTER\\_NOT\\_SETTABLE\\_IN\\_GTID\\_MODE](#) was removed after 8.0.22.

- Error number: [1859](#); Symbol: [ER\\_DUP\\_UNKNOWN\\_IN\\_INDEX](#); SQLSTATE: [23000](#)

Message: Duplicate entry for key '%s'

- Error number: [1860](#); Symbol: [ER\\_IDENT\\_CAUSES\\_TOO\\_LONG\\_PATH](#); SQLSTATE: [HY000](#)

Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.

- Error number: [1861](#); Symbol: [ER\\_ALTER\\_OPERATION\\_NOT\\_SUPPORTED\\_REASON\\_NOT\\_NULL](#); SQLSTATE: [HY000](#)

Message: cannot silently convert NULL values, as required in this SQL\_MODE

- Error number: [1862](#); Symbol: [ER\\_MUST\\_CHANGE\\_PASSWORD\\_LOGIN](#); SQLSTATE: [HY000](#)

Message: Your password has expired. To log in you must change it using a client that supports expired passwords.

- Error number: [1863](#); Symbol: [ER\\_ROW\\_IN\\_WRONG\\_PARTITION](#); SQLSTATE: [HY000](#)

Message: Found a row in wrong partition %s

- Error number: [1864](#); Symbol: [ER\\_MTS\\_EVENT\\_BIGGER\\_PENDING\\_JOBS\\_SIZE\\_MAX](#); SQLSTATE: [HY000](#)

Message: Cannot schedule event %s, relay-log name %s, position %s to Worker thread because its size %lu exceeds %lu of replica\_pending\_jobs\_size\_max.

[ER\\_MTS\\_EVENT\\_BIGGER\\_PENDING\\_JOBS\\_SIZE\\_MAX](#) was removed after 8.0.32.

- Error number: [1864](#); Symbol: [ER\\_MTA\\_EVENT\\_BIGGER\\_PENDING\\_JOBS\\_SIZE\\_MAX](#); SQLSTATE: [HY000](#)

Message: Cannot schedule event %s, relay-log name %s, position %s to Worker thread because its size %lu exceeds %lu of replica\_pending\_jobs\_size\_max.

[ER\\_MTA\\_EVENT\\_BIGGER\\_PENDING\\_JOBS\\_SIZE\\_MAX](#) was added in 8.0.33.

- Error number: [1866](#); Symbol: [ER\\_BINLOG\\_LOGICAL\\_CORRUPTION](#); SQLSTATE: [HY000](#)

Message: The binary log file '%s' is logically corrupted: %s

- Error number: [1867](#); Symbol: [ER\\_WARN\\_PURGE\\_LOG\\_IN\\_USE](#); SQLSTATE: [HY000](#)

Message: file %s was not purged because it was being read by %d thread(s), purged only %d out of %d files.

- Error number: [1868](#); Symbol: [ER\\_WARN\\_PURGE\\_LOG\\_IS\\_ACTIVE](#); SQLSTATE: [HY000](#)

Message: file %s was not purged because it is the active log file.

- Error number: [1869](#); Symbol: [ER\\_AUTO\\_INCREMENT\\_CONFLICT](#); SQLSTATE: [HY000](#)

---

Message: Auto-increment value in UPDATE conflicts with internally generated values

- Error number: 1870; Symbol: [WARN\\_ON\\_BLOCKHOLE\\_IN\\_RBR](#); SQLSTATE: HY000

Message: Row events are not logged for %s statements that modify BLACKHOLE tables in row format.  
Table(s): '%s'

- Error number: 1871; Symbol: [ER\\_SLAVE\\_MI\\_INIT\\_REPOSITORY](#); SQLSTATE: HY000

Message: Slave failed to initialize master info structure from the repository

[ER\\_SLAVE\\_MI\\_INIT\\_REPOSITORY](#) was removed after 8.0.32.

- Error number: 1871; Symbol: [ER\\_REPLICA\\_CM\\_INIT\\_REPOSITORY](#); SQLSTATE: HY000

Message: Replica failed to initialize connection metadata structure from the repository

[ER\\_REPLICA\\_CM\\_INIT\\_REPOSITORY](#) was added in 8.0.33.

- Error number: 1872; Symbol: [ER\\_SLAVE\\_RLI\\_INIT\\_REPOSITORY](#); SQLSTATE: HY000

Message: Slave failed to initialize relay log info structure from the repository

[ER\\_SLAVE\\_RLI\\_INIT\\_REPOSITORY](#) was removed after 8.0.32.

- Error number: 1872; Symbol: [ER\\_REPLICA\\_AM\\_INIT\\_REPOSITORY](#); SQLSTATE: HY000

Message: Replica failed to initialize applier metadata structure from the repository

[ER\\_REPLICA\\_AM\\_INIT\\_REPOSITORY](#) was added in 8.0.33.

- Error number: 1873; Symbol: [ER\\_ACCESS\\_DENIED\\_CHANGE\\_USER\\_ERROR](#); SQLSTATE: 28000

Message: Access denied trying to change to user '%s'@'%s' (using password: %s). Disconnecting.

- Error number: 1874; Symbol: [ER\\_INNO\\_DB\\_READ\\_ONLY](#); SQLSTATE: HY000

Message: InnoDB is in read only mode.

- Error number: 1875; Symbol: [ER\\_STOP\\_SLAVE\\_SQL\\_THREAD\\_TIMEOUT](#); SQLSTATE: HY000

Message: STOP SLAVE command execution is incomplete: Slave SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.

[ER\\_STOP\\_SLAVE\\_SQL\\_THREAD\\_TIMEOUT](#) was removed after 8.0.32.

- Error number: 1875; Symbol: [ER\\_STOP\\_REPLICA\\_SQL\\_THREAD\\_TIMEOUT](#); SQLSTATE: HY000

Message: STOP REPLICA command execution is incomplete: Replica SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.

[ER\\_STOP\\_REPLICA\\_SQL\\_THREAD\\_TIMEOUT](#) was added in 8.0.33.

- Error number: 1876; Symbol: [ER\\_STOP\\_SLAVE\\_IO\\_THREAD\\_TIMEOUT](#); SQLSTATE: HY000

Message: STOP SLAVE command execution is incomplete: Slave IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.

[ER\\_STOP\\_SLAVE\\_IO\\_THREAD\\_TIMEOUT](#) was removed after 8.0.32.



- 
- Error number: [1876](#); Symbol: [ER\\_STOP\\_REPLICA\\_IO\\_THREAD\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
Message: STOP REPLICA command execution is incomplete: Replica IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.  
[ER\\_STOP\\_REPLICA\\_IO\\_THREAD\\_TIMEOUT](#) was added in 8.0.33.
  - Error number: [1877](#); Symbol: [ER\\_TABLE\\_CORRUPT](#); SQLSTATE: [HY000](#)  
Message: Operation cannot be performed. The table '%s.%s' is missing, corrupt or contains bad data.
  - Error number: [1878](#); Symbol: [ER\\_TEMP\\_FILE\\_WRITE\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Temporary file write failure.
  - Error number: [1879](#); Symbol: [ER\\_INNODB\\_FT\\_AUX\\_NOT\\_HEX\\_ID](#); SQLSTATE: [HY000](#)  
Message: Upgrade index name failed, please use create index(alter table) algorithm copy to rebuild index.
  - Error number: [1880](#); Symbol: [ER\\_OLD\\_TEMPORALS\\_UPGRADED](#); SQLSTATE: [HY000](#)  
Message: TIME/TIMESTAMP/DATETIME columns of old format have been upgraded to the new format.
  - Error number: [1881](#); Symbol: [ER\\_INNODB\\_FORCED\\_RECOVERY](#); SQLSTATE: [HY000](#)  
Message: Operation not allowed when innodb\_force\_recovery > 0.
  - Error number: [1882](#); Symbol: [ER\\_AES\\_INVALID\\_IV](#); SQLSTATE: [HY000](#)  
Message: The initialization vector supplied to %s is too short. Must be at least %d bytes long
  - Error number: [1883](#); Symbol: [ER\\_PLUGIN\\_CANNOT\\_BE\\_UNINSTALLED](#); SQLSTATE: [HY000](#)  
Message: Plugin '%s' cannot be uninstalled now. %s
  - Error number: [1884](#); Symbol: [ER\\_GTID\\_UNSAFE\\_BINLOG\\_SPLITTABLE\\_STATEMENT\\_AND\\_GTID\\_GROUP](#); SQLSTATE: [HY000](#)  
Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID\_NEXT == 'UUID:NUMBER'.  
[ER\\_GTID\\_UNSAFE\\_BINLOG\\_SPLITTABLE\\_STATEMENT\\_AND\\_GTID\\_GROUP](#) was removed after 8.0.4.
  - Error number: [1884](#); Symbol: [ER\\_GTID\\_UNSAFE\\_BINLOG\\_SPLITTABLE\\_STATEMENT\\_AND\\_ASSIGNED\\_GTID](#); SQLSTATE: [HY000](#)  
Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID\_NEXT == 'UUID:NUMBER'.  
[ER\\_GTID\\_UNSAFE\\_BINLOG\\_SPLITTABLE\\_STATEMENT\\_AND\\_ASSIGNED\\_GTID](#) was added in 8.0.11.
  - Error number: [1885](#); Symbol: [ER\\_SLAVE\\_HAS\\_MORE\\_GTIDS\\_THAN\\_MASTER](#); SQLSTATE: [HY000](#)  
Message: Slave has more GTIDs than the master has, using the master's SERVER\_UUID. This may indicate that the end of the binary log was truncated or that the last binary log file was lost, e.g., after a power or disk failure when sync\_binlog != 1. The master may or may not have rolled back transactions that were already replicated to the slave. Suggest to replicate any transactions that master has rolled

---

back from slave to master, and/or commit empty transactions on master to account for transactions that have been committed on master but are not included in GTID\_EXECUTED.

[ER\\_SLAVE\\_HAS\\_MORE\\_GTIDS\\_THAN\\_MASTER](#) was removed after 8.0.32.

- Error number: [1885](#); Symbol: [ER\\_REPLICA\\_HAS\\_MORE\\_GTIDS\\_THAN\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Replica has more GTIDs than the source has, using the source's SERVER\_UUID. This may indicate that the the last binary log file was truncated or lost, e.g., after a power failure when sync\_binlog != 1. The source may have rolled back transactions that were already replicated to the replica. Replicate any transactions that source has rolled back from replica to source, and/or commit empty transactions on source to account for transactions that have been committed on source but are not included in GTID\_EXECUTED.

[ER\\_REPLICA\\_HAS\\_MORE\\_GTIDS\\_THAN\\_SOURCE](#) was added in 8.0.33.

- Error number: [1886](#); Symbol: [ER\\_MISSING\\_KEY](#); SQLSTATE: [HY000](#)

Message: The table '%s.%s' does not have the necessary key(s) defined on it. Please check the table definition and create index(s) accordingly.

[ER\\_MISSING\\_KEY](#) was added in 8.0.4.

- Error number: [1887](#); Symbol: [WARN\\_NAMED\\_PIPE\\_ACCESS\\_EVERYONE](#); SQLSTATE: [HY000](#)

Message: Setting named\_pipe\_full\_access\_group='%s' is insecure. Consider using a Windows group with fewer members.

[WARN\\_NAMED\\_PIPE\\_ACCESS\\_EVERYONE](#) was added in 8.0.17.

- Error number: [3000](#); Symbol: [ER\\_FILE\\_CORRUPT](#); SQLSTATE: [HY000](#)

Message: File %s is corrupted

- Error number: [3001](#); Symbol: [ER\\_ERROR\\_ON\\_MASTER](#); SQLSTATE: [HY000](#)

Message: Query partially completed on the master (error on master: %d) and was aborted. There is a chance that your master is inconsistent at this point. If you are sure that your master is ok, run this query manually on the slave and then restart the slave with SET GLOBAL SQL\_REPLICA\_SKIP\_COUNTER=1; START SLAVE;. Query:'%s'

[ER\\_ERROR\\_ON\\_MASTER](#) was removed after 8.0.32.

- Error number: [3001](#); Symbol: [ER\\_ERROR\\_ON\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Query partially completed on the source (error on source: %d) and was aborted. There is a chance that your source is inconsistent at this point. If you are sure that your source is ok, run this query manually on the replica and then restart the replica with SET GLOBAL SQL\_REPLICA\_SKIP\_COUNTER=1; START REPLICA;. Query:'%s'

[ER\\_ERROR\\_ON\\_SOURCE](#) was added in 8.0.33.

- Error number: [3003](#); Symbol: [ER\\_STORAGE\\_ENGINE\\_NOT\\_LOADED](#); SQLSTATE: [HY000](#)

Message: Storage engine for table '%s'.'%s' is not loaded.

- Error number: [3004](#); Symbol: [ER\\_GET\\_STACKED\\_DA\\_WITHOUT\\_ACTIVE\\_HANDLER](#); SQLSTATE: [0Z002](#)

---

Message: GET STACKED DIAGNOSTICS when handler not active

- Error number: 3005; Symbol: [ER\\_WARN\\_LEGACY\\_SYNTAX\\_CONVERTED](#); SQLSTATE: [HY000](#)

Message: %s is no longer supported. The statement was converted to %s.

- Error number: 3006; Symbol: [ER\\_BINLOG\\_UNSAFE\\_FULLTEXT\\_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it uses a fulltext parser plugin which may not return the same value on the replica.

- Error number: 3007; Symbol: [ER\\_CANNOT\\_DISCARD\\_TEMPORARY\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot DISCARD/IMPORT tablespace associated with temporary table

- Error number: 3008; Symbol: [ER\\_FK\\_DEPTH\\_EXCEEDED](#); SQLSTATE: [HY000](#)

Message: Foreign key cascade delete/update exceeds max depth of %d.

- Error number: 3009; Symbol: [ER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_PLEASE\\_UPDATE\\_V2](#); SQLSTATE: [HY000](#)

Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

- Error number: 3010; Symbol: [ER\\_WARN\\_TRIGGER\\_DOESNT\\_HAVE\\_CREATED](#); SQLSTATE: [HY000](#)

Message: Trigger %s.%s.%s does not have CREATED attribute.

- Error number: 3011; Symbol: [ER\\_REFERENCED\\_TRG\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)

Message: Referenced trigger '%s' for the given action time and event type does not exist.

- Error number: 3012; Symbol: [ER\\_EXPLAIN\\_NOT\\_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: EXPLAIN FOR CONNECTION command is supported only for SELECT/UPDATE/INSERT/DELETE/REPLACE

- Error number: 3013; Symbol: [ER\\_INVALID\\_FIELD\\_SIZE](#); SQLSTATE: [HY000](#)

Message: Invalid size for column '%s'.

- Error number: 3014; Symbol: [ER\\_MISSING\\_HA\\_CREATE\\_OPTION](#); SQLSTATE: [HY000](#)

Message: Table storage engine '%s' found required create option missing

- Error number: 3015; Symbol: [ER\\_ENGINE\\_OUT\\_OF\\_MEMORY](#); SQLSTATE: [HY000](#)

Message: Out of memory in storage engine '%s'.

- Error number: 3016; Symbol: [ER\\_PASSWORD\\_EXPIRE\\_ANONYMOUS\\_USER](#); SQLSTATE: [HY000](#)

Message: The password for anonymous user cannot be expired.

- Error number: 3017; Symbol: [ER\\_SLAVE\\_SQL\\_THREAD\\_MUST\\_STOP](#); SQLSTATE: [HY000](#)

Message: This operation cannot be performed with a running slave sql thread; run STOP SLAVE SQL\_THREAD first

---

`ER_SLAVE_SQL_THREAD_MUST_STOP` was removed after 8.0.32.

- Error number: 3017; Symbol: `ER_REPLICA_SQL_THREAD_MUST_STOP`; SQLSTATE: `HY000`

Message: This operation cannot be performed with a running replica sql thread; run STOP REPLICA SQL\_THREAD first

`ER_REPLICA_SQL_THREAD_MUST_STOP` was added in 8.0.33.

- Error number: 3018; Symbol: `ER_NO_FT_MATERIALIZED_SUBQUERY`; SQLSTATE: `HY000`

Message: Cannot create FULLTEXT index on materialized subquery

- Error number: 3019; Symbol: `ER_INNODB_UNDO_LOG_FULL`; SQLSTATE: `HY000`

Message: Undo Log error: %s

- Error number: 3020; Symbol: `ER_INVALID_ARGUMENT_FOR_LOGARITHM`; SQLSTATE: `2201E`

Message: Invalid argument for logarithm

- Error number: 3021; Symbol: `ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP`; SQLSTATE: `HY000`

Message: This operation cannot be performed with a running slave io thread; run STOP SLAVE IO\_THREAD FOR CHANNEL '%s' first.

`ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP` was removed after 8.0.32.

- Error number: 3021; Symbol: `ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP`; SQLSTATE: `HY000`

Message: This operation cannot be performed with a running replica io thread; run STOP REPLICA IO\_THREAD FOR CHANNEL '%s' first.

`ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP` was added in 8.0.33.

- Error number: 3022; Symbol: `ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO`; SQLSTATE: `HY000`

Message: This operation may not be safe when the replica has temporary tables. The tables will be kept open until the server restarts or until the tables are deleted by any replicated DROP statement. Suggest to wait until `replica_open_temp_tables = 0`.

- Error number: 3023; Symbol: `ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS`; SQLSTATE: `HY000`

Message: CHANGE MASTER TO with a MASTER\_LOG\_FILE clause but no MASTER\_LOG\_POS clause may not be safe. The old position value may not be valid for the new binary log file.

`ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS` was removed after 8.0.32.

- Error number: 3023; Symbol: `ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS`; SQLSTATE: `HY000`

Message: CHANGE REPLICATION SOURCE TO with a SOURCE\_LOG\_FILE clause but no SOURCE\_LOG\_POS clause may not be safe. The old position value may not be valid for the new binary log file.

`ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS` was added in 8.0.33.

- Error number: 3024; Symbol: `ER_QUERY_TIMEOUT`; SQLSTATE: `HY000`

Message: Query execution was interrupted, maximum statement execution time exceeded

- 
- Error number: [3025](#); Symbol: [ER\\_NON\\_RO\\_SELECT\\_DISABLE\\_TIMER](#); SQLSTATE: [HY000](#)

Message: Select is not a read only statement, disabling timer

- Error number: [3026](#); Symbol: [ER\\_DUP\\_LIST\\_ENTRY](#); SQLSTATE: [HY000](#)

Message: Duplicate entry '%s'.

- Error number: [3028](#); Symbol: [ER\\_AGGREGATE\\_ORDER\\_FOR\\_UNION](#); SQLSTATE: [HY000](#)

Message: Expression #%u of ORDER BY contains aggregate function and applies to a UNION, EXCEPT or INTERSECT

- Error number: [3029](#); Symbol: [ER\\_AGGREGATE\\_ORDER\\_NON\\_AGG\\_QUERY](#); SQLSTATE: [HY000](#)

Message: Expression #%u of ORDER BY contains aggregate function and applies to the result of a non-aggregated query

- Error number: [3030](#); Symbol: [ER\\_SLAVE\\_WORKER\\_STOPPED\\_PREVIOUS\\_THD\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Slave worker has stopped after at least one previous worker encountered an error when replica-preserve-commit-order was enabled. To preserve commit order, the last transaction executed by this thread has not been committed. When restarting the slave after fixing any failed threads, you should fix this worker as well.

[ER\\_SLAVE\\_WORKER\\_STOPPED\\_PREVIOUS\\_THD\\_ERROR](#) was removed after 8.0.32.

- Error number: [3030](#); Symbol: [ER\\_REPLICA\\_WORKER\\_STOPPED\\_PREVIOUS\\_THD\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Replica worker has stopped after at least one previous worker encountered an error when replica-preserve-commit-order was enabled. To preserve commit order, the last transaction executed by this thread has not been committed. When restarting the replica after fixing any failed threads, you should fix this worker as well.

[ER\\_REPLICA\\_WORKER\\_STOPPED\\_PREVIOUS\\_THD\\_ERROR](#) was added in 8.0.33.

- Error number: [3031](#); Symbol: [ER\\_DONT\\_SUPPORT\\_SLAVE\\_PRESERVE\\_COMMIT\\_ORDER](#); SQLSTATE: [HY000](#)

Message: slave\_preserve\_commit\_order is not supported %s.

[ER\\_DONT\\_SUPPORT\\_SLAVE\\_PRESERVE\\_COMMIT\\_ORDER](#) was removed after 8.0.25.

- Error number: [3031](#); Symbol: [ER\\_DONT\\_SUPPORT\\_REPLICA\\_PRESERVE\\_COMMIT\\_ORDER](#); SQLSTATE: [HY000](#)

Message: replica\_preserve\_commit\_order is not supported %s.

[ER\\_DONT\\_SUPPORT\\_REPLICA\\_PRESERVE\\_COMMIT\\_ORDER](#) was added in 8.0.26.

- Error number: [3032](#); Symbol: [ER\\_SERVER\\_OFFLINE\\_MODE](#); SQLSTATE: [HY000](#)

Message: The server is currently in offline mode

- 
- Error number: 3033; Symbol: `ER_GIS_DIFFERENT_SRIDS`; SQLSTATE: `HY000`  
Message: Binary geometry function %s given two geometries of different srids: %u and %u, which should have been identical.  
Geometry values passed as arguments to spatial functions must have the same SRID value.
  - Error number: 3034; Symbol: `ER_GIS_UNSUPPORTED_ARGUMENT`; SQLSTATE: `HY000`  
Message: Calling geometry function %s with unsupported types of arguments.  
A spatial function was called with a combination of argument types that the function does not support.
  - Error number: 3035; Symbol: `ER_GIS_UNKNOWN_ERROR`; SQLSTATE: `HY000`  
Message: Unknown GIS error occurred in function %s.
  - Error number: 3036; Symbol: `ER_GIS_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`  
Message: Unknown exception caught in GIS function %s.
  - Error number: 3037; Symbol: `ER_GIS_INVALID_DATA`; SQLSTATE: `22023`  
Message: Invalid GIS data provided to function %s.  
A spatial function was called with an argument not recognized as a valid geometry value.
  - Error number: 3038; Symbol: `ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION`; SQLSTATE: `HY000`  
Message: The geometry has no data in function %s.
  - Error number: 3039; Symbol: `ER_BOOST_GEOMETRY_CENTROID_EXCEPTION`; SQLSTATE: `HY000`  
Message: Unable to calculate centroid because geometry is empty in function %s.
  - Error number: 3040; Symbol: `ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION`; SQLSTATE: `HY000`  
Message: Geometry overlay calculation error: geometry data is invalid in function %s.
  - Error number: 3041; Symbol: `ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION`; SQLSTATE: `HY000`  
Message: Geometry turn info calculation error: geometry data is invalid in function %s.
  - Error number: 3042; Symbol: `ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION`; SQLSTATE: `HY000`  
Message: Analysis procedures of intersection points interrupted unexpectedly in function %s.
  - Error number: 3043; Symbol: `ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`  
Message: Unknown exception thrown in function %s.
  - Error number: 3044; Symbol: `ER_STD_BAD_ALLOC_ERROR`; SQLSTATE: `HY000`  
Message: Memory allocation error: %s in function %s.
  - Error number: 3045; Symbol: `ER_STD_DOMAIN_ERROR`; SQLSTATE: `HY000`  
Message: Domain error: %s in function %s.

- 
- Error number: 3046; Symbol: `ER_STD_LENGTH_ERROR`; SQLSTATE: `HY000`  
Message: Length error: %s in function %s.
  - Error number: 3047; Symbol: `ER_STD_INVALID_ARGUMENT`; SQLSTATE: `HY000`  
Message: Invalid argument error: %s in function %s.
  - Error number: 3048; Symbol: `ER_STD_OUT_OF_RANGE_ERROR`; SQLSTATE: `HY000`  
Message: Out of range error: %s in function %s.
  - Error number: 3049; Symbol: `ER_STD_OVERFLOW_ERROR`; SQLSTATE: `HY000`  
Message: Overflow error: %s in function %s.
  - Error number: 3050; Symbol: `ER_STD_RANGE_ERROR`; SQLSTATE: `HY000`  
Message: Range error: %s in function %s.
  - Error number: 3051; Symbol: `ER_STD_UNDERFLOW_ERROR`; SQLSTATE: `HY000`  
Message: Underflow error: %s in function %s.
  - Error number: 3052; Symbol: `ER_STD_LOGIC_ERROR`; SQLSTATE: `HY000`  
Message: Logic error: %s in function %s.
  - Error number: 3053; Symbol: `ER_STD_RUNTIME_ERROR`; SQLSTATE: `HY000`  
Message: Runtime error: %s in function %s.
  - Error number: 3054; Symbol: `ER_STD_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`  
Message: Unknown exception: %s in function %s.
  - Error number: 3055; Symbol: `ER_GIS_DATA_WRONG_ENDIANESS`; SQLSTATE: `HY000`  
Message: Geometry byte string must be little endian.
  - Error number: 3056; Symbol: `ER_CHANGE_MASTER_PASSWORD_LENGTH`; SQLSTATE: `HY000`  
Message: The password provided for the replication user exceeds the maximum length of 32 characters  
`ER_CHANGE_MASTER_PASSWORD_LENGTH` was removed after 8.0.32.
  - Error number: 3056; Symbol: `ER_CHANGE_SOURCE_PASSWORD_LENGTH`; SQLSTATE: `HY000`  
Message: The password provided for the replication user exceeds the maximum length of 32 characters  
`ER_CHANGE_SOURCE_PASSWORD_LENGTH` was added in 8.0.33.
  - Error number: 3057; Symbol: `ER_USER_LOCK_WRONG_NAME`; SQLSTATE: `42000`  
Message: Incorrect user-level lock name '%s'. The name is empty, NULL, or can not be expressed in the current character-set.
  - Error number: 3058; Symbol: `ER_USER_LOCK_DEADLOCK`; SQLSTATE: `HY000`  
Message: Deadlock found when trying to get user-level lock; try rolling back transaction/releasing locks and restarting lock acquisition.

---

This error is returned when the metadata locking subsystem detects a deadlock for an attempt to acquire a named lock with `GET_LOCK`.

- Error number: 3059; Symbol: `ER_REPLACE_INACCESSIBLE_ROWS`; SQLSTATE: `HY000`  
Message: REPLACE cannot be executed as it requires deleting rows that are not in the view
- Error number: 3060; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS`; SQLSTATE: `HY000`  
Message: Do not support online operation on table with GIS index
- Error number: 3061; Symbol: `ER_ILLEGAL_USER_VAR`; SQLSTATE: `42000`  
Message: User variable name '%s' is illegal
- Error number: 3062; Symbol: `ER_GTID_MODE_OFF`; SQLSTATE: `HY000`  
Message: Cannot %s when GTID\_MODE = OFF.
- Error number: 3064; Symbol: `ER_INCORRECT_TYPE`; SQLSTATE: `HY000`  
Message: Incorrect type for argument %s in function %s.
- Error number: 3065; Symbol: `ER_FIELD_IN_ORDER_NOT_SELECT`; SQLSTATE: `HY000`  
Message: Expression #%u of ORDER BY clause is not in SELECT list, references column '%s' which is not in SELECT list; this is incompatible with %s
- Error number: 3066; Symbol: `ERAggregate_IN_ORDER_NOT_SELECT`; SQLSTATE: `HY000`  
Message: Expression #%u of ORDER BY clause is not in SELECT list, contains aggregate function; this is incompatible with %s
- Error number: 3067; Symbol: `ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN`; SQLSTATE: `HY000`  
Message: Supplied filter list contains a value which is not in the required format 'db\_pattern.table\_pattern'
- Error number: 3068; Symbol: `ER_NET_OK_PACKET_TOO_LARGE`; SQLSTATE: `08S01`  
Message: OK packet too large
- Error number: 3069; Symbol: `ER_INVALID_JSON_DATA`; SQLSTATE: `HY000`  
Message: Invalid JSON data provided to function %s: %s
- Error number: 3070; Symbol: `ER_INVALID_GEOJSON_MISSING_MEMBER`; SQLSTATE: `HY000`  
Message: Invalid GeoJSON data provided to function %s: Missing required member '%s'
- Error number: 3071; Symbol: `ER_INVALID_GEOJSON_WRONG_TYPE`; SQLSTATE: `HY000`  
Message: Invalid GeoJSON data provided to function %s: Member '%s' must be of type '%s'
- Error number: 3072; Symbol: `ER_INVALID_GEOJSON_UNSPECIFIED`; SQLSTATE: `HY000`  
Message: Invalid GeoJSON data provided to function %s



- 
- Error number: [3073](#); Symbol: [ER\\_DIMENSION\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)  
Message: Unsupported number of coordinate dimensions in function %s: Found %u, expected %u
  - Error number: [3074](#); Symbol: [ER\\_SLAVE\\_CHANNEL\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: Slave channel '%s' does not exist.  
[ER\\_SLAVE\\_CHANNEL\\_DOES\\_NOT\\_EXIST](#) was removed after 8.0.32.
  - Error number: [3074](#); Symbol: [ER\\_REPLICA\\_CHANNEL\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: Replica channel '%s' does not exist.  
[ER\\_REPLICA\\_CHANNEL\\_DOES\\_NOT\\_EXIST](#) was added in 8.0.33.
  - Error number: [3076](#); Symbol: [ER\\_SLAVE\\_CHANNEL\\_NAME\\_INVALID\\_OR\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
Message: Couldn't create channel: Channel name is either invalid or too long.  
[ER\\_SLAVE\\_CHANNEL\\_NAME\\_INVALID\\_OR\\_TOO\\_LONG](#) was removed after 8.0.32.
  - Error number: [3076](#); Symbol: [ER\\_REPLICA\\_CHANNEL\\_NAME\\_INVALID\\_OR\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
Message: Couldn't create channel: Channel name is either invalid or too long.  
[ER\\_REPLICA\\_CHANNEL\\_NAME\\_INVALID\\_OR\\_TOO\\_LONG](#) was added in 8.0.33.
  - Error number: [3077](#); Symbol: [ER\\_SLAVE\\_NEW\\_CHANNEL\\_WRONG\\_REPOSITORY](#); SQLSTATE: [HY000](#)  
Message: To have multiple channels, repository cannot be of type FILE; Please check the repository configuration and convert them to TABLE.  
[ER\\_SLAVE\\_NEW\\_CHANNEL\\_WRONG\\_REPOSITORY](#) was removed after 8.0.32.
  - Error number: [3077](#); Symbol: [ER\\_REPLICA\\_NEW\\_CHANNEL\\_WRONG\\_REPOSITORY](#); SQLSTATE: [HY000](#)  
Message: To have multiple channels, repository cannot be of type FILE; Please check the repository configuration and convert them to TABLE.  
[ER\\_REPLICA\\_NEW\\_CHANNEL\\_WRONG\\_REPOSITORY](#) was added in 8.0.33.
  - Error number: [3079](#); Symbol: [ER\\_SLAVE\\_MULTIPLE\\_CHANNELS\\_CMD](#); SQLSTATE: [HY000](#)  
Message: Multiple channels exist on the slave. Please provide channel name as an argument.  
[ER\\_SLAVE\\_MULTIPLE\\_CHANNELS\\_CMD](#) was removed after 8.0.32.
  - Error number: [3079](#); Symbol: [ER\\_REPLICA\\_MULTIPLE\\_CHANNELS\\_CMD](#); SQLSTATE: [HY000](#)  
Message: Multiple channels exist on the replica. Please provide channel name as an argument.  
[ER\\_REPLICA\\_MULTIPLE\\_CHANNELS\\_CMD](#) was added in 8.0.33.
  - Error number: [3080](#); Symbol: [ER\\_SLAVE\\_MAX\\_CHANNELS\\_EXCEEDED](#); SQLSTATE: [HY000](#)  
Message: Maximum number of replication channels allowed exceeded.

---

`ER_SLAVE_MAX_CHANNELS_EXCEEDED` was removed after 8.0.32.

- Error number: 3080; Symbol: `ER_REPLICA_MAX_CHANNELS_EXCEEDED`; SQLSTATE: `HY000`

Message: Maximum number of replication channels allowed exceeded.

`ER_REPLICA_MAX_CHANNELS_EXCEEDED` was added in 8.0.33.

- Error number: 3081; Symbol: `ER_SLAVE_CHANNEL_MUST_STOP`; SQLSTATE: `HY000`

Message: This operation cannot be performed with running replication threads; run STOP SLAVE FOR CHANNEL '%s' first

`ER_SLAVE_CHANNEL_MUST_STOP` was removed after 8.0.32.

- Error number: 3081; Symbol: `ER_REPLICA_CHANNEL_MUST_STOP`; SQLSTATE: `HY000`

Message: This operation cannot be performed with running replication threads; run STOP REPLICA FOR CHANNEL '%s' first

`ER_REPLICA_CHANNEL_MUST_STOP` was added in 8.0.33.

- Error number: 3082; Symbol: `ER_SLAVE_CHANNEL_NOT_RUNNING`; SQLSTATE: `HY000`

Message: This operation requires running replication threads; configure slave and run START SLAVE FOR CHANNEL '%s'

`ER_SLAVE_CHANNEL_NOT_RUNNING` was removed after 8.0.32.

- Error number: 3082; Symbol: `ER_REPLICA_CHANNEL_NOT_RUNNING`; SQLSTATE: `HY000`

Message: This operation requires running replication threads; configure replica and run START REPLICA FOR CHANNEL '%s'

`ER_REPLICA_CHANNEL_NOT_RUNNING` was added in 8.0.33.

- Error number: 3083; Symbol: `ER_SLAVE_CHANNEL_WAS_RUNNING`; SQLSTATE: `HY000`

Message: Replication thread(s) for channel '%s' are already running.

`ER_SLAVE_CHANNEL_WAS_RUNNING` was removed after 8.0.32.

- Error number: 3083; Symbol: `ER_REPLICA_CHANNEL_WAS_RUNNING`; SQLSTATE: `HY000`

Message: Replication thread(s) for channel '%s' are already running.

`ER_REPLICA_CHANNEL_WAS_RUNNING` was added in 8.0.33.

- Error number: 3084; Symbol: `ER_SLAVE_CHANNEL_WAS_NOT_RUNNING`; SQLSTATE: `HY000`

Message: Replication thread(s) for channel '%s' are already stopped.

`ER_SLAVE_CHANNEL_WAS_NOT_RUNNING` was removed after 8.0.32.

- Error number: 3084; Symbol: `ER_REPLICA_CHANNEL_WAS_NOT_RUNNING`; SQLSTATE: `HY000`

Message: Replication thread(s) for channel '%s' are already stopped.

`ER_REPLICA_CHANNEL_WAS_NOT_RUNNING` was added in 8.0.33.

- 
- Error number: 3085; Symbol: `ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP`; SQLSTATE: HY000  
Message: This operation cannot be performed with a running slave sql thread; run STOP SLAVE SQL\_THREAD FOR CHANNEL '%s' first.  
`ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP` was removed after 8.0.32.
  - Error number: 3085; Symbol: `ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP`; SQLSTATE: HY000  
Message: This operation cannot be performed with a running replica sql thread; run STOP REPLICA SQL\_THREAD FOR CHANNEL '%s' first.  
`ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP` was added in 8.0.33.
  - Error number: 3086; Symbol: `ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER`; SQLSTATE: HY000  
Message: When sql\_replica\_skip\_counter > 0, it is not allowed to start more than one SQL thread by using 'START SLAVE [SQL\_THREAD]'. Value of sql\_replica\_skip\_counter can only be used by one SQL thread at a time. Please use 'START SLAVE [SQL\_THREAD] FOR CHANNEL' to start the SQL thread which will use the value of sql\_replica\_skip\_counter.  
`ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER` was removed after 8.0.32.
  - Error number: 3086; Symbol: `ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER`; SQLSTATE: HY000  
Message: When sql\_replica\_skip\_counter > 0, it is not allowed to start more than one SQL thread by using 'START REPLICA [SQL\_THREAD]'. Value of sql\_replica\_skip\_counter can only be used by one SQL thread at a time. Please use 'START REPLICA [SQL\_THREAD] FOR CHANNEL' to start the SQL thread which will use the value of sql\_replica\_skip\_counter.  
`ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER` was added in 8.0.33.
  - Error number: 3087; Symbol: `ER_WRONG_FIELD_WITH_GROUP_V2`; SQLSTATE: HY000  
Message: Expression #%u of %s is not in GROUP BY clause and contains nonaggregated column '%s' which is not functionally dependent on columns in GROUP BY clause; this is incompatible with sql\_mode=only\_full\_group\_by
  - Error number: 3088; Symbol: `ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2`; SQLSTATE: HY000  
Message: In aggregated query without GROUP BY, expression #%u of %s contains nonaggregated column '%s'; this is incompatible with sql\_mode=only\_full\_group\_by
  - Error number: 3089; Symbol: `ER_WARN_DEPRECATED_SYSVAR_UPDATE`; SQLSTATE: HY000  
Message: Updating '%s' is deprecated. It will be made read-only in a future release.
  - Error number: 3090; Symbol: `ER_WARN_DEPRECATED_SQLMODE`; SQLSTATE: HY000  
Message: Changing sql mode '%s' is deprecated. It will be removed in a future release.
  - Error number: 3091; Symbol: `ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID`; SQLSTATE: HY000  
Message: DROP DATABASE failed; some tables may have been dropped but the database directory remains. The GTID has not been added to GTID\_EXECUTED and the statement was not written to the binary log. Fix this as follows: (1) remove all files from the database directory %s; (2) SET GTID\_NEXT='%s'; (3) DROP DATABASE '%s'.

- 
- Error number: [3092](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_CONFIGURATION](#); SQLSTATE: [HY000](#)  
Message: The server is not configured properly to be an active member of the group. Please see more details on error log.
  - Error number: [3093](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_RUNNING](#); SQLSTATE: [HY000](#)  
Message: The START GROUP\_REPLICATION command failed since the group is already running.
  - Error number: [3094](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_APPLIER\\_INIT\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The START GROUP\_REPLICATION command failed as the applier module failed to start.
  - Error number: [3095](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_STOP\\_APPLIER\\_THREAD\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
Message: The STOP GROUP\_REPLICATION command execution is incomplete: The applier thread got the stop signal while it was busy. The applier thread will stop once the current task is complete.
  - Error number: [3096](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_COMMUNICATION\\_LAYER\\_SESSION\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The START GROUP\_REPLICATION command failed as there was an error when initializing the group communication layer.
  - Error number: [3097](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_COMMUNICATION\\_LAYER\\_JOIN\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The START GROUP\_REPLICATION command failed as there was an error when joining the communication group.
  - Error number: [3098](#); Symbol: [ER\\_BEFORE\\_DML\\_VALIDATION\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The table does not comply with the requirements by an external plugin.
  - Error number: [3099](#); Symbol: [ER\\_PREVENTS\\_VARIABLE\\_WITHOUT\\_RBR](#); SQLSTATE: [HY000](#)  
Message: Cannot change the value of variable %s without binary log format as ROW.  
[transaction\\_write\\_set\\_extraction](#) option value is set and [binlog\\_format](#) is not ROW.
  - Error number: [3100](#); Symbol: [ER\\_RUN\\_HOOK\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error on observer while running replication hook '%s'.
  - Error number: [3101](#); Symbol: [ER\\_TRANSACTION\\_ROLLBACK\\_DURING\\_COMMIT](#); SQLSTATE: [40000](#)  
Message: Plugin instructed the server to rollback the current transaction.  
  
When using Group Replication, this means that a transaction failed the group certification process, due to one or more members detecting a potential conflict, and was thus rolled back. See [Group Replication](#).
  - Error number: [3102](#); Symbol: [ER\\_GENERATED\\_COLUMN\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: [HY000](#)  
Message: Expression of generated column '%s' contains a disallowed function.
  - Error number: [3103](#); Symbol: [ER\\_UNSUPPORTED\\_ALTER\\_INPLACE\\_ON\\_VIRTUAL\\_COLUMN](#); SQLSTATE: [HY000](#)

---

Message: INPLACE ADD or DROP of virtual columns cannot be combined with other ALTER TABLE actions

- Error number: 3104; Symbol: `ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN`; SQLSTATE: `HY000`

Message: Cannot define foreign key with %s clause on a generated column.

- Error number: 3105; Symbol: `ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN`; SQLSTATE: `HY000`

Message: The value specified for generated column '%s' in table '%s' is not allowed.

- Error number: 3106; Symbol: `ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN`; SQLSTATE: `HY000`

Message: '%s' is not supported for generated columns.

- Error number: 3107; Symbol: `ER_GENERATED_COLUMN_NON_PRIOR`; SQLSTATE: `HY000`

Message: Generated column can refer only to generated columns defined prior to it.

To address this issue, change the table definition to define each generated column later than any generated columns to which it refers.

- Error number: 3108; Symbol: `ER_DEPENDENT_BY_GENERATED_COLUMN`; SQLSTATE: `HY000`

Message: Column '%s' has a generated column dependency.

You cannot drop or rename a generated column if another column refers to it. You must either drop those columns as well, or redefine them not to refer to the generated column.

- Error number: 3109; Symbol: `ER_GENERATED_COLUMN_REF_AUTO_INC`; SQLSTATE: `HY000`

Message: Generated column '%s' cannot refer to auto-increment column.

- Error number: 3110; Symbol: `ER_FEATURE_NOT_AVAILABLE`; SQLSTATE: `HY000`

Message: The '%s' feature is not available; you need to remove '%s' or use MySQL built with '%s'

- Error number: 3111; Symbol: `ER_CANT_SET_GTID_MODE`; SQLSTATE: `HY000`

Message: SET @@GLOBAL.GTID\_MODE = %s is not allowed because %s.

- Error number: 3112; Symbol: `ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF`; SQLSTATE: `HY000`

Message: The replication receiver thread%s cannot start in AUTO\_POSITION mode: this server uses @@GLOBAL.GTID\_MODE = OFF.

- Error number: 3116; Symbol: `ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX`; SQLSTATE: `HY000`

Message: Cannot set ENFORCE\_GTID\_CONSISTENCY = ON because there are ongoing transactions that violate GTID consistency.

`ER_CANT_SET_ENFORCE_GTID_CONSISTENCY_ON_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS` was renamed to `ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX`.

- 
- Error number: 3117; Symbol: `ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX`; SQLSTATE: HY000  
  
Message: There are ongoing transactions that violate GTID consistency.  
  
`ER_SET_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS` was renamed to `ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX`.
  - Error number: 3118; Symbol: `ER_ACCOUNT_HAS_BEEN_LOCKED`; SQLSTATE: HY000  
  
Message: Access denied for user '%s'@'%s'. Account is locked.  
  
The account was locked with `CREATE USER ... ACCOUNT LOCK` or `ALTER USER ... ACCOUNT LOCK`. An administrator can unlock it with `ALTER USER ... ACCOUNT UNLOCK`.
  - Error number: 3119; Symbol: `ER_WRONG_TABLESPACE_NAME`; SQLSTATE: 42000  
  
Message: Incorrect tablespace name '%s'
  - Error number: 3120; Symbol: `ER_TABLESPACE_IS_NOT_EMPTY`; SQLSTATE: HY000  
  
Message: Tablespace '%s' is not empty.
  - Error number: 3121; Symbol: `ER_WRONG_FILE_NAME`; SQLSTATE: HY000  
  
Message: Incorrect File Name '%s'.
  - Error number: 3122; Symbol: `ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION`; SQLSTATE: HY000  
  
Message: Inconsistent intersection points.
  - Error number: 3123; Symbol: `ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR`; SQLSTATE: HY000  
  
Message: Optimizer hint syntax error
  - Error number: 3124; Symbol: `ER_WARN_BAD_MAX_EXECUTION_TIME`; SQLSTATE: HY000  
  
Message: Unsupported MAX\_EXECUTION\_TIME
  - Error number: 3125; Symbol: `ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME`; SQLSTATE: HY000  
  
Message: MAX\_EXECUTION\_TIME hint is supported by top-level standalone SELECT statements only  
  
The `MAX_EXECUTION_TIME` optimizer hint is supported only for `SELECT` statements.
  - Error number: 3126; Symbol: `ER_WARN_CONFLICTING_HINT`; SQLSTATE: HY000  
  
Message: Hint %s is ignored as conflicting/duplicated
  - Error number: 3127; Symbol: `ER_WARN_UNKNOWN_QB_NAME`; SQLSTATE: HY000  
  
Message: Query block name %s is not found for %s hint
  - Error number: 3128; Symbol: `ER_UNRESOLVED_HINT_NAME`; SQLSTATE: HY000  
  
Message: Unresolved name %s for %s hint
-

- 
- Error number: 3129; Symbol: [ER\\_WARN\\_ON\\_MODIFYING\\_GTID\\_EXECUTED\\_TABLE](#); SQLSTATE: [HY000](#)  
  
Message: Please do not modify the %s table. This is a mysql internal system table to store GTIDs for committed transactions. Modifying it can lead to an inconsistent GTID state.
  - Error number: 3130; Symbol: [ER\\_PLUGGABLE\\_PROTOCOL\\_COMMAND\\_NOT\\_SUPPORTED](#); SQLSTATE: [HY000](#)  
  
Message: Command not supported by pluggable protocols
  - Error number: 3131; Symbol: [ER\\_LOCKING\\_SERVICE\\_WRONG\\_NAME](#); SQLSTATE: [42000](#)  
  
Message: Incorrect locking service lock name '%s'.  
  
A locking service name was specified as [NULL](#), the empty string, or a string longer than 64 characters. Namespace and lock names must be non-[NULL](#), nonempty, and no more than 64 characters long.
  - Error number: 3132; Symbol: [ER\\_LOCKING\\_SERVICE\\_DEADLOCK](#); SQLSTATE: [HY000](#)  
  
Message: Deadlock found when trying to get locking service lock; try releasing locks and restarting lock acquisition.
  - Error number: 3133; Symbol: [ER\\_LOCKING\\_SERVICE\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
  
Message: Service lock wait timeout exceeded.
  - Error number: 3134; Symbol: [ER\\_GIS\\_MAX\\_POINTS\\_IN\\_GEOMETRY\\_OVERFLOWED](#); SQLSTATE: [HY000](#)  
  
Message: Parameter %s exceeds the maximum number of points in a geometry (%lu) in function %s.
  - Error number: 3135; Symbol: [ER\\_SQL\\_MODE\\_MERGED](#); SQLSTATE: [HY000](#)  
  
Message: 'NO\_ZERO\_DATE', 'NO\_ZERO\_IN\_DATE' and 'ERROR\_FOR\_DIVISION\_BY\_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.
  - Error number: 3136; Symbol: [ER\\_VTOKEN\\_PLUGIN\\_TOKEN\\_MISMATCH](#); SQLSTATE: [HY000](#)  
  
Message: Version token mismatch for %.\*s. Correct value %.\*s  
  
The client has set its [version\\_tokens\\_session](#) system variable to the list of tokens it requires the server to match, but the server token list has at least one matching token name that has a value different from what the client requires. See [Version Tokens](#).
  - Error number: 3137; Symbol: [ER\\_VTOKEN\\_PLUGIN\\_TOKEN\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
  
Message: Version token %.\*s not found.  
  
The client has set its [version\\_tokens\\_session](#) system variable to the list of tokens it requires the server to match, but the server token list is missing at least one of those tokens. See [Version Tokens](#).
  - Error number: 3138; Symbol: [ER\\_CANT\\_SET\\_VARIABLE\\_WHEN\\_OWNING\\_GTID](#); SQLSTATE: [HY000](#)  
  
Message: Variable %s cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.
  - Error number: 3139; Symbol: [ER\\_SLAVE\\_CHANNEL\\_OPERATION\\_NOT\\_ALLOWED](#); SQLSTATE: [HY000](#)

---

Message: %s cannot be performed on channel '%s'.

[ER\\_SLAVE\\_CHANNEL\\_OPERATION\\_NOT\\_ALLOWED](#) was removed after 8.0.32.

- Error number: [3139](#); Symbol: [ER\\_REPLICA\\_CHANNEL\\_OPERATION\\_NOT\\_ALLOWED](#); SQLSTATE: [HY000](#)

Message: %s cannot be performed on channel '%s'.

[ER\\_REPLICA\\_CHANNEL\\_OPERATION\\_NOT\\_ALLOWED](#) was added in 8.0.33.

- Error number: [3140](#); Symbol: [ER\\_INVALID\\_JSON\\_TEXT](#); SQLSTATE: [22032](#)

Message: Invalid JSON text: "%s" at position %u in value for column '%s'.

- Error number: [3141](#); Symbol: [ER\\_INVALID\\_JSON\\_TEXT\\_IN\\_PARAM](#); SQLSTATE: [22032](#)

Message: Invalid JSON text in argument %u to function %s: "%s" at position %u.%s

- Error number: [3142](#); Symbol: [ER\\_INVALID\\_JSON\\_BINARY\\_DATA](#); SQLSTATE: [HY000](#)

Message: The JSON binary value contains invalid data.

- Error number: [3143](#); Symbol: [ER\\_INVALID\\_JSON\\_PATH](#); SQLSTATE: [42000](#)

Message: Invalid JSON path expression. The error is around character position %u.%s

- Error number: [3144](#); Symbol: [ER\\_INVALID\\_JSON\\_CHARSET](#); SQLSTATE: [22032](#)

Message: Cannot create a JSON value from a string with CHARACTER SET '%s'.

- Error number: [3145](#); Symbol: [ER\\_INVALID\\_JSON\\_CHARSET\\_IN\\_FUNCTION](#); SQLSTATE: [22032](#)

Message: Invalid JSON character data provided to function %s: '%s'; utf8 is required.

- Error number: [3146](#); Symbol: [ER\\_INVALID\\_TYPE\\_FOR\\_JSON](#); SQLSTATE: [22032](#)

Message: Invalid data type for JSON data in argument %u to function %s; a JSON string or JSON type is required.

- Error number: [3147](#); Symbol: [ER\\_INVALID\\_CAST\\_TO\\_JSON](#); SQLSTATE: [22032](#)

Message: Cannot CAST value to JSON.

- Error number: [3148](#); Symbol: [ER\\_INVALID\\_JSON\\_PATH\\_CHARSET](#); SQLSTATE: [42000](#)

Message: A path expression must be encoded in the utf8 character set. The path expression '%s' is encoded in character set '%s'.

- Error number: [3149](#); Symbol: [ER\\_INVALID\\_JSON\\_PATH\\_WILDCARD](#); SQLSTATE: [42000](#)

Message: In this situation, path expressions may not contain the \* and \*\* tokens or an array range.

- Error number: [3150](#); Symbol: [ER\\_JSON\\_VALUE\\_TOO\\_BIG](#); SQLSTATE: [22032](#)

Message: The JSON value is too big to be stored in a JSON column.

- Error number: [3151](#); Symbol: [ER\\_JSON\\_KEY\\_TOO\\_BIG](#); SQLSTATE: [22032](#)

Message: The JSON object contains a key name that is too long.



- 
- Error number: [3152](#); Symbol: [ER\\_JSON\\_USED\\_AS\\_KEY](#); SQLSTATE: [42000](#)  
Message: JSON column '%s' supports indexing only via generated columns on a specified JSON path.
  - Error number: [3153](#); Symbol: [ER\\_JSON\\_VACUOUS\\_PATH](#); SQLSTATE: [42000](#)  
Message: The path expression '\$' is not allowed in this context.
  - Error number: [3154](#); Symbol: [ER\\_JSON\\_BAD\\_ONE\\_OR\\_ALL\\_ARG](#); SQLSTATE: [42000](#)  
Message: The oneOrAll argument to %s may take these values: 'one' or 'all'.
  - Error number: [3155](#); Symbol: [ER\\_NUMERIC\\_JSON\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [22003](#)  
Message: Out of range JSON value for CAST to %s%s from column %s at row %ld
  - Error number: [3156](#); Symbol: [ER\\_INVALID\\_JSON\\_VALUE\\_FOR\\_CAST](#); SQLSTATE: [22018](#)  
Message: Invalid JSON value for CAST to %s%s from column %s at row %ld
  - Error number: [3157](#); Symbol: [ER\\_JSON\\_DOCUMENT\\_TOO\\_DEEP](#); SQLSTATE: [22032](#)  
Message: The JSON document exceeds the maximum depth.
  - Error number: [3158](#); Symbol: [ER\\_JSON\\_DOCUMENT\\_NULL\\_KEY](#); SQLSTATE: [22032](#)  
Message: JSON documents may not contain NULL member names.
  - Error number: [3159](#); Symbol: [ER\\_SECURE\\_TRANSPORT\\_REQUIRED](#); SQLSTATE: [HY000](#)  
Message: Connections using insecure transport are prohibited while --require\_secure\_transport=ON.  
  
With the [require\\_secure\\_transport](#) system variable, clients can connect only using secure transports. Qualifying connections are those using SSL, a Unix socket file, or shared memory.
  - Error number: [3160](#); Symbol: [ER\\_NO\\_SECURE\\_TRANSPORTS\\_CONFIGURED](#); SQLSTATE: [HY000](#)  
Message: No secure transports (SSL or Shared Memory) are configured, unable to set --require\_secure\_transport=ON.  
  
The [require\\_secure\\_transport](#) system variable cannot be enabled if the server does not support at least one secure transport. Configure the server with the required SSL keys/certificates to enable SSL connections, or enable the [shared\\_memory](#) system variable to enable shared-memory connections.
  - Error number: [3161](#); Symbol: [ER\\_DISABLED\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Storage engine %s is disabled (Table creation is disallowed).  
  
An attempt was made to create a table or tablespace using a storage engine listed in the value of the [disabled\\_storage\\_engines](#) system variable, or to change an existing table or tablespace to such an engine. Choose a different storage engine.
  - Error number: [3162](#); Symbol: [ER\\_USER\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: Authorization ID %s does not exist.
  - Error number: [3163](#); Symbol: [ER\\_USER\\_ALREADY\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Authorization ID %s already exists.

- 
- Error number: 3164; Symbol: `ER_AUDIT_API_ABORT`; SQLSTATE: `HY000`  
Message: Aborted by Audit API ('%s';%d).  
  
This error indicates that an audit plugin terminated execution of an event. The message typically indicates the event subclass name and a numeric status value.
  - Error number: 3165; Symbol: `ER_INVALID_JSON_PATH_ARRAY_CELL`; SQLSTATE: `42000`  
Message: A path expression is not a path to a cell in an array.
  - Error number: 3166; Symbol: `ER_BUFPOOL_RESIZE_INPROGRESS`; SQLSTATE: `HY000`  
Message: Another buffer pool resize is already in progress.
  - Error number: 3167; Symbol: `ER_FEATURE_DISABLED_SEE_DOC`; SQLSTATE: `HY000`  
Message: The '%s' feature is disabled; see the documentation for '%s'
  - Error number: 3168; Symbol: `ER_SERVER_ISNT_AVAILABLE`; SQLSTATE: `HY000`  
Message: Server isn't available
  - Error number: 3169; Symbol: `ER_SESSION_WAS_KILLED`; SQLSTATE: `HY000`  
Message: Session was killed
  - Error number: 3170; Symbol: `ER_CAPACITY_EXCEEDED`; SQLSTATE: `HY000`  
Message: Memory capacity of %llu bytes for '%s' exceeded. %s
  - Error number: 3171; Symbol: `ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER`; SQLSTATE: `HY000`  
Message: Range optimization was not done for this query.
  - Error number: 3173; Symbol: `ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING_A_GTID`; SQLSTATE: `HY000`  
  
Message: The client holds ownership of the GTID %s. Therefore, `WAIT_FOR_EXECUTED_GTID_SET` cannot wait for this GTID.
  - Error number: 3174; Symbol: `ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL`; SQLSTATE: `HY000`  
Message: Cannot add foreign key on the base column of indexed virtual column.
  - Error number: 3175; Symbol: `ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT`; SQLSTATE: `HY000`  
  
Message: Cannot create index on virtual column whose base column has foreign constraint.
  - Error number: 3176; Symbol: `ER_ERROR_ON_MODIFYING_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`  
  
Message: Please do not modify the %s table with an XA transaction. This is an internal system table used to store GTIDs for committed transactions. Although modifying it can lead to an inconsistent GTID state, if necessary you can modify it with a non-XA transaction.
  - Error number: 3177; Symbol: `ER_LOCK_REFUSED_BY_ENGINE`; SQLSTATE: `HY000`  
Message: Lock acquisition refused by storage engine.

- 
- Error number: 3178; Symbol: `ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN`; SQLSTATE: HY000  
Message: ADD COLUMN col...VIRTUAL, ADD INDEX(col)
  - Error number: 3179; Symbol: `ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE`; SQLSTATE: HY000  
Message: Master key rotation is not supported by storage engine.
  - Error number: 3181; Symbol: `ER_MASTER_KEY_ROTATION_BINLOG_FAILED`; SQLSTATE: HY000  
Message: Write to binlog failed. However, master key rotation has been completed successfully.
  - Error number: 3182; Symbol: `ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE`; SQLSTATE: HY000  
Message: Storage engine is not available.
  - Error number: 3183; Symbol: `ER_TABLESPACE_CANNOT_ENCRYPT`; SQLSTATE: HY000  
Message: This tablespace can't be encrypted.
  - Error number: 3184; Symbol: `ER_INVALID_ENCRYPTION_OPTION`; SQLSTATE: HY000  
Message: Invalid encryption option.
  - Error number: 3185; Symbol: `ER_CANNOT_FIND_KEY_IN_KEYRING`; SQLSTATE: HY000  
Message: Can't find master key from keyring, please check in the server log if a keyring is loaded and initialized successfully.
  - Error number: 3186; Symbol: `ER_CAPACITY_EXCEEDED_IN_PARSER`; SQLSTATE: HY000  
Message: Parser bailed out for this query.
  - Error number: 3187; Symbol: `ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE`; SQLSTATE: HY000  
Message: Cannot alter encryption attribute by inplace algorithm.
  - Error number: 3188; Symbol: `ER_KEYRING_UDF_KEYRING_SERVICE_ERROR`; SQLSTATE: HY000  
Message: Function '%s' failed because underlying keyring service returned an error. Please check if a keyring is installed and that provided arguments are valid for the keyring you are using.
  - Error number: 3189; Symbol: `ER_USER_COLUMN_OLD_LENGTH`; SQLSTATE: HY000  
Message: It seems that your db schema is old. The %s column is 77 characters long and should be 93 characters long. Please perform the MySQL upgrade procedure.
  - Error number: 3190; Symbol: `ER_CANT_RESET_MASTER`; SQLSTATE: HY000  
Message: RESET MASTER is not allowed because %s.  
`ER_CANT_RESET_MASTER` was removed after 8.0.32.
  - Error number: 3190; Symbol: `ER_CANT_RESET_SOURCE`; SQLSTATE: HY000  
Message: RESET SOURCE is not allowed because %s.  
`ER_CANT_RESET_SOURCE` was added in 8.0.33.

- 
- Error number: 3191; Symbol: `ER_GROUP_REPLICATION_MAX_GROUP_SIZE`; SQLSTATE: `HY000`  
Message: The START GROUP\_REPLICATION command failed since the group already has 9 members.
  - Error number: 3192; Symbol: `ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED`; SQLSTATE: `HY000`  
Message: Cannot add foreign key on the base column of stored column.
  - Error number: 3193; Symbol: `ER_TABLE_REFERENCED`; SQLSTATE: `HY000`  
Message: Cannot complete the operation because table is referenced by another connection.
  - Error number: 3197; Symbol: `ER_XA_RETRY`; SQLSTATE: `HY000`  
Message: The resource manager is not able to commit the transaction branch at this time. Please retry later.  
`ER_XA_RETRY` was added in 8.0.2.
  - Error number: 3198; Symbol: `ER_KEYRING_AWS_UDF_AWS_KMS_ERROR`; SQLSTATE: `HY000`  
Message: Function %s failed due to: %s.  
`ER_KEYRING_AWS_UDF_AWS_KMS_ERROR` was added in 8.0.2.
  - Error number: 3199; Symbol: `ER_BINLOG_UNSAFE_XA`; SQLSTATE: `HY000`  
Message: Statement is unsafe because it is being used inside a XA transaction. Concurrent XA transactions may deadlock on replicas when replicated using statements.  
`ER_BINLOG_UNSAFE_XA` was added in 8.0.2.
  - Error number: 3200; Symbol: `ER_UDF_ERROR`; SQLSTATE: `HY000`  
Message: %s UDF failed; %s  
`ER_UDF_ERROR` was added in 8.0.4.
  - Error number: 3201; Symbol: `ER_KEYRING_MIGRATION_FAILURE`; SQLSTATE: `HY000`  
Message: Can not perform keyring migration : %s  
`ER_KEYRING_MIGRATION_FAILURE` was added in 8.0.4.
  - Error number: 3202; Symbol: `ER_KEYRING_ACCESS_DENIED_ERROR`; SQLSTATE: `42000`  
Message: Access denied; you need %s privileges for this operation  
`ER_KEYRING_ACCESS_DENIED_ERROR` was added in 8.0.4.
  - Error number: 3203; Symbol: `ER_KEYRING_MIGRATION_STATUS`; SQLSTATE: `HY000`  
Message: Keyring migration %s.  
`ER_KEYRING_MIGRATION_STATUS` was added in 8.0.4.
  - Error number: 3218; Symbol:  
`ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_VALUE`; SQLSTATE: `HY000`

---

Message: Invalid "max\_array\_length" argument value.

[ER\\_AUDIT\\_LOG\\_UDF\\_READ\\_INVALID\\_MAX\\_ARRAY\\_LENGTH\\_ARG\\_VALUE](#) was added in 8.0.11.

- Error number: [3231](#); Symbol: [ER\\_WRITE\\_SET\\_EXCEEDS\\_LIMIT](#); SQLSTATE: [HY000](#)

Message: The size of writeset data for the current transaction exceeds a limit imposed by an external component. If using Group Replication check 'group\_replication\_transaction\_size\_limit'.

[ER\\_WRITE\\_SET\\_EXCEEDS\\_LIMIT](#) was added in 8.0.23.

- Error number: [3235](#); Symbol: [ER\\_AES\\_INVALID\\_KDF\\_NAME](#); SQLSTATE: [HY000](#)

Message: KDF method name is not valid. Please use hkdf or pbkdf2\_hmac method name

[ER\\_AES\\_INVALID\\_KDF\\_NAME](#) was added in 8.0.30.

- Error number: [3236](#); Symbol: [ER\\_AES\\_INVALID\\_KDF\\_ITERATIONS](#); SQLSTATE: [HY000](#)

Message: For KDF method pbkdf2\_hmac iterations value less than 1000 or more than 65535 is not allowed due to security reasons. Please provide iterations >= 1000 and iterations < 65535

[ER\\_AES\\_INVALID\\_KDF\\_ITERATIONS](#) was added in 8.0.30.

- Error number: [3237](#); Symbol: [WARN\\_AES\\_KEY\\_SIZE](#); SQLSTATE: [HY000](#)

Message: AES key size should be %d bytes length or secure KDF methods hkdf or pbkdf2\_hmac should be used, please provide exact AES key size or use KDF methods for better security.

[WARN\\_AES\\_KEY\\_SIZE](#) was added in 8.0.30.

- Error number: [3238](#); Symbol: [ER\\_AES\\_INVALID\\_KDF\\_OPTION\\_SIZE](#); SQLSTATE: [HY000](#)

Message: KDF option size is invalid, please provide valid size < %d bytes and not NULL

[ER\\_AES\\_INVALID\\_KDF\\_OPTION\\_SIZE](#) was added in 8.0.30.

- Error number: [3500](#); Symbol: [ER\\_UNSUPPORT\\_COMPRESSED\\_TEMPORARY\\_TABLE](#); SQLSTATE: [HY000](#)

Message: CREATE TEMPORARY TABLE is not allowed with ROW\_FORMAT=COMPRESSED or KEY\_BLOCK\_SIZE.

- Error number: [3501](#); Symbol: [ER\\_ACL\\_OPERATION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: The ACL operation failed due to the following error from SE: errcode %d - %s

- Error number: [3502](#); Symbol: [ER\\_UNSUPPORTED\\_INDEX\\_ALGORITHM](#); SQLSTATE: [HY000](#)

Message: This storage engine does not support the %s index algorithm, storage engine default was used instead.

- Error number: [3503](#); Symbol: [ER\\_NO\\_SUCH\\_DB](#); SQLSTATE: [42Y07](#)

Message: Database '%s' doesn't exist

- Error number: [3504](#); Symbol: [ER\\_TOO\\_BIG\\_ENUM](#); SQLSTATE: [HY000](#)

Message: Too many enumeration values for column %s.

- 
- Error number: 3505; Symbol: ER\_TOO\_LONG\_SET\_ENUM\_VALUE; SQLSTATE: HY000  
Message: Too long enumeration/set value for column %s.
  - Error number: 3506; Symbol: ER\_INVALID\_DD\_OBJECT; SQLSTATE: HY000  
Message: %s dictionary object is invalid. (%s)
  - Error number: 3507; Symbol: ER\_UPDATING\_DD\_TABLE; SQLSTATE: HY000  
Message: Failed to update %s dictionary object.
  - Error number: 3508; Symbol: ER\_INVALID\_DD\_OBJECT\_ID; SQLSTATE: HY000  
Message: Dictionary object id (%lu) does not exist.
  - Error number: 3509; Symbol: ER\_INVALID\_DD\_OBJECT\_NAME; SQLSTATE: HY000  
Message: Dictionary object name '%s' is invalid. (%s)
  - Error number: 3510; Symbol: ER\_TABLESPACE\_MISSING\_WITH\_NAME; SQLSTATE: HY000  
Message: Tablespace %s doesn't exist.
  - Error number: 3511; Symbol: ER\_TOO\_LONG\_ROUTINE\_COMMENT; SQLSTATE: HY000  
Message: Comment for routine '%s' is too long (max = %lu)
  - Error number: 3512; Symbol: ER\_SP\_LOAD\_FAILED; SQLSTATE: HY000  
Message: Failed to load routine '%s'.
  - Error number: 3513; Symbol: ER\_INVALID\_BITWISE\_OPERANDS\_SIZE; SQLSTATE: HY000  
Message: Binary operands of bitwise operators must be of equal length
  - Error number: 3514; Symbol: ER\_INVALID\_BITWISE\_AGGREGATE\_OPERANDS\_SIZE; SQLSTATE: HY000  
Message: Aggregate bitwise functions cannot accept arguments longer than 511 bytes; consider using the SUBSTRING() function
  - Error number: 3515; Symbol: ER\_WARN\_UNSUPPORTED\_HINT; SQLSTATE: HY000  
Message: Hints aren't supported in %s
  - Error number: 3516; Symbol: ER\_UNEXPECTED\_GEOMETRY\_TYPE; SQLSTATE: 22S01  
Message: %s value is a geometry of unexpected type %s in %s.
  - Error number: 3517; Symbol: ER\_SRS\_PARSE\_ERROR; SQLSTATE: SR002  
Message: Can't parse the spatial reference system definition of SRID %u.
  - Error number: 3518; Symbol: ER\_SRS\_PROJ\_PARAMETER\_MISSING; SQLSTATE: SR003  
Message: The spatial reference system definition for SRID %u does not specify the mandatory %s (EPSG %u) projection parameter.
  - Error number: 3519; Symbol: ER\_WARN\_SRS\_NOT\_FOUND; SQLSTATE: 01000

---

Message: There's no spatial reference system with SRID %u.

- Error number: 3520; Symbol: `ER_SRS_NOT_CARTESIAN`; SQLSTATE: 22S00

Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which is not Cartesian.

- Error number: 3521; Symbol: `ER_SRS_NOT_CARTESIAN_UNDEFINED`; SQLSTATE: SR001

Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which has not been defined.

- Error number: 3522; Symbol: `ER_PK_INDEX_CANT_BE_INVISIBLE`; SQLSTATE: HY000

Message: A primary key index cannot be invisible

- Error number: 3523; Symbol: `ER_UNKNOWN_AUTHID`; SQLSTATE: HY000

Message: Unknown authorization ID '%s' @ '%s'

- Error number: 3524; Symbol: `ER_FAILED_ROLE_GRANT`; SQLSTATE: HY000

Message: Failed to grant %s to %s

- Error number: 3525; Symbol: `ER_OPEN_ROLE_TABLES`; SQLSTATE: HY000

Message: Failed to open the security system tables

- Error number: 3526; Symbol: `ER_FAILED_DEFAULT_ROLES`; SQLSTATE: HY000

Message: Failed to set default roles

- Error number: 3527; Symbol: `ER_COMPONENTS_NO_SCHEME`; SQLSTATE: HY000

Message: Cannot find schema in specified URN: '%s'.

- Error number: 3528; Symbol: `ER_COMPONENTS_NO_SCHEME_SERVICE`; SQLSTATE: HY000

Message: Cannot acquire scheme load service implementation for schema '%s' in specified URN: '%s'.

- Error number: 3529; Symbol: `ER_COMPONENTS_CANT_LOAD`; SQLSTATE: HY000

Message: Cannot load component from specified URN: '%s'.

- Error number: 3530; Symbol: `ER_ROLE_NOT_GRANTED`; SQLSTATE: HY000

Message: '%s' @ '%s' is not granted to '%s' @ '%s'

- Error number: 3531; Symbol: `ER_FAILED_REVOKE_ROLE`; SQLSTATE: HY000

Message: Could not revoke role from '%s' @ '%s'

- Error number: 3532; Symbol: `ER_RENAME_ROLE`; SQLSTATE: HY000

Message: Renaming of a role identifier is forbidden

- Error number: 3533; Symbol: `ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION`; SQLSTATE: HY000

---

Message: Cannot acquire specified service implementation: '%s'.

- Error number: 3534; Symbol: `ER_COMPONENTS_CANT_SATISFY_DEPENDENCY`; SQLSTATE: HY000

Message: Cannot satisfy dependency for service '%s' required by component '%s'.

- Error number: 3535; Symbol: `ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION`; SQLSTATE: HY000

Message: Cannot register service implementation '%s' provided by component '%s'.

- Error number: 3536; Symbol: `ER_COMPONENTS_LOAD_CANT_INITIALIZE`; SQLSTATE: HY000

Message: Initialization method provided by component '%s' failed.

- Error number: 3537; Symbol: `ER_COMPONENTS_UNLOAD_NOT_LOADED`; SQLSTATE: HY000

Message: Component specified by URN '%s' to unload has not been loaded before.

- Error number: 3538; Symbol: `ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE`; SQLSTATE: HY000

Message: De-initialization method provided by component '%s' failed.

- Error number: 3539; Symbol: `ER_COMPONENTS_CANT_RELEASE_SERVICE`; SQLSTATE: HY000

Message: Release of previously acquired service implementation failed.

- Error number: 3540; Symbol: `ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE`; SQLSTATE: HY000

Message: Unregistration of service implementation '%s' provided by component '%s' failed during unloading of the component.

- Error number: 3541; Symbol: `ER_COMPONENTS_CANT_UNLOAD`; SQLSTATE: HY000

Message: Cannot unload component from specified URN: '%s'.

- Error number: 3542; Symbol: `ER_WARN_UNLOAD_THE_NOT_PERSISTED`; SQLSTATE: HY000

Message: The Persistent Dynamic Loader was used to unload a component '%s', but it was not used to load that component before.

- Error number: 3543; Symbol: `ER_COMPONENT_TABLE_INCORRECT`; SQLSTATE: HY000

Message: The mysql.component table is missing or has an incorrect definition.

- Error number: 3544; Symbol: `ER_COMPONENT_MANIPULATE_ROW_FAILED`; SQLSTATE: HY000

Message: Failed to manipulate component '%s' persistence data. Error code %d from storage engine.

- Error number: 3545; Symbol: `ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP`; SQLSTATE: HY000

Message: The component with specified URN: '%s' was specified in group more than once.

- Error number: 3546; Symbol: `ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS`; SQLSTATE: HY000

Message: @@GLOBAL.GTID\_PURGED cannot be changed: %s



- 
- Error number: 3547; Symbol: `ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES`; SQLSTATE: HY000  
Message: Can not lock user management caches for processing.
  - Error number: 3548; Symbol: `ER_SRS_NOT_FOUND`; SQLSTATE: SR001  
Message: There's no spatial reference system with SRID %u.
  - Error number: 3549; Symbol: `ER_VARIABLE_NOT_PERSISTED`; SQLSTATE: HY000  
Message: Variables cannot be persisted. Please retry.
  - Error number: 3550; Symbol: `ER_IS_QUERY_INVALID_CLAUSE`; SQLSTATE: HY000  
Message: Information schema queries do not support the '%s' clause.
  - Error number: 3551; Symbol: `ER_UNABLE_TO_STORE_STATISTICS`; SQLSTATE: HY000  
Message: Unable to store dynamic %s statistics into data dictionary.
  - Error number: 3552; Symbol: `ER_NO_SYSTEM_SCHEMA_ACCESS`; SQLSTATE: HY000  
Message: Access to system schema '%s' is rejected.
  - Error number: 3553; Symbol: `ER_NO_SYSTEM_TABLESPACE_ACCESS`; SQLSTATE: HY000  
Message: Access to system tablespace '%s' is rejected.
  - Error number: 3554; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS`; SQLSTATE: HY000  
Message: Access to %s '%s.%s' is rejected.
  - Error number: 3555; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE`; SQLSTATE: HY000  
Message: data dictionary table  
`ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE` was added in 8.0.1.
  - Error number: 3556; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE`; SQLSTATE: HY000  
Message: system table  
`ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE` was added in 8.0.1.
  - Error number: 3557; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE`; SQLSTATE: HY000  
Message: table  
`ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE` was added in 8.0.1.
  - Error number: 3558; Symbol: `ER_INVALID_OPTION_KEY`; SQLSTATE: 22023  
Message: Invalid option key '%s' in function %s.  
`ER_INVALID_OPTION_KEY` was added in 8.0.1.
  - Error number: 3559; Symbol: `ER_INVALID_OPTION_VALUE`; SQLSTATE: 22023

---

Message: Invalid value '%s' for option '%s' in function '%s'.

[ER\\_INVALID\\_OPTION\\_VALUE](#) was added in 8.0.1.

- Error number: 3560; Symbol: [ER\\_INVALID\\_OPTION\\_KEY\\_VALUE\\_PAIR](#); SQLSTATE: 22023

Message: The string '%s' is not a valid key %c value pair in function %s.

[ER\\_INVALID\\_OPTION\\_KEY\\_VALUE\\_PAIR](#) was added in 8.0.1.

- Error number: 3561; Symbol: [ER\\_INVALID\\_OPTION\\_START\\_CHARACTER](#); SQLSTATE: 22023

Message: The options argument in function %s starts with the invalid character '%c'.

[ER\\_INVALID\\_OPTION\\_START\\_CHARACTER](#) was added in 8.0.1.

- Error number: 3562; Symbol: [ER\\_INVALID\\_OPTION\\_END\\_CHARACTER](#); SQLSTATE: 22023

Message: The options argument in function %s ends with the invalid character '%c'.

[ER\\_INVALID\\_OPTION\\_END\\_CHARACTER](#) was added in 8.0.1.

- Error number: 3563; Symbol: [ER\\_INVALID\\_OPTION\\_CHARACTERS](#); SQLSTATE: 22023

Message: The options argument in function %s contains the invalid character sequence '%s'.

[ER\\_INVALID\\_OPTION\\_CHARACTERS](#) was added in 8.0.1.

- Error number: 3564; Symbol: [ER\\_DUPLICATE\\_OPTION\\_KEY](#); SQLSTATE: 22023

Message: Duplicate option key '%s' in function '%s'.

[ER\\_DUPLICATE\\_OPTION\\_KEY](#) was added in 8.0.1.

- Error number: 3565; Symbol: [ER\\_WARN\\_SRS\\_NOT\\_FOUND\\_AXIS\\_ORDER](#); SQLSTATE: 01000

Message: There's no spatial reference system with SRID %u. The axis order is unknown.

[ER\\_WARN\\_SRS\\_NOT\\_FOUND\\_AXIS\\_ORDER](#) was added in 8.0.1.

- Error number: 3566; Symbol: [ER\\_NO\\_ACCESS\\_TO\\_NATIVE\\_FCT](#); SQLSTATE: HY000

Message: Access to native function '%s' is rejected.

[ER\\_NO\\_ACCESS\\_TO\\_NATIVE\\_FCT](#) was added in 8.0.1.

- Error number: 3567; Symbol: [ER\\_RESET\\_MASTER\\_TO\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: HY000

Message: The requested value '%llu' for the next binary log index is out of range. Please use a value between '1' and '%lu'.

[ER\\_RESET\\_MASTER\\_TO\\_VALUE\\_OUT\\_OF\\_RANGE](#) was added in 8.0.1, removed after 8.0.32.

- Error number: 3567; Symbol: [ER\\_RESET\\_SOURCE\\_TO\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: HY000

Message: The requested value '%llu' for the next binary log index is out of range. Please use a value between '1' and '%lu'.

[ER\\_RESET\\_SOURCE\\_TO\\_VALUE\\_OUT\\_OF\\_RANGE](#) was added in 8.0.33.

- 
- Error number: 3568; Symbol: `ER_UNRESOLVED_TABLE_LOCK`; SQLSTATE: `HY000`  
Message: Unresolved table name %s in locking clause.  
`ER_UNRESOLVED_TABLE_LOCK` was added in 8.0.1.
  - Error number: 3569; Symbol: `ER_DUPLICATE_TABLE_LOCK`; SQLSTATE: `HY000`  
Message: Table %s appears in multiple locking clauses.  
`ER_DUPLICATE_TABLE_LOCK` was added in 8.0.1.
  - Error number: 3570; Symbol: `ER_BINLOG_UNSAFE_SKIP_LOCKED`; SQLSTATE: `HY000`  
Message: Statement is unsafe because it uses SKIP LOCKED. The set of inserted values is non-deterministic.  
`ER_BINLOG_UNSAFE_SKIP_LOCKED` was added in 8.0.1.
  - Error number: 3571; Symbol: `ER_BINLOG_UNSAFE_NOWAIT`; SQLSTATE: `HY000`  
Message: Statement is unsafe because it uses NOWAIT. Whether the command will succeed or fail is not deterministic.  
`ER_BINLOG_UNSAFE_NOWAIT` was added in 8.0.1.
  - Error number: 3572; Symbol: `ER_LOCK_NOWAIT`; SQLSTATE: `HY000`  
Message: Statement aborted because lock(s) could not be acquired immediately and NOWAIT is set.  
`ER_LOCK_NOWAIT` was added in 8.0.1.
  - Error number: 3573; Symbol: `ER_CTE_RECURSIVE_REQUIRES_UNION`; SQLSTATE: `HY000`  
Message: Recursive Common Table Expression '%s' should contain a UNION  
`ER_CTE_RECURSIVE_REQUIRES_UNION` was added in 8.0.1.
  - Error number: 3574; Symbol: `ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST`; SQLSTATE: `HY000`  
Message: Recursive Common Table Expression '%s' should have one or more non-recursive query blocks followed by one or more recursive ones  
`ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST` was added in 8.0.1.
  - Error number: 3575; Symbol: `ER_CTE_RECURSIVE_FORBIDS_AGGREGATION`; SQLSTATE: `HY000`  
Message: Recursive Common Table Expression '%s' can contain neither aggregation nor window functions in recursive query block  
`ER_CTE_RECURSIVE_FORBIDS_AGGREGATION` was added in 8.0.1.
  - Error number: 3576; Symbol: `ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER`; SQLSTATE: `HY000`  
Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must neither be in the right argument of a LEFT JOIN, nor be forced to be non-first with join order hints  
`ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER` was added in 8.0.1.

- 
- Error number: 3577; Symbol: `ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE`; SQLSTATE: HY000

Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must be referenced only once, and not in any subquery

`ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE` was added in 8.0.1.

- Error number: 3578; Symbol: `ER_SWITCH_TMP_ENGINE`; SQLSTATE: HY000

Message: '%s' requires @@internal\_tmp\_disk\_storage\_engine=InnoDB

`ER_SWITCH_TMP_ENGINE` was added in 8.0.1.

- Error number: 3579; Symbol: `ER_WINDOW_NO_SUCH_WINDOW`; SQLSTATE: HY000

Message: Window name '%s' is not defined.

`ER_WINDOW_NO_SUCH_WINDOW` was added in 8.0.2.

- Error number: 3580; Symbol: `ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH`; SQLSTATE: HY000

Message: There is a circularity in the window dependency graph.

`ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH` was added in 8.0.2.

- Error number: 3581; Symbol: `ER_WINDOW_NO_CHILD_PARTITIONING`; SQLSTATE: HY000

Message: A window which depends on another cannot define partitioning.

`ER_WINDOW_NO_CHILD_PARTITIONING` was added in 8.0.2.

- Error number: 3582; Symbol: `ER_WINDOW_NO_INHERIT_FRAME`; SQLSTATE: HY000

Message: Window '%s' has a frame definition, so cannot be referenced by another window.

`ER_WINDOW_NO_INHERIT_FRAME` was added in 8.0.2.

- Error number: 3583; Symbol: `ER_WINDOW_NO_REDEFINE_ORDER_BY`; SQLSTATE: HY000

Message: Window '%s' cannot inherit '%s' since both contain an ORDER BY clause.

`ER_WINDOW_NO_REDEFINE_ORDER_BY` was added in 8.0.2.

- Error number: 3584; Symbol: `ER_WINDOW_FRAME_START_ILLEGAL`; SQLSTATE: HY000

Message: Window '%s': frame start cannot be UNBOUNDED FOLLOWING.

`ER_WINDOW_FRAME_START_ILLEGAL` was added in 8.0.2.

- Error number: 3585; Symbol: `ER_WINDOW_FRAME_END_ILLEGAL`; SQLSTATE: HY000

Message: Window '%s': frame end cannot be UNBOUNDED PRECEDING.

`ER_WINDOW_FRAME_END_ILLEGAL` was added in 8.0.2.

- Error number: 3586; Symbol: `ER_WINDOW_FRAME_ILLEGAL`; SQLSTATE: HY000

Message: Window '%s': frame start or end is negative, NULL or of non-integral type

---

`ER_WINDOW_FRAME_ILLEGAL` was added in 8.0.2.

- Error number: `3587`; Symbol: `ER_WINDOW_RANGE_FRAME_ORDER_TYPE`; SQLSTATE: `HY000`

Message: Window '%s' with RANGE N PRECEDING/FOLLOWING frame requires exactly one ORDER BY expression, of numeric or temporal type

`ER_WINDOW_RANGE_FRAME_ORDER_TYPE` was added in 8.0.2.

- Error number: `3588`; Symbol: `ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE`; SQLSTATE: `HY000`

Message: Window '%s' with RANGE frame has ORDER BY expression of datetime type. Only INTERVAL bound value allowed.

`ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE` was added in 8.0.2.

- Error number: `3589`; Symbol: `ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE`; SQLSTATE: `HY000`

Message: Window '%s' with RANGE frame has ORDER BY expression of numeric type, INTERVAL bound value not allowed.

`ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE` was added in 8.0.2.

- Error number: `3590`; Symbol: `ER_WINDOW_RANGE_BOUND_NOT_CONSTANT`; SQLSTATE: `HY000`

Message: Window '%s' has a non-constant frame bound.

`ER_WINDOW_RANGE_BOUND_NOT_CONSTANT` was added in 8.0.2.

- Error number: `3591`; Symbol: `ER_WINDOW_DUPLICATE_NAME`; SQLSTATE: `HY000`

Message: Window '%s' is defined twice.

`ER_WINDOW_DUPLICATE_NAME` was added in 8.0.2.

- Error number: `3592`; Symbol: `ER_WINDOW_ILLEGAL_ORDER_BY`; SQLSTATE: `HY000`

Message: Window '%s': ORDER BY or PARTITION BY uses legacy position indication which is not supported, use expression.

`ER_WINDOW_ILLEGAL_ORDER_BY` was added in 8.0.2.

- Error number: `3593`; Symbol: `ER_WINDOW_INVALID_WINDOW_FUNC_USE`; SQLSTATE: `HY000`

Message: You cannot use the window function '%s' in this context.'

`ER_WINDOW_INVALID_WINDOW_FUNC_USE` was added in 8.0.2.

- Error number: `3594`; Symbol: `ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE`; SQLSTATE: `HY000`

Message: You cannot use the alias '%s' of an expression containing a window function in this context.'

`ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE` was added in 8.0.2.

- Error number: `3595`; Symbol: `ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SPEC`; SQLSTATE: `HY000`

Message: You cannot nest a window function in the specification of window '%s'.

---

`ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SPEC` was added in 8.0.2.

- Error number: 3596; Symbol: `ER_WINDOW_ROWS_INTERVAL_USE`; SQLSTATE: HY000

Message: Window '%s': INTERVAL can only be used with RANGE frames.

`ER_WINDOW_ROWS_INTERVAL_USE` was added in 8.0.2.

- Error number: 3597; Symbol: `ER_WINDOW_NO_GROUP_ORDER`; SQLSTATE: HY000

Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY

`ER_WINDOW_NO_GROUP_ORDER` was added in 8.0.2, removed after 8.0.12.

- Error number: 3597; Symbol: `ER_WINDOW_NO_GROUP_ORDER_UNUSED`; SQLSTATE: HY000

Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY

`ER_WINDOW_NO_GROUP_ORDER_UNUSED` was added in 8.0.13.

- Error number: 3598; Symbol: `ER_WINDOW_EXPLAIN_JSON`; SQLSTATE: HY000

Message: To get information about window functions use EXPLAIN FORMAT=JSON

`ER_WINDOW_EXPLAIN_JSON` was added in 8.0.2.

- Error number: 3599; Symbol: `ER_WINDOW_FUNCTION_IGNORES_FRAME`; SQLSTATE: HY000

Message: Window function '%s' ignores the frame clause of window '%s' and aggregates over the whole partition

`ER_WINDOW_FUNCTION_IGNORES_FRAME` was added in 8.0.2.

- Error number: 3600; Symbol: `ER_WINDOW_SE_NOT_ACCEPTABLE`; SQLSTATE: HY000

Message: Windowing requires @@internal\_tmp\_mem\_storage\_engine=TempTable.

`ER_WINDOW_SE_NOT_ACCEPTABLE` was added in 8.0.2, removed after 8.0.3.

- Error number: 3600; Symbol: `ER_WL9236_NOW_UNUSED`; SQLSTATE: HY000

Message: Windowing requires @@internal\_tmp\_mem\_storage\_engine=TempTable.

`ER_WL9236_NOW_UNUSED` was added in 8.0.4.

- Error number: 3601; Symbol: `ER_INVALID_NO_OF_ARGS`; SQLSTATE: HY000

Message: Too many arguments for function %s: %lu; maximum allowed is %s.

`ER_INVALID_NO_OF_ARGS` was added in 8.0.1.

- Error number: 3602; Symbol: `ER_FIELD_IN_GROUPING_NOT_GROUP_BY`; SQLSTATE: HY000

Message: Argument #%u of GROUPING function is not in GROUP BY

`ER_FIELD_IN_GROUPING_NOT_GROUP_BY` was added in 8.0.1.

- 
- Error number: [3603](#); Symbol: [ER\\_TOO\\_LONG\\_TABLESPACE\\_COMMENT](#); SQLSTATE: [HY000](#)  
Message: Comment for tablespace '%s' is too long (max = %lu)  
[ER\\_TOO\\_LONG\\_TABLESPACE\\_COMMENT](#) was added in 8.0.1.
  - Error number: [3604](#); Symbol: [ER\\_ENGINE\\_CANT\\_DROP\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Storage engine can't drop table '%s'  
[ER\\_ENGINE\\_CANT\\_DROP\\_TABLE](#) was added in 8.0.1.
  - Error number: [3605](#); Symbol: [ER\\_ENGINE\\_CANT\\_DROP\\_MISSING\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Storage engine can't drop table '%s' because it is missing. Use DROP TABLE IF EXISTS to remove it from data-dictionary.  
[ER\\_ENGINE\\_CANT\\_DROP\\_MISSING\\_TABLE](#) was added in 8.0.1.
  - Error number: [3606](#); Symbol: [ER\\_TABLESPACE\\_DUP\\_FILENAME](#); SQLSTATE: [HY000](#)  
Message: Duplicate file name for tablespace '%s'  
[ER\\_TABLESPACE\\_DUP\\_FILENAME](#) was added in 8.0.1.
  - Error number: [3607](#); Symbol: [ER\\_DB\\_DROP\\_RMDIR2](#); SQLSTATE: [HY000](#)  
Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.  
[ER\\_DB\\_DROP\\_RMDIR2](#) was added in 8.0.1.
  - Error number: [3608](#); Symbol: [ER\\_IMP\\_NO\\_FILES\\_MATCHED](#); SQLSTATE: [HY000](#)  
Message: No SDI files matched the pattern '%s'  
[ER\\_IMP\\_NO\\_FILES\\_MATCHED](#) was added in 8.0.1.
  - Error number: [3609](#); Symbol: [ER\\_IMP\\_SCHEMA\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: Schema '%s', referenced in SDI, does not exist.  
[ER\\_IMP\\_SCHEMA\\_DOES\\_NOT\\_EXIST](#) was added in 8.0.1.
  - Error number: [3610](#); Symbol: [ER\\_IMP\\_TABLE\\_ALREADY\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Table '%s.%s', referenced in SDI, already exists.  
[ER\\_IMP\\_TABLE\\_ALREADY\\_EXISTS](#) was added in 8.0.1.
  - Error number: [3611](#); Symbol: [ER\\_IMP\\_INCOMPATIBLE\\_MYSQLD\\_VERSION](#); SQLSTATE: [HY000](#)  
Message: Imported mysqld\_version (%llu) is not compatible with current (%llu)  
[ER\\_IMP\\_INCOMPATIBLE\\_MYSQLD\\_VERSION](#) was added in 8.0.1.
  - Error number: [3612](#); Symbol: [ER\\_IMP\\_INCOMPATIBLE\\_DD\\_VERSION](#); SQLSTATE: [HY000](#)  
Message: Imported dd version (%u) is not compatible with current (%u)

---

`ER_IMP_INCOMPATIBLE_DD_VERSION` was added in 8.0.1.

- Error number: 3613; Symbol: `ER_IMP_INCOMPATIBLE_SDI_VERSION`; SQLSTATE: HY000

Message: Imported sdi version (%llu) is not compatible with current (%llu)

`ER_IMP_INCOMPATIBLE_SDI_VERSION` was added in 8.0.1.

- Error number: 3614; Symbol: `ER_WARN_INVALID_HINT`; SQLSTATE: HY000

Message: Invalid number of arguments for hint %s

`ER_WARN_INVALID_HINT` was added in 8.0.1.

- Error number: 3615; Symbol: `ER_VAR_DOES_NOT_EXIST`; SQLSTATE: HY000

Message: Variable %s does not exist in persisted config file

`ER_VAR_DOES_NOT_EXIST` was added in 8.0.1.

- Error number: 3616; Symbol: `ER_LONGITUDE_OUT_OF_RANGE`; SQLSTATE: 22S02

Message: Longitude %f is out of range in function %s. It must be within (%f, %f].

`ER_LONGITUDE_OUT_OF_RANGE` was added in 8.0.1.

- Error number: 3617; Symbol: `ER_LATITUDE_OUT_OF_RANGE`; SQLSTATE: 22S03

Message: Latitude %f is out of range in function %s. It must be within [%f, %f].

`ER_LATITUDE_OUT_OF_RANGE` was added in 8.0.1.

- Error number: 3618; Symbol: `ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS`; SQLSTATE: 22S00

Message: %s(%s) has not been implemented for geographic spatial reference systems.

`ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS` was added in 8.0.1.

- Error number: 3619; Symbol: `ER_ILLEGAL_PRIVILEGE_LEVEL`; SQLSTATE: HY000

Message: Illegal privilege level specified for %s

`ER_ILLEGAL_PRIVILEGE_LEVEL` was added in 8.0.1.

- Error number: 3620; Symbol: `ER_NO_SYSTEM_VIEW_ACCESS`; SQLSTATE: HY000

Message: Access to system view INFORMATION\_SCHEMA.'%s' is rejected.

`ER_NO_SYSTEM_VIEW_ACCESS` was added in 8.0.2.

- Error number: 3621; Symbol: `ER_COMPONENT_FILTER_FLABBERGASTED`; SQLSTATE: HY000

Message: The log-filter component "%s" got confused at "%s" ...

`ER_COMPONENT_FILTER_FLABBERGASTED` was added in 8.0.2.

- Error number: 3622; Symbol: `ER_PART_EXPR_TOO_LONG`; SQLSTATE: HY000

Message: Partitioning expression is too long.



---

`ER_PART_EXPR_TOO_LONG` was added in 8.0.2.

- Error number: `3623`; Symbol: `ER_UDF_DROP_DYNAMICALY_REGISTERED`; SQLSTATE: `HY000`  
Message: DROP FUNCTION can't drop a dynamically registered user defined function  
`ER_UDF_DROP_DYNAMICALY_REGISTERED` was added in 8.0.2.
- Error number: `3624`; Symbol: `ER_UNABLE_TO_STORE_COLUMN_STATISTICS`; SQLSTATE: `HY000`  
Message: Unable to store column statistics for column '%s' in table '%s'. '%s'  
`ER_UNABLE_TO_STORE_COLUMN_STATISTICS` was added in 8.0.2.
- Error number: `3625`; Symbol: `ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS`; SQLSTATE: `HY000`  
Message: Unable to update column statistics for column '%s' in table '%s'. '%s'  
`ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS` was added in 8.0.2.
- Error number: `3626`; Symbol: `ER_UNABLE_TO_DROP_COLUMN_STATISTICS`; SQLSTATE: `HY000`  
Message: Unable to remove column statistics for column '%s' in table '%s'. '%s'  
`ER_UNABLE_TO_DROP_COLUMN_STATISTICS` was added in 8.0.2.
- Error number: `3627`; Symbol: `ER_UNABLE_TO_BUILD_HISTOGRAM`; SQLSTATE: `HY000`  
Message: Unable to build histogram statistics for column '%s' in table '%s'. '%s'  
`ER_UNABLE_TO_BUILD_HISTOGRAM` was added in 8.0.2.
- Error number: `3628`; Symbol: `ER_MANDATORY_ROLE`; SQLSTATE: `HY000`  
Message: The role %s is a mandatory role and can't be revoked or dropped. The restriction can be lifted by excluding the role identifier from the global variable mandatory\_roles.  
`ER_MANDATORY_ROLE` was added in 8.0.2.
- Error number: `3629`; Symbol: `ER_MISSING_TABLESPACE_FILE`; SQLSTATE: `HY000`  
Message: Tablespace '%s' does not have a file named '%s'  
`ER_MISSING_TABLESPACE_FILE` was added in 8.0.3.
- Error number: `3630`; Symbol: `ER_PERSIST_ONLY_ACCESS_DENIED_ERROR`; SQLSTATE: `42000`  
Message: Access denied; you need %s privileges for this operation  
`ER_PERSIST_ONLY_ACCESS_DENIED_ERROR` was added in 8.0.3.
- Error number: `3631`; Symbol: `ER_CMD_NEED_SUPER`; SQLSTATE: `HY000`  
Message: You need the SUPER privilege for command '%s'  
`ER_CMD_NEED_SUPER` was added in 8.0.3.
- Error number: `3632`; Symbol: `ER_PATH_IN_DATADIR`; SQLSTATE: `HY000`

---

Message: Path is within the current data directory '%s'

[ER\\_PATH\\_IN\\_DATADIR](#) was added in 8.0.3.

- Error number: [3633](#); Symbol: [ER\\_DDL\\_IN\\_PROGRESS](#); SQLSTATE: [HY000](#)

Message: Concurrent DDL is performed during the operation. Please try again.

[ER\\_DDL\\_IN\\_PROGRESS](#) was added in 8.0.3, removed after 8.0.16.

- Error number: [3633](#); Symbol: [ER\\_CLONE\\_DDL\\_IN\\_PROGRESS](#); SQLSTATE: [HY000](#)

Message: Concurrent DDL is performed during clone operation. Please try again.

[ER\\_CLONE\\_DDL\\_IN\\_PROGRESS](#) was added in 8.0.17.

- Error number: [3634](#); Symbol: [ER\\_TOO\\_MANY\\_CONCURRENT\\_CLONES](#); SQLSTATE: [HY000](#)

Message: Too many concurrent clone operations. Maximum allowed - %d.

[ER\\_TOO\\_MANY\\_CONCURRENT\\_CLONES](#) was added in 8.0.3, removed after 8.0.16.

- Error number: [3634](#); Symbol: [ER\\_CLONE\\_TOO\\_MANY\\_CONCURRENT\\_CLONES](#); SQLSTATE: [HY000](#)

Message: Too many concurrent clone operations. Maximum allowed - %d.

[ER\\_CLONE\\_TOO\\_MANY\\_CONCURRENT\\_CLONES](#) was added in 8.0.17.

- Error number: [3635](#); Symbol: [ER\\_APPLIER\\_LOG\\_EVENT\\_VALIDATION\\_ERROR](#); SQLSTATE: [HY000](#)

Message: The table in transaction %s does not comply with the requirements by an external plugin.

[ER\\_APPLIER\\_LOG\\_EVENT\\_VALIDATION\\_ERROR](#) was added in 8.0.3.

- Error number: [3636](#); Symbol: [ER\\_CTE\\_MAX\\_RECURSION\\_DEPTH](#); SQLSTATE: [HY000](#)

Message: Recursive query aborted after %u iterations. Try increasing @@cte\_max\_recursion\_depth to a larger value.

[ER\\_CTE\\_MAX\\_RECURSION\\_DEPTH](#) was added in 8.0.3.

- Error number: [3637](#); Symbol: [ER\\_NOT\\_HINT\\_UPDATABLE\\_VARIABLE](#); SQLSTATE: [HY000](#)

Message: Variable %s cannot be set using SET\_VAR hint.

[ER\\_NOT\\_HINT\\_UPDATABLE\\_VARIABLE](#) was added in 8.0.3.

- Error number: [3638](#); Symbol: [ER\\_CREDENTIALS\\_CONTRADICT\\_TO\\_HISTORY](#); SQLSTATE: [HY000](#)

Message: Cannot use these credentials for '%.\*s@%.\*s' because they contradict the password history policy

[ER\\_CREDENTIALS\\_CONTRADICT\\_TO\\_HISTORY](#) was added in 8.0.3.

- Error number: [3639](#); Symbol: [ER\\_WARNING\\_PASSWORD\\_HISTORY\\_CLAUSES\\_VOID](#); SQLSTATE: [HY000](#)

Message: Non-zero password history clauses ignored for user '%s'@'%s' as its authentication plugin %s does not support password history

---

`ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID` was added in 8.0.3.

- Error number: `3640`; Symbol: `ER_CLIENT_DOES_NOT_SUPPORT`; SQLSTATE: `HY000`

Message: The client doesn't support %s

`ER_CLIENT_DOES_NOT_SUPPORT` was added in 8.0.3.

- Error number: `3641`; Symbol: `ER_I_S_SKIPPED_TABLESPACE`; SQLSTATE: `HY000`

Message: Tablespace '%s' was skipped since its definition is being modified by concurrent DDL statement

`ER_I_S_SKIPPED_TABLESPACE` was added in 8.0.3.

- Error number: `3642`; Symbol: `ER_TABLESPACE_ENGINE_MISMATCH`; SQLSTATE: `HY000`

Message: Engine '%s' does not match stored engine '%s' for tablespace '%s'

`ER_TABLESPACE_ENGINE_MISMATCH` was added in 8.0.3.

- Error number: `3643`; Symbol: `ER_WRONG_SRID_FOR_COLUMN`; SQLSTATE: `HY000`

Message: The SRID of the geometry does not match the SRID of the column '%s'. The SRID of the geometry is %lu, but the SRID of the column is %lu. Consider changing the SRID of the geometry or the SRID property of the column.

`ER_WRONG_SRID_FOR_COLUMN` was added in 8.0.3.

- Error number: `3644`; Symbol: `ER_CANNOT_ALTER_SRID_DUE_TO_INDEX`; SQLSTATE: `HY000`

Message: The SRID specification on the column '%s' cannot be changed because there is a spatial index on the column. Please remove the spatial index before altering the SRID specification.

`ER_CANNOT_ALTER_SRID_DUE_TO_INDEX` was added in 8.0.3.

- Error number: `3645`; Symbol: `ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED`; SQLSTATE: `HY000`

Message: When %s, the option `binlog_row_value_options=%s` will be ignored and updates will be written in full format to binary log.

`ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED` was added in 8.0.3.

- Error number: `3646`; Symbol: `ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED`; SQLSTATE: `HY000`

Message: When %s, the option `log_bin_use_v1_row_events=1` will be ignored and row events will be written in new format to binary log.

`ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED` was added in 8.0.3.

- Error number: `3647`; Symbol: `ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_IMAGES`; SQLSTATE: `HY000`

Message: When %s, the option `binlog_row_value_options=%s` will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to `binlog_row_value_options` is limited to less than 50%%.

`ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_IMAGES` was added in 8.0.3.

- 
- Error number: 3648; Symbol: [ER\\_COULD\\_NOT\\_APPLY\\_JSON\\_DIFF](#); SQLSTATE: HY000  
Message: Could not apply JSON diff in table %.\*s, column %s.  
[ER\\_COULD\\_NOT\\_APPLY\\_JSON\\_DIFF](#) was added in 8.0.3.
  - Error number: 3649; Symbol: [ER\\_CORRUPTED\\_JSON\\_DIFF](#); SQLSTATE: HY000  
Message: Corrupted JSON diff for table %.\*s, column %s.  
[ER\\_CORRUPTED\\_JSON\\_DIFF](#) was added in 8.0.3.
  - Error number: 3650; Symbol: [ER\\_RESOURCE\\_GROUP\\_EXISTS](#); SQLSTATE: HY000  
Message: Resource Group '%s' exists  
[ER\\_RESOURCE\\_GROUP\\_EXISTS](#) was added in 8.0.3.
  - Error number: 3651; Symbol: [ER\\_RESOURCE\\_GROUP\\_NOT\\_EXISTS](#); SQLSTATE: HY000  
Message: Resource Group '%s' does not exist.  
[ER\\_RESOURCE\\_GROUP\\_NOT\\_EXISTS](#) was added in 8.0.3.
  - Error number: 3652; Symbol: [ER\\_INVALID\\_VCPU\\_ID](#); SQLSTATE: HY000  
Message: Invalid cpu id %u  
[ER\\_INVALID\\_VCPU\\_ID](#) was added in 8.0.3.
  - Error number: 3653; Symbol: [ER\\_INVALID\\_VCPU\\_RANGE](#); SQLSTATE: HY000  
Message: Invalid VCPU range %u-%u  
[ER\\_INVALID\\_VCPU\\_RANGE](#) was added in 8.0.3.
  - Error number: 3654; Symbol: [ER\\_INVALID\\_THREAD\\_PRIORITY](#); SQLSTATE: HY000  
Message: Invalid thread priority value %d for %s resource group %s. Allowed range is [%d, %d].  
[ER\\_INVALID\\_THREAD\\_PRIORITY](#) was added in 8.0.3.
  - Error number: 3655; Symbol: [ER\\_DISALLOWED\\_OPERATION](#); SQLSTATE: HY000  
Message: %s operation is disallowed on %s  
[ER\\_DISALLOWED\\_OPERATION](#) was added in 8.0.3.
  - Error number: 3656; Symbol: [ER\\_RESOURCE\\_GROUP\\_BUSY](#); SQLSTATE: HY000  
Message: Resource group %s is busy.  
[ER\\_RESOURCE\\_GROUP\\_BUSY](#) was added in 8.0.3.
  - Error number: 3657; Symbol: [ER\\_RESOURCE\\_GROUP\\_DISABLED](#); SQLSTATE: HY000  
Message: Resource group %s is disabled.  
[ER\\_RESOURCE\\_GROUP\\_DISABLED](#) was added in 8.0.3.

- 
- Error number: 3658; Symbol: `ER_FEATURE_UNSUPPORTED`; SQLSTATE: `HY000`  
Message: Feature %s is unsupported (%s).  
`ER_FEATURE_UNSUPPORTED` was added in 8.0.3.
  - Error number: 3659; Symbol: `ER_ATTRIBUTE_IGNORED`; SQLSTATE: `HY000`  
Message: Attribute %s is ignored (%s).  
`ER_ATTRIBUTE_IGNORED` was added in 8.0.3.
  - Error number: 3660; Symbol: `ER_INVALID_THREAD_ID`; SQLSTATE: `HY000`  
Message: Invalid thread id (%llu).  
`ER_INVALID_THREAD_ID` was added in 8.0.3.
  - Error number: 3661; Symbol: `ER_RESOURCE_GROUP_BIND_FAILED`; SQLSTATE: `HY000`  
Message: Unable to bind resource group %s with thread id (%llu).(%)s).  
`ER_RESOURCE_GROUP_BIND_FAILED` was added in 8.0.3.
  - Error number: 3662; Symbol: `ER_INVALID_USE_OF_FORCE_OPTION`; SQLSTATE: `HY000`  
Message: Option FORCE invalid as DISABLE option is not specified.  
`ER_INVALID_USE_OF_FORCE_OPTION` was added in 8.0.3.
  - Error number: 3663; Symbol: `ER_GROUP_REPLICATION_COMMAND_FAILURE`; SQLSTATE: `HY000`  
Message: The %s command encountered a failure. %s  
`ER_GROUP_REPLICATION_COMMAND_FAILURE` was added in 8.0.4.
  - Error number: 3664; Symbol: `ER_SDI_OPERATION_FAILED`; SQLSTATE: `HY000`  
Message: Failed to %s SDI '%s.%s' in tablespace '%s'.  
`ER_SDI_OPERATION_FAILED` was added in 8.0.3.
  - Error number: 3665; Symbol: `ER_MISSING_JSON_TABLE_VALUE`; SQLSTATE: `22035`  
Message: Missing value for JSON\_TABLE column '%s'  
`ER_MISSING_JSON_TABLE_VALUE` was added in 8.0.4.
  - Error number: 3666; Symbol: `ER_WRONG_JSON_TABLE_VALUE`; SQLSTATE: `2203F`  
Message: Can't store an array or an object in the scalar JSON\_TABLE column '%s'  
`ER_WRONG_JSON_TABLE_VALUE` was added in 8.0.4.
  - Error number: 3667; Symbol: `ER_TF_MUST_HAVE_ALIAS`; SQLSTATE: `42000`  
Message: Every table function must have an alias  
`ER_TF_MUST_HAVE_ALIAS` was added in 8.0.4.

- 
- Error number: 3668; Symbol: `ER_TF_FORBIDDEN_JOIN_TYPE`; SQLSTATE: `HY000`  
Message: INNER or LEFT JOIN must be used for LATERAL references made by '%s'  
`ER_TF_FORBIDDEN_JOIN_TYPE` was added in 8.0.4.
  - Error number: 3669; Symbol: `ER_JT_VALUE_OUT_OF_RANGE`; SQLSTATE: `22003`  
Message: Value is out of range for JSON\_TABLE's column '%s'  
`ER_JT_VALUE_OUT_OF_RANGE` was added in 8.0.4.
  - Error number: 3670; Symbol: `ER_JT_MAX_NESTED_PATH`; SQLSTATE: `42000`  
Message: More than supported %u NESTED PATHs were found in JSON\_TABLE '%s'  
`ER_JT_MAX_NESTED_PATH` was added in 8.0.4.
  - Error number: 3671; Symbol: `ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH_METHOD`; SQLSTATE: `HY000`  
Message: The selected authentication method %.\*s does not support password expiration  
`ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH_METHOD` was added in 8.0.4.
  - Error number: 3672; Symbol: `ER_INVALID_GEOJSON_CRS_NOT_TOP_LEVEL`; SQLSTATE: `HY000`  
Message: Invalid GeoJSON data provided to function %s: Member 'crs' must be specified in the top level object.  
`ER_INVALID_GEOJSON_CRS_NOT_TOP_LEVEL` was added in 8.0.4.
  - Error number: 3673; Symbol: `ER_BAD_NULL_ERROR_NOT_IGNORED`; SQLSTATE: `23000`  
Message: Column '%s' cannot be null  
`ER_BAD_NULL_ERROR_NOT_IGNORED` was added in 8.0.4.
  - Error number: 3674; Symbol: `WARN_USELESS_SPATIAL_INDEX`; SQLSTATE: `HY000`  
Message: The spatial index on column '%s' will not be used by the query optimizer since the column does not have an SRID attribute. Consider adding an SRID attribute to the column.  
`WARN_USELESS_SPATIAL_INDEX` was added in 8.0.4.
  - Error number: 3675; Symbol: `ER_DISK_FULL_NOWAIT`; SQLSTATE: `HY000`  
Message: Create table/tablespace '%s' failed, as disk is full  
`ER_DISK_FULL_NOWAIT` was added in 8.0.4.
  - Error number: 3676; Symbol: `ER_PARSE_ERROR_IN_DIGEST_FN`; SQLSTATE: `HY000`  
Message: Could not parse argument to digest function: "%s".  
`ER_PARSE_ERROR_IN_DIGEST_FN` was added in 8.0.4.
  - Error number: 3677; Symbol: `ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN`; SQLSTATE: `HY000`  
Message: Could not parse argument to digest function.

---

`ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN` was added in 8.0.4.

- Error number: `3678`; Symbol: `ER_SCHEMA_DIR_EXISTS`; SQLSTATE: `HY000`

Message: Schema directory '%s' already exists. This must be resolved manually (e.g. by moving the schema directory to another location).

`ER_SCHEMA_DIR_EXISTS` was added in 8.0.4.

- Error number: `3679`; Symbol: `ER_SCHEMA_DIR_MISSING`; SQLSTATE: `HY000`

Message: Schema directory '%s' does not exist

`ER_SCHEMA_DIR_MISSING` was added in 8.0.4.

- Error number: `3680`; Symbol: `ER_SCHEMA_DIR_CREATE_FAILED`; SQLSTATE: `HY000`

Message: Failed to create schema directory '%s' (errno: %d - %s)

`ER_SCHEMA_DIR_CREATE_FAILED` was added in 8.0.4.

- Error number: `3681`; Symbol: `ER_SCHEMA_DIR_UNKNOWN`; SQLSTATE: `HY000`

Message: Schema '%s' does not exist, but schema directory '%s' was found. This must be resolved manually (e.g. by moving the schema directory to another location).

`ER_SCHEMA_DIR_UNKNOWN` was added in 8.0.4.

- Error number: `3682`; Symbol: `ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326`; SQLSTATE: `22S00`

Message: Function %s is only defined for SRID 0 and SRID 4326.

`ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326` was added in 8.0.4.

- Error number: `3683`; Symbol: `ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOGETHER`; SQLSTATE: `HY000`

Message: The option `expire_logs_days` and `binlog_expire_logs_seconds` cannot be used together. Please use `binlog_expire_logs_seconds` to set the expire time (`expire_logs_days` is deprecated)

`ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOGETHER` was added in 8.0.11.

- Error number: `3684`; Symbol: `ER_REGEX_STRING_NOT_TERMINATED`; SQLSTATE: `HY000`

Message: An output string could not be zero-terminated because the length exceeds the buffer capacity.

`ER_REGEX_STRING_NOT_TERMINATED` was added in 8.0.4, removed after 8.0.4.

- Error number: `3684`; Symbol: `ER_REGEX_BUFFER_OVERFLOW`; SQLSTATE: `HY000`

Message: The result string is larger than the result buffer.

`ER_REGEX_BUFFER_OVERFLOW` was added in 8.0.4.

- Error number: `3685`; Symbol: `ER_REGEX_ILLEGAL_ARGUMENT`; SQLSTATE: `HY000`

Message: Illegal argument to a regular expression.

`ER_REGEX_ILLEGAL_ARGUMENT` was added in 8.0.4.

- 
- Error number: 3686; Symbol: `ER_REGEX_INDEX_OUTOFBOUNDS_ERROR`; SQLSTATE: HY000  
Message: Index out of bounds in regular expression search.  
`ER_REGEX_INDEX_OUTOFBOUNDS_ERROR` was added in 8.0.4.
  - Error number: 3687; Symbol: `ER_REGEX_INTERNAL_ERROR`; SQLSTATE: HY000  
Message: Internal error in the regular expression library.  
`ER_REGEX_INTERNAL_ERROR` was added in 8.0.4.
  - Error number: 3688; Symbol: `ER_REGEX_RULE_SYNTAX`; SQLSTATE: HY000  
Message: Syntax error in regular expression on line %u, character %u.  
`ER_REGEX_RULE_SYNTAX` was added in 8.0.4.
  - Error number: 3689; Symbol: `ER_REGEX_BAD_ESCAPE_SEQUENCE`; SQLSTATE: HY000  
Message: Unrecognized escape sequence in regular expression.  
`ER_REGEX_BAD_ESCAPE_SEQUENCE` was added in 8.0.4.
  - Error number: 3690; Symbol: `ER_REGEX_UNIMPLEMENTED`; SQLSTATE: HY000  
Message: The regular expression contains a feature that is not implemented in this library version.  
`ER_REGEX_UNIMPLEMENTED` was added in 8.0.4.
  - Error number: 3691; Symbol: `ER_REGEX_MISMATCHED_PAREN`; SQLSTATE: HY000  
Message: Mismatched parenthesis in regular expression.  
`ER_REGEX_MISMATCHED_PAREN` was added in 8.0.4.
  - Error number: 3692; Symbol: `ER_REGEX_BAD_INTERVAL`; SQLSTATE: HY000  
Message: Incorrect description of a {min,max} interval.  
`ER_REGEX_BAD_INTERVAL` was added in 8.0.4.
  - Error number: 3693; Symbol: `ER_REGEX_MAX_LT_MIN`; SQLSTATE: HY000  
Message: The maximum is less than the minimum in a {min,max} interval.  
`ER_REGEX_MAX_LT_MIN` was added in 8.0.4.
  - Error number: 3694; Symbol: `ER_REGEX_INVALID_BACK_REF`; SQLSTATE: HY000  
Message: Invalid back-reference in regular expression.  
`ER_REGEX_INVALID_BACK_REF` was added in 8.0.4.
  - Error number: 3695; Symbol: `ER_REGEX_LOOK_BEHIND_LIMIT`; SQLSTATE: HY000  
Message: The look-behind assertion exceeds the limit in regular expression.  
`ER_REGEX_LOOK_BEHIND_LIMIT` was added in 8.0.4.



- 
- Error number: 3696; Symbol: `ER_REGEX_MISSING_CLOSE_BRACKET`; SQLSTATE: `HY000`  
Message: The regular expression contains an unclosed bracket expression.  
`ER_REGEX_MISSING_CLOSE_BRACKET` was added in 8.0.4.
  - Error number: 3697; Symbol: `ER_REGEX_INVALID_RANGE`; SQLSTATE: `HY000`  
Message: The regular expression contains an [x-y] character range where x comes after y.  
`ER_REGEX_INVALID_RANGE` was added in 8.0.4.
  - Error number: 3698; Symbol: `ER_REGEX_STACK_OVERFLOW`; SQLSTATE: `HY000`  
Message: Overflow in the regular expression backtrack stack.  
`ER_REGEX_STACK_OVERFLOW` was added in 8.0.4.
  - Error number: 3699; Symbol: `ER_REGEX_TIME_OUT`; SQLSTATE: `HY000`  
Message: Timeout exceeded in regular expression match.  
`ER_REGEX_TIME_OUT` was added in 8.0.4.
  - Error number: 3700; Symbol: `ER_REGEX_PATTERN_TOO_BIG`; SQLSTATE: `HY000`  
Message: The regular expression pattern exceeds limits on size or complexity.  
`ER_REGEX_PATTERN_TOO_BIG` was added in 8.0.4.
  - Error number: 3701; Symbol: `ER_CANT_SET_ERROR_LOG_SERVICE`; SQLSTATE: `HY000`  
Message: Value for %s got confusing at or around "%s". Syntax may be wrong, component may not be INSTALLED, or a component that does not support instances may be listed more than once.  
`ER_CANT_SET_ERROR_LOG_SERVICE` was added in 8.0.4.
  - Error number: 3702; Symbol: `ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE`; SQLSTATE: `HY000`  
Message: Setting an empty %s pipeline disables error logging!  
`ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE` was added in 8.0.4.
  - Error number: 3703; Symbol: `ER_COMPONENT_FILTER_DIAGNOSTICS`; SQLSTATE: `HY000`  
Message: filter %s: %s  
`ER_COMPONENT_FILTER_DIAGNOSTICS` was added in 8.0.4.
  - Error number: 3704; Symbol: `ER_INNODB_CANNOT_BE_IGNORED`; SQLSTATE: `HY000`  
Message: ignore-builtin-innodb is ignored and will be removed in future releases.  
`ER_INNODB_CANNOT_BE_IGNORED` was added in 8.0.2, removed after 8.0.2.
  - Error number: 3704; Symbol: `ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS`; SQLSTATE: `22S00`  
Message: %s(%s) has not been implemented for Cartesian spatial reference systems.  
`ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS` was added in 8.0.4.

- 
- Error number: 3705; Symbol: `ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS`; SQLSTATE: 22S00  
Message: %s(%s) has not been implemented for projected spatial reference systems.  
`ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS` was added in 8.0.4.
  - Error number: 3706; Symbol: `ER_NONPOSITIVE_RADIUS`; SQLSTATE: 22003  
Message: Invalid radius provided to function %s: Radius must be greater than zero.  
`ER_NONPOSITIVE_RADIUS` was added in 8.0.4.
  - Error number: 3707; Symbol: `ER_RESTART_SERVER_FAILED`; SQLSTATE: HY000  
Message: Restart server failed (%s).  
`ER_RESTART_SERVER_FAILED` was added in 8.0.4.
  - Error number: 3708; Symbol: `ER_SRS_MISSING_MANDATORY_ATTRIBUTE`; SQLSTATE: SR006  
Message: Missing mandatory attribute %s.  
`ER_SRS_MISSING_MANDATORY_ATTRIBUTE` was added in 8.0.4.
  - Error number: 3709; Symbol: `ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS`; SQLSTATE: SR006  
Message: Multiple definitions of attribute %s.  
`ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS` was added in 8.0.4.
  - Error number: 3710; Symbol: `ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE`; SQLSTATE: SR006  
Message: The spatial reference system name can't be an empty string or start or end with whitespace.  
`ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE` was added in 8.0.4.
  - Error number: 3711; Symbol: `ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE`; SQLSTATE: SR006  
Message: The organization name can't be an empty string or start or end with whitespace.  
`ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE` was added in 8.0.4.
  - Error number: 3712; Symbol: `ER_SRS_ID_ALREADY_EXISTS`; SQLSTATE: SR004  
Message: There is already a spatial reference system with SRID %u.  
`ER_SRS_ID_ALREADY_EXISTS` was added in 8.0.4.
  - Error number: 3713; Symbol: `ER_WARN_SRS_ID_ALREADY_EXISTS`; SQLSTATE: 01S00  
Message: There is already a spatial reference system with SRID %u.  
`ER_WARN_SRS_ID_ALREADY_EXISTS` was added in 8.0.4.
  - Error number: 3714; Symbol: `ER_CANT_MODIFY_SRID_0`; SQLSTATE: SR000  
Message: SRID 0 is not modifiable.  
`ER_CANT_MODIFY_SRID_0` was added in 8.0.4.

- 
- Error number: 3715; Symbol: `ER_WARN_RESERVED_SRID_RANGE`; SQLSTATE: 01S01  
Message: The SRID range [%u, %u] has been reserved for system use. SRSs in this range may be added, modified or removed without warning during upgrade.  
`ER_WARN_RESERVED_SRID_RANGE` was added in 8.0.4.
  - Error number: 3716; Symbol: `ER_CANT_MODIFY_SRS_USED_BY_COLUMN`; SQLSTATE: SR005  
Message: Can't modify SRID %u. There is at least one column depending on it.  
`ER_CANT_MODIFY_SRS_USED_BY_COLUMN` was added in 8.0.4.
  - Error number: 3717; Symbol: `ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE`; SQLSTATE: SR006  
Message: Invalid character in attribute %s.  
`ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE` was added in 8.0.4.
  - Error number: 3718; Symbol: `ER_SRS_ATTRIBUTE_STRING_TOO_LONG`; SQLSTATE: SR006  
Message: Attribute %s is too long. The maximum length is %u characters.  
`ER_SRS_ATTRIBUTE_STRING_TOO_LONG` was added in 8.0.4.
  - Error number: 3719; Symbol: `ER_DEPRECATED_UTF8_ALIAS`; SQLSTATE: HY000  
Message: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.  
`ER_DEPRECATED_UTF8_ALIAS` was added in 8.0.11.
  - Error number: 3720; Symbol: `ER_DEPRECATED_NATIONAL`; SQLSTATE: HY000  
Message: NATIONAL/NCHAR/NVARCHAR implies the character set UTF8MB3, which will be replaced by UTF8MB4 in a future release. Please consider using CHAR(x) CHARACTER SET UTF8MB4 in order to be unambiguous.  
`ER_DEPRECATED_NATIONAL` was added in 8.0.11.
  - Error number: 3721; Symbol: `ER_INVALID_DEFAULT_UTF8MB4_COLLATION`; SQLSTATE: HY000  
Message: Invalid default collation %s: utf8mb4\_0900\_ai\_ci or utf8mb4\_general\_ci expected  
`ER_INVALID_DEFAULT_UTF8MB4_COLLATION` was added in 8.0.11.
  - Error number: 3722; Symbol: `ER_UNABLE_TO_COLLECT_LOG_STATUS`; SQLSTATE: HY000  
Message: Unable to collect information for column '%s': %s.  
`ER_UNABLE_TO_COLLECT_LOG_STATUS` was added in 8.0.11.
  - Error number: 3723; Symbol: `ER_RESERVED_TABLESPACE_NAME`; SQLSTATE: HY000  
Message: The table '%s' may not be created in the reserved tablespace '%s'.  
`ER_RESERVED_TABLESPACE_NAME` was added in 8.0.11.
  - Error number: 3724; Symbol: `ER_UNABLE_TO_SET_OPTION`; SQLSTATE: HY000

---

Message: This option cannot be set %s.

`ER_UNABLE_TO_SET_OPTION` was added in 8.0.11.

- Error number: 3725; Symbol: `ER_SLAVE_POSSIBLY_DIVERGED_AFTER_DDL`; SQLSTATE: `HY000`

Message: A commit for an atomic DDL statement was unsuccessful on the master and the slave. The slave supports atomic DDL statements but the master does not, so the action taken by the slave and master might differ. Check that their states have not diverged before proceeding.

`ER_SLAVE_POSSIBLY_DIVERGED_AFTER_DDL` was added in 8.0.11, removed after 8.0.32.

- Error number: 3725; Symbol: `ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL`; SQLSTATE: `HY000`

Message: A commit for an atomic DDL statement was unsuccessful on the source and the replica. The replica supports atomic DDL statements but the source does not, so the action taken by the replica and source might differ. Check that their states have not diverged before proceeding.

`ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL` was added in 8.0.33.

- Error number: 3726; Symbol: `ER_SRS_NOT_GEOGRAPHIC`; SQLSTATE: `22S00`

Message: Function %s is only defined for geographic spatial reference systems, but one of its arguments is in SRID %u, which is not geographic.

`ER_SRS_NOT_GEOGRAPHIC` was added in 8.0.12.

- Error number: 3727; Symbol: `ER_POLYGON_TOO_LARGE`; SQLSTATE: `22023`

Message: Function %s encountered a polygon that was too large. Polygons must cover less than half the planet.

`ER_POLYGON_TOO_LARGE` was added in 8.0.12.

- Error number: 3728; Symbol: `ER_SPATIAL_UNIQUE_INDEX`; SQLSTATE: `HY000`

Message: Spatial indexes can't be primary or unique indexes.

`ER_SPATIAL_UNIQUE_INDEX` was added in 8.0.12.

- Error number: 3729; Symbol: `ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX`; SQLSTATE: `HY000`

Message: The index type %s is not supported for spatial indexes.

`ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX` was added in 8.0.12.

- Error number: 3730; Symbol: `ER_FK_CANNOT_DROP_PARENT`; SQLSTATE: `HY000`

Message: Cannot drop table '%s' referenced by a foreign key constraint '%s' on table '%s'.

`ER_FK_CANNOT_DROP_PARENT` was added in 8.0.12.

- Error number: 3731; Symbol: `ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE`; SQLSTATE: `22S02`

Message: A parameter of function %s contains a geometry with longitude %f, which is out of range. It must be within (%f, %f].

---

`ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE` was added in 8.0.12.

- Error number: 3732; Symbol: `ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE`; SQLSTATE: 22S03  
Message: A parameter of function %s contains a geometry with latitude %f, which is out of range. It must be within [%f, %f].

`ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE` was added in 8.0.12.

- Error number: 3733; Symbol: `ER_FK_CANNOT_USE_VIRTUAL_COLUMN`; SQLSTATE: HY000  
Message: Foreign key '%s' uses virtual column '%s' which is not supported.

`ER_FK_CANNOT_USE_VIRTUAL_COLUMN` was added in 8.0.12.

- Error number: 3734; Symbol: `ER_FK_NO_COLUMN_PARENT`; SQLSTATE: HY000  
Message: Failed to add the foreign key constraint. Missing column '%s' for constraint '%s' in the referenced table '%s'

`ER_FK_NO_COLUMN_PARENT` was added in 8.0.12.

- Error number: 3735; Symbol: `ER_CANT_SET_ERROR_SUPPRESSION_LIST`; SQLSTATE: HY000  
Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.

`ER_CANT_SET_ERROR_SUPPRESSION_LIST` was added in 8.0.13.

- Error number: 3736; Symbol: `ER_SRS_GEOGCS_INVALID_AXES`; SQLSTATE: SR002  
Message: The spatial reference system definition for SRID %u specifies invalid geographic axes '%s' and '%s'. One axis must be NORTH or SOUTH and the other must be EAST or WEST.

`ER_SRS_GEOGCS_INVALID_AXES` was added in 8.0.13.

- Error number: 3737; Symbol: `ER_SRS_INVALID_SEMI_MAJOR_AXIS`; SQLSTATE: SR002  
Message: The length of the semi-major axis must be a positive number.

`ER_SRS_INVALID_SEMI_MAJOR_AXIS` was added in 8.0.13.

- Error number: 3738; Symbol: `ER_SRS_INVALID_INVERSE_FLATTENING`; SQLSTATE: SR002  
Message: The inverse flattening must be larger than 1.0, or 0.0 if the ellipsoid is a sphere.

`ER_SRS_INVALID_INVERSE_FLATTENING` was added in 8.0.13.

- Error number: 3739; Symbol: `ER_SRS_INVALID_ANGULAR_UNIT`; SQLSTATE: SR002  
Message: The angular unit conversion factor must be a positive number.

`ER_SRS_INVALID_ANGULAR_UNIT` was added in 8.0.13.

- Error number: 3740; Symbol: `ER_SRS_INVALID_PRIME_MERIDIAN`; SQLSTATE: SR002  
Message: The prime meridian must be within (-180, 180] degrees, specified in the SRS angular unit.

`ER_SRS_INVALID_PRIME_MERIDIAN` was added in 8.0.13.

- 
- Error number: 3741; Symbol: `ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED`; SQLSTATE: 22S00  
Message: Transformation from SRID %u is not supported.  
`ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED` was added in 8.0.13.
  - Error number: 3742; Symbol: `ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED`; SQLSTATE: 22S00  
Message: Transformation to SRID %u is not supported.  
`ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED` was added in 8.0.13.
  - Error number: 3743; Symbol: `ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84`; SQLSTATE: 22S00  
Message: Transformation from SRID %u is not supported. The spatial reference system has no TOWGS84 clause.  
`ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84` was added in 8.0.13.
  - Error number: 3744; Symbol: `ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84`; SQLSTATE: 22S00  
Message: Transformation to SRID %u is not supported. The spatial reference system has no TOWGS84 clause.  
`ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84` was added in 8.0.13.
  - Error number: 3745; Symbol: `ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT`; SQLSTATE: HY000  
Message: Changing @@session.binlog\_format is disallowed when the session has open temporary table(s). You could wait until these temporary table(s) are dropped and try again.  
`ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT` was added in 8.0.13.
  - Error number: 3746; Symbol: `ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT`; SQLSTATE: HY000  
Message: Changing @@global.binlog\_format or @@persist.binlog\_format is disallowed when any replication channel has open temporary table(s). You could wait until Replica\_open\_temp\_tables = 0 and try again  
`ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT` was added in 8.0.13.
  - Error number: 3747; Symbol: `ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT`; SQLSTATE: HY000  
Message: Changing @@global.binlog\_format or @@persist.binlog\_format is disallowed when any replication channel applier thread is running. You could execute STOP REPLICAS SQL\_THREAD and try again.  
`ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT` was added in 8.0.13.
  - Error number: 3748; Symbol: `ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR`; SQLSTATE: HY000  
Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog\_format=STATEMENT.

---

`ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR` was added in 8.0.13.

- Error number: 3750; Symbol: `ER_TABLE_WITHOUT_PK`; SQLSTATE: HY000

Message: Unable to create or change a table without a primary key, when the system variable 'sql\_require\_primary\_key' is set. Add a primary key to the table or unset this variable to avoid this message. Note that tables without a primary key can cause performance problems in row-based replication, so please consult your DBA before changing this setting.

`ER_TABLE_WITHOUT_PK` was added in 8.0.13.

- Error number: 3751; Symbol: `WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX`; SQLSTATE: 01000

Message: Data truncated for functional index '%s' at row %ld

`WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX` was added in 8.0.13, removed after 8.0.16.

- Error number: 3751; Symbol: `ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX`; SQLSTATE: 01000

Message: Data truncated for functional index '%s' at row %ld

`ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX` was added in 8.0.17.

- Error number: 3752; Symbol: `ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX`; SQLSTATE: 22003

Message: Value is out of range for functional index '%s' at row %ld

`ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX` was added in 8.0.13.

- Error number: 3753; Symbol: `ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTION`; SQLSTATE: 42000

Message: Cannot create a functional index on a function that returns a JSON or GEOMETRY value.

`ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTION` was added in 8.0.13.

- Error number: 3754; Symbol: `ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT`; SQLSTATE: HY000

Message: Functional index '%s' cannot refer to an auto-increment column.

`ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT` was added in 8.0.13.

- Error number: 3755; Symbol: `ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX`; SQLSTATE: HY000

Message: Cannot drop column '%s' because it is used by a functional index. In order to drop the column, you must remove the functional index.

`ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX` was added in 8.0.13.

- Error number: 3756; Symbol: `ER_FUNCTIONAL_INDEX_PRIMARY_KEY`; SQLSTATE: HY000

Message: The primary key cannot be a functional index

`ER_FUNCTIONAL_INDEX_PRIMARY_KEY` was added in 8.0.13.

- 
- Error number: 3757; Symbol: `ER_FUNCTIONAL_INDEX_ON_LOB`; SQLSTATE: `HY000`  
  
Message: Cannot create a functional index on an expression that returns a BLOB or TEXT. Please consider using CAST.  
  
`ER_FUNCTIONAL_INDEX_ON_LOB` was added in 8.0.13.
  - Error number: 3758; Symbol: `ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`  
  
Message: Expression of functional index '%s' contains a disallowed function.  
  
`ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.13.
  - Error number: 3759; Symbol: `ER_FULLTEXT_FUNCTIONAL_INDEX`; SQLSTATE: `HY000`  
  
Message: Fulltext functional index is not supported.  
  
`ER_FULLTEXT_FUNCTIONAL_INDEX` was added in 8.0.13.
  - Error number: 3760; Symbol: `ER_SPATIAL_FUNCTIONAL_INDEX`; SQLSTATE: `HY000`  
  
Message: Spatial functional index is not supported.  
  
`ER_SPATIAL_FUNCTIONAL_INDEX` was added in 8.0.13.
  - Error number: 3761; Symbol: `ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX`; SQLSTATE: `HY000`  
  
Message: The used storage engine cannot index the expression '%s'.  
  
`ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX` was added in 8.0.13.
  - Error number: 3762; Symbol: `ER_FUNCTIONAL_INDEX_ON_FIELD`; SQLSTATE: `HY000`  
  
Message: Functional index on a column is not supported. Consider using a regular index instead.  
  
`ER_FUNCTIONAL_INDEX_ON_FIELD` was added in 8.0.13.
  - Error number: 3763; Symbol: `ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`  
  
Message: Expression of generated column '%s' contains a disallowed function: %s.  
  
`ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.13.
  - Error number: 3764; Symbol: `ER_GENERATED_COLUMN_ROW_VALUE`; SQLSTATE: `HY000`  
  
Message: Expression of generated column '%s' cannot refer to a row value.  
  
`ER_GENERATED_COLUMN_ROW_VALUE` was added in 8.0.13.
  - Error number: 3765; Symbol: `ER_GENERATED_COLUMN_VARIABLES`; SQLSTATE: `HY000`  
  
Message: Expression of generated column '%s' cannot refer user or system variables.  
  
`ER_GENERATED_COLUMN_VARIABLES` was added in 8.0.13.



- 
- Error number: 3766; Symbol: [ER\\_DEPENDENT\\_BY\\_DEFAULT\\_GENERATED\\_VALUE](#); SQLSTATE: HY000

Message: Column '%s' of table '%s' has a default value expression dependency and cannot be dropped or renamed.

[ER\\_DEPENDENT\\_BY\\_DEFAULT\\_GENERATED\\_VALUE](#) was added in 8.0.13.

- Error number: 3767; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_NON\\_PRIOR](#); SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to a column defined after it if that column is a generated column or has an expression as default value.

[ER\\_DEFAULT\\_VAL\\_GENERATED\\_NON\\_PRIOR](#) was added in 8.0.13.

- Error number: 3768; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_REF\\_AUTO\\_INC](#); SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to an auto-increment column.

[ER\\_DEFAULT\\_VAL\\_GENERATED\\_REF\\_AUTO\\_INC](#) was added in 8.0.13.

- Error number: 3769; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000

Message: Default value expression of column '%s' contains a disallowed function.

[ER\\_DEFAULT\\_VAL\\_GENERATED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#) was added in 8.0.13.

- Error number: 3770; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_NAMED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000

Message: Default value expression of column '%s' contains a disallowed function: %s.

[ER\\_DEFAULT\\_VAL\\_GENERATED\\_NAMED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#) was added in 8.0.13.

- Error number: 3771; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_ROW\\_VALUE](#); SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to a row value.

[ER\\_DEFAULT\\_VAL\\_GENERATED\\_ROW\\_VALUE](#) was added in 8.0.13.

- Error number: 3772; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_VARIABLES](#); SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer user or system variables.

[ER\\_DEFAULT\\_VAL\\_GENERATED\\_VARIABLES](#) was added in 8.0.13.

- Error number: 3773; Symbol: [ER\\_DEFAULT\\_AS\\_VAL\\_GENERATED](#); SQLSTATE: HY000

Message: DEFAULT function cannot be used with default value expressions

[ER\\_DEFAULT\\_AS\\_VAL\\_GENERATED](#) was added in 8.0.13.

- Error number: 3774; Symbol: [ER\\_UNSUPPORTED\\_ACTION\\_ON\\_DEFAULT\\_VAL\\_GENERATED](#); SQLSTATE: HY000

Message: '%s' is not supported for default value expressions.

[ER\\_UNSUPPORTED\\_ACTION\\_ON\\_DEFAULT\\_VAL\\_GENERATED](#) was added in 8.0.13.

- 
- Error number: 3775; Symbol: `ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION`; SQLSTATE: `HY000`  
  
Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.  
  
`ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION` was added in 8.0.13.
  - Error number: 3776; Symbol: `ER_FK_CANNOT_CHANGE_ENGINE`; SQLSTATE: `HY000`  
  
Message: Cannot change table's storage engine because the table participates in a foreign key constraint.  
  
`ER_FK_CANNOT_CHANGE_ENGINE` was added in 8.0.13.
  - Error number: 3777; Symbol: `ER_WARN_DEPRECATED_USER_SET_EXPR`; SQLSTATE: `HY000`  
  
Message: Setting user variables within expressions is deprecated and will be removed in a future release. Consider alternatives: 'SET variable=expression, ...', or 'SELECT expression(s) INTO variables(s)'.  
  
`ER_WARN_DEPRECATED_USER_SET_EXPR` was added in 8.0.13.
  - Error number: 3778; Symbol: `ER_WARN_DEPRECATED_UTF8MB3_COLLATION`; SQLSTATE: `HY000`  
  
Message: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.  
  
`ER_WARN_DEPRECATED_UTF8MB3_COLLATION` was added in 8.0.13.
  - Error number: 3779; Symbol: `ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX`; SQLSTATE: `HY000`  
  
Message: Nested comment syntax is deprecated and will be removed in a future release.  
  
`ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX` was added in 8.0.13.
  - Error number: 3780; Symbol: `ER_FK_INCOMPATIBLE_COLUMNS`; SQLSTATE: `HY000`  
  
Message: Referencing column '%s' and referenced column '%s' in foreign key constraint '%s' are incompatible.  
  
`ER_FK_INCOMPATIBLE_COLUMNS` was added in 8.0.14.
  - Error number: 3781; Symbol: `ER_GR_HOLD_WAIT_TIMEOUT`; SQLSTATE: `HY000`  
  
Message: Timeout exceeded for held statement while new Group Replication primary member is applying backlog.  
  
`ER_GR_HOLD_WAIT_TIMEOUT` was added in 8.0.14.
  - Error number: 3782; Symbol: `ER_GR_HOLD_KILLED`; SQLSTATE: `HY000`  
  
Message: Held statement aborted because Group Replication plugin got shut down or thread was killed while new primary member was applying backlog.  
  
`ER_GR_HOLD_KILLED` was added in 8.0.14.
  - Error number: 3783; Symbol: `ER_GR_HOLD_MEMBER_STATUS_ERROR`; SQLSTATE: `HY000`

---

Message: Held statement was aborted due to member being in error state, while backlog is being applied during Group Replication primary election.

`ER_GR_HOLD_MEMBER_STATUS_ERROR` was added in 8.0.14.

- Error number: 3784; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY`; SQLSTATE: HY000

Message: Failed to fetch key from keyring, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY` was added in 8.0.14.

- Error number: 3785; Symbol: `ER_RPL_ENCRYPTION_KEY_NOT_FOUND`; SQLSTATE: HY000

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

`ER_RPL_ENCRYPTION_KEY_NOT_FOUND` was added in 8.0.14.

- Error number: 3786; Symbol: `ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY`; SQLSTATE: HY000

Message: Fetched an invalid key from keyring.

`ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY` was added in 8.0.14.

- Error number: 3787; Symbol: `ER_RPL_ENCRYPTION_HEADER_ERROR`; SQLSTATE: HY000

Message: Error reading a replication log encryption header: %s.

`ER_RPL_ENCRYPTION_HEADER_ERROR` was added in 8.0.14.

- Error number: 3788; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS`; SQLSTATE: HY000

Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.

`ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS` was added in 8.0.14.

- Error number: 3789; Symbol: `ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED`; SQLSTATE: HY000

Message: Key %s exists unexpected.

`ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED` was added in 8.0.14.

- Error number: 3790; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY`; SQLSTATE: HY000

Message: Failed to generate key, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY` was added in 8.0.14.

- Error number: 3791; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY`; SQLSTATE: HY000

Message: Failed to store key, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY` was added in 8.0.14.

- Error number: 3792; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY`; SQLSTATE: HY000

Message: Failed to remove key, please check if keyring is loaded.

---

`ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY` was added in 8.0.14.

- Error number: 3793; Symbol: `ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION`; SQLSTATE: HY000

Message: Failed to change binlog\_encryption value. %s.

`ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION` was added in 8.0.14.

- Error number: 3794; Symbol: `ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED`; SQLSTATE: HY000

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED` was added in 8.0.14.

- Error number: 3795; Symbol: `ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE`; SQLSTATE: HY000

Message: slow query log file format changed as requested, but setting will have no effect when not actually logging to a file.

`ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE` was added in 8.0.14.

- Error number: 3796; Symbol: `ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED`; SQLSTATE: HY000

Message: The option group\_replication\_consistency cannot be used on the current member state.

`ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED` was added in 8.0.14.

- Error number: 3797; Symbol: `ER_GRP_TRX_CONSISTENCY_BEFORE`; SQLSTATE: HY000

Message: Error while waiting for group transactions commit on group\_replication\_consistency='BEFORE'.

`ER_GRP_TRX_CONSISTENCY_BEFORE` was added in 8.0.14.

- Error number: 3798; Symbol: `ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN`; SQLSTATE: HY000

Message: Error while waiting for transactions with group\_replication\_consistency='AFTER' to commit.

`ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN` was added in 8.0.14.

- Error number: 3799; Symbol: `ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED`; SQLSTATE: HY000

Message: The Group Replication plugin is stopping, therefore new transactions are not allowed to start.

`ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED` was added in 8.0.14.

- Error number: 3800; Symbol: `ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED`; SQLSTATE: HY000

Message: Expression of functional index '%s' cannot refer to a row value.

`ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED` was added in 8.0.14.

- 
- Error number: 3801; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT`; SQLSTATE: HY000  
Message: Failed to encrypt content to write into binlog file: %s.  
`ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT` was added in 8.0.14.
  - Error number: 3802; Symbol: `ER_PAGE_TRACKING_NOT_STARTED`; SQLSTATE: HY000  
Message: Page Tracking is not started yet.  
`ER_PAGE_TRACKING_NOT_STARTED` was added in 8.0.16.
  - Error number: 3803; Symbol: `ER_PAGE_TRACKING_RANGE_NOT_TRACKED`; SQLSTATE: HY000  
Message: Tracking was not enabled for the LSN range specified  
`ER_PAGE_TRACKING_RANGE_NOT_TRACKED` was added in 8.0.16.
  - Error number: 3804; Symbol: `ER_PAGE_TRACKING_CANNOT_PURGE`; SQLSTATE: HY000  
Message: Cannot purge data when concurrent clone is in progress. Try later.  
`ER_PAGE_TRACKING_CANNOT_PURGE` was added in 8.0.16.
  - Error number: 3805; Symbol: `ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY`; SQLSTATE: HY000  
Message: Cannot rotate binary log master key when 'binlog-encryption' is off.  
`ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY` was added in 8.0.16.
  - Error number: 3806; Symbol: `ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION`; SQLSTATE: HY000  
Message: Unable to recover binary log master key, the combination of new\_master\_key\_seqno=%u, master\_key\_seqno=%u and old\_master\_key\_seqno=%u are wrong.  
`ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION` was added in 8.0.16.
  - Error number: 3807; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE_KEY`; SQLSTATE: HY000  
Message: Failed to operate binary log master key on keyring, please check if keyring is loaded. The statement had no effect: the old binary log master key is still in use, the keyring, binary and relay log files are unchanged, and the server could not start using a new binary log master key for encrypting new binary and relay log files.  
`ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE_KEY` was added in 8.0.16.
  - Error number: 3808; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOGS`; SQLSTATE: HY000  
Message: Failed to rotate one or more binary or relay log files. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.  
`ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOGS` was added in 8.0.16.
-

- 
- Error number: 3809; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT_LOG`; SQLSTATE: `HY000`

Message: %s. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.

`ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT_LOG` was added in 8.0.16.

- Error number: 3810; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_UNUSED_KEYS`; SQLSTATE: `HY000`

Message: Failed to remove unused binary log encryption keys from the keyring, please check if keyring is loaded. The unused binary log encryption keys may still exist in the keyring, and they will be removed upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

`ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_UNUSED_KEYS` was added in 8.0.16.

- Error number: 3811; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY`; SQLSTATE: `HY000`

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

`ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY` was added in 8.0.16.

- Error number: 3812; Symbol: `ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT`; SQLSTATE: `HY000`

Message: An expression of non-boolean type specified to a check constraint '%s'.

`ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT` was added in 8.0.16.

- Error number: 3813; Symbol: `ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMN`; SQLSTATE: `HY000`

Message: Column check constraint '%s' references other column.

`ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMN` was added in 8.0.16.

- Error number: 3814; Symbol: `ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: An expression of a check constraint '%s' contains disallowed function: %s.

`ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.16.

- Error number: 3815; Symbol: `ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: An expression of a check constraint '%s' contains disallowed function.

`ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.16.

- Error number: 3816; Symbol: `ER_CHECK_CONSTRAINT_VARIABLES`; SQLSTATE: `HY000`

Message: An expression of a check constraint '%s' cannot refer to a user or system variable.

---

`ER_CHECK_CONSTRAINT_VARIABLES` was added in 8.0.16.

- Error number: 3817; Symbol: `ER_CHECK_CONSTRAINT_ROW_VALUE`; SQLSTATE: HY000

Message: Check constraint '%s' cannot refer to a row value.

`ER_CHECK_CONSTRAINT_ROW_VALUE` was added in 8.0.16.

- Error number: 3818; Symbol: `ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN`; SQLSTATE: HY000

Message: Check constraint '%s' cannot refer to an auto-increment column.

`ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN` was added in 8.0.16.

- Error number: 3819; Symbol: `ER_CHECK_CONSTRAINT_VIOLATED`; SQLSTATE: HY000

Message: Check constraint '%s' is violated.

`ER_CHECK_CONSTRAINT_VIOLATED` was added in 8.0.16.

- Error number: 3820; Symbol: `ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN`; SQLSTATE: HY000

Message: Check constraint '%s' refers to non-existing column '%s'.

`ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN` was added in 8.0.16.

- Error number: 3821; Symbol: `ER_CHECK_CONSTRAINT_NOT_FOUND`; SQLSTATE: HY000

Message: Check constraint '%s' is not found in the table.

`ER_CHECK_CONSTRAINT_NOT_FOUND` was added in 8.0.16.

- Error number: 3822; Symbol: `ER_CHECK_CONSTRAINT_DUP_NAME`; SQLSTATE: HY000

Message: Duplicate check constraint name '%s'.

`ER_CHECK_CONSTRAINT_DUP_NAME` was added in 8.0.16.

- Error number: 3823; Symbol: `ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION_COLUMN`; SQLSTATE: HY000

Message: Column '%s' cannot be used in a check constraint '%s': needed in a foreign key constraint '%s' referential action.

`ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION_COLUMN` was added in 8.0.16.

- Error number: 3824; Symbol: `WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB`; SQLSTATE: HY000

Message: Creating an unencrypted table in a database with default encryption enabled.

`WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB` was added in 8.0.16.

- Error number: 3825; Symbol: `ER_INVALID_ENCRYPTION_REQUEST`; SQLSTATE: HY000

Message: Request to create %s table while using an %s tablespace.

`ER_INVALID_ENCRYPTION_REQUEST` was added in 8.0.16.

- 
- Error number: 3826; Symbol: `ER_CANNOT_SET_TABLE_ENCRYPTION`; SQLSTATE: HY000  
Message: Table encryption differ from its database default encryption, and user doesn't have enough privilege.  
`ER_CANNOT_SET_TABLE_ENCRYPTION` was added in 8.0.16.
  - Error number: 3827; Symbol: `ER_CANNOT_SET_DATABASE_ENCRYPTION`; SQLSTATE: HY000  
Message: Database default encryption differ from 'default\_table\_encryption' setting, and user doesn't have enough privilege.  
`ER_CANNOT_SET_DATABASE_ENCRYPTION` was added in 8.0.16.
  - Error number: 3828; Symbol: `ER_CANNOT_SET_TABLESPACE_ENCRYPTION`; SQLSTATE: HY000  
Message: Tablespace encryption differ from 'default\_table\_encryption' setting, and user doesn't have enough privilege.  
`ER_CANNOT_SET_TABLESPACE_ENCRYPTION` was added in 8.0.16.
  - Error number: 3829; Symbol: `ER_TABLESPACE_CANNOT_BE_ENCRYPTED`; SQLSTATE: HY000  
Message: This tablespace can't be encrypted, because one of table's schema has default encryption OFF and user doesn't have enough privilege.  
`ER_TABLESPACE_CANNOT_BE_ENCRYPTED` was added in 8.0.16.
  - Error number: 3830; Symbol: `ER_TABLESPACE_CANNOT_BE_DECRYPTED`; SQLSTATE: HY000  
Message: This tablespace can't be decrypted, because one of table's schema has default encryption ON and user doesn't have enough privilege.  
`ER_TABLESPACE_CANNOT_BE_DECRYPTED` was added in 8.0.16.
  - Error number: 3831; Symbol: `ER_TABLESPACE_TYPE_UNKNOWN`; SQLSTATE: HY000  
Message: Cannot determine the type of the tablespace named '%s'.  
`ER_TABLESPACE_TYPE_UNKNOWN` was added in 8.0.16.
  - Error number: 3832; Symbol: `ER_TARGET_TABLESPACE_UNENCRYPTED`; SQLSTATE: HY000  
Message: Source tablespace is encrypted but target tablespace is not.  
`ER_TARGET_TABLESPACE_UNENCRYPTED` was added in 8.0.16.
  - Error number: 3833; Symbol: `ER_CANNOT_USE_ENCRYPTION_CLAUSE`; SQLSTATE: HY000  
Message: ENCRYPTION clause is not valid for %s tablespace.  
`ER_CANNOT_USE_ENCRYPTION_CLAUSE` was added in 8.0.16.
  - Error number: 3834; Symbol: `ER_INVALID_MULTIPLE_CLAUSES`; SQLSTATE: HY000  
Message: Multiple %s clauses  
`ER_INVALID_MULTIPLE_CLAUSES` was added in 8.0.16.
  - Error number: 3835; Symbol: `ER_UNSUPPORTED_USE_OF_GRANT_AS`; SQLSTATE: HY000



---

Message: GRANT ... AS is currently supported only for global privileges.

[ER\\_UNSUPPORTED\\_USE\\_OF\\_GRANT\\_AS](#) was added in 8.0.16.

- Error number: [3836](#); Symbol: [ER\\_UNKNOWN\\_AUTH\\_ID\\_OR\\_ACCESS\\_DENIED\\_FOR\\_GRANT\\_AS](#); SQLSTATE: [HY000](#)

Message: Either some of the authorization IDs in the AS clause are invalid or the current user lacks privileges to execute the statement.

[ER\\_UNKNOWN\\_AUTH\\_ID\\_OR\\_ACCESS\\_DENIED\\_FOR\\_GRANT\\_AS](#) was added in 8.0.16.

- Error number: [3837](#); Symbol: [ER\\_DEPENDENT\\_BY\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: [HY000](#)

Message: Column '%s' has a functional index dependency and cannot be dropped or renamed.

[ER\\_DEPENDENT\\_BY\\_FUNCTIONAL\\_INDEX](#) was added in 8.0.17.

- Error number: [3838](#); Symbol: [ER\\_PLUGIN\\_NOT\\_EARLY](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.

[ER\\_PLUGIN\\_NOT\\_EARLY](#) was added in 8.0.17.

- Error number: [3839](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_START\\_SUBDIR\\_PATH](#); SQLSTATE: [HY000](#)

Message: Redo log archiving start prohibits path name in 'subdir' argument

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_START\\_SUBDIR\\_PATH](#) was added in 8.0.17.

- Error number: [3840](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_START\\_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: Redo log archiving start timed out

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_START\\_TIMEOUT](#) was added in 8.0.17.

- Error number: [3841](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIRS\\_INVALID](#); SQLSTATE: [HY000](#)

Message: Server variable 'innodb\_redo\_log\_archive\_dirs' is NULL or empty

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIRS\\_INVALID](#) was added in 8.0.17.

- Error number: [3842](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_LABEL\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Label '%s' not found in server variable 'innodb\_redo\_log\_archive\_dirs'

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_LABEL\\_NOT\\_FOUND](#) was added in 8.0.17.

- Error number: [3843](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: Directory is empty after label '%s' in server variable 'innodb\_redo\_log\_archive\_dirs'

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_EMPTY](#) was added in 8.0.17.

- Error number: [3844](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_NO\\_SUCH\\_DIR](#); SQLSTATE: [HY000](#)

---

Message: Redo log archive directory '%s' does not exist or is not a directory

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_NO\\_SUCH\\_DIR](#) was added in 8.0.17.

- Error number: [3845](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_CLASH](#); SQLSTATE: [HY000](#)

Message: Redo log archive directory '%s' is in, under, or over server directory '%s' - '%s'

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_CLASH](#) was added in 8.0.17.

- Error number: [3846](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_PERMISSIONS](#); SQLSTATE: [HY000](#)

Message: Redo log archive directory '%s' is accessible to all OS users

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_PERMISSIONS](#) was added in 8.0.17.

- Error number: [3847](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_FILE\\_CREATE](#); SQLSTATE: [HY000](#)

Message: Cannot create redo log archive file '%s' (OS errno: %d - %s)

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_FILE\\_CREATE](#) was added in 8.0.17.

- Error number: [3848](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_ACTIVE](#); SQLSTATE: [HY000](#)

Message: Redo log archiving has been started on '%s' - Call innodb\_redo\_log\_archive\_stop() first

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_ACTIVE](#) was added in 8.0.17.

- Error number: [3849](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_INACTIVE](#); SQLSTATE: [HY000](#)

Message: Redo log archiving is not active

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_INACTIVE](#) was added in 8.0.17.

- Error number: [3850](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Redo log archiving failed: %s

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_FAILED](#) was added in 8.0.17.

- Error number: [3851](#); Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_SESSION](#); SQLSTATE: [HY000](#)

Message: Redo log archiving has not been started by this session

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_SESSION](#) was added in 8.0.17.

- Error number: [3852](#); Symbol: [ER\\_STD\\_REGEX\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Regex error: %s in function %s.

[ER\\_STD\\_REGEX\\_ERROR](#) was added in 8.0.17.

- Error number: [3853](#); Symbol: [ER\\_INVALID\\_JSON\\_TYPE](#); SQLSTATE: [22032](#)

Message: Invalid JSON type in argument %u to function %s; an %s is required.

[ER\\_INVALID\\_JSON\\_TYPE](#) was added in 8.0.17.

- 
- Error number: 3854; Symbol: `ER_CANNOT_CONVERT_STRING`; SQLSTATE: HY000  
Message: Cannot convert string '%s' from %s to %s  
`ER_CANNOT_CONVERT_STRING` was added in 8.0.17.
  - Error number: 3855; Symbol: `ER_DEPENDENT_BY_PARTITION_FUNC`; SQLSTATE: HY000  
Message: Column '%s' has a partitioning function dependency and cannot be dropped or renamed.  
`ER_DEPENDENT_BY_PARTITION_FUNC` was added in 8.0.17.
  - Error number: 3856; Symbol: `ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT`; SQLSTATE: HY000  
Message: AUTO\_INCREMENT support for FLOAT/DOUBLE columns is deprecated and will be removed in a future release. Consider removing AUTO\_INCREMENT from column '%s'.  
`ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT` was added in 8.0.17.
  - Error number: 3857; Symbol: `ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKUP`; SQLSTATE: HY000  
Message: Cannot stop the slave SQL thread while the instance is locked for backup. Try running `UNLOCK INSTANCE` first.  
`ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKUP` was added in 8.0.17, removed after 8.0.32.
  - Error number: 3857; Symbol: `ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP`; SQLSTATE: HY000  
Message: Cannot stop the replica SQL thread while the instance is locked for backup. Try running `UNLOCK INSTANCE` first.  
`ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP` was added in 8.0.33.
  - Error number: 3858; Symbol: `ER_WARN_DEPRECATED_FLOAT_DIGITS`; SQLSTATE: HY000  
Message: Specifying number of digits for floating point data types is deprecated and will be removed in a future release.  
`ER_WARN_DEPRECATED_FLOAT_DIGITS` was added in 8.0.17.
  - Error number: 3859; Symbol: `ER_WARN_DEPRECATED_FLOAT_UNSIGNED`; SQLSTATE: HY000  
Message: UNSIGNED for decimal and floating point data types is deprecated and support for it will be removed in a future release.  
`ER_WARN_DEPRECATED_FLOAT_UNSIGNED` was added in 8.0.17.
  - Error number: 3860; Symbol: `ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH`; SQLSTATE: HY000  
Message: Integer display width is deprecated and will be removed in a future release.  
`ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH` was added in 8.0.17.

- 
- Error number: 3861; Symbol: `ER_WARN_DEPRECATED_ZEROFILL`; SQLSTATE: `HY000`  
Message: The ZEROFILL attribute is deprecated and will be removed in a future release. Use the LPAD function to zero-pad numbers, or store the formatted numbers in a CHAR column.  
`ER_WARN_DEPRECATED_ZEROFILL` was added in 8.0.17.
  - Error number: 3862; Symbol: `ER_CLONE_DONOR`; SQLSTATE: `HY000`  
Message: Clone Donor Error: %s.  
`ER_CLONE_DONOR` was added in 8.0.17.
  - Error number: 3863; Symbol: `ER_CLONE_PROTOCOL`; SQLSTATE: `HY000`  
Message: Clone received unexpected response from Donor : %s.  
`ER_CLONE_PROTOCOL` was added in 8.0.17.
  - Error number: 3864; Symbol: `ER_CLONE_DONOR_VERSION`; SQLSTATE: `HY000`  
Message: Clone Donor MySQL version: %s is different from Recipient MySQL version %s.  
`ER_CLONE_DONOR_VERSION` was added in 8.0.17.
  - Error number: 3865; Symbol: `ER_CLONE_OS`; SQLSTATE: `HY000`  
Message: Clone Donor OS: %s is different from Recipient OS: %s.  
`ER_CLONE_OS` was added in 8.0.17.
  - Error number: 3866; Symbol: `ER_CLONE_PLATFORM`; SQLSTATE: `HY000`  
Message: Clone Donor platform: %s is different from Recipient platform: %s.  
`ER_CLONE_PLATFORM` was added in 8.0.17.
  - Error number: 3867; Symbol: `ER_CLONE_CHARSET`; SQLSTATE: `HY000`  
Message: Clone Donor collation: %s is unavailable in Recipient.  
`ER_CLONE_CHARSET` was added in 8.0.17.
  - Error number: 3868; Symbol: `ER_CLONE_CONFIG`; SQLSTATE: `HY000`  
Message: Clone Configuration %s: Donor value: %s is different from Recipient value: %s.  
`ER_CLONE_CONFIG` was added in 8.0.17.
  - Error number: 3869; Symbol: `ER_CLONE_SYS_CONFIG`; SQLSTATE: `HY000`  
Message: Clone system configuration: %s  
`ER_CLONE_SYS_CONFIG` was added in 8.0.17.
  - Error number: 3870; Symbol: `ER_CLONE_PLUGIN_MATCH`; SQLSTATE: `HY000`  
Message: Clone Donor plugin %s is not active in Recipient.  
`ER_CLONE_PLUGIN_MATCH` was added in 8.0.17.

- 
- Error number: [3871](#); Symbol: [ER\\_CLONE\\_LOOPBACK](#); SQLSTATE: [HY000](#)  
Message: Clone cannot use loop back connection while cloning into current data directory.  
[ER\\_CLONE\\_LOOPBACK](#) was added in 8.0.17.
  - Error number: [3872](#); Symbol: [ER\\_CLONE\\_ENCRYPTION](#); SQLSTATE: [HY000](#)  
Message: Clone needs SSL connection for encrypted table.  
[ER\\_CLONE\\_ENCRYPTION](#) was added in 8.0.17.
  - Error number: [3873](#); Symbol: [ER\\_CLONE\\_DISK\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Clone estimated database size is %s. Available space %s is not enough.  
[ER\\_CLONE\\_DISK\\_SPACE](#) was added in 8.0.17.
  - Error number: [3874](#); Symbol: [ER\\_CLONE\\_IN\\_PROGRESS](#); SQLSTATE: [HY000](#)  
Message: Concurrent clone in progress. Please try after clone is complete.  
[ER\\_CLONE\\_IN\\_PROGRESS](#) was added in 8.0.17.
  - Error number: [3875](#); Symbol: [ER\\_CLONE\\_DISALLOWED](#); SQLSTATE: [HY000](#)  
Message: The clone operation cannot be executed when %s.  
[ER\\_CLONE\\_DISALLOWED](#) was added in 8.0.17.
  - Error number: [3876](#); Symbol: [ER\\_CANNOT\\_GRANT\\_ROLES\\_TO\\_ANONYMOUS\\_USER](#); SQLSTATE: [HY000](#)  
Message: Cannot grant roles to an anonymous user.  
[ER\\_CANNOT\\_GRANT\\_ROLES\\_TO\\_ANONYMOUS\\_USER](#) was added in 8.0.16.
  - Error number: [3877](#); Symbol: [ER\\_SECONDARY\\_ENGINE\\_PLUGIN](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_SECONDARY\\_ENGINE\\_PLUGIN](#) was added in 8.0.14.
  - Error number: [3878](#); Symbol: [ER\\_SECOND\\_PASSWORD\\_CANNOT\\_BE\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: Empty password can not be retained as second password for user '%s'@'%s'.  
[ER\\_SECOND\\_PASSWORD\\_CANNOT\\_BE\\_EMPTY](#) was added in 8.0.14.
  - Error number: [3879](#); Symbol: [ER\\_DB\\_ACCESS\\_DENIED](#); SQLSTATE: [HY000](#)  
Message: Access denied for AuthId `%s`@`%s` to database '%s'.  
[ER\\_DB\\_ACCESS\\_DENIED](#) was added in 8.0.16.
  - Error number: [3880](#); Symbol: [ER\\_DA\\_AUTH\\_ID\\_WITH\\_SYSTEM\\_USER\\_PRIV\\_IN\\_MANDATORY\\_ROLES](#); SQLSTATE: [HY000](#)  
Message: Cannot set mandatory\_roles: AuthId `%s`@`%s` has '%s' privilege.  
[ER\\_DA\\_AUTH\\_ID\\_WITH\\_SYSTEM\\_USER\\_PRIV\\_IN\\_MANDATORY\\_ROLES](#) was added in 8.0.17.

- 
- Error number: 3881; Symbol: `ER_DA_RPL_GTID_TABLE_CANNOT_OPEN`; SQLSTATE: `HY000`  
Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.  
`ER_DA_RPL_GTID_TABLE_CANNOT_OPEN` was added in 8.0.17.
  - Error number: 3882; Symbol: `ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT`; SQLSTATE: `SU001`  
Message: The geometry passed to function %s is in SRID 0, which doesn't specify a length unit. Can't convert to '%s'.  
`ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT` was added in 8.0.14.
  - Error number: 3883; Symbol: `ER_DA_PLUGIN_INSTALL_ERROR`; SQLSTATE: `HY000`  
Message: Error installing plugin '%s': %s  
`ER_DA_PLUGIN_INSTALL_ERROR` was added in 8.0.17.
  - Error number: 3884; Symbol: `ER_NO_SESSION_TEMP`; SQLSTATE: `HY000`  
Message: Storage engine could not allocate temporary tablespace for this session.  
`ER_NO_SESSION_TEMP` was added in 8.0.13.
  - Error number: 3885; Symbol: `ER_DA_UNKNOWN_ERROR_NUMBER`; SQLSTATE: `HY000`  
Message: Got unknown error: %d  
`ER_DA_UNKNOWN_ERROR_NUMBER` was added in 8.0.17.
  - Error number: 3886; Symbol: `ER_COLUMN_CHANGE_SIZE`; SQLSTATE: `HY000`  
Message: Could not change column '%s' of table '%s'. The resulting size of index '%s' would exceed the max key length of %d bytes.  
`ER_COLUMN_CHANGE_SIZE` was added in 8.0.14.
  - Error number: 3887; Symbol: `ER_REGEX_INVALID_CAPTURE_GROUP_NAME`; SQLSTATE: `HY000`  
Message: A capture group has an invalid name.  
`ER_REGEX_INVALID_CAPTURE_GROUP_NAME` was added in 8.0.11.
  - Error number: 3888; Symbol: `ER_DA_SSL_LIBRARY_ERROR`; SQLSTATE: `HY000`  
Message: Failed to set up SSL because of the following SSL library error: %s  
`ER_DA_SSL_LIBRARY_ERROR` was added in 8.0.17.
  - Error number: 3889; Symbol: `ER_SECONDARY_ENGINE`; SQLSTATE: `HY000`  
Message: Secondary engine operation failed. %s.  
`ER_SECONDARY_ENGINE` was added in 8.0.13.
  - Error number: 3890; Symbol: `ER_SECONDARY_ENGINE_DDL`; SQLSTATE: `HY000`  
Message: DDLs on a table with a secondary engine defined are not allowed.

---

[ER\\_SECONDARY\\_ENGINE\\_DDL](#) was added in 8.0.13.

- Error number: [3891](#); Symbol: [ER\\_INCORRECT\\_CURRENT\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Incorrect current password. Specify the correct password which has to be replaced.

[ER\\_INCORRECT\\_CURRENT\\_PASSWORD](#) was added in 8.0.13.

- Error number: [3892](#); Symbol: [ER\\_MISSING\\_CURRENT\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Current password needs to be specified in the REPLACE clause in order to change it.

[ER\\_MISSING\\_CURRENT\\_PASSWORD](#) was added in 8.0.13.

- Error number: [3893](#); Symbol: [ER\\_CURRENT\\_PASSWORD\\_NOT\\_REQUIRED](#); SQLSTATE: [HY000](#)

Message: Do not specify the current password while changing it for other users.

[ER\\_CURRENT\\_PASSWORD\\_NOT\\_REQUIRED](#) was added in 8.0.13.

- Error number: [3894](#); Symbol: [ER\\_PASSWORD\\_CANNOT\\_BE\\_RETAINED\\_ON\\_PLUGIN\\_CHANGE](#); SQLSTATE: [HY000](#)

Message: Current password can not be retained for user '%s'@'%s' because authentication plugin is being changed.

[ER\\_PASSWORD\\_CANNOT\\_BE\\_RETAINED\\_ON\\_PLUGIN\\_CHANGE](#) was added in 8.0.14.

- Error number: [3895](#); Symbol: [ER\\_CURRENT\\_PASSWORD\\_CANNOT\\_BE\\_RETAINED](#); SQLSTATE: [HY000](#)

Message: Current password can not be retained for user '%s'@'%s' because new password is empty.

[ER\\_CURRENT\\_PASSWORD\\_CANNOT\\_BE\\_RETAINED](#) was added in 8.0.14.

- Error number: [3896](#); Symbol: [ER\\_PARTIAL\\_REVOKES\\_EXIST](#); SQLSTATE: [HY000](#)

Message: At least one partial revoke exists on a database. The system variable '@@partial\_revokes' must be set to ON.

[ER\\_PARTIAL\\_REVOKES\\_EXIST](#) was added in 8.0.16.

- Error number: [3897](#); Symbol: [ER\\_CANNOT\\_GRANT\\_SYSTEM\\_PRIV\\_TO\\_MANDATORY\\_ROLE](#); SQLSTATE: [HY000](#)

Message: AuthId '%s'@'%s' is set as mandatory\_roles. Cannot grant the '%s' privilege.

[ER\\_CANNOT\\_GRANT\\_SYSTEM\\_PRIV\\_TO\\_MANDATORY\\_ROLE](#) was added in 8.0.16.

- Error number: [3898](#); Symbol: [ER\\_XA\\_REPLICATION\\_FILTERS](#); SQLSTATE: [HY000](#)

Message: The use of replication filters with XA transactions is not supported, and can lead to an undefined state in the replica.

[ER\\_XA\\_REPLICATION\\_FILTERS](#) was added in 8.0.12.

- Error number: [3899](#); Symbol: [ER\\_UNSUPPORTED\\_SQL\\_MODE](#); SQLSTATE: [HY000](#)

Message: sql\_mode=0x%08x is not supported.

---

`ER_UNSUPPORTED_SQL_MODE` was added in 8.0.11.

- Error number: 3900; Symbol: `ER_REGEX_INVALID_FLAG`; SQLSTATE: HY000

Message: Invalid match mode flag in regular expression.

`ER_REGEX_INVALID_FLAG` was added in 8.0.12.

- Error number: 3901; Symbol: `ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS`; SQLSTATE: HY000

Message: '%s' privilege for database '%s' exists both as partial revoke and mysql.db simultaneously. It could mean that the 'mysql' schema is corrupted.

`ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS` was added in 8.0.16.

- Error number: 3902; Symbol: `ER_UNIT_NOT_FOUND`; SQLSTATE: SU001

Message: There's no unit of measure named '%s'.

`ER_UNIT_NOT_FOUND` was added in 8.0.14.

- Error number: 3903; Symbol: `ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX`; SQLSTATE: 22018

Message: Invalid JSON value for CAST for functional index '%s'.

`ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX` was added in 8.0.16.

- Error number: 3904; Symbol: `ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX`; SQLSTATE: 22003

Message: Out of range JSON value for CAST for functional index '%s'.

`ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX` was added in 8.0.16.

- Error number: 3905; Symbol: `ER_EXCEEDED_MV_KEYS_NUM`; SQLSTATE: HY000

Message: Exceeded max number of values per record for multi-valued index '%s' by %u value(s).

`ER_EXCEEDED_MV_KEYS_NUM` was added in 8.0.16.

- Error number: 3906; Symbol: `ER_EXCEEDED_MV_KEYS_SPACE`; SQLSTATE: HY000

Message: Exceeded max total length of values per record for multi-valued index '%s' by %u bytes.

`ER_EXCEEDED_MV_KEYS_SPACE` was added in 8.0.16.

- Error number: 3907; Symbol: `ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG`; SQLSTATE: 22001

Message: Data too long for functional index '%s'.

`ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG` was added in 8.0.16.

- Error number: 3908; Symbol: `ER_WRONG_MVI_VALUE`; SQLSTATE: HY000

Message: Cannot store an array or an object in a scalar key part of the index '%s'.

`ER_WRONG_MVI_VALUE` was added in 8.0.16.



- 
- Error number: [3909](#); Symbol: [ER\\_WARN\\_FUNC\\_INDEX\\_NOT\\_APPLICABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot use functional index '%s' due to type or collation conversion.  
[ER\\_WARN\\_FUNC\\_INDEX\\_NOT\\_APPLICABLE](#) was added in 8.0.16.
  - Error number: [3910](#); Symbol: [ER\\_GRP\\_RPL\\_UDF\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The function '%s' failed. %s  
[ER\\_GRP\\_RPL\\_UDF\\_ERROR](#) was added in 8.0.13.
  - Error number: [3911](#); Symbol: [ER\\_UPDATE\\_GTID\\_PURGED\\_WITH\\_GR](#); SQLSTATE: [HY000](#)  
Message: Cannot update GTID\_PURGED with the Group Replication plugin running  
[ER\\_UPDATE\\_GTID\\_PURGED\\_WITH\\_GR](#) was added in 8.0.12.
  - Error number: [3912](#); Symbol: [ER\\_GROUPING\\_ON\\_TIMESTAMP\\_IN\\_DST](#); SQLSTATE: [HY000](#)  
Message: Grouping on temporal is non-deterministic for timezones having DST. Please consider switching to UTC for this query.  
[ER\\_GROUPING\\_ON\\_TIMESTAMP\\_IN\\_DST](#) was added in 8.0.17.
  - Error number: [3913](#); Symbol: [ER\\_TABLE\\_NAME\\_CAUSES\\_TOO\\_LONG\\_PATH](#); SQLSTATE: [HY000](#)  
Message: Long database name and identifier for object resulted in a path length too long for table '%s'. Please check the path limit for your OS.  
[ER\\_TABLE\\_NAME\\_CAUSES\\_TOO\\_LONG\\_PATH](#) was added in 8.0.4.
  - Error number: [3914](#); Symbol: [ER\\_AUDIT\\_LOG\\_INSUFFICIENT\\_PRIVILEGE](#); SQLSTATE: [HY000](#)  
Message: Request ignored for '%s'@'%s'. Role needed to perform operation: '%s'  
[ER\\_AUDIT\\_LOG\\_INSUFFICIENT\\_PRIVILEGE](#) was added in 8.0.16.
  - Error number: [3916](#); Symbol: [ER\\_DA\\_GRP\\_RPL\\_STARTED\\_AUTO\\_REJOIN](#); SQLSTATE: [HY000](#)  
Message: Started auto-rejoin procedure attempt %lu of %lu  
[ER\\_DA\\_GRP\\_RPL\\_STARTED\\_AUTO\\_REJOIN](#) was added in 8.0.17.
  - Error number: [3917](#); Symbol: [ER\\_SYSVAR\\_CHANGE\\_DURING\\_QUERY](#); SQLSTATE: [HY000](#)  
Message: A plugin was loaded or unloaded during a query, a system variable table was changed.  
[ER\\_SYSVAR\\_CHANGE\\_DURING\\_QUERY](#) was added in 8.0.18.
  - Error number: [3918](#); Symbol: [ER\\_GLOBSTAT\\_CHANGE\\_DURING\\_QUERY](#); SQLSTATE: [HY000](#)  
Message: A plugin was loaded or unloaded during a query, a global status variable was changed.  
[ER\\_GLOBSTAT\\_CHANGE\\_DURING\\_QUERY](#) was added in 8.0.18.
  - Error number: [3919](#); Symbol: [ER\\_GRP\\_RPL\\_MESSAGE\\_SERVICE\\_INIT\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: The START GROUP\_REPLICATION command failed to start its message service.

---

`ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE` was added in 8.0.18.

- Error number: 3920; Symbol: `ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CLIENT`; SQLSTATE: `HY000`

Message: Invalid MASTER\_COMPRESSION\_ALGORITHMS '%s' for channel '%s'.

`ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CLIENT` was added in 8.0.18, removed after 8.0.32.

- Error number: 3920; Symbol: `ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_CLIENT`; SQLSTATE: `HY000`

Message: Invalid SOURCE\_COMPRESSION\_ALGORITHMS '%s' for channel '%s'.

`ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_CLIENT` was added in 8.0.33.

- Error number: 3921; Symbol: `ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT`; SQLSTATE: `HY000`

Message: Invalid MASTER\_ZSTD\_COMPRESSION\_LEVEL %u for channel '%s'.

`ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT` was added in 8.0.18, removed after 8.0.32.

- Error number: 3921; Symbol: `ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT`; SQLSTATE: `HY000`

Message: Invalid SOURCE\_ZSTD\_COMPRESSION\_LEVEL %u for channel '%s'.

`ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT` was added in 8.0.33.

- Error number: 3922; Symbol: `ER_WRONG_COMPRESSION_ALGORITHM_CLIENT`; SQLSTATE: `HY000`

Message: Invalid compression algorithm '%s'.

`ER_WRONG_COMPRESSION_ALGORITHM_CLIENT` was added in 8.0.18.

- Error number: 3923; Symbol: `ER_WRONG_COMPRESSION_LEVEL_CLIENT`; SQLSTATE: `HY000`

Message: Invalid zstd compression level for algorithm '%s'.

`ER_WRONG_COMPRESSION_LEVEL_CLIENT` was added in 8.0.18.

- Error number: 3924; Symbol: `ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT`; SQLSTATE: `HY000`

Message: Specified compression algorithm list '%s' exceeds total count of 3 for channel '%s'.

`ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT` was added in 8.0.18, removed after 8.0.32.

- Error number: 3924; Symbol: `ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT`; SQLSTATE: `HY000`

Message: Specified compression algorithm list '%s' exceeds total count of 3 for channel '%s'.

`ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT` was added in 8.0.33.

- 
- Error number: 3925; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS`; SQLSTATE: HY000  
  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to ``@`%s`, but anonymous users are disallowed for PRIVILEGE\_CHECKS\_USER.  
  
`ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS` was added in 8.0.18.
  - Error number: 3926; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST`; SQLSTATE: HY000  
  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to `%s`@`%s`, but this is not an existing user.  
  
`ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST` was added in 8.0.18.
  - Error number: 3927; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT`; SQLSTATE: HY000  
  
Message: Invalid, corrupted PRIVILEGE\_CHECKS\_USER was found in the replication configuration repository for channel '%s'. Use CHANGE REPLICATION SOURCE TO PRIVILEGE\_CHECKS\_USER to correct the configuration.  
  
`ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT` was added in 8.0.18.
  - Error number: 3928; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV`; SQLSTATE: HY000  
  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to `%s`@`%s`, but this user does not have REPLICATION\_APPLIER privilege.  
  
`ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV` was added in 8.0.18.
  - Error number: 3929; Symbol: `ER_WARN_DA_PRIVILEGE_NOT_REGISTERED`; SQLSTATE: HY000  
  
Message: Dynamic privilege '%s' is not registered with the server.  
  
`ER_WARN_DA_PRIVILEGE_NOT_REGISTERED` was added in 8.0.18.
  - Error number: 3930; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_INVALID`; SQLSTATE: HY000  
  
Message: Function '%s' failed because key is invalid.  
  
`ER_CLIENT_KEYRING_UDF_KEY_INVALID` was added in 8.0.19.
  - Error number: 3931; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID`; SQLSTATE: HY000  
  
Message: Function '%s' failed because key type is invalid.  
  
`ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID` was added in 8.0.19.
  - Error number: 3932; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG`; SQLSTATE: HY000  
  
Message: Function '%s' failed because key length is too long.  
  
`ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG` was added in 8.0.19.
  - Error number: 3933; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG`; SQLSTATE: HY000  
  
Message: Function '%s' failed because key type is too long.
-

---

`ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG` was added in 8.0.19.

- Error number: 3934; Symbol: `ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED_REPORT`; SQLSTATE: `HY000`

Message: %s.

`ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED_REPORT` was added in 8.0.19.

- Error number: 3935; Symbol: `ER_DA_UDF_INVALID_CHARSET_SPECIFIED`; SQLSTATE: `HY000`

Message: Invalid character set '%s' was specified. It must be either character set name or collation name as supported by server.

`ER_DA_UDF_INVALID_CHARSET_SPECIFIED` was added in 8.0.19.

- Error number: 3936; Symbol: `ER_DA_UDF_INVALID_CHARSET`; SQLSTATE: `HY000`

Message: Invalid character set '%s' was specified. It must be a character set name as supported by server.

`ER_DA_UDF_INVALID_CHARSET` was added in 8.0.19.

- Error number: 3937; Symbol: `ER_DA_UDF_INVALID_COLLATION`; SQLSTATE: `HY000`

Message: Invalid collation '%s' was specified. It must be a collation name as supported by server.

`ER_DA_UDF_INVALID_COLLATION` was added in 8.0.19.

- Error number: 3938; Symbol: `ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE`; SQLSTATE: `HY000`

Message: Invalid extension argument type '%s' was specified. Refer the MySQL manual for the valid UDF extension arguments type.

`ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE` was added in 8.0.19.

- Error number: 3939; Symbol: `ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME`; SQLSTATE: `HY000`

Message: Table has multiple constraints with the name '%s'. Please use constraint specific '%s' clause.

`ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME` was added in 8.0.19.

- Error number: 3940; Symbol: `ER_CONSTRAINT_NOT_FOUND`; SQLSTATE: `HY000`

Message: Constraint '%s' does not exist.

`ER_CONSTRAINT_NOT_FOUND` was added in 8.0.19.

- Error number: 3941; Symbol: `ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Altering constraint enforcement is not supported for the constraint '%s'. Enforcement state alter is not supported for the PRIMARY, UNIQUE and FOREIGN KEY type constraints.

`ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED` was added in 8.0.19.

- 
- Error number: 3942; Symbol: `ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS`; SQLSTATE: `HY000`  
  
Message: Each row of a VALUES clause must have at least one column, unless when used as source in an INSERT statement.  
  
`ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS` was added in 8.0.19.
  - Error number: 3943; Symbol: `ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT`; SQLSTATE: `HY000`  
  
Message: A VALUES clause cannot use DEFAULT values, unless used as a source in an INSERT statement.  
  
`ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT` was added in 8.0.19.
  - Error number: 3944; Symbol: `ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT`; SQLSTATE: `HY000`  
  
Message: The query does not comply with variable `require_row_format` restrictions.  
  
`ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT` was added in 8.0.19.
  - Error number: 3945; Symbol: `ER_REQUIRE_ROW_FORMAT_INVALID_VALUE`; SQLSTATE: `HY000`  
  
Message: The requested value %s is invalid for REQUIRE\_ROW\_FORMAT, must be either 0 or 1.  
  
`ER_REQUIRE_ROW_FORMAT_INVALID_VALUE` was added in 8.0.19.
  - Error number: 3946; Symbol: `ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY`; SQLSTATE: `HY000`  
  
Message: Failed to acquire lock on user management service, unable to determine if role '%s'@'%s' is mandatory  
  
`ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY` was added in 8.0.19.
  - Error number: 3947; Symbol: `ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST`; SQLSTATE: `HY000`  
  
Message: Failed to acquire lock on user management service, unable to fetch mandatory role list  
  
`ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST` was added in 8.0.19.
  - Error number: 3948; Symbol: `ER_CLIENT_LOCAL_FILES_DISABLED`; SQLSTATE: `42000`  
  
Message: Loading local data is disabled; this must be enabled on both the client and server sides  
  
`ER_CLIENT_LOCAL_FILES_DISABLED` was added in 8.0.19.
  - Error number: 3949; Symbol: `ER_IMP_INCOMPATIBLE_CFG_VERSION`; SQLSTATE: `HY000`  
  
Message: Failed to import %s because the CFG file version (%u) is not compatible with the current version (%u)  
  
`ER_IMP_INCOMPATIBLE_CFG_VERSION` was added in 8.0.19.
  - Error number: 3950; Symbol: `ER_DA_OOM`; SQLSTATE: `HY000`  
  
Message: Out of memory

---

[ER\\_DA\\_OOM](#) was added in 8.0.19.

- Error number: [3951](#); Symbol: [ER\\_DA\\_UDF\\_INVALID\\_ARGUMENT\\_TO\\_SET\\_CHARSET](#); SQLSTATE: [HY000](#)

Message: Character set can be set only for the UDF argument type STRING.

[ER\\_DA\\_UDF\\_INVALID\\_ARGUMENT\\_TO\\_SET\\_CHARSET](#) was added in 8.0.19.

- Error number: [3952](#); Symbol: [ER\\_DA\\_UDF\\_INVALID\\_RETURN\\_TYPE\\_TO\\_SET\\_CHARSET](#); SQLSTATE: [HY000](#)

Message: Character set can be set only for the UDF RETURN type STRING.

[ER\\_DA\\_UDF\\_INVALID\\_RETURN\\_TYPE\\_TO\\_SET\\_CHARSET](#) was added in 8.0.19.

- Error number: [3953](#); Symbol: [ER\\_MULTIPLE\\_INTO\\_CLAUSES](#); SQLSTATE: [HY000](#)

Message: Multiple INTO clauses in one query block.

[ER\\_MULTIPLE\\_INTO\\_CLAUSES](#) was added in 8.0.19.

- Error number: [3954](#); Symbol: [ER\\_MISPLACED\\_INTO](#); SQLSTATE: [HY000](#)

Message: Misplaced INTO clause, INTO is not allowed inside subqueries, and must be placed at end of UNION clauses.

[ER\\_MISPLACED\\_INTO](#) was added in 8.0.19.

- Error number: [3955](#); Symbol: [ER\\_USER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_BLOCKED\\_BY\\_PASSWORD\\_LOCK](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins.

[ER\\_USER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_BLOCKED\\_BY\\_PASSWORD\\_LOCK](#) was added in 8.0.19.

- Error number: [3956](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_YEAR\\_UNSIGNED](#); SQLSTATE: [HY000](#)

Message: UNSIGNED for the YEAR data type is deprecated and support for it will be removed in a future release.

[ER\\_WARN\\_DEPRECATED\\_YEAR\\_UNSIGNED](#) was added in 8.0.19.

- Error number: [3957](#); Symbol: [ER\\_CLONE\\_NETWORK\\_PACKET](#); SQLSTATE: [HY000](#)

Message: Clone needs max\_allowed\_packet value to be %u or more. Current value is %u

[ER\\_CLONE\\_NETWORK\\_PACKET](#) was added in 8.0.19.

- Error number: [3958](#); Symbol: [ER\\_SDI\\_OPERATION\\_FAILED\\_MISSING\\_RECORD](#); SQLSTATE: [HY000](#)

Message: Failed to %s sdi for %s.%s in %s due to missing record.

[ER\\_SDI\\_OPERATION\\_FAILED\\_MISSING\\_RECORD](#) was added in 8.0.19.

- 
- Error number: [3959](#); Symbol: [ER\\_DEPENDENT\\_BY\\_CHECK\\_CONSTRAINT](#); SQLSTATE: [HY000](#)  
Message: Check constraint '%s' uses column '%s', hence column cannot be dropped or renamed.  
[ER\\_DEPENDENT\\_BY\\_CHECK\\_CONSTRAINT](#) was added in 8.0.19.
  - Error number: [3960](#); Symbol: [ER\\_GRP\\_OPERATION\\_NOT\\_ALLOWED\\_GR\\_MUST\\_STOP](#); SQLSTATE: [HY000](#)  
Message: This operation cannot be performed while Group Replication is running; run STOP GROUP\_REPLICATION first  
[ER\\_GRP\\_OPERATION\\_NOT\\_ALLOWED\\_GR\\_MUST\\_STOP](#) was added in 8.0.20.
  - Error number: [3961](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_JSON\\_TABLE\\_ON\\_ERROR\\_ON\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: Specifying an ON EMPTY clause after the ON ERROR clause in a JSON\_TABLE column definition is deprecated syntax and will be removed in a future release. Specify ON EMPTY before ON ERROR instead.  
[ER\\_WARN\\_DEPRECATED\\_JSON\\_TABLE\\_ON\\_ERROR\\_ON\\_EMPTY](#) was added in 8.0.20.
  - Error number: [3962](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_INNER\\_INTO](#); SQLSTATE: [HY000](#)  
Message: The INTO clause is deprecated inside query blocks of query expressions and will be removed in a future release. Please move the INTO clause to the end of statement instead.  
[ER\\_WARN\\_DEPRECATED\\_INNER\\_INTO](#) was added in 8.0.20.
  - Error number: [3963](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_VALUES\\_FUNCTION\\_ALWAYS\\_NULL](#); SQLSTATE: [HY000](#)  
Message: The VALUES function is deprecated and will be removed in a future release. It always returns NULL in this context. If you meant to access a value from the VALUES clause of the INSERT statement, consider using an alias (INSERT INTO ... VALUES (...) AS alias) and reference alias.col instead of VALUES(col) in the ON DUPLICATE KEY UPDATE clause.  
[ER\\_WARN\\_DEPRECATED\\_VALUES\\_FUNCTION\\_ALWAYS\\_NULL](#) was added in 8.0.20.
  - Error number: [3964](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_SQL\\_CALC\\_FOUND\\_ROWS](#); SQLSTATE: [HY000](#)  
Message: SQL\_CALC\_FOUND\_ROWS is deprecated and will be removed in a future release. Consider using two separate queries instead.  
[ER\\_WARN\\_DEPRECATED\\_SQL\\_CALC\\_FOUND\\_ROWS](#) was added in 8.0.16.
  - Error number: [3965](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_FOUND\\_ROWS](#); SQLSTATE: [HY000](#)  
Message: FOUND\_ROWS() is deprecated and will be removed in a future release. Consider using COUNT(\*) instead.  
[ER\\_WARN\\_DEPRECATED\\_FOUND\\_ROWS](#) was added in 8.0.16.
  - Error number: [3966](#); Symbol: [ER\\_MISSING\\_JSON\\_VALUE](#); SQLSTATE: [22035](#)  
Message: No value was found by '%s' on the specified path.  
[ER\\_MISSING\\_JSON\\_VALUE](#) was added in 8.0.21.

- 
- Error number: 3967; Symbol: `ER_MULTIPLE_JSON_VALUES`; SQLSTATE: 22034

Message: More than one value was found by '%s' on the specified path.

`ER_MULTIPLE_JSON_VALUES` was added in 8.0.21.

- Error number: 3968; Symbol: `ER_HOSTNAME_TOO_LONG`; SQLSTATE: HY000

Message: Hostname cannot be longer than %d characters.

`ER_HOSTNAME_TOO_LONG` was added in 8.0.21.

- Error number: 3969; Symbol: `ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_KEY`; SQLSTATE: HY000

Message: Column '%s.%s.%s' having prefix key part '%s(%u)' is ignored by the partitioning function. Use of prefixed columns in the PARTITION BY KEY() clause is deprecated and will be removed in a future release.

`ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_KEY` was added in 8.0.21.

- Error number: 3970; Symbol: `ER_GROUP_REPLICATION_USER_EMPTY_MSG`; SQLSTATE: HY000

Message: The START GROUP\_REPLICATION command failed since the username provided for recovery channel is empty.

`ER_GROUP_REPLICATION_USER_EMPTY_MSG` was added in 8.0.21.

- Error number: 3971; Symbol: `ER_GROUP_REPLICATION_USER_MANDATORY_MSG`; SQLSTATE: HY000

Message: The START GROUP\_REPLICATION command failed since the USER option was not provided with PASSWORD for recovery channel.

`ER_GROUP_REPLICATION_USER_MANDATORY_MSG` was added in 8.0.21.

- Error number: 3972; Symbol: `ER_GROUP_REPLICATION_PASSWORD_LENGTH`; SQLSTATE: HY000

Message: The START GROUP\_REPLICATION command failed since the password provided for the recovery channel exceeds the maximum length of 32 characters.

`ER_GROUP_REPLICATION_PASSWORD_LENGTH` was added in 8.0.21.

- Error number: 3973; Symbol: `ER_SUBQUERY_TRANSFORM_REJECTED`; SQLSTATE: HY000

Message: Statement requires a transform of a subquery to a non-SET operation (like IN2EXISTS, or subquery-to-LATERAL-derived-table). This is not allowed with optimizer switch 'subquery\_to\_derived' on

`ER_SUBQUERY_TRANSFORM_REJECTED` was added in 8.0.21.

- Error number: 3974; Symbol: `ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT`; SQLSTATE: HY000

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port)

`ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT` was added in 8.0.21.



- 
- Error number: 3975; Symbol: `ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID`; SQLSTATE: `HY000`

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

`ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID` was added in 8.0.21.

- Error number: 3976; Symbol: `ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART`; SQLSTATE: `HY000`

Message: Variable '%s' cannot be set to the value of '%s'. %s

`ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART` was added in 8.0.21.

- Error number: 3977; Symbol: `ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION`; SQLSTATE: `HY000`

Message: Only BINLOG INSERT, COMMIT and ROLLBACK statements are allowed after CREATE TABLE with START TRANSACTION statement.

`ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION` was added in 8.0.21.

- Error number: 3978; Symbol: `ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT`; SQLSTATE: `HY000`

Message: Foreign key creation is not allowed with CREATE TABLE as SELECT and CREATE TABLE with START TRANSACTION statement.

`ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT` was added in 8.0.21.

- Error number: 3979; Symbol: `ER_NOT_ALLOWED_WITH_START_TRANSACTION`; SQLSTATE: `HY000`

Message: START TRANSACTION clause cannot be used %s

`ER_NOT_ALLOWED_WITH_START_TRANSACTION` was added in 8.0.21.

- Error number: 3980; Symbol: `ER_INVALID_JSON_ATTRIBUTE`; SQLSTATE: `HY000`

Message: Invalid json attribute, error: "%s" at pos %u: '%s'

`ER_INVALID_JSON_ATTRIBUTE` was added in 8.0.21.

- Error number: 3981; Symbol: `ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Storage engine '%s' does not support ENGINE\_ATTRIBUTE.

`ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED` was added in 8.0.21.

- Error number: 3982; Symbol: `ER_INVALID_USER_ATTRIBUTE_JSON`; SQLSTATE: `HY000`

Message: The user attribute must be a valid JSON object

`ER_INVALID_USER_ATTRIBUTE_JSON` was added in 8.0.21.

- 
- Error number: 3983; Symbol: `ER_INNODB_REDO_DISABLED`; SQLSTATE: `HY000`

Message: Cannot perform operation as InnoDB redo logging is disabled. Please retry after enabling redo log with ALTER INSTANCE

`ER_INNODB_REDO_DISABLED` was added in 8.0.21.

- Error number: 3984; Symbol: `ER_INNODB_REDO_ARCHIVING_ENABLED`; SQLSTATE: `HY000`

Message: Cannot perform operation as InnoDB is archiving redo log. Please retry after stopping redo archive by invoking `innodb_redo_log_archive_stop()`

`ER_INNODB_REDO_ARCHIVING_ENABLED` was added in 8.0.21.

- Error number: 3985; Symbol: `ER_MDL_OUT_OF_RESOURCES`; SQLSTATE: `HY000`

Message: Not enough resources to complete lock request.

`ER_MDL_OUT_OF_RESOURCES` was added in 8.0.21.

- Error number: 3986; Symbol: `ER_IMPLICIT_COMPARISON_FOR_JSON`; SQLSTATE: `HY000`

Message: Evaluating a JSON value in SQL boolean context does an implicit comparison against JSON integer 0; if this is not what you want, consider converting JSON to a SQL numeric type with `JSON_VALUE RETURNING`

`ER_IMPLICIT_COMPARISON_FOR_JSON` was added in 8.0.21.

- Error number: 3987; Symbol: `ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET`; SQLSTATE: `HY000`

Message: The function %s does not support the character set '%s'.

`ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET` was added in 8.0.21.

- Error number: 3988; Symbol: `ER_IMPOSSIBLE_STRING_CONVERSION`; SQLSTATE: `HY000`

Message: Conversion from collation %s into %s impossible for %s

`ER_IMPOSSIBLE_STRING_CONVERSION` was added in 8.0.22.

- Error number: 3989; Symbol: `ER_SCHEMA_READ_ONLY`; SQLSTATE: `HY000`

Message: Schema '%s' is in read only mode.

`ER_SCHEMA_READ_ONLY` was added in 8.0.22.

- Error number: 3990; Symbol: `ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF`; SQLSTATE: `HY000`

Message: Failed to enable Asynchronous Replication Connection Failover feature. The `CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1` can only be set when `@@GLOBAL.GTID_MODE = ON`.

`ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF` was added in 8.0.22.

- 
- Error number: 3991; Symbol: `ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF`; SQLSTATE: HY000  
  
Message: Failed to enable Asynchronous Replication Connection Failover feature. The CHANGE REPLICATION SOURCE TO SOURCE\_CONNECTION\_AUTO\_FAILOVER = 1 can only be set when SOURCE\_AUTO\_POSITION option of CHANGE REPLICATION SOURCE TO is enabled.  
  
`ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF` was added in 8.0.22.
  - Error number: 3992; Symbol: `ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT_OFF`; SQLSTATE: HY000  
  
Message: The @@GLOBAL.GTID\_MODE = %s cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE REPLICATION SOURCE TO SOURCE\_CONNECTION\_AUTO\_FAILOVER = 1.  
  
`ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT_OFF` was added in 8.0.22.
  - Error number: 3993; Symbol: `ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT_OFF`; SQLSTATE: HY000  
  
Message: CHANGE REPLICATION SOURCE TO SOURCE\_AUTO\_POSITION = 0 cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE REPLICATION SOURCE TO SOURCE\_CONNECTION\_AUTO\_FAILOVER = 1.  
  
`ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT_OFF` was added in 8.0.22.
  - Error number: 3994; Symbol: `ER_INVALID_PARAMETER_USE`; SQLSTATE: HY000  
  
Message: Invalid use of parameters in '%s'  
  
`ER_INVALID_PARAMETER_USE` was added in 8.0.22.
  - Error number: 3995; Symbol: `ER_CHARACTER_SET_MISMATCH`; SQLSTATE: HY000  
  
Message: Character set '%s' cannot be used in conjunction with '%s' in call to %s.  
  
`ER_CHARACTER_SET_MISMATCH` was added in 8.0.22.
  - Error number: 3996; Symbol: `ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED`; SQLSTATE: HY000  
  
Message: Changing %s not supported on this platform. Falling back to the default.  
  
`ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED` was added in 8.0.22.
  - Error number: 3997; Symbol: `ER_INVALID_TIME_ZONE_INTERVAL`; SQLSTATE: HY000  
  
Message: Invalid time zone interval: '%s'  
  
`ER_INVALID_TIME_ZONE_INTERVAL` was added in 8.0.22.
  - Error number: 3998; Symbol: `ER_INVALID_CAST`; SQLSTATE: HY000  
  
Message: Cannot cast value to %s.  
  
`ER_INVALID_CAST` was added in 8.0.22.
  - Error number: 3999; Symbol: `ER_HYPERGRAPH_NOT_SUPPORTED_YET`; SQLSTATE: 42000

---

Message: The hypergraph optimizer does not yet support '%s'

[ER\\_HYPERGRAPH\\_NOT\\_SUPPORTED\\_YET](#) was added in 8.0.22.

- Error number: [4000](#); Symbol: [ER\\_WARN\\_HYPERGRAPH\\_EXPERIMENTAL](#); SQLSTATE: [HY000](#)

Message: The hypergraph optimizer is highly experimental and is meant for testing only. Do not enable it unless you are a MySQL developer.

[ER\\_WARN\\_HYPERGRAPH\\_EXPERIMENTAL](#) was added in 8.0.22.

- Error number: [4001](#); Symbol: [ER\\_DA\\_NO\\_ERROR\\_LOG\\_PARSER\\_CONFIGURED](#); SQLSTATE: [HY000](#)

Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance\_schema.error\_log.

[ER\\_DA\\_NO\\_ERROR\\_LOG\\_PARSER\\_CONFIGURED](#) was added in 8.0.22.

- Error number: [4002](#); Symbol: [ER\\_DA\\_ERROR\\_LOG\\_TABLE\\_DISABLED](#); SQLSTATE: [HY000](#)

Message: None of the log-sinks selected in @@global.log\_error\_services supports writing to the performance schema. The server will not be able to make the current runs' error events available in performance\_schema.error\_log. To change this, add a log-sink that supports the performance schema to @@global.log\_error\_services.

[ER\\_DA\\_ERROR\\_LOG\\_TABLE\\_DISABLED](#) was added in 8.0.22.

- Error number: [4003](#); Symbol: [ER\\_DA\\_ERROR\\_LOG\\_MULTIPLE\\_FILTERS](#); SQLSTATE: [HY000](#)

Message: @@global.log\_error\_services lists more than one log-filter service. This is discouraged as it will make it hard to understand which rule in which filter affected a log-event.

[ER\\_DA\\_ERROR\\_LOG\\_MULTIPLE\\_FILTERS](#) was added in 8.0.22.

- Error number: [4004](#); Symbol: [ER\\_DA\\_CANT\\_OPEN\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)

Message: Could not open file '%s' for error logging%s%s

[ER\\_DA\\_CANT\\_OPEN\\_ERROR\\_LOG](#) was added in 8.0.22.

- Error number: [4005](#); Symbol: [ER\\_USER\\_REFERENCED\\_AS\\_DEFINER](#); SQLSTATE: [HY000](#)

Message: User %s is referenced as a definer account in %s.

[ER\\_USER\\_REFERENCED\\_AS\\_DEFINER](#) was added in 8.0.22.

- Error number: [4006](#); Symbol: [ER\\_CANNOT\\_USER\\_REFERENCED\\_AS\\_DEFINER](#); SQLSTATE: [HY000](#)

Message: Operation %s failed for %s as it is referenced as a definer account in %s.

[ER\\_CANNOT\\_USER\\_REFERENCED\\_AS\\_DEFINER](#) was added in 8.0.22.

- Error number: [4007](#); Symbol: [ER\\_REGEX\\_NUMBER\\_TOO\\_BIG](#); SQLSTATE: [HY000](#)

Message: Decimal number in regular expression is too large.

[ER\\_REGEX\\_NUMBER\\_TOO\\_BIG](#) was added in 8.0.22.

- Error number: [4008](#); Symbol: [ER\\_SPVAR\\_NONINTEGER\\_TYPE](#); SQLSTATE: [HY000](#)

---

Message: The variable "%s" has a non-integer based type

[ER\\_SPVAR\\_NONINTEGER\\_TYPE](#) was added in 8.0.22.

- Error number: [4009](#); Symbol: [WARN\\_UNSUPPORTED\\_ACL\\_TABLES\\_READ](#); SQLSTATE: [HY000](#)

Message: Reads with serializable isolation/SELECT FOR SHARE are not supported for ACL tables.

[WARN\\_UNSUPPORTED\\_ACL\\_TABLES\\_READ](#) was added in 8.0.22.

- Error number: [4010](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_ACL\\_TABLE\\_READ\\_IN\\_DML\\_DDL](#); SQLSTATE: [HY000](#)

Message: The statement is unsafe because it updates a table depending on ACL table read operation. As storage engine row locks are skipped for ACL table, it may not have same effect on source and replica.

[ER\\_BINLOG\\_UNSAFE\\_ACL\\_TABLE\\_READ\\_IN\\_DML\\_DDL](#) was added in 8.0.22.

- Error number: [4011](#); Symbol: [ER\\_STOP\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP REPLICA command execution is incomplete: Replica Monitor thread got the stop signal, thread is busy, Monitor thread will stop once the current task is complete.

[ER\\_STOP\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_TIMEOUT](#) was added in 8.0.23.

- Error number: [4012](#); Symbol: [ER\\_STARTING\\_REPLICA\\_MONITOR\\_IO\\_THREAD](#); SQLSTATE: [HY000](#)

Message: The Replica Monitor thread failed to start.

[ER\\_STARTING\\_REPLICA\\_MONITOR\\_IO\\_THREAD](#) was added in 8.0.23.

- Error number: [4013](#); Symbol: [ER\\_CANT\\_USE\\_ANONYMOUS\\_TO\\_GTID\\_WITH\\_GTID\\_MODE\\_NOT\\_ON](#); SQLSTATE: [HY000](#)

Message: Replication cannot start%s with ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS = LOCAL|<UUID> as this server uses @@GLOBAL.GTID\_MODE <> ON.

[ER\\_CANT\\_USE\\_ANONYMOUS\\_TO\\_GTID\\_WITH\\_GTID\\_MODE\\_NOT\\_ON](#) was added in 8.0.23.

- Error number: [4014](#); Symbol: [ER\\_CANT\\_COMBINE\\_ANONYMOUS\\_TO\\_GTID\\_AND\\_AUTOPOSITION](#); SQLSTATE: [HY000](#)

Message: The options ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS = LOCAL|<UUID> and SOURCE\_AUTO\_POSITION = 1 cannot be used together.

[ER\\_CANT\\_COMBINE\\_ANONYMOUS\\_TO\\_GTID\\_AND\\_AUTOPOSITION](#) was added in 8.0.23.

- 
- Error number: 4015; Symbol:  
`ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUIRES_GTID_MODE_ON`; SQLSTATE:  
`HY000`  
  
Message: CHANGE REPLICATION SOURCE TO  
`ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` cannot be executed because  
`@@GLOBAL.GTID_MODE <> ON`.  
  
`ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUIRES_GTID_MODE_ON` was added in  
8.0.23.
  - Error number: 4016; Symbol: `ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE_ON`;  
SQLSTATE: `HY000`  
  
Message: The value of `sql_slave_skip_counter` will only take effect for channels running with  
`ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS <> OFF`.  
  
`ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE_ON` was added in 8.0.23, removed after  
8.0.25.
  - Error number: 4016; Symbol: `ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE_ON`;  
SQLSTATE: `HY000`  
  
Message: The value of `sql_replica_skip_counter` will only take effect for channels running with  
`ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS <> OFF`.  
  
`ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE_ON` was added in 8.0.26.
  - Error number: 4017; Symbol:  
`ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_AS_LOCAL_OR_UUID`; SQLSTATE:  
`HY000`  
  
Message: Using `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS` creates limitations on the  
replication topology - you cannot fail over between downstream and upstream servers. Only use this  
option if it is not possible to enable GTIDs on the source, for instance, because of lack of permissions.  
If possible, use the procedure for enabling GTID transactions online instead, as described in the  
documentation.  
  
`ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_AS_LOCAL_OR_UUID` was added in  
8.0.23.
  - Error number: 4018; Symbol:  
`ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_SQL_THD_AFTER_GTIDS`; SQLSTATE:  
`HY000`  
  
Message: `WAIT_UNTIL_SQL_THREAD_AFTER_GTIDS` cannot be used on a channel configured with  
`ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`  
  
`ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_SQL_THD_AFTER_GTIDS` was added in  
8.0.23.
  - Error number: 4019; Symbol:  
`ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS_TO_GTID`; SQLSTATE: `HY000`  
  
Message: The `SQL_AFTER_GTIDS` or `SQL_BEFORE_GTIDS` clauses for  
`START REPLICA` cannot be used when the replication channel is configured with  
`ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`.

---

`ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS_TO_GTID` was added in 8.0.23.

- Error number: 4020; Symbol: `ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME`; SQLSTATE: HY000

Message: Replication '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID>` where the UUID value is equal to the `group_replication_group_name`

`ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME` was added in 8.0.23.

- Error number: 4021; Symbol: `ER_CANT_USE_SAME_UUID_AS_GROUP_NAME`; SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID>` cannot be executed because the UUID value is equal to the `group_replication_group_name`.

`ER_CANT_USE_SAME_UUID_AS_GROUP_NAME` was added in 8.0.23.

- Error number: 4022; Symbol: `ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING`; SQLSTATE: HY000

Message: The `group_replication_recovery` channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.

`ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING` was added in 8.0.23.

- Error number: 4023; Symbol: `ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE`; SQLSTATE: HY000

Message: `AUTOEXTEND_SIZE` should be a multiple of %uM

`ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE` was added in 8.0.23.

- Error number: 4024; Symbol: `ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE`; SQLSTATE: HY000

Message: InnoDB: "%s" not allowed with general tablespaces

`ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE` was added in 8.0.23.

- Error number: 4025; Symbol: `ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE`; SQLSTATE: HY000

Message: `AUTOEXTEND_SIZE` value should be between %uM and %uM

`ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE` was added in 8.0.23.

- Error number: 4026; Symbol: `ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE`; SQLSTATE: HY000

Message: `AUTOEXTEND_SIZE` clause is not valid for %s tablespace.

`ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE` was added in 8.0.23.

- Error number: 4027; Symbol: `ER_ROLE_GRANTED_TO_ITSELF`; SQLSTATE: HY000

Message: User account %s is directly or indirectly granted to the role %s. The GRANT would create a loop

`ER_ROLE_GRANTED_TO_ITSELF` was added in 8.0.23.

- 
- Error number: 4028; Symbol: `ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN`; SQLSTATE: HY000  
Message: A table must have at least one visible column.  
`ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN` was added in 8.0.23.
  - Error number: 4029; Symbol: `ER_INNODB_COMPRESSION_FAILURE`; SQLSTATE: HY000  
Message: Compression failed with the following error : %s  
`ER_INNODB_COMPRESSION_FAILURE` was added in 8.0.23.
  - Error number: 4030; Symbol: `ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE`; SQLSTATE: HY000  
Message: The parameter network\_namespace is reserved for future use. Please use the CHANGE REPLICATION SOURCE command to set channel network\_namespace parameter.  
`ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE` was added in 8.0.23.
  - Error number: 4031; Symbol: `ER_CLIENT_INTERACTION_TIMEOUT`; SQLSTATE: HY000  
Message: The client was disconnected by the server because of inactivity. See wait\_timeout and interactive\_timeout for configuring this behavior.  
`ER_CLIENT_INTERACTION_TIMEOUT` was added in 8.0.24.
  - Error number: 4032; Symbol: `ER_INVALID_CAST_TO_GEOMETRY`; SQLSTATE: 22S01  
Message: Invalid cast from %s to %s.  
`ER_INVALID_CAST_TO_GEOMETRY` was added in 8.0.24.
  - Error number: 4033; Symbol: `ER_INVALID_CAST_POLYGON_RING_DIRECTION`; SQLSTATE: 22S04  
Message: Invalid cast from %s to %s. A polygon ring is in the wrong direction.  
`ER_INVALID_CAST_POLYGON_RING_DIRECTION` was added in 8.0.24.
  - Error number: 4034; Symbol: `ER_GIS_DIFFERENT_SRIDS_AGGREGATION`; SQLSTATE: 22S05  
Message: Arguments to function %s contains geometries with different SRIDs: %u and %u. All geometries must have the same SRID.  
`ER_GIS_DIFFERENT_SRIDS_AGGREGATION` was added in 8.0.24.
  - Error number: 4035; Symbol: `ER_RELOAD_KEYRING_FAILURE`; SQLSTATE: HY000  
Message: Keyring reload failed. Please check error log for more details.  
`ER_RELOAD_KEYRING_FAILURE` was added in 8.0.24.
  - Error number: 4036; Symbol: `ER_SDI_GET_KEYS_INVALID_TABLESPACE`; SQLSTATE: HY000  
Message: Tablespace '%s' is invalid for SDI operations.  
`ER_SDI_GET_KEYS_INVALID_TABLESPACE` was added in 8.0.24.
  - Error number: 4037; Symbol: `ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE`; SQLSTATE: HY000



---

Message: Value too long setting SOURCE\_COMPRESSION\_ALGORITHMS option to a %d chars long string for channel '%s'.

[ER\\_CHANGE\\_RPL\\_SRC\\_WRONG\\_COMPRESSION\\_ALGORITHM\\_SIZE](#) was added in 8.0.24.

- Error number: [4038](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_TLS\\_VERSION\\_FOR\\_CHANNEL\\_CLI](#); SQLSTATE: [HY000](#)

Message: A deprecated TLS version %s is enabled for channel %s. Please use TLSv1.2 or higher.

[ER\\_WARN\\_DEPRECATED\\_TLS\\_VERSION\\_FOR\\_CHANNEL\\_CLI](#) was added in 8.0.26, removed after 8.0.27.

- Error number: [4039](#); Symbol: [ER\\_CANT\\_USE\\_SAME\\_UUID\\_AS\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: [HY000](#)

Message: CHANGE REPLICATION SOURCE TO ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS = <UUID> cannot be executed because the UUID value is equal to the group\_replication\_view\_change\_uuid.

[ER\\_CANT\\_USE\\_SAME\\_UUID\\_AS\\_VIEW\\_CHANGE\\_UUID](#) was added in 8.0.26.

- Error number: [4040](#); Symbol: [ER\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: [HY000](#)

Message: Replication '%s' is configured with ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS = <UUID> where the UUID value is equal to the group\_replication\_view\_change\_uuid

[ER\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#) was added in 8.0.26.

- Error number: [4041](#); Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_FAIL\\_GET\\_VARIABLE](#); SQLSTATE: [HY000](#)

Message: Unable to retrieve group\_replication\_view\_change\_uuid variable during server checks on replication operations.

[ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_FAIL\\_GET\\_VARIABLE](#) was added in 8.0.26.

- Error number: [4042](#); Symbol: [ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_AND\\_PRUNE\\_SECONDS](#); SQLSTATE: [HY000](#)

Message: Both audit\_log\_max\_size and audit\_log\_prune\_seconds are set to non-zero. audit\_log\_max\_size takes precedence and audit\_log\_prune\_seconds is ignored

[ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_AND\\_PRUNE\\_SECONDS](#) was added in 8.0.26.

- Error number: [4043](#); Symbol: [ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_CLOSE\\_TO\\_ROTATE\\_ON\\_SIZE](#); SQLSTATE: [HY000](#)

Message: audit\_log\_rotate\_on\_size is not granular enough for the value of audit\_log\_max\_size supplied. Should be at least %d times smaller.

[ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_CLOSE\\_TO\\_ROTATE\\_ON\\_SIZE](#) was added in 8.0.26.

- 
- Error number: 4044; Symbol: `ER_KERBEROS_CREATE_USER`; SQLSTATE: HY000  
Message: Create/Alter user has failed, Configured user realm as authentication string is empty, Please make sure to configure authentication string as user realm.  
`ER_KERBEROS_CREATE_USER` was added in 8.0.26.
  - Error number: 4045; Symbol: `ER_INSTALL_PLUGIN_CONFLICT_CLIENT`; SQLSTATE: HY000  
Message: Cannot install the %s plugin when the %s plugin is installed.  
`ER_INSTALL_PLUGIN_CONFLICT_CLIENT` was added in 8.0.26.
  - Error number: 4046; Symbol: `ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED`; SQLSTATE: HY000  
Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.  
`ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED` was added in 8.0.26.
  - Error number: 4047; Symbol: `ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED`; SQLSTATE: HY000  
Message: The until clause SQL\_AFTER\_MTS\_GAPS is being used for channel '%s' when GTID\_MODE = ON and SOURCE\_AUTO\_POSITION=1 meaning the server did not compute internally what gaps may exist in the relay log transaction execution. To close any execution gaps use either the SQL\_BEFORE\_GTIDS or SQL\_AFTER\_GTIDS until clause.  
`ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED` was added in 8.0.26.
  - Error number: 4048; Symbol: `ER_INVALID_ASSIGNMENT_TARGET`; SQLSTATE: 42000  
Message: Invalid target for assignment in INSERT or UPDATE statement '%s'.  
`ER_INVALID_ASSIGNMENT_TARGET` was added in 8.0.26.
  - Error number: 4049; Symbol: `ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY`; SQLSTATE: HY000  
Message: This operation cannot be performed on a Group Replication secondary member, it must be done on the group primary.  
`ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY` was added in 8.0.26.
  - Error number: 4050; Symbol: `ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION`; SQLSTATE: HY000  
Message: Unable to propagate the SOURCE\_CONNECTION\_AUTO\_FAILOVER value for channel '%s' to group replication members. Please retry the operation.  
`ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION` was added in 8.0.26.
  - Error number: 4051; Symbol: `ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_JSON`; SQLSTATE: HY000  
Message: audit\_log\_format\_unix\_timestamp is applicable only when audit\_log\_format = JSON.  
`ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_JSON` was added in 8.0.26.

- 
- Error number: 4052; Symbol: `ER_INVALID_MFA_PLUGIN_SPECIFIED`; SQLSTATE: HY000  
Message: Invalid plugin "%s" specified as %d factor during "%s".  
`ER_INVALID_MFA_PLUGIN_SPECIFIED` was added in 8.0.27.
  - Error number: 4053; Symbol: `ER_IDENTIFIED_BY_UNSUPPORTED`; SQLSTATE: HY000  
Message: IDENTIFIED BY clause during "%s" not supported for plugin "%s".  
`ER_IDENTIFIED_BY_UNSUPPORTED` was added in 8.0.27.
  - Error number: 4054; Symbol: `ER_INVALID_PLUGIN_FOR_REGISTRATION`; SQLSTATE: HY000  
Message: This operation is not supported for plugin "%s".  
`ER_INVALID_PLUGIN_FOR_REGISTRATION` was added in 8.0.27.
  - Error number: 4055; Symbol: `ER_PLUGIN_REQUIRES_REGISTRATION`; SQLSTATE: HY000  
Message: Authentication plugin requires registration. Please refer ALTER USER syntax or set --fido-register-factor command line option to do registration.  
`ER_PLUGIN_REQUIRES_REGISTRATION` was added in 8.0.27.
  - Error number: 4056; Symbol: `ER_MFA_METHOD_EXISTS`; SQLSTATE: HY000  
Message: %d factor authentication method exists. Please do ALTER USER... DROP %d factor before doing this operation OR do ALTER USER... MODIFY %d factor... to modify existing %d factor authentication method.  
`ER_MFA_METHOD_EXISTS` was added in 8.0.27.
  - Error number: 4057; Symbol: `ER_MFA_METHOD_NOT_EXISTS`; SQLSTATE: HY000  
Message: %d factor authentication method doesn't exist. Please do ALTER USER... ADD %d factor... before doing this operation.  
`ER_MFA_METHOD_NOT_EXISTS` was added in 8.0.27.
  - Error number: 4058; Symbol: `ER_AUTHENTICATION_POLICY_MISMATCH`; SQLSTATE: HY000  
Message: %d factor authentication method does not match against authentication policy. Please refer @@authentication\_policy system variable.  
`ER_AUTHENTICATION_POLICY_MISMATCH` was added in 8.0.27.
  - Error number: 4059; Symbol: `ER_PLUGIN_REGISTRATION_DONE`; SQLSTATE: HY000  
Message: The registration for %d factor authentication method is already completed. You cannot perform registration multiple times.  
`ER_PLUGIN_REGISTRATION_DONE` was added in 8.0.27.
-

- 
- Error number: 4060; Symbol: `ER_INVALID_USER_FOR_REGISTRATION`; SQLSTATE: `HY000`

Message: The registration operation is not allowed for user '%s'@'%s'. The operation can only be performed in user's own session.

`ER_INVALID_USER_FOR_REGISTRATION` was added in 8.0.27.

- Error number: 4061; Symbol: `ER_USER_REGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: Authentication plugin's registration failed.

`ER_USER_REGISTRATION_FAILED` was added in 8.0.27.

- Error number: 4062; Symbol: `ER_MFA_METHODS_INVALID_ORDER`; SQLSTATE: `HY000`

Message: %d factor authentication method should be added before %d factor authentication method.

`ER_MFA_METHODS_INVALID_ORDER` was added in 8.0.27.

- Error number: 4063; Symbol: `ER_MFA_METHODS_IDENTICAL`; SQLSTATE: `HY000`

Message: Authentication factor should be different.

`ER_MFA_METHODS_IDENTICAL` was added in 8.0.27.

- Error number: 4064; Symbol: `ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER`; SQLSTATE: `HY000`

Message: The operation "%s" cannot be performed for user '%s'@'%s' configured to connect without a password.

`ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER` was added in 8.0.27.

- Error number: 4065; Symbol: `ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID_ONLY`; SQLSTATE: `HY000`

Message: GTID\_ONLY cannot be enabled for replication channel '%s'. You need GTID\_MODE = ON, SOURCE\_AUTO\_POSITION = 1 and REQUIRE\_ROW\_FORMAT = 1.

`ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID_ONLY` was added in 8.0.27.

- Error number: 4066; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMAT_WITH_GTID_ONLY`; SQLSTATE: `HY000`

Message: REQUIRE\_ROW\_FORMAT cannot be disabled for replication channel '%s' when GTID\_ONLY=1.

`ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMAT_WITH_GTID_ONLY` was added in 8.0.27.

- 
- Error number: 4067; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION_WITH_GTID_ONLY`; SQLSTATE: HY000  
  
Message: SOURCE\_AUTO\_POSITION cannot be disabled for replication channel '%s' when GTID\_ONLY=1.  
  
`ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION_WITH_GTID_ONLY` was added in 8.0.27.
  - Error number: 4068; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITHOUT_POSITIONS`; SQLSTATE: HY000  
  
Message: When disabling GTID\_ONLY and SOURCE\_AUTO\_POSITION FOR CHANNEL '%s' you must provide SOURCE\_LOG\_FILE and SOURCE\_LOG\_POS as source positions are invalid.  
  
`ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITHOUT_POSITIONS` was added in 8.0.27.
  - Error number: 4069; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POS_WITHOUT_POSITIONS`; SQLSTATE: HY000  
  
Message: When disabling SOURCE\_AUTO\_POSITION FOR CHANNEL '%s' you must provide SOURCE\_LOG\_FILE and SOURCE\_LOG\_POS as source positions are invalid.  
  
`ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POS_WITHOUT_POSITIONS` was added in 8.0.27.
  - Error number: 4070; Symbol: `ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_NOT_ON`; SQLSTATE: HY000  
  
Message: When configuring a group replication channel you must do it when GTID\_MODE = ON.  
  
`ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_NOT_ON` was added in 8.0.27.
  - Error number: 4071; Symbol: `ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON`; SQLSTATE: HY000  
  
Message: Replication cannot start%s with GTID\_ONLY = 1 as this server uses @@GLOBAL.GTID\_MODE <> ON.  
  
`ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON` was added in 8.0.27.
  - Error number: 4072; Symbol: `ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS`; SQLSTATE: HY000  
  
Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of GTID\_ONLY=1. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.  
  
`ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS` was added in 8.0.27.
  - Error number: 4073; Symbol: `ER_DA_SSL_FIPS_MODE_ERROR`; SQLSTATE: HY000  
  
Message: SSL fips mode error: %s  
  
`ER_DA_SSL_FIPS_MODE_ERROR` was added in 8.0.27.
  - Error number: 4074; Symbol: `ER_VALUE_OUT_OF_RANGE`; SQLSTATE: HY000

---

Message: %s=%llu is outside the valid range [%llu,%llu]. %llu will be used.

[ER\\_VALUE\\_OUT\\_OF\\_RANGE](#) was added in 8.0.27.

- Error number: [4075](#); Symbol: [ER\\_FULLTEXT\\_WITH\\_ROLLUP](#); SQLSTATE: [HY000](#)

Message: MATCH does not support ROLLUP columns.

[ER\\_FULLTEXT\\_WITH\\_ROLLUP](#) was added in 8.0.28.

- Error number: [4076](#); Symbol: [ER\\_REGEX\\_MISSING\\_RESOURCE](#); SQLSTATE: [HY000](#)

Message: Missing locale resource in regular expression library.

[ER\\_REGEX\\_MISSING\\_RESOURCE](#) was added in 8.0.28.

- Error number: [4077](#); Symbol: [ER\\_WARN\\_REGEX\\_USING\\_DEFAULT](#); SQLSTATE: [HY000](#)

Message: Regular expression library used default (root) locale.

[ER\\_WARN\\_REGEX\\_USING\\_DEFAULT](#) was added in 8.0.28.

- Error number: [4078](#); Symbol: [ER\\_REGEX\\_MISSING\\_FILE](#); SQLSTATE: [HY000](#)

Message: Missing data file in regular expression library.

[ER\\_REGEX\\_MISSING\\_FILE](#) was added in 8.0.28.

- Error number: [4079](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_COLLATION](#); SQLSTATE: [HY000](#)

Message: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.

[ER\\_WARN\\_DEPRECATED\\_COLLATION](#) was added in 8.0.28.

- Error number: [4080](#); Symbol: [ER\\_CONCURRENT\\_PROCEDURE\\_USAGE](#); SQLSTATE: [HY000](#)

Message: The %s was called when there was already another concurrent call to this procedure. No action was taken. Wait for other calls to %s to finish before retrying.

[ER\\_CONCURRENT\\_PROCEDURE\\_USAGE](#) was added in 8.0.28.

- Error number: [4081](#); Symbol: [ER\\_DA\\_GLOBAL\\_CONN\\_LIMIT](#); SQLSTATE: [HY000](#)

Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.

[ER\\_DA\\_GLOBAL\\_CONN\\_LIMIT](#) was added in 8.0.28.

- Error number: [4082](#); Symbol: [ER\\_DA\\_CONN\\_LIMIT](#); SQLSTATE: [HY000](#)

Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.

[ER\\_DA\\_CONN\\_LIMIT](#) was added in 8.0.28.

- Error number: [4083](#); Symbol:

[ER\\_ALTER\\_OPERATION\\_NOT\\_SUPPORTED\\_REASON\\_COLUMN\\_TYPE\\_INSTANT](#); SQLSTATE: [HY000](#)

Message: Need to rebuild the table to change column type

---

[ER\\_ALTER\\_OPERATION\\_NOT\\_SUPPORTED\\_REASON\\_COLUMN\\_TYPE\\_INSTANT](#) was added in 8.0.28.

- Error number: [4084](#); Symbol: [ER\\_WARN\\_SF\\_UDF\\_NAME\\_COLLISION](#); SQLSTATE: [HY000](#)

Message: This function '%s' has the same name as a loadable function (UDF). To invoke the stored function, it is necessary to qualify it with the schema name.

[ER\\_WARN\\_SF\\_UDF\\_NAME\\_COLLISION](#) was added in 8.0.28.

- Error number: [4085](#); Symbol: [ER\\_CANNOT\\_PURGE\\_BINLOG\\_WITH\\_BACKUP\\_LOCK](#); SQLSTATE: [HY000](#)

Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.

[ER\\_CANNOT\\_PURGE\\_BINLOG\\_WITH\\_BACKUP\\_LOCK](#) was added in 8.0.28.

- Error number: [4086](#); Symbol: [ER\\_TOO\\_MANY\\_WINDOWS](#); SQLSTATE: [HY000](#)

Message: Too many windows in SELECT: %d. Maximum allowed is %d. Use named windows to share windows between window functions.

[ER\\_TOO\\_MANY\\_WINDOWS](#) was added in 8.0.28.

- Error number: [4087](#); Symbol: [ER\\_MYSQLBACKUP\\_CLIENT\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_MYSQLBACKUP\\_CLIENT\\_MSG](#) was added in 8.0.28.

- Error number: [4088](#); Symbol: [ER\\_COMMENT\\_CONTAINS\\_INVALID\\_STRING](#); SQLSTATE: [HY000](#)

Message: Comment for %s '%s' contains an invalid %s character string: '%s'.

[ER\\_COMMENT\\_CONTAINS\\_INVALID\\_STRING](#) was added in 8.0.28.

- Error number: [4089](#); Symbol: [ER\\_DEFINITION\\_CONTAINS\\_INVALID\\_STRING](#); SQLSTATE: [HY000](#)

Message: Definition of %s '%s.%s' contains an invalid %s character string: '%s'.

[ER\\_DEFINITION\\_CONTAINS\\_INVALID\\_STRING](#) was added in 8.0.28.

- Error number: [4090](#); Symbol: [ER\\_CANT\\_EXECUTE\\_COMMAND\\_WITH\\_ASSIGNED\\_GTID\\_NEXT](#); SQLSTATE: [HY000](#)

Message: Can't execute the given command when @@SESSION.GTID\_NEXT == 'UUID:NUMBER'.

[ER\\_CANT\\_EXECUTE\\_COMMAND\\_WITH\\_ASSIGNED\\_GTID\\_NEXT](#) was added in 8.0.28.

- Error number: [4091](#); Symbol: [ER\\_XA\\_TEMP\\_TABLE](#); SQLSTATE: [HY000](#)

Message: XA: Temporary tables cannot be accessed inside XA transactions when xa\_detach\_on\_prepare=ON

[ER\\_XA\\_TEMP\\_TABLE](#) was added in 8.0.29.

- Error number: [4092](#); Symbol: [ER\\_INNODB\\_MAX\\_ROW\\_VERSION](#); SQLSTATE: [HY000](#)

Message: Maximum row versions reached for table %s. No more columns can be added or dropped instantly. Please use COPY/INPLACE.

---

`ER_INNODB_MAX_ROW_VERSION` was added in 8.0.29.

- Error number: 4093; Symbol: `ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_SIZE`; SQLSTATE: HY000

Message: Column can't be added with ALGORITHM=INSTANT as after this max possible row size crosses max permissible row size. Try ALGORITHM=INPLACE/COPY.

`ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_SIZE` was added in 8.0.29, removed after 8.0.31.

- Error number: 4094; Symbol: `ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGE_IS_RUNNING`; SQLSTATE: HY000

Message: All queries have been blocked while function 'group\_replication\_set\_as\_primary()' is executing. Please refer timeout parameter of function 'group\_replication\_set\_as\_primary()'.

`ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGE_IS_RUNNING` was added in 8.0.29.

- Error number: 4095; Symbol: `ER_WARN_DEPRECATED_DATETIME_DELIMITER`; SQLSTATE: HY000

Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is deprecated. Prefer the standard '%c'.

`ER_WARN_DEPRECATED_DATETIME_DELIMITER` was added in 8.0.29.

- Error number: 4096; Symbol: `ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER`; SQLSTATE: HY000

Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is superfluous and is deprecated. Please remove.

`ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER` was added in 8.0.29.

- Error number: 4097; Symbol: `ER_CANNOT_PERSIST_SENSITIVE_VARIABLES`; SQLSTATE: HY000

Message: Cannot persist SENSITIVE system variable '%s' because keyring component support is unavailable.

`ER_CANNOT_PERSIST_SENSITIVE_VARIABLES` was added in 8.0.29.

- Error number: 4098; Symbol: `ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES`; SQLSTATE: HY000

Message: SENSITIVE system variable '%s' was persisted without encryption. Consider restarting server with keyring component support to persist SENSITIVE variables securely.

`ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES` was added in 8.0.29.

- Error number: 4099; Symbol: `ER_WARN_TRG_ALREADY_EXISTS`; SQLSTATE: HY000

Message: Trigger '%s' already exists on the table '%s'. '%s'.

`ER_WARN_TRG_ALREADY_EXISTS` was added in 8.0.29.



- 
- Error number: 4100; Symbol: `ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DIFFERENT_TABLE`; SQLSTATE: HY000  
  
Message: Trigger '%s'.'%s' already exists on a different table. The 'IF NOT EXISTS' clause is only supported for triggers associated with the same table.  
  
`ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DIFFERENT_TABLE` was added in 8.0.29.
  - Error number: 4101; Symbol: `ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FCT_NAME_COLLISION`; SQLSTATE: HY000  
  
Message: This function '%s' has the same name as a native function. The 'IF NOT EXISTS' clause is not supported while creating a loadable function with the same name as a native function.  
  
`ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FCT_NAME_COLLISION` was added in 8.0.29.
  - Error number: 4102; Symbol: `ER_SET_PASSWORD_AUTH_PLUGIN_ERROR`; SQLSTATE: HY000  
  
Message: SET PASSWORD has no significance for user '%s'@'%s' as the authentication method used doesn't store authentication data in the MySQL server. Please consider using ALTER USER instead if you want to change authentication parameters.  
  
`ER_SET_PASSWORD_AUTH_PLUGIN_ERROR` was added in 8.0.29.
  - Error number: 4105; Symbol: `ER_SRS_INVALID_LATITUDE_OF_ORIGIN`; SQLSTATE: SR002  
  
Message: Latitude of origin must be within [-90, 90] degrees, specified in the SRS angular unit.  
  
`ER_SRS_INVALID_LATITUDE_OF_ORIGIN` was added in 8.0.30.
  - Error number: 4106; Symbol: `ER_SRS_INVALID_LONGITUDE_OF_ORIGIN`; SQLSTATE: SR002  
  
Message: Longitude of origin must be within (-180, 180] degrees, specified in the SRS angular unit.  
  
`ER_SRS_INVALID_LONGITUDE_OF_ORIGIN` was added in 8.0.30.
  - Error number: 4107; Symbol: `ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT`; SQLSTATE: SR002  
  
Message: The spatial reference system definition for SRID %u contains unused projection parameter "%s".  
  
`ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT` was added in 8.0.30.
  - Error number: 4108; Symbol: `ER_GIPK_COLUMN_EXISTS`; SQLSTATE: HY000  
  
Message: Failed to generate invisible primary key. Column 'my\_row\_id' already exists.  
  
`ER_GIPK_COLUMN_EXISTS` was added in 8.0.30.
  - Error number: 4109; Symbol: `ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS`; SQLSTATE: HY000  
  
Message: Failed to generate invisible primary key. Auto-increment column already exists.  
  
`ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS` was added in 8.0.30.

- 
- Error number: 4110; Symbol: `ER_GIPK_COLUMN_ALTER_NOT_ALLOWED`; SQLSTATE: `HY000`  
Message: Altering generated invisible primary key column 'my\_row\_id' is not allowed.  
`ER_GIPK_COLUMN_ALTER_NOT_ALLOWED` was added in 8.0.30.
  - Error number: 4111; Symbol: `ER_DROP_PK_COLUMN_TO_DROP_GIPK`; SQLSTATE: `HY000`  
Message: Please drop primary key column to be able to drop generated invisible primary key.  
`ER_DROP_PK_COLUMN_TO_DROP_GIPK` was added in 8.0.30.
  - Error number: 4112; Symbol: `ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR`; SQLSTATE: `HY000`  
Message: Generating an invisible primary key for a table created using `CREATE TABLE ... SELECT ...` is disallowed when `binlog_format=STATEMENT`. It cannot be guaranteed that the `SELECT` retrieves rows in the same order on source and replica. Therefore, it cannot be guaranteed that the value generated for the generated implicit primary key column will be the same on source and replica for all rows. Use `binlog_format=ROW` or `MIXED` to execute this statement.  
`ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR` was added in 8.0.30.
  - Error number: 4113; Symbol: `ER_DA_EXPIRE_LOGS_DAYS_IGNORED`; SQLSTATE: `HY000`  
Message: The option `expire_logs_days` cannot be used together with option `binlog_expire_logs_seconds`. To set one, first unset the other by setting it to 0.  
`ER_DA_EXPIRE_LOGS_DAYS_IGNORED` was added in 8.0.30.
  - Error number: 4114; Symbol: `ER_CTE_RECURSIVE_NOT_UNION`; SQLSTATE: `HY000`  
Message: Recursive table reference in `EXCEPT` or `INTERSECT` operand is not allowed.  
`ER_CTE_RECURSIVE_NOT_UNION` was added in 8.0.31.
  - Error number: 4115; Symbol: `ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CTX`; SQLSTATE: `HY000`  
Message: Error when trying to fetch information from security context object, when trying to connect the server.  
`ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CTX` was added in 8.0.31.
  - Error number: 4116; Symbol: `ER_COMMAND_SERVICE_BACKEND_FAILED`; SQLSTATE: `HY000`  
Message: Error in command service backend interface, because of : "%s"  
`ER_COMMAND_SERVICE_BACKEND_FAILED` was added in 8.0.31.
  - Error number: 4117; Symbol: `ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS`; SQLSTATE: `HY000`  
Message: The `PRIVILEGE_CHECKS_USER` for channel '%s' would need `FILE` privilege to execute a `LOAD DATA INFILE` statement replicated in statement format. Consider using `binlog_format=ROW` on source. If the replicated events are trusted, recover from the failure by temporarily granting `FILE` to the `PRIVILEGE_CHECKS_USER`.  
`ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS` was added in 8.0.31.

- 
- Error number: 4118; Symbol: `ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE`; SQLSTATE: `HY000`

Message: The 'SET GLOBAL group\_replication\_force\_members=%s' command encountered a failure.  
%s

`ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE` was added in 8.0.31.

- Error number: 4119; Symbol: `ER_WARN_DEPRECATED_IDENT`; SQLSTATE: `HY000`

Message: Using %s as unquoted identifier is deprecated, please use quotes or rename the identifier.

`ER_WARN_DEPRECATED_IDENT` was added in 8.0.31.

- Error number: 4120; Symbol: `ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED`; SQLSTATE: `HY000`

Message: Max number of duplicate rows in INTERSECT ALL exceeded.

`ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED` was added in 8.0.31.

- Error number: 4121; Symbol: `ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT`; SQLSTATE: `HY000`

Message: Query threads count(%u) exceeds transaction threads limit(%u) per group. Please use query threads count per group smaller or equal to max transaction threads limit per group

`ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT` was added in 8.0.31.

- Error number: 4122; Symbol: `ER_BAD_TIMESTAMP_FORMAT`; SQLSTATE: `HY000`

Message: Invalid timestamp format in %s udf

`ER_BAD_TIMESTAMP_FORMAT` was added in 8.0.31.

- Error number: 4123; Symbol: `ER_SHAPE_PREDICTION_UDF`; SQLSTATE: `HY000`

Message: SHAPE\_PREDICTION UDF %s got error because of %s.

`ER_SHAPE_PREDICTION_UDF` was added in 8.0.31.

- Error number: 4124; Symbol: `ER_SRS_INVALID_HEIGHT`; SQLSTATE: `SR002`

Message: Height parameter must be non negative.

`ER_SRS_INVALID_HEIGHT` was added in 8.0.32.

- Error number: 4125; Symbol: `ER_SRS_INVALID_SCALING`; SQLSTATE: `SR002`

Message: Scaling parameter must be non negative.

`ER_SRS_INVALID_SCALING` was added in 8.0.32.

- Error number: 4126; Symbol: `ER_SRS_INVALID_ZONE_WIDTH`; SQLSTATE: `SR002`

Message: Zone width parameter must be an integer between 1-60.

`ER_SRS_INVALID_ZONE_WIDTH` was added in 8.0.32.

- 
- Error number: 4127; Symbol: `ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A`; SQLSTATE: `SR002`  
  
Message: Latitude of origin must be +-90 degrees, specified in the SRS angular unit, in Polar Stereographic (variant A) projection method (EPSG:9810).  
  
`ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A` was added in 8.0.32.
  - Error number: 4128; Symbol: `ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION`; SQLSTATE: `HY000`  
  
Message: The client is using a deprecated `CLIENT_NO_SCHEMA` client option. `CLIENT_NO_SCHEMA` will be removed in a future release.  
  
`ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION` was added in 8.0.32.
  - Error number: 4129; Symbol: `ER_TABLE_NOT_EMPTY`; SQLSTATE: `HY000`  
  
Message: Table '%s' is not empty.  
  
`ER_TABLE_NOT_EMPTY` was added in 8.0.32.
  - Error number: 4130; Symbol: `ER_TABLE_NO_PRIMARY_KEY`; SQLSTATE: `HY000`  
  
Message: Table '%s' has no primary key.  
  
`ER_TABLE_NO_PRIMARY_KEY` was added in 8.0.32.
  - Error number: 4131; Symbol: `ER_TABLE_IN_SHARED_TABLESPACE`; SQLSTATE: `HY000`  
  
Message: Table '%s' is in a shared tablespace.  
  
`ER_TABLE_IN_SHARED_TABLESPACE` was added in 8.0.32.
  - Error number: 4132; Symbol: `ER_INDEX_OTHER_THAN_PK`; SQLSTATE: `HY000`  
  
Message: Table '%s' has indexes other than primary key.  
  
`ER_INDEX_OTHER_THAN_PK` was added in 8.0.32.
  - Error number: 4133; Symbol: `ER_LOAD_BULK_DATA_UNSORTED`; SQLSTATE: `HY000`  
  
Message: [IN PRIMARY KEY ORDER] specified but data not sorted: LOAD BULK DATA into table '%s' failed: %s  
  
`ER_LOAD_BULK_DATA_UNSORTED` was added in 8.0.32.
  - Error number: 4134; Symbol: `ER_BULK_EXECUTOR_ERROR`; SQLSTATE: `HY000`  
  
Message: Bulk executor error: %s  
  
`ER_BULK_EXECUTOR_ERROR` was added in 8.0.32.
  - Error number: 4135; Symbol: `ER_BULK_READER_LIBCURL_INIT_FAILED`; SQLSTATE: `HY000`  
  
Message: Bulk reader failed to initialize libcurl  
  
`ER_BULK_READER_LIBCURL_INIT_FAILED` was added in 8.0.32.
  - Error number: 4136; Symbol: `ER_BULK_READER_LIBCURL_ERROR`; SQLSTATE: `HY000`

---

Message: Bulk reader got libcurl error: %s

[ER\\_BULK\\_READER\\_LIBCURL\\_ERROR](#) was added in 8.0.32.

- Error number: [4137](#); Symbol: [ER\\_BULK\\_READER\\_SERVER\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk reader got error response from server: %ld

[ER\\_BULK\\_READER\\_SERVER\\_ERROR](#) was added in 8.0.32.

- Error number: [4138](#); Symbol: [ER\\_BULK\\_READER\\_COMMUNICATION\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk reader got error in communication with source server, check the error log for additional details.

[ER\\_BULK\\_READER\\_COMMUNICATION\\_ERROR](#) was added in 8.0.32.

- Error number: [4139](#); Symbol: [ER\\_BULK\\_LOAD\\_DATA\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Bulk loader failed, mysql\_load->load returned an error, check the error log for additional details.

[ER\\_BULK\\_LOAD\\_DATA\\_FAILED](#) was added in 8.0.32.

- Error number: [4140](#); Symbol: [ER\\_BULK\\_LOADER\\_COLUMN\\_TOO\\_BIG\\_FOR\\_LEFTOVER\\_BUFFER](#); SQLSTATE: [HY000](#)

Message: CSV column too big for leftover buffer.

[ER\\_BULK\\_LOADER\\_COLUMN\\_TOO\\_BIG\\_FOR\\_LEFTOVER\\_BUFFER](#) was added in 8.0.32.

- Error number: [4141](#); Symbol: [ER\\_BULK\\_LOADER\\_COMPONENT\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk loader component error: %s

[ER\\_BULK\\_LOADER\\_COMPONENT\\_ERROR](#) was added in 8.0.32.

- Error number: [4142](#); Symbol: [ER\\_BULK\\_LOADER\\_FILE\\_CONTAINS\\_LESS\\_LINES\\_THAN\\_IGNORE\\_CLAUSE](#); SQLSTATE: [HY000](#)

Message: The first file being loaded contained less lines than the ignore clause

[ER\\_BULK\\_LOADER\\_FILE\\_CONTAINS\\_LESS\\_LINES\\_THAN\\_IGNORE\\_CLAUSE](#) was added in 8.0.32.

- Error number: [4143](#); Symbol: [ER\\_BULK\\_PARSER\\_MISSING\\_ENCLOSED\\_BY](#); SQLSTATE: [HY000](#)

Message: Missing ENCLOSED BY character at row %ld in file '%s'. Add OPTIONALLY to the ENCLOSED BY clause to allow this input.

[ER\\_BULK\\_PARSER\\_MISSING\\_ENCLOSED\\_BY](#) was added in 8.0.32.

- Error number: [4144](#); Symbol: [ER\\_BULK\\_PARSER\\_ROW\\_BUFFER\\_MAX\\_TOTAL\\_COLS\\_EXCEEDED](#); SQLSTATE: [HY000](#)

Message: The number of input columns that need to be buffered for parsing exceeded predefined buffer max size for file '%s'.

[ER\\_BULK\\_PARSER\\_ROW\\_BUFFER\\_MAX\\_TOTAL\\_COLS\\_EXCEEDED](#) was added in 8.0.32.

- 
- Error number: 4145; Symbol: `ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED`; SQLSTATE: HY000  
  
Message: The column data that needed to be copied due to escaped characters exceeded the size of the internal copy buffer for file '%s'.  
  
`ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED` was added in 8.0.32.
  - Error number: 4146; Symbol: `ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT`; SQLSTATE: HY000  
  
Message: Unexpected end of input found at row %ld in file '%s'. Data for some columns is missing.  
  
`ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT` was added in 8.0.32.
  - Error number: 4147; Symbol: `ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR`; SQLSTATE: HY000  
  
Message: Unexpected row terminator found at row %ld in file '%s'. Data for some columns is missing.  
  
`ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR` was added in 8.0.32.
  - Error number: 4148; Symbol: `ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY`; SQLSTATE: HY000  
  
Message: Unexpected characters after ending ENCLOSED BY character found at row %ld in file '%s'.  
  
`ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY` was added in 8.0.32.
  - Error number: 4149; Symbol: `ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE`; SQLSTATE: HY000  
  
Message: Unexpected characters after NULL escape (\N) found at row %ld in file '%s'.  
  
`ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE` was added in 8.0.32.
  - Error number: 4150; Symbol: `ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR`; SQLSTATE: HY000  
  
Message: Unexpected characters after column terminator found at row %ld in file '%s'.  
  
`ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR` was added in 8.0.32.
  - Error number: 4151; Symbol: `ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE`; SQLSTATE: HY000  
  
Message: Unexpected end of input found at row %ld in file '%s' resulting in incomplete escape sequence.  
  
`ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE` was added in 8.0.32.
  - Error number: 4152; Symbol: `ER_LOAD_BULK_DATA_FAILED`; SQLSTATE: HY000  
  
Message: LOAD BULK DATA into table '%s' failed: %s  
  
`ER_LOAD_BULK_DATA_FAILED` was added in 8.0.32.
  - Error number: 4153; Symbol: `ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD`; SQLSTATE: HY000  
  
Message: Incorrect %s value: '%s' for column '%s' at row %ld in file '%s'

---

`ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD` was added in 8.0.32.

- Error number: `4154`; Symbol: `ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL`; SQLSTATE: `HY000`

Message: NULL supplied to NOT NULL column '%s' at row %ld in file '%s'

`ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL` was added in 8.0.32.

- Error number: `4155`; Symbol: `ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITH_GR`; SQLSTATE: `HY000`

Message: On a Group Replication channel, setting `REQUIRE_TABLE_PRIMARY_KEY_CHECK` to 'GENERATE' is not allowed.

`ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITH_GR` was added in 8.0.32.

- Error number: `4156`; Symbol: `ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE`; SQLSTATE: `HY000`

Message: Cannot change the '%s' system variable in read-only mode.

`ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE` was added in 8.0.32.

- Error number: `4157`; Symbol: `ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTED_MAX_SIZE`; SQLSTATE: `HY000`

Message: Column can't be added or dropped with `ALGORITHM=INSTANT` as either max possible row size already crosses max permissible row size or may cross it after add. Try `ALGORITHM=INPLACE/COPY`.

`ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTED_MAX_SIZE` was added in 8.0.32.

- Error number: `4158`; Symbol: `ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_FIELDS`; SQLSTATE: `HY000`

Message: Column can't be added to '%s' with `ALGORITHM=INSTANT` anymore. Please try `ALGORITHM=INPLACE/COPY`.

`ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_FIELDS` was added in 8.0.32.

- Error number: `4159`; Symbol: `ER_CANT_SET_PERSISTED`; SQLSTATE: `HY000`

Message: Failed to set persisted options.

`ER_CANT_SET_PERSISTED` was added in 8.0.2.

- Error number: `4160`; Symbol: `ER_INSTALL_COMPONENT_SET_NULL_VALUE`; SQLSTATE: `HY000`

Message: The value supplied for %s in the SET list cannot be null

`ER_INSTALL_COMPONENT_SET_NULL_VALUE` was added in 8.0.33.

- Error number: `4161`; Symbol: `ER_INSTALL_COMPONENT_SET_UNUSED_VALUE`; SQLSTATE: `HY000`

Message: The assignment of %s in SET doesn't match any of the variables registered by the component(s)

`ER_INSTALL_COMPONENT_SET_UNUSED_VALUE` was added in 8.0.33.

- 
- Error number: 4162; Symbol: `ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS`; SQLSTATE: HY000

Message: '%s' is a user defined collation. User defined collations are deprecated and will be removed in a future release. Consider using a compiled collation instead.

`ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS` was added in 8.0.33.

- Error number: 4163; Symbol: `ER_USER_LOCK_OVERLONG_NAME`; SQLSTATE: 42000

Message: User-level lock name '%s' should not exceed %d characters.

`ER_USER_LOCK_OVERLONG_NAME` was added in 8.0.34.

- Error number: 4164; Symbol: `ER_WARN_NO_SPACE_VERSION_COMMENT`; SQLSTATE: HY000

Message: Immediately starting the version comment after the version number is deprecated and may change behavior in a future release. Please insert a white-space character after the version number.

`ER_WARN_NO_SPACE_VERSION_COMMENT` was added in 8.0.34.

- Error number: 4165; Symbol: `ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGED_CHARACTERS`; SQLSTATE: HY000

Message: The new password must have at least '%u' characters that are different from the old password. It has only '%u' character(s) different. For this comparison, uppercase letters and lowercase letters are considered to be equal.

`ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGED_CHARACTERS` was added in 8.0.34.

- Error number: 4166; Symbol: `ER_WARN_DEPRECATED_WITH_NOTE`; SQLSTATE: HY000

Message: '%s' is deprecated and will be removed in a future release. %s

`ER_WARN_DEPRECATED_WITH_NOTE` was added in 8.0.35.

- Error number: 4167; Symbol: `ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY`; SQLSTATE: HY000

Message: Running recursive calls to SQL execution service is not supported

`ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY` was added in 8.0.43.

- Error number: MY-010000; Symbol: `ER_PARSER_TRACE`; SQLSTATE: XX999

Message: Parser saw: %s

`ER_PARSER_TRACE` was added in 8.0.2.

- Error number: MY-010001; Symbol: `ER_BOOTSTRAP_CANT_THREAD`; SQLSTATE: HY000

Message: Can't create thread to handle bootstrap (errno: %d)

`ER_BOOTSTRAP_CANT_THREAD` was added in 8.0.2.



- 
- Error number: [MY-010002](#); Symbol: [ER\\_TRIGGER\\_INVALID\\_VALUE](#); SQLSTATE: [HY000](#)  
Message: Trigger for table '%s'. '%s': invalid %s value (%s).  
[ER\\_TRIGGER\\_INVALID\\_VALUE](#) was added in 8.0.2.
  - Error number: [MY-010003](#); Symbol: [ER\\_OPT\\_WRONG\\_TREE](#); SQLSTATE: [HY000](#)  
Message: Wrong tree: %s  
[ER\\_OPT\\_WRONG\\_TREE](#) was added in 8.0.2.
  - Error number: [MY-010004](#); Symbol: [ER\\_DD\\_FAILSAFE](#); SQLSTATE: [HY000](#)  
Message: Error: Invalid %s  
[ER\\_DD\\_FAILSAFE](#) was added in 8.0.2.
  - Error number: [MY-010005](#); Symbol: [ER\\_DD\\_NO\\_WRITES\\_NO\\_REPOPULATION](#); SQLSTATE: [HY000](#)  
Message: Skip re-populating collations and character sets tables in %s%sread-only mode.  
[ER\\_DD\\_NO\\_WRITES\\_NO\\_REPOPULATION](#) was added in 8.0.2.
  - Error number: [MY-010006](#); Symbol: [ER\\_DD\\_VERSION\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: Using data dictionary with version '%d'.  
[ER\\_DD\\_VERSION\\_FOUND](#) was added in 8.0.2.
  - Error number: [MY-010007](#); Symbol: [ER\\_DD\\_VERSION\\_INSTALLED](#); SQLSTATE: [HY000](#)  
Message: Installed data dictionary with version %d  
[ER\\_DD\\_VERSION\\_INSTALLED](#) was added in 8.0.2.
  - Error number: [MY-010008](#); Symbol: [ER\\_DD\\_VERSION\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)  
Message: Data Dictionary version '%d' not supported.  
[ER\\_DD\\_VERSION\\_UNSUPPORTED](#) was added in 8.0.2.
  - Error number: [MY-010009](#); Symbol: [ER\\_LOG\\_SYSLOG\\_FACILITY\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to set syslog facility to "%s", setting to "%s" (%d) instead.  
[ER\\_LOG\\_SYSLOG\\_FACILITY\\_FAIL](#) was added in 8.0.2, removed after 8.0.12.
  - Error number: [MY-010010](#); Symbol: [ER\\_LOG\\_SYSLOG\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: Cannot open %s; check privileges, or remove syseventlog from --log-error-services!  
[ER\\_LOG\\_SYSLOG\\_CANNOT\\_OPEN](#) was added in 8.0.2.
  - Error number: [MY-010011](#); Symbol: [ER\\_LOG\\_SLOW\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: either restart the query logging by using "SET GLOBAL SLOW\_QUERY\_LOG=ON" or  
[ER\\_LOG\\_SLOW\\_CANNOT\\_OPEN](#) was added in 8.0.2.

- 
- Error number: [MY-010012](#); Symbol: [ER\\_LOG\\_GENERAL\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: either restart the query logging by using "SET GLOBAL GENERAL\_LOG=ON" or [ER\\_LOG\\_GENERAL\\_CANNOT\\_OPEN](#) was added in 8.0.2.
  - Error number: [MY-010013](#); Symbol: [ER\\_LOG\\_CANNOT\\_WRITE](#); SQLSTATE: [HY000](#)  
Message: Failed to write to %s: %s  
[ER\\_LOG\\_CANNOT\\_WRITE](#) was added in 8.0.2.
  - Error number: [MY-010014](#); Symbol: [ER\\_RPL\\_ZOMBIE\\_ENCOUNTED](#); SQLSTATE: [HY000](#)  
Message: While initializing dump thread for replica with %s <%s>, found a zombie dump thread with the same %s. Source is killing the zombie dump thread(%u).  
[ER\\_RPL\\_ZOMBIE\\_ENCOUNTED](#) was added in 8.0.2, removed after 8.0.40.
  - Error number: [MY-010015](#); Symbol: [ER\\_RPL\\_GTID\\_TABLE\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.  
[ER\\_RPL\\_GTID\\_TABLE\\_CANNOT\\_OPEN](#) was added in 8.0.2.
  - Error number: [MY-010016](#); Symbol: [ER\\_SYSTEM\\_SCHEMA\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: System schema directory does not exist.  
[ER\\_SYSTEM\\_SCHEMA\\_NOT\\_FOUND](#) was added in 8.0.2.
  - Error number: [MY-010017](#); Symbol: [ER\\_DD\\_INIT\\_UPGRADE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Error in initializing dictionary, upgrade will do a cleanup and exit  
[ER\\_DD\\_INIT\\_UPGRADE\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010018](#); Symbol: [ER\\_VIEW\\_UNKNOWN\\_CHARSET\\_OR\\_COLLATION](#); SQLSTATE: [HY000](#)  
Message: View '%s'. '%s': unknown charset name and/or collation name (client: '%s'; connection: '%s').  
[ER\\_VIEW\\_UNKNOWN\\_CHARSET\\_OR\\_COLLATION](#) was added in 8.0.2.
  - Error number: [MY-010019](#); Symbol: [ER\\_DD\\_VIEW\\_CANT\\_ALLOC\\_CHARSET](#); SQLSTATE: [HY000](#)  
Message: Error in allocating memory for character set name for view %s.%s.  
[ER\\_DD\\_VIEW\\_CANT\\_ALLOC\\_CHARSET](#) was added in 8.0.2.
  - Error number: [MY-010020](#); Symbol: [ER\\_DD\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Data Dictionary initialization failed.  
[ER\\_DD\\_INIT\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010021](#); Symbol: [ER\\_DD\\_UPDATING\\_PLUGIN\\_MD\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to update plugin metadata in dictionary tables.

---

`ER_DD_UPDATING_PLUGIN_MD_FAILED` was added in 8.0.2.

- Error number: `MY-010022`; Symbol: `ER_DD_POPULATING_TABLES_FAILED`; SQLSTATE: `HY000`  
Message: Failed to Populate DD tables.

`ER_DD_POPULATING_TABLES_FAILED` was added in 8.0.2.

- Error number: `MY-010023`; Symbol: `ER_DD_VIEW_CANT_CREATE`; SQLSTATE: `HY000`  
Message: Error in Creating View %s.%s

`ER_DD_VIEW_CANT_CREATE` was added in 8.0.2.

- Error number: `MY-010024`; Symbol: `ER_DD_METADATA_NOT_FOUND`; SQLSTATE: `HY000`  
Message: Unable to start server. Cannot find the meta data for data dictionary table '%s'.

`ER_DD_METADATA_NOT_FOUND` was added in 8.0.2.

- Error number: `MY-010025`; Symbol: `ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN`; SQLSTATE: `HY000`  
Message: Dictionary cache not empty at shutdown.

`ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN` was added in 8.0.2.

- Error number: `MY-010026`; Symbol: `ER_DD_OBJECT_REMAINS`; SQLSTATE: `HY000`  
Message: Dictionary objects used but not released.

`ER_DD_OBJECT_REMAINS` was added in 8.0.2.

- Error number: `MY-010027`; Symbol: `ER_DD_OBJECT_REMAINS_IN_RELEASER`; SQLSTATE: `HY000`  
Message: Dictionary objects left in default releaser.

`ER_DD_OBJECT_REMAINS_IN_RELEASER` was added in 8.0.2.

- Error number: `MY-010028`; Symbol: `ER_DD_OBJECT_RELEASER_REMAINS`; SQLSTATE: `HY000`  
Message: Dictionary object auto releaser not deleted

`ER_DD_OBJECT_RELEASER_REMAINS` was added in 8.0.2.

- Error number: `MY-010029`; Symbol: `ER_DD_CANT_GET_OBJECT_KEY`; SQLSTATE: `HY000`  
Message: Error: Unable to create primary object key

`ER_DD_CANT_GET_OBJECT_KEY` was added in 8.0.2.

- Error number: `MY-010030`; Symbol: `ER_DD_CANT_CREATE_OBJECT_KEY`; SQLSTATE: `HY000`  
Message: Error: Unable to create object key

`ER_DD_CANT_CREATE_OBJECT_KEY` was added in 8.0.2.

- Error number: `MY-010031`; Symbol: `ER_CANT_CREATE_HANDLE_MGR_THREAD`; SQLSTATE: `HY000`  
Message: Can't create handle\_manager thread (errno= %d)

---

`ER_CANT_CREATE_HANDLE_MGR_THREAD` was added in 8.0.2.

- Error number: `MY-010032`; Symbol: `ER_RPL_REPO_HAS_GAPS`; SQLSTATE: `HY000`

Message: It is not possible to change the type of the relay log's repository because there are workers' repositories with gaps. Please, fix the gaps first before doing such change.

`ER_RPL_REPO_HAS_GAPS` was added in 8.0.2.

- Error number: `MY-010033`; Symbol: `ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY`; SQLSTATE: `HY000`

Message: option 'enforce-gtid-consistency': value '%s' was not recognized. Setting enforce-gtid-consistency to OFF.

`ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY` was added in 8.0.2.

- Error number: `MY-010034`; Symbol: `ER_CHANGED_ENFORCE_GTID_CONSISTENCY`; SQLSTATE: `HY000`

Message: Changed ENFORCE\_GTID\_CONSISTENCY from %s to %s.

`ER_CHANGED_ENFORCE_GTID_CONSISTENCY` was added in 8.0.2.

- Error number: `MY-010035`; Symbol: `ER_CHANGED_GTID_MODE`; SQLSTATE: `HY000`

Message: Changed GTID\_MODE from %s to %s.

`ER_CHANGED_GTID_MODE` was added in 8.0.2.

- Error number: `MY-010036`; Symbol: `ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT`; SQLSTATE: `HY000`

Message: %s is set to a disabled storage engine %s.

`ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT` was added in 8.0.2.

- Error number: `MY-010037`; Symbol: `ER_DEBUG_SYNC_HIT`; SQLSTATE: `HY000`

Message: Debug sync points hit: %s

`ER_DEBUG_SYNC_HIT` was added in 8.0.2.

- Error number: `MY-010038`; Symbol: `ER_DEBUG_SYNC_EXECUTED`; SQLSTATE: `HY000`

Message: Debug sync points executed: %s

`ER_DEBUG_SYNC_EXECUTED` was added in 8.0.2.

- Error number: `MY-010039`; Symbol: `ER_DEBUG_SYNC_THREAD_MAX`; SQLSTATE: `HY000`

Message: Debug sync points max active per thread: %s

`ER_DEBUG_SYNC_THREAD_MAX` was added in 8.0.2.

- Error number: `MY-010040`; Symbol: `ER_DEBUG_SYNC_OOM`; SQLSTATE: `HY000`

Message: Debug Sync Facility disabled due to lack of memory.

---

`ER_DEBUG_SYNC_OOM` was added in 8.0.2.

- Error number: `MY-010041`; Symbol: `ER_CANT_INIT_TC_LOG`; SQLSTATE: `HY000`

Message: Can't init tc log

`ER_CANT_INIT_TC_LOG` was added in 8.0.2.

- Error number: `MY-010042`; Symbol: `ER_EVENT_CANT_INIT_QUEUE`; SQLSTATE: `HY000`

Message: Event Scheduler: Can't initialize the execution queue

`ER_EVENT_CANT_INIT_QUEUE` was added in 8.0.2.

- Error number: `MY-010043`; Symbol: `ER_EVENT_PURGING_QUEUE`; SQLSTATE: `HY000`

Message: Event Scheduler: Purging the queue. %u events

`ER_EVENT_PURGING_QUEUE` was added in 8.0.2.

- Error number: `MY-010044`; Symbol: `ER_EVENT_LAST_EXECUTION`; SQLSTATE: `HY000`

Message: Event Scheduler: Last execution of %s.%s. %s

`ER_EVENT_LAST_EXECUTION` was added in 8.0.2.

- Error number: `MY-010045`; Symbol: `ER_EVENT_MESSAGE_STACK`; SQLSTATE: `HY000`

Message: %\*s

`ER_EVENT_MESSAGE_STACK` was added in 8.0.2.

- Error number: `MY-010046`; Symbol: `ER_EVENT_EXECUTION_FAILED`; SQLSTATE: `HY000`

Message: Event Scheduler: [%s].[%s.%s] event execution failed.

`ER_EVENT_EXECUTION_FAILED` was added in 8.0.2.

- Error number: `MY-010047`; Symbol: `ER_CANT_INIT_SCHEDULER_THREAD`; SQLSTATE: `HY000`

Message: Event Scheduler: Cannot initialize the scheduler thread

`ER_CANT_INIT_SCHEDULER_THREAD` was added in 8.0.2.

- Error number: `MY-010048`; Symbol: `ER_SCHEDULER_STOPPED`; SQLSTATE: `HY000`

Message: Event Scheduler: Stopped

`ER_SCHEDULER_STOPPED` was added in 8.0.2.

- Error number: `MY-010049`; Symbol: `ER_CANT_CREATE_SCHEDULER_THREAD`; SQLSTATE: `HY000`

Message: Event scheduler: Failed to start scheduler, Can not create thread for event scheduler (errno=%d)

`ER_CANT_CREATE_SCHEDULER_THREAD` was added in 8.0.2.

- Error number: `MY-010050`; Symbol: `ER_SCHEDULER_WAITING`; SQLSTATE: `HY000`

---

Message: Event Scheduler: Waiting for the scheduler thread to reply

[ER\\_SCHEDULER\\_WAITING](#) was added in 8.0.2.

- Error number: [MY-010051](#); Symbol: [ER\\_SCHEDULER\\_STARTED](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: scheduler thread started with id %u

[ER\\_SCHEDULER\\_STARTED](#) was added in 8.0.2.

- Error number: [MY-010052](#); Symbol: [ER\\_SCHEDULER\\_STOPPING\\_FAILED\\_TO\\_GET\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Serious error during getting next event to execute. Stopping

[ER\\_SCHEDULER\\_STOPPING\\_FAILED\\_TO\\_GET\\_EVENT](#) was added in 8.0.2.

- Error number: [MY-010053](#); Symbol: [ER\\_SCHEDULER\\_STOPPING\\_FAILED\\_TO\\_CREATE\\_WORKER](#); SQLSTATE: [HY000](#)

Message: Event\_scheduler::execute\_top: Can not create event worker thread (errno=%d). Stopping event scheduler

[ER\\_SCHEDULER\\_STOPPING\\_FAILED\\_TO\\_CREATE\\_WORKER](#) was added in 8.0.2.

- Error number: [MY-010054](#); Symbol: [ER\\_SCHEDULER\\_KILLING](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Killing the scheduler thread, thread id %u

[ER\\_SCHEDULER\\_KILLING](#) was added in 8.0.2.

- Error number: [MY-010055](#); Symbol: [ER\\_UNABLE\\_TO\\_RESOLVE\\_IP](#); SQLSTATE: [HY000](#)

Message: IP address '%s' could not be resolved: %s

[ER\\_UNABLE\\_TO\\_RESOLVE\\_IP](#) was added in 8.0.2.

- Error number: [MY-010056](#); Symbol: [ER\\_UNABLE\\_TO\\_RESOLVE\\_HOSTNAME](#); SQLSTATE: [HY000](#)

Message: Host name '%s' could not be resolved: %s

[ER\\_UNABLE\\_TO\\_RESOLVE\\_HOSTNAME](#) was added in 8.0.2.

- Error number: [MY-010057](#); Symbol: [ER\\_HOSTNAME\\_RESEMBLES\\_IPV4](#); SQLSTATE: [HY000](#)

Message: IP address '%s' has been resolved to the host name '%s', which resembles IPv4-address itself.

[ER\\_HOSTNAME\\_RESEMBLES\\_IPV4](#) was added in 8.0.2.

- Error number: [MY-010058](#); Symbol: [ER\\_HOSTNAME\\_DOESNT\\_RESOLVE\\_TO](#); SQLSTATE: [HY000](#)

Message: Hostname '%s' does not resolve to '%s'.

[ER\\_HOSTNAME\\_DOESNT\\_RESOLVE\\_TO](#) was added in 8.0.2.

- Error number: [MY-010059](#); Symbol: [ER\\_ADDRESSES\\_FOR\\_HOSTNAME\\_HEADER](#); SQLSTATE: [HY000](#)

Message: Hostname '%s' has the following IP addresses:

---

`ER_ADDRESSES_FOR_HOSTNAME_HEADER` was added in 8.0.2.

- Error number: `MY-010060`; Symbol: `ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM`; SQLSTATE: `HY000`

Message: - %s

`ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM` was added in 8.0.2.

- Error number: `MY-010061`; Symbol: `ER_TRG_WITHOUT_DEFINER`; SQLSTATE: `HY000`

Message: Definer clause is missing in Trigger of Table %s. Rebuild Trigger to fix definer.

`ER_TRG_WITHOUT_DEFINER` was added in 8.0.2.

- Error number: `MY-010062`; Symbol: `ER_TRG_NO_CLIENT_CHARSET`; SQLSTATE: `HY000`

Message: Client character set is missing for trigger of table %s. Using default character set.

`ER_TRG_NO_CLIENT_CHARSET` was added in 8.0.2.

- Error number: `MY-010063`; Symbol: `ER_PARSING_VIEW`; SQLSTATE: `HY000`

Message: Error in parsing view %s.%s

`ER_PARSING_VIEW` was added in 8.0.2.

- Error number: `MY-010064`; Symbol: `ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP`; SQLSTATE: `HY000`

Message: Failed to bootstrap components infrastructure.

`ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP` was added in 8.0.2.

- Error number: `MY-010065`; Symbol: `ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN`; SQLSTATE: `HY000`

Message: Failed to shutdown components infrastructure.

`ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN` was added in 8.0.2.

- Error number: `MY-010066`; Symbol: `ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP`; SQLSTATE: `HY000`

Message: Failed to bootstrap persistent components loader.

`ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP` was added in 8.0.2.

- Error number: `MY-010067`; Symbol: `ER_DEPART_WITH_GRACE`; SQLSTATE: `HY000`

Message: Giving %d client threads a chance to die gracefully

`ER_DEPART_WITH_GRACE` was added in 8.0.2.

- Error number: `MY-010068`; Symbol: `ER_CA_SELF_SIGNED`; SQLSTATE: `HY000`

Message: CA certificate %s is self signed.

`ER_CA_SELF_SIGNED` was added in 8.0.2.

- 
- Error number: [MY-010069](#); Symbol: [ER\\_SSL\\_LIBRARY\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Failed to set up SSL because of the following SSL library error: %s  
[ER\\_SSL\\_LIBRARY\\_ERROR](#) was added in 8.0.2.
  - Error number: [MY-010070](#); Symbol: [ER\\_NO\\_THD\\_NO\\_UUID](#); SQLSTATE: [HY000](#)  
Message: Failed to generate a server UUID because it is failed to allocate the THD.  
[ER\\_NO\\_THD\\_NO\\_UUID](#) was added in 8.0.2.
  - Error number: [MY-010071](#); Symbol: [ER\\_UUID\\_SALT](#); SQLSTATE: [HY000](#)  
Message: Salting uuid generator variables, current\_pid: %lu, server\_start\_time: %lu, bytes\_sent: %llu,  
[ER\\_UUID\\_SALT](#) was added in 8.0.2.
  - Error number: [MY-010072](#); Symbol: [ER\\_UUID\\_IS](#); SQLSTATE: [HY000](#)  
Message: Generated uuid: '%s', server\_start\_time: %lu, bytes\_sent: %llu  
[ER\\_UUID\\_IS](#) was added in 8.0.2.
  - Error number: [MY-010073](#); Symbol: [ER\\_UUID\\_INVALID](#); SQLSTATE: [HY000](#)  
Message: The server\_uuid stored in auto.cnf file is not a valid UUID.  
[ER\\_UUID\\_INVALID](#) was added in 8.0.2.
  - Error number: [MY-010074](#); Symbol: [ER\\_UUID\\_SCRUB](#); SQLSTATE: [HY000](#)  
Message: Garbage characters found at the end of the server\_uuid value in auto.cnf file. It should be of length '%d' (UUID\_LENGTH). Clear it and restart the server.  
[ER\\_UUID\\_SCRUB](#) was added in 8.0.2.
  - Error number: [MY-010075](#); Symbol: [ER\\_CREATING\\_NEW\\_UUID](#); SQLSTATE: [HY000](#)  
Message: No existing UUID has been found, so we assume that this is the first time that this server has been started. Generating a new UUID: %s.  
[ER\\_CREATING\\_NEW\\_UUID](#) was added in 8.0.2.
  - Error number: [MY-010076](#); Symbol: [ER\\_CANT\\_CREATE\\_UUID](#); SQLSTATE: [HY000](#)  
Message: Initialization of the server's UUID failed because it could not be read from the auto.cnf file. If this is a new server, the initialization failed because it was not possible to generate a new UUID.  
[ER\\_CANT\\_CREATE\\_UUID](#) was added in 8.0.2.
  - Error number: [MY-010077](#); Symbol: [ER\\_UNKNOWN\\_UNSUPPORTED\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Unknown/unsupported storage engine: %s  
[ER\\_UNKNOWN\\_UNSUPPORTED\\_STORAGE\\_ENGINE](#) was added in 8.0.2.
  - Error number: [MY-010078](#); Symbol: [ER\\_SECURE\\_AUTH\\_VALUE\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)



---

Message: Unsupported value 0 for secure-auth

[ER\\_SECURE\\_AUTH\\_VALUE\\_UNSUPPORTED](#) was added in 8.0.2.

- Error number: [MY-010079](#); Symbol: [ER\\_INVALID\\_INSTRUMENT](#); SQLSTATE: [HY000](#)

Message: Invalid instrument name or value for performance\_schema\_instrument '%s'

[ER\\_INVALID\\_INSTRUMENT](#) was added in 8.0.2.

- Error number: [MY-010080](#); Symbol: [ER\\_INNODB\\_MANDATORY](#); SQLSTATE: [HY000](#)

Message: The use of InnoDB is mandatory since MySQL 5.7. The former options like '--innodb=0/1/OFF/ON' or '--skip-innodb' are ignored.

[ER\\_INNODB\\_MANDATORY](#) was added in 8.0.2.

- Error number: [MY-010082](#); Symbol: [ER\\_OLD\\_PASSWORDS\\_NO\\_MIDDLE\\_GROUND](#); SQLSTATE: [HY000](#)

Message: Invalid old\_passwords mode: 1. Valid values are 2 and 0

[ER\\_OLD\\_PASSWORDS\\_NO\\_MIDDLE\\_GROUND](#) was added in 8.0.2, removed after 8.0.15.

- Error number: [MY-010083](#); Symbol: [ER\\_VERBOSE\\_REQUIRES\\_HELP](#); SQLSTATE: [HY000](#)

Message: --verbose is for use with --help; did you mean --log-error-verbosity?

[ER\\_VERBOSE\\_REQUIRES\\_HELP](#) was added in 8.0.2.

- Error number: [MY-010084](#); Symbol: [ER\\_POINTLESS\\_WITHOUT\\_SLOWLOG](#); SQLSTATE: [HY000](#)

Message: options --log-slow-admin-statements, --log-queries-not-using-indexes and --log-slow-replica-statements have no effect if --slow-query-log is not set

[ER\\_POINTLESS\\_WITHOUT\\_SLOWLOG](#) was added in 8.0.2.

- Error number: [MY-010085](#); Symbol: [ER\\_WASTEFUL\\_NET\\_BUFFER\\_SIZE](#); SQLSTATE: [HY000](#)

Message: net\_buffer\_length (%lu) is set to be larger than max\_allowed\_packet (%lu). Please rectify.

[ER\\_WASTEFUL\\_NET\\_BUFFER\\_SIZE](#) was added in 8.0.2.

- Error number: [MY-010086](#); Symbol: [ER\\_DEPRECATED\\_TIMESTAMP\\_IMPLICIT\\_DEFAULTS](#); SQLSTATE: [HY000](#)

Message: TIMESTAMP with implicit DEFAULT value is deprecated. Please use --explicit\_defaults\_for\_timestamp server option (see documentation for more details).

[ER\\_DEPRECATED\\_TIMESTAMP\\_IMPLICIT\\_DEFAULTS](#) was added in 8.0.2.

- Error number: [MY-010087](#); Symbol: [ER\\_FT\\_BOOL\\_SYNTAX\\_INVALID](#); SQLSTATE: [HY000](#)

Message: Invalid ft-boolean-syntax string: %s

[ER\\_FT\\_BOOL\\_SYNTAX\\_INVALID](#) was added in 8.0.2.

- Error number: [MY-010088](#); Symbol: [ER\\_CREDENTIALLESS\\_AUTO\\_USER\\_BAD](#); SQLSTATE: [HY000](#)

Message: 'NO\_AUTO\_CREATE\_USER' sql mode was not set.

---

`ER_CREDENTIALLESS_AUTO_USER_BAD` was added in 8.0.2.

- Error number: `MY-010089`; Symbol: `ER_CONNECTION_HANDLING_OOM`; SQLSTATE: `HY000`

Message: Could not allocate memory for connection handling

`ER_CONNECTION_HANDLING_OOM` was added in 8.0.2.

- Error number: `MY-010090`; Symbol: `ER_THREAD_HANDLING_OOM`; SQLSTATE: `HY000`

Message: Could not allocate memory for thread handling

`ER_THREAD_HANDLING_OOM` was added in 8.0.2.

- Error number: `MY-010091`; Symbol: `ER_CANT_CREATE_TEST_FILE`; SQLSTATE: `HY000`

Message: Can't create test file %s

`ER_CANT_CREATE_TEST_FILE` was added in 8.0.2.

- Error number: `MY-010092`; Symbol: `ER_CANT_CREATE_PID_FILE`; SQLSTATE: `HY000`

Message: Can't start server: can't create PID file: %s

`ER_CANT_CREATE_PID_FILE` was added in 8.0.2.

- Error number: `MY-010093`; Symbol: `ER_CANT_REMOVE_PID_FILE`; SQLSTATE: `HY000`

Message: Unable to delete pid file: %s

`ER_CANT_REMOVE_PID_FILE` was added in 8.0.2.

- Error number: `MY-010094`; Symbol: `ER_CANT_CREATE_SHUTDOWN_THREAD`; SQLSTATE: `HY000`

Message: Can't create thread to handle shutdown requests (errno= %d)

`ER_CANT_CREATE_SHUTDOWN_THREAD` was added in 8.0.2.

- Error number: `MY-010095`; Symbol: `ER_SEC_FILE_PRIV_CANT_ACCESS_DIR`; SQLSTATE: `HY000`

Message: Failed to access directory for --secure-file-priv. Please make sure that directory exists and is accessible by MySQL Server. Supplied value : %s

`ER_SEC_FILE_PRIV_CANT_ACCESS_DIR` was added in 8.0.2.

- Error number: `MY-010096`; Symbol: `ER_SEC_FILE_PRIV_IGNORED`; SQLSTATE: `HY000`

Message: Ignoring --secure-file-priv value as server is running with --initialize(-insecure).

`ER_SEC_FILE_PRIV_IGNORED` was added in 8.0.2.

- Error number: `MY-010097`; Symbol: `ER_SEC_FILE_PRIV_EMPTY`; SQLSTATE: `HY000`

Message: Insecure configuration for --secure-file-priv: Current value does not restrict location of generated files. Consider setting it to a valid, non-empty path.

`ER_SEC_FILE_PRIV_EMPTY` was added in 8.0.2.

- Error number: `MY-010098`; Symbol: `ER_SEC_FILE_PRIV_NULL`; SQLSTATE: `HY000`

---

Message: --secure-file-priv is set to NULL. Operations related to importing and exporting data are disabled

ER\_SEC\_FILE\_PRIV\_NULL was added in 8.0.2.

- Error number: MY-010099; Symbol: ER\_SEC\_FILE\_PRIV\_DIRECTORY\_INSECURE; SQLSTATE: HY000

Message: Insecure configuration for --secure-file-priv: %s is accessible through --secure-file-priv. Consider choosing a different directory.

ER\_SEC\_FILE\_PRIV\_DIRECTORY\_INSECURE was added in 8.0.2.

- Error number: MY-010100; Symbol: ER\_SEC\_FILE\_PRIV\_CANT\_STAT; SQLSTATE: HY000

Message: Failed to get stat for directory pointed out by --secure-file-priv

ER\_SEC\_FILE\_PRIV\_CANT\_STAT was added in 8.0.2.

- Error number: MY-010101; Symbol: ER\_SEC\_FILE\_PRIV\_DIRECTORY\_PERMISSIONS; SQLSTATE: HY000

Message: Insecure configuration for --secure-file-priv: Location is accessible to all OS users. Consider choosing a different directory.

ER\_SEC\_FILE\_PRIV\_DIRECTORY\_PERMISSIONS was added in 8.0.2.

- Error number: MY-010102; Symbol: ER\_SEC\_FILE\_PRIV\_ARGUMENT\_TOO\_LONG; SQLSTATE: HY000

Message: Value for --secure-file-priv is longer than maximum limit of %d

ER\_SEC\_FILE\_PRIV\_ARGUMENT\_TOO\_LONG was added in 8.0.2.

- Error number: MY-010103; Symbol: ER\_CANT\_CREATE\_NAMED\_PIPES\_THREAD; SQLSTATE: HY000

Message: Can't create thread to handle named pipes (errno= %d)

ER\_CANT\_CREATE\_NAMED\_PIPES\_THREAD was added in 8.0.2.

- Error number: MY-010104; Symbol: ER\_CANT\_CREATE\_TCPIP\_THREAD; SQLSTATE: HY000

Message: Can't create thread to handle TCP/IP (errno= %d)

ER\_CANT\_CREATE\_TCPIP\_THREAD was added in 8.0.2.

- Error number: MY-010105; Symbol: ER\_CANT\_CREATE\_SHM\_THREAD; SQLSTATE: HY000

Message: Can't create thread to handle shared memory (errno= %d)

ER\_CANT\_CREATE\_SHM\_THREAD was added in 8.0.2.

- Error number: MY-010106; Symbol: ER\_CANT\_CREATE\_INTERRUPT\_THREAD; SQLSTATE: HY000

Message: Can't create interrupt-thread (error %d, errno: %d)

ER\_CANT\_CREATE\_INTERRUPT\_THREAD was added in 8.0.2.

- Error number: MY-010107; Symbol: ER\_WRITABLE\_CONFIG\_REMOVED; SQLSTATE: HY000

---

Message: World-writable config file '%s' has been removed.

[ER\\_WRITABLE\\_CONFIG\\_REMOVED](#) was added in 8.0.2.

- Error number: [MY-010108](#); Symbol: [ER\\_CORE\\_VALUES](#); SQLSTATE: [HY000](#)

Message: setrlimit could not change the size of core files to 'infinity'; We may not be able to generate a core file on signals

[ER\\_CORE\\_VALUES](#) was added in 8.0.2.

- Error number: [MY-010109](#); Symbol: [ER\\_WRONG\\_DATETIME\\_SPEC](#); SQLSTATE: [HY000](#)

Message: Wrong date/time format specifier: %s

[ER\\_WRONG\\_DATETIME\\_SPEC](#) was added in 8.0.2.

- Error number: [MY-010110](#); Symbol: [ER\\_RPL\\_BINLOG\\_FILTERS\\_OOM](#); SQLSTATE: [HY000](#)

Message: Could not allocate replication and binlog filters: %s

[ER\\_RPL\\_BINLOG\\_FILTERS\\_OOM](#) was added in 8.0.2.

- Error number: [MY-010111](#); Symbol: [ER\\_KEYCACHE\\_OOM](#); SQLSTATE: [HY000](#)

Message: Cannot allocate the keycache

[ER\\_KEYCACHE\\_OOM](#) was added in 8.0.2.

- Error number: [MY-010112](#); Symbol: [ER\\_CONFIRMING\\_THE\\_FUTURE](#); SQLSTATE: [HY000](#)

Message: Current time has got past year 2038. Validating current time with %d iterations before initiating the normal server shutdown process.

[ER\\_CONFIRMING\\_THE\\_FUTURE](#) was added in 8.0.2.

- Error number: [MY-010113](#); Symbol: [ER\\_BACK\\_IN\\_TIME](#); SQLSTATE: [HY000](#)

Message: Iteration %d: Obtained valid current time from system

[ER\\_BACK\\_IN\\_TIME](#) was added in 8.0.2.

- Error number: [MY-010114](#); Symbol: [ER\\_FUTURE\\_DATE](#); SQLSTATE: [HY000](#)

Message: Iteration %d: Current time obtained from system is greater than 2038

[ER\\_FUTURE\\_DATE](#) was added in 8.0.2.

- Error number: [MY-010115](#); Symbol: [ER\\_UNSUPPORTED\\_DATE](#); SQLSTATE: [HY000](#)

Message: This MySQL server doesn't support dates later then 2038

[ER\\_UNSUPPORTED\\_DATE](#) was added in 8.0.2.

- Error number: [MY-010116](#); Symbol: [ER\\_STARTING\\_AS](#); SQLSTATE: [HY000](#)

Message: %s (mysqld %s) starting as process %lu

[ER\\_STARTING\\_AS](#) was added in 8.0.2.

- 
- Error number: [MY-010117](#); Symbol: [ER\\_SHUTTING\\_DOWN\\_SLAVE\\_THREADS](#); SQLSTATE: [HY000](#)  
Message: Shutting down slave threads  
[ER\\_SHUTTING\\_DOWN\\_SLAVE\\_THREADS](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010117](#); Symbol: [ER\\_SHUTTING\\_DOWN\\_REPLICA\\_THREADS](#); SQLSTATE: [HY000](#)  
Message: Shutting down replica threads  
[ER\\_SHUTTING\\_DOWN\\_REPLICA\\_THREADS](#) was added in 8.0.33.
  - Error number: [MY-010118](#); Symbol: [ER\\_DISCONNECTING\\_REMAINING\\_CLIENTS](#); SQLSTATE: [HY000](#)  
Message: Forcefully disconnecting %d remaining clients  
[ER\\_DISCONNECTING\\_REMAINING\\_CLIENTS](#) was added in 8.0.2.
  - Error number: [MY-010119](#); Symbol: [ER\\_ABORTING](#); SQLSTATE: [HY000](#)  
Message: Aborting  
[ER\\_ABORTING](#) was added in 8.0.2.
  - Error number: [MY-010120](#); Symbol: [ER\\_BINLOG\\_END](#); SQLSTATE: [HY000](#)  
Message: Binlog end  
[ER\\_BINLOG\\_END](#) was added in 8.0.2.
  - Error number: [MY-010121](#); Symbol: [ER\\_CALL\\_ME\\_LOCALHOST](#); SQLSTATE: [HY000](#)  
Message: gethostname failed, using '%s' as hostname  
[ER\\_CALL\\_ME\\_LOCALHOST](#) was added in 8.0.2.
  - Error number: [MY-010122](#); Symbol: [ER\\_USER\\_REQUIRES\\_ROOT](#); SQLSTATE: [HY000](#)  
Message: One can only use the --user switch if running as root  
[ER\\_USER\\_REQUIRES\\_ROOT](#) was added in 8.0.2.
  - Error number: [MY-010123](#); Symbol: [ER REALLY RUN AS ROOT](#); SQLSTATE: [HY000](#)  
Message: Fatal error: Please read "Security" section of the manual to find out how to run mysqld as root!  
[ER REALLY RUN AS ROOT](#) was added in 8.0.2.
  - Error number: [MY-010124](#); Symbol: [ER\\_USER\\_WHAT\\_USER](#); SQLSTATE: [HY000](#)  
Message: Fatal error: Can't change to run as user '%s' ; Please check that the user exists!  
[ER\\_USER\\_WHAT\\_USER](#) was added in 8.0.2.
  - Error number: [MY-010125](#); Symbol: [ER\\_TRANSPORTS\\_WHAT\\_TRANSPORTS](#); SQLSTATE: [HY000](#)  
Message: Server is started with --require-secure-transport=ON but no secure transports (SSL or Shared Memory) are configured.  
[ER\\_TRANSPORTS\\_WHAT\\_TRANSPORTS](#) was added in 8.0.2.

- 
- Error number: [MY-010126](#); Symbol: [ER\\_FAIL\\_SETGID](#); SQLSTATE: [HY000](#)  
Message: setgid: %s  
[ER\\_FAIL\\_SETGID](#) was added in 8.0.2.
  - Error number: [MY-010127](#); Symbol: [ER\\_FAIL\\_SETTUID](#); SQLSTATE: [HY000](#)  
Message: settuid: %s  
[ER\\_FAIL\\_SETTUID](#) was added in 8.0.2.
  - Error number: [MY-010128](#); Symbol: [ER\\_FAIL\\_SETREGID](#); SQLSTATE: [HY000](#)  
Message: setregid: %s  
[ER\\_FAIL\\_SETREGID](#) was added in 8.0.2.
  - Error number: [MY-010129](#); Symbol: [ER\\_FAIL\\_SETREUID](#); SQLSTATE: [HY000](#)  
Message: setreuid: %s  
[ER\\_FAIL\\_SETREUID](#) was added in 8.0.2.
  - Error number: [MY-010130](#); Symbol: [ER\\_FAIL\\_CHROOT](#); SQLSTATE: [HY000](#)  
Message: chroot: %s  
[ER\\_FAIL\\_CHROOT](#) was added in 8.0.2.
  - Error number: [MY-010131](#); Symbol: [ER\\_WIN\\_LISTEN\\_BUT\\_HOW](#); SQLSTATE: [HY000](#)  
Message: TCP/IP, --shared-memory, or --named-pipe should be configured on NT OS  
[ER\\_WIN\\_LISTEN\\_BUT\\_HOW](#) was added in 8.0.2.
  - Error number: [MY-010132](#); Symbol: [ER\\_NOT\\_RIGHT\\_NOW](#); SQLSTATE: [HY000](#)  
Message: CTRL-C ignored during startup  
[ER\\_NOT\\_RIGHT\\_NOW](#) was added in 8.0.2.
  - Error number: [MY-010133](#); Symbol: [ER\\_FIXING\\_CLIENT\\_CHARSET](#); SQLSTATE: [HY000](#)  
Message: '%s' can not be used as client character set. '%s' will be used as default client character set.  
[ER\\_FIXING\\_CLIENT\\_CHARSET](#) was added in 8.0.2.
  - Error number: [MY-010134](#); Symbol: [ER\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Out of memory  
[ER\\_OOM](#) was added in 8.0.2.
  - Error number: [MY-010135](#); Symbol: [ER\\_FAILED\\_TO\\_LOCK\\_MEM](#); SQLSTATE: [HY000](#)  
Message: Failed to lock memory. Errno: %d  
[ER\\_FAILED\\_TO\\_LOCK\\_MEM](#) was added in 8.0.2.

- 
- Error number: [MY-010136](#); Symbol: [ER\\_MYINIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: my\_init() failed.  
[ER\\_MYINIT\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010137](#); Symbol: [ER\\_BEG\\_INITFILE](#); SQLSTATE: [HY000](#)  
Message: Execution of init\_file '%s' started.  
[ER\\_BEG\\_INITFILE](#) was added in 8.0.2.
  - Error number: [MY-010138](#); Symbol: [ER\\_END\\_INITFILE](#); SQLSTATE: [HY000](#)  
Message: Execution of init\_file '%s' ended.  
[ER\\_END\\_INITFILE](#) was added in 8.0.2.
  - Error number: [MY-010139](#); Symbol: [ER\\_CHANGED\\_MAX\\_OPEN\\_FILES](#); SQLSTATE: [HY000](#)  
Message: Changed limits: max\_open\_files: %lu (requested %lu)  
[ER\\_CHANGED\\_MAX\\_OPEN\\_FILES](#) was added in 8.0.2.
  - Error number: [MY-010140](#); Symbol: [ER\\_CANT\\_INCREASE\\_MAX\\_OPEN\\_FILES](#); SQLSTATE: [HY000](#)  
Message: Could not increase number of max\_open\_files to more than %lu (request: %lu)  
[ER\\_CANT\\_INCREASE\\_MAX\\_OPEN\\_FILES](#) was added in 8.0.2.
  - Error number: [MY-010141](#); Symbol: [ER\\_CHANGED\\_MAX\\_CONNECTIONS](#); SQLSTATE: [HY000](#)  
Message: Changed limits: max\_connections: %lu (requested %lu)  
[ER\\_CHANGED\\_MAX\\_CONNECTIONS](#) was added in 8.0.2.
  - Error number: [MY-010142](#); Symbol: [ER\\_CHANGED\\_TABLE\\_OPEN\\_CACHE](#); SQLSTATE: [HY000](#)  
Message: Changed limits: table\_open\_cache: %lu (requested %lu)  
[ER\\_CHANGED\\_TABLE\\_OPEN\\_CACHE](#) was added in 8.0.2.
  - Error number: [MY-010143](#); Symbol: [ER\\_THE\\_USER\\_ABIDES](#); SQLSTATE: [HY000](#)  
Message: Ignoring user change to '%s' because the user was set to '%s' earlier on the command line  
[ER\\_THE\\_USER\\_ABIDES](#) was added in 8.0.2.
  - Error number: [MY-010144](#); Symbol: [ER\\_RPL\\_CANT\\_ADD\\_DO\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Could not add do table rule '%s'!  
[ER\\_RPL\\_CANT\\_ADD\\_DO\\_TABLE](#) was added in 8.0.2.
  - Error number: [MY-010145](#); Symbol: [ER\\_RPL\\_CANT\\_ADD\\_IGNORE\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Could not add ignore table rule '%s'!  
[ER\\_RPL\\_CANT\\_ADD\\_IGNORE\\_TABLE](#) was added in 8.0.2.

- 
- Error number: [MY-010146](#); Symbol: [ER\\_TRACK\\_VARIABLES\\_BOGUS](#); SQLSTATE: [HY000](#)  
Message: The variable session\_track\_system\_variables either has duplicate values or invalid values.  
[ER\\_TRACK\\_VARIABLES\\_BOGUS](#) was added in 8.0.2.
  - Error number: [MY-010147](#); Symbol: [ER\\_EXCESS\\_ARGUMENTS](#); SQLSTATE: [HY000](#)  
Message: Too many arguments (first extra is '%s').  
[ER\\_EXCESS\\_ARGUMENTS](#) was added in 8.0.2.
  - Error number: [MY-010148](#); Symbol: [ER\\_VERBOSE\\_HINT](#); SQLSTATE: [HY000](#)  
Message: Use --verbose --help to get a list of available options!  
[ER\\_VERBOSE\\_HINT](#) was added in 8.0.2.
  - Error number: [MY-010149](#); Symbol: [ER\\_CANT\\_READ\\_ERRMSG](#); SQLSTATE: [HY000](#)  
Message: Unable to read errmsg.sys file  
[ER\\_CANT\\_READ\\_ERRMSG](#) was added in 8.0.2.
  - Error number: [MY-010150](#); Symbol: [ER\\_CANT\\_INIT\\_DBS](#); SQLSTATE: [HY000](#)  
Message: Can't init databases  
[ER\\_CANT\\_INIT\\_DBS](#) was added in 8.0.2.
  - Error number: [MY-010151](#); Symbol: [ER\\_LOG\\_OUTPUT\\_CONTRADICTORY](#); SQLSTATE: [HY000](#)  
Message: There were other values specified to log-output besides NONE. Disabling slow and general logs anyway.  
[ER\\_LOG\\_OUTPUT\\_CONTRADICTORY](#) was added in 8.0.2.
  - Error number: [MY-010152](#); Symbol: [ER\\_NO\\_CSV\\_NO\\_LOG\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: CSV engine is not present, falling back to the log files  
[ER\\_NO\\_CSV\\_NO\\_LOG\\_TABLES](#) was added in 8.0.2.
  - Error number: [MY-010153](#); Symbol: [ER\\_RPL\\_REWRITEDB\\_MISSING\\_ARROW](#); SQLSTATE: [HY000](#)  
Message: Bad syntax in replicate-rewrite-db - missing '->'  
[ER\\_RPL\\_REWRITEDB\\_MISSING\\_ARROW](#) was added in 8.0.2.
  - Error number: [MY-010154](#); Symbol: [ER\\_RPL\\_REWRITEDB\\_EMPTY\\_FROM](#); SQLSTATE: [HY000](#)  
Message: Bad syntax in replicate-rewrite-db - empty FROM db!  
[ER\\_RPL\\_REWRITEDB\\_EMPTY\\_FROM](#) was added in 8.0.2.
  - Error number: [MY-010155](#); Symbol: [ER\\_RPL\\_REWRITEDB\\_EMPTY\\_TO](#); SQLSTATE: [HY000](#)  
Message: Bad syntax in replicate-rewrite-db - empty TO db!  
[ER\\_RPL\\_REWRITEDB\\_EMPTY\\_TO](#) was added in 8.0.2.



- 
- Error number: `MY-010156`; Symbol: `ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE`; SQLSTATE: `HY000`  
  
Message: Although a path was specified for the %s, log tables are used. To enable logging to files use the --log-output=file option.  
  
`ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE` was added in 8.0.2.
  - Error number: `MY-010157`; Symbol: `ER_LOG_FILE_INVALID`; SQLSTATE: `HY000`  
  
Message: Invalid value for %s: %s  
  
`ER_LOG_FILE_INVALID` was added in 8.0.2.
  - Error number: `MY-010158`; Symbol: `ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSUPPORTED`; SQLSTATE: `HY000`  
  
Message: The server option 'lower\_case\_table\_names' is configured to use case sensitive table names but the data directory is on a case-insensitive file system which is an unsupported combination. Please consider either using a case sensitive file system for your data directory or switching to a case-insensitive table name mode.  
  
`ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSUPPORTED` was added in 8.0.2.
  - Error number: `MY-010159`; Symbol: `ER_LOWER_CASE_TABLE_NAMES_USING_2`; SQLSTATE: `HY000`  
  
Message: Setting lower\_case\_table\_names=2 because file system for %s is case insensitive  
  
`ER_LOWER_CASE_TABLE_NAMES_USING_2` was added in 8.0.2.
  - Error number: `MY-010160`; Symbol: `ER_LOWER_CASE_TABLE_NAMES_USING_0`; SQLSTATE: `HY000`  
  
Message: lower\_case\_table\_names was set to 2, even though your the file system '%s' is case sensitive. Now setting lower\_case\_table\_names to 0 to avoid future problems.  
  
`ER_LOWER_CASE_TABLE_NAMES_USING_0` was added in 8.0.2.
  - Error number: `MY-010161`; Symbol: `ER_NEED_LOG_BIN`; SQLSTATE: `HY000`  
  
Message: You need to use --log-bin to make %s work.  
  
`ER_NEED_LOG_BIN` was added in 8.0.2.
  - Error number: `MY-010162`; Symbol: `ER_NEED_FILE_INSTEAD_OF_DIR`; SQLSTATE: `HY000`  
  
Message: Path '%s' is a directory name, please specify a file name for %s option  
  
`ER_NEED_FILE_INSTEAD_OF_DIR` was added in 8.0.2.
  - Error number: `MY-010163`; Symbol: `ER_LOG_BIN_BETTER_WITH_NAME`; SQLSTATE: `HY000`  
  
Message: No argument was provided to --log-bin, and --log-bin-index was not used; so replication may break when this MySQL server acts as a source and has his hostname changed!! Please use '--log-bin=%s' to avoid this problem.  
  
`ER_LOG_BIN_BETTER_WITH_NAME` was added in 8.0.2.
  - Error number: `MY-010164`; Symbol: `ER_BINLOG_NEEDS_SERVERID`; SQLSTATE: `HY000`

---

Message: You have enabled the binary log, but you haven't provided the mandatory server-id. Please refer to the proper server start-up parameters documentation

[ER\\_BINLOG\\_NEEDS\\_SERVERID](#) was added in 8.0.2.

- Error number: [MY-010165](#); Symbol: [ER\\_RPL\\_CANT\\_MAKE\\_PATHS](#); SQLSTATE: [HY000](#)

Message: Unable to create replication path names: out of memory or path names too long (path name exceeds %d or file name exceeds %d).

[ER\\_RPL\\_CANT\\_MAKE\\_PATHS](#) was added in 8.0.2.

- Error number: [MY-010166](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_GTID](#); SQLSTATE: [HY000](#)

Message: Failed to initialize GTID structures.

[ER\\_CANT\\_INITIALIZE\\_GTID](#) was added in 8.0.2.

- Error number: [MY-010167](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_EARLY\\_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize early plugins.

[ER\\_CANT\\_INITIALIZE\\_EARLY\\_PLUGINS](#) was added in 8.0.2.

- Error number: [MY-010168](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_BUILTIN\\_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize builtin plugins.

[ER\\_CANT\\_INITIALIZE\\_BUILTIN\\_PLUGINS](#) was added in 8.0.2.

- Error number: [MY-010169](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_DYNAMIC\\_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize dynamic plugins.

[ER\\_CANT\\_INITIALIZE\\_DYNAMIC\\_PLUGINS](#) was added in 8.0.2.

- Error number: [MY-010170](#); Symbol: [ER\\_PERFSCHEMA\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Performance schema disabled (reason: init failed).

[ER\\_PERFSCHEMA\\_INIT\\_FAILED](#) was added in 8.0.2.

- Error number: [MY-010171](#); Symbol: [ER\\_STACKSIZE\\_UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: Asked for %lu thread stack, but got %ld

[ER\\_STACKSIZE\\_UNEXPECTED](#) was added in 8.0.2.

- Error number: [MY-010172](#); Symbol: [ER\\_CANT\\_SET\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: failed to set datadir to %s

[ER\\_CANT\\_SET\\_DATADIR](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010173](#); Symbol: [ER\\_CANT\\_STAT\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: Can't read data directory's stats (%d): %s. Assuming that it's not owned by the same user/group

---

`ER_CANT_STAT_DATADIR` was added in 8.0.2.

- Error number: `MY-010174`; Symbol: `ER_CANT_CHOWN_DATADIR`; SQLSTATE: `HY000`

Message: Can't change data directory owner to %s

`ER_CANT_CHOWN_DATADIR` was added in 8.0.2.

- Error number: `MY-010175`; Symbol: `ER_CANT_SET_UP_PERSISTED_VALUES`; SQLSTATE: `HY000`

Message: Setting persistent options failed.

`ER_CANT_SET_UP_PERSISTED_VALUES` was added in 8.0.2.

- Error number: `MY-010176`; Symbol: `ER_CANT_SAVE_GTIDS`; SQLSTATE: `HY000`

Message: Failed to save the set of Global Transaction Identifiers of the last binary log into the `mysql.gtid_executed` table while the server was shutting down. The next server restart will make another attempt to save Global Transaction Identifiers into the table.

`ER_CANT_SAVE_GTIDS` was added in 8.0.2.

- Error number: `MY-010177`; Symbol: `ER_AUTH_CANT_SET_DEFAULT_PLUGIN`; SQLSTATE: `HY000`

Message: Can't start server: Invalid value for --default-authentication-plugin

`ER_AUTH_CANT_SET_DEFAULT_PLUGIN` was added in 8.0.2.

- Error number: `MY-010178`; Symbol: `ER_CANT_JOIN_SHUTDOWN_THREAD`; SQLSTATE: `HY000`

Message: Could not join %sthread. error:%d

`ER_CANT_JOIN_SHUTDOWN_THREAD` was added in 8.0.2.

- Error number: `MY-010179`; Symbol: `ER_CANT_HASH_DO_AND_IGNORE_RULES`; SQLSTATE: `HY000`

Message: An error occurred while building `do_table` and `ignore_table` rules to hashes for global replication filter.

`ER_CANT_HASH_DO_AND_IGNORE_RULES` was added in 8.0.2.

- Error number: `MY-010180`; Symbol: `ER_CANT_OPEN_CA`; SQLSTATE: `HY000`

Message: Error opening CA certificate file

`ER_CANT_OPEN_CA` was added in 8.0.2.

- Error number: `MY-010181`; Symbol: `ER_CANT_ACCESS_CAPATH`; SQLSTATE: `HY000`

Message: Error accessing directory pointed by --ssl-capath

`ER_CANT_ACCESS_CAPATH` was added in 8.0.2.

- Error number: `MY-010182`; Symbol: `ER_SSL_TRYING_DATADIR_DEFAULTS`; SQLSTATE: `HY000`

Message: Found %s, %s and %s in data directory. Trying to enable SSL support using them.

`ER_SSL_TRYING_DATADIR_DEFAULTS` was added in 8.0.2.

- 
- Error number: [MY-010183](#); Symbol: [ER\\_AUTO\\_OPTIONS\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to create %s(file: '%s', errno %d)  
[ER\\_AUTO\\_OPTIONS\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010184](#); Symbol: [ER\\_CANT\\_INIT\\_TIMER](#); SQLSTATE: [HY000](#)  
Message: Failed to initialize timer component (errno %d).  
[ER\\_CANT\\_INIT\\_TIMER](#) was added in 8.0.2.
  - Error number: [MY-010185](#); Symbol: [ER\\_SERVERID\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)  
Message: server-id configured is too large to represent with server-id-bits configured.  
[ER\\_SERVERID\\_TOO\\_LARGE](#) was added in 8.0.2.
  - Error number: [MY-010186](#); Symbol: [ER\\_DEFAULT\\_SE\\_UNAVAILABLE](#); SQLSTATE: [HY000](#)  
Message: Default%s storage engine (%s) is not available  
[ER\\_DEFAULT\\_SE\\_UNAVAILABLE](#) was added in 8.0.2.
  - Error number: [MY-010187](#); Symbol: [ER\\_CANT\\_OPEN\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Could not open file '%s' for error logging%s%s  
[ER\\_CANT\\_OPEN\\_ERROR\\_LOG](#) was added in 8.0.2.
  - Error number: [MY-010188](#); Symbol: [ER\\_INVALID\\_ERROR\\_LOG\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Invalid log file name after expanding symlinks: '%s'  
[ER\\_INVALID\\_ERROR\\_LOG\\_NAME](#) was added in 8.0.2.
  - Error number: [MY-010189](#); Symbol: [ER\\_RPL\\_INFINITY\\_DENIED](#); SQLSTATE: [HY000](#)  
Message: using --replicate-same-server-id in conjunction with --log-replica-updates is impossible, it would lead to infinite loops in this server.  
[ER\\_RPL\\_INFINITY\\_DENIED](#) was added in 8.0.2.
  - Error number: [MY-010190](#); Symbol: [ER\\_RPL\\_INFINITY\\_IGNORED](#); SQLSTATE: [HY000](#)  
Message: using --replicate-same-server-id in conjunction with --log-replica-updates would lead to infinite loops in this server. However this will be ignored as the --log-bin option is not defined or your server is running with global transaction identifiers enabled.  
[ER\\_RPL\\_INFINITY\\_IGNORED](#) was added in 8.0.2.
  - Error number: [MY-010191](#); Symbol: [ER\\_NDB\\_TABLES\\_NOT\\_READY](#); SQLSTATE: [HY000](#)  
Message: NDB : Tables not available after %lu seconds. Consider increasing --ndb-wait-setup value  
[ER\\_NDB\\_TABLES\\_NOT\\_READY](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010192](#); Symbol: [ER\\_TABLE\\_CHECK\\_INTACT](#); SQLSTATE: [HY000](#)  
Message: %s

---

`ER_TABLE_CHECK_INTACT` was added in 8.0.2.

- Error number: `MY-010193`; Symbol: `ER_DD_TABLESPACE_NOT_FOUND`; SQLSTATE: `HY000`

Message: Unable to start server. The data dictionary tablespace '%s' does not exist.

`ER_DD_TABLESPACE_NOT_FOUND` was added in 8.0.2.

- Error number: `MY-010194`; Symbol: `ER_DD_TRG_CONNECTION_COLLATION_MISSING`; SQLSTATE: `HY000`

Message: Connection collation is missing for trigger of table %s. Using default connection collation.

`ER_DD_TRG_CONNECTION_COLLATION_MISSING` was added in 8.0.2.

- Error number: `MY-010195`; Symbol: `ER_DD_TRG_DB_COLLATION_MISSING`; SQLSTATE: `HY000`

Message: Database collation is missing for trigger of table %s. Using Default character set.

`ER_DD_TRG_DB_COLLATION_MISSING` was added in 8.0.2.

- Error number: `MY-010196`; Symbol: `ER_DD_TRG_DEFINER_OOM`; SQLSTATE: `HY000`

Message: Error in Memory allocation for Definer %s for Trigger.

`ER_DD_TRG_DEFINER_OOM` was added in 8.0.2.

- Error number: `MY-010197`; Symbol: `ER_DD_TRG_FILE_UNREADABLE`; SQLSTATE: `HY000`

Message: Error in reading %s.TRG file.

`ER_DD_TRG_FILE_UNREADABLE` was added in 8.0.2.

- Error number: `MY-010198`; Symbol: `ER_TRG_CANT_PARSE`; SQLSTATE: `HY000`

Message: Error in parsing Triggers from %s.TRG file.

`ER_TRG_CANT_PARSE` was added in 8.0.2.

- Error number: `MY-010199`; Symbol: `ER_DD_TRG_CANT_ADD`; SQLSTATE: `HY000`

Message: Error in creating DD entry for Trigger %s.%s

`ER_DD_TRG_CANT_ADD` was added in 8.0.2.

- Error number: `MY-010200`; Symbol: `ER_DD_CANT_RESOLVE_VIEW`; SQLSTATE: `HY000`

Message: Resolving dependency for the view '%s.%s' failed. View is no more valid to use

`ER_DD_CANT_RESOLVE_VIEW` was added in 8.0.2.

- Error number: `MY-010201`; Symbol: `ER_DD_VIEW_WITHOUT_DEFINER`; SQLSTATE: `HY000`

Message: %s.%s has no definer (as per an old view format). Current user is used as definer. Please recreate the view.

`ER_DD_VIEW_WITHOUT_DEFINER` was added in 8.0.2.

- Error number: `MY-010202`; Symbol: `ER_PLUGIN_INIT_FAILED`; SQLSTATE: `HY000`

---

Message: Plugin '%s' init function returned error.

[ER\\_PLUGIN\\_INIT\\_FAILED](#) was added in 8.0.2.

- Error number: [MY-010203](#); Symbol: [ER\\_RPL\\_TRX\\_DELEGATES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Initialization of transaction delegates failed. Please report a bug.

[ER\\_RPL\\_TRX\\_DELEGATES\\_INIT\\_FAILED](#) was added in 8.0.2.

- Error number: [MY-010204](#); Symbol: [ER\\_RPL\\_BINLOG\\_STORAGE\\_DELEGATES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Initialization binlog storage delegates failed. Please report a bug.

[ER\\_RPL\\_BINLOG\\_STORAGE\\_DELEGATES\\_INIT\\_FAILED](#) was added in 8.0.2.

- Error number: [MY-010205](#); Symbol: [ER\\_RPL\\_BINLOG\\_TRANSMIT\\_DELEGATES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Initialization of binlog transmit delegates failed. Please report a bug.

[ER\\_RPL\\_BINLOG\\_TRANSMIT\\_DELEGATES\\_INIT\\_FAILED](#) was added in 8.0.2.

- Error number: [MY-010206](#); Symbol: [ER\\_RPL\\_BINLOG\\_RELAY\\_DELEGATES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Initialization binlog relay IO delegates failed. Please report a bug.

[ER\\_RPL\\_BINLOG\\_RELAY\\_DELEGATES\\_INIT\\_FAILED](#) was added in 8.0.2.

- Error number: [MY-010207](#); Symbol: [ER\\_RPL\\_PLUGIN\\_FUNCTION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Run function '...' in plugin '%s' failed

[ER\\_RPL\\_PLUGIN\\_FUNCTION\\_FAILED](#) was added in 8.0.2.

- Error number: [MY-010208](#); Symbol: [ER\\_SQL\\_HA\\_READ\\_FAILED](#); SQLSTATE: [HY000](#)

Message: mysql\_ha\_read: Got error %d when reading table '%s'

[ER\\_SQL\\_HA\\_READ\\_FAILED](#) was added in 8.0.2.

- Error number: [MY-010209](#); Symbol: [ER\\_SR\\_BOGUS\\_VALUE](#); SQLSTATE: [HY000](#)

Message: Stored routine '%s'. '%s': invalid value in column %s.

[ER\\_SR\\_BOGUS\\_VALUE](#) was added in 8.0.2.

- Error number: [MY-010210](#); Symbol: [ER\\_SR\\_INVALID\\_CONTEXT](#); SQLSTATE: [HY000](#)

Message: Invalid creation context '%s.%s'.

[ER\\_SR\\_INVALID\\_CONTEXT](#) was added in 8.0.2.

- Error number: [MY-010211](#); Symbol: [ER\\_READING\\_TABLE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Got error %d when reading table '%s'

---

[ER\\_READING\\_TABLE\\_FAILED](#) was added in 8.0.2.

- Error number: [MY-010212](#); Symbol: [ER\\_DES\\_FILE\\_WRONG\\_KEY](#); SQLSTATE: [HY000](#)

Message: load\_des\_file: Found wrong key\_number: %c

[ER\\_DES\\_FILE\\_WRONG\\_KEY](#) was added in 8.0.2.

- Error number: [MY-010214](#); Symbol: [ER\\_JSON\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Persisted config file is corrupt. Please ensure mysqld-auto.cnf file is valid JSON.

[ER\\_JSON\\_PARSE\\_ERROR](#) was added in 8.0.2.

- Error number: [MY-010215](#); Symbol: [ER\\_CONFIG\\_OPTION\\_WITHOUT\\_GROUP](#); SQLSTATE: [HY000](#)

Message: Found option without preceding group in config file

[ER\\_CONFIG\\_OPTION\\_WITHOUT\\_GROUP](#) was added in 8.0.2.

- Error number: [MY-010216](#); Symbol: [ER\\_VALGRIND\\_DO\\_QUICK\\_LEAK\\_CHECK](#); SQLSTATE: [HY000](#)

Message: VALGRIND\_DO\_QUICK\_LEAK\_CHECK

[ER\\_VALGRIND\\_DO\\_QUICK\\_LEAK\\_CHECK](#) was added in 8.0.2.

- Error number: [MY-010217](#); Symbol: [ER\\_VALGRIND\\_COUNT\\_LEAKS](#); SQLSTATE: [HY000](#)

Message: VALGRIND\_COUNT\_LEAKS reports %lu leaked bytes for query '%.\*s'

[ER\\_VALGRIND\\_COUNT\\_LEAKS](#) was added in 8.0.2.

- Error number: [MY-010218](#); Symbol: [ER\\_LOAD\\_DATA\\_INFILE\\_FAILED\\_IN\\_UNEXPECTED\\_WAY](#); SQLSTATE: [HY000](#)

Message: LOAD DATA INFILE in the replica SQL Thread can only read from --replica-load-tmpdir. Please, report a bug.

[ER\\_LOAD\\_DATA\\_INFILE\\_FAILED\\_IN\\_UNEXPECTED\\_WAY](#) was added in 8.0.2.

- Error number: [MY-010219](#); Symbol: [ER\\_UNKNOWN\\_ERROR\\_NUMBER](#); SQLSTATE: [HY000](#)

Message: Got unknown error: %d

[ER\\_UNKNOWN\\_ERROR\\_NUMBER](#) was added in 8.0.2.

- Error number: [MY-010220](#); Symbol: [ER\\_UDF\\_CANT\\_ALLOC\\_FOR\\_STRUCTURES](#); SQLSTATE: [HY000](#)

Message: Can't allocate memory for udf structures

[ER\\_UDF\\_CANT\\_ALLOC\\_FOR\\_STRUCTURES](#) was added in 8.0.2.

- Error number: [MY-010221](#); Symbol: [ER\\_UDF\\_CANT\\_ALLOC\\_FOR\\_FUNCTION](#); SQLSTATE: [HY000](#)

Message: Can't alloc memory for udf function: '%s'

[ER\\_UDF\\_CANT\\_ALLOC\\_FOR\\_FUNCTION](#) was added in 8.0.2.

- 
- Error number: [MY-010222](#); Symbol: [ER\\_UDF\\_INVALID\\_ROW\\_IN\\_FUNCTION\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Invalid row in mysql.func table for function '%s'

[ER\\_UDF\\_INVALID\\_ROW\\_IN\\_FUNCTION\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010223](#); Symbol: [ER\\_UDF\\_CANT\\_OPEN\\_FUNCTION\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not open the mysql.func table. Please perform the MySQL upgrade procedure.

[ER\\_UDF\\_CANT\\_OPEN\\_FUNCTION\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010224](#); Symbol: [ER\\_XA\\_RECOVER\\_FOUND\\_TRX\\_IN\\_SE](#); SQLSTATE: [HY000](#)

Message: Found %d prepared transaction(s) in %s

[ER\\_XA\\_RECOVER\\_FOUND\\_TRX\\_IN\\_SE](#) was added in 8.0.2.

- Error number: [MY-010225](#); Symbol: [ER\\_XA\\_RECOVER\\_FOUND\\_XA\\_TRX](#); SQLSTATE: [HY000](#)

Message: Found %d prepared XA transactions

[ER\\_XA\\_RECOVER\\_FOUND\\_XA\\_TRX](#) was added in 8.0.2.

- Error number: [MY-010226](#); Symbol: [ER\\_XA\\_IGNOREING\\_XID](#); SQLSTATE: [HY000](#)

Message: ignore xid %s

[ER\\_XA\\_IGNOREING\\_XID](#) was added in 8.0.2, removed after 8.0.29.

- Error number: [MY-010227](#); Symbol: [ER\\_XA\\_COMMITTING\\_XID](#); SQLSTATE: [HY000](#)

Message: commit xid %s

[ER\\_XA\\_COMMITTING\\_XID](#) was added in 8.0.2, removed after 8.0.29.

- Error number: [MY-010228](#); Symbol: [ER\\_XA\\_ROLLING\\_BACK\\_XID](#); SQLSTATE: [HY000](#)

Message: rollback xid %s

[ER\\_XA\\_ROLLING\\_BACK\\_XID](#) was added in 8.0.2, removed after 8.0.29.

- Error number: [MY-010229](#); Symbol: [ER\\_XA\\_STARTING\\_RECOVERY](#); SQLSTATE: [HY000](#)

Message: Starting XA crash recovery...

[ER\\_XA\\_STARTING\\_RECOVERY](#) was added in 8.0.2.

- Error number: [MY-010230](#); Symbol: [ER\\_XA\\_NO\\_MULTI\\_2PC\\_HEURISTIC\\_RECOVER](#); SQLSTATE: [HY000](#)

Message: --tc-heuristic-recover rollback strategy is not safe on systems with more than one 2-phase-commit-capable storage engine. Aborting crash recovery.

[ER\\_XA\\_NO\\_MULTI\\_2PC\\_HEURISTIC\\_RECOVER](#) was added in 8.0.2.



- 
- Error number: [MY-010231](#); Symbol: [ER\\_XA\\_RECOVER\\_EXPLANATION](#); SQLSTATE: [HY000](#)

Message: Found %d prepared transactions! It means that mysqld was not shut down properly last time and critical recovery information (last binlog or %s file) was manually deleted after a crash. You have to start mysqld with --tc-heuristic-recover switch to commit or rollback pending transactions.

[ER\\_XA\\_RECOVER\\_EXPLANATION](#) was added in 8.0.2.

- Error number: [MY-010232](#); Symbol: [ER\\_XA\\_RECOVERY\\_DONE](#); SQLSTATE: [HY000](#)

Message: XA crash recovery finished.

[ER\\_XA\\_RECOVERY\\_DONE](#) was added in 8.0.2.

- Error number: [MY-010233](#); Symbol: [ER\\_TRX\\_GTID\\_COLLECT\\_REJECT](#); SQLSTATE: [HY000](#)

Message: Failed to collect GTID to send in the response packet!

[ER\\_TRX\\_GTID\\_COLLECT\\_REJECT](#) was added in 8.0.2.

- Error number: [MY-010234](#); Symbol: [ER\\_SQL\\_AUTHOR\\_DEFAULT\\_ROLES\\_FAIL](#); SQLSTATE: [HY000](#)

Message: MYSQL.DEFAULT\_ROLES couldn't be updated for authorization identifier %s

[ER\\_SQL\\_AUTHOR\\_DEFAULT\\_ROLES\\_FAIL](#) was added in 8.0.2.

- Error number: [MY-010235](#); Symbol: [ER\\_SQL\\_USER\\_TABLE\\_CREATE\\_WARNING](#); SQLSTATE: [HY000](#)

Message: Following users were specified in CREATE USER IF NOT EXISTS but they already exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s

[ER\\_SQL\\_USER\\_TABLE\\_CREATE\\_WARNING](#) was added in 8.0.2.

- Error number: [MY-010236](#); Symbol: [ER\\_SQL\\_USER\\_TABLE\\_ALTER\\_WARNING](#); SQLSTATE: [HY000](#)

Message: Following users were specified in ALTER USER IF EXISTS but they do not exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s

[ER\\_SQL\\_USER\\_TABLE\\_ALTER\\_WARNING](#) was added in 8.0.2.

- Error number: [MY-010237](#); Symbol: [ER\\_ROW\\_IN\\_WRONG\\_PARTITION\\_PLEASE\\_REPAIR](#); SQLSTATE: [HY000](#)

Message: Table '%s' corrupted: row in wrong partition: %s -- Please REPAIR the table!

[ER\\_ROW\\_IN\\_WRONG\\_PARTITION\\_PLEASE\\_REPAIR](#) was added in 8.0.2.

- Error number: [MY-010238](#); Symbol: [ER\\_MYISAM\\_CRASHED\\_ERROR\\_IN\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Got an error from thread\_id=%u, %s:%d

[ER\\_MYISAM\\_CRASHED\\_ERROR\\_IN\\_THREAD](#) was added in 8.0.2.

- 
- Error number: [MY-010239](#); Symbol: [ER\\_MYISAM\\_CRASHED\\_ERROR\\_IN](#); SQLSTATE: [HY000](#)  
Message: Got an error from unknown thread, %s:%d  
[ER\\_MYISAM\\_CRASHED\\_ERROR\\_IN](#) was added in 8.0.2.
  - Error number: [MY-010240](#); Symbol: [ER\\_TOO\\_MANY\\_STORAGE\\_ENGINES](#); SQLSTATE: [HY000](#)  
Message: Too many storage engines!  
[ER\\_TOO\\_MANY\\_STORAGE\\_ENGINES](#) was added in 8.0.2.
  - Error number: [MY-010241](#); Symbol: [ER\\_SE\\_TYPECODE\\_CONFLICT](#); SQLSTATE: [HY000](#)  
Message: Storage engine '%s' has conflicting typecode. Assigning value %d.  
[ER\\_SE\\_TYPECODE\\_CONFLICT](#) was added in 8.0.2.
  - Error number: [MY-010242](#); Symbol: [ER\\_TRX\\_WRITE\\_SET\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Out of memory on transaction write set extraction  
[ER\\_TRX\\_WRITE\\_SET\\_OOM](#) was added in 8.0.2.
  - Error number: [MY-010243](#); Symbol: [ER\\_HANDLERTON\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Unable to allocate memory for plugin '%s' handlerton.  
[ER\\_HANDLERTON\\_OOM](#) was added in 8.0.2.
  - Error number: [MY-010244](#); Symbol: [ER\\_CONN\\_SHM\\_LISTENER](#); SQLSTATE: [HY000](#)  
Message: Shared memory setting up listener  
[ER\\_CONN\\_SHM\\_LISTENER](#) was added in 8.0.2.
  - Error number: [MY-010245](#); Symbol: [ER\\_CONN\\_SHM\\_CANT\\_CREATE\\_SERVICE](#); SQLSTATE: [HY000](#)  
Message: Can't create shared memory service: %s. : %s  
[ER\\_CONN\\_SHM\\_CANT\\_CREATE\\_SERVICE](#) was added in 8.0.2.
  - Error number: [MY-010246](#); Symbol: [ER\\_CONN\\_SHM\\_CANT\\_CREATE\\_CONNECTION](#); SQLSTATE: [HY000](#)  
Message: Can't create shared memory connection: %s. : %s  
[ER\\_CONN\\_SHM\\_CANT\\_CREATE\\_CONNECTION](#) was added in 8.0.2.
  - Error number: [MY-010247](#); Symbol: [ER\\_CONN\\_PIP\\_CANT\\_CREATE\\_EVENT](#); SQLSTATE: [HY000](#)  
Message: Can't create event, last error=%u  
[ER\\_CONN\\_PIP\\_CANT\\_CREATE\\_EVENT](#) was added in 8.0.2.
  - Error number: [MY-010248](#); Symbol: [ER\\_CONN\\_PIP\\_CANT\\_CREATE\\_PIPE](#); SQLSTATE: [HY000](#)  
Message: Can't create new named pipe!: %s  
[ER\\_CONN\\_PIP\\_CANT\\_CREATE\\_PIPE](#) was added in 8.0.2.

- 
- Error number: `MY-010249`; Symbol: `ER_CONN_PER_THREAD_NO_THREAD`; SQLSTATE: `HY000`  
Message: Can't create thread to handle new connection(errno= %d)  
`ER_CONN_PER_THREAD_NO_THREAD` was added in 8.0.2.
  - Error number: `MY-010250`; Symbol: `ER_CONN_TCP_NO_SOCKET`; SQLSTATE: `HY000`  
Message: Failed to create a socket for %s '%s': errno: %d.  
`ER_CONN_TCP_NO_SOCKET` was added in 8.0.2.
  - Error number: `MY-010251`; Symbol: `ER_CONN_TCP_CREATED`; SQLSTATE: `HY000`  
Message: Server socket created on IP: '%s'.  
`ER_CONN_TCP_CREATED` was added in 8.0.2.
  - Error number: `MY-010252`; Symbol: `ER_CONN_TCP_ADDRESS`; SQLSTATE: `HY000`  
Message: Server hostname (bind-address): '%s'; port: %d  
`ER_CONN_TCP_ADDRESS` was added in 8.0.2.
  - Error number: `MY-010253`; Symbol: `ER_CONN_TCP_IPV6_AVAILABLE`; SQLSTATE: `HY000`  
Message: IPv6 is available.  
`ER_CONN_TCP_IPV6_AVAILABLE` was added in 8.0.2.
  - Error number: `MY-010254`; Symbol: `ER_CONN_TCP_IPV6_UNAVAILABLE`; SQLSTATE: `HY000`  
Message: IPv6 is not available.  
`ER_CONN_TCP_IPV6_UNAVAILABLE` was added in 8.0.2.
  - Error number: `MY-010255`; Symbol: `ER_CONN_TCP_ERROR_WITH_STRERROR`; SQLSTATE: `HY000`  
Message: Can't create IP socket: %s  
`ER_CONN_TCP_ERROR_WITH_STRERROR` was added in 8.0.2.
  - Error number: `MY-010256`; Symbol: `ER_CONN_TCP_CANT_RESOLVE_HOSTNAME`; SQLSTATE: `HY000`  
Message: Can't start server: cannot resolve hostname!  
`ER_CONN_TCP_CANT_RESOLVE_HOSTNAME` was added in 8.0.2.
  - Error number: `MY-010257`; Symbol: `ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT`; SQLSTATE: `HY000`  
Message: Do you already have another mysqld server running on port: %d ?  
`ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT` was added in 8.0.2.
  - Error number: `MY-010258`; Symbol: `ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET`; SQLSTATE: `HY000`  
Message: Do you already have another mysqld server running on socket: %s ?

---

`ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET` was added in 8.0.2.

- Error number: `MY-010259`; Symbol: `ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE`; SQLSTATE: `HY000`

Message: Another process with pid %d is using unix socket file.

`ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE` was added in 8.0.2.

- Error number: `MY-010260`; Symbol: `ER_CONN_TCP_CANT_RESET_V6ONLY`; SQLSTATE: `HY000`

Message: Failed to reset IPV6\_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.

`ER_CONN_TCP_CANT_RESET_V6ONLY` was added in 8.0.2.

- Error number: `MY-010261`; Symbol: `ER_CONN_TCP_BIND_RETRY`; SQLSTATE: `HY000`

Message: Retrying bind on TCP/IP port %u

`ER_CONN_TCP_BIND_RETRY` was added in 8.0.2.

- Error number: `MY-010262`; Symbol: `ER_CONN_TPC_BIND_FAIL`; SQLSTATE: `HY000`

Message: Can't start server: Bind on TCP/IP port: %s

`ER_CONN_TPC_BIND_FAIL` was added in 8.0.2, removed after 8.0.11.

- Error number: `MY-010262`; Symbol: `ER_CONN_TCP_BIND_FAIL`; SQLSTATE: `HY000`

Message: Can't start server: Bind on TCP/IP port: %s

`ER_CONN_TCP_BIND_FAIL` was added in 8.0.12.

- Error number: `MY-010263`; Symbol: `ER_CONN_TCP_IP_NOT_LOGGED`; SQLSTATE: `HY000`

Message: Fails to print out IP-address.

`ER_CONN_TCP_IP_NOT_LOGGED` was added in 8.0.2.

- Error number: `MY-010264`; Symbol: `ER_CONN_TCP_RESOLVE_INFO`; SQLSTATE: `HY000`

Message: - '%s' resolves to '%s';

`ER_CONN_TCP_RESOLVE_INFO` was added in 8.0.2.

- Error number: `MY-010265`; Symbol: `ER_CONN_TCP_START_FAIL`; SQLSTATE: `HY000`

Message: Can't start server: listen() on TCP/IP port: %s

`ER_CONN_TCP_START_FAIL` was added in 8.0.2.

- Error number: `MY-010266`; Symbol: `ER_CONN_TCP_LISTEN_FAIL`; SQLSTATE: `HY000`

Message: listen() on TCP/IP failed with error %d

`ER_CONN_TCP_LISTEN_FAIL` was added in 8.0.2.

- Error number: `MY-010267`; Symbol: `ER_CONN_UNIX_PATH_TOO_LONG`; SQLSTATE: `HY000`

---

Message: The socket file path is too long (> %u): %s

[ER\\_CONN\\_UNIX\\_PATH\\_TOO\\_LONG](#) was added in 8.0.2.

- Error number: [MY-010268](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_FAIL](#); SQLSTATE: [HY000](#)

Message: Unable to setup unix socket lock file.

[ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_FAIL](#) was added in 8.0.2.

- Error number: [MY-010269](#); Symbol: [ER\\_CONN\\_UNIX\\_NO\\_FD](#); SQLSTATE: [HY000](#)

Message: Can't start server: UNIX Socket : %s

[ER\\_CONN\\_UNIX\\_NO\\_FD](#) was added in 8.0.2.

- Error number: [MY-010270](#); Symbol: [ER\\_CONN\\_UNIX\\_NO\\_BIND\\_NO\\_START](#); SQLSTATE: [HY000](#)

Message: Can't start server : Bind on unix socket: %s

[ER\\_CONN\\_UNIX\\_NO\\_BIND\\_NO\\_START](#) was added in 8.0.2.

- Error number: [MY-010271](#); Symbol: [ER\\_CONN\\_UNIX\\_LISTEN\\_FAILED](#); SQLSTATE: [HY000](#)

Message: listen() on Unix socket failed with error %d

[ER\\_CONN\\_UNIX\\_LISTEN\\_FAILED](#) was added in 8.0.2.

- Error number: [MY-010272](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_GIVING\\_UP](#); SQLSTATE: [HY000](#)

Message: Unable to create unix socket lock file %s after retries.

[ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_GIVING\\_UP](#) was added in 8.0.2.

- Error number: [MY-010273](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_CREATE](#); SQLSTATE: [HY000](#)

Message: Could not create unix socket lock file %s.

[ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_CREATE](#) was added in 8.0.2.

- Error number: [MY-010274](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_OPEN](#); SQLSTATE: [HY000](#)

Message: Could not open unix socket lock file %s.

[ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_OPEN](#) was added in 8.0.2.

- Error number: [MY-010275](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_READ](#); SQLSTATE: [HY000](#)

Message: Could not read unix socket lock file %s.

[ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_READ](#) was added in 8.0.2.

- Error number: [MY-010276](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: Unix socket lock file is empty %s.

[ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_EMPTY](#) was added in 8.0.2.

- Error number: [MY-010277](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_PIDLESS](#); SQLSTATE: [HY000](#)

---

Message: Invalid pid in unix socket lock file %s.

`ER_CONN_UNIX_LOCK_FILE_PIDLESS` was added in 8.0.2.

- Error number: `MY-010278`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_WRITE`; SQLSTATE: `HY000`

Message: Could not write unix socket lock file %s errno %d.

`ER_CONN_UNIX_LOCK_FILE_CANT_WRITE` was added in 8.0.2.

- Error number: `MY-010279`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_DELETE`; SQLSTATE: `HY000`

Message: Could not remove unix socket lock file %s errno %d.

`ER_CONN_UNIX_LOCK_FILE_CANT_DELETE` was added in 8.0.2.

- Error number: `MY-010280`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_SYNC`; SQLSTATE: `HY000`

Message: Could not sync unix socket lock file %s errno %d.

`ER_CONN_UNIX_LOCK_FILE_CANT_SYNC` was added in 8.0.2.

- Error number: `MY-010281`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE`; SQLSTATE: `HY000`

Message: Could not close unix socket lock file %s errno %d.

`ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE` was added in 8.0.2.

- Error number: `MY-010282`; Symbol: `ER_CONN_SOCKET_SELECT_FAILED`; SQLSTATE: `HY000`

Message: mysqld: Got error %d from select

`ER_CONN_SOCKET_SELECT_FAILED` was added in 8.0.2.

- Error number: `MY-010283`; Symbol: `ER_CONN_SOCKET_ACCEPT_FAILED`; SQLSTATE: `HY000`

Message: Error in accept: %s

`ER_CONN_SOCKET_ACCEPT_FAILED` was added in 8.0.2.

- Error number: `MY-010284`; Symbol: `ER_AUTH_RSA_CANT_FIND`; SQLSTATE: `HY000`

Message: RSA %s key file not found: %s. Some authentication plugins will not work.

`ER_AUTH_RSA_CANT_FIND` was added in 8.0.2.

- Error number: `MY-010285`; Symbol: `ER_AUTH_RSA_CANT_PARSE`; SQLSTATE: `HY000`

Message: Failure to parse RSA %s key (file exists): %s: %s

`ER_AUTH_RSA_CANT_PARSE` was added in 8.0.2.

- Error number: `MY-010286`; Symbol: `ER_AUTH_RSA_CANT_READ`; SQLSTATE: `HY000`

Message: Failure to read key file: %s

`ER_AUTH_RSA_CANT_READ` was added in 8.0.2.

- Error number: `MY-010287`; Symbol: `ER_AUTH_RSA_FILES_NOT_FOUND`; SQLSTATE: `HY000`

---

Message: RSA key files not found. Some authentication plugins will not work.

[ER\\_AUTH\\_RSA\\_FILES\\_NOT\\_FOUND](#) was added in 8.0.2.

- Error number: [MY-010288](#); Symbol: [ER\\_CONN\\_ATTR\\_TRUNCATED](#); SQLSTATE: [HY000](#)

Message: Connection attributes of length %lu were truncated (%d bytes lost) for connection %llu, user %s@%s (as %s), auth: %s

[ER\\_CONN\\_ATTR\\_TRUNCATED](#) was added in 8.0.2.

- Error number: [MY-010289](#); Symbol: [ER\\_X509\\_CIPHERS\\_MISMATCH](#); SQLSTATE: [HY000](#)

Message: X.509 ciphers mismatch: should be '%s' but is '%s'

[ER\\_X509\\_CIPHERS\\_MISMATCH](#) was added in 8.0.2.

- Error number: [MY-010290](#); Symbol: [ER\\_X509\\_ISSUER\\_MISMATCH](#); SQLSTATE: [HY000](#)

Message: X.509 issuer mismatch: should be '%s' but is '%s'

[ER\\_X509\\_ISSUER\\_MISMATCH](#) was added in 8.0.2.

- Error number: [MY-010291](#); Symbol: [ER\\_X509\\_SUBJECT\\_MISMATCH](#); SQLSTATE: [HY000](#)

Message: X.509 subject mismatch: should be '%s' but is '%s'

[ER\\_X509\\_SUBJECT\\_MISMATCH](#) was added in 8.0.2.

- Error number: [MY-010292](#); Symbol: [ER\\_AUTH\\_CANT\\_ACTIVATE\\_ROLE](#); SQLSTATE: [HY000](#)

Message: Failed to activate default role %s for %s

[ER\\_AUTH\\_CANT\\_ACTIVATE\\_ROLE](#) was added in 8.0.2.

- Error number: [MY-010293](#); Symbol: [ER\\_X509\\_NEEDS\\_RSA\\_PRIVKEY](#); SQLSTATE: [HY000](#)

Message: Could not generate RSA private key required for X.509 certificate.

[ER\\_X509\\_NEEDS\\_RSA\\_PRIVKEY](#) was added in 8.0.2.

- Error number: [MY-010294](#); Symbol: [ER\\_X509\\_CANT\\_WRITE\\_KEY](#); SQLSTATE: [HY000](#)

Message: Could not write key file: %s

[ER\\_X509\\_CANT\\_WRITE\\_KEY](#) was added in 8.0.2.

- Error number: [MY-010295](#); Symbol: [ER\\_X509\\_CANT\\_CHMOD\\_KEY](#); SQLSTATE: [HY000](#)

Message: Could not set file permission for %s

[ER\\_X509\\_CANT\\_CHMOD\\_KEY](#) was added in 8.0.2.

- Error number: [MY-010296](#); Symbol: [ER\\_X509\\_CANT\\_READ\\_CA\\_KEY](#); SQLSTATE: [HY000](#)

Message: Could not read CA key file: %s

[ER\\_X509\\_CANT\\_READ\\_CA\\_KEY](#) was added in 8.0.2.

- 
- Error number: `MY-010297`; Symbol: `ER_X509_CANT_READ_CA_CERT`; SQLSTATE: `HY000`  
Message: Could not read CA certificate file: %s  
`ER_X509_CANT_READ_CA_CERT` was added in 8.0.2.
  - Error number: `MY-010298`; Symbol: `ER_X509_CANT_CREATE_CERT`; SQLSTATE: `HY000`  
Message: Could not generate X.509 certificate.  
`ER_X509_CANT_CREATE_CERT` was added in 8.0.2.
  - Error number: `MY-010299`; Symbol: `ER_X509_CANT_WRITE_CERT`; SQLSTATE: `HY000`  
Message: Could not write certificate file: %s  
`ER_X509_CANT_WRITE_CERT` was added in 8.0.2.
  - Error number: `MY-010300`; Symbol: `ER_AUTH_CANT_CREATE_RSA_PAIR`; SQLSTATE: `HY000`  
Message: Could not generate RSA Private/Public key pair  
`ER_AUTH_CANT_CREATE_RSA_PAIR` was added in 8.0.2.
  - Error number: `MY-010301`; Symbol: `ER_AUTH_CANT_WRITE_PRIVKEY`; SQLSTATE: `HY000`  
Message: Could not write private key file: %s  
`ER_AUTH_CANT_WRITE_PRIVKEY` was added in 8.0.2.
  - Error number: `MY-010302`; Symbol: `ER_AUTH_CANT_WRITE_PUBKEY`; SQLSTATE: `HY000`  
Message: Could not write public key file: %s  
`ER_AUTH_CANT_WRITE_PUBKEY` was added in 8.0.2.
  - Error number: `MY-010303`; Symbol: `ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION`; SQLSTATE: `HY000`  
Message: Skipping generation of SSL certificates as options related to SSL are specified.  
`ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION` was added in 8.0.2.
  - Error number: `MY-010304`; Symbol: `ER_AUTH_USING_EXISTING_CERTS`; SQLSTATE: `HY000`  
Message: Skipping generation of SSL certificates as certificate files are present in data directory.  
`ER_AUTH_USING_EXISTING_CERTS` was added in 8.0.2.
  - Error number: `MY-010305`; Symbol: `ER_AUTH_CERTS_SAVED_TO_DATADIR`; SQLSTATE: `HY000`  
Message: Auto generated SSL certificates are placed in data directory.  
`ER_AUTH_CERTS_SAVED_TO_DATADIR` was added in 8.0.2.
  - Error number: `MY-010306`; Symbol: `ER_AUTH_CERT_GENERATION_DISABLED`; SQLSTATE: `HY000`  
Message: Skipping generation of SSL certificates as `--auto_generate_certs` is set to OFF.  
`ER_AUTH_CERT_GENERATION_DISABLED` was added in 8.0.2.



- 
- Error number: [MY-010307](#); Symbol: [ER\\_AUTH\\_RSA\\_CONF\\_PREVENTS\\_KEY\\_GENERATION](#); SQLSTATE: [HY000](#)  
  
Message: Skipping generation of RSA key pair through %s as options related to RSA keys are specified.  
  
[ER\\_AUTH\\_RSA\\_CONF\\_PREVENTS\\_KEY\\_GENERATION](#) was added in 8.0.2.
  - Error number: [MY-010308](#); Symbol: [ER\\_AUTH\\_KEY\\_GENERATION\\_SKIPPED\\_PAIR\\_PRESENT](#); SQLSTATE: [HY000](#)  
  
Message: Skipping generation of RSA key pair through %s as key files are present in data directory.  
  
[ER\\_AUTH\\_KEY\\_GENERATION\\_SKIPPED\\_PAIR\\_PRESENT](#) was added in 8.0.2.
  - Error number: [MY-010309](#); Symbol: [ER\\_AUTH\\_KEYS\\_SAVED\\_TO\\_DATADIR](#); SQLSTATE: [HY000](#)  
  
Message: Auto generated RSA key files through %s are placed in data directory.  
  
[ER\\_AUTH\\_KEYS\\_SAVED\\_TO\\_DATADIR](#) was added in 8.0.2.
  - Error number: [MY-010310](#); Symbol: [ER\\_AUTH\\_KEY\\_GENERATION\\_DISABLED](#); SQLSTATE: [HY000](#)  
  
Message: Skipping generation of RSA key pair as %s is set to OFF.  
  
[ER\\_AUTH\\_KEY\\_GENERATION\\_DISABLED](#) was added in 8.0.2.
  - Error number: [MY-010311](#); Symbol: [ER\\_AUTHCACHE\\_PROXIES\\_PRIV\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)  
  
Message: 'proxies\_priv' entry '%s@%s %s@%s' ignored in --skip-name-resolve mode.  
  
[ER\\_AUTHCACHE\\_PROXIES\\_PRIV\\_SKIPPED\\_NEEDS\\_RESOLVE](#) was added in 8.0.2.
  - Error number: [MY-010312](#); Symbol: [ER\\_AUTHCACHE\\_PLUGIN\\_MISSING](#); SQLSTATE: [HY000](#)  
  
Message: The plugin '%s' used to authenticate user '%s'@'%s' is not loaded. Nobody can currently login using this account.  
  
[ER\\_AUTHCACHE\\_PLUGIN\\_MISSING](#) was added in 8.0.2.
  - Error number: [MY-010313](#); Symbol: [ER\\_AUTHCACHE\\_PLUGIN\\_CONFIG](#); SQLSTATE: [HY000](#)  
  
Message: The plugin '%s' is used to authenticate user '%s'@'%s', %s configured. Nobody can currently login using this account.  
  
[ER\\_AUTHCACHE\\_PLUGIN\\_CONFIG](#) was added in 8.0.2.
  - Error number: [MY-010314](#); Symbol: [ER\\_AUTHCACHE\\_ROLE\\_TABLES\\_DODGY](#); SQLSTATE: [HY000](#)  
  
Message: Could not load mysql.role\_edges and mysql.default\_roles tables. ACL DDLs will not work unless mysql\_upgrade is executed.  
  
[ER\\_AUTHCACHE\\_ROLE\\_TABLES\\_DODGY](#) was added in 8.0.2, removed after 8.0.4.
-

- 
- Error number: [MY-010315](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)  
  
Message: 'user' entry '%s@%s' ignored in --skip-name-resolve mode.  
  
[ER\\_AUTHCACHE\\_USER\\_SKIPPED\\_NEEDS\\_RESOLVE](#) was added in 8.0.2.
  - Error number: [MY-010316](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_TABLE\\_DODGY](#); SQLSTATE: [HY000](#)  
  
Message: Fatal error: Could not read the column 'authentication\_string' from table 'mysql.user'. Please perform the MySQL upgrade procedure.  
  
[ER\\_AUTHCACHE\\_USER\\_TABLE\\_DODGY](#) was added in 8.0.2.
  - Error number: [MY-010317](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_IGNORED\\_DEPRECATED\\_PASSWORD](#); SQLSTATE: [HY000](#)  
  
Message: User entry '%s@%s' has a deprecated pre-4.1 password. The user will be ignored and no one can login with this user anymore.  
  
[ER\\_AUTHCACHE\\_USER\\_IGNORED\\_DEPRECATED\\_PASSWORD](#) was added in 8.0.2.
  - Error number: [MY-010318](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_IGNORED\\_NEEDS\\_PLUGIN](#); SQLSTATE: [HY000](#)  
  
Message: User entry '%s@%s' has an empty plugin value. The user will be ignored and no one can login with this user anymore.  
  
[ER\\_AUTHCACHE\\_USER\\_IGNORED\\_NEEDS\\_PLUGIN](#) was added in 8.0.2.
  - Error number: [MY-010319](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_IGNORED\\_INVALID\\_PASSWORD](#); SQLSTATE: [HY000](#)  
  
Message: Found invalid password for user: '%s@%s'; Ignoring user  
  
[ER\\_AUTHCACHE\\_USER\\_IGNORED\\_INVALID\\_PASSWORD](#) was added in 8.0.2.
  - Error number: [MY-010320](#); Symbol: [ER\\_AUTHCACHE\\_EXPIRED\\_PASSWORD\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)  
  
Message: 'user' entry '%s@%s' has the password ignore flag raised, but its authentication plugin doesn't support password expiration. The user id will be ignored.  
  
[ER\\_AUTHCACHE\\_EXPIRED\\_PASSWORD\\_UNSUPPORTED](#) was added in 8.0.2.
  - Error number: [MY-010321](#); Symbol: [ER\\_NO\\_SUPER\\_WITHOUT\\_USER\\_PLUGIN](#); SQLSTATE: [HY000](#)  
  
Message: Some of the user accounts with SUPER privileges were disabled because of empty mysql.user.plugin value. If you are upgrading from MySQL 5.6 to MySQL 5.7 it means that substitution for the empty plugin column was not possible. Probably because of pre 4.1 password hash. If your account is disabled you will need to perform the MySQL upgrade procedure. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.  
  
[ER\\_NO\\_SUPER\\_WITHOUT\\_USER\\_PLUGIN](#) was added in 8.0.2.

- 
- Error number: [MY-010322](#); Symbol: [ER\\_AUTHCACHE\\_DB\\_IGNORED\\_EMPTY\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Found an entry in the 'db' table with empty database name; Skipped  
[ER\\_AUTHCACHE\\_DB\\_IGNORED\\_EMPTY\\_NAME](#) was added in 8.0.2.
  - Error number: [MY-010323](#); Symbol: [ER\\_AUTHCACHE\\_DB\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)  
Message: 'db' entry '%s %s@%s' ignored in --skip-name-resolve mode.  
[ER\\_AUTHCACHE\\_DB\\_SKIPPED\\_NEEDS\\_RESOLVE](#) was added in 8.0.2.
  - Error number: [MY-010324](#); Symbol: [ER\\_AUTHCACHE\\_DB\\_ENTRY\\_LOWERCASED\\_REVOKE\\_WILL\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: 'db' entry '%s %s@%s' had database in mixed case that has been forced to lowercase because lower\_case\_table\_names is set. It will not be possible to remove this privilege using REVOKE.  
[ER\\_AUTHCACHE\\_DB\\_ENTRY\\_LOWERCASED\\_REVOKE\\_WILL\\_FAIL](#) was added in 8.0.2.
  - Error number: [MY-010325](#); Symbol: [ER\\_AUTHCACHE\\_TABLE\\_PROXIES\\_PRIV\\_MISSING](#); SQLSTATE: [HY000](#)  
Message: The system table mysql.proxies\_priv is missing. Please perform the MySQL upgrade procedure.  
[ER\\_AUTHCACHE\\_TABLE\\_PROXIES\\_PRIV\\_MISSING](#) was added in 8.0.2.
  - Error number: [MY-010326](#); Symbol: [ER\\_AUTHCACHE\\_CANT\\_OPEN\\_AND\\_LOCK\\_PRIVILEGE\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: Fatal error: Can't open and lock privilege tables: %s  
[ER\\_AUTHCACHE\\_CANT\\_OPEN\\_AND\\_LOCK\\_PRIVILEGE\\_TABLES](#) was added in 8.0.2.
  - Error number: [MY-010327](#); Symbol: [ER\\_AUTHCACHE\\_CANT\\_INIT\\_GRANT\\_SUBSYSTEM](#); SQLSTATE: [HY000](#)  
Message: Fatal: can't initialize grant subsystem - '%s'  
[ER\\_AUTHCACHE\\_CANT\\_INIT\\_GRANT\\_SUBSYSTEM](#) was added in 8.0.2.
  - Error number: [MY-010328](#); Symbol: [ER\\_AUTHCACHE\\_PROCS\\_PRIV\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)  
Message: 'procs\_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.  
[ER\\_AUTHCACHE\\_PROCS\\_PRIV\\_SKIPPED\\_NEEDS\\_RESOLVE](#) was added in 8.0.2.
  - Error number: [MY-010329](#); Symbol: [ER\\_AUTHCACHE\\_PROCS\\_PRIV\\_ENTRY\\_IGNORED\\_BAD\\_ROUTINE\\_TYPE](#); SQLSTATE: [HY000](#)  
Message: 'procs\_priv' entry '%s' ignored, bad routine type  
[ER\\_AUTHCACHE\\_PROCS\\_PRIV\\_ENTRY\\_IGNORED\\_BAD\\_ROUTINE\\_TYPE](#) was added in 8.0.2.
  - Error number: [MY-010330](#); Symbol: [ER\\_AUTHCACHE\\_TABLES\\_PRIV\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)

---

Message: 'tables\_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.

[ER\\_AUTHCACHE\\_TABLES\\_PRIV\\_SKIPPED\\_NEEDS\\_RESOLVE](#) was added in 8.0.2.

- Error number: [MY-010331](#); Symbol:

[ER\\_USER\\_NOT\\_IN\\_EXTRA\\_USERS\\_BINLOG\\_POSSIBLY\\_INCOMPLETE](#); SQLSTATE: [HY000](#)

Message: Failed to add %s in extra\_users. Binary log entry may miss some of the users.

[ER\\_USER\\_NOT\\_IN\\_EXTRA\\_USERS\\_BINLOG\\_POSSIBLY\\_INCOMPLETE](#) was added in 8.0.2.

- Error number: [MY-010332](#); Symbol: [ER\\_DD\\_SCHEMA\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. The data dictionary schema '%s' does not exist.

[ER\\_DD\\_SCHEMA\\_NOT\\_FOUND](#) was added in 8.0.2.

- Error number: [MY-010333](#); Symbol: [ER\\_DD\\_TABLE\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. The data dictionary table '%s' does not exist.

[ER\\_DD\\_TABLE\\_NOT\\_FOUND](#) was added in 8.0.2.

- Error number: [MY-010334](#); Symbol: [ER\\_DD\\_SE\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize DD Storage Engine

[ER\\_DD\\_SE\\_INIT\\_FAILED](#) was added in 8.0.2.

- Error number: [MY-010335](#); Symbol: [ER\\_DD\\_ABORTING\\_PARTIAL\\_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.

[ER\\_DD\\_ABORTING\\_PARTIAL\\_UPGRADE](#) was added in 8.0.2.

- Error number: [MY-010336](#); Symbol: [ER\\_DD\\_FRM\\_EXISTS\\_FOR\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Found .frm file with same name as one of the Dictionary Tables.

[ER\\_DD\\_FRM\\_EXISTS\\_FOR\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010337](#); Symbol: [ER\\_DD\\_CREATED\\_FOR\\_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Created Data Dictionary for upgrade

[ER\\_DD\\_CREATED\\_FOR\\_UPGRADE](#) was added in 8.0.2.

- Error number: [MY-010338](#); Symbol: [ER\\_ERRMSG\\_CANT\\_FIND\\_FILE](#); SQLSTATE: [HY000](#)

Message: Can't find error-message file '%s'. Check error-message file location and 'lc-messages-dir' configuration directive.

[ER\\_ERRMSG\\_CANT\\_FIND\\_FILE](#) was added in 8.0.2.

- Error number: [MY-010339](#); Symbol: [ER\\_ERRMSG\\_LOADING\\_55\\_STYLE](#); SQLSTATE: [HY000](#)

Message: Using pre 5.5 semantics to load error messages from %s. If this is not intended, refer to the documentation for valid usage of --lc-messages-dir and --language parameters.

---

`ER_ERRMSG_LOADING_55_STYLE` was added in 8.0.2.

- Error number: `MY-010340`; Symbol: `ER_ERRMSG_MISSING_IN_FILE`; SQLSTATE: `HY000`

Message: Error message file '%s' had only %d error messages, but it should contain at least %d error messages. Check that the above file is the right version for this program!

`ER_ERRMSG_MISSING_IN_FILE` was added in 8.0.2.

- Error number: `MY-010341`; Symbol: `ER_ERRMSG_OOM`; SQLSTATE: `HY000`

Message: Not enough memory for messagefile '%s'

`ER_ERRMSG_OOM` was added in 8.0.2.

- Error number: `MY-010342`; Symbol: `ER_ERRMSG_CANT_READ`; SQLSTATE: `HY000`

Message: Can't read from messagefile '%s'

`ER_ERRMSG_CANT_READ` was added in 8.0.2.

- Error number: `MY-010343`; Symbol: `ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD`; SQLSTATE: `HY000`

Message: Found incompatible DECIMAL field '%s' in %s; Please do "ALTER TABLE `%s` FORCE" to fix it!

`ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD` was added in 8.0.2.

- Error number: `MY-010344`; Symbol: `ER_TABLE_INCOMPATIBLE_YEAR_FIELD`; SQLSTATE: `HY000`

Message: Found incompatible YEAR(x) field '%s' in %s; Please do "ALTER TABLE `%s` FORCE" to fix it!

`ER_TABLE_INCOMPATIBLE_YEAR_FIELD` was added in 8.0.2.

- Error number: `MY-010345`; Symbol: `ER_INVALID_CHARSET_AND_DEFAULT_IS_MB`; SQLSTATE: `HY000`

Message: '%s' had no or invalid character set, and default character set is multi-byte, so character column sizes may have changed

`ER_INVALID_CHARSET_AND_DEFAULT_IS_MB` was added in 8.0.2.

- Error number: `MY-010346`; Symbol: `ER_TABLE_WRONG_KEY_DEFINITION`; SQLSTATE: `HY000`

Message: Found wrong key definition in %s; Please do "ALTER TABLE `%s` FORCE " to fix it!

`ER_TABLE_WRONG_KEY_DEFINITION` was added in 8.0.2.

- Error number: `MY-010347`; Symbol: `ER_CANT_OPEN_FRM_FILE`; SQLSTATE: `HY000`

Message: Unable to open file %s

`ER_CANT_OPEN_FRM_FILE` was added in 8.0.2.

- Error number: `MY-010348`; Symbol: `ER_CANT_READ_FRM_FILE`; SQLSTATE: `HY000`

Message: Error in reading file %s

---

`ER_CANT_READ_FRM_FILE` was added in 8.0.2.

- Error number: `MY-010349`; Symbol: `ER_TABLE_CREATED_WITH_DIFFERENT_VERSION`; SQLSTATE: `HY000`

Message: Table '%s' was created with a different version of MySQL and cannot be read

`ER_TABLE_CREATED_WITH_DIFFERENT_VERSION` was added in 8.0.2.

- Error number: `MY-010350`; Symbol: `ER_VIEW_UNPARSABLE`; SQLSTATE: `HY000`

Message: Unable to read view %s

`ER_VIEW_UNPARSABLE` was added in 8.0.2.

- Error number: `MY-010351`; Symbol: `ER_FILE_TYPE_UNKNOWN`; SQLSTATE: `HY000`

Message: File %s has unknown type in its header.

`ER_FILE_TYPE_UNKNOWN` was added in 8.0.2.

- Error number: `MY-010352`; Symbol: `ER_INVALID_INFO_IN_FRM`; SQLSTATE: `HY000`

Message: Incorrect information in file %s

`ER_INVALID_INFO_IN_FRM` was added in 8.0.2.

- Error number: `MY-010353`; Symbol: `ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES`; SQLSTATE: `HY000`

Message: Can't open and lock privilege tables: %s

`ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES` was added in 8.0.2.

- Error number: `MY-010354`; Symbol: `ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENTS`; SQLSTATE: `HY000`

Message: Plugin '%s' cannot subscribe to `MYSQL_AUDIT_AUTHORIZATION` events. Currently not supported.

`ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENTS` was added in 8.0.2.

- Error number: `MY-010355`; Symbol: `ER_AUDIT_PLUGIN_HAS_INVALID_DATA`; SQLSTATE: `HY000`

Message: Plugin '%s' has invalid data.

`ER_AUDIT_PLUGIN_HAS_INVALID_DATA` was added in 8.0.2.

- Error number: `MY-010356`; Symbol: `ER_TZ_OOM_INITIALIZING_TIME_ZONES`; SQLSTATE: `HY000`

Message: Fatal error: OOM while initializing time zones

`ER_TZ_OOM_INITIALIZING_TIME_ZONES` was added in 8.0.2.

- Error number: `MY-010357`; Symbol: `ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE`; SQLSTATE: `HY000`

Message: Can't open and lock time zone table: %s trying to live without them

---

`ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE` was added in 8.0.2.

- Error number: `MY-010358`; Symbol: `ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`

Message: Fatal error: Out of memory while loading `mysql.time_zone_leap_second` table

`ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE` was added in 8.0.2.

- Error number: `MY-010359`; Symbol: `ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`

Message: Fatal error: While loading `mysql.time_zone_leap_second` table: too much leaps

`ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE` was added in 8.0.2.

- Error number: `MY-010360`; Symbol: `ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`

Message: Fatal error: Error while loading `mysql.time_zone_leap_second` table

`ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE` was added in 8.0.2.

- Error number: `MY-010361`; Symbol: `ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE`; SQLSTATE: `HY000`

Message: Fatal error: Illegal or unknown default time zone '%s'

`ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE` was added in 8.0.2.

- Error number: `MY-010362`; Symbol: `ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE`; SQLSTATE: `HY000`

Message: Can't find description of time zone '%.\*s'

`ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE` was added in 8.0.2.

- Error number: `MY-010363`; Symbol: `ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID`; SQLSTATE: `HY000`

Message: Can't find description of time zone '%u'

`ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID` was added in 8.0.2.

- Error number: `MY-010364`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE`; SQLSTATE: `HY000`

Message: Error while loading time zone description from `mysql.time_zone_transition_type` table: too big transition type id

`ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE` was added in 8.0.2.

- Error number: `MY-010365`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEED_SPACE`; SQLSTATE: `HY000`

Message: Error while loading time zone description from `mysql.time_zone_transition_type` table: not enough room for abbreviations

---

`ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEED_SPACE` was added in 8.0.2.

- Error number: `MY-010366`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR`; SQLSTATE: `HY000`

Message: Error while loading time zone description from `mysql.time_zone_transition_type` table

`ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR` was added in 8.0.2.

- Error number: `MY-010367`; Symbol: `ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS`; SQLSTATE: `HY000`

Message: Error while loading time zone description from `mysql.time_zone_transition` table: too much transitions

`ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS` was added in 8.0.2.

- Error number: `MY-010368`; Symbol: `ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE`; SQLSTATE: `HY000`

Message: Error while loading time zone description from `mysql.time_zone_transition` table: bad transition type id

`ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE` was added in 8.0.2.

- Error number: `MY-010369`; Symbol: `ER_TZ_TRANSITION_TABLE_LOAD_ERROR`; SQLSTATE: `HY000`

Message: Error while loading time zone description from `mysql.time_zone_transition` table

`ER_TZ_TRANSITION_TABLE_LOAD_ERROR` was added in 8.0.2.

- Error number: `MY-010370`; Symbol: `ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE`; SQLSTATE: `HY000`

Message: loading time zone without transition types

`ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE` was added in 8.0.2.

- Error number: `MY-010371`; Symbol: `ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION`; SQLSTATE: `HY000`

Message: Out of memory while loading time zone description

`ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION` was added in 8.0.2.

- Error number: `MY-010372`; Symbol: `ER_TZ_CANT_BUILD_MKTIME_MAP`; SQLSTATE: `HY000`

Message: Unable to build mktime map for time zone

`ER_TZ_CANT_BUILD_MKTIME_MAP` was added in 8.0.2.

- Error number: `MY-010373`; Symbol: `ER_TZ_OOM_WHILE_LOADING_TIME_ZONE`; SQLSTATE: `HY000`

Message: Out of memory while loading time zone

`ER_TZ_OOM_WHILE_LOADING_TIME_ZONE` was added in 8.0.2.

- Error number: `MY-010374`; Symbol: `ER_TZ_OOM_WHILE_SETTING_TIME_ZONE`; SQLSTATE: `HY000`



---

Message: Fatal error: Out of memory while setting new time zone

[ER\\_TZ\\_OOM\\_WHILE\\_SETTING\\_TIME\\_ZONE](#) was added in 8.0.2.

- Error number: [MY-010375](#); Symbol: [ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_UNTIL\\_CONDITION\\_BAD](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread is stopped because UNTIL condition is bad(%s:%llu).

[ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_UNTIL\\_CONDITION\\_BAD](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010375](#); Symbol: [ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_UNTIL\\_CONDITION\\_BAD](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread is stopped because UNTIL condition is bad(%s:%llu).

[ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_UNTIL\\_CONDITION\\_BAD](#) was added in 8.0.33.

- Error number: [MY-010376](#); Symbol: [ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_UNTIL\\_POSITION\\_REACHED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread stopped because it reached its UNTIL position %llu

[ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_UNTIL\\_POSITION\\_REACHED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010376](#); Symbol: [ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_UNTIL\\_POSITION\\_REACHED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because it reached its UNTIL position %llu

[ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_UNTIL\\_POSITION\\_REACHED](#) was added in 8.0.33.

- Error number: [MY-010377](#); Symbol: [ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_ALREADY\\_APPLIED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread stopped because UNTIL SQL\_BEFORE\_GTIDS %s is already applied

[ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_ALREADY\\_APPLIED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010377](#); Symbol: [ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_ALREADY\\_APPLIED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because UNTIL SQL\_BEFORE\_GTIDS %s is already applied

[ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_ALREADY\\_APPLIED](#) was added in 8.0.33.

- Error number: [MY-010378](#); Symbol: [ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_REACHED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread stopped because it reached UNTIL SQL\_BEFORE\_GTIDS %s

[ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_REACHED](#) was added in 8.0.2, removed after 8.0.32.

- 
- Error number: `MY-010378`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED`; SQLSTATE: `HY000`  
  
Message: Replica SQL thread stopped because it reached UNTIL SQL\_BEFORE\_GTIDS %s  
  
`ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED` was added in 8.0.33.
  - Error number: `MY-010379`; Symbol: `ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED`; SQLSTATE: `HY000`  
  
Message: Slave SQL thread stopped because it reached UNTIL SQL\_AFTER\_GTIDS %s  
  
`ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010379`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED`; SQLSTATE: `HY000`  
  
Message: Replica SQL thread stopped because it reached UNTIL SQL\_AFTER\_GTIDS %s  
  
`ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED` was added in 8.0.33.
  - Error number: `MY-010380`; Symbol: `ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED`; SQLSTATE: `HY000`  
  
Message: Slave SQL thread stopped according to UNTIL SQL\_AFTER\_MTS\_GAPS as it has processed all gap transactions left from the previous slave session.  
  
`ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010380`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED`; SQLSTATE: `HY000`  
  
Message: Replica SQL thread stopped according to UNTIL SQL\_AFTER\_MTS\_GAPS as it has processed all gap transactions left from the previous replica session.  
  
`ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED` was added in 8.0.33.
  - Error number: `MY-010381`; Symbol: `ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED`; SQLSTATE: `HY000`  
  
Message: Group Replication plugin is not installed.  
  
`ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED` was added in 8.0.2.
  - Error number: `MY-010382`; Symbol: `ER_GTID_ALREADY_ADDED_BY_USER`; SQLSTATE: `HY000`  
  
Message: The transaction owned GTID is already in the %s table, which is caused by an explicit modifying from user client.  
  
`ER_GTID_ALREADY_ADDED_BY_USER` was added in 8.0.2.
  - Error number: `MY-010383`; Symbol: `ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`  
  
Message: Failed to delete the row: '%s' from the gtid\_executed table.  
  
`ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE` was added in 8.0.2.

- 
- Error number: [MY-010384](#); Symbol: [ER\\_FAILED\\_TO\\_COMPRESS\\_GTID\\_EXECUTED\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to compress the gtid\_executed table.

[ER\\_FAILED\\_TO\\_COMPRESS\\_GTID\\_EXECUTED\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010385](#); Symbol: [ER\\_FAILED\\_TO\\_COMPRESS\\_GTID\\_EXECUTED\\_TABLE\\_OOM](#); SQLSTATE: [HY000](#)

Message: Failed to compress the gtid\_executed table, because it is failed to allocate the THD.

[ER\\_FAILED\\_TO\\_COMPRESS\\_GTID\\_EXECUTED\\_TABLE\\_OOM](#) was added in 8.0.2.

- Error number: [MY-010386](#); Symbol: [ER\\_FAILED\\_TO\\_INIT\\_THREAD\\_ATTR\\_FOR\\_GTID\\_TABLE\\_COMPRESSION](#); SQLSTATE: [HY000](#)

Message: Failed to initialize thread attribute when creating compression thread.

[ER\\_FAILED\\_TO\\_INIT\\_THREAD\\_ATTR\\_FOR\\_GTID\\_TABLE\\_COMPRESSION](#) was added in 8.0.2.

- Error number: [MY-010387](#); Symbol: [ER\\_FAILED\\_TO\\_CREATE\\_GTID\\_TABLE\\_COMPRESSION\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Can not create thread to compress gtid\_executed table (errno= %d)

[ER\\_FAILED\\_TO\\_CREATE\\_GTID\\_TABLE\\_COMPRESSION\\_THREAD](#) was added in 8.0.2.

- Error number: [MY-010388](#); Symbol: [ER\\_FAILED\\_TO\\_JOIN\\_GTID\\_TABLE\\_COMPRESSION\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Could not join gtid\_executed table compression thread. error:%d

[ER\\_FAILED\\_TO\\_JOIN\\_GTID\\_TABLE\\_COMPRESSION\\_THREAD](#) was added in 8.0.2.

- Error number: [MY-010389](#); Symbol: [ER\\_NPIPE\\_FAILED\\_TO\\_INIT\\_SECURITY\\_DESCRIPTOR](#); SQLSTATE: [HY000](#)

Message: Can't start server : Initialize security descriptor: %s

[ER\\_NPIPE\\_FAILED\\_TO\\_INIT\\_SECURITY\\_DESCRIPTOR](#) was added in 8.0.2.

- Error number: [MY-010390](#); Symbol: [ER\\_NPIPE\\_FAILED\\_TO\\_SET\\_SECURITY\\_DESCRIPTOR](#); SQLSTATE: [HY000](#)

Message: Can't start server : Set security descriptor: %s

[ER\\_NPIPE\\_FAILED\\_TO\\_SET\\_SECURITY\\_DESCRIPTOR](#) was added in 8.0.2.

- Error number: [MY-010391](#); Symbol: [ER\\_NPIPE\\_PIPE\\_ALREADY\\_IN\\_USE](#); SQLSTATE: [HY000](#)

Message: Can't start server : Named Pipe "%s" already in use.

[ER\\_NPIPE\\_PIPE\\_ALREADY\\_IN\\_USE](#) was added in 8.0.2.

- 
- Error number: [MY-010392](#); Symbol: [ER\\_NDB\\_SLAVE\\_SAW\\_EPOCH\\_LOWER\\_THAN\\_PREVIOUS\\_ON\\_START](#); SQLSTATE: [HY000](#)  
  
Message: NDB Slave : At SQL thread start applying epoch %llu/%llu (%llu) from Master ServerId %u which is lower than previously applied epoch %llu/%llu (%llu). Group Master Log : %s Group Master Log Pos : %llu. Check slave positioning.  
  
[ER\\_NDB\\_SLAVE\\_SAW\\_EPOCH\\_LOWER\\_THAN\\_PREVIOUS\\_ON\\_START](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010393](#); Symbol: [ER\\_NDB\\_SLAVE\\_SAW\\_EPOCH\\_LOWER\\_THAN\\_PREVIOUS](#); SQLSTATE: [HY000](#)  
  
Message: NDB Slave : SQL thread stopped as applying epoch %llu/%llu (%llu) from Master ServerId %u which is lower than previously applied epoch %llu/%llu (%llu). Group Master Log : %s Group Master Log Pos : %llu  
  
[ER\\_NDB\\_SLAVE\\_SAW\\_EPOCH\\_LOWER\\_THAN\\_PREVIOUS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010394](#); Symbol: [ER\\_NDB\\_SLAVE\\_SAW\\_ALREADY\\_COMMITTED\\_EPOCH](#); SQLSTATE: [HY000](#)  
  
Message: NDB Slave : SQL thread stopped as attempted to reapply already committed epoch %llu/%llu (%llu) from server id %u. Group Master Log : %s Group Master Log Pos : %llu.  
  
[ER\\_NDB\\_SLAVE\\_SAW\\_ALREADY\\_COMMITTED\\_EPOCH](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010395](#); Symbol: [ER\\_NDB\\_SLAVE\\_PREVIOUS\\_EPOCH\\_NOT\\_COMMITTED](#); SQLSTATE: [HY000](#)  
  
Message: NDB Slave : SQL thread stopped as attempting to apply new epoch %llu/%llu (%llu) while lower received epoch %llu/%llu (%llu) has not been committed. Master server id : %u. Group Master Log : %s Group Master Log Pos : %llu.  
  
[ER\\_NDB\\_SLAVE\\_PREVIOUS\\_EPOCH\\_NOT\\_COMMITTED](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010396](#); Symbol: [ER\\_NDB\\_SLAVE\\_MISSING\\_DATA\\_FOR\\_TIMESTAMP\\_COLUMN](#); SQLSTATE: [HY000](#)  
  
Message: NDB Slave: missing data for %s timestamp column %u.  
  
[ER\\_NDB\\_SLAVE\\_MISSING\\_DATA\\_FOR\\_TIMESTAMP\\_COLUMN](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010397](#); Symbol: [ER\\_NDB\\_SLAVE\\_LOGGING\\_EXCEPTIONS\\_TO](#); SQLSTATE: [HY000](#)  
  
Message: NDB Slave: Table %s.%s logging exceptions to %s.%s  
  
[ER\\_NDB\\_SLAVE\\_LOGGING\\_EXCEPTIONS\\_TO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010398](#); Symbol: [ER\\_NDB\\_SLAVE\\_LOW\\_EPOCH\\_RESOLUTION](#); SQLSTATE: [HY000](#)  
  
Message: NDB Slave: Table %s.%s : %s, low epoch resolution  
  
[ER\\_NDB\\_SLAVE\\_LOW\\_EPOCH\\_RESOLUTION](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: [MY-010399](#); Symbol: [ER\\_NDB\\_INFO\\_FOUND\\_UNEXPECTED\\_FIELD\\_TYPE](#); SQLSTATE: [HY000](#)  
  
Message: Found unexpected field type %u  
  
[ER\\_NDB\\_INFO\\_FOUND\\_UNEXPECTED\\_FIELD\\_TYPE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010400](#); Symbol: [ER\\_NDB\\_INFO\\_FAILED\\_TO\\_CREATE\\_NDBINFO](#); SQLSTATE: [HY000](#)  
  
Message: Failed to create NdbInfo  
  
[ER\\_NDB\\_INFO\\_FAILED\\_TO\\_CREATE\\_NDBINFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010401](#); Symbol: [ER\\_NDB\\_INFO\\_FAILED\\_TO\\_INIT\\_NDBINFO](#); SQLSTATE: [HY000](#)  
  
Message: Failed to init NdbInfo  
  
[ER\\_NDB\\_INFO\\_FAILED\\_TO\\_INIT\\_NDBINFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010402](#); Symbol: [ER\\_NDB\\_CLUSTER\\_WRONG\\_NUMBER\\_OF\\_FUNCTION\\_ARGUMENTS](#); SQLSTATE: [HY000](#)  
  
Message: ndb\_serialize\_cond: Unexpected mismatch of found and expected number of function arguments %u  
  
[ER\\_NDB\\_CLUSTER\\_WRONG\\_NUMBER\\_OF\\_FUNCTION\\_ARGUMENTS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010403](#); Symbol: [ER\\_NDB\\_CLUSTER\\_SCHEMA\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: %s - %s.%s  
  
[ER\\_NDB\\_CLUSTER\\_SCHEMA\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010404](#); Symbol: [ER\\_NDB\\_CLUSTER\\_GENERIC\\_MESSAGE](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_NDB\\_CLUSTER\\_GENERIC\\_MESSAGE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010405](#); Symbol: [ER\\_RPL\\_CANT\\_OPEN\\_INFO\\_TABLE](#); SQLSTATE: [HY000](#)  
  
Message: Info table is not ready to be used. Table '%s.%s' cannot be opened.  
  
[ER\\_RPL\\_CANT\\_OPEN\\_INFO\\_TABLE](#) was added in 8.0.2.
  - Error number: [MY-010406](#); Symbol: [ER\\_RPL\\_CANT\\_SCAN\\_INFO\\_TABLE](#); SQLSTATE: [HY000](#)  
  
Message: Info table is not ready to be used. Table '%s.%s' cannot be scanned.  
  
[ER\\_RPL\\_CANT\\_SCAN\\_INFO\\_TABLE](#) was added in 8.0.2.
  - Error number: [MY-010407](#); Symbol: [ER\\_RPL\\_CORRUPTED\\_INFO\\_TABLE](#); SQLSTATE: [HY000](#)  
  
Message: Corrupted table %s.%s. Check out table definition.

- 
- Error number: `MY-010408`; Symbol: `ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE`; SQLSTATE: `HY000`  
  
Message: Info table has a problem with its key field(s). Table '%s.%s' expected field #%u to be '%s' but found '%s' instead.  
  
`ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE` was added in 8.0.2.
  - Error number: `MY-010409`; Symbol: `ER_RPL_WORKER_ID_IS`; SQLSTATE: `HY000`  
  
Message: Choosing worker id %lu, the following is going to be %lu  
  
`ER_RPL_WORKER_ID_IS` was added in 8.0.2.
  - Error number: `MY-010410`; Symbol: `ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX`; SQLSTATE: `HY000`  
  
Message: Transaction is tagged with inconsistent logical timestamps: sequence\_number (%lld) <= last\_committed (%lld)  
  
`ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX` was added in 8.0.2.
  - Error number: `MY-010411`; Symbol: `ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX`; SQLSTATE: `HY000`  
  
Message: Transaction's sequence number is inconsistent with that of a preceding one: sequence\_number (%lld) <= previous sequence\_number (%lld)  
  
`ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX` was added in 8.0.2.
  - Error number: `MY-010412`; Symbol: `ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPOSITORIES`; SQLSTATE: `HY000`  
  
Message: For the creation of replication channels the connection metadata and applier metadata repositories must be set to TABLE  
  
`ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPOSITORIES` was added in 8.0.2.
  - Error number: `MY-010413`; Symbol: `ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID`; SQLSTATE: `HY000`  
  
Message: For the creation of replication channels the server id must be different from 0  
  
`ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID` was added in 8.0.2.
  - Error number: `MY-010414`; Symbol: `ER_RPL_REPO_SHOULD_BE_TABLE`; SQLSTATE: `HY000`  
  
Message: Replica: Wrong repository. Repository should be TABLE  
  
`ER_RPL_REPO_SHOULD_BE_TABLE` was added in 8.0.2.
  - Error number: `MY-010415`; Symbol: `ER_RPL_ERROR_CREATING_MASTER_INFO`; SQLSTATE: `HY000`  
  
Message: Error creating master info: %s.  
  
`ER_RPL_ERROR_CREATING_MASTER_INFO` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010415`; Symbol: `ER_RPL_ERROR_CREATING_CONNECTION_METADATA`; SQLSTATE: `HY000`

---

Message: Error creating connection metadata: %s.

[ER\\_RPL\\_ERROR\\_CREATING\\_CONNECTION\\_METADATA](#) was added in 8.0.33.

- Error number: [MY-010416](#); Symbol: [ER\\_RPL\\_ERROR\\_CHANGING\\_MASTER\\_INFO\\_REPO\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Error changing the type of master info's repository: %s.

[ER\\_RPL\\_ERROR\\_CHANGING\\_MASTER\\_INFO\\_REPO\\_TYPE](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010416](#); Symbol: [ER\\_RPL\\_ERROR\\_CHANGING\\_CONNECTION\\_METADATA\\_REPO\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Error changing the type of connection metadata's repository: %s.

[ER\\_RPL\\_ERROR\\_CHANGING\\_CONNECTION\\_METADATA\\_REPO\\_TYPE](#) was added in 8.0.33.

- Error number: [MY-010417](#); Symbol: [ER\\_RPL\\_CHANGING\\_RELAY\\_LOG\\_INFO\\_REPO\\_TYPE\\_FAILED\\_DUE\\_TO\\_GAPS](#); SQLSTATE: [HY000](#)

Message: It is not possible to change the type of the relay log repository because there are workers repositories with possible execution gaps. The value of --relay\_log\_info\_repository is altered to one of the found Worker repositories. The gaps have to be sorted out before resuming with the type change.

[ER\\_RPL\\_CHANGING\\_RELAY\\_LOG\\_INFO\\_REPO\\_TYPE\\_FAILED\\_DUE\\_TO\\_GAPS](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010417](#); Symbol: [ER\\_RPL\\_CHANGING\\_APPLIER\\_METADATA\\_REPO\\_TYPE\\_FAILED\\_DUE\\_TO\\_GAPS](#); SQLSTATE: [HY000](#)

Message: It is not possible to change the type of the relay log repository because there are workers repositories with possible execution gaps. The value of --relay\_log\_info\_repository is altered to one of the found Worker repositories. The gaps have to be sorted out before resuming with the type change.

[ER\\_RPL\\_CHANGING\\_APPLIER\\_METADATA\\_REPO\\_TYPE\\_FAILED\\_DUE\\_TO\\_GAPS](#) was added in 8.0.33.

- Error number: [MY-010418](#); Symbol: [ER\\_RPL\\_ERROR\\_CREATING\\_RELAY\\_LOG\\_INFO](#); SQLSTATE: [HY000](#)

Message: Error creating relay log info: %s.

[ER\\_RPL\\_ERROR\\_CREATING\\_RELAY\\_LOG\\_INFO](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010418](#); Symbol: [ER\\_RPL\\_ERROR\\_CREATING\\_APPLIER\\_METADATA](#); SQLSTATE: [HY000](#)

Message: Error creating applier metadata: %s.

[ER\\_RPL\\_ERROR\\_CREATING\\_APPLIER\\_METADATA](#) was added in 8.0.33.

- Error number: [MY-010419](#); Symbol: [ER\\_RPL\\_ERROR\\_CHANGING\\_RELAY\\_LOG\\_INFO\\_REPO\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Error changing the type of relay log info's repository: %s.

[ER\\_RPL\\_ERROR\\_CHANGING\\_RELAY\\_LOG\\_INFO\\_REPO\\_TYPE](#) was added in 8.0.2, removed after 8.0.32.

- 
- Error number: [MY-010419](#); Symbol: [ER\\_RPL\\_ERROR\\_CHANGING\\_APPLIER\\_METADATA\\_REPO\\_TYPE](#); SQLSTATE: [HY000](#)  
Message: Error changing the type of applier metadata's repository: %s.  
[ER\\_RPL\\_ERROR\\_CHANGING\\_APPLIER\\_METADATA\\_REPO\\_TYPE](#) was added in 8.0.33.
  - Error number: [MY-010420](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_DELETE\\_FROM\\_SLAVE\\_WORKERS\\_INFO\\_REPOSITORY](#); SQLSTATE: [HY000](#)  
Message: Could not delete from Slave Workers info repository.  
[ER\\_RPL\\_FAILED\\_TO\\_DELETE\\_FROM\\_SLAVE\\_WORKERS\\_INFO\\_REPOSITORY](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010420](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_DELETE\\_FROM\\_REPLICA\\_WORKERS\\_INFO\\_REPOSITORY](#); SQLSTATE: [HY000](#)  
Message: Could not delete from Replica Workers info repository.  
[ER\\_RPL\\_FAILED\\_TO\\_DELETE\\_FROM\\_REPLICA\\_WORKERS\\_INFO\\_REPOSITORY](#) was added in 8.0.33.
  - Error number: [MY-010421](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_RESET\\_STATE\\_IN\\_SLAVE\\_INFO\\_REPOSITORY](#); SQLSTATE: [HY000](#)  
Message: Could not store the reset Slave Worker state into the slave info repository.  
[ER\\_RPL\\_FAILED\\_TO\\_RESET\\_STATE\\_IN\\_SLAVE\\_INFO\\_REPOSITORY](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010421](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_RESET\\_STATE\\_IN\\_REPLICA\\_INFO\\_REPOSITORY](#); SQLSTATE: [HY000](#)  
Message: Could not store the reset Replica Worker state into the replica info repository.  
[ER\\_RPL\\_FAILED\\_TO\\_RESET\\_STATE\\_IN\\_REPLICA\\_INFO\\_REPOSITORY](#) was added in 8.0.33.
  - Error number: [MY-010422](#); Symbol: [ER\\_RPL\\_ERROR\\_CHECKING\\_REPOSITORY](#); SQLSTATE: [HY000](#)  
Message: Error in checking %s repository info type of %s.  
[ER\\_RPL\\_ERROR\\_CHECKING\\_REPOSITORY](#) was added in 8.0.2.
  - Error number: [MY-010423](#); Symbol: [ER\\_RPL\\_SLAVE\\_GENERIC\\_MESSAGE](#); SQLSTATE: [HY000](#)  
Message: Slave: %s  
[ER\\_RPL\\_SLAVE\\_GENERIC\\_MESSAGE](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010423](#); Symbol: [ER\\_RPL\\_REPLICA\\_GENERIC\\_MESSAGE](#); SQLSTATE: [HY000](#)  
Message: Replica: %s  
[ER\\_RPL\\_REPLICA\\_GENERIC\\_MESSAGE](#) was added in 8.0.33.
  - Error number: [MY-010424](#); Symbol: [ER\\_RPL\\_SLAVE\\_COULD\\_NOT\\_CREATE\\_CHANNEL\\_LIST](#); SQLSTATE: [HY000](#)  
Message: Slave: Could not create channel list



---

`ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010424`; Symbol: `ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST`; SQLSTATE: `HY000`

Message: Replica: Could not create channel list

`ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST` was added in 8.0.33.

- Error number: `MY-010425`; Symbol: `ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORIES`; SQLSTATE: `HY000`

Message: Replica: This replica was a multisourced replica previously which is supported only by both TABLE based connection metadata and applier metadata repositories. Found one or both of the info repos to be type FILE. Set both repos to type TABLE.

`ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORIES` was added in 8.0.2.

- Error number: `MY-010426`; Symbol: `ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE`; SQLSTATE: `HY000`

Message: Slave: Failed to initialize the master info structure for channel '%s'; its record may still be present in 'mysql.slave\_master\_info' table, consider deleting it.

`ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010426`; Symbol: `ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA_STRUCTURE`; SQLSTATE: `HY000`

Message: Replica: Failed to initialize the connection metadata structure for channel '%s'; its record may still be present in the applier metadata repository, consider deleting it.

`ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA_STRUCTURE` was added in 8.0.33.

- Error number: `MY-010427`; Symbol: `ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE`; SQLSTATE: `HY000`

Message: Failed to initialize the master info structure%

`ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010427`; Symbol: `ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_STRUCTURE`; SQLSTATE: `HY000`

Message: Failed to initialize the connection metadata structure%

`ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_STRUCTURE` was added in 8.0.33.

- Error number: `MY-010428`; Symbol: `ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER_INFO`; SQLSTATE: `HY000`

Message: Slave: Failed to create a channel from master info table repository.

`ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER_INFO` was added in 8.0.2, removed after 8.0.32.

- 
- Error number: [MY-010428](#); Symbol: [ER\\_RPL\\_REPLICA\\_FAILED\\_TO\\_CREATE\\_CHANNEL\\_FROM\\_CONNECTION\\_METADATA](#); SQLSTATE: [HY000](#)  
  
Message: Replica: Failed to create a channel from connection metadata repository.  
  
[ER\\_RPL\\_REPLICA\\_FAILED\\_TO\\_CREATE\\_CHANNEL\\_FROM\\_CONNECTION\\_METADATA](#) was added in 8.0.33.
  - Error number: [MY-010429](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_CREATE\\_NEW\\_INFO\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: Failed to create a new info file (file '%s', errno %d)  
  
[ER\\_RPL\\_FAILED\\_TO\\_CREATE\\_NEW\\_INFO\\_FILE](#) was added in 8.0.2.
  - Error number: [MY-010430](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_CREATE\\_CACHE\\_FOR\\_INFO\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: Failed to create a cache on info file (file '%s')  
  
[ER\\_RPL\\_FAILED\\_TO\\_CREATE\\_CACHE\\_FOR\\_INFO\\_FILE](#) was added in 8.0.2.
  - Error number: [MY-010431](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_OPEN\\_INFO\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: Failed to open the existing info file (file '%s', errno %d)  
  
[ER\\_RPL\\_FAILED\\_TO\\_OPEN\\_INFO\\_FILE](#) was added in 8.0.2.
  - Error number: [MY-010432](#); Symbol: [ER\\_RPL\\_GTID\\_MEMORY\\_FINALLY\\_AVAILABLE](#); SQLSTATE: [HY000](#)  
  
Message: Server overcomes the temporary 'out of memory' in '%d' tries while allocating a new chunk of intervals for storing GTIDs.  
  
[ER\\_RPL\\_GTID\\_MEMORY\\_FINALLY\\_AVAILABLE](#) was added in 8.0.2.
  - Error number: [MY-010433](#); Symbol: [ER\\_SERVER\\_COST\\_UNKNOWN\\_COST\\_CONSTANT](#); SQLSTATE: [HY000](#)  
  
Message: Unknown cost constant "%s" in mysql.server\_cost table  
  
[ER\\_SERVER\\_COST\\_UNKNOWN\\_COST\\_CONSTANT](#) was added in 8.0.2.
  - Error number: [MY-010434](#); Symbol: [ER\\_SERVER\\_COST\\_INVALID\\_COST\\_CONSTANT](#); SQLSTATE: [HY000](#)  
  
Message: Invalid value for cost constant "%s" in mysql.server\_cost table: %.1f  
  
[ER\\_SERVER\\_COST\\_INVALID\\_COST\\_CONSTANT](#) was added in 8.0.2.
  - Error number: [MY-010435](#); Symbol: [ER\\_ENGINE\\_COST\\_UNKNOWN\\_COST\\_CONSTANT](#); SQLSTATE: [HY000](#)  
  
Message: Unknown cost constant "%s" in mysql.engine\_cost table  
  
[ER\\_ENGINE\\_COST\\_UNKNOWN\\_COST\\_CONSTANT](#) was added in 8.0.2.

- 
- Error number: [MY-010436](#); Symbol: [ER\\_ENGINE\\_COST\\_UNKNOWN\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)  
  
Message: Unknown storage engine "%s" in mysql.engine\_cost table  
  
[ER\\_ENGINE\\_COST\\_UNKNOWN\\_STORAGE\\_ENGINE](#) was added in 8.0.2.
  - Error number: [MY-010437](#); Symbol: [ER\\_ENGINE\\_COST\\_INVALID\\_DEVICE\\_TYPE\\_FOR\\_SE](#); SQLSTATE: [HY000](#)  
  
Message: Invalid device type %d for "%s" storage engine for cost constant "%s" in mysql.engine\_cost table  
  
[ER\\_ENGINE\\_COST\\_INVALID\\_DEVICE\\_TYPE\\_FOR\\_SE](#) was added in 8.0.2.
  - Error number: [MY-010438](#); Symbol: [ER\\_ENGINE\\_COST\\_INVALID\\_CONST\\_CONSTANT\\_FOR\\_SE\\_AND\\_DEVICE](#); SQLSTATE: [HY000](#)  
  
Message: Invalid value for cost constant "%s" for "%s" storage engine and device type %d in mysql.engine\_cost table: %.1f  
  
[ER\\_ENGINE\\_COST\\_INVALID\\_CONST\\_CONSTANT\\_FOR\\_SE\\_AND\\_DEVICE](#) was added in 8.0.2.
  - Error number: [MY-010439](#); Symbol: [ER\\_SERVER\\_COST\\_FAILED\\_TO\\_READ](#); SQLSTATE: [HY000](#)  
  
Message: Error while reading from mysql.server\_cost table.  
  
[ER\\_SERVER\\_COST\\_FAILED\\_TO\\_READ](#) was added in 8.0.2.
  - Error number: [MY-010440](#); Symbol: [ER\\_ENGINE\\_COST\\_FAILED\\_TO\\_READ](#); SQLSTATE: [HY000](#)  
  
Message: Error while reading from mysql.engine\_cost table.  
  
[ER\\_ENGINE\\_COST\\_FAILED\\_TO\\_READ](#) was added in 8.0.2.
  - Error number: [MY-010441](#); Symbol: [ER\\_FAILED\\_TO\\_OPEN\\_COST\\_CONSTANT\\_TABLES](#); SQLSTATE: [HY000](#)  
  
Message: Failed to open optimizer cost constant tables  
  
[ER\\_FAILED\\_TO\\_OPEN\\_COST\\_CONSTANT\\_TABLES](#) was added in 8.0.2.
  - Error number: [MY-010442](#); Symbol: [ER\\_RPL\\_UNSUPPORTED\\_UNIGNORABLE\\_EVENT\\_IN\\_STREAM](#); SQLSTATE: [HY000](#)  
  
Message: Unsupported non-ignorable event fed into the event stream.  
  
[ER\\_RPL\\_UNSUPPORTED\\_UNIGNORABLE\\_EVENT\\_IN\\_STREAM](#) was added in 8.0.2.
  - Error number: [MY-010443](#); Symbol: [ER\\_RPL\\_GTID\\_LOG\\_EVENT\\_IN\\_STREAM](#); SQLSTATE: [HY000](#)  
  
Message: GTID\_LOG\_EVENT or ANONYMOUS\_GTID\_LOG\_EVENT is not expected in an event stream %s.  
  
[ER\\_RPL\\_GTID\\_LOG\\_EVENT\\_IN\\_STREAM](#) was added in 8.0.2.
  - Error number: [MY-010444](#); Symbol: [ER\\_RPL\\_UNEXPECTED\\_BEGIN\\_IN\\_STREAM](#); SQLSTATE: [HY000](#)  
  
Message: QUERY(BEGIN) is not expected in an event stream in the middle of a %s.

---

`ER_RPL_UNEXPECTED_BEGIN_IN_STREAM` was added in 8.0.2.

- Error number: `MY-010445`; Symbol: `ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOG_EVENT_IN_STREAM`; SQLSTATE: `HY000`

Message: QUERY(COMMIT or ROLLBACK) or XID\_LOG\_EVENT is not expected in an event stream %s.

`ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOG_EVENT_IN_STREAM` was added in 8.0.2.

- Error number: `MY-010446`; Symbol: `ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM`; SQLSTATE: `HY000`

Message: QUERY(XA ROLLBACK) is not expected in an event stream %s.

`ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM` was added in 8.0.2.

- Error number: `MY-010447`; Symbol: `ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER`; SQLSTATE: `HY000`

Message: Event Scheduler: [%s].[%s.%s] execution failed, failed to authenticate the user.

`ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER` was added in 8.0.2.

- Error number: `MY-010448`; Symbol: `ER_EVENT_EXECUTION_FAILED_USER_LOST_EVENT_PRIVILEGE`; SQLSTATE: `HY000`

Message: Event Scheduler: [%s].[%s.%s] execution failed, user no longer has EVENT privilege.

`ER_EVENT_EXECUTION_FAILED_USER_LOST_EVENT_PRIVILEGE` was added in 8.0.2.

- Error number: `MY-010449`; Symbol: `ER_EVENT_ERROR_DURING_COMPILATION`; SQLSTATE: `HY000`

Message: Event Scheduler: %serror during compilation of %s.%s

`ER_EVENT_ERROR_DURING_COMPILATION` was added in 8.0.2.

- Error number: `MY-010450`; Symbol: `ER_EVENT_DROPPING`; SQLSTATE: `HY000`

Message: Event Scheduler: Dropping %s.%s

`ER_EVENT_DROPPING` was added in 8.0.2.

- Error number: `MY-010451`; Symbol: `ER_NDB_SCHEMA_GENERIC_MESSAGE`; SQLSTATE: `HY000`

Message: Ndb schema[%s.%s]: %s

`ER_NDB_SCHEMA_GENERIC_MESSAGE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010452`; Symbol: `ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR`; SQLSTATE: `HY000`

Message: In RBR mode, Replica received incompatible DECIMAL field (old-style decimal field) from Source while creating conversion table. Please consider changing datatype on Source to new style decimal by executing ALTER command for column Name: %s.%s.%s.

`ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR` was added in 8.0.2.

- Error number: `MY-010453`; Symbol: `ER_INIT_ROOT_WITHOUT_PASSWORD`; SQLSTATE: `HY000`

---

Message: root@localhost is created with an empty password ! Please consider switching off the --initialize-insecure option.

`ER_INIT_ROOT_WITHOUT_PASSWORD` was added in 8.0.2.

- Error number: `MY-010454`; Symbol: `ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT`; SQLSTATE: `HY000`

Message: A temporary password is generated for root@localhost: %s

`ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT` was added in 8.0.2.

- Error number: `MY-010455`; Symbol: `ER_INIT_CANT_OPEN_BOOTSTRAP_FILE`; SQLSTATE: `HY000`

Message: Failed to open the bootstrap file %s

`ER_INIT_CANT_OPEN_BOOTSTRAP_FILE` was added in 8.0.2.

- Error number: `MY-010456`; Symbol: `ER_INIT_BOOTSTRAP_COMPLETE`; SQLSTATE: `HY000`

Message: Bootstrapping complete

`ER_INIT_BOOTSTRAP_COMPLETE` was added in 8.0.2.

- Error number: `MY-010457`; Symbol: `ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE`; SQLSTATE: `HY000`

Message: --initialize specified but the data directory has files in it. Aborting.

`ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE` was added in 8.0.2.

- Error number: `MY-010458`; Symbol: `ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE`; SQLSTATE: `HY000`

Message: --initialize specified on an existing data directory.

`ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE` was added in 8.0.2.

- Error number: `MY-010459`; Symbol: `ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE`; SQLSTATE: `HY000`

Message: --initialize specified but the data directory exists and the path is too long. Aborting.

`ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE` was added in 8.0.2.

- Error number: `MY-010460`; Symbol: `ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE`; SQLSTATE: `HY000`

Message: --initialize specified but the data directory exists and is not writable. Aborting.

`ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE` was added in 8.0.2.

- Error number: `MY-010461`; Symbol: `ER_INIT_CREATING_DD`; SQLSTATE: `HY000`

Message: Creating the data directory %s

`ER_INIT_CREATING_DD` was added in 8.0.2.

- Error number: `MY-010462`; Symbol: `ER_RPL_BINLOG_STARTING_DUMP`; SQLSTATE: `HY000`

---

Message: Start binlog\_dump to source\_thread\_id(%u) replica\_server(%u), pos(%s, %llu)

`ER_RPL_BINLOG_STARTING_DUMP` was added in 8.0.2.

- Error number: `MY-010463`; Symbol: `ER_RPL_BINLOG_MASTER_SENDS_HEARTBEAT`; SQLSTATE: `HY000`

Message: master sends heartbeat message

`ER_RPL_BINLOG_MASTER_SENDS_HEARTBEAT` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010463`; Symbol: `ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT`; SQLSTATE: `HY000`

Message: source sends heartbeat message

`ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT` was added in 8.0.33.

- Error number: `MY-010464`; Symbol: `ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO`; SQLSTATE: `HY000`

Message: the rest of heartbeat info skipped ...

`ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO` was added in 8.0.2.

- Error number: `MY-010465`; Symbol: `ER_RPL_BINLOG_MASTER_USES_CHECKSUM_AND_SLAVE_CANT`; SQLSTATE: `HY000`

Message: Master is configured to log replication events with checksum, but will not send such events to slaves that cannot process them

`ER_RPL_BINLOG_MASTER_USES_CHECKSUM_AND_SLAVE_CANT` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010465`; Symbol: `ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICA_CANT`; SQLSTATE: `HY000`

Message: Source is configured to log replication events with checksum, but will not send such events to replicas that cannot process them

`ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICA_CANT` was added in 8.0.33.

- Error number: `MY-010466`; Symbol: `ER_NDB_QUERY_FAILED`; SQLSTATE: `HY000`

Message: NDB: Query '%s' failed, error: %d: %s

`ER_NDB_QUERY_FAILED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010467`; Symbol: `ER_KILLING_THREAD`; SQLSTATE: `HY000`

Message: Killing thread %lu

`ER_KILLING_THREAD` was added in 8.0.2.

- Error number: `MY-010468`; Symbol: `ER_DETACHING_SESSION_LEFT_BY_PLUGIN`; SQLSTATE: `HY000`

Message: Plugin %s is deinitializing a thread but left a session attached. Detaching it forcefully.

---

`ER_DETACHING_SESSION_LEFT_BY_PLUGIN` was added in 8.0.2.

- Error number: `MY-010469`; Symbol: `ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN`; SQLSTATE: `HY000`

Message: Failed to detach the session.

`ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN` was added in 8.0.2.

- Error number: `MY-010470`; Symbol: `ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN`; SQLSTATE: `HY000`

Message: Closed forcefully %u session%s left opened by plugin %s

`ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN` was added in 8.0.2.

- Error number: `MY-010471`; Symbol: `ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS`; SQLSTATE: `HY000`

Message: Failed to decrement the number of threads

`ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS` was added in 8.0.2.

- Error number: `MY-010472`; Symbol: `ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS`; SQLSTATE: `HY000`

Message: Plugin %s did not deinitialize %u threads

`ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS` was added in 8.0.2.

- Error number: `MY-010473`; Symbol: `ER_KILLED_THREADS_OF_PLUGIN`; SQLSTATE: `HY000`

Message: Killed %u threads of plugin %s

`ER_KILLED_THREADS_OF_PLUGIN` was added in 8.0.2.

- Error number: `MY-010474`; Symbol: `ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN`; SQLSTATE: `HY000`

Message: NDB Slave : Could not determine maximum replicated epoch from %s.%s at Slave start, error %u %s

`ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010475`; Symbol: `ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_SET_TO`; SQLSTATE: `HY000`

Message: NDB Slave : MaxReplicatedEpoch set to %llu (%u/%u) at Slave start

`ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_SET_TO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010476`; Symbol: `ER_NDB_NODE_ID_AND_MANAGEMENT_SERVER_INFO`; SQLSTATE: `HY000`

Message: NDB: NodeID is %lu, management server '%s:%lu'

`ER_NDB_NODE_ID_AND_MANAGEMENT_SERVER_INFO` was added in 8.0.2, removed after 8.0.13.

- 
- Error number: [MY-010477](#); Symbol: [ER\\_NDB\\_DISCONNECT\\_INFO](#); SQLSTATE: [HY000](#)  
Message: tid %u: node[%u] transaction\_hint=%u, transaction\_no\_hint=%u  
[ER\\_NDB\\_DISCONNECT\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010478](#); Symbol: [ER\\_NDB\\_COLUMN\\_DEFAULTS\\_DIFFER](#); SQLSTATE: [HY000](#)  
Message: NDB Internal error: Default values differ for column %u, ndb\_default: %d  
[ER\\_NDB\\_COLUMN\\_DEFAULTS\\_DIFFER](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010479](#); Symbol: [ER\\_NDB\\_COLUMN\\_SHOULD\\_NOT\\_HAVE\\_NATIVE\\_DEFAULT](#); SQLSTATE: [HY000](#)  
Message: NDB Internal error: Column %u has native default, but shouldn't. Flags=%u, type=%u  
[ER\\_NDB\\_COLUMN\\_SHOULD\\_NOT\\_HAVE\\_NATIVE\\_DEFAULT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010480](#); Symbol: [ER\\_NDB\\_FIELD\\_INFO](#); SQLSTATE: [HY000](#)  
Message: field[ name: '%s', type: %u, real\_type: %u, flags: 0x%x, is\_null: %d]  
[ER\\_NDB\\_FIELD\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010481](#); Symbol: [ER\\_NDB\\_COLUMN\\_INFO](#); SQLSTATE: [HY000](#)  
Message: ndbCol[name: '%s', type: %u, column\_no: %d, nullable: %d]  
[ER\\_NDB\\_COLUMN\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010482](#); Symbol: [ER\\_NDB\\_OOM\\_IN\\_FIX\\_UNIQUE\\_INDEX\\_ATTR\\_ORDER](#); SQLSTATE: [HY000](#)  
Message: fix\_unique\_index\_attr\_order: my\_malloc(%u) failure  
[ER\\_NDB\\_OOM\\_IN\\_FIX\\_UNIQUE\\_INDEX\\_ATTR\\_ORDER](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010483](#); Symbol: [ER\\_NDB\\_SLAVE\\_MALFORMED\\_EVENT\\_RECEIVED\\_ON\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: NDB Slave : Malformed event received on table %s cannot parse. Stopping Slave.  
[ER\\_NDB\\_SLAVE\\_MALFORMED\\_EVENT\\_RECEIVED\\_ON\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010484](#); Symbol: [ER\\_NDB\\_SLAVE\\_CONFLICT\\_FUNCTION\\_REQUIRES\\_ROLE](#); SQLSTATE: [HY000](#)  
Message: NDB Slave : Conflict function %s defined on table %s requires ndb\_slave\_conflict\_role variable to be set. Stopping slave.  
[ER\\_NDB\\_SLAVE\\_CONFLICT\\_FUNCTION\\_REQUIRES\\_ROLE](#) was added in 8.0.2, removed after 8.0.13.



- 
- Error number: [MY-010485](#); Symbol: [ER\\_NDB\\_SLAVE\\_CONFLICT\\_DETECTION\\_REQUIRES\\_TRANSACTION\\_IDS](#); SQLSTATE: [HY000](#)  
  
Message: NDB Slave : Transactional conflict detection defined on table %s, but events received without transaction ids. Check --ndb-log-transaction-id setting on upstream Cluster.  
  
[ER\\_NDB\\_SLAVE\\_CONFLICT\\_DETECTION\\_REQUIRES\\_TRANSACTION\\_IDS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010486](#); Symbol: [ER\\_NDB\\_SLAVE\\_BINLOG\\_MISSING\\_INFO\\_FOR\\_CONFLICT\\_DETECTION](#); SQLSTATE: [HY000](#)  
  
Message: NDB Slave : Binlog event on table %s missing info necessary for conflict detection. Check binlog format options on upstream cluster.  
  
[ER\\_NDB\\_SLAVE\\_BINLOG\\_MISSING\\_INFO\\_FOR\\_CONFLICT\\_DETECTION](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010487](#); Symbol: [ER\\_NDB\\_ERROR\\_IN\\_READAUTOINCREMENTVALUE](#); SQLSTATE: [HY000](#)  
  
Message: Error %lu in readAutoIncrementValue(): %s  
  
[ER\\_NDB\\_ERROR\\_IN\\_READAUTOINCREMENTVALUE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010488](#); Symbol: [ER\\_NDB\\_FOUND\\_UNCOMMITTED\\_AUTOCOMMIT](#); SQLSTATE: [HY000](#)  
  
Message: found uncommitted autocommit+rbwr transaction, commit status: %d  
  
[ER\\_NDB\\_FOUND\\_UNCOMMITTED\\_AUTOCOMMIT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010489](#); Symbol: [ER\\_NDB\\_SLAVE\\_TOO\\_MANY\\_RETRIES](#); SQLSTATE: [HY000](#)  
  
Message: Ndb slave retried transaction %u time(s) in vain. Giving up.  
  
[ER\\_NDB\\_SLAVE\\_TOO\\_MANY\\_RETRIES](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010490](#); Symbol: [ER\\_NDB\\_SLAVE\\_ERROR\\_IN\\_UPDATE\\_CREATE\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Error %lu in ::update\_create\_info(): %s  
  
[ER\\_NDB\\_SLAVE\\_ERROR\\_IN\\_UPDATE\\_CREATE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010491](#); Symbol: [ER\\_NDB\\_SLAVE\\_CANT\\_ALLOCATE\\_TABLE\\_SHARE](#); SQLSTATE: [HY000](#)  
  
Message: NDB: allocating table share for %s failed  
  
[ER\\_NDB\\_SLAVE\\_CANT\\_ALLOCATE\\_TABLE\\_SHARE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010492](#); Symbol: [ER\\_NDB\\_BINLOG\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)  
  
Message: NDB Binlog: (%d)%s  
  
[ER\\_NDB\\_BINLOG\\_ERROR\\_INFO\\_FROM\\_DA](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010493](#); Symbol: [ER\\_NDB\\_BINLOG\\_CREATE\\_TABLE\\_EVENT](#); SQLSTATE: [HY000](#)

---

Message: NDB Binlog: CREATE TABLE Event: %s

[ER\\_NDB\\_BINLOG\\_CREATE\\_TABLE\\_EVENT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010494](#); Symbol: [ER\\_NDB\\_BINLOG\\_FAILED\\_CREATE\\_TABLE\\_EVENT\\_OPERATIONS](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: FAILED CREATE TABLE event operations. Event: %s

[ER\\_NDB\\_BINLOG\\_FAILED\\_CREATE\\_TABLE\\_EVENT\\_OPERATIONS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010495](#); Symbol: [ER\\_NDB\\_BINLOG\\_RENAME\\_EVENT](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: RENAME Event: %s

[ER\\_NDB\\_BINLOG\\_RENAME\\_EVENT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010496](#); Symbol: [ER\\_NDB\\_BINLOG\\_FAILED\\_CREATE\\_EVENT\\_OPERATIONS\\_DURING\\_RENAME](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: FAILED create event operations during RENAME. Event %s

[ER\\_NDB\\_BINLOG\\_FAILED\\_CREATE\\_EVENT\\_OPERATIONS\\_DURING\\_RENAME](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010497](#); Symbol: [ER\\_NDB\\_UNEXPECTED\\_RENAME\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Unexpected rename case detected, sql\_command: %d

[ER\\_NDB\\_UNEXPECTED\\_RENAME\\_TYPE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010498](#); Symbol: [ER\\_NDB\\_ERROR\\_IN\\_GET\\_AUTO\\_INCREMENT](#); SQLSTATE: [HY000](#)

Message: Error %lu in ::get\_auto\_increment(): %s

[ER\\_NDB\\_ERROR\\_IN\\_GET\\_AUTO\\_INCREMENT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010499](#); Symbol: [ER\\_NDB\\_CREATING\\_SHARE\\_IN\\_OPEN](#); SQLSTATE: [HY000](#)

Message: Calling ndbcluster\_create\_binlog\_setup(%s) in ::open

[ER\\_NDB\\_CREATING\\_SHARE\\_IN\\_OPEN](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010500](#); Symbol: [ER\\_NDB\\_TABLE\\_OPENED\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)

Message: table '%s' opened read only

[ER\\_NDB\\_TABLE\\_OPENED\\_READ\\_ONLY](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010501](#); Symbol: [ER\\_NDB\\_INITIALIZE\\_GIVEN\\_CLUSTER\\_PLUGIN\\_DISABLED](#); SQLSTATE: [HY000](#)

Message: NDB: '--initialize' -> ndbcluster plugin disabled

[ER\\_NDB\\_INITIALIZE\\_GIVEN\\_CLUSTER\\_PLUGIN\\_DISABLED](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: [MY-010502](#); Symbol: [ER\\_NDB\\_BINLOG\\_FORMAT\\_CHANGED\\_FROM\\_STMT\\_TO\\_MIXED](#); SQLSTATE: [HY000](#)  
  
Message: NDB: Changed global value of binlog\_format from STATEMENT to MIXED  
  
[ER\\_NDB\\_BINLOG\\_FORMAT\\_CHANGED\\_FROM\\_STMT\\_TO\\_MIXED](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010503](#); Symbol: [ER\\_NDB\\_TRAILING\\_SHARE\\_RELEASED\\_BY\\_CLOSE\\_CACHED\\_TABLES](#); SQLSTATE: [HY000](#)  
  
Message: NDB\_SHARE: trailing share %s, released by close\_cached\_tables  
  
[ER\\_NDB\\_TRAILING\\_SHARE\\_RELEASED\\_BY\\_CLOSE\\_CACHED\\_TABLES](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010504](#); Symbol: [ER\\_NDB\\_SHARE\\_ALREADY\\_EXISTS](#); SQLSTATE: [HY000](#)  
  
Message: NDB\_SHARE: %s already exists use\_count=%d. Moving away for safety, but possible memleak.  
  
[ER\\_NDB\\_SHARE\\_ALREADY\\_EXISTS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010505](#); Symbol: [ER\\_NDB\\_HANDLE\\_TRAILING\\_SHARE\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: handle\_trailing\_share: %s use\_count: %u  
  
[ER\\_NDB\\_HANDLE\\_TRAILING\\_SHARE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010506](#); Symbol: [ER\\_NDB\\_CLUSTER\\_GET\\_SHARE\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: ndbcluster\_get\_share: %s use\_count: %u  
  
[ER\\_NDB\\_CLUSTER\\_GET\\_SHARE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010507](#); Symbol: [ER\\_NDB\\_CLUSTER\\_REAL\\_FREE\\_SHARE\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: ndbcluster\_real\_free\_share: %s use\_count: %u  
  
[ER\\_NDB\\_CLUSTER\\_REAL\\_FREE\\_SHARE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010508](#); Symbol: [ER\\_NDB\\_CLUSTER\\_REAL\\_FREE\\_SHARE\\_DROP\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: ndbcluster\_real\_free\_share: %s, still open - ignored 'free' (leaked?)  
  
[ER\\_NDB\\_CLUSTER\\_REAL\\_FREE\\_SHARE\\_DROP\\_FAILED](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010509](#); Symbol: [ER\\_NDB\\_CLUSTER\\_FREE\\_SHARE\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: ndbcluster\_free\_share: %s use\_count: %u  
  
[ER\\_NDB\\_CLUSTER\\_FREE\\_SHARE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010510](#); Symbol: [ER\\_NDB\\_CLUSTER\\_MARK\\_SHARE\\_DROPPED\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: ndbcluster\_mark\_share\_dropped: %s use\_count: %u

---

`ER_NDB_CLUSTER_MARK_SHARE_DROPPED_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010511`; Symbol:

`ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROYING_SHARE`; `SQLSTATE: HY000`

Message: `ndbcluster_mark_share_dropped: destroys share %s`

`ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROYING_SHARE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010512`; Symbol: `ER_NDB_CLUSTER_OOM_THD_NDB`; `SQLSTATE: HY000`

Message: Could not allocate `Thd_ndb` object

`ER_NDB_CLUSTER_OOM_THD_NDB` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010513`; Symbol: `ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY`; `SQLSTATE: HY000`

Message: NDB Binlog: Ndb tables initially read only.

`ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010514`; Symbol: `ER_NDB_UTIL_THREAD_OOM`; `SQLSTATE: HY000`

Message: `ndb util thread: malloc failure, query cache not maintained properly`

`ER_NDB_UTIL_THREAD_OOM` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010515`; Symbol: `ER_NDB_ILLEGAL_VALUE_FOR_NDB_RECV_THREAD_CPU_MASK`; `SQLSTATE: HY000`

Message: Trying to set `ndb_recv_thread_cpu_mask` to illegal value = %s, ignored

`ER_NDB_ILLEGAL_VALUE_FOR_NDB_RECV_THREAD_CPU_MASK` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010516`; Symbol: `ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD_CPU_MASK`; `SQLSTATE: HY000`

Message: Trying to set too many CPU's in `ndb_recv_thread_cpu_mask`, ignored this variable, erroneous value = %s

`ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD_CPU_MASK` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010517`; Symbol: `ER_DEBUG_CHECK_SHARES_OPEN`; `SQLSTATE: HY000`

Message: `debug_check_shares open:`

`ER_DEBUG_CHECK_SHARES_OPEN` was added in 8.0.2.

- Error number: `MY-010518`; Symbol: `ER_DEBUG_CHECK_SHARES_INFO`; `SQLSTATE: HY000`

Message: %s.%s: state: %s(%u) use\_count: %u

`ER_DEBUG_CHECK_SHARES_INFO` was added in 8.0.2.

- 
- Error number: [MY-010519](#); Symbol: [ER\\_DEBUG\\_CHECK\\_SHARES\\_DROPPED](#); SQLSTATE: [HY000](#)  
Message: debug\_check\_shares dropped:  
  
[ER\\_DEBUG\\_CHECK\\_SHARES\\_DROPPED](#) was added in 8.0.2.
  - Error number: [MY-010520](#); Symbol: [ER\\_INVALID\\_OR\\_OLD\\_TABLE\\_OR\\_DB\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Invalid (old?) table or database name '%s'  
  
[ER\\_INVALID\\_OR\\_OLD\\_TABLE\\_OR\\_DB\\_NAME](#) was added in 8.0.2.
  - Error number: [MY-010521](#); Symbol: [ER\\_TC\\_RECOVERING\\_AFTER\\_CRASH\\_USING](#); SQLSTATE: [HY000](#)  
Message: Recovering after a crash using %s  
  
[ER\\_TC\\_RECOVERING\\_AFTER\\_CRASH\\_USING](#) was added in 8.0.2.
  - Error number: [MY-010522](#); Symbol: [ER\\_TC\\_CANT\\_AUTO\\_RECOVER\\_WITH\\_TC\\_HEURISTIC\\_RECOVER](#); SQLSTATE: [HY000](#)  
Message: Cannot perform automatic crash recovery when --tc-heuristic-recover is used  
  
[ER\\_TC\\_CANT\\_AUTO\\_RECOVER\\_WITH\\_TC\\_HEURISTIC\\_RECOVER](#) was added in 8.0.2.
  - Error number: [MY-010523](#); Symbol: [ER\\_TC\\_BAD\\_MAGIC\\_IN\\_TC\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Bad magic header in tc log  
  
[ER\\_TC\\_BAD\\_MAGIC\\_IN\\_TC\\_LOG](#) was added in 8.0.2.
  - Error number: [MY-010524](#); Symbol: [ER\\_TC\\_NEED\\_N\\_SE\\_SUPPORTING\\_2PC\\_FOR\\_RECOVERY](#); SQLSTATE: [HY000](#)  
Message: Recovery failed! You must enable exactly %d storage engines that support two-phase commit protocol  
  
[ER\\_TC\\_NEED\\_N\\_SE\\_SUPPORTING\\_2PC\\_FOR\\_RECOVERY](#) was added in 8.0.2.
  - Error number: [MY-010525](#); Symbol: [ER\\_TC\\_RECOVERY\\_FAILED\\_THESE\\_ARE\\_YOUR\\_OPTIONS](#); SQLSTATE: [HY000](#)  
Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error) and restart, or delete tc log and start mysqld with --tc-heuristic-recover={commit|rollback}  
  
[ER\\_TC\\_RECOVERY\\_FAILED\\_THESE\\_ARE\\_YOUR\\_OPTIONS](#) was added in 8.0.2.
  - Error number: [MY-010526](#); Symbol: [ER\\_TC\\_HEURISTIC\\_RECOVERY\\_MODE](#); SQLSTATE: [HY000](#)  
Message: Heuristic crash recovery mode  
  
[ER\\_TC\\_HEURISTIC\\_RECOVERY\\_MODE](#) was added in 8.0.2.
  - Error number: [MY-010527](#); Symbol: [ER\\_TC\\_HEURISTIC\\_RECOVERY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Heuristic crash recovery failed

- 
- Error number: [MY-010528](#); Symbol: [ER\\_TC\\_RESTART\\_WITHOUT\\_TC\\_HEURISTIC\\_RECOVER](#); SQLSTATE: [HY000](#)

Message: Please restart mysqld without --tc-heuristic-recover

[ER\\_TC\\_RESTART\\_WITHOUT\\_TC\\_HEURISTIC\\_RECOVER](#) was added in 8.0.2.

- Error number: [MY-010529](#); Symbol: [ER\\_RPL\\_SLAVE\\_FAILED\\_TO\\_CREATE\\_OR\\_RECOVER\\_INFO\\_REPOSITORIES](#); SQLSTATE: [HY000](#)

Message: Failed to create or recover replication info repositories.

[ER\\_RPL\\_SLAVE\\_FAILED\\_TO\\_CREATE\\_OR\\_RECOVER\\_INFO\\_REPOSITORIES](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010529](#); Symbol: [ER\\_RPL\\_REPLICA\\_FAILED\\_TO\\_CREATE\\_OR\\_RECOVER\\_INFO\\_REPOSITORIES](#); SQLSTATE: [HY000](#)

Message: Failed to create or recover replication info repositories.

[ER\\_RPL\\_REPLICA\\_FAILED\\_TO\\_CREATE\\_OR\\_RECOVER\\_INFO\\_REPOSITORIES](#) was added in 8.0.33.

- Error number: [MY-010530](#); Symbol: [ER\\_RPL\\_SLAVE\\_AUTO\\_POSITION\\_IS\\_1\\_AND\\_GTID\\_MODE\\_IS\\_OFF](#); SQLSTATE: [HY000](#)

Message: Detected misconfiguration: replication channel '%s' was configured with AUTO\_POSITION = 1, but the server was started with --gtid-mode=off. Either reconfigure replication using CHANGE MASTER TO MASTER\_AUTO\_POSITION = 0 FOR CHANNEL '%s', or change GTID\_MODE to some value other than OFF, before starting the slave receiver thread.

[ER\\_RPL\\_SLAVE\\_AUTO\\_POSITION\\_IS\\_1\\_AND\\_GTID\\_MODE\\_IS\\_OFF](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010530](#); Symbol: [ER\\_RPL\\_REPLICA\\_AUTO\\_POSITION\\_IS\\_1\\_AND\\_GTID\\_MODE\\_IS\\_OFF](#); SQLSTATE: [HY000](#)

Message: Detected misconfiguration: replication channel '%s' was configured with AUTO\_POSITION = 1, but the server was started with --gtid-mode=off. Either reconfigure replication using CHANGE REPLICATION SOURCE TO SOURCE\_AUTO\_POSITION = 0 FOR CHANNEL '%s', or change GTID\_MODE to some value other than OFF, before starting the replica receiver thread.

[ER\\_RPL\\_REPLICA\\_AUTO\\_POSITION\\_IS\\_1\\_AND\\_GTID\\_MODE\\_IS\\_OFF](#) was added in 8.0.33.

- Error number: [MY-010531](#); Symbol: [ER\\_RPL\\_SLAVE\\_CANT\\_START\\_SLAVE\\_FOR\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Slave: Could not start slave for channel '%s'. operation discontinued

[ER\\_RPL\\_SLAVE\\_CANT\\_START\\_SLAVE\\_FOR\\_CHANNEL](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010531](#); Symbol: [ER\\_RPL\\_REPLICA\\_CANT\\_START\\_REPLICA\\_FOR\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Replica: Could not start replica for channel '%s'. operation discontinued

[ER\\_RPL\\_REPLICA\\_CANT\\_START\\_REPLICA\\_FOR\\_CHANNEL](#) was added in 8.0.33.

- 
- Error number: [MY-010532](#); Symbol: [ER\\_RPL\\_SLAVE\\_CANT\\_STOP\\_SLAVE\\_FOR\\_CHANNEL](#); SQLSTATE: [HY000](#)  
  
Message: Slave: Could not stop slave for channel '%s' operation discontinued  
  
[ER\\_RPL\\_SLAVE\\_CANT\\_STOP\\_SLAVE\\_FOR\\_CHANNEL](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010532](#); Symbol: [ER\\_RPL\\_REPLICA\\_CANT\\_STOP\\_REPLICA\\_FOR\\_CHANNEL](#); SQLSTATE: [HY000](#)  
  
Message: Replica: Could not stop replica for channel '%s' operation discontinued  
  
[ER\\_RPL\\_REPLICA\\_CANT\\_STOP\\_REPLICA\\_FOR\\_CHANNEL](#) was added in 8.0.33.
  - Error number: [MY-010533](#); Symbol: [ER\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_MASTER](#); SQLSTATE: [HY000](#)  
  
Message: Error during --relay-log-recovery: Could not locate rotate event from the master.  
  
[ER\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_MASTER](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010533](#); Symbol: [ER\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_SOURCE](#); SQLSTATE: [HY000](#)  
  
Message: Error during --relay-log-recovery: Could not locate rotate event from the source.  
  
[ER\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_SOURCE](#) was added in 8.0.33.
  - Error number: [MY-010534](#); Symbol: [ER\\_RPL\\_RECOVERY\\_ERROR\\_READ\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: Error during --relay-log-recovery: Error reading events from relay log: %d  
  
[ER\\_RPL\\_RECOVERY\\_ERROR\\_READ\\_RELAY\\_LOG](#) was added in 8.0.2.
  - Error number: [MY-010535](#); Symbol: [ER\\_RPL\\_RECOVERY\\_ERROR\\_FREEING\\_IO\\_CACHE](#); SQLSTATE: [HY000](#)  
  
Message: Error during --relay-log-recovery: Error while freeing IO\_CACHE object  
  
[ER\\_RPL\\_RECOVERY\\_ERROR\\_FREEING\\_IO\\_CACHE](#) was added in 8.0.2, removed after 8.0.12.
  - Error number: [MY-010536](#); Symbol: [ER\\_RPL\\_RECOVERY\\_SKIPPED\\_GROUP\\_REPLICATION\\_CHANNEL](#); SQLSTATE: [HY000](#)  
  
Message: Relay log recovery skipped for group replication channel.  
  
[ER\\_RPL\\_RECOVERY\\_SKIPPED\\_GROUP\\_REPLICATION\\_CHANNEL](#) was added in 8.0.2.
  - Error number: [MY-010537](#); Symbol: [ER\\_RPL\\_RECOVERY\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error during --relay-log-recovery: %s  
  
[ER\\_RPL\\_RECOVERY\\_ERROR](#) was added in 8.0.2.
  - Error number: [MY-010538](#); Symbol: [ER\\_RPL\\_RECOVERY\\_IO\\_ERROR\\_READING\\_RELAY\\_LOG\\_INDEX](#); SQLSTATE: [HY000](#)  
  
Message: Error during --relay-log-recovery: Could not read relay log index file due to an IO error.

---

`ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX` was added in 8.0.2.

- Error number: `MY-010539`; Symbol: `ER_RPL_RECOVERY_FILE_MASTER_POS_INFO`; SQLSTATE: `HY000`

Message: Recovery from master pos %ld and file %s%. Previous relay log pos and relay log file had been set to %lld, %s respectively.

`ER_RPL_RECOVERY_FILE_MASTER_POS_INFO` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010539`; Symbol: `ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO`; SQLSTATE: `HY000`

Message: Recovery from source pos %ld and file %s%. Previous relay log pos and relay log file had been set to %lld, %s respectively.

`ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO` was added in 8.0.33.

- Error number: `MY-010540`; Symbol: `ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRES_POSITION`; SQLSTATE: `HY000`

Message: Error during --relay-log-recovery: replicate\_same\_server\_id is in use and sql thread's positions are not initialized, hence relay log recovery cannot happen.

`ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRES_POSITION` was added in 8.0.2.

- Error number: `MY-010541`; Symbol: `ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR`; SQLSTATE: `HY000`

Message: MTS recovery: starting coordinator thread to fill MTS gaps.

`ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010541`; Symbol: `ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR`; SQLSTATE: `HY000`

Message: MTA recovery: starting coordinator thread to fill MTA gaps.

`ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR` was added in 8.0.33.

- Error number: `MY-010542`; Symbol: `ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDINATOR`; SQLSTATE: `HY000`

Message: MTS recovery: failed to start the coordinator thread. Check the error log for additional details.

`ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDINATOR` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010542`; Symbol: `ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR`; SQLSTATE: `HY000`

Message: MTA recovery: failed to start the coordinator thread. Check the error log for additional details.

`ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR` was added in 8.0.33.

- Error number: `MY-010543`; Symbol: `ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED`; SQLSTATE: `HY000`



---

Message: MTS recovery: automatic recovery failed. Either the slave server had stopped due to an error during an earlier session or relay logs are corrupted. Fix the cause of the slave side error and restart the slave server or consider using RESET SLAVE.

`ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010543`; Symbol: `ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED`; SQLSTATE: `HY000`

Message: MTA recovery: automatic recovery failed. Either the replica server had stopped due to an error during an earlier session or relay logs are corrupted. Fix the cause of the replica side error and restart the replica server or consider using RESET REPLICA.

`ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED` was added in 8.0.33.

- Error number: `MY-010544`; Symbol: `ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG`; SQLSTATE: `HY000`

Message: Failed to open the relay log '%s' (relay\_log\_pos %s).

`ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010544`; Symbol: `ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG`; SQLSTATE: `HY000`

Message: Failed to open the relay log '%s' (relay\_log\_pos %s).

`ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG` was added in 8.0.33.

- Error number: `MY-010545`; Symbol: `ER_RPL_MTS_RECOVERY_SUCCESSFUL`; SQLSTATE: `HY000`

Message: MTS recovery: completed successfully.

`ER_RPL_MTS_RECOVERY_SUCCESSFUL` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010545`; Symbol: `ER_RPL_MTA_RECOVERY_SUCCESSFUL`; SQLSTATE: `HY000`

Message: MTA recovery: completed successfully.

`ER_RPL_MTA_RECOVERY_SUCCESSFUL` was added in 8.0.33.

- Error number: `MY-010546`; Symbol: `ER_RPL_SERVER_ID_MISSING`; SQLSTATE: `HY000`

Message: Server id not set, will not start replica%s

`ER_RPL_SERVER_ID_MISSING` was added in 8.0.2.

- Error number: `MY-010547`; Symbol: `ER_RPL_CANT_CREATE_SLAVE_THREAD`; SQLSTATE: `HY000`

Message: Can't create slave thread%s.

`ER_RPL_CANT_CREATE_SLAVE_THREAD` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010547`; Symbol: `ER_RPL_CANT_CREATE_REPLICA_THREAD`; SQLSTATE: `HY000`

Message: Can't create replica thread%s.

`ER_RPL_CANT_CREATE_REPLICA_THREAD` was added in 8.0.33.

- 
- Error number: [MY-010548](#); Symbol: [ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_WAS\\_KILLED](#); SQLSTATE: [HY000](#)  
  
Message: The slave IO thread%s was killed while executing initialization query '%s'  
  
[ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_WAS\\_KILLED](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010548](#); Symbol: [ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_WAS\\_KILLED](#); SQLSTATE: [HY000](#)  
  
Message: The replica IO thread%s was killed while executing initialization query '%s'  
  
[ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_WAS\\_KILLED](#) was added in 8.0.33.
  - Error number: [MY-010549](#); Symbol: [ER\\_RPL\\_SLAVE\\_MASTER\\_UUID\\_HAS\\_CHANGED](#); SQLSTATE: [HY000](#)  
  
Message: The master's UUID has changed, although this should not happen unless you have changed it manually. The old UUID was %s.  
  
[ER\\_RPL\\_SLAVE\\_MASTER\\_UUID\\_HAS\\_CHANGED](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010550](#); Symbol: [ER\\_RPL\\_SLAVE\\_USES\\_CHECKSUM\\_AND\\_MASTER\\_PRE\\_50](#); SQLSTATE: [HY000](#)  
  
Message: Found a master with MySQL server version older than 5.0. With checksums enabled on the slave, replication might not work correctly. To ensure correct replication, restart the slave server with --replica\_sql\_verify\_checksum=0.  
  
[ER\\_RPL\\_SLAVE\\_USES\\_CHECKSUM\\_AND\\_MASTER\\_PRE\\_50](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010550](#); Symbol: [ER\\_RPL\\_REPLICA\\_USES\\_CHECKSUM\\_AND\\_SOURCE\\_PRE\\_50](#); SQLSTATE: [HY000](#)  
  
Message: Found a source with MySQL server version older than 5.0. With checksums enabled on the replica, replication might not work correctly. To ensure correct replication, restart the replica server with --replica\_sql\_verify\_checksum=0.  
  
[ER\\_RPL\\_REPLICA\\_USES\\_CHECKSUM\\_AND\\_SOURCE\\_PRE\\_50](#) was added in 8.0.33.
  - Error number: [MY-010551](#); Symbol: [ER\\_RPL\\_SLAVE\\_SECONDS\\_BEHIND\\_MASTER\\_DUBIOUS](#); SQLSTATE: [HY000](#)  
  
Message: "SELECT UNIX\_TIMESTAMP()" failed on master, do not trust column Seconds\_Behind\_Master of SHOW SLAVE STATUS. Error: %s (%d)  
  
[ER\\_RPL\\_SLAVE\\_SECONDS\\_BEHIND\\_MASTER\\_DUBIOUS](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010551](#); Symbol: [ER\\_RPL\\_REPLICA\\_SECONDS\\_BEHIND\\_SOURCE\\_DUBIOUS](#); SQLSTATE: [HY000](#)  
  
Message: "SELECT UNIX\_TIMESTAMP()" failed on source, do not trust column Seconds\_Behind\_Source of SHOW REPLICA STATUS. Error: %s (%d)  
  
[ER\\_RPL\\_REPLICA\\_SECONDS\\_BEHIND\\_SOURCE\\_DUBIOUS](#) was added in 8.0.33.

- 
- Error number: [MY-010552](#); Symbol: [ER\\_RPL\\_SLAVE\\_CANT\\_FLUSH\\_MASTER\\_INFO\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: Failed to flush master info file.  
  
[ER\\_RPL\\_SLAVE\\_CANT\\_FLUSH\\_MASTER\\_INFO\\_FILE](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010552](#); Symbol: [ER\\_RPL\\_REPLICA\\_CANT\\_FLUSH\\_CONNECTION\\_METADATA\\_REPOS](#); SQLSTATE: [HY000](#)  
  
Message: Failed to flush connection metadata repository.  
  
[ER\\_RPL\\_REPLICA\\_CANT\\_FLUSH\\_CONNECTION\\_METADATA\\_REPOS](#) was added in 8.0.33.
  - Error number: [MY-010553](#); Symbol: [ER\\_RPL\\_SLAVE\\_REPORT\\_HOST\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
  
Message: The length of report\_host is %zu. It is larger than the max length(%d), so this slave cannot be registered to the master%s.  
  
[ER\\_RPL\\_SLAVE\\_REPORT\\_HOST\\_TOO\\_LONG](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010553](#); Symbol: [ER\\_RPL\\_REPLICA\\_REPORT\\_HOST\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
  
Message: The length of report\_host is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.  
  
[ER\\_RPL\\_REPLICA\\_REPORT\\_HOST\\_TOO\\_LONG](#) was added in 8.0.33.
  - Error number: [MY-010554](#); Symbol: [ER\\_RPL\\_SLAVE\\_REPORT\\_USER\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
  
Message: The length of report\_user is %zu. It is larger than the max length(%d), so this slave cannot be registered to the master%s.  
  
[ER\\_RPL\\_SLAVE\\_REPORT\\_USER\\_TOO\\_LONG](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010554](#); Symbol: [ER\\_RPL\\_REPLICA\\_REPORT\\_USER\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
  
Message: The length of report\_user is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.  
  
[ER\\_RPL\\_REPLICA\\_REPORT\\_USER\\_TOO\\_LONG](#) was added in 8.0.33.
  - Error number: [MY-010555](#); Symbol: [ER\\_RPL\\_SLAVE\\_REPORT\\_PASSWORD\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
  
Message: The length of report\_password is %zu. It is larger than the max length(%d), so this slave cannot be registered to the master%s.  
  
[ER\\_RPL\\_SLAVE\\_REPORT\\_PASSWORD\\_TOO\\_LONG](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010555](#); Symbol: [ER\\_RPL\\_REPLICA\\_REPORT\\_PASSWORD\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
  
Message: The length of report\_password is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.  
  
[ER\\_RPL\\_REPLICA\\_REPORT\\_PASSWORD\\_TOO\\_LONG](#) was added in 8.0.33.

- 
- Error number: `MY-010556`; Symbol: `ER_RPL_SLAVE_ERROR_RETRYING`; SQLSTATE: `HY000`  
  
Message: Error on %s: %d %s, will retry in %d secs  
  
`ER_RPL_SLAVE_ERROR_RETRYING` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010556`; Symbol: `ER_RPL_REPLICA_ERROR_RETRYING`; SQLSTATE: `HY000`  
  
Message: Error on %s: %d %s, will retry in %d secs  
  
`ER_RPL_REPLICA_ERROR_RETRYING` was added in 8.0.33.
  - Error number: `MY-010557`; Symbol: `ER_RPL_SLAVE_ERROR_READING_FROM_SERVER`; SQLSTATE: `HY000`  
  
Message: Error reading packet from server%s: %s (server\_errno=%d)  
  
`ER_RPL_SLAVE_ERROR_READING_FROM_SERVER` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010557`; Symbol: `ER_RPL_REPLICA_ERROR_READING_FROM_SERVER`; SQLSTATE: `HY000`  
  
Message: Error reading packet from server%s: %s (server\_errno=%d)  
  
`ER_RPL_REPLICA_ERROR_READING_FROM_SERVER` was added in 8.0.33.
  - Error number: `MY-010558`; Symbol: `ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER`; SQLSTATE: `HY000`  
  
Message: Slave%s: received end packet from server due to dump thread being killed on master. Dump threads are killed for example during master shutdown, explicitly by a user, or when the master receives a binlog send request from a duplicate server UUID <%s> : Error %s  
  
`ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010558`; Symbol: `ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE`; SQLSTATE: `HY000`  
  
Message: Replica%s: received end packet from server due to dump thread being killed on source. Dump threads are killed for example during source shutdown, explicitly by a user, or when the source receives a binlog send request from a duplicate server UUID <%s> : Error %s  
  
`ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE` was added in 8.0.33.
  - Error number: `MY-010559`; Symbol: `ER_RPL_MTS_STATISTICS`; SQLSTATE: `HY000`  
  
Message: Multi-threaded slave statistics%s: seconds elapsed = %lu; events assigned = %llu; worker queues filled over overrun level = %lu; waited due a Worker queue full = %lu; waited due the total size = %lu; waited at clock conflicts = %llu waited (count) when Workers occupied = %lu waited when Workers occupied = %llu  
  
`ER_RPL_MTS_STATISTICS` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010559`; Symbol: `ER_RPL_MTA_STATISTICS`; SQLSTATE: `HY000`  
  
Message: Multi-threaded replica statistics%s: seconds elapsed = %lu; events assigned = %llu; worker queues filled over overrun level = %lu; waited due a Worker queue full = %lu; waited due the total size =

---

%lu; waited at clock conflicts = %llu waited (count) when Workers occupied = %lu waited when Workers occupied = %llu

[ER\\_RPL\\_MTA\\_STATISTICS](#) was added in 8.0.33.

- Error number: [MY-010560](#); Symbol: [ER\\_RPL\\_MTS\\_RECOVERY\\_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Slave%s: MTS Recovery has completed at relay log %s, position %llu master log %s, position %llu.

[ER\\_RPL\\_MTS\\_RECOVERY\\_COMPLETE](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010560](#); Symbol: [ER\\_RPL\\_MTA\\_RECOVERY\\_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Replica%s: MTA Recovery has completed at relay log %s, position %llu source log %s, position %llu.

[ER\\_RPL\\_MTA\\_RECOVERY\\_COMPLETE](#) was added in 8.0.33.

- Error number: [MY-010561](#); Symbol: [ER\\_RPL\\_SLAVE\\_CANT\\_INIT\\_RELAY\\_LOG\\_POSITION](#); SQLSTATE: [HY000](#)

Message: Error initializing relay log position%s: %s

[ER\\_RPL\\_SLAVE\\_CANT\\_INIT\\_RELAY\\_LOG\\_POSITION](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010561](#); Symbol: [ER\\_RPL\\_REPLICA\\_CANT\\_INIT\\_RELAY\\_LOG\\_POSITION](#); SQLSTATE: [HY000](#)

Message: Error initializing relay log position%s: %s

[ER\\_RPL\\_REPLICA\\_CANT\\_INIT\\_RELAY\\_LOG\\_POSITION](#) was added in 8.0.33.

- Error number: [MY-010562](#); Symbol: [ER\\_RPL\\_SLAVE\\_CONNECTED\\_TO\\_MASTER\\_REPLICATION\\_STARTED](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread%s: connected to master '%s@%s:%d', replication started in log '%s' at position %s

[ER\\_RPL\\_SLAVE\\_CONNECTED\\_TO\\_MASTER\\_REPLICATION\\_STARTED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010563](#); Symbol: [ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_KILLED](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread%s killed while connecting to master

[ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_KILLED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010563](#); Symbol: [ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_KILLED](#); SQLSTATE: [HY000](#)

Message: Replica I/O thread%s killed while connecting to source

[ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_KILLED](#) was added in 8.0.33.

- Error number: [MY-010564](#); Symbol: [ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_CANT\\_REGISTER\\_ON\\_MASTER](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread couldn't register on master

---

`ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MASTER` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010564`; Symbol: `ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOURCE`; SQLSTATE: `HY000`

Message: Replica I/O thread couldn't register on source

`ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOURCE` was added in 8.0.33.

- Error number: `MY-010565`; Symbol: `ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD`; SQLSTATE: `HY000`

Message: Forcing to reconnect slave I/O thread%s

`ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010565`; Symbol: `ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD`; SQLSTATE: `HY000`

Message: Forcing to reconnect replica I/O thread%s

`ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD` was added in 8.0.33.

- Error number: `MY-010566`; Symbol: `ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP`; SQLSTATE: `HY000`

Message: Failed on request\_dump() %s

`ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010566`; Symbol: `ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP`; SQLSTATE: `HY000`

Message: Failed on request\_dump() %s

`ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP` was added in 8.0.33.

- Error number: `MY-010567`; Symbol: `ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWED_PACKET`; SQLSTATE: `HY000`

Message: Log entry on master is longer than slave\_max\_allowed\_packet (%lu) on slave. If the entry is correct, restart the server with a higher value of slave\_max\_allowed\_packet

`ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWED_PACKET` was added in 8.0.2, removed after 8.0.25.

- Error number: `MY-010567`; Symbol: `ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET`; SQLSTATE: `HY000`

Message: Log entry on source is longer than replica\_max\_allowed\_packet (%lu) on replica. If the entry is correct, restart the server with a higher value of replica\_max\_allowed\_packet

`ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET` was added in 8.0.26.

- Error number: `MY-010568`; Symbol: `ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM`; SQLSTATE: `HY000`

Message: Stopping slave I/O thread due to out-of-memory error from master

---

`ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010568`; Symbol: `ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM`; SQLSTATE: `HY000`

Message: Stopping replica I/O thread due to out-of-memory error from source

`ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM` was added in 8.0.33.

- Error number: `MY-010569`; Symbol: `ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE`; SQLSTATE: `HY000`

Message: Slave I/O thread aborted while waiting for relay log space

`ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010569`; Symbol: `ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE`; SQLSTATE: `HY000`

Message: Replica I/O thread aborted while waiting for relay log space

`ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE` was added in 8.0.33.

- Error number: `MY-010570`; Symbol: `ER_RPL_SLAVE_IO_THREAD_EXITING`; SQLSTATE: `HY000`

Message: Slave I/O thread exiting%s, read up to log '%s', position %s

`ER_RPL_SLAVE_IO_THREAD_EXITING` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010570`; Symbol: `ER_RPL_REPLICA_IO_THREAD_EXITING`; SQLSTATE: `HY000`

Message: Replica I/O thread exiting%s, read up to log '%s', position %s

`ER_RPL_REPLICA_IO_THREAD_EXITING` was added in 8.0.33.

- Error number: `MY-010571`; Symbol: `ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER`; SQLSTATE: `HY000`

Message: Failed during slave worker initialization%s

`ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010571`; Symbol: `ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER`; SQLSTATE: `HY000`

Message: Failed during replica worker initialization%s

`ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER` was added in 8.0.33.

- Error number: `MY-010572`; Symbol: `ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO_FOR_WORKER`; SQLSTATE: `HY000`

Message: Slave: MTS group recovery relay log info based on Worker-Id %lu, group\_relay\_log\_name %s, group\_relay\_log\_pos %llu group\_master\_log\_name %s, group\_master\_log\_pos %llu

`ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO_FOR_WORKER` was added in 8.0.2, removed after 8.0.32.

- 
- Error number: [MY-010572](#); Symbol: [ER\\_RPL\\_MTA\\_GROUP\\_RECOVERY\\_APPLIER\\_METADATA\\_FOR\\_WORKER](#); SQLSTATE: [HY000](#)  
  
Message: Replica: MTA group recovery applier metadata based on Worker-Id %lu, group\_relay\_log\_name %s, group\_relay\_log\_pos %llu group\_source\_log\_name %s, group\_source\_log\_pos %llu  
  
[ER\\_RPL\\_MTA\\_GROUP\\_RECOVERY\\_APPLIER\\_METADATA\\_FOR\\_WORKER](#) was added in 8.0.33.
  - Error number: [MY-010573](#); Symbol: [ER\\_RPL\\_ERROR\\_LOOKING\\_FOR\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: Error looking for %s.  
  
[ER\\_RPL\\_ERROR\\_LOOKING\\_FOR\\_LOG](#) was added in 8.0.2.
  - Error number: [MY-010574](#); Symbol: [ER\\_RPL\\_MTS\\_GROUP\\_RECOVERY\\_RELAY\\_LOG\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Slave: MTS group recovery relay log info group\_master\_log\_name %s, event\_master\_log\_pos %llu.  
  
[ER\\_RPL\\_MTS\\_GROUP\\_RECOVERY\\_RELAY\\_LOG\\_INFO](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010574](#); Symbol: [ER\\_RPL\\_MTA\\_GROUP\\_RECOVERY\\_APPLIER\\_METADATA](#); SQLSTATE: [HY000](#)  
  
Message: Replica: MTA group recovery applier metadata group\_source\_log\_name %s, event\_source\_log\_pos %llu.  
  
[ER\\_RPL\\_MTA\\_GROUP\\_RECOVERY\\_APPLIER\\_METADATA](#) was added in 8.0.33.
  - Error number: [MY-010575](#); Symbol: [ER\\_RPL\\_CANT\\_FIND\\_FOLLOWUP\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: Error looking for file after %s.  
  
[ER\\_RPL\\_CANT\\_FIND\\_FOLLOWUP\\_FILE](#) was added in 8.0.2.
  - Error number: [MY-010576](#); Symbol: [ER\\_RPL\\_MTS\\_CHECKPOINT\\_PERIOD\\_DIFFERS\\_FROM\\_CNT](#); SQLSTATE: [HY000](#)  
  
Message: This an error cnt != mta\_checkpoint\_period  
  
[ER\\_RPL\\_MTS\\_CHECKPOINT\\_PERIOD\\_DIFFERS\\_FROM\\_CNT](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010576](#); Symbol: [ER\\_RPL\\_MTA\\_CHECKPOINT\\_PERIOD\\_DIFFERS\\_FROM\\_CNT](#); SQLSTATE: [HY000](#)  
  
Message: This an error cnt != mta\_checkpoint\_period  
  
[ER\\_RPL\\_MTA\\_CHECKPOINT\\_PERIOD\\_DIFFERS\\_FROM\\_CNT](#) was added in 8.0.33.
  - Error number: [MY-010577](#); Symbol: [ER\\_RPL\\_SLAVE\\_WORKER\\_THREAD\\_CREATION\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Failed during slave worker thread creation%s  
  
[ER\\_RPL\\_SLAVE\\_WORKER\\_THREAD\\_CREATION\\_FAILED](#) was added in 8.0.2, removed after 8.0.32.



- 
- Error number: [MY-010577](#); Symbol: [ER\\_RPL\\_REPLICA\\_WORKER\\_THREAD\\_CREATION\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Failed during replica worker thread creation%s  
  
[ER\\_RPL\\_REPLICA\\_WORKER\\_THREAD\\_CREATION\\_FAILED](#) was added in 8.0.33.
  - Error number: [MY-010578](#); Symbol: [ER\\_RPL\\_SLAVE\\_WORKER\\_THREAD\\_CREATION\\_FAILED\\_WITH\\_ERRNO](#); SQLSTATE: [HY000](#)  
  
Message: Failed during slave worker thread creation%s (errno= %d)  
  
[ER\\_RPL\\_SLAVE\\_WORKER\\_THREAD\\_CREATION\\_FAILED\\_WITH\\_ERRNO](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010578](#); Symbol: [ER\\_RPL\\_REPLICA\\_WORKER\\_THREAD\\_CREATION\\_FAILED\\_WITH\\_ERRNO](#); SQLSTATE: [HY000](#)  
  
Message: Failed during replica worker thread creation%s (errno= %d)  
  
[ER\\_RPL\\_REPLICA\\_WORKER\\_THREAD\\_CREATION\\_FAILED\\_WITH\\_ERRNO](#) was added in 8.0.33.
  - Error number: [MY-010579](#); Symbol: [ER\\_RPL\\_SLAVE\\_FAILED\\_TO\\_INIT\\_PARTITIONS\\_HASH](#); SQLSTATE: [HY000](#)  
  
Message: Failed to init partitions hash  
  
[ER\\_RPL\\_SLAVE\\_FAILED\\_TO\\_INIT\\_PARTITIONS\\_HASH](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010579](#); Symbol: [ER\\_RPL\\_REPLICA\\_FAILED\\_TO\\_INIT\\_PARTITIONS\\_HASH](#); SQLSTATE: [HY000](#)  
  
Message: Failed to init partitions hash  
  
[ER\\_RPL\\_REPLICA\\_FAILED\\_TO\\_INIT\\_PARTITIONS\\_HASH](#) was added in 8.0.33.
  - Error number: [MY-010580](#); Symbol: [ER\\_RPL\\_SLAVE\\_NDB\\_TABLES\\_NOT\\_AVAILABLE](#); SQLSTATE: [HY000](#)  
  
Message: Slave SQL thread : NDB : Tables not available after %lu seconds. Consider increasing --ndb-wait-setup value  
  
[ER\\_RPL\\_SLAVE\\_NDB\\_TABLES\\_NOT\\_AVAILABLE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010581](#); Symbol: [ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_STARTING](#); SQLSTATE: [HY000](#)  
  
Message: Slave SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s  
  
[ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_STARTING](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010581](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STARTING](#); SQLSTATE: [HY000](#)  
  
Message: Replica SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s  
  
[ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STARTING](#) was added in 8.0.33.
  - Error number: [MY-010582](#); Symbol: [ER\\_RPL\\_SLAVE\\_SKIP\\_COUNTER\\_EXECUTED](#); SQLSTATE: [HY000](#)

---

Message: 'SQL\_REPLICA\_SKIP\_COUNTER=%ld' executed at relay\_log\_file='%s', relay\_log\_pos='%ld', master\_log\_name='%s', master\_log\_pos='%ld' and new position at relay\_log\_file='%s', relay\_log\_pos='%ld', master\_log\_name='%s', master\_log\_pos='%ld'

[ER\\_RPL\\_SLAVE\\_SKIP\\_COUNTER\\_EXECUTED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010582](#); Symbol: [ER\\_RPL\\_REPLICA\\_SKIP\\_COUNTER\\_EXECUTED](#); SQLSTATE: [HY000](#)

Message: 'SQL\_REPLICA\_SKIP\_COUNTER=%ld' executed at relay\_log\_file='%s', relay\_log\_pos='%ld', source\_log\_name='%s', source\_log\_pos='%ld' and new position at relay\_log\_file='%s', relay\_log\_pos='%ld', source\_log\_name='%s', source\_log\_pos='%ld'

[ER\\_RPL\\_REPLICA\\_SKIP\\_COUNTER\\_EXECUTED](#) was added in 8.0.33.

- Error number: [MY-010583](#); Symbol: [ER\\_RPL\\_SLAVE\\_ADDITIONAL\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)

Message: Slave (additional info): %s Error\_code: MY-%06d

[ER\\_RPL\\_SLAVE\\_ADDITIONAL\\_ERROR\\_INFO\\_FROM\\_DA](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010583](#); Symbol: [ER\\_RPL\\_REPLICA\\_ADDITIONAL\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)

Message: Replica (additional info): %s Error\_code: MY-%06d

[ER\\_RPL\\_REPLICA\\_ADDITIONAL\\_ERROR\\_INFO\\_FROM\\_DA](#) was added in 8.0.33.

- Error number: [MY-010584](#); Symbol: [ER\\_RPL\\_SLAVE\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)

Message: Slave: %s Error\_code: MY-%06d

[ER\\_RPL\\_SLAVE\\_ERROR\\_INFO\\_FROM\\_DA](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010584](#); Symbol: [ER\\_RPL\\_REPLICA\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)

Message: Replica: %s Error\_code: MY-%06d

[ER\\_RPL\\_REPLICA\\_ERROR\\_INFO\\_FROM\\_DA](#) was added in 8.0.33.

- Error number: [MY-010585](#); Symbol: [ER\\_RPL\\_SLAVE\\_ERROR\\_LOADING\\_USER\\_DEFINED\\_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Error loading user-defined library, slave SQL thread aborted. Install the missing library, and restart the slave SQL thread with "SLAVE START". We stopped at log '%s' position %s

[ER\\_RPL\\_SLAVE\\_ERROR\\_LOADING\\_USER\\_DEFINED\\_LIBRARY](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010585](#); Symbol: [ER\\_RPL\\_REPLICA\\_ERROR\\_LOADING\\_USER\\_DEFINED\\_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Error loading user-defined library, replica SQL thread aborted. Install the missing library, and restart the replica SQL thread with "START REPLICA". We stopped at log '%s' position %s

[ER\\_RPL\\_REPLICA\\_ERROR\\_LOADING\\_USER\\_DEFINED\\_LIBRARY](#) was added in 8.0.33.

- 
- Error number: [MY-010586](#); Symbol: [ER\\_RPL\\_SLAVE\\_ERROR\\_RUNNING\\_QUERY](#); SQLSTATE: [HY000](#)  
Message: Error running query, slave SQL thread aborted. Fix the problem, and restart the slave SQL thread with "SLAVE START". We stopped at log '%s' position %s  
[ER\\_RPL\\_SLAVE\\_ERROR\\_RUNNING\\_QUERY](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010586](#); Symbol: [ER\\_RPL\\_REPLICA\\_ERROR\\_RUNNING\\_QUERY](#); SQLSTATE: [HY000](#)  
Message: Error running query, replica SQL thread aborted. Fix the problem, and restart the replica SQL thread with "START REPLICA". We stopped at log '%s' position %s  
[ER\\_RPL\\_REPLICA\\_ERROR\\_RUNNING\\_QUERY](#) was added in 8.0.33.
  - Error number: [MY-010587](#); Symbol: [ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_EXITING](#); SQLSTATE: [HY000](#)  
Message: Slave SQL thread%s exiting, replication stopped in log '%s' at position %s  
[ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_EXITING](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010587](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_EXITING](#); SQLSTATE: [HY000](#)  
Message: Replica SQL thread%s exiting, replication stopped in log '%s' at position %s  
[ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_EXITING](#) was added in 8.0.33.
  - Error number: [MY-010588](#); Symbol: [ER\\_RPL\\_SLAVE\\_READ\\_INVALID\\_EVENT\\_FROM\\_MASTER](#); SQLSTATE: [HY000](#)  
Message: Read invalid event from master: '%s', master could be corrupt but a more likely cause of this is a bug  
[ER\\_RPL\\_SLAVE\\_READ\\_INVALID\\_EVENT\\_FROM\\_MASTER](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010588](#); Symbol: [ER\\_RPL\\_REPLICA\\_READ\\_INVALID\\_EVENT\\_FROM\\_SOURCE](#); SQLSTATE: [HY000](#)  
Message: Read invalid event from source: '%s', source could be corrupt but a more likely cause of this is a bug  
[ER\\_RPL\\_REPLICA\\_READ\\_INVALID\\_EVENT\\_FROM\\_SOURCE](#) was added in 8.0.33.
  - Error number: [MY-010589](#); Symbol: [ER\\_RPL\\_SLAVE\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_CONFIGURATION](#); SQLSTATE: [HY000](#)  
Message: The queue event failed for channel '%s' as its configuration is invalid.  
[ER\\_RPL\\_SLAVE\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_CONFIGURATION](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010589](#); Symbol: [ER\\_RPL\\_REPLICA\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_CONFIGURATION](#); SQLSTATE: [HY000](#)  
Message: The queue event failed for channel '%s' as its configuration is invalid.  
[ER\\_RPL\\_REPLICA\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_CONFIGURATION](#) was added in 8.0.33.
  - Error number: [MY-010590](#); Symbol: [ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#); SQLSTATE: [HY000](#)

---

Message: An unexpected event sequence was detected by the IO thread while queuing the event received from master '%s' binary log file, at position %llu.

[ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010590](#); Symbol:

[ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#); SQLSTATE: [HY000](#)

Message: An unexpected event sequence was detected by the IO thread while queuing the event received from source '%s' binary log file, at position %llu.

[ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#) was added in 8.0.33.

- Error number: [MY-010591](#); Symbol: [ER\\_RPL\\_SLAVE\\_CANT\\_USE\\_CHARSET](#); SQLSTATE: [HY000](#)

Message: '%s' can not be used as client character set. '%s' will be used as default client character set while connecting to master.

[ER\\_RPL\\_SLAVE\\_CANT\\_USE\\_CHARSET](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010591](#); Symbol: [ER\\_RPL\\_REPLICA\\_CANT\\_USE\\_CHARSET](#); SQLSTATE: [HY000](#)

Message: '%s' can not be used as client character set. '%s' will be used as default client character set while connecting to source.

[ER\\_RPL\\_REPLICA\\_CANT\\_USE\\_CHARSET](#) was added in 8.0.33.

- Error number: [MY-010592](#); Symbol:

[ER\\_RPL\\_SLAVE\\_CONNECTED\\_TO\\_MASTER\\_REPLICATION\\_RESUMED](#); SQLSTATE: [HY000](#)

Message: Slave%s: connected to master '%s@%s:%d', replication resumed in log '%s' at position %s

[ER\\_RPL\\_SLAVE\\_CONNECTED\\_TO\\_MASTER\\_REPLICATION\\_RESUMED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010592](#); Symbol:

[ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_REPLICATION\\_RESUMED](#); SQLSTATE: [HY000](#)

Message: Replica%s: connected to source '%s@%s:%d', replication resumed in log '%s' at position %s

[ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_REPLICATION\\_RESUMED](#) was added in 8.0.33.

- Error number: [MY-010593](#); Symbol: [ER\\_RPL\\_SLAVE\\_NEXT\\_LOG\\_IS\\_ACTIVE](#); SQLSTATE: [HY000](#)

Message: next log '%s' is active

[ER\\_RPL\\_SLAVE\\_NEXT\\_LOG\\_IS\\_ACTIVE](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010593](#); Symbol: [ER\\_RPL\\_REPLICA\\_NEXT\\_LOG\\_IS\\_ACTIVE](#); SQLSTATE: [HY000](#)

Message: next log '%s' is active

[ER\\_RPL\\_REPLICA\\_NEXT\\_LOG\\_IS\\_ACTIVE](#) was added in 8.0.33.

- Error number: [MY-010594](#); Symbol: [ER\\_RPL\\_SLAVE\\_NEXT\\_LOG\\_IS\\_INACTIVE](#); SQLSTATE: [HY000](#)

Message: next log '%s' is not active

---

`ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010594`; Symbol: `ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE`; SQLSTATE: `HY000`

Message: next log '%s' is not active

`ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE` was added in 8.0.33.

- Error number: `MY-010595`; Symbol: `ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_EVENT`; SQLSTATE: `HY000`

Message: Slave SQL thread%s: I/O error reading event (errno: %d cur\_log->error: %d)

`ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_EVENT` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010595`; Symbol: `ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT`; SQLSTATE: `HY000`

Message: Replica SQL thread%s: I/O error reading event (errno: %d cur\_log->error: %d)

`ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT` was added in 8.0.33.

- Error number: `MY-010596`; Symbol: `ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS`; SQLSTATE: `HY000`

Message: Error reading relay log event%s: %s

`ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010596`; Symbol: `ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS`; SQLSTATE: `HY000`

Message: Error reading relay log event%s: %s

`ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS` was added in 8.0.33.

- Error number: `MY-010597`; Symbol: `ER_SLAVE_CHANGE_MASTER_TO_EXECUTED`; SQLSTATE: `HY000`

Message: 'CHANGE MASTER TO%s executed'. Previous state master\_host='%s', master\_port=%u, master\_log\_file='%s', master\_log\_pos= %ld, master\_bind='%s'. New state master\_host='%s', master\_port= %u, master\_log\_file='%s', master\_log\_pos= %ld, master\_bind='%s'.

`ER_SLAVE_CHANGE_MASTER_TO_EXECUTED` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010597`; Symbol: `ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED`; SQLSTATE: `HY000`

Message: 'CHANGE REPLICATION SOURCE TO%s executed'. Previous state source\_host='%s', source\_port= %u, source\_log\_file='%s', source\_log\_pos= %ld, source\_bind='%s'. New state source\_host='%s', source\_port= %u, source\_log\_file='%s', source\_log\_pos= %ld, source\_bind='%s'.

`ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED` was added in 8.0.33.

- 
- Error number: [MY-010598](#); Symbol: [ER\\_RPL\\_SLAVE\\_NEW\\_MASTER\\_INFO\\_NEEDS\\_REPOS\\_TYPE\\_OTHER\\_THAN\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: Slave: Cannot create new master info structure when repositories are of type FILE. Convert slave repositories to TABLE to replicate from multiple sources.  
  
[ER\\_RPL\\_SLAVE\\_NEW\\_MASTER\\_INFO\\_NEEDS\\_REPOS\\_TYPE\\_OTHER\\_THAN\\_FILE](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010598](#); Symbol: [ER\\_RPL\\_REPLICA\\_NEW\\_C\\_M\\_NEEDS\\_REPOS\\_TYPE\\_OTHER\\_THAN\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: Replica: Cannot create new connection metadata structure when repositories are of type FILE. Convert replica repositories to TABLE to replicate from multiple sources.  
  
[ER\\_RPL\\_REPLICA\\_NEW\\_C\\_M\\_NEEDS\\_REPOS\\_TYPE\\_OTHER\\_THAN\\_FILE](#) was added in 8.0.33.
  - Error number: [MY-010599](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_STAT\\_LOG\\_IN\\_INDEX](#); SQLSTATE: [HY000](#)  
  
Message: log %s listed in the index, but failed to stat.  
  
[ER\\_RPL\\_FAILED\\_TO\\_STAT\\_LOG\\_IN\\_INDEX](#) was added in 8.0.2.
  - Error number: [MY-010600](#); Symbol: [ER\\_RPL\\_LOG\\_NOT\\_FOUND\\_WHILE\\_COUNTING\\_RELAY\\_LOG\\_SPACE](#); SQLSTATE: [HY000](#)  
  
Message: Could not find first log while counting relay log space.  
  
[ER\\_RPL\\_LOG\\_NOT\\_FOUND\\_WHILE\\_COUNTING\\_RELAY\\_LOG\\_SPACE](#) was added in 8.0.2.
  - Error number: [MY-010601](#); Symbol: [ER\\_SLAVE\\_CANT\\_USE\\_TEMPDIR](#); SQLSTATE: [HY000](#)  
  
Message: Unable to use slave's temporary directory '%s'.  
  
[ER\\_SLAVE\\_CANT\\_USE\\_TEMPDIR](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010601](#); Symbol: [ER\\_REPLICA\\_CANT\\_USE\\_TEMPDIR](#); SQLSTATE: [HY000](#)  
  
Message: Unable to use replica's temporary directory '%s'.  
  
[ER\\_REPLICA\\_CANT\\_USE\\_TEMPDIR](#) was added in 8.0.33.
  - Error number: [MY-010602](#); Symbol: [ER\\_RPL\\_RELAY\\_LOG\\_NEEDS\\_FILE\\_NOT\\_DIRECTORY](#); SQLSTATE: [HY000](#)  
  
Message: Path '%s' is a directory name, please specify a file name for --relay-log option.  
  
[ER\\_RPL\\_RELAY\\_LOG\\_NEEDS\\_FILE\\_NOT\\_DIRECTORY](#) was added in 8.0.2.
  - Error number: [MY-010603](#); Symbol: [ER\\_RPL\\_RELAY\\_LOG\\_INDEX\\_NEEDS\\_FILE\\_NOT\\_DIRECTORY](#); SQLSTATE: [HY000](#)  
  
Message: Path '%s' is a directory name, please specify a file name for --relay-log-index option.  
  
[ER\\_RPL\\_RELAY\\_LOG\\_INDEX\\_NEEDS\\_FILE\\_NOT\\_DIRECTORY](#) was added in 8.0.2.

- 
- Error number: [MY-010604](#); Symbol: [ER\\_RPL\\_PLEASE\\_USE\\_OPTION\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: Neither --relay-log nor --relay-log-index were used; so replication may break when this MySQL server acts as a replica and has his hostname changed!! Please use '--relay-log=%s' to avoid this problem.  
  
[ER\\_RPL\\_PLEASE\\_USE\\_OPTION\\_RELAY\\_LOG](#) was added in 8.0.2.
  - Error number: [MY-010605](#); Symbol: [ER\\_RPL\\_OPEN\\_INDEX\\_FILE\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Failed in open\_index\_file() called from Relay\_log\_info::rli\_init\_info().  
  
[ER\\_RPL\\_OPEN\\_INDEX\\_FILE\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010606](#); Symbol: [ER\\_RPL\\_CANT\\_INITIALIZE\\_GTID\\_SETS\\_IN\\_RLI\\_INIT\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Failed in init\_gtid\_sets() called from Relay\_log\_info::rli\_init\_info().  
  
[ER\\_RPL\\_CANT\\_INITIALIZE\\_GTID\\_SETS\\_IN\\_RLI\\_INIT\\_INFO](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010606](#); Symbol: [ER\\_RPL\\_CANT\\_INITIALIZE\\_GTID\\_SETS\\_IN\\_AM\\_INIT\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Failed in init\_gtid\_sets() called from Relay\_log\_info::rli\_init\_info().  
  
[ER\\_RPL\\_CANT\\_INITIALIZE\\_GTID\\_SETS\\_IN\\_AM\\_INIT\\_INFO](#) was added in 8.0.33.
  - Error number: [MY-010607](#); Symbol: [ER\\_RPL\\_CANT\\_OPEN\\_LOG\\_IN\\_RLI\\_INIT\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Failed in open\_log() called from Relay\_log\_info::rli\_init\_info().  
  
[ER\\_RPL\\_CANT\\_OPEN\\_LOG\\_IN\\_RLI\\_INIT\\_INFO](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010607](#); Symbol: [ER\\_RPL\\_CANT\\_OPEN\\_LOG\\_IN\\_AM\\_INIT\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Failed in open\_log() called from Relay\_log\_info::rli\_init\_info().  
  
[ER\\_RPL\\_CANT\\_OPEN\\_LOG\\_IN\\_AM\\_INIT\\_INFO](#) was added in 8.0.33.
  - Error number: [MY-010608](#); Symbol: [ER\\_RPL\\_ERROR\\_WRITING\\_RELAY\\_LOG\\_CONFIGURATION](#); SQLSTATE: [HY000](#)  
  
Message: Error writing relay log configuration.  
  
[ER\\_RPL\\_ERROR\\_WRITING\\_RELAY\\_LOG\\_CONFIGURATION](#) was added in 8.0.2.
  - Error number: [MY-010609](#); Symbol: [ER\\_NDB\\_OOM\\_GET\\_NDB\\_BLOBS\\_VALUE](#); SQLSTATE: [HY000](#)  
  
Message: get\_ndb\_blobs\_value: my\_malloc(%u) failed  
  
[ER\\_NDB\\_OOM\\_GET\\_NDB\\_BLOBS\\_VALUE](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: [MY-010610](#); Symbol: [ER\\_NDB\\_THREAD\\_TIMED\\_OUT](#); SQLSTATE: [HY000](#)  
Message: NDB: Thread id %u timed out (30s) waiting for epoch %u/%u to be handled. Progress : %u/%u  
-> %u/%u.  
[ER\\_NDB\\_THREAD\\_TIMED\\_OUT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010611](#); Symbol: [ER\\_NDB\\_TABLE\\_IS\\_NOT\\_DISTRIBUTED](#); SQLSTATE: [HY000](#)  
Message: NDB: Inconsistency detected in distributed privilege tables. Table '%s.%s' is not distributed  
[ER\\_NDB\\_TABLE\\_IS\\_NOT\\_DISTRIBUTED](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010612](#); Symbol: [ER\\_NDB\\_CREATING\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: NDB: Creating %s.%s  
[ER\\_NDB\\_CREATING\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010613](#); Symbol: [ER\\_NDB\\_FLUSHING\\_TABLE\\_INFO](#); SQLSTATE: [HY000](#)  
Message: NDB: Flushing %s.%s  
[ER\\_NDB\\_FLUSHING\\_TABLE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010614](#); Symbol: [ER\\_NDB\\_CLEANING\\_STRAY\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: NDB: Cleaning stray tables from database '%s'  
[ER\\_NDB\\_CLEANING\\_STRAY\\_TABLES](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010615](#); Symbol: [ER\\_NDB\\_DISCOVERED\\_MISSING\\_DB](#); SQLSTATE: [HY000](#)  
Message: NDB: Discovered missing database '%s'  
[ER\\_NDB\\_DISCOVERED\\_MISSING\\_DB](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010616](#); Symbol: [ER\\_NDB\\_DISCOVERED\\_REMAINING\\_DB](#); SQLSTATE: [HY000](#)  
Message: NDB: Discovered remaining database '%s'  
[ER\\_NDB\\_DISCOVERED\\_REMAINING\\_DB](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010617](#); Symbol: [ER\\_NDB\\_CLUSTER\\_FIND\\_ALL\\_DBS\\_RETRY](#); SQLSTATE: [HY000](#)  
Message: NDB: ndbcluster\_find\_all\_databases retry: %u - %s  
[ER\\_NDB\\_CLUSTER\\_FIND\\_ALL\\_DBS\\_RETRY](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010618](#); Symbol: [ER\\_NDB\\_CLUSTER\\_FIND\\_ALL\\_DBS\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: NDB: ndbcluster\_find\_all\_databases fail: %u - %s  
[ER\\_NDB\\_CLUSTER\\_FIND\\_ALL\\_DBS\\_FAIL](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010619](#); Symbol: [ER\\_NDB\\_SKIPPING\\_SETUP\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: NDB: skipping setup table %s.%s, in state %d  
[ER\\_NDB\\_SKIPPING\\_SETUP\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.



- 
- Error number: [MY-010620](#); Symbol: [ER\\_NDB\\_FAILED\\_TO\\_SET\\_UP\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: NDB: failed to setup table %s.%s, error: %d, %s  
[ER\\_NDB\\_FAILED\\_TO\\_SET\\_UP\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010621](#); Symbol: [ER\\_NDB\\_MISSING\\_FRM\\_DISCOVERING](#); SQLSTATE: [HY000](#)  
Message: NDB: missing frm for %s.%s, discovering...  
[ER\\_NDB\\_MISSING\\_FRM\\_DISCOVERING](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010622](#); Symbol: [ER\\_NDB\\_MISMATCH\\_IN\\_FRM\\_DISCOVERING](#); SQLSTATE: [HY000](#)  
Message: NDB: mismatch in frm for %s.%s, discovering...  
[ER\\_NDB\\_MISMATCH\\_IN\\_FRM\\_DISCOVERING](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010623](#); Symbol: [ER\\_NDB\\_BINLOG\\_CLEANING\\_UP\\_SETUP\\_LEFTOVERS](#); SQLSTATE: [HY000](#)  
Message: ndb\_binlog\_setup: Clean up leftovers  
[ER\\_NDB\\_BINLOG\\_CLEANING\\_UP\\_SETUP\\_LEFTOVERS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010624](#); Symbol: [ER\\_NDB\\_WAITING\\_INFO](#); SQLSTATE: [HY000](#)  
Message: NDB %s: waiting max %u sec for %s %s. epochs: (%u/%u,%u/%u,%u/%u) injector proc\_info: %s  
[ER\\_NDB\\_WAITING\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010625](#); Symbol: [ER\\_NDB\\_WAITING\\_INFO\\_WITH\\_MAP](#); SQLSTATE: [HY000](#)  
Message: NDB %s: waiting max %u sec for %s %s. epochs: (%u/%u,%u/%u,%u/%u) injector proc\_info: %s map: %x%08x  
[ER\\_NDB\\_WAITING\\_INFO\\_WITH\\_MAP](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010626](#); Symbol: [ER\\_NDB\\_TIMEOUT\\_WHILE\\_DISTRIBUTING](#); SQLSTATE: [HY000](#)  
Message: NDB %s: distributing %s timed out. Ignoring...  
[ER\\_NDB\\_TIMEOUT\\_WHILE\\_DISTRIBUTING](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010627](#); Symbol: [ER\\_NDB\\_NOT\\_WAITING\\_FOR\\_DISTRIBUTING](#); SQLSTATE: [HY000](#)  
Message: NDB %s: not waiting for distributing %s  
[ER\\_NDB\\_NOT\\_WAITING\\_FOR\\_DISTRIBUTING](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010628](#); Symbol: [ER\\_NDB\\_DISTRIBUTED\\_INFO](#); SQLSTATE: [HY000](#)  
Message: NDB: distributed %s.%s(%u/%u) type: %s(%u) query: '%s' to %x%08x  
[ER\\_NDB\\_DISTRIBUTED\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010629](#); Symbol: [ER\\_NDB\\_DISTRIBUTION\\_COMPLETE](#); SQLSTATE: [HY000](#)

---

Message: NDB: distribution of %s.%s(%u/%u) type: %s(%u) query: \'%s\' - complete!

[ER\\_NDB\\_DISTRIBUTION\\_COMPLETE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010630](#); Symbol: [ER\\_NDB\\_SCHEMA\\_DISTRIBUTION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: NDB Schema dist: Data node: %d failed, subscriber bitmask %x%08x

[ER\\_NDB\\_SCHEMA\\_DISTRIBUTION\\_FAILED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010631](#); Symbol: [ER\\_NDB\\_SCHEMA\\_DISTRIBUTION\\_REPORTS\\_SUBSCRIBE](#); SQLSTATE: [HY000](#)

Message: NDB Schema dist: Data node: %d reports subscribe from node %d, subscriber bitmask %x%08x

[ER\\_NDB\\_SCHEMA\\_DISTRIBUTION\\_REPORTS\\_SUBSCRIBE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010632](#); Symbol: [ER\\_NDB\\_SCHEMA\\_DISTRIBUTION\\_REPORTS\\_UNSUBSCRIBE](#); SQLSTATE: [HY000](#)

Message: NDB Schema dist: Data node: %d reports unsubscribe from node %d, subscriber bitmask %x%08x

[ER\\_NDB\\_SCHEMA\\_DISTRIBUTION\\_REPORTS\\_UNSUBSCRIBE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010633](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_DISCOVER\\_TABLE\\_FROM\\_SCHEMA\\_EVENT](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Could not discover table '%s.%s' from binlog schema event '%s' from node %d. my\_errno: %d

[ER\\_NDB\\_BINLOG\\_CANT\\_DISCOVER\\_TABLE\\_FROM\\_SCHEMA\\_EVENT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010634](#); Symbol: [ER\\_NDB\\_BINLOG\\_SIGNALLING\\_UNKNOWN\\_VALUE](#); SQLSTATE: [HY000](#)

Message: NDB: unknown value for binlog signalling 0x%X, %s not logged

[ER\\_NDB\\_BINLOG\\_SIGNALLING\\_UNKNOWN\\_VALUE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010635](#); Symbol: [ER\\_NDB\\_BINLOG\\_REPLY\\_TO](#); SQLSTATE: [HY000](#)

Message: NDB: reply to %s.%s(%u/%u) from %s to %x%08x

[ER\\_NDB\\_BINLOG\\_REPLY\\_TO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010636](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_RELEASE\\_SLOCK](#); SQLSTATE: [HY000](#)

Message: NDB: Could not release slock on '%s.%s', Error code: %d Message: %s

[ER\\_NDB\\_BINLOG\\_CANT\\_RELEASE\\_SLOCK](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: [MY-010637](#); Symbol: [ER\\_NDB\\_CANT\\_FIND\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: NDB schema: Could not find table '%s.%s' in NDB  
[ER\\_NDB\\_CANT\\_FIND\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010638](#); Symbol: [ER\\_NDB\\_DISCARDING\\_EVENT\\_NO\\_OBJ](#); SQLSTATE: [HY000](#)  
Message: NDB: Discarding event...no obj: %s (%u/%u)  
[ER\\_NDB\\_DISCARDING\\_EVENT\\_NO\\_OBJ](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010639](#); Symbol: [ER\\_NDB\\_DISCARDING\\_EVENT\\_ID\\_VERSION\\_MISMATCH](#); SQLSTATE: [HY000](#)  
Message: NDB: Discarding event...key: %s non matching id/version [%u/%u] != [%u/%u]  
[ER\\_NDB\\_DISCARDING\\_EVENT\\_ID\\_VERSION\\_MISMATCH](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010640](#); Symbol: [ER\\_NDB\\_CLEAR\\_SLOCK\\_INFO](#); SQLSTATE: [HY000](#)  
Message: NDB: CLEAR\_SLOCK key: %s(%u/%u) %x%08x, from %s to %x%08x  
[ER\\_NDB\\_CLEAR\\_SLOCK\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010641](#); Symbol: [ER\\_NDB\\_BINLOG\\_SKIPPING\\_LOCAL\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Skipping locally defined table '%s.%s' from binlog schema event '%s' from node %d.  
[ER\\_NDB\\_BINLOG\\_SKIPPING\\_LOCAL\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010642](#); Symbol: [ER\\_NDB\\_BINLOG\\_ONLINE\\_ALTER\\_RENAME](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: handling online alter/rename  
[ER\\_NDB\\_BINLOG\\_ONLINE\\_ALTER\\_RENAME](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010643](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_REOPEN\\_SHADOW\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Failed to re-open shadow table %s.%s  
[ER\\_NDB\\_BINLOG\\_CANT\\_REOPEN\\_SHADOW\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010644](#); Symbol: [ER\\_NDB\\_BINLOG\\_ONLINE\\_ALTER\\_RENAME\\_COMPLETE](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: handling online alter/rename done  
[ER\\_NDB\\_BINLOG\\_ONLINE\\_ALTER\\_RENAME\\_COMPLETE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010645](#); Symbol: [ER\\_NDB\\_BINLOG\\_SKIPPING\\_DROP\\_OF\\_LOCAL\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Skipping drop of locally defined table '%s.%s' from binlog schema event '%s' from node %d.  
[ER\\_NDB\\_BINLOG\\_SKIPPING\\_DROP\\_OF\\_LOCAL\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.
-

- 
- Error number: [MY-010646](#); Symbol: [ER\\_NDB\\_BINLOG\\_SKIPPING\\_RENAME\\_OF\\_LOCAL\\_TABLE](#); SQLSTATE: [HY000](#)  
  
Message: NDB Binlog: Skipping renaming locally defined table '%s.%s' from binlog schema event '%s' from node %d.  
  
[ER\\_NDB\\_BINLOG\\_SKIPPING\\_RENAME\\_OF\\_LOCAL\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010647](#); Symbol: [ER\\_NDB\\_BINLOG\\_SKIPPING\\_DROP\\_OF\\_DB\\_CONTAINING\\_LOCAL\\_TABLES](#); SQLSTATE: [HY000](#)  
  
Message: NDB Binlog: Skipping drop database '%s' since it contained local tables binlog schema event '%s' from node %d.  
  
[ER\\_NDB\\_BINLOG\\_SKIPPING\\_DROP\\_OF\\_DB\\_CONTAINING\\_LOCAL\\_TABLES](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010648](#); Symbol: [ER\\_NDB\\_BINLOG\\_GOT\\_DIST\\_PRIV\\_EVENT\\_FLUSHING\\_PRIVILEGES](#); SQLSTATE: [HY000](#)  
  
Message: Got dist\_priv event: %s, flushing privileges  
  
[ER\\_NDB\\_BINLOG\\_GOT\\_DIST\\_PRIV\\_EVENT\\_FLUSHING\\_PRIVILEGES](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010649](#); Symbol: [ER\\_NDB\\_BINLOG\\_GOT\\_SCHEMA\\_EVENT](#); SQLSTATE: [HY000](#)  
  
Message: NDB: got schema event on %s.%s(%u/%u) query: '%s' type: %s(%d) node: %u slock: %x %08x  
  
[ER\\_NDB\\_BINLOG\\_GOT\\_SCHEMA\\_EVENT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010650](#); Symbol: [ER\\_NDB\\_BINLOG\\_SKIPPING\\_OLD\\_SCHEMA\\_OPERATION](#); SQLSTATE: [HY000](#)  
  
Message: NDB schema: Skipping old schema operation(RENAME\_TABLE\_NEW) on %s.%s  
  
[ER\\_NDB\\_BINLOG\\_SKIPPING\\_OLD\\_SCHEMA\\_OPERATION](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010651](#); Symbol: [ER\\_NDB\\_CLUSTER\\_FAILURE](#); SQLSTATE: [HY000](#)  
  
Message: NDB Schema dist: cluster failure at epoch %u/%u.  
  
[ER\\_NDB\\_CLUSTER\\_FAILURE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010652](#); Symbol: [ER\\_NDB\\_TABLES\\_INITIALLY\\_READ\\_ONLY\\_ON\\_RECONNECT](#); SQLSTATE: [HY000](#)  
  
Message: NDB Binlog: ndb tables initially read only on reconnect.  
  
[ER\\_NDB\\_TABLES\\_INITIALLY\\_READ\\_ONLY\\_ON\\_RECONNECT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010653](#); Symbol: [ER\\_NDB\\_IGNOREING\\_UNKNOWN\\_EVENT](#); SQLSTATE: [HY000](#)  
  
Message: NDB Schema dist: unknown event %u, ignoring...  
  
[ER\\_NDB\\_IGNOREING\\_UNKNOWN\\_EVENT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010654](#); Symbol: [ER\\_NDB\\_BINLOG\\_OPENING\\_INDEX](#); SQLSTATE: [HY000](#)

---

Message: NDB Binlog: Opening ndb\_binlog\_index: %d, '%s'

[ER\\_NDB\\_BINLOG\\_OPENING\\_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010655](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_LOCK\\_NDB\\_BINLOG\\_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Unable to lock table ndb\_binlog\_index

[ER\\_NDB\\_BINLOG\\_CANT\\_LOCK\\_NDB\\_BINLOG\\_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010656](#); Symbol: [ER\\_NDB\\_BINLOG\\_INJECTING\\_RANDOM\\_WRITE\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Injecting random write failure

[ER\\_NDB\\_BINLOG\\_INJECTING\\_RANDOM\\_WRITE\\_FAILURE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010657](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_WRITE\\_TO\\_NDB\\_BINLOG\\_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Failed writing to ndb\_binlog\_index for epoch %u/%u orig\_server\_id %u orig\_epoch %u/%u with error %d.

[ER\\_NDB\\_BINLOG\\_CANT\\_WRITE\\_TO\\_NDB\\_BINLOG\\_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010658](#); Symbol: [ER\\_NDB\\_BINLOG\\_WRITING\\_TO\\_NDB\\_BINLOG\\_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Writing row (%s) to ndb\_binlog\_index - %s

[ER\\_NDB\\_BINLOG\\_WRITING\\_TO\\_NDB\\_BINLOG\\_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010659](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_COMMIT\\_TO\\_NDB\\_BINLOG\\_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Failed committing transaction to ndb\_binlog\_index with error %d.

[ER\\_NDB\\_BINLOG\\_CANT\\_COMMIT\\_TO\\_NDB\\_BINLOG\\_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010660](#); Symbol: [ER\\_NDB\\_BINLOG\\_WRITE\\_TO\\_NDB\\_BINLOG\\_INDEX\\_FAILED\\_AFTER\\_KILL](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Failed writing to ndb\_binlog\_index table while retrying after kill during shutdown

[ER\\_NDB\\_BINLOG\\_WRITE\\_TO\\_NDB\\_BINLOG\\_INDEX\\_FAILED\\_AFTER\\_KILL](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010661](#); Symbol: [ER\\_NDB\\_BINLOG\\_USING\\_SERVER\\_ID\\_0\\_SLAVES\\_WILL\\_NOT](#); SQLSTATE: [HY000](#)

Message: NDB: server id set to zero - changes logged to bin log with server id zero will be logged with another server id by slave mysqlds

[ER\\_NDB\\_BINLOG\\_USING\\_SERVER\\_ID\\_0\\_SLAVES\\_WILL\\_NOT](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: [MY-010662](#); Symbol: [ER\\_NDB\\_SERVER\\_ID\\_RESERVED\\_OR\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)  
Message: NDB: server id provided is too large to be represented in opt\_server\_id\_bits or is reserved  
[ER\\_NDB\\_SERVER\\_ID\\_RESERVED\\_OR\\_TOO\\_LARGE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010663](#); Symbol: [ER\\_NDB\\_BINLOG\\_NDB\\_LOG\\_TRANSACTION\\_ID\\_REQUIRES\\_V2\\_ROW\\_EVENTS](#); SQLSTATE: [HY000](#)  
Message: NDB: --ndb-log-transaction-id requires v2 Binlog row events but server is using v1.  
[ER\\_NDB\\_BINLOG\\_NDB\\_LOG\\_TRANSACTION\\_ID\\_REQUIRES\\_V2\\_ROW\\_EVENTS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010664](#); Symbol: [ER\\_NDB\\_BINLOG\\_NDB\\_LOG\\_APPLY\\_STATUS\\_FORCING\\_FULL\\_USE\\_WRITE](#); SQLSTATE: [HY000](#)  
Message: NDB: ndb-log-apply-status forcing %s.%s to FULL USE\_WRITE  
[ER\\_NDB\\_BINLOG\\_NDB\\_LOG\\_APPLY\\_STATUS\\_FORCING\\_FULL\\_USE\\_WRITE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010665](#); Symbol: [ER\\_NDB\\_BINLOG\\_GENERIC\\_MESSAGE](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: %s  
[ER\\_NDB\\_BINLOG\\_GENERIC\\_MESSAGE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010666](#); Symbol: [ER\\_NDB\\_CONFLICT\\_GENERIC\\_MESSAGE](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_NDB\\_CONFLICT\\_GENERIC\\_MESSAGE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010667](#); Symbol: [ER\\_NDB\\_TRANS\\_DEPENDENCY\\_TRACKER\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_NDB\\_TRANS\\_DEPENDENCY\\_TRACKER\\_ERROR](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010668](#); Symbol: [ER\\_NDB\\_CONFLICT\\_FN\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: NDB Slave: Table %s.%s : Parse error on conflict fn : %s  
[ER\\_NDB\\_CONFLICT\\_FN\\_PARSE\\_ERROR](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010669](#); Symbol: [ER\\_NDB\\_CONFLICT\\_FN\\_SETUP\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: NDB Slave: Table %s.%s : %s  
[ER\\_NDB\\_CONFLICT\\_FN\\_SETUP\\_ERROR](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010670](#); Symbol: [ER\\_NDB\\_BINLOG\\_FAILED\\_TO\\_GET\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Failed to get table %s from ndb: %s, %d  
[ER\\_NDB\\_BINLOG\\_FAILED\\_TO\\_GET\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: [MY-010671](#); Symbol: [ER\\_NDB\\_BINLOG\\_NOT\\_LOGGING](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: NOT logging %s  
[ER\\_NDB\\_BINLOG\\_NOT\\_LOGGING](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010672](#); Symbol: [ER\\_NDB\\_BINLOG\\_CREATE\\_TABLE\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: FAILED CREATE (DISCOVER) TABLE Event: %s  
[ER\\_NDB\\_BINLOG\\_CREATE\\_TABLE\\_EVENT\\_FAILED](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010673](#); Symbol: [ER\\_NDB\\_BINLOG\\_CREATE\\_TABLE\\_EVENT\\_INFO](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: CREATE (DISCOVER) TABLE Event: %s  
[ER\\_NDB\\_BINLOG\\_CREATE\\_TABLE\\_EVENT\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010674](#); Symbol: [ER\\_NDB\\_BINLOG\\_DISCOVER\\_TABLE\\_EVENT\\_INFO](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: DISCOVER TABLE Event: %s  
[ER\\_NDB\\_BINLOG\\_DISCOVER\\_TABLE\\_EVENT\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010675](#); Symbol: [ER\\_NDB\\_BINLOG\\_BLOB\\_REQUIRES\\_PK](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: logging of table %s with BLOB attribute and no PK is not supported  
[ER\\_NDB\\_BINLOG\\_BLOB\\_REQUIRES\\_PK](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010676](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_EVENT\\_IN\\_DB](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Unable to create event in database. Event: %s Error Code: %d Message: %s  
[ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_EVENT\\_IN\\_DB](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010677](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_EVENT\\_IN\\_DB\\_AND\\_CANT\\_DROP](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Unable to create event in database. Attempt to correct with drop failed. Event: %s Error Code: %d Message: %s  
[ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_EVENT\\_IN\\_DB\\_AND\\_CANT\\_DROP](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010678](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_EVENT\\_IN\\_DB\\_DROPPED](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Unable to create event in database. Attempt to correct with drop ok, but create failed. Event: %s Error Code: %d Message: %s  
[ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_EVENT\\_IN\\_DB\\_DROPPED](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010679](#); Symbol: [ER\\_NDB\\_BINLOG\\_DISCOVER\\_REUSING\\_OLD\\_EVENT\\_OPS](#); SQLSTATE: [HY000](#)
-

---

Message: NDB Binlog: discover reusing old ev op

[ER\\_NDB\\_BINLOG\\_DISCOVER\\_REUSING\\_OLD\\_EVENT\\_OPS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010680](#); Symbol: [ER\\_NDB\\_BINLOG\\_CREATING\\_NDBEVENTOPERATION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Creating NdbEventOperation failed for %s

[ER\\_NDB\\_BINLOG\\_CREATING\\_NDBEVENTOPERATION\\_FAILED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010681](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_BLOB](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Creating NdbEventOperation blob field %u handles failed (code=%d) for %s

[ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_BLOB](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010682](#); Symbol: [ER\\_NDB\\_BINLOG\\_NDBEVENT\\_EXECUTE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: ndbevent->execute failed for %s; %d %s

[ER\\_NDB\\_BINLOG\\_NDBEVENT\\_EXECUTE\\_FAILED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010683](#); Symbol: [ER\\_NDB\\_CREATE\\_EVENT\\_OPS\\_LOGGING\\_INFO](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: logging %s (%s,%s)

[ER\\_NDB\\_CREATE\\_EVENT\\_OPS\\_LOGGING\\_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010684](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_DROP\\_EVENT\\_FROM\\_DB](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Unable to drop event in database. Event: %s Error Code: %d Message: %s

[ER\\_NDB\\_BINLOG\\_CANT\\_DROP\\_EVENT\\_FROM\\_DB](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010685](#); Symbol: [ER\\_NDB\\_TIMED\\_OUT\\_IN\\_DROP\\_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB %s: %s timed out. Ignoring...

[ER\\_NDB\\_TIMED\\_OUT\\_IN\\_DROP\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010686](#); Symbol: [ER\\_NDB\\_BINLOG\\_UNHANDLED\\_ERROR\\_FOR\\_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: unhandled error %d for table %s

[ER\\_NDB\\_BINLOG\\_UNHANDLED\\_ERROR\\_FOR\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010687](#); Symbol: [ER\\_NDB\\_BINLOG\\_CLUSTER\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: cluster failure for %s at epoch %u/%u.

[ER\\_NDB\\_BINLOG\\_CLUSTER\\_FAILURE](#) was added in 8.0.2, removed after 8.0.13.



- 
- Error number: [MY-010688](#); Symbol: [ER\\_NDB\\_BINLOG\\_UNKNOWN\\_NON\\_DATA\\_EVENT](#); SQLSTATE: [HY000](#)  
  
Message: NDB Binlog: unknown non data event %d for %s. Ignoring...  
  
[ER\\_NDB\\_BINLOG\\_UNKNOWN\\_NON\\_DATA\\_EVENT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010689](#); Symbol: [ER\\_NDB\\_BINLOG\\_INJECTOR\\_DISCARDING\\_ROW\\_EVENT\\_METADATA](#); SQLSTATE: [HY000](#)  
  
Message: NDB: Binlog Injector discarding row event meta data as server is using v1 row events. (%u %x)  
  
[ER\\_NDB\\_BINLOG\\_INJECTOR\\_DISCARDING\\_ROW\\_EVENT\\_METADATA](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010690](#); Symbol: [ER\\_NDB\\_REMAINING\\_OPEN\\_TABLES](#); SQLSTATE: [HY000](#)  
  
Message: remove\_all\_event\_operations: Remaining open tables:  
  
[ER\\_NDB\\_REMAINING\\_OPEN\\_TABLES](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010691](#); Symbol: [ER\\_NDB\\_REMAINING\\_OPEN\\_TABLE\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: %s.%s, use\_count: %u  
  
[ER\\_NDB\\_REMAINING\\_OPEN\\_TABLE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010692](#); Symbol: [ER\\_NDB\\_COULD\\_NOT\\_GET\\_APPLY\\_STATUS\\_SHARE](#); SQLSTATE: [HY000](#)  
  
Message: NDB: Could not get apply status share  
  
[ER\\_NDB\\_COULD\\_NOT\\_GET\\_APPLY\\_STATUS\\_SHARE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010693](#); Symbol: [ER\\_NDB\\_BINLOG\\_SERVER\\_SHUTDOWN\\_DURING\\_NDB\\_CLUSTER\\_START](#); SQLSTATE: [HY000](#)  
  
Message: NDB Binlog: Server shutdown detected while waiting for ndbcluster to start...  
  
[ER\\_NDB\\_BINLOG\\_SERVER\\_SHUTDOWN\\_DURING\\_NDB\\_CLUSTER\\_START](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010694](#); Symbol: [ER\\_NDB\\_BINLOG\\_CLUSTER\\_RESTARTED\\_RESET\\_MASTER\\_SUGGESTED](#); SQLSTATE: [HY000](#)  
  
Message: NDB Binlog: cluster has been restarted --initial or with older filesystem.  
ndb\_latest\_handled\_binlog\_epoch: %u/%u, while current epoch: %u/%u. RESET MASTER should be issued. Resetting ndb\_latest\_handled\_binlog\_epoch.  
  
[ER\\_NDB\\_BINLOG\\_CLUSTER\\_RESTARTED\\_RESET\\_MASTER\\_SUGGESTED](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010695](#); Symbol: [ER\\_NDB\\_BINLOG\\_CLUSTER\\_HAS\\_RECONNECTED](#); SQLSTATE: [HY000](#)  
  
Message: NDB Binlog: cluster has reconnected. Changes to the database that occurred while disconnected will not be in the binlog

---

`ER_NDB_BINLOG_CLUSTER_HAS_RECONNECTED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010696`; Symbol: `ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH`; SQLSTATE: `HY000`

Message: NDB Binlog: starting log at epoch %u/%u

`ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010697`; Symbol: `ER_NDB_BINLOG_NDB_TABLES_WRITABLE`; SQLSTATE: `HY000`

Message: NDB Binlog: ndb tables writable

`ER_NDB_BINLOG_NDB_TABLES_WRITABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010698`; Symbol: `ER_NDB_BINLOG_SHUTDOWN_DETECTED`; SQLSTATE: `HY000`

Message: NDB Binlog: Server shutdown detected...

`ER_NDB_BINLOG_SHUTDOWN_DETECTED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010699`; Symbol: `ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITING`; SQLSTATE: `HY000`

Message: NDB Binlog: Just lost schema connection, hanging around

`ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITING` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010700`; Symbol: `ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONTINUING`; SQLSTATE: `HY000`

Message: NDB Binlog: ...and on our way

`ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONTINUING` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010701`; Symbol: `ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT`; SQLSTATE: `HY000`

Message: NDB: error %lu (%s) on handling binlog schema event

`ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010702`; Symbol: `ER_NDB_BINLOG_CANT_INJECT_APPLY_STATUS_WRITE_ROW`; SQLSTATE: `HY000`

Message: NDB Binlog: Failed to inject apply status write row

`ER_NDB_BINLOG_CANT_INJECT_APPLY_STATUS_WRITE_ROW` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010703`; Symbol: `ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK`; SQLSTATE: `HY000`

Message: NDB Binlog: Error during ROLLBACK of GCI %u/%u. Error: %d

`ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK` was added in 8.0.2, removed after 8.0.13.

- 
- Error number: [MY-010704](#); Symbol: [ER\\_NDB\\_BINLOG\\_ERROR\\_DURING\\_GCI\\_COMMIT](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Error during COMMIT of GCI. Error: %d  
[ER\\_NDB\\_BINLOG\\_ERROR\\_DURING\\_GCI\\_COMMIT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010705](#); Symbol: [ER\\_NDB\\_BINLOG\\_LATEST\\_TRX\\_IN\\_EPOCH\\_NOT\\_IN\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: latest transaction in epoch %u/%u not in binlog as latest handled epoch is %u/%u  
[ER\\_NDB\\_BINLOG\\_LATEST\\_TRX\\_IN\\_EPOCH\\_NOT\\_IN\\_BINLOG](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010706](#); Symbol: [ER\\_NDB\\_BINLOG\\_RELEASING\\_EXTRA\\_SHARE\\_REFERENCES](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Release extra share references  
[ER\\_NDB\\_BINLOG\\_RELEASING\\_EXTRA\\_SHARE\\_REFERENCES](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010707](#); Symbol: [ER\\_NDB\\_BINLOG\\_REMAINING\\_OPEN\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: remaining open tables:  
[ER\\_NDB\\_BINLOG\\_REMAINING\\_OPEN\\_TABLES](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010708](#); Symbol: [ER\\_NDB\\_BINLOG\\_REMAINING\\_OPEN\\_TABLE\\_INFO](#); SQLSTATE: [HY000](#)  
Message: %s.%s state: %u use\_count: %u  
[ER\\_NDB\\_BINLOG\\_REMAINING\\_OPEN\\_TABLE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010709](#); Symbol: [ER\\_TREE\\_CORRUPT\\_PARENT\\_SHOULD\\_POINT\\_AT\\_PARENT](#); SQLSTATE: [HY000](#)  
Message: Wrong tree: Parent doesn't point at parent  
[ER\\_TREE\\_CORRUPT\\_PARENT\\_SHOULD\\_POINT\\_AT\\_PARENT](#) was added in 8.0.2.
  - Error number: [MY-010710](#); Symbol: [ER\\_TREE\\_CORRUPT\\_ROOT\\_SHOULD\\_BE\\_BLACK](#); SQLSTATE: [HY000](#)  
Message: Wrong tree: Root should be black  
[ER\\_TREE\\_CORRUPT\\_ROOT\\_SHOULD\\_BE\\_BLACK](#) was added in 8.0.2.
  - Error number: [MY-010711](#); Symbol: [ER\\_TREE\\_CORRUPT\\_2\\_CONSECUTIVE\\_REDS](#); SQLSTATE: [HY000](#)  
Message: Wrong tree: Found two red in a row  
[ER\\_TREE\\_CORRUPT\\_2\\_CONSECUTIVE\\_REDS](#) was added in 8.0.2.
  - Error number: [MY-010712](#); Symbol: [ER\\_TREE\\_CORRUPT\\_RIGHT\\_IS\\_LEFT](#); SQLSTATE: [HY000](#)  
Message: Wrong tree: Found right == left
-

---

`ER_TREE_CORRUPT_RIGHT_IS_LEFT` was added in 8.0.2.

- Error number: `MY-010713`; Symbol: `ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT`; SQLSTATE: `HY000`

Message: Wrong tree: Incorrect black-count: %d - %d

`ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT` was added in 8.0.2.

- Error number: `MY-010714`; Symbol: `ER_WRONG_COUNT_FOR_ORIGIN`; SQLSTATE: `HY000`

Message: Use\_count: Wrong count %lu for origin %p

`ER_WRONG_COUNT_FOR_ORIGIN` was added in 8.0.2.

- Error number: `MY-010715`; Symbol: `ER_WRONG_COUNT_FOR_KEY`; SQLSTATE: `HY000`

Message: Use\_count: Wrong count for key at %p, %lu should be %lu

`ER_WRONG_COUNT_FOR_KEY` was added in 8.0.2.

- Error number: `MY-010716`; Symbol: `ER_WRONG_COUNT_OF_ELEMENTS`; SQLSTATE: `HY000`

Message: Wrong number of elements: %u (should be %u) for tree at %p

`ER_WRONG_COUNT_OF_ELEMENTS` was added in 8.0.2.

- Error number: `MY-010717`; Symbol: `ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error reading slave worker configuration

`ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010717`; Symbol: `ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error reading replica worker configuration

`ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION` was added in 8.0.33.

- Error number: `MY-010718`; Symbol: `ER_RPL_ERROR_WRITING_SLAVE_WORKER_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error writing slave worker configuration

`ER_RPL_ERROR_WRITING_SLAVE_WORKER_CONFIGURATION` was added in 8.0.2, removed after 8.0.18.

- Error number: `MY-010719`; Symbol: `ER_RPL_FAILED_TO_OPEN_RELAY_LOG`; SQLSTATE: `HY000`

Message: Failed to open relay log %s, error: %s

`ER_RPL_FAILED_TO_OPEN_RELAY_LOG` was added in 8.0.2.

- Error number: `MY-010720`; Symbol: `ER_RPL_WORKER_CANT_READ_RELAY_LOG`; SQLSTATE: `HY000`

Message: Error when worker read relay log events, relay log name %s, position %llu

---

`ER_RPL_WORKER_CANT_READ_RELAY_LOG` was added in 8.0.2.

- Error number: `MY-010721`; Symbol: `ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG`; SQLSTATE: `HY000`

Message: Failed to find next relay log when retrying the transaction, current relay log is %s

`ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG` was added in 8.0.2.

- Error number: `MY-010722`; Symbol: `ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED`; SQLSTATE: `HY000`

Message: Multi-threaded slave: Coordinator has waited %lu times hitting replica\_pending\_jobs\_size\_max; current event size = %zu.

`ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010722`; Symbol: `ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED`; SQLSTATE: `HY000`

Message: Multi-threaded replica: Coordinator has waited %lu times hitting replica\_pending\_jobs\_size\_max; current event size = %zu.

`ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED` was added in 8.0.33.

- Error number: `MY-010723`; Symbol: `ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES`; SQLSTATE: `HY000`

Message: Failed to write the DROP statement for temporary tables to binary log

`ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES` was added in 8.0.2.

- Error number: `MY-010724`; Symbol: `ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_HEAP_TABLE`; SQLSTATE: `HY000`

Message: When opening HEAP table, could not allocate memory to write 'DELETE FROM '%s'.'%s' to the binary log

`ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_HEAP_TABLE` was added in 8.0.2.

- Error number: `MY-010725`; Symbol: `ER_FAILED_TO_REPAIR_TABLE`; SQLSTATE: `HY000`

Message: Couldn't repair table: %s.%s

`ER_FAILED_TO_REPAIR_TABLE` was added in 8.0.2.

- Error number: `MY-010726`; Symbol: `ER_FAILED_TO_REMOVE_TEMP_TABLE`; SQLSTATE: `HY000`

Message: Could not remove temporary table: '%s', error: %d

`ER_FAILED_TO_REMOVE_TEMP_TABLE` was added in 8.0.2.

- Error number: `MY-010727`; Symbol: `ER_SYSTEM_TABLE_NOT_TRANSACTIONAL`; SQLSTATE: `HY000`

Message: System table '%.\*s' is expected to be transactional.

`ER_SYSTEM_TABLE_NOT_TRANSACTIONAL` was added in 8.0.2.

- 
- Error number: `MY-010728`; Symbol: `ER_RPL_ERROR_WRITING_MASTER_CONFIGURATION`; SQLSTATE: `HY000`  
  
Message: Error writing master configuration.  
  
`ER_RPL_ERROR_WRITING_MASTER_CONFIGURATION` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010728`; Symbol: `ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION`; SQLSTATE: `HY000`  
  
Message: Error writing source configuration.  
  
`ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION` was added in 8.0.33.
  - Error number: `MY-010729`; Symbol: `ER_RPL_ERROR_READING_MASTER_CONFIGURATION`; SQLSTATE: `HY000`  
  
Message: Error reading master configuration.  
  
`ER_RPL_ERROR_READING_MASTER_CONFIGURATION` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010729`; Symbol: `ER_RPL_ERROR_READING_SOURCE_CONFIGURATION`; SQLSTATE: `HY000`  
  
Message: Error reading source configuration.  
  
`ER_RPL_ERROR_READING_SOURCE_CONFIGURATION` was added in 8.0.33.
  - Error number: `MY-010730`; Symbol: `ER_RPL_SSL_INFO_IN_MASTER_INFO_IGNORED`; SQLSTATE: `HY000`  
  
Message: SSL information in the master info file are ignored because this MySQL slave was compiled without SSL support.  
  
`ER_RPL_SSL_INFO_IN_MASTER_INFO_IGNORED` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010730`; Symbol: `ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED`; SQLSTATE: `HY000`  
  
Message: SSL information in the connection metadata repository are ignored because this MySQL replica was compiled without SSL support.  
  
`ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED` was added in 8.0.33.
  - Error number: `MY-010731`; Symbol: `ER_PLUGIN_FAILED_DEINITIALIZATION`; SQLSTATE: `HY000`  
  
Message: Plugin '%s' of type %s failed deinitialization  
  
`ER_PLUGIN_FAILED_DEINITIALIZATION` was added in 8.0.2.
  - Error number: `MY-010732`; Symbol: `ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION`; SQLSTATE: `HY000`  
  
Message: Plugin '%s' has ref\_count=%d after deinitialization.  
  
`ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION` was added in 8.0.2.
  - Error number: `MY-010733`; Symbol: `ER_PLUGIN_SHUTTING_DOWN_PLUGIN`; SQLSTATE: `HY000`

---

Message: Shutting down plugin '%s'

[ER\\_PLUGIN\\_SHUTTING\\_DOWN\\_PLUGIN](#) was added in 8.0.2.

- Error number: [MY-010734](#); Symbol: [ER\\_PLUGIN\\_REGISTRATION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' registration as a %s failed.

[ER\\_PLUGIN\\_REGISTRATION\\_FAILED](#) was added in 8.0.2.

- Error number: [MY-010735](#); Symbol: [ER\\_PLUGIN\\_CANT\\_OPEN\\_PLUGIN\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not open the mysql.plugin table. Please perform the MySQL upgrade procedure.

[ER\\_PLUGIN\\_CANT\\_OPEN\\_PLUGIN\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010736](#); Symbol: [ER\\_PLUGIN\\_CANT\\_LOAD](#); SQLSTATE: [HY000](#)

Message: Couldn't load plugin named '%s' with soname '%s'.

[ER\\_PLUGIN\\_CANT\\_LOAD](#) was added in 8.0.2.

- Error number: [MY-010737](#); Symbol: [ER\\_PLUGIN\\_LOAD\\_PARAMETER\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)

Message: plugin-load parameter too long

[ER\\_PLUGIN\\_LOAD\\_PARAMETER\\_TOO\\_LONG](#) was added in 8.0.2.

- Error number: [MY-010738](#); Symbol: [ER\\_PLUGIN\\_FORCING\\_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' will be forced to shutdown

[ER\\_PLUGIN\\_FORCING\\_SHUTDOWN](#) was added in 8.0.2.

- Error number: [MY-010739](#); Symbol: [ER\\_PLUGIN\\_HAS\\_NONZERO\\_REFCOUNT\\_AFTER\\_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' has ref\_count=%d after shutdown.

[ER\\_PLUGIN\\_HAS\\_NONZERO\\_REFCOUNT\\_AFTER\\_SHUTDOWN](#) was added in 8.0.2.

- Error number: [MY-010740](#); Symbol: [ER\\_PLUGIN\\_UNKNOWN\\_VARIABLE\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Unknown variable type code 0x%x in plugin '%s'.

[ER\\_PLUGIN\\_UNKNOWN\\_VARIABLE\\_TYPE](#) was added in 8.0.2.

- Error number: [MY-010741](#); Symbol: [ER\\_PLUGIN\\_VARIABLE\\_SET\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)

Message: Server variable %s of plugin %s was forced to be read-only: string variable without update\_func and PLUGIN\_VAR\_MEMALLOC flag

[ER\\_PLUGIN\\_VARIABLE\\_SET\\_READ\\_ONLY](#) was added in 8.0.2.

- Error number: [MY-010742](#); Symbol: [ER\\_PLUGIN\\_VARIABLE\\_MISSING\\_NAME](#); SQLSTATE: [HY000](#)

Message: Missing variable name in plugin '%s'.

[ER\\_PLUGIN\\_VARIABLE\\_MISSING\\_NAME](#) was added in 8.0.2.

- 
- Error number: `MY-010743`; Symbol: `ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL`; SQLSTATE: `HY000`  
Message: Thread local variable '%s' not allocated in plugin '%s'.  
`ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL` was added in 8.0.2.
  - Error number: `MY-010744`; Symbol: `ER_PLUGIN_OOM`; SQLSTATE: `HY000`  
Message: Out of memory for plugin '%s'.  
`ER_PLUGIN_OOM` was added in 8.0.2.
  - Error number: `MY-010745`; Symbol: `ER_PLUGIN_BAD_OPTIONS`; SQLSTATE: `HY000`  
Message: Bad options for plugin '%s'.  
`ER_PLUGIN_BAD_OPTIONS` was added in 8.0.2.
  - Error number: `MY-010746`; Symbol: `ER_PLUGIN_PARSING_OPTIONS_FAILED`; SQLSTATE: `HY000`  
Message: Parsing options for plugin '%s' failed.  
`ER_PLUGIN_PARSING_OPTIONS_FAILED` was added in 8.0.2.
  - Error number: `MY-010747`; Symbol: `ER_PLUGIN_DISABLED`; SQLSTATE: `HY000`  
Message: Plugin '%s' is disabled.  
`ER_PLUGIN_DISABLED` was added in 8.0.2.
  - Error number: `MY-010748`; Symbol: `ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES`; SQLSTATE: `HY000`  
Message: Plugin '%s' has conflicting system variables  
`ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES` was added in 8.0.2.
  - Error number: `MY-010749`; Symbol: `ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS`; SQLSTATE: `HY000`  
Message: Setting persistent options for plugin '%s' failed.  
`ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS` was added in 8.0.2.
  - Error number: `MY-010750`; Symbol: `ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR`; SQLSTATE: `HY000`  
Message: Failed on my\_net\_write, writing to stderr instead: %s  
`ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR` was added in 8.0.2.
  - Error number: `MY-010751`; Symbol: `ER_RETRYING_REPAIR_WITHOUT_QUICK`; SQLSTATE: `HY000`  
Message: Retrying repair of: '%s' without quick  
`ER_RETRYING_REPAIR_WITHOUT_QUICK` was added in 8.0.2.
  - Error number: `MY-010752`; Symbol: `ER_RETRYING_REPAIR_WITH_KEYCACHE`; SQLSTATE: `HY000`



---

Message: Retrying repair of: '%s' with keycache

[ER\\_RETRYING\\_REPAIR\\_WITH\\_KEYCACHE](#) was added in 8.0.2.

- Error number: [MY-010753](#); Symbol: [ER\\_FOUND\\_ROWS\\_WHILE\\_REPAIRING](#); SQLSTATE: [HY000](#)

Message: Found %s of %s rows when repairing '%s'

[ER\\_FOUND\\_ROWS\\_WHILE\\_REPAIRING](#) was added in 8.0.2.

- Error number: [MY-010754](#); Symbol: [ER\\_ERROR\\_DURING\\_OPTIMIZE\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Warning: Optimize table got errno %d on %s.%s, retrying

[ER\\_ERROR\\_DURING\\_OPTIMIZE\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010755](#); Symbol: [ER\\_ERROR\\_ENABLING\\_KEYS](#); SQLSTATE: [HY000](#)

Message: Warning: Enabling keys got errno %d on %s.%s, retrying

[ER\\_ERROR\\_ENABLING\\_KEYS](#) was added in 8.0.2.

- Error number: [MY-010756](#); Symbol: [ER\\_CHECKING\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Checking table: '%s'

[ER\\_CHECKING\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010757](#); Symbol: [ER\\_RECOVERING\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Recovering table: '%s'

[ER\\_RECOVERING\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010758](#); Symbol: [ER\\_CANT\\_CREATE\\_TABLE\\_SHARE\\_FROM\\_FRM](#); SQLSTATE: [HY000](#)

Message: Error in creating TABLE\_SHARE from %s.frm file.

[ER\\_CANT\\_CREATE\\_TABLE\\_SHARE\\_FROM\\_FRM](#) was added in 8.0.2.

- Error number: [MY-010759](#); Symbol: [ER\\_CANT\\_LOCK\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Unable to acquire lock on %s.%s

[ER\\_CANT\\_LOCK\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010760](#); Symbol: [ER\\_CANT\\_ALLOC\\_TABLE\\_OBJECT](#); SQLSTATE: [HY000](#)

Message: Error in allocation memory for TABLE object.

[ER\\_CANT\\_ALLOC\\_TABLE\\_OBJECT](#) was added in 8.0.2.

- Error number: [MY-010761](#); Symbol: [ER\\_CANT\\_CREATE\\_HANDLER\\_OBJECT\\_FOR\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Error in creating handler object for table %s.%s

[ER\\_CANT\\_CREATE\\_HANDLER\\_OBJECT\\_FOR\\_TABLE](#) was added in 8.0.2.

- 
- Error number: [MY-010762](#); Symbol: [ER\\_CANT\\_SET\\_HANDLER\\_REFERENCE\\_FOR\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Error in setting handler reference for table %s.%s  
[ER\\_CANT\\_SET\\_HANDLER\\_REFERENCE\\_FOR\\_TABLE](#) was added in 8.0.2.
  - Error number: [MY-010763](#); Symbol: [ER\\_CANT\\_LOCK\\_TABLESPACE](#); SQLSTATE: [HY000](#)  
Message: Unable to acquire lock on tablespace name %s  
[ER\\_CANT\\_LOCK\\_TABLESPACE](#) was added in 8.0.2.
  - Error number: [MY-010764](#); Symbol: [ER\\_CANT\\_UPGRADE\\_GENERATED\\_COLUMNS\\_TO\\_DD](#); SQLSTATE: [HY000](#)  
Message: Error in processing generated columns for table %s.%s  
[ER\\_CANT\\_UPGRADE\\_GENERATED\\_COLUMNS\\_TO\\_DD](#) was added in 8.0.2.
  - Error number: [MY-010765](#); Symbol: [ER\\_DD\\_ERROR\\_CREATING\\_ENTRY](#); SQLSTATE: [HY000](#)  
Message: Error in Creating DD entry for %s.%s  
[ER\\_DD\\_ERROR\\_CREATING\\_ENTRY](#) was added in 8.0.2.
  - Error number: [MY-010766](#); Symbol: [ER\\_DD\\_CANT\\_FETCH\\_TABLE\\_DATA](#); SQLSTATE: [HY000](#)  
Message: Error in fetching %s.%s table data from dictionary  
[ER\\_DD\\_CANT\\_FETCH\\_TABLE\\_DATA](#) was added in 8.0.2.
  - Error number: [MY-010767](#); Symbol: [ER\\_DD\\_CANT\\_FIX\\_SE\\_DATA](#); SQLSTATE: [HY000](#)  
Message: Error in fixing SE data for %s.%s  
[ER\\_DD\\_CANT\\_FIX\\_SE\\_DATA](#) was added in 8.0.2.
  - Error number: [MY-010768](#); Symbol: [ER\\_DD\\_CANT\\_CREATE\\_SP](#); SQLSTATE: [HY000](#)  
Message: Error in creating stored program '%s.%s'  
[ER\\_DD\\_CANT\\_CREATE\\_SP](#) was added in 8.0.2.
  - Error number: [MY-010769](#); Symbol: [ER\\_CANT\\_OPEN\\_DB\\_OPT\\_USING\\_DEFAULT\\_CHARSET](#); SQLSTATE: [HY000](#)  
Message: Unable to open db.opt file %s. Using default Character set.  
[ER\\_CANT\\_OPEN\\_DB\\_OPT\\_USING\\_DEFAULT\\_CHARSET](#) was added in 8.0.2.
  - Error number: [MY-010770](#); Symbol: [ER\\_CANT\\_CREATE\\_CACHE\\_FOR\\_DB\\_OPT](#); SQLSTATE: [HY000](#)  
Message: Unable to initialize IO cache to open db.opt file %s.  
[ER\\_CANT\\_CREATE\\_CACHE\\_FOR\\_DB\\_OPT](#) was added in 8.0.2.
  - Error number: [MY-010771](#); Symbol: [ER\\_CANT\\_IDENTIFY\\_CHARSET\\_USING\\_DEFAULT](#); SQLSTATE: [HY000](#)

---

Message: Unable to identify the charset in %s. Using default character set.

[ER\\_CANT\\_IDENTIFY\\_CHARSET\\_USING\\_DEFAULT](#) was added in 8.0.2.

- Error number: [MY-010772](#); Symbol: [ER\\_DB\\_OPT\\_NOT\\_FOUND\\_USING\\_DEFAULT\\_CHARSET](#); SQLSTATE: [HY000](#)

Message: db.opt file not found for %s database. Using default Character set.

[ER\\_DB\\_OPT\\_NOT\\_FOUND\\_USING\\_DEFAULT\\_CHARSET](#) was added in 8.0.2.

- Error number: [MY-010773](#); Symbol: [ER\\_EVENT\\_CANT\\_GET\\_TIMEZONE\\_FROM\\_FIELD](#); SQLSTATE: [HY000](#)

Message: Event '%s'. '%s': invalid value in column mysql.event.time\_zone.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the [mysql.event](#) system table and migrates its contents to the internal data dictionary.

[ER\\_EVENT\\_CANT\\_GET\\_TIMEZONE\\_FROM\\_FIELD](#) was added in 8.0.2.

- Error number: [MY-010774](#); Symbol: [ER\\_EVENT\\_CANT\\_FIND\\_TIMEZONE](#); SQLSTATE: [HY000](#)

Message: Event '%s'. '%s': has invalid time zone value

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the [mysql.event](#) system table and migrates its contents to the internal data dictionary.

[ER\\_EVENT\\_CANT\\_FIND\\_TIMEZONE](#) was added in 8.0.2.

- Error number: [MY-010775](#); Symbol: [ER\\_EVENT\\_CANT\\_GET\\_CHARSET](#); SQLSTATE: [HY000](#)

Message: Event '%s'. '%s': invalid value in column mysql.event.character\_set\_client.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the [mysql.event](#) system table and migrates its contents to the internal data dictionary.

[ER\\_EVENT\\_CANT\\_GET\\_CHARSET](#) was added in 8.0.2.

- Error number: [MY-010776](#); Symbol: [ER\\_EVENT\\_CANT\\_GET\\_COLLATION](#); SQLSTATE: [HY000](#)

Message: Event '%s'. '%s': invalid value in column mysql.event.collation\_connection.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the [mysql.event](#) system table and migrates its contents to the internal data dictionary.

[ER\\_EVENT\\_CANT\\_GET\\_COLLATION](#) was added in 8.0.2.

- Error number: [MY-010777](#); Symbol: [ER\\_EVENT\\_CANT\\_OPEN\\_TABLE\\_MYSQL\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Failed to open mysql.event Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the [mysql.event](#) system table and migrates its contents to the internal data dictionary.

[ER\\_EVENT\\_CANT\\_OPEN\\_TABLE\\_MYSQL\\_EVENT](#) was added in 8.0.2.

- 
- Error number: [MY-010778](#); Symbol: [ER\\_CANT\\_PARSE\\_STORED\\_ROUTINE\\_BODY](#); SQLSTATE: [HY000](#)

Message: Parsing '%s.%s' routine body failed.%s

[ER\\_CANT\\_PARSE\\_STORED\\_ROUTINE\\_BODY](#) was added in 8.0.2.

- Error number: [MY-010779](#); Symbol: [ER\\_CANT\\_OPEN\\_TABLE\\_MYSQL\\_PROC](#); SQLSTATE: [HY000](#)

Message: Failed to open mysql.proc Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the [mysql.proc](#) system table and migrates its contents to the internal data dictionary.

[ER\\_CANT\\_OPEN\\_TABLE\\_MYSQL\\_PROC](#) was added in 8.0.2.

- Error number: [MY-010780](#); Symbol: [ER\\_CANT\\_READ\\_TABLE\\_MYSQL\\_PROC](#); SQLSTATE: [HY000](#)

Message: Failed to read mysql.proc table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the [mysql.proc](#) system table and migrates its contents to the internal data dictionary.

[ER\\_CANT\\_READ\\_TABLE\\_MYSQL\\_PROC](#) was added in 8.0.2.

- Error number: [MY-010781](#); Symbol: [ER\\_FILE\\_EXISTS\\_DURING\\_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Found %s file in mysql schema. DD will create .ibd file with same name. Please rename table and start upgrade process again.

[ER\\_FILE\\_EXISTS\\_DURING\\_UPGRADE](#) was added in 8.0.2.

- Error number: [MY-010782](#); Symbol: [ER\\_CANT\\_OPEN\\_DATADIR\\_AFTER\\_UPGRADE\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Unable to open the data directory %s during clean up after upgrade failed

[ER\\_CANT\\_OPEN\\_DATADIR\\_AFTER\\_UPGRADE\\_FAILURE](#) was added in 8.0.2.

- Error number: [MY-010783](#); Symbol: [ER\\_CANT\\_SET\\_PATH\\_FOR](#); SQLSTATE: [HY000](#)

Message: Failed to set path %s

[ER\\_CANT\\_SET\\_PATH\\_FOR](#) was added in 8.0.2.

- Error number: [MY-010784](#); Symbol: [ER\\_CANT\\_OPEN\\_DIR](#); SQLSTATE: [HY000](#)

Message: Failed to open dir %s

[ER\\_CANT\\_OPEN\\_DIR](#) was added in 8.0.2.

- Error number: [MY-010785](#); Symbol: [ER\\_NDB\\_EMPTY\\_NODEID\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: Found empty nodeid specified in --ndb-cluster-connection-pool-nodeids='%s'.

[ER\\_NDB\\_EMPTY\\_NODEID\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: [MY-010786](#); Symbol: [ER\\_NDB\\_CANT\\_PARSE\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#); SQLSTATE: [HY000](#)  
  
Message: NDB: Could not parse '%s' in --ndb-cluster-connection-pool-nodeids='%s'.  
  
[ER\\_NDB\\_CANT\\_PARSE\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010787](#); Symbol: [ER\\_NDB\\_INVALID\\_NODEID\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#); SQLSTATE: [HY000](#)  
  
Message: NDB: Invalid nodeid %d in --ndb-cluster-connection-pool-nodeids='%s'.  
  
[ER\\_NDB\\_INVALID\\_NODEID\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010788](#); Symbol: [ER\\_NDB\\_DUPLICATE\\_NODEID\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#); SQLSTATE: [HY000](#)  
  
Message: NDB: Found duplicate nodeid %d in --ndb-cluster-connection-pool-nodeids='%s'.  
  
[ER\\_NDB\\_DUPLICATE\\_NODEID\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010789](#); Symbol: [ER\\_NDB\\_POOL\\_SIZE\\_MUST\\_MATCH\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#); SQLSTATE: [HY000](#)  
  
Message: NDB: The size of the cluster connection pool must be equal to the number of nodeids in --ndb-cluster-connection-pool-nodeids='%s'.  
  
[ER\\_NDB\\_POOL\\_SIZE\\_MUST\\_MATCH\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010790](#); Symbol: [ER\\_NDB\\_NODEID\\_NOT\\_FIRST\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#); SQLSTATE: [HY000](#)  
  
Message: NDB: The nodeid specified by --ndb-nodeid must be equal to the first nodeid in --ndb-cluster-connection-pool-nodeids='%s'.  
  
[ER\\_NDB\\_NODEID\\_NOT\\_FIRST\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010791](#); Symbol: [ER\\_NDB\\_USING\\_NODEID](#); SQLSTATE: [HY000](#)  
  
Message: NDB: using nodeid %u  
  
[ER\\_NDB\\_USING\\_NODEID](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010792](#); Symbol: [ER\\_NDB\\_CANT\\_ALLOC\\_GLOBAL\\_NDB\\_CLUSTER\\_CONNECTION](#); SQLSTATE: [HY000](#)  
  
Message: NDB: failed to allocate global ndb cluster connection  
  
[ER\\_NDB\\_CANT\\_ALLOC\\_GLOBAL\\_NDB\\_CLUSTER\\_CONNECTION](#) was added in 8.0.2, removed after 8.0.13.
-

- 
- Error number: [MY-010793](#); Symbol: [ER\\_NDB\\_CANT\\_ALLOC\\_GLOBAL\\_NDB\\_OBJECT](#); SQLSTATE: [HY000](#)  
Message: NDB: failed to allocate global ndb object  
[ER\\_NDB\\_CANT\\_ALLOC\\_GLOBAL\\_NDB\\_OBJECT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010794](#); Symbol: [ER\\_NDB\\_USING\\_NODEID\\_LIST](#); SQLSTATE: [HY000](#)  
Message: NDB[%u]: using nodeid %u  
[ER\\_NDB\\_USING\\_NODEID\\_LIST](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010795](#); Symbol: [ER\\_NDB\\_CANT\\_ALLOC\\_NDB\\_CLUSTER\\_CONNECTION](#); SQLSTATE: [HY000](#)  
Message: NDB[%u]: failed to allocate cluster connect object  
[ER\\_NDB\\_CANT\\_ALLOC\\_NDB\\_CLUSTER\\_CONNECTION](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010796](#); Symbol: [ER\\_NDB\\_STARTING\\_CONNECT\\_THREAD](#); SQLSTATE: [HY000](#)  
Message: NDB[%u]: starting connect thread  
[ER\\_NDB\\_STARTING\\_CONNECT\\_THREAD](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010797](#); Symbol: [ER\\_NDB\\_NODE\\_INFO](#); SQLSTATE: [HY000](#)  
Message: NDB[%u]: NodeID: %d, %s  
[ER\\_NDB\\_NODE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010798](#); Symbol: [ER\\_NDB\\_CANT\\_START\\_CONNECT\\_THREAD](#); SQLSTATE: [HY000](#)  
Message: NDB[%u]: failed to start connect thread  
[ER\\_NDB\\_CANT\\_START\\_CONNECT\\_THREAD](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010799](#); Symbol: [ER\\_NDB\\_GENERIC\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: NDB: error (%u) %s  
[ER\\_NDB\\_GENERIC\\_ERROR](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010800](#); Symbol: [ER\\_NDB\\_CPU\\_MASK\\_TOO\\_SHORT](#); SQLSTATE: [HY000](#)  
Message: Ignored receive thread CPU mask, mask too short, %u CPUs needed in mask, only %u CPUs provided  
[ER\\_NDB\\_CPU\\_MASK\\_TOO\\_SHORT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010801](#); Symbol: [ER\\_EVENT\\_ERROR\\_CREATING\\_QUERY\\_TO\\_WRITE\\_TO\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Event Error: An error occurred while creating query string, before writing it into binary log.  
[ER\\_EVENT\\_ERROR\\_CREATING\\_QUERY\\_TO\\_WRITE\\_TO\\_BINLOG](#) was added in 8.0.2.
  - Error number: [MY-010802](#); Symbol: [ER\\_EVENT\\_SCHEDULER\\_ERROR\\_LOADING\\_FROM\\_DB](#); SQLSTATE: [HY000](#)

---

Message: Event Scheduler: Error while loading from disk.

[ER\\_EVENT\\_SCHEDULER\\_ERROR\\_LOADING\\_FROM\\_DB](#) was added in 8.0.2.

- Error number: [MY-010803](#); Symbol: [ER\\_EVENT\\_SCHEDULER\\_ERROR\\_GETTING\\_EVENT\\_OBJECT](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error getting event object.

[ER\\_EVENT\\_SCHEDULER\\_ERROR\\_GETTING\\_EVENT\\_OBJECT](#) was added in 8.0.2.

- Error number: [MY-010804](#); Symbol: [ER\\_EVENT\\_SCHEDULER\\_GOT\\_BAD\\_DATA\\_FROM\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error while loading events from mysql.events. The table probably contains bad data or is corrupted

[ER\\_EVENT\\_SCHEDULER\\_GOT\\_BAD\\_DATA\\_FROM\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010805](#); Symbol: [ER\\_EVENT\\_CANT\\_GET\\_LOCK\\_FOR\\_DROPPING\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to obtain lock for dropping event %s from schema %s

[ER\\_EVENT\\_CANT\\_GET\\_LOCK\\_FOR\\_DROPPING\\_EVENT](#) was added in 8.0.2.

- Error number: [MY-010806](#); Symbol: [ER\\_EVENT\\_UNABLE\\_TO\\_DROP\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to drop event %s from schema %s

[ER\\_EVENT\\_UNABLE\\_TO\\_DROP\\_EVENT](#) was added in 8.0.2.

- Error number: [MY-010807](#); Symbol: [ER\\_BINLOG\\_ATTACHING\\_THREAD\\_MEMORY\\_FINALY\\_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: Server overcomes the temporary 'out of memory' in '%d' tries while attaching to session thread during the group commit phase.

[ER\\_BINLOG\\_ATTACHING\\_THREAD\\_MEMORY\\_FINALY\\_AVAILABLE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010808](#); Symbol: [ER\\_BINLOG\\_CANT\\_RESIZE\\_CACHE](#); SQLSTATE: [HY000](#)

Message: Unable to resize binlog IOCACHE auxiliary file

[ER\\_BINLOG\\_CANT\\_RESIZE\\_CACHE](#) was added in 8.0.2.

- Error number: [MY-010809](#); Symbol: [ER\\_BINLOG\\_FILE\\_BEING\\_READ\\_NOT\\_PURGED](#); SQLSTATE: [HY000](#)

Message: file %s was not purged because it was being read by thread number %u

[ER\\_BINLOG\\_FILE\\_BEING\\_READ\\_NOT\\_PURGED](#) was added in 8.0.2.

- 
- Error number: [MY-010810](#); Symbol: [ER\\_BINLOG\\_IO\\_ERROR\\_READING\\_HEADER](#); SQLSTATE: [HY000](#)  
Message: I/O error reading the header from the binary log, errno=%d, io cache code=%d  
[ER\\_BINLOG\\_IO\\_ERROR\\_READING\\_HEADER](#) was added in 8.0.2.
  - Error number: [MY-010811](#); Symbol: [ER\\_BINLOG\\_CANT\\_OPEN\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Failed to open log (file '%s', errno %d)  
[ER\\_BINLOG\\_CANT\\_OPEN\\_LOG](#) was added in 8.0.2, removed after 8.0.12.
  - Error number: [MY-010812](#); Symbol: [ER\\_BINLOG\\_CANT\\_CREATE\\_CACHE\\_FOR\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Failed to create a cache on log (file '%s')  
[ER\\_BINLOG\\_CANT\\_CREATE\\_CACHE\\_FOR\\_LOG](#) was added in 8.0.2, removed after 8.0.12.
  - Error number: [MY-010813](#); Symbol: [ER\\_BINLOG\\_FILE\\_EXTENSION\\_NUMBER\\_EXHAUSTED](#); SQLSTATE: [HY000](#)  
Message: Log filename extension number exhausted: %06lu. Please fix this by archiving old logs and updating the index files.  
[ER\\_BINLOG\\_FILE\\_EXTENSION\\_NUMBER\\_EXHAUSTED](#) was added in 8.0.2.
  - Error number: [MY-010814](#); Symbol: [ER\\_BINLOG\\_FILE\\_NAME\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
Message: Log filename too large: %s%s (%zu). Please fix this by archiving old logs and updating the index files.  
[ER\\_BINLOG\\_FILE\\_NAME\\_TOO\\_LONG](#) was added in 8.0.2.
  - Error number: [MY-010815](#); Symbol: [ER\\_BINLOG\\_FILE\\_EXTENSION\\_NUMBER\\_RUNNING\\_LOW](#); SQLSTATE: [HY000](#)  
Message: Next log extension: %lu. Remaining log filename extensions: %lu. Please consider archiving some logs.  
[ER\\_BINLOG\\_FILE\\_EXTENSION\\_NUMBER\\_RUNNING\\_LOW](#) was added in 8.0.2.
  - Error number: [MY-010816](#); Symbol: [ER\\_BINLOG\\_CANT\\_OPEN\\_FOR\\_LOGGING](#); SQLSTATE: [HY000](#)  
Message: Could not open %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.  
[ER\\_BINLOG\\_CANT\\_OPEN\\_FOR\\_LOGGING](#) was added in 8.0.2.
  - Error number: [MY-010817](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_SYNC\\_INDEX\\_FILE](#); SQLSTATE: [HY000](#)  
Message: MYSQL\_BIN\_LOG::open\_index\_file failed to sync the index file.  
[ER\\_BINLOG\\_FAILED\\_TO\\_SYNC\\_INDEX\\_FILE](#) was added in 8.0.2.
  - Error number: [MY-010818](#); Symbol: [ER\\_BINLOG\\_ERROR\\_READING\\_GTIDS\\_FROM\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)



---

Message: Error reading GTIDs from relaylog: %d

[ER\\_BINLOG\\_ERROR\\_READING\\_GTIDS\\_FROM\\_RELAY\\_LOG](#) was added in 8.0.2.

- Error number: [MY-010819](#); Symbol: [ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_RELAY\\_LOG\\_INFO](#); SQLSTATE: [HY000](#)

Message: %lu events read in relaylog file '%s' for updating Retrieved\_Gtid\_Set and/or IO thread transaction parser state.

[ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_RELAY\\_LOG\\_INFO](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010819](#); Symbol: [ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_APPLIER\\_METADATA](#); SQLSTATE: [HY000](#)

Message: %lu events read in relaylog file '%s' for updating Retrieved\_Gtid\_Set and/or IO thread transaction parser state.

[ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_APPLIER\\_METADATA](#) was added in 8.0.33.

- Error number: [MY-010820](#); Symbol: [ER\\_BINLOG\\_ERROR\\_READING\\_GTIDS\\_FROM\\_BINARY\\_LOG](#); SQLSTATE: [HY000](#)

Message: Error reading GTIDs from binary log: %d

[ER\\_BINLOG\\_ERROR\\_READING\\_GTIDS\\_FROM\\_BINARY\\_LOG](#) was added in 8.0.2.

- Error number: [MY-010821](#); Symbol: [ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_BINLOG\\_INFO](#); SQLSTATE: [HY000](#)

Message: Read %lu events from binary log file '%s' to determine the GTIDs purged from binary logs.

[ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_BINLOG\\_INFO](#) was added in 8.0.2.

- Error number: [MY-010822](#); Symbol: [ER\\_BINLOG\\_CANT\\_GENERATE\\_NEW\\_FILE\\_NAME](#); SQLSTATE: [HY000](#)

Message: MYSQL\_BIN\_LOG::open failed to generate new file name.

[ER\\_BINLOG\\_CANT\\_GENERATE\\_NEW\\_FILE\\_NAME](#) was added in 8.0.2.

- Error number: [MY-010823](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_SYNC\\_INDEX\\_FILE\\_IN\\_OPEN](#); SQLSTATE: [HY000](#)

Message: MYSQL\_BIN\_LOG::open failed to sync the index file.

[ER\\_BINLOG\\_FAILED\\_TO\\_SYNC\\_INDEX\\_FILE\\_IN\\_OPEN](#) was added in 8.0.2.

- Error number: [MY-010824](#); Symbol: [ER\\_BINLOG\\_CANT\\_USE\\_FOR\\_LOGGING](#); SQLSTATE: [HY000](#)

Message: Could not use %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.

[ER\\_BINLOG\\_CANT\\_USE\\_FOR\\_LOGGING](#) was added in 8.0.2.

- Error number: [MY-010825](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_CLOSE\\_INDEX\\_FILE\\_WHILE\\_REBUILDING](#); SQLSTATE: [HY000](#)

---

Message: While rebuilding index file %s: Failed to close the index file.

`ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING` was added in 8.0.2.

- Error number: `MY-010826`; Symbol: `ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING`; SQLSTATE: `HY000`

Message: While rebuilding index file %s: Failed to delete the existing index file. It could be that file is being used by some other process.

`ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING` was added in 8.0.2.

- Error number: `MY-010827`; Symbol: `ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING`; SQLSTATE: `HY000`

Message: While rebuilding index file %s: Failed to rename the new index file to the existing index file.

`ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING` was added in 8.0.2.

- Error number: `MY-010828`; Symbol: `ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING`; SQLSTATE: `HY000`

Message: After rebuilding the index file %s: Failed to open the index file.

`ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING` was added in 8.0.2.

- Error number: `MY-010829`; Symbol: `ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX`; SQLSTATE: `HY000`

Message: MYSQL\_BIN\_LOG::add\_log\_to\_index failed to append log file name: %s, to crash safe index file.

`ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX` was added in 8.0.2.

- Error number: `MY-010830`; Symbol: `ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES`; SQLSTATE: `HY000`

Message: Failed to locate old binlog or relay log files

`ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES` was added in 8.0.2.

- Error number: `MY-010831`; Symbol: `ER_BINLOG_CANT_DELETE_FILE`; SQLSTATE: `HY000`

Message: Failed to delete file '%s'

`ER_BINLOG_CANT_DELETE_FILE` was added in 8.0.2.

- Error number: `MY-010832`; Symbol: `ER_BINLOG_CANT_SET_TMP_INDEX_NAME`; SQLSTATE: `HY000`

Message: MYSQL\_BIN\_LOG::set\_crash\_safe\_index\_file\_name failed to set file name.

`ER_BINLOG_CANT_SET_TMP_INDEX_NAME` was added in 8.0.2.

- 
- Error number: [MY-010833](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_OPEN\\_TEMPORARY\\_INDEX\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: MYSQL\_BIN\_LOG::open\_crash\_safe\_index\_file failed to open temporary index file.  
  
[ER\\_BINLOG\\_FAILED\\_TO\\_OPEN\\_TEMPORARY\\_INDEX\\_FILE](#) was added in 8.0.2.
  - Error number: [MY-010834](#); Symbol: [ER\\_BINLOG\\_ERROR\\_GETTING\\_NEXT\\_LOG\\_FROM\\_INDEX](#); SQLSTATE: [HY000](#)  
  
Message: next log error: %d offset: %s log: %s included: %d  
  
[ER\\_BINLOG\\_ERROR\\_GETTING\\_NEXT\\_LOG\\_FROM\\_INDEX](#) was added in 8.0.2, removed after 8.0.12.
  - Error number: [MY-010835](#); Symbol: [ER\\_BINLOG\\_CANT\\_OPEN\\_TMP\\_INDEX](#); SQLSTATE: [HY000](#)  
  
Message: %s failed to open the crash safe index file.  
  
[ER\\_BINLOG\\_CANT\\_OPEN\\_TMP\\_INDEX](#) was added in 8.0.2.
  - Error number: [MY-010836](#); Symbol: [ER\\_BINLOG\\_CANT\\_COPY\\_INDEX\\_TO\\_TMP](#); SQLSTATE: [HY000](#)  
  
Message: %s failed to copy index file to crash safe index file.  
  
[ER\\_BINLOG\\_CANT\\_COPY\\_INDEX\\_TO\\_TMP](#) was added in 8.0.2.
  - Error number: [MY-010837](#); Symbol: [ER\\_BINLOG\\_CANT\\_CLOSE\\_TMP\\_INDEX](#); SQLSTATE: [HY000](#)  
  
Message: %s failed to close the crash safe index file.  
  
[ER\\_BINLOG\\_CANT\\_CLOSE\\_TMP\\_INDEX](#) was added in 8.0.2.
  - Error number: [MY-010838](#); Symbol: [ER\\_BINLOG\\_CANT\\_MOVE\\_TMP\\_TO\\_INDEX](#); SQLSTATE: [HY000](#)  
  
Message: %s failed to move crash safe index file to index file.  
  
[ER\\_BINLOG\\_CANT\\_MOVE\\_TMP\\_TO\\_INDEX](#) was added in 8.0.2.
  - Error number: [MY-010839](#); Symbol: [ER\\_BINLOG\\_PURGE\\_LOGS\\_CALLED\\_WITH\\_FILE\\_NOT\\_IN\\_INDEX](#); SQLSTATE: [HY000](#)  
  
Message: MYSQL\_BIN\_LOG::purge\_logs was called with file %s not listed in the index.  
  
[ER\\_BINLOG\\_PURGE\\_LOGS\\_CALLED\\_WITH\\_FILE\\_NOT\\_IN\\_INDEX](#) was added in 8.0.2.
  - Error number: [MY-010840](#); Symbol: [ER\\_BINLOG\\_PURGE\\_LOGS\\_CANT\\_SYNC\\_INDEX\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: MYSQL\_BIN\_LOG::purge\_logs failed to sync the index file.  
  
[ER\\_BINLOG\\_PURGE\\_LOGS\\_CANT\\_SYNC\\_INDEX\\_FILE](#) was added in 8.0.2.
  - Error number: [MY-010841](#); Symbol: [ER\\_BINLOG\\_PURGE\\_LOGS\\_CANT\\_COPY\\_TO\\_REGISTER\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: MYSQL\_BIN\_LOG::purge\_logs failed to copy %s to register file.

- 
- Error number: [MY-010842](#); Symbol: [ER\\_BINLOG\\_PURGE\\_LOGS\\_CANT\\_FLUSH\\_REGISTER\\_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL\_BIN\_LOG::purge\_logs failed to flush register file.

[ER\\_BINLOG\\_PURGE\\_LOGS\\_CANT\\_FLUSH\\_REGISTER\\_FILE](#) was added in 8.0.2.

- Error number: [MY-010843](#); Symbol: [ER\\_BINLOG\\_PURGE\\_LOGS\\_CANT\\_UPDATE\\_INDEX\\_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL\_BIN\_LOG::purge\_logs failed to update the index file

[ER\\_BINLOG\\_PURGE\\_LOGS\\_CANT\\_UPDATE\\_INDEX\\_FILE](#) was added in 8.0.2.

- Error number: [MY-010844](#); Symbol: [ER\\_BINLOG\\_PURGE\\_LOGS\\_FAILED\\_TO\\_PURGE\\_LOG](#); SQLSTATE: [HY000](#)

Message: MYSQL\_BIN\_LOG::purge\_logs failed to process registered files that would be purged.

[ER\\_BINLOG\\_PURGE\\_LOGS\\_FAILED\\_TO\\_PURGE\\_LOG](#) was added in 8.0.2.

- Error number: [MY-010845](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_SET\\_PURGE\\_INDEX\\_FILE\\_NAME](#); SQLSTATE: [HY000](#)

Message: MYSQL\_BIN\_LOG::set\_purge\_index\_file\_name failed to set file name.

[ER\\_BINLOG\\_FAILED\\_TO\\_SET\\_PURGE\\_INDEX\\_FILE\\_NAME](#) was added in 8.0.2.

- Error number: [MY-010846](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_OPEN\\_REGISTER\\_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL\_BIN\_LOG::open\_purge\_index\_file failed to open register file.

[ER\\_BINLOG\\_FAILED\\_TO\\_OPEN\\_REGISTER\\_FILE](#) was added in 8.0.2.

- Error number: [MY-010847](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_REINIT\\_REGISTER\\_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL\_BIN\_LOG::purge\_index\_entry failed to reinit register file for read

[ER\\_BINLOG\\_FAILED\\_TO\\_REINIT\\_REGISTER\\_FILE](#) was added in 8.0.2.

- Error number: [MY-010848](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_READ\\_REGISTER\\_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL\_BIN\_LOG::purge\_index\_entry error %d reading from register file.

[ER\\_BINLOG\\_FAILED\\_TO\\_READ\\_REGISTER\\_FILE](#) was added in 8.0.2.

- Error number: [MY-010849](#); Symbol: [ER\\_CANT\\_STAT\\_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to execute mysql\_file\_stat on file '%s'

[ER\\_CANT\\_STAT\\_FILE](#) was added in 8.0.2.

- 
- Error number: `MY-010850`; Symbol: `ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILES`; SQLSTATE: `HY000`  
  
Message: Failed to delete log file '%s'; consider examining correspondence of your binlog index file to the actual binlog files  
  
`ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILES` was added in 8.0.2.
  - Error number: `MY-010851`; Symbol: `ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX`; SQLSTATE: `HY000`  
  
Message: Failed to delete file '%s' and read the binlog index file  
  
`ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX` was added in 8.0.2.
  - Error number: `MY-010852`; Symbol: `ER_BINLOG_FAILED_TO_DELETE_LOG_FILE`; SQLSTATE: `HY000`  
  
Message: Failed to delete log file '%s'  
  
`ER_BINLOG_FAILED_TO_DELETE_LOG_FILE` was added in 8.0.2.
  - Error number: `MY-010853`; Symbol: `ER_BINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES`; SQLSTATE: `HY000`  
  
Message: %s An incident event has been written to the binary log which will stop the slaves.  
  
`ER_BINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010853`; Symbol: `ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS`; SQLSTATE: `HY000`  
  
Message: %s An incident event has been written to the binary log which will stop the replicas.  
  
`ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS` was added in 8.0.33.
  - Error number: `MY-010854`; Symbol: `ER_BINLOG_CANT_FIND_LOG_IN_INDEX`; SQLSTATE: `HY000`  
  
Message: `find_log_pos()` failed (error: %d)  
  
`ER_BINLOG_CANT_FIND_LOG_IN_INDEX` was added in 8.0.2.
  - Error number: `MY-010855`; Symbol: `ER_BINLOG_RECOVERING_AFTER_CRASH_USING`; SQLSTATE: `HY000`  
  
Message: Recovering after a crash using %s  
  
`ER_BINLOG_RECOVERING_AFTER_CRASH_USING` was added in 8.0.2.
  - Error number: `MY-010856`; Symbol: `ER_BINLOG_CANT_OPEN_CRASHED_BINLOG`; SQLSTATE: `HY000`  
  
Message: Failed to open the crashed binlog file when source server is recovering it.  
  
`ER_BINLOG_CANT_OPEN_CRASHED_BINLOG` was added in 8.0.2.

- 
- Error number: [MY-010857](#); Symbol: [ER\\_BINLOG\\_CANT\\_TRIM\\_CRASHED\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Failed to trim the crashed binlog file when source server is recovering it.  
[ER\\_BINLOG\\_CANT\\_TRIM\\_CRASHED\\_BINLOG](#) was added in 8.0.2.
  - Error number: [MY-010858](#); Symbol: [ER\\_BINLOG\\_CRASHED\\_BINLOG\\_TRIMMED](#); SQLSTATE: [HY000](#)  
Message: Crashed binlog file %s size is %llu, but recovered up to %llu. Binlog trimmed to %llu bytes.  
[ER\\_BINLOG\\_CRASHED\\_BINLOG\\_TRIMMED](#) was added in 8.0.2.
  - Error number: [MY-010859](#); Symbol: [ER\\_BINLOG\\_CANT\\_CLEAR\\_IN\\_USE\\_FLAG\\_FOR\\_CRASHED\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Failed to clear LOG\_EVENT\_BINLOG\_IN\_USE\_F for the crashed binlog file when source server is recovering it.  
[ER\\_BINLOG\\_CANT\\_CLEAR\\_IN\\_USE\\_FLAG\\_FOR\\_CRASHED\\_BINLOG](#) was added in 8.0.2.
  - Error number: [MY-010860](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_RUN\\_AFTER\\_SYNC\\_HOOK](#); SQLSTATE: [HY000](#)  
Message: Failed to run 'after\_sync' hooks  
[ER\\_BINLOG\\_FAILED\\_TO\\_RUN\\_AFTER\\_SYNC\\_HOOK](#) was added in 8.0.2.
  - Error number: [MY-010861](#); Symbol: [ER\\_TURNING\\_LOGGING\\_OFF\\_FOR\\_THE\\_DURATION](#); SQLSTATE: [HY000](#)  
Message: %s Hence turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.  
[ER\\_TURNING\\_LOGGING\\_OFF\\_FOR\\_THE\\_DURATION](#) was added in 8.0.2.
  - Error number: [MY-010862](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_RUN\\_AFTER\\_FLUSH\\_HOOK](#); SQLSTATE: [HY000](#)  
Message: Failed to run 'after\_flush' hooks  
[ER\\_BINLOG\\_FAILED\\_TO\\_RUN\\_AFTER\\_FLUSH\\_HOOK](#) was added in 8.0.2.
  - Error number: [MY-010863](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error) and restart, or delete (or rename) binary log and start mysqld with --tc-heuristic-recover={commit|rollback}  
[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_FAILED](#) was added in 8.0.2, removed after 8.0.29.
  - Error number: [MY-010864](#); Symbol: [ER\\_BINLOG\\_WARNING\\_SUPPRESSED](#); SQLSTATE: [HY000](#)  
Message: The following warning was suppressed %d times during the last %d seconds in the error log  
[ER\\_BINLOG\\_WARNING\\_SUPPRESSED](#) was added in 8.0.2.

- 
- Error number: [MY-010865](#); Symbol: [ER\\_NDB\\_LOG\\_ENTRY](#); SQLSTATE: [HY000](#)  
Message: NDB: %s  
[ER\\_NDB\\_LOG\\_ENTRY](#) was added in 8.0.2.
  - Error number: [MY-010866](#); Symbol: [ER\\_NDB\\_LOG\\_ENTRY\\_WITH\\_PREFIX](#); SQLSTATE: [HY000](#)  
Message: NDB %s: %s  
[ER\\_NDB\\_LOG\\_ENTRY\\_WITH\\_PREFIX](#) was added in 8.0.2.
  - Error number: [MY-010867](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_PURGE\\_THD](#); SQLSTATE: [HY000](#)  
Message: NDB: Unable to purge %s.%s File=%s (failed to setup thd)  
[ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_PURGE\\_THD](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010868](#); Symbol: [ER\\_INNODB\\_UNKNOWN\\_COLLATION](#); SQLSTATE: [HY000](#)  
Message: Unknown collation #%lu.  
[ER\\_INNODB\\_UNKNOWN\\_COLLATION](#) was added in 8.0.2.
  - Error number: [MY-010869](#); Symbol: [ER\\_INNODB\\_INVALID\\_LOG\\_GROUP\\_HOME\\_DIR](#); SQLSTATE: [HY000](#)  
Message: syntax error in innodb\_log\_group\_home\_dir  
[ER\\_INNODB\\_INVALID\\_LOG\\_GROUP\\_HOME\\_DIR](#) was added in 8.0.2.
  - Error number: [MY-010870](#); Symbol: [ER\\_INNODB\\_INVALID\\_INNODB\\_UNDO\\_DIRECTORY](#); SQLSTATE: [HY000](#)  
Message: syntax error in innodb\_undo\_directory  
[ER\\_INNODB\\_INVALID\\_INNODB\\_UNDO\\_DIRECTORY](#) was added in 8.0.2.
  - Error number: [MY-010871](#); Symbol: [ER\\_INNODB\\_ILLEGAL\\_COLON\\_IN\\_POOL](#); SQLSTATE: [HY000](#)  
Message: InnoDB: innodb\_buffer\_pool\_filename cannot have colon (:) in the file name.  
[ER\\_INNODB\\_ILLEGAL\\_COLON\\_IN\\_POOL](#) was added in 8.0.2.
  - Error number: [MY-010872](#); Symbol: [ER\\_INNODB\\_INVALID\\_PAGE\\_SIZE](#); SQLSTATE: [HY000](#)  
Message: InnoDB: Invalid page size=%lu.  
[ER\\_INNODB\\_INVALID\\_PAGE\\_SIZE](#) was added in 8.0.2.
  - Error number: [MY-010873](#); Symbol: [ER\\_INNODB\\_DIRTY\\_WATER\\_MARK\\_NOT\\_LOW](#); SQLSTATE: [HY000](#)  
Message: InnoDB: innodb\_max\_dirty\_pages\_pct\_lwm cannot be set higher than innodb\_max\_dirty\_pages\_pct. Setting innodb\_max\_dirty\_pages\_pct\_lwm to %lf  
[ER\\_INNODB\\_DIRTY\\_WATER\\_MARK\\_NOT\\_LOW](#) was added in 8.0.2.
  - Error number: [MY-010874](#); Symbol: [ER\\_INNODB\\_IO\\_CAPACITY\\_EXCEEDS\\_MAX](#); SQLSTATE: [HY000](#)

---

Message: InnoDB: innodb\_io\_capacity cannot be set higher than innodb\_io\_capacity\_max. Setting innodb\_io\_capacity to %lu

[ER\\_INNODB\\_IO\\_CAPACITY\\_EXCEEDS\\_MAX](#) was added in 8.0.2.

- Error number: [MY-010875](#); Symbol: [ER\\_INNODB\\_FILES\\_SAME](#); SQLSTATE: [HY000](#)

Message: %s and %s file names seem to be the same.

[ER\\_INNODB\\_FILES\\_SAME](#) was added in 8.0.2.

- Error number: [MY-010876](#); Symbol: [ER\\_INNODB\\_UNREGISTERED\\_TRX\\_ACTIVE](#); SQLSTATE: [HY000](#)

Message: Transaction not registered for MySQL 2PC, but transaction is active

[ER\\_INNODB\\_UNREGISTERED\\_TRX\\_ACTIVE](#) was added in 8.0.2.

- Error number: [MY-010877](#); Symbol: [ER\\_INNODB\\_CLOSING\\_CONNECTION\\_ROLLS\\_BACK](#); SQLSTATE: [HY000](#)

Message: MySQL is closing a connection that has an active InnoDB transaction. %llu row modifications will roll back.

[ER\\_INNODB\\_CLOSING\\_CONNECTION\\_ROLLS\\_BACK](#) was added in 8.0.2.

- Error number: [MY-010878](#); Symbol: [ER\\_INNODB\\_TRX\\_XLATION\\_TABLE\\_OOM](#); SQLSTATE: [HY000](#)

Message: InnoDB: fail to allocate memory for index translation table. Number of Index:%lu, array size: %lu

[ER\\_INNODB\\_TRX\\_XLATION\\_TABLE\\_OOM](#) was added in 8.0.2.

- Error number: [MY-010879](#); Symbol: [ER\\_INNODB\\_CANT\\_FIND\\_INDEX\\_IN\\_INNODB\\_DD](#); SQLSTATE: [HY000](#)

Message: Cannot find index %s in InnoDB index dictionary.

[ER\\_INNODB\\_CANT\\_FIND\\_INDEX\\_IN\\_INNODB\\_DD](#) was added in 8.0.2.

- Error number: [MY-010880](#); Symbol: [ER\\_INNODB\\_INDEX\\_COLUMN\\_INFO\\_UNLIKE\\_MYSQLS](#); SQLSTATE: [HY000](#)

Message: Found index %s whose column info does not match that of MySQL.

[ER\\_INNODB\\_INDEX\\_COLUMN\\_INFO\\_UNLIKE\\_MYSQLS](#) was added in 8.0.2.

- Error number: [MY-010881](#); Symbol: [ER\\_INNODB\\_CANT\\_OPEN\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to open table %s.

[ER\\_INNODB\\_CANT\\_OPEN\\_TABLE](#) was added in 8.0.2, removed after 8.0.18.

- Error number: [MY-010882](#); Symbol: [ER\\_INNODB\\_CANT\\_BUILD\\_INDEX\\_XLATION\\_TABLE\\_FOR](#); SQLSTATE: [HY000](#)

Message: Build InnoDB index translation table for Table %s failed

[ER\\_INNODB\\_CANT\\_BUILD\\_INDEX\\_XLATION\\_TABLE\\_FOR](#) was added in 8.0.2.



- 
- Error number: [MY-010883](#); Symbol: [ER\\_INNODB\\_PK\\_NOT\\_IN\\_MYSQL](#); SQLSTATE: [HY000](#)  
Message: Table %s has a primary key in InnoDB data dictionary, but not in MySQL!  
[ER\\_INNODB\\_PK\\_NOT\\_IN\\_MYSQL](#) was added in 8.0.2.
  - Error number: [MY-010884](#); Symbol: [ER\\_INNODB\\_PK\\_ONLY\\_IN\\_MYSQL](#); SQLSTATE: [HY000](#)  
Message: Table %s has no primary key in InnoDB data dictionary, but has one in MySQL! If you created the table with a MySQL version < 3.23.54 and did not define a primary key, but defined a unique key with all non-NULL columns, then MySQL internally treats that key as the primary key. You can fix this error by dump + DROP + CREATE + reimport of the table.  
[ER\\_INNODB\\_PK\\_ONLY\\_IN\\_MYSQL](#) was added in 8.0.2.
  - Error number: [MY-010885](#); Symbol: [ER\\_INNODB\\_CLUSTERED\\_INDEX\\_PRIVATE](#); SQLSTATE: [HY000](#)  
Message: Table %s key\_used\_on\_scan is %lu even though there is no primary key inside InnoDB.  
[ER\\_INNODB\\_CLUSTERED\\_INDEX\\_PRIVATE](#) was added in 8.0.2.
  - Error number: [MY-010886](#); Symbol: [ER\\_INNODB\\_PARTITION\\_TABLE\\_LOWERCASED](#); SQLSTATE: [HY000](#)  
Message: Partition table %s opened after converting to lower case. The table may have been moved from a case-insensitive file system. Please recreate the table in the current file system.  
[ER\\_INNODB\\_PARTITION\\_TABLE\\_LOWERCASED](#) was added in 8.0.2, removed after 8.0.18.
  - Error number: [MY-010887](#); Symbol: [ER\\_ERRMSG\\_REPLACEMENT\\_DODGY](#); SQLSTATE: [HY000](#)  
Message: Cannot replace error message (%s,%s,%s) "%s" with "%s"; wrong number or type of %% substitutions.  
[ER\\_ERRMSG\\_REPLACEMENT\\_DODGY](#) was added in 8.0.2.
  - Error number: [MY-010888](#); Symbol: [ER\\_ERRMSG\\_REPLACEMENTS\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Table for error message replacements could not be found or read, or one or more replacements could not be applied.  
[ER\\_ERRMSG\\_REPLACEMENTS\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010889](#); Symbol: [ER\\_NPIPE\\_CANT\\_CREATE](#); SQLSTATE: [HY000](#)  
Message: %s: %s  
[ER\\_NPIPE\\_CANT\\_CREATE](#) was added in 8.0.2.
  - Error number: [MY-010890](#); Symbol: [ER\\_PARTITION\\_MOVE\\_CREATED\\_DUPLICATE\\_ROW\\_PLEASE\\_FIX](#); SQLSTATE: [HY000](#)  
Message: Table '%s': Delete from part %d failed with error %d. But it was already inserted into part %d, when moving the misplaced row! Please manually fix the duplicate row: %s  
[ER\\_PARTITION\\_MOVE\\_CREATED\\_DUPLICATE\\_ROW\\_PLEASE\\_FIX](#) was added in 8.0.2.
  - Error number: [MY-010891](#); Symbol: [ER\\_AUDIT\\_CANT\\_ABORT\\_COMMAND](#); SQLSTATE: [HY000](#)

---

Message: Command '%s' cannot be aborted. The trigger error was (%d) [%s]: %s

[ER\\_AUDIT\\_CANT\\_ABORT\\_COMMAND](#) was added in 8.0.2.

- Error number: [MY-010892](#); Symbol: [ER\\_AUDIT\\_CANT\\_ABORT\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Event '%s' cannot be aborted. The trigger error was (%d) [%s]: %s

[ER\\_AUDIT\\_CANT\\_ABORT\\_EVENT](#) was added in 8.0.2.

- Error number: [MY-010893](#); Symbol: [ER\\_AUDIT\\_WARNING](#); SQLSTATE: [HY000](#)

Message: %s. The trigger error was (%d) [%s]: %s

[ER\\_AUDIT\\_WARNING](#) was added in 8.0.2.

- Error number: [MY-010894](#); Symbol: [ER\\_NDB\\_NUMBER\\_OF\\_CHANNELS](#); SQLSTATE: [HY000](#)

Message: Slave SQL: Configuration with number of replication masters = %u' is not supported when applying to Ndb

[ER\\_NDB\\_NUMBER\\_OF\\_CHANNELS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010895](#); Symbol: [ER\\_NDB\\_SLAVE\\_PARALLEL\\_WORKERS](#); SQLSTATE: [HY000](#)

Message: Slave SQL: Configuration 'slave\_parallel\_workers = %lu' is not supported when applying to Ndb

[ER\\_NDB\\_SLAVE\\_PARALLEL\\_WORKERS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010896](#); Symbol: [ER\\_NDB\\_DISTRIBUTING\\_ERR](#); SQLSTATE: [HY000](#)

Message: NDB %s: distributing %s err: %u

[ER\\_NDB\\_DISTRIBUTING\\_ERR](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010897](#); Symbol: [ER\\_RPL\\_SLAVE\\_INSECURE\\_CHANGE\\_MASTER](#); SQLSTATE: [HY000](#)

Message: Storing MySQL user name or password information in the master info repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START SLAVE; see the 'START SLAVE Syntax' in the MySQL Manual for more information.

[ER\\_RPL\\_SLAVE\\_INSECURE\\_CHANGE\\_MASTER](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-010897](#); Symbol: [ER\\_RPL\\_REPLICA\\_INSECURE\\_CHANGE\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Storing MySQL user name or password information in the connection metadata repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START REPLICA; see the 'START REPLICA Syntax' in the MySQL Manual for more information.

[ER\\_RPL\\_REPLICA\\_INSECURE\\_CHANGE\\_SOURCE](#) was added in 8.0.33.

- Error number: [MY-010898](#); Symbol: [ER\\_RPL\\_SLAVE\\_FLUSH\\_RELAY\\_LOGS\\_NOT\\_ALLOWED](#); SQLSTATE: [HY000](#)

---

Message: FLUSH RELAY LOGS cannot be performed on channel '%s'.

[ER\\_RPL\\_SLAVE\\_FLUSH\\_RELAY\\_LOGS\\_NOT\\_ALLOWED](#) was added in 8.0.4, removed after 8.0.15.

- Error number: [MY-010899](#); Symbol: [ER\\_RPL\\_SLAVE\\_INCORRECT\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Slave channel '%s' does not exist.

[ER\\_RPL\\_SLAVE\\_INCORRECT\\_CHANNEL](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-010899](#); Symbol: [ER\\_RPL\\_REPLICA\\_INCORRECT\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Replica channel '%s' does not exist.

[ER\\_RPL\\_REPLICA\\_INCORRECT\\_CHANNEL](#) was added in 8.0.33.

- Error number: [MY-010900](#); Symbol: [ER\\_FAILED\\_TO\\_FIND\\_DL\\_ENTRY](#); SQLSTATE: [HY000](#)

Message: Can't find symbol '%s' in library.

[ER\\_FAILED\\_TO\\_FIND\\_DL\\_ENTRY](#) was added in 8.0.4.

- Error number: [MY-010901](#); Symbol: [ER\\_FAILED\\_TO\\_OPEN\\_SHARED\\_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Can't open shared library '%s' (errno: %d %s).

[ER\\_FAILED\\_TO\\_OPEN\\_SHARED\\_LIBRARY](#) was added in 8.0.4.

- Error number: [MY-010902](#); Symbol: [ER\\_THREAD\\_PRIORITY\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: Thread priority attribute setting in Resource Group SQL shall be ignored due to unsupported platform or insufficient privilege.

[ER\\_THREAD\\_PRIORITY\\_IGNORED](#) was added in 8.0.4.

- Error number: [MY-010903](#); Symbol: [ER\\_BINLOG\\_CACHE\\_SIZE\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)

Message: Option binlog\_cache\_size (%lu) is greater than max\_binlog\_cache\_size (%lu); setting binlog\_cache\_size equal to max\_binlog\_cache\_size.

[ER\\_BINLOG\\_CACHE\\_SIZE\\_TOO\\_LARGE](#) was added in 8.0.4.

- Error number: [MY-010904](#); Symbol: [ER\\_BINLOG\\_STMT\\_CACHE\\_SIZE\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)

Message: Option binlog\_stmt\_cache\_size (%lu) is greater than max\_binlog\_stmt\_cache\_size (%lu); setting binlog\_stmt\_cache\_size equal to max\_binlog\_stmt\_cache\_size.

[ER\\_BINLOG\\_STMT\\_CACHE\\_SIZE\\_TOO\\_LARGE](#) was added in 8.0.4.

- Error number: [MY-010905](#); Symbol: [ER\\_FAILED\\_TO\\_GENERATE\\_UNIQUE\\_LOGFILE](#); SQLSTATE: [HY000](#)

Message: Can't generate a unique log-filename %s.(1-999).

[ER\\_FAILED\\_TO\\_GENERATE\\_UNIQUE\\_LOGFILE](#) was added in 8.0.4.

- Error number: [MY-010906](#); Symbol: [ER\\_FAILED\\_TO\\_READ\\_FILE](#); SQLSTATE: [HY000](#)

---

Message: Error reading file '%s' (errno: %d - %s)

[ER\\_FAILED\\_TO\\_READ\\_FILE](#) was added in 8.0.4.

- Error number: [MY-010907](#); Symbol: [ER\\_FAILED\\_TO\\_WRITE\\_TO\\_FILE](#); SQLSTATE: [HY000](#)

Message: Error writing file '%s' (errno: %d - %s)

[ER\\_FAILED\\_TO\\_WRITE\\_TO\\_FILE](#) was added in 8.0.4.

- Error number: [MY-010908](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_MESSAGE\\_AND\\_STATEMENT](#); SQLSTATE: [HY000](#)

Message: %s Statement: %s

[ER\\_BINLOG\\_UNSAFE\\_MESSAGE\\_AND\\_STATEMENT](#) was added in 8.0.4.

- Error number: [MY-010909](#); Symbol: [ER\\_FORCE\\_CLOSE\\_THREAD](#); SQLSTATE: [HY000](#)

Message: %s: Forcing close of thread %ld user: '%s'.

[ER\\_FORCE\\_CLOSE\\_THREAD](#) was added in 8.0.4.

- Error number: [MY-010910](#); Symbol: [ER\\_SERVER\\_SHUTDOWN\\_COMPLETE](#); SQLSTATE: [HY000](#)

Message: %s: Shutdown complete (mysqld %s) %s.

[ER\\_SERVER\\_SHUTDOWN\\_COMPLETE](#) was added in 8.0.4.

- Error number: [MY-010911](#); Symbol: [ER\\_RPL\\_CANT\\_HAVE\\_SAME\\_BASENAME](#); SQLSTATE: [HY000](#)

Message: Cannot have same base name '%s' for both binary and relay logs. Please check %s (default '%s' if --log-bin option is not used, default '%s' if --log-bin option is used without argument) and %s (default '%s') options to ensure they do not conflict.

[ER\\_RPL\\_CANT\\_HAVE\\_SAME\\_BASENAME](#) was added in 8.0.3.

- Error number: [MY-010912](#); Symbol:

[ER\\_RPL\\_GTID\\_MODE\\_REQUIRES\\_ENFORCE\\_GTID\\_CONSISTENCY\\_ON](#); SQLSTATE: [HY000](#)

Message: GTID\_MODE = ON requires ENFORCE\_GTID\_CONSISTENCY = ON.

[ER\\_RPL\\_GTID\\_MODE\\_REQUIRES\\_ENFORCE\\_GTID\\_CONSISTENCY\\_ON](#) was added in 8.0.4.

- Error number: [MY-010913](#); Symbol: [ER\\_WARN\\_NO\\_SERVERID\\_SPECIFIED](#); SQLSTATE: [HY000](#)

Message: You have not provided a mandatory server-id. Servers in a replication topology must have unique server-ids. Please refer to the proper server start-up parameters documentation.

[ER\\_WARN\\_NO\\_SERVERID\\_SPECIFIED](#) was added in 8.0.3.

- Error number: [MY-010914](#); Symbol: [ER\\_ABORTING\\_USER\\_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).

[ER\\_ABORTING\\_USER\\_CONNECTION](#) was added in 8.0.4.

- Error number: [MY-010915](#); Symbol: [ER\\_SQL\\_MODE\\_MERGED\\_WITH\\_STRICT\\_MODE](#); SQLSTATE: [HY000](#)

---

Message: 'NO\_ZERO\_DATE', 'NO\_ZERO\_IN\_DATE' and 'ERROR\_FOR\_DIVISION\_BY\_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.

[ER\\_SQL\\_MODE\\_MERGED\\_WITH\\_STRICT\\_MODE](#) was added in 8.0.4.

- Error number: [MY-010916](#); Symbol: [ER\\_GTID\\_PURGED\\_WAS\\_UPDATED](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID\_PURGED was changed from '%s' to '%s'.

[ER\\_GTID\\_PURGED\\_WAS\\_UPDATED](#) was added in 8.0.4.

- Error number: [MY-010917](#); Symbol: [ER\\_GTID\\_EXECUTED\\_WAS\\_UPDATED](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID\_EXECUTED was changed from '%s' to '%s'.

[ER\\_GTID\\_EXECUTED\\_WAS\\_UPDATED](#) was added in 8.0.4.

- Error number: [MY-010918](#); Symbol: [ER\\_DEPRECATED\\_MSG\\_WITH\\_REPLACEMENT](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead.

[ER\\_DEPRECATED\\_MSG\\_WITH\\_REPLACEMENT](#) was added in 8.0.4.

- Error number: [MY-010919](#); Symbol: [ER\\_TRG\\_CREATION\\_CTX\\_NOT\\_SET](#); SQLSTATE: [HY000](#)

Message: Triggers for table `%s`.`%s` have no creation context

[ER\\_TRG\\_CREATION\\_CTX\\_NOT\\_SET](#) was added in 8.0.4.

- Error number: [MY-010920](#); Symbol: [ER\\_FILE\\_HAS\\_OLD\\_FORMAT](#); SQLSTATE: [HY000](#)

Message: '%s' has an old format, you should re-create the '%s' object(s)

[ER\\_FILE\\_HAS\\_OLD\\_FORMAT](#) was added in 8.0.4.

- Error number: [MY-010921](#); Symbol: [ER\\_VIEW\\_CREATION\\_CTX\\_NOT\\_SET](#); SQLSTATE: [HY000](#)

Message: View `%s`.`%s` has no creation context

[ER\\_VIEW\\_CREATION\\_CTX\\_NOT\\_SET](#) was added in 8.0.4.

- Error number: [MY-010923](#); Symbol: [ER\\_TABLE\\_UPGRADE\\_REQUIRED](#); SQLSTATE: [HY000](#)

Message: Table upgrade required. Please do "REPAIR TABLE `%s`" or dump/reload to fix it!

[ER\\_TABLE\\_UPGRADE\\_REQUIRED](#) was added in 8.0.4.

- Error number: [MY-010924](#); Symbol: [ER\\_GET\\_ERRNO\\_FROM\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' from storage engine.

[ER\\_GET\\_ERRNO\\_FROM\\_STORAGE\\_ENGINE](#) was added in 8.0.4.

- Error number: [MY-010925](#); Symbol: [ER\\_ACCESS\\_DENIED\\_ERROR\\_WITHOUT\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'

[ER\\_ACCESS\\_DENIED\\_ERROR\\_WITHOUT\\_PASSWORD](#) was added in 8.0.4.

- 
- Error number: [MY-010926](#); Symbol: [ER\\_ACCESS\\_DENIED\\_ERROR\\_WITH\\_PASSWORD](#); SQLSTATE: [HY000](#)  
Message: Access denied for user '%s'@'%s' (using password: %s)  
[ER\\_ACCESS\\_DENIED\\_ERROR\\_WITH\\_PASSWORD](#) was added in 8.0.4.
  - Error number: [MY-010927](#); Symbol: [ER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_LOCKED](#); SQLSTATE: [HY000](#)  
Message: Access denied for user '%s'@'%s'. Account is locked.  
[ER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_LOCKED](#) was added in 8.0.4.
  - Error number: [MY-010928](#); Symbol: [ER\\_MUST\\_CHANGE\\_EXPIRED\\_PASSWORD](#); SQLSTATE: [HY000](#)  
Message: Your password has expired. To log in you must change it using a client that supports expired passwords.  
[ER\\_MUST\\_CHANGE\\_EXPIRED\\_PASSWORD](#) was added in 8.0.4, removed after 8.0.28.
  - Error number: [MY-010929](#); Symbol: [ER\\_SYSTEM\\_TABLES\\_NOT\\_SUPPORTED\\_BY\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Storage engine '%s' does not support system tables. [%s.%s].  
[ER\\_SYSTEM\\_TABLES\\_NOT\\_SUPPORTED\\_BY\\_STORAGE\\_ENGINE](#) was added in 8.0.4.
  - Error number: [MY-010930](#); Symbol: [ER\\_FILESORT\\_TERMINATED](#); SQLSTATE: [HY000](#)  
Message: Sort aborted  
[ER\\_FILESORT\\_TERMINATED](#) was added in 8.0.4, removed after 8.0.18.
  - Error number: [MY-010931](#); Symbol: [ER\\_SERVER\\_STARTUP\\_MSG](#); SQLSTATE: [HY000](#)  
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s.  
[ER\\_SERVER\\_STARTUP\\_MSG](#) was added in 8.0.4.
  - Error number: [MY-010932](#); Symbol: [ER\\_FAILED\\_TO\\_FIND\\_LOCALE\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Unknown locale: '%s'.  
[ER\\_FAILED\\_TO\\_FIND\\_LOCALE\\_NAME](#) was added in 8.0.4.
  - Error number: [MY-010933](#); Symbol: [ER\\_FAILED\\_TO\\_FIND\\_COLLATION\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Unknown collation: '%s'.  
[ER\\_FAILED\\_TO\\_FIND\\_COLLATION\\_NAME](#) was added in 8.0.4.
  - Error number: [MY-010934](#); Symbol: [ER\\_SERVER\\_OUT\\_OF\\_RESOURCES](#); SQLSTATE: [HY000](#)  
Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space  
[ER\\_SERVER\\_OUT\\_OF\\_RESOURCES](#) was added in 8.0.4.
  - Error number: [MY-010935](#); Symbol: [ER\\_SERVER\\_OUTOFMEMORY](#); SQLSTATE: [HY000](#)

---

Message: Out of memory; restart server and try again (needed %d bytes)

[ER\\_SERVER\\_OUTOFMEMORY](#) was added in 8.0.4.

- Error number: [MY-010936](#); Symbol: [ER\\_INVALID\\_COLLATION\\_FOR\\_CHARSET](#); SQLSTATE: [HY000](#)

Message: COLLATION '%s' is not valid for CHARACTER SET '%s'

[ER\\_INVALID\\_COLLATION\\_FOR\\_CHARSET](#) was added in 8.0.4.

- Error number: [MY-010937](#); Symbol: [ER\\_CANT\\_START\\_ERROR\\_LOG\\_SERVICE](#); SQLSTATE: [HY000](#)

Message: Failed to set %s at or around "%s" -- service is valid, but can not be initialized; please check its configuration and make sure it can read its input(s) and write to its output(s).

[ER\\_CANT\\_START\\_ERROR\\_LOG\\_SERVICE](#) was added in 8.0.4.

- Error number: [MY-010938](#); Symbol: [ER\\_CREATING\\_NEW\\_UUID\\_FIRST\\_START](#); SQLSTATE: [HY000](#)

Message: Generating a new UUID: %s.

[ER\\_CREATING\\_NEW\\_UUID\\_FIRST\\_START](#) was added in 8.0.4.

- Error number: [MY-010939](#); Symbol: [ER\\_FAILED\\_TO\\_GET\\_ABSOLUTE\\_PATH](#); SQLSTATE: [HY000](#)

Message: Failed to get absolute path of program executable %s

[ER\\_FAILED\\_TO\\_GET\\_ABSOLUTE\\_PATH](#) was added in 8.0.4.

- Error number: [MY-010940](#); Symbol: [ER\\_PERFSCHEMA\\_COMPONENTS\\_INFRASTRUCTURE\\_BOOTSTRAP](#); SQLSTATE: [HY000](#)

Message: Failed to bootstrap performance schema components infrastructure.

[ER\\_PERFSCHEMA\\_COMPONENTS\\_INFRASTRUCTURE\\_BOOTSTRAP](#) was added in 8.0.4.

- Error number: [MY-010941](#); Symbol: [ER\\_PERFSCHEMA\\_COMPONENTS\\_INFRASTRUCTURE\\_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Failed to deinit performance schema components infrastructure.

[ER\\_PERFSCHEMA\\_COMPONENTS\\_INFRASTRUCTURE\\_SHUTDOWN](#) was added in 8.0.4.

- Error number: [MY-010942](#); Symbol: [ER\\_DUP\\_FD\\_OPEN\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Could not open duplicate fd for %s: %s.

[ER\\_DUP\\_FD\\_OPEN\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-010943](#); Symbol: [ER\\_SYSTEM\\_VIEW\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: System views initialization failed.

[ER\\_SYSTEM\\_VIEW\\_INIT\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-010944](#); Symbol: [ER\\_RESOURCE\\_GROUP\\_POST\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Resource group post initialization failed.

---

`ER_RESOURCE_GROUP_POST_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010945`; Symbol: `ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED`; SQLSTATE: `HY000`

Message: Resource Group subsystem initialization failed.

`ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010946`; Symbol: `ER_FAILED_START_MYSQLD_DAEMON`; SQLSTATE: `HY000`

Message: Failed to start mysqld daemon. Check mysqld error log.

`ER_FAILED_START_MYSQLD_DAEMON` was added in 8.0.4.

- Error number: `MY-010947`; Symbol: `ER_CANNOT_CHANGE_TO_ROOT_DIR`; SQLSTATE: `HY000`

Message: Cannot change to root directory: %s.

`ER_CANNOT_CHANGE_TO_ROOT_DIR` was added in 8.0.4.

- Error number: `MY-010948`; Symbol: `ER_PERSISTENT_PRIVILEGES_BOOTSTRAP`; SQLSTATE: `HY000`

Message: Failed to bootstrap persistent privileges.

`ER_PERSISTENT_PRIVILEGES_BOOTSTRAP` was added in 8.0.4.

- Error number: `MY-010949`; Symbol: `ER_BASEDIR_SET_TO`; SQLSTATE: `HY000`

Message: Basedir set to %s.

`ER_BASEDIR_SET_TO` was added in 8.0.4.

- Error number: `MY-010950`; Symbol: `ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED`; SQLSTATE: `HY000`

Message: Could not add wild do table rule '%s'!

`ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED` was added in 8.0.4.

- Error number: `MY-010951`; Symbol: `ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED`; SQLSTATE: `HY000`

Message: Could not add wild ignore table rule '%s'!

`ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED` was added in 8.0.4.

- Error number: `MY-010952`; Symbol: `ER_PRIVILEGE_SYSTEM_INIT_FAILED`; SQLSTATE: `HY000`

Message: The privilege system failed to initialize correctly. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.

`ER_PRIVILEGE_SYSTEM_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010953`; Symbol: `ER_CANNOT_SET_LOG_ERROR_SERVICES`; SQLSTATE: `HY000`

Message: Cannot set services "%s" requested in --log-error-services, using defaults.

`ER_CANNOT_SET_LOG_ERROR_SERVICES` was added in 8.0.4.



- 
- Error number: [MY-010954](#); Symbol: [ER\\_PERFSCHEMA\\_TABLES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Performance schema tables initialization failed.  
  
[ER\\_PERFSCHEMA\\_TABLES\\_INIT\\_FAILED](#) was added in 8.0.4.
  - Error number: [MY-010955](#); Symbol: [ER\\_TX\\_EXTRACTION\\_ALGORITHM\\_FOR\\_BINLOG\\_TX\\_DEPEDENCY\\_TRACKING](#); SQLSTATE: [HY000](#)  
  
Message: The transaction\_write\_set\_extraction must be set to %s when binlog\_transaction\_dependency\_tracking is %s.  
  
[ER\\_TX\\_EXTRACTION\\_ALGORITHM\\_FOR\\_BINLOG\\_TX\\_DEPEDENCY\\_TRACKING](#) was added in 8.0.4.
  - Error number: [MY-010956](#); Symbol: [ER\\_INVALID\\_REPLICATION\\_TIMESTAMPS](#); SQLSTATE: [HY000](#)  
  
Message: Invalid replication timestamps: original commit timestamp is more recent than the immediate commit timestamp. This may be an issue if delayed replication is active. Make sure that servers have their clocks set to the correct time. No further message will be emitted until after timestamps become valid again.  
  
[ER\\_INVALID\\_REPLICATION\\_TIMESTAMPS](#) was added in 8.0.4, removed after 8.0.25.
  - Error number: [MY-010957](#); Symbol: [ER\\_RPL\\_TIMESTAMPS\\_RETURNED\\_TO\\_NORMAL](#); SQLSTATE: [HY000](#)  
  
Message: The replication timestamps have returned to normal values.  
  
[ER\\_RPL\\_TIMESTAMPS\\_RETURNED\\_TO\\_NORMAL](#) was added in 8.0.4, removed after 8.0.25.
  - Error number: [MY-010958](#); Symbol: [ER\\_BINLOG\\_FILE\\_OPEN\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: %s.  
  
[ER\\_BINLOG\\_FILE\\_OPEN\\_FAILED](#) was added in 8.0.4.
  - Error number: [MY-010959](#); Symbol: [ER\\_BINLOG\\_EVENT\\_WRITE\\_TO\\_STMT\\_CACHE\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Failed to write an incident event into stmt\_cache.  
  
[ER\\_BINLOG\\_EVENT\\_WRITE\\_TO\\_STMT\\_CACHE\\_FAILED](#) was added in 8.0.4.
  - Error number: [MY-010960](#); Symbol: [ER\\_SLAVE\\_RELAY\\_LOG\\_TRUNCATE\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Relaylog file %s size was %llu, but was truncated at %llu.  
  
[ER\\_SLAVE\\_RELAY\\_LOG\\_TRUNCATE\\_INFO](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-010960](#); Symbol: [ER\\_REPLICA\\_RELAY\\_LOG\\_TRUNCATE\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Relaylog file %s size was %llu, but was truncated at %llu.  
  
[ER\\_REPLICA\\_RELAY\\_LOG\\_TRUNCATE\\_INFO](#) was added in 8.0.33.

- 
- Error number: [MY-010961](#); Symbol: [ER\\_SLAVE\\_RELAY\\_LOG\\_PURGE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Unable to purge relay log files. %s:%s.  
[ER\\_SLAVE\\_RELAY\\_LOG\\_PURGE\\_FAILED](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-010961](#); Symbol: [ER\\_REPLICA\\_RELAY\\_LOG\\_PURGE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Unable to purge relay log files. %s:%s.  
[ER\\_REPLICA\\_RELAY\\_LOG\\_PURGE\\_FAILED](#) was added in 8.0.33.
  - Error number: [MY-010962](#); Symbol: [ER\\_RPL\\_SLAVE\\_FILTER\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Slave: failed in creating filter for channel '%s'.  
[ER\\_RPL\\_SLAVE\\_FILTER\\_CREATE\\_FAILED](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-010962](#); Symbol: [ER\\_RPL\\_REPLICA\\_FILTER\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Replica: failed in creating filter for channel '%s'.  
[ER\\_RPL\\_REPLICA\\_FILTER\\_CREATE\\_FAILED](#) was added in 8.0.33.
  - Error number: [MY-010963](#); Symbol: [ER\\_RPL\\_SLAVE\\_GLOBAL\\_FILTERS\\_COPY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Slave: failed in copying the global filters to its own per-channel filters on configuration for channel '%s'.  
[ER\\_RPL\\_SLAVE\\_GLOBAL\\_FILTERS\\_COPY\\_FAILED](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-010963](#); Symbol: [ER\\_RPL\\_REPLICA\\_GLOBAL\\_FILTERS\\_COPY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Replica: failed in copying the global filters to its own per-channel filters on configuration for channel '%s'.  
[ER\\_RPL\\_REPLICA\\_GLOBAL\\_FILTERS\\_COPY\\_FAILED](#) was added in 8.0.33.
  - Error number: [MY-010964](#); Symbol: [ER\\_RPL\\_SLAVE\\_RESET\\_FILTER\\_OPTIONS](#); SQLSTATE: [HY000](#)  
Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.  
[ER\\_RPL\\_SLAVE\\_RESET\\_FILTER\\_OPTIONS](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-010964](#); Symbol: [ER\\_RPL\\_REPLICA\\_RESET\\_FILTER\\_OPTIONS](#); SQLSTATE: [HY000](#)  
Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.  
[ER\\_RPL\\_REPLICA\\_RESET\\_FILTER\\_OPTIONS](#) was added in 8.0.33.

- 
- Error number: [MY-010965](#); Symbol: [ER\\_MISSING\\_GRANT\\_SYSTEM\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: The system table mysql.global\_grants is missing. Please perform the MySQL upgrade procedure.  
[ER\\_MISSING\\_GRANT\\_SYSTEM\\_TABLE](#) was added in 8.0.4.
  - Error number: [MY-010966](#); Symbol: [ER\\_MISSING\\_ACL\\_SYSTEM\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: ACL table mysql.%.\*s missing. Some operations may fail.  
[ER\\_MISSING\\_ACL\\_SYSTEM\\_TABLE](#) was added in 8.0.4.
  - Error number: [MY-010967](#); Symbol: [ER\\_ANONYMOUS\\_AUTH\\_ID\\_NOT\\_ALLOWED\\_IN\\_MANDATORY\\_ROLES](#); SQLSTATE: [HY000](#)  
Message: Can't set mandatory\_role %s@%s: Anonymous authorization IDs are not allowed as roles.  
[ER\\_ANONYMOUS\\_AUTH\\_ID\\_NOT\\_ALLOWED\\_IN\\_MANDATORY\\_ROLES](#) was added in 8.0.4.
  - Error number: [MY-010968](#); Symbol: [ER\\_UNKNOWN\\_AUTH\\_ID\\_IN\\_MANDATORY\\_ROLE](#); SQLSTATE: [HY000](#)  
Message: Can't set mandatory\_role: There's no such authorization ID %s@%s.  
[ER\\_UNKNOWN\\_AUTH\\_ID\\_IN\\_MANDATORY\\_ROLE](#) was added in 8.0.4.
  - Error number: [MY-010969](#); Symbol: [ER\\_WRITE\\_ROW\\_TO\\_PARTITION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Table '%s' failed to move/insert a row from part %d into part %d: %s.  
[ER\\_WRITE\\_ROW\\_TO\\_PARTITION\\_FAILED](#) was added in 8.0.4.
  - Error number: [MY-010970](#); Symbol: [ER\\_RESOURCE\\_GROUP\\_METADATA\\_UPDATE\\_SKIPPED](#); SQLSTATE: [HY000](#)  
Message: Skipped updating resource group metadata in InnoDB read only mode.  
[ER\\_RESOURCE\\_GROUP\\_METADATA\\_UPDATE\\_SKIPPED](#) was added in 8.0.4.
  - Error number: [MY-010971](#); Symbol: [ER\\_FAILED\\_TO\\_PERSIST\\_RESOURCE\\_GROUP\\_METADATA](#); SQLSTATE: [HY000](#)  
Message: Failed to persist resource group %s to Data Dictionary.  
[ER\\_FAILED\\_TO\\_PERSIST\\_RESOURCE\\_GROUP\\_METADATA](#) was added in 8.0.4.
  - Error number: [MY-010972](#); Symbol: [ER\\_FAILED\\_TO\\_DESERIALIZE\\_RESOURCE\\_GROUP](#); SQLSTATE: [HY000](#)  
Message: Failed to deserialize resource group %s.  
[ER\\_FAILED\\_TO\\_DESERIALIZE\\_RESOURCE\\_GROUP](#) was added in 8.0.4.
  - Error number: [MY-010973](#); Symbol: [ER\\_FAILED\\_TO\\_UPDATE\\_RESOURCE\\_GROUP](#); SQLSTATE: [HY000](#)  
Message: Update of resource group %s failed.  
[ER\\_FAILED\\_TO\\_UPDATE\\_RESOURCE\\_GROUP](#) was added in 8.0.4.

- 
- Error number: [MY-010974](#); Symbol: [ER\\_RESOURCE\\_GROUP\\_VALIDATION\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Validation of resource group %s failed. Resource group is disabled.  
  
[ER\\_RESOURCE\\_GROUP\\_VALIDATION\\_FAILED](#) was added in 8.0.4.
  - Error number: [MY-010975](#); Symbol: [ER\\_FAILED\\_TO\\_ALLOCATE\\_MEMORY\\_FOR\\_RESOURCE\\_GROUP](#); SQLSTATE: [HY000](#)  
  
Message: Unable to allocate memory for Resource Group %s.  
  
[ER\\_FAILED\\_TO\\_ALLOCATE\\_MEMORY\\_FOR\\_RESOURCE\\_GROUP](#) was added in 8.0.4.
  - Error number: [MY-010976](#); Symbol: [ER\\_FAILED\\_TO\\_ALLOCATE\\_MEMORY\\_FOR\\_RESOURCE\\_GROUP\\_HASH](#); SQLSTATE: [HY000](#)  
  
Message: Failed to allocate memory for resource group hash.  
  
[ER\\_FAILED\\_TO\\_ALLOCATE\\_MEMORY\\_FOR\\_RESOURCE\\_GROUP\\_HASH](#) was added in 8.0.4.
  - Error number: [MY-010977](#); Symbol: [ER\\_FAILED\\_TO\\_ADD\\_RESOURCE\\_GROUP\\_TO\\_MAP](#); SQLSTATE: [HY000](#)  
  
Message: Failed to add resource group %s to resource group map.  
  
[ER\\_FAILED\\_TO\\_ADD\\_RESOURCE\\_GROUP\\_TO\\_MAP](#) was added in 8.0.4.
  - Error number: [MY-010978](#); Symbol: [ER\\_RESOURCE\\_GROUP\\_IS\\_DISABLED](#); SQLSTATE: [HY000](#)  
  
Message: Resource group feature is disabled. (Server is compiled with DISABLE\_PSI\_THREAD).  
  
[ER\\_RESOURCE\\_GROUP\\_IS\\_DISABLED](#) was added in 8.0.4.
  - Error number: [MY-010979](#); Symbol: [ER\\_FAILED\\_TO\\_APPLY\\_RESOURCE\\_GROUP\\_CONTROLLER](#); SQLSTATE: [HY000](#)  
  
Message: Unable to apply resource group controller %s.  
  
[ER\\_FAILED\\_TO\\_APPLY\\_RESOURCE\\_GROUP\\_CONTROLLER](#) was added in 8.0.4.
  - Error number: [MY-010980](#); Symbol: [ER\\_FAILED\\_TO\\_ACQUIRE\\_LOCK\\_ON\\_RESOURCE\\_GROUP](#); SQLSTATE: [HY000](#)  
  
Message: Unable to acquire lock on the resource group %s. Hint to switch resource group shall be ignored.  
  
[ER\\_FAILED\\_TO\\_ACQUIRE\\_LOCK\\_ON\\_RESOURCE\\_GROUP](#) was added in 8.0.4.
  - Error number: [MY-010981](#); Symbol: [ER\\_PFS\\_NOTIFICATION\\_FUNCTION\\_REGISTER\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: PFS %s notification function registration failed.  
  
[ER\\_PFS\\_NOTIFICATION\\_FUNCTION\\_REGISTER\\_FAILED](#) was added in 8.0.4.
  - Error number: [MY-010982](#); Symbol: [ER\\_RES\\_GRP\\_SET\\_THR\\_AFFINITY\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Unable to bind thread id %llu to cpu id %u (error code %d - %s).

---

`ER_RES_GRP_SET_THR_AFFINITY_FAILED` was added in 8.0.4.

- Error number: `MY-010983`; Symbol: `ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED`; SQLSTATE: `HY000`

Message: Unable to bind thread id %llu to cpu ids (error code %d - %s).

`ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED` was added in 8.0.4.

- Error number: `MY-010984`; Symbol: `ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED`; SQLSTATE: `HY000`

Message: Unbind thread id %llu failed. (error code %d - %s).

`ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED` was added in 8.0.4.

- Error number: `MY-010985`; Symbol: `ER_RES_GRP_SET_THREAD_PRIORITY_FAILED`; SQLSTATE: `HY000`

Message: Setting thread priority %d to thread id %llu failed. (error code %d - %s).

`ER_RES_GRP_SET_THREAD_PRIORITY_FAILED` was added in 8.0.4.

- Error number: `MY-010986`; Symbol: `ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY`; SQLSTATE: `HY000`

Message: Unable to determine CAP\_SYS\_NICE capability.

`ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY` was added in 8.0.4.

- Error number: `MY-010987`; Symbol: `ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE`; SQLSTATE: `HY000`

Message: %s failed: Failed to get handle for thread %llu.

`ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE` was added in 8.0.4.

- Error number: `MY-010988`; Symbol: `ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Retrieval of thread priority unsupported on %s.

`ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED` was added in 8.0.4.

- Error number: `MY-010989`; Symbol: `ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT`; SQLSTATE: `HY000`

Message: Unable to determine the number of CPUs.

`ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT` was added in 8.0.4.

- Error number: `MY-010990`; Symbol: `ER_RES_GRP_FEATURE_NOT_AVAILABLE`; SQLSTATE: `HY000`

Message: Resource group feature shall not be available. Incompatible thread handling option.

`ER_RES_GRP_FEATURE_NOT_AVAILABLE` was added in 8.0.4.

- Error number: `MY-010991`; Symbol: `ER_RES_GRP_INVALID_THREAD_PRIORITY`; SQLSTATE: `HY000`

---

Message: Invalid thread priority %d for a %s resource group. Allowed range is [%d, %d].

[ER\\_RES\\_GRP\\_INVALID\\_THREAD\\_PRIORITY](#) was added in 8.0.4.

- Error number: [MY-010992](#); Symbol: [ER\\_RES\\_GRP\\_SOLARIS\\_PROCESSOR\\_BIND\\_TO\\_CPUID\\_FAILED](#); SQLSTATE: [HY000](#)

Message: bind\_to\_cpu failed: processor\_bind for cpuid %u failed (error code %d - %s).

[ER\\_RES\\_GRP\\_SOLARIS\\_PROCESSOR\\_BIND\\_TO\\_CPUID\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-010993](#); Symbol: [ER\\_RES\\_GRP\\_SOLARIS\\_PROCESSOR\\_BIND\\_TO\\_THREAD\\_FAILED](#); SQLSTATE: [HY000](#)

Message: bind\_to\_cpu failed: processor\_bind for thread %%lx with cpu id %u (error code %d - %s).

[ER\\_RES\\_GRP\\_SOLARIS\\_PROCESSOR\\_BIND\\_TO\\_THREAD\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-010994](#); Symbol: [ER\\_RES\\_GRP\\_SOLARIS\\_PROCESSOR\\_AFFINITY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: %s failed: processor\_affinity failed (error code %d - %s).

[ER\\_RES\\_GRP\\_SOLARIS\\_PROCESSOR\\_AFFINITY\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-010995](#); Symbol: [ER\\_DD\\_UPGRADE\\_RENAME\\_IDX\\_STATS\\_FILE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in renaming mysql\_index\_stats.ibd.

[ER\\_DD\\_UPGRADE\\_RENAME\\_IDX\\_STATS\\_FILE\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-010996](#); Symbol: [ER\\_DD\\_UPGRADE\\_DD\\_OPEN\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in opening data directory %s.

[ER\\_DD\\_UPGRADE\\_DD\\_OPEN\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-010997](#); Symbol: [ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_FETCH\\_TABLESPACES](#); SQLSTATE: [HY000](#)

Message: Error in fetching list of tablespaces.

[ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_FETCH\\_TABLESPACES](#) was added in 8.0.4.

- Error number: [MY-010998](#); Symbol: [ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_ACQUIRE\\_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Error in acquiring Tablespace for SDI insertion %s.

[ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_ACQUIRE\\_TABLESPACE](#) was added in 8.0.4.

- Error number: [MY-010999](#); Symbol: [ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_RESOLVE\\_TABLESPACE\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Error in resolving Engine name for tablespace %s with engine %s.

[ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_RESOLVE\\_TABLESPACE\\_ENGINE](#) was added in 8.0.4.

- 
- Error number: `MY-011000`; Symbol: `ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE`; SQLSTATE: `HY000`  
  
Message: Error in creating SDI for %s tablespace.  
  
`ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE` was added in 8.0.4.
  - Error number: `MY-011001`; Symbol: `ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE`; SQLSTATE: `HY000`  
  
Message: Error in storing SDI for %s tablespace.  
  
`ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE` was added in 8.0.4.
  - Error number: `MY-011002`; Symbol: `ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES`; SQLSTATE: `HY000`  
  
Message: Error in fetching list of tables.  
  
`ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES` was added in 8.0.4.
  - Error number: `MY-011003`; Symbol: `ER_DD_UPGRADE_DD_POPULATED`; SQLSTATE: `HY000`  
  
Message: Finished populating Data Dictionary tables with data.  
  
`ER_DD_UPGRADE_DD_POPULATED` was added in 8.0.4.
  - Error number: `MY-011004`; Symbol: `ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED`; SQLSTATE: `HY000`  
  
Message: Could not open the upgrade info file '%s' in the MySQL servers datadir, errno: %d.  
  
`ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED` was added in 8.0.4.
  - Error number: `MY-011005`; Symbol: `ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED`; SQLSTATE: `HY000`  
  
Message: Could not close the upgrade info file '%s' in the MySQL servers datadir, errno: %d.  
  
`ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED` was added in 8.0.4.
  - Error number: `MY-011006`; Symbol: `ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED`; SQLSTATE: `HY000`  
  
Message: Got error %d from SE while migrating tablespaces.  
  
`ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED` was added in 8.0.4.
  - Error number: `MY-011007`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS`; SQLSTATE: `HY000`  
  
Message: Error in creating TABLE statistics entry. Fix statistics data by using ANALYZE command.  
  
`ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS` was added in 8.0.4.
  - Error number: `MY-011008`; Symbol: `ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED`; SQLSTATE: `HY000`  
  
Message: Finished migrating TABLE statistics data.

---

`ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED` was added in 8.0.4.

- Error number: `MY-011009`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS`; SQLSTATE: `HY000`

Message: Error in creating Index statistics entry. Fix statistics data by using ANALYZE command.

`ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS` was added in 8.0.4.

- Error number: `MY-011010`; Symbol: `ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED`; SQLSTATE: `HY000`

Message: Finished migrating INDEX statistics data.

`ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED` was added in 8.0.4.

- Error number: `MY-011011`; Symbol: `ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR`; SQLSTATE: `HY000`

Message: Failed to find valid data directory.

`ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR` was added in 8.0.4.

- Error number: `MY-011012`; Symbol: `ER_DD_UPGRADE_START`; SQLSTATE: `HY000`

Message: Starting upgrade of data directory.

`ER_DD_UPGRADE_START` was added in 8.0.4.

- Error number: `MY-011013`; Symbol: `ER_DD_UPGRADE_FAILED_INIT_DD_SE`; SQLSTATE: `HY000`

Message: Failed to initialize DD Storage Engine.

`ER_DD_UPGRADE_FAILED_INIT_DD_SE` was added in 8.0.4.

- Error number: `MY-011014`; Symbol: `ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_ABORT`; SQLSTATE: `HY000`

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.

`ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_ABORT` was added in 8.0.4.

- Error number: `MY-011015`; Symbol: `ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_CONTINUE`; SQLSTATE: `HY000`

Message: Found partially upgraded DD. Upgrade will continue and start the server.

`ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_CONTINUE` was added in 8.0.4.

- Error number: `MY-011016`; Symbol: `ER_DD_UPGRADE_SE_LOGS_FAILED`; SQLSTATE: `HY000`

Message: Error in upgrading engine logs.

`ER_DD_UPGRADE_SE_LOGS_FAILED` was added in 8.0.4.

- Error number: `MY-011017`; Symbol: `ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED`; SQLSTATE: `HY000`



---

Message: Error in updating SDI information.

[ER\\_DD\\_UPGRADE\\_SDI\\_INFO\\_UPDATE\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-011018](#); Symbol: [ER\\_SKIP\\_UPDATING\\_METADATA\\_IN\\_SE\\_RO\\_MODE](#); SQLSTATE: [HY000](#)

Message: Skip updating %s metadata in InnoDB read-only mode.

[ER\\_SKIP\\_UPDATING\\_METADATA\\_IN\\_SE\\_RO\\_MODE](#) was added in 8.0.4.

- Error number: [MY-011019](#); Symbol: [ER\\_CREATED\\_SYSTEM\\_WITH\\_VERSION](#); SQLSTATE: [HY000](#)

Message: Created system views with I\_S version %d.

[ER\\_CREATED\\_SYSTEM\\_WITH\\_VERSION](#) was added in 8.0.4.

- Error number: [MY-011020](#); Symbol: [ER\\_UNKNOWN\\_ERROR\\_DETECTED\\_IN\\_SE](#); SQLSTATE: [HY000](#)

Message: Unknown error detected %d in handler.

[ER\\_UNKNOWN\\_ERROR\\_DETECTED\\_IN\\_SE](#) was added in 8.0.4.

- Error number: [MY-011021](#); Symbol: [ER\\_READ\\_LOG\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in Log\_event::read\_log\_event(): '%s', data\_len: %lu, event\_type: %d.

[ER\\_READ\\_LOG\\_EVENT\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-011022](#); Symbol: [ER\\_ROW\\_DATA\\_TOO\\_BIG\\_TO\\_WRITE\\_IN\\_BINLOG](#); SQLSTATE: [HY000](#)

Message: The row data is greater than 4GB, which is too big to write to the binary log.

[ER\\_ROW\\_DATA\\_TOO\\_BIG\\_TO\\_WRITE\\_IN\\_BINLOG](#) was added in 8.0.4.

- Error number: [MY-011023](#); Symbol: [ER\\_FAILED\\_TO\\_CONSTRUCT\\_DROP\\_EVENT\\_QUERY](#); SQLSTATE: [HY000](#)

Message: Unable to construct DROP EVENT SQL query string.

[ER\\_FAILED\\_TO\\_CONSTRUCT\\_DROP\\_EVENT\\_QUERY](#) was added in 8.0.4.

- Error number: [MY-011024](#); Symbol: [ER\\_FAILED\\_TO\\_BINLOG\\_DROP\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to binlog drop event %s.%s.

[ER\\_FAILED\\_TO\\_BINLOG\\_DROP\\_EVENT](#) was added in 8.0.4.

- Error number: [MY-011025](#); Symbol: [ER\\_FAILED\\_TO\\_START\\_SLAVE\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Failed to start slave threads for channel '%s'.

[ER\\_FAILED\\_TO\\_START\\_SLAVE\\_THREAD](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011025](#); Symbol: [ER\\_FAILED\\_TO\\_START\\_REPLICA\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Failed to start replica threads for channel '%s'.

---

`ER_FAILED_TO_START_REPLICA_THREAD` was added in 8.0.33.

- Error number: `MY-011026`; Symbol: `ER_RPL_IO_THREAD_KILLED`; SQLSTATE: `HY000`

Message: %s%s.

`ER_RPL_IO_THREAD_KILLED` was added in 8.0.4.

- Error number: `MY-011027`; Symbol: `ER_SLAVE_RECONNECT_FAILED`; SQLSTATE: `HY000`

Message: Failed registering on master, reconnecting to try again, log '%s' at position %s. %s.

`ER_SLAVE_RECONNECT_FAILED` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011027`; Symbol: `ER_REPLICA_RECONNECT_FAILED`; SQLSTATE: `HY000`

Message: Failed registering on source, reconnecting to try again, log '%s' at position %s. %s.

`ER_REPLICA_RECONNECT_FAILED` was added in 8.0.33.

- Error number: `MY-011028`; Symbol: `ER_SLAVE_KILLED_AFTER_RECONNECT`; SQLSTATE: `HY000`

Message: Slave I/O thread killed during or after reconnect.

`ER_SLAVE_KILLED_AFTER_RECONNECT` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011028`; Symbol: `ER_REPLICA_KILLED_AFTER_RECONNECT`; SQLSTATE: `HY000`

Message: Replica I/O thread killed during or after reconnect.

`ER_REPLICA_KILLED_AFTER_RECONNECT` was added in 8.0.33.

- Error number: `MY-011029`; Symbol: `ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS`; SQLSTATE: `HY000`

Message: Some of the channels are not created/initialized properly. Check for additional messages above. You will not be able to start replication on those channels until the issue is resolved and the server restarted.

`ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011029`; Symbol: `ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS`; SQLSTATE: `HY000`

Message: Some of the channels are not created/initialized properly. Check for additional messages above. You will not be able to start replication on those channels until the issue is resolved and the server restarted.

`ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS` was added in 8.0.33.

- Error number: `MY-011030`; Symbol: `ER_FAILED_TO_ADD_RPL_FILTER`; SQLSTATE: `HY000`

Message: Failed to add a replication filter into filter map for channel '%s'.

`ER_FAILED_TO_ADD_RPL_FILTER` was added in 8.0.4.

- Error number: `MY-011031`; Symbol: `ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL`; SQLSTATE: `HY000`

---

Message: There are per-channel replication filter(s) configured for group replication channel '%s' which is disallowed. The filter(s) have been discarded.

`ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL` was added in 8.0.4.

- Error number: `MY-011032`; Symbol: `ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL`; SQLSTATE: `HY000`

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

`ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL` was added in 8.0.4.

- Error number: `MY-011033`; Symbol: `ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES`; SQLSTATE: `HY000`

Message: An error occurred while building `do_table` and `ignore_table` rules to hashes for per-channel filter.

`ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES` was added in 8.0.4.

- Error number: `MY-011034`; Symbol: `ER_CLONE_PLUGIN_NOT_LOADED`; SQLSTATE: `HY000`

Message: Clone plugin not loaded.

`ER_CLONE_PLUGIN_NOT_LOADED` was added in 8.0.4, removed after 8.0.16.

- Error number: `MY-011034`; Symbol: `ER_CLONE_PLUGIN_NOT_LOADED_TRACE`; SQLSTATE: `HY000`

Message: Clone plugin cannot be loaded.

`ER_CLONE_PLUGIN_NOT_LOADED_TRACE` was added in 8.0.17.

- Error number: `MY-011035`; Symbol: `ER_CLONE_HANDLER_EXISTS`; SQLSTATE: `HY000`

Message: Clone Handler exists.

`ER_CLONE_HANDLER_EXISTS` was added in 8.0.4, removed after 8.0.16.

- Error number: `MY-011035`; Symbol: `ER_CLONE_HANDLER_EXIST_TRACE`; SQLSTATE: `HY000`

Message: Clone Handler exists.

`ER_CLONE_HANDLER_EXIST_TRACE` was added in 8.0.17.

- Error number: `MY-011036`; Symbol: `ER_FAILED_TO_CREATE_CLONE_HANDLER`; SQLSTATE: `HY000`

Message: Could not create Clone Handler.

`ER_FAILED_TO_CREATE_CLONE_HANDLER` was added in 8.0.4, removed after 8.0.16.

- Error number: `MY-011036`; Symbol: `ER_CLONE_CREATE_HANDLER_FAIL_TRACE`; SQLSTATE: `HY000`

Message: Could not create Clone Handler.

`ER_CLONE_CREATE_HANDLER_FAIL_TRACE` was added in 8.0.17.

- Error number: `MY-011037`; Symbol: `ER_CYCLE_TIMER_IS_NOT_AVAILABLE`; SQLSTATE: `HY000`

---

Message: The CYCLE timer is not available. WAIT events in the performance\_schema will not be timed.

[ER\\_CYCLE\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#) was added in 8.0.4.

- Error number: [MY-011038](#); Symbol: [ER\\_NANOSECOND\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: The NANOSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance\_schema will not be timed.

[ER\\_NANOSECOND\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#) was added in 8.0.4.

- Error number: [MY-011039](#); Symbol: [ER\\_MICROSECOND\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: The MICROSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance\_schema will not be timed.

[ER\\_MICROSECOND\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#) was added in 8.0.4.

- Error number: [MY-011040](#); Symbol: [ER\\_PFS\\_MALLOC\\_ARRAY\\_OVERFLOW](#); SQLSTATE: [HY000](#)

Message: Failed to allocate memory for %zu chunks each of size %zu for buffer '%s' due to overflow.

[ER\\_PFS\\_MALLOC\\_ARRAY\\_OVERFLOW](#) was added in 8.0.4.

- Error number: [MY-011041](#); Symbol: [ER\\_PFS\\_MALLOC\\_ARRAY\\_OOM](#); SQLSTATE: [HY000](#)

Message: Failed to allocate %zu bytes for buffer '%s' due to out-of-memory.

[ER\\_PFS\\_MALLOC\\_ARRAY\\_OOM](#) was added in 8.0.4.

- Error number: [MY-011042](#); Symbol: [ER\\_INNODB\\_FAILED\\_TO\\_FIND\\_IDX\\_WITH\\_KEY\\_NO](#); SQLSTATE: [HY000](#)

Message: InnoDB could not find index %s key no %u for table %s through its index translation table.

[ER\\_INNODB\\_FAILED\\_TO\\_FIND\\_IDX\\_WITH\\_KEY\\_NO](#) was added in 8.0.4.

- Error number: [MY-011043](#); Symbol: [ER\\_INNODB\\_FAILED\\_TO\\_FIND\\_IDX](#); SQLSTATE: [HY000](#)

Message: Cannot find index %s in InnoDB index translation table.

[ER\\_INNODB\\_FAILED\\_TO\\_FIND\\_IDX](#) was added in 8.0.4.

- Error number: [MY-011044](#); Symbol: [ER\\_INNODB\\_FAILED\\_TO\\_FIND\\_IDX\\_FROM\\_DICT\\_CACHE](#); SQLSTATE: [HY000](#)

Message: InnoDB could not find key no %u with name %s from dict cache for table %s.

[ER\\_INNODB\\_FAILED\\_TO\\_FIND\\_IDX\\_FROM\\_DICT\\_CACHE](#) was added in 8.0.4.

- Error number: [MY-011045](#); Symbol: [ER\\_INNODB\\_ACTIVE\\_INDEX\\_CHANGE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: InnoDB: change\_active\_index(%u) failed.

[ER\\_INNODB\\_ACTIVE\\_INDEX\\_CHANGE\\_FAILED](#) was added in 8.0.4.

- 
- Error number: [MY-011046](#); Symbol: [ER\\_INNODB\\_DIFF\\_IN\\_REF\\_LEN](#); SQLSTATE: [HY000](#)  
Message: Stored ref len is %lu, but table ref len is %lu.  
[ER\\_INNODB\\_DIFF\\_IN\\_REF\\_LEN](#) was added in 8.0.4.
  - Error number: [MY-011047](#); Symbol: [ER\\_WRONG\\_TYPE\\_FOR\\_COLUMN\\_PREFIX\\_IDX\\_FLD](#); SQLSTATE: [HY000](#)  
Message: MySQL is trying to create a column prefix index field, on an inappropriate data type. Table name %s, column name %s.  
[ER\\_WRONG\\_TYPE\\_FOR\\_COLUMN\\_PREFIX\\_IDX\\_FLD](#) was added in 8.0.4.
  - Error number: [MY-011048](#); Symbol: [ER\\_INNODB\\_CANNOT\\_CREATE\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot create table %s.  
[ER\\_INNODB\\_CANNOT\\_CREATE\\_TABLE](#) was added in 8.0.4.
  - Error number: [MY-011049](#); Symbol: [ER\\_INNODB\\_INTERNAL\\_INDEX](#); SQLSTATE: [HY000](#)  
Message: Found index %s in InnoDB index list but not its MySQL index number. It could be an InnoDB internal index.  
[ER\\_INNODB\\_INTERNAL\\_INDEX](#) was added in 8.0.4.
  - Error number: [MY-011050](#); Symbol: [ER\\_INNODB\\_IDX\\_CNT\\_MORE\\_THAN\\_DEFINED\\_IN\\_MYSQL](#); SQLSTATE: [HY000](#)  
Message: InnoDB: Table %s contains %lu indexes inside InnoDB, which is different from the number of indexes %u defined in MySQL.  
[ER\\_INNODB\\_IDX\\_CNT\\_MORE\\_THAN\\_DEFINED\\_IN\\_MYSQL](#) was added in 8.0.4.
  - Error number: [MY-011051](#); Symbol: [ER\\_INNODB\\_IDX\\_CNT\\_FEWER\\_THAN\\_DEFINED\\_IN\\_MYSQL](#); SQLSTATE: [HY000](#)  
Message: Table %s contains fewer indexes inside InnoDB than are defined in the MySQL. Have you mixed up with data dictionary from different installation?  
[ER\\_INNODB\\_IDX\\_CNT\\_FEWER\\_THAN\\_DEFINED\\_IN\\_MYSQL](#) was added in 8.0.4.
  - Error number: [MY-011052](#); Symbol: [ER\\_INNODB\\_IDX\\_COLUMN\\_CNT\\_DIFF](#); SQLSTATE: [HY000](#)  
Message: Index %s of %s has %lu columns unique inside InnoDB, but MySQL is asking statistics for %lu columns. Have you mixed data dictionary from different installation?  
[ER\\_INNODB\\_IDX\\_COLUMN\\_CNT\\_DIFF](#) was added in 8.0.4.
  - Error number: [MY-011053](#); Symbol: [ER\\_INNODB\\_USE\\_MONITOR\\_GROUP\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Monitor counter '%s' cannot be turned on/off individually. Please use its module name to turn on/off the counters in the module as a group.  
[ER\\_INNODB\\_USE\\_MONITOR\\_GROUP\\_NAME](#) was added in 8.0.4.
  - Error number: [MY-011054](#); Symbol: [ER\\_INNODB\\_MONITOR\\_DEFAULT\\_VALUE\\_NOT\\_DEFINED](#); SQLSTATE: [HY000](#)

---

Message: Default value is not defined for this set option. Please specify correct counter or module name.

[ER\\_INNO\\_DB\\_MONITOR\\_DEFAULT\\_VALUE\\_NOT\\_DEFINED](#) was added in 8.0.4.

- Error number: [MY-011055](#); Symbol: [ER\\_INNO\\_DB\\_MONITOR\\_IS\\_ENABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB: Monitor %s is already enabled.

[ER\\_INNO\\_DB\\_MONITOR\\_IS\\_ENABLED](#) was added in 8.0.4.

- Error number: [MY-011056](#); Symbol: [ER\\_INNO\\_DB\\_INVALID\\_MONITOR\\_COUNTER\\_NAME](#); SQLSTATE: [HY000](#)

Message: Invalid monitor counter : %s.

[ER\\_INNO\\_DB\\_INVALID\\_MONITOR\\_COUNTER\\_NAME](#) was added in 8.0.4.

- Error number: [MY-011057](#); Symbol: [ER\\_WIN\\_LOAD\\_LIBRARY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: LoadLibrary("%s") failed: GetLastError returns %lu.

[ER\\_WIN\\_LOAD\\_LIBRARY\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-011058](#); Symbol: [ER\\_PARTITION\\_HANDLER\\_ADMIN\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s.

[ER\\_PARTITION\\_HANDLER\\_ADMIN\\_MSG](#) was added in 8.0.4.

- Error number: [MY-011059](#); Symbol: [ER\\_RPL\\_RLI\\_INIT\\_INFO\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s.

[ER\\_RPL\\_RLI\\_INIT\\_INFO\\_MSG](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011059](#); Symbol: [ER\\_RPL\\_AM\\_INIT\\_INFO\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s.

[ER\\_RPL\\_AM\\_INIT\\_INFO\\_MSG](#) was added in 8.0.33.

- Error number: [MY-011060](#); Symbol: [ER\\_DD\\_UPGRADE\\_TABLE\\_INTACT\\_ERROR](#); SQLSTATE: [HY000](#)

Message: %s.

[ER\\_DD\\_UPGRADE\\_TABLE\\_INTACT\\_ERROR](#) was added in 8.0.4.

- Error number: [MY-011061](#); Symbol: [ER\\_SERVER\\_INIT\\_COMPILED\\_IN\\_COMMANDS](#); SQLSTATE: [HY000](#)

Message: %s.

[ER\\_SERVER\\_INIT\\_COMPILED\\_IN\\_COMMANDS](#) was added in 8.0.4.

- Error number: [MY-011062](#); Symbol: [ER\\_MYISAM\\_CHECK\\_METHOD\\_ERROR](#); SQLSTATE: [HY000](#)

Message: %s.

[ER\\_MYISAM\\_CHECK\\_METHOD\\_ERROR](#) was added in 8.0.4.

- 
- Error number: [MY-011063](#); Symbol: [ER\\_MYISAM\\_CRASHED\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s.  
[ER\\_MYISAM\\_CRASHED\\_ERROR](#) was added in 8.0.4.
  - Error number: [MY-011064](#); Symbol: [ER\\_WAITPID\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Unable to wait for process %lld.  
[ER\\_WAITPID\\_FAILED](#) was added in 8.0.4.
  - Error number: [MY-011065](#); Symbol: [ER\\_FAILED\\_TO\\_FIND\\_MYSQLD\\_STATUS](#); SQLSTATE: [HY000](#)  
Message: Unable to determine if daemon is running: %s (rc=%d).  
[ER\\_FAILED\\_TO\\_FIND\\_MYSQLD\\_STATUS](#) was added in 8.0.4.
  - Error number: [MY-011066](#); Symbol: [ER\\_INNODB\\_ERROR\\_LOGGER\\_MSG](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_INNODB\\_ERROR\\_LOGGER\\_MSG](#) was added in 8.0.4.
  - Error number: [MY-011067](#); Symbol: [ER\\_INNODB\\_ERROR\\_LOGGER\\_FATAL\\_MSG](#); SQLSTATE: [HY000](#)  
Message: [FATAL] InnoDB: %s  
[ER\\_INNODB\\_ERROR\\_LOGGER\\_FATAL\\_MSG](#) was added in 8.0.4.
  - Error number: [MY-011068](#); Symbol: [ER\\_DEPRECATED\\_SYNTAX\\_WITH\\_REPLACEMENT](#); SQLSTATE: [HY000](#)  
Message: The syntax '%s' is deprecated and will be removed in a future release. Please use %s instead.  
[ER\\_DEPRECATED\\_SYNTAX\\_WITH\\_REPLACEMENT](#) was added in 8.0.4.
  - Error number: [MY-011069](#); Symbol: [ER\\_DEPRECATED\\_SYNTAX\\_NO\\_REPLACEMENT](#); SQLSTATE: [HY000](#)  
Message: The syntax '%s' is deprecated and will be removed in a future release.  
[ER\\_DEPRECATED\\_SYNTAX\\_NO\\_REPLACEMENT](#) was added in 8.0.4.
  - Error number: [MY-011070](#); Symbol: [ER\\_DEPRECATE\\_MSG\\_NO\\_REPLACEMENT](#); SQLSTATE: [HY000](#)  
Message: '%s' is deprecated and will be removed in a future release.  
[ER\\_DEPRECATE\\_MSG\\_NO\\_REPLACEMENT](#) was added in 8.0.4.
  - Error number: [MY-011071](#); Symbol: [ER\\_LOG\\_PRINTF\\_MSG](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_LOG\\_PRINTF\\_MSG](#) was added in 8.0.4.
  - Error number: [MY-011072](#); Symbol: [ER\\_BINLOG\\_LOGGING\\_NOT\\_POSSIBLE](#); SQLSTATE: [HY000](#)  
Message: Binary logging not possible. Message: %s.

---

`ER_BINLOG_LOGGING_NOT_POSSIBLE` was added in 8.0.4.

- Error number: `MY-011073`; Symbol: `ER_FAILED_TO_SET_PERSISTED_OPTIONS`; SQLSTATE: `HY000`

Message: Failed to set persisted options.

`ER_FAILED_TO_SET_PERSISTED_OPTIONS` was added in 8.0.4.

- Error number: `MY-011074`; Symbol: `ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION`; SQLSTATE: `HY000`

Message: Cannot acquire specified service implementation: '%s'.

`ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION` was added in 8.0.4.

- Error number: `MY-011075`; Symbol: `ER_RES_GRP_INVALID_VCPU_RANGE`; SQLSTATE: `HY000`

Message: Invalid VCPU range %u-%u.

`ER_RES_GRP_INVALID_VCPU_RANGE` was added in 8.0.4.

- Error number: `MY-011076`; Symbol: `ER_RES_GRP_INVALID_VCPU_ID`; SQLSTATE: `HY000`

Message: Invalid cpu id %u.

`ER_RES_GRP_INVALID_VCPU_ID` was added in 8.0.4.

- Error number: `MY-011077`; Symbol: `ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE`; SQLSTATE: `HY000`

Message: Got error %d during FLUSH\_LOGS.

`ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE` was added in 8.0.4.

- Error number: `MY-011078`; Symbol: `ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY`; SQLSTATE: `HY000`

Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.

`ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY` was added in 8.0.4.

- Error number: `MY-011079`; Symbol: `ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER`; SQLSTATE: `HY000`

Message: The option `expire_logs_days` cannot be used together with option `binlog_expire_logs_seconds`. Therefore, value of `expire_logs_days` is ignored.

`ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER` was added in 8.0.4, removed after 8.0.4.

- Error number: `MY-011079`; Symbol: `ER_EXPIRE_LOGS_DAYS_IGNORED`; SQLSTATE: `HY000`

Message: The option `expire_logs_days` cannot be used together with option `binlog_expire_logs_seconds`. Therefore, value of `expire_logs_days` is ignored.

`ER_EXPIRE_LOGS_DAYS_IGNORED` was added in 8.0.4.



- 
- Error number: [MY-011080](#); Symbol: [ER\\_BINLOG\\_MALFORMED\\_OR\\_OLD\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: malformed or very old relay log which does not have FormatDescriptor.  
  
[ER\\_BINLOG\\_MALFORMED\\_OR\\_OLD\\_RELAY\\_LOG](#) was added in 8.0.4.
  - Error number: [MY-011081](#); Symbol: [ER\\_DD\\_UPGRADE\\_VIEW\\_COLUMN\\_NAME\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
  
Message: Upgrade of view '%s.%s' failed. Re-create the view with the explicit column name lesser than 64 characters.  
  
[ER\\_DD\\_UPGRADE\\_VIEW\\_COLUMN\\_NAME\\_TOO\\_LONG](#) was added in 8.0.4.
  - Error number: [MY-011082](#); Symbol: [ER\\_TABLE\\_NEEDS\\_DUMP\\_UPGRADE](#); SQLSTATE: [HY000](#)  
  
Message: Table upgrade required for '%s'. Please dump/reload table to fix it!  
  
[ER\\_TABLE\\_NEEDS\\_DUMP\\_UPGRADE](#) was added in 8.0.4.
  - Error number: [MY-011083](#); Symbol: [ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_UPDATE\\_VER\\_NO\\_IN\\_TABLESPACE](#); SQLSTATE: [HY000](#)  
  
Message: Error in updating version number in %s tablespace.  
  
[ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_UPDATE\\_VER\\_NO\\_IN\\_TABLESPACE](#) was added in 8.0.4.
  - Error number: [MY-011084](#); Symbol: [ER\\_KEYRING\\_MIGRATION\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Keyring migration failed.  
  
[ER\\_KEYRING\\_MIGRATION\\_FAILED](#) was added in 8.0.4.
  - Error number: [MY-011085](#); Symbol: [ER\\_KEYRING\\_MIGRATION\\_SUCCESSFUL](#); SQLSTATE: [HY000](#)  
  
Message: Keyring migration successful.  
  
[ER\\_KEYRING\\_MIGRATION\\_SUCCESSFUL](#) was added in 8.0.4.
  - Error number: [MY-011086](#); Symbol: [ER\\_RESTART\\_RECEIVED\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Received RESTART from user %s. Restarting mysqld (Version: %s).  
  
[ER\\_RESTART\\_RECEIVED\\_INFO](#) was added in 8.0.4.
  - Error number: [MY-011087](#); Symbol: [ER\\_LCTN\\_CHANGED](#); SQLSTATE: [HY000](#)  
  
Message: Different lower\_case\_table\_names settings for server ('%u') and data dictionary ('%u').  
  
[ER\\_LCTN\\_CHANGED](#) was added in 8.0.4.
  - Error number: [MY-011088](#); Symbol: [ER\\_DD\\_INITIALIZE](#); SQLSTATE: [HY000](#)  
  
Message: Data dictionary initializing version '%u'.  
  
[ER\\_DD\\_INITIALIZE](#) was added in 8.0.4.
  - Error number: [MY-011089](#); Symbol: [ER\\_DD\\_RESTART](#); SQLSTATE: [HY000](#)

---

Message: Data dictionary restarting version '%u'.

`ER_DD_RESTART` was added in 8.0.4.

- Error number: `MY-011090`; Symbol: `ER_DD_UPGRADE`; SQLSTATE: `HY000`

Message: Data dictionary upgrading from version '%u' to '%u'.

`ER_DD_UPGRADE` was added in 8.0.4.

- Error number: `MY-011091`; Symbol: `ER_DD_UPGRADE_OFF`; SQLSTATE: `HY000`

Message: Data dictionary upgrade prohibited by the command line option '--no\_dd\_upgrade'.

`ER_DD_UPGRADE_OFF` was added in 8.0.4.

- Error number: `MY-011092`; Symbol: `ER_DD_UPGRADE_VERSION_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Upgrading the data dictionary from dictionary version '%u' is not supported.

`ER_DD_UPGRADE_VERSION_NOT_SUPPORTED` was added in 8.0.4.

- Error number: `MY-011093`; Symbol: `ER_DD_UPGRADE_SCHEMA_UNAVAILABLE`; SQLSTATE: `HY000`

Message: Upgrading the data dictionary failed, temporary schema name '%s' not available.

`ER_DD_UPGRADE_SCHEMA_UNAVAILABLE` was added in 8.0.4.

- Error number: `MY-011094`; Symbol: `ER_DD_MINOR_DOWNGRADE`; SQLSTATE: `HY000`

Message: Data dictionary minor downgrade from version '%u' to '%u'.

`ER_DD_MINOR_DOWNGRADE` was added in 8.0.4.

- Error number: `MY-011095`; Symbol: `ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Minor downgrade of the Data dictionary from dictionary version '%u' is not supported.

`ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED` was added in 8.0.4.

- Error number: `MY-011096`; Symbol: `ER_DD_NO_VERSION_FOUND`; SQLSTATE: `HY000`

Message: No data dictionary version number found.

`ER_DD_NO_VERSION_FOUND` was added in 8.0.4.

- Error number: `MY-011097`; Symbol: `ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM`; SQLSTATE: `HY000`

Message: Thread pool not supported, requires a minimum of %s.

`ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM` was added in 8.0.4.

- Error number: `MY-011098`; Symbol: `ER_THREAD_POOL_SIZE_TOO_LOW`; SQLSTATE: `HY000`

Message: thread\_pool\_size=0 means thread pool disabled, Allowed range of thread\_pool\_size is %d-%d.

---

`ER_THREAD_POOL_SIZE_TOO_LOW` was added in 8.0.4.

- Error number: `MY-011099`; Symbol: `ER_THREAD_POOL_SIZE_TOO_HIGH`; SQLSTATE: `HY000`

Message: `thread_pool_size=%lu` is too high, `%d` is maximum, thread pool is disabled. Allowed range of `thread_pool_size` is `%d-%d`.

`ER_THREAD_POOL_SIZE_TOO_HIGH` was added in 8.0.4.

- Error number: `MY-011100`; Symbol: `ER_THREAD_POOL_ALGORITHM_INVALID`; SQLSTATE: `HY000`

Message: `thread_pool_algorithm` can be set to 0 and 1, 0 indicates the default low concurrency algorithm, 1 means a high concurrency algorithm.

`ER_THREAD_POOL_ALGORITHM_INVALID` was added in 8.0.4.

- Error number: `MY-011101`; Symbol: `ER_THREAD_POOL_INVALID_STALL_LIMIT`; SQLSTATE: `HY000`

Message: `thread_pool_stall_limit` can be `%d` at minimum and `%d` at maximum, smaller values would render the thread pool fairly useless and higher values could make it possible to have undetected deadlock issues in the MySQL Server.

`ER_THREAD_POOL_INVALID_STALL_LIMIT` was added in 8.0.4.

- Error number: `MY-011102`; Symbol: `ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER`; SQLSTATE: `HY000`

Message: Invalid value of `thread_pool_prio_kickup_timer` specified. Value of `thread_pool_prio_kickup_timer` should be in range 0-4294967294.

`ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER` was added in 8.0.4.

- Error number: `MY-011103`; Symbol: `ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID`; SQLSTATE: `HY000`

Message: `thread_pool_max_unused_threads` cannot be set higher than `%d`.

`ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID` was added in 8.0.4.

- Error number: `MY-011104`; Symbol: `ER_THREAD_POOL_CON_HANDLER_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to instantiate the connection handler object.

`ER_THREAD_POOL_CON_HANDLER_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-011105`; Symbol: `ER_THREAD_POOL_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize thread pool plugin.

`ER_THREAD_POOL_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-011107`; Symbol: `ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA`; SQLSTATE: `HY000`

Message: Can't setup connection teardown thread-specific data.

`ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA` was added in 8.0.4.

- 
- Error number: `MY-011108`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER_THD`; SQLSTATE: `HY000`  
  
Message: Creation of connect handler thread failed.  
  
`ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER_THD` was added in 8.0.4.
  - Error number: `MY-011109`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONN`; SQLSTATE: `HY000`  
  
Message: Failed to create thd and authenticate connection.  
  
`ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONN` was added in 8.0.4.
  - Error number: `MY-011110`; Symbol: `ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT`; SQLSTATE: `HY000`  
  
Message: Failed to process connection event.  
  
`ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT` was added in 8.0.4.
  - Error number: `MY-011111`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_POOL`; SQLSTATE: `HY000`  
  
Message: Can't create pool thread (error %d, errno: %d).  
  
`ER_THREAD_POOL_FAILED_TO_CREATE_POOL` was added in 8.0.4.
  - Error number: `MY-011112`; Symbol: `ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS`; SQLSTATE: `HY000`  
  
Message: %.\*s.  
  
`ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS` was added in 8.0.4.
  - Error number: `MY-011113`; Symbol: `ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED`; SQLSTATE: `HY000`  
  
Message: `tp_group_low_level_init()` failed.  
  
`ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED` was added in 8.0.4.
  - Error number: `MY-011114`; Symbol: `ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED`; SQLSTATE: `HY000`  
  
Message: Rearm failed even after 30 seconds, can't continue without notify socket.  
  
`ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED` was added in 8.0.4.
  - Error number: `MY-011115`; Symbol: `ER_THREAD_POOL_BUFFER_TOO_SMALL`; SQLSTATE: `HY000`  
  
Message: %s: %s buffer is too small  
  
`ER_THREAD_POOL_BUFFER_TOO_SMALL` was added in 8.0.4.

- 
- Error number: [MY-011116](#); Symbol: [ER\\_MECAB\\_NOT\\_SUPPORTED](#); SQLSTATE: [HY000](#)  
Message: Mecab v%s is not supported, the lowest version supported is v%s.  
[ER\\_MECAB\\_NOT\\_SUPPORTED](#) was added in 8.0.4.
  - Error number: [MY-011117](#); Symbol: [ER\\_MECAB\\_NOT\\_VERIFIED](#); SQLSTATE: [HY000](#)  
Message: Mecab v%s is not verified, the highest version supported is v%s.  
[ER\\_MECAB\\_NOT\\_VERIFIED](#) was added in 8.0.4.
  - Error number: [MY-011118](#); Symbol: [ER\\_MECAB\\_CREATING\\_MODEL](#); SQLSTATE: [HY000](#)  
Message: Mecab: Trying createModel(%s).  
[ER\\_MECAB\\_CREATING\\_MODEL](#) was added in 8.0.4.
  - Error number: [MY-011119](#); Symbol: [ER\\_MECAB\\_FAILED\\_TO\\_CREATE\\_MODEL](#); SQLSTATE: [HY000](#)  
Message: Mecab: createModel() failed: %s.  
[ER\\_MECAB\\_FAILED\\_TO\\_CREATE\\_MODEL](#) was added in 8.0.4.
  - Error number: [MY-011120](#); Symbol: [ER\\_MECAB\\_FAILED\\_TO\\_CREATE\\_TRIGGER](#); SQLSTATE: [HY000](#)  
Message: Mecab: createTagger() failed: %s.  
[ER\\_MECAB\\_FAILED\\_TO\\_CREATE\\_TRIGGER](#) was added in 8.0.4.
  - Error number: [MY-011121](#); Symbol: [ER\\_MECAB\\_UNSUPPORTED\\_CHARSET](#); SQLSTATE: [HY000](#)  
Message: Mecab: Unsupported dictionary charset %s.  
[ER\\_MECAB\\_UNSUPPORTED\\_CHARSET](#) was added in 8.0.4.
  - Error number: [MY-011122](#); Symbol: [ER\\_MECAB\\_CHARSET\\_LOADED](#); SQLSTATE: [HY000](#)  
Message: Mecab: Loaded dictionary charset is %s.  
[ER\\_MECAB\\_CHARSET\\_LOADED](#) was added in 8.0.4.
  - Error number: [MY-011123](#); Symbol: [ER\\_MECAB\\_PARSE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Mecab: parse() failed: %s.  
[ER\\_MECAB\\_PARSE\\_FAILED](#) was added in 8.0.4.
  - Error number: [MY-011124](#); Symbol: [ER\\_MECAB\\_OOM\\_WHILE\\_PARSING\\_TEXT](#); SQLSTATE: [HY000](#)  
Message: Mecab: parse() failed: out of memory.  
[ER\\_MECAB\\_OOM\\_WHILE\\_PARSING\\_TEXT](#) was added in 8.0.4.
  - Error number: [MY-011125](#); Symbol: [ER\\_MECAB\\_CREATE\\_LATTICE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Mecab: createLattice() failed: %s.  
[ER\\_MECAB\\_CREATE\\_LATTICE\\_FAILED](#) was added in 8.0.4.

- 
- Error number: [MY-011126](#); Symbol: [ER\\_SEMISYNC\\_TRACE\\_ENTER\\_FUNC](#); SQLSTATE: [HY000](#)  
Message: ---> %s enter.  
[ER\\_SEMISYNC\\_TRACE\\_ENTER\\_FUNC](#) was added in 8.0.4.
  - Error number: [MY-011127](#); Symbol: [ER\\_SEMISYNC\\_TRACE\\_EXIT\\_WITH\\_INT\\_EXIT\\_CODE](#); SQLSTATE: [HY000](#)  
Message: <--- %s exit (%d).  
[ER\\_SEMISYNC\\_TRACE\\_EXIT\\_WITH\\_INT\\_EXIT\\_CODE](#) was added in 8.0.4.
  - Error number: [MY-011128](#); Symbol: [ER\\_SEMISYNC\\_TRACE\\_EXIT\\_WITH\\_BOOL\\_EXIT\\_CODE](#); SQLSTATE: [HY000](#)  
Message: <--- %s exit (%s).  
[ER\\_SEMISYNC\\_TRACE\\_EXIT\\_WITH\\_BOOL\\_EXIT\\_CODE](#) was added in 8.0.4.
  - Error number: [MY-011129](#); Symbol: [ER\\_SEMISYNC\\_TRACE\\_EXIT](#); SQLSTATE: [HY000](#)  
Message: <--- %s exit.  
[ER\\_SEMISYNC\\_TRACE\\_EXIT](#) was added in 8.0.4.
  - Error number: [MY-011130](#); Symbol: [ER\\_SEMISYNC\\_RPL\\_INIT\\_FOR\\_TRX](#); SQLSTATE: [HY000](#)  
Message: Semi-sync replication initialized for transactions.  
[ER\\_SEMISYNC\\_RPL\\_INIT\\_FOR\\_TRX](#) was added in 8.0.4.
  - Error number: [MY-011131](#); Symbol: [ER\\_SEMISYNC\\_FAILED\\_TO\\_ALLOCATE\\_TRX\\_NODE](#); SQLSTATE: [HY000](#)  
Message: %s: transaction node allocation failed for: (%s, %lu).  
[ER\\_SEMISYNC\\_FAILED\\_TO\\_ALLOCATE\\_TRX\\_NODE](#) was added in 8.0.4.
  - Error number: [MY-011132](#); Symbol: [ER\\_SEMISYNC\\_BINLOG\\_WRITE\\_OUT\\_OF\\_ORDER](#); SQLSTATE: [HY000](#)  
Message: %s: binlog write out-of-order, tail (%s, %lu), new node (%s, %lu).  
[ER\\_SEMISYNC\\_BINLOG\\_WRITE\\_OUT\\_OF\\_ORDER](#) was added in 8.0.4.
  - Error number: [MY-011133](#); Symbol: [ER\\_SEMISYNC\\_INSERT\\_LOG\\_INFO\\_IN\\_ENTRY](#); SQLSTATE: [HY000](#)  
Message: %s: insert (%s, %lu) in entry(%u).  
[ER\\_SEMISYNC\\_INSERT\\_LOG\\_INFO\\_IN\\_ENTRY](#) was added in 8.0.4.
  - Error number: [MY-011134](#); Symbol: [ER\\_SEMISYNC\\_PROBE\\_LOG\\_INFO\\_IN\\_ENTRY](#); SQLSTATE: [HY000](#)  
Message: %s: probe (%s, %lu) in entry(%u).  
[ER\\_SEMISYNC\\_PROBE\\_LOG\\_INFO\\_IN\\_ENTRY](#) was added in 8.0.4.

- 
- Error number: [MY-011135](#); Symbol: [ER\\_SEMISYNC\\_CLEARED\\_ALL\\_ACTIVE\\_TRANSACTION\\_NODES](#); SQLSTATE: [HY000](#)  
  
Message: %s: cleared all nodes.  
  
[ER\\_SEMISYNC\\_CLEARED\\_ALL\\_ACTIVE\\_TRANSACTION\\_NODES](#) was added in 8.0.4.
  - Error number: [MY-011136](#); Symbol: [ER\\_SEMISYNC\\_CLEARED\\_ACTIVE\\_TRANSACTION\\_TILL\\_POS](#); SQLSTATE: [HY000](#)  
  
Message: %s: cleared %d nodes back until pos (%s, %lu).  
  
[ER\\_SEMISYNC\\_CLEARED\\_ACTIVE\\_TRANSACTION\\_TILL\\_POS](#) was added in 8.0.4.
  - Error number: [MY-011137](#); Symbol: [ER\\_SEMISYNC\\_REPLY\\_MAGIC\\_NO\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Read semi-sync reply magic number error.  
  
[ER\\_SEMISYNC\\_REPLY\\_MAGIC\\_NO\\_ERROR](#) was added in 8.0.4.
  - Error number: [MY-011138](#); Symbol: [ER\\_SEMISYNC\\_REPLY\\_PKT\\_LENGTH\\_TOO\\_SMALL](#); SQLSTATE: [HY000](#)  
  
Message: Read semi-sync reply length error: packet is too small.  
  
[ER\\_SEMISYNC\\_REPLY\\_PKT\\_LENGTH\\_TOO\\_SMALL](#) was added in 8.0.4.
  - Error number: [MY-011139](#); Symbol: [ER\\_SEMISYNC\\_REPLY\\_BINLOG\\_FILE\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)  
  
Message: Read semi-sync reply binlog file length too large.  
  
[ER\\_SEMISYNC\\_REPLY\\_BINLOG\\_FILE\\_TOO\\_LARGE](#) was added in 8.0.4.
  - Error number: [MY-011140](#); Symbol: [ER\\_SEMISYNC\\_SERVER\\_REPLY](#); SQLSTATE: [HY000](#)  
  
Message: %s: Got reply(%s, %lu) from server %u.  
  
[ER\\_SEMISYNC\\_SERVER\\_REPLY](#) was added in 8.0.4.
  - Error number: [MY-011141](#); Symbol: [ER\\_SEMISYNC\\_FUNCTION\\_CALLED\\_TWICE](#); SQLSTATE: [HY000](#)  
  
Message: %s called twice.  
  
[ER\\_SEMISYNC\\_FUNCTION\\_CALLED\\_TWICE](#) was added in 8.0.4.
  - Error number: [MY-011142](#); Symbol: [ER\\_SEMISYNC\\_RPL\\_ENABLED\\_ON\\_MASTER](#); SQLSTATE: [HY000](#)  
  
Message: Semi-sync replication enabled on the master.  
  
[ER\\_SEMISYNC\\_RPL\\_ENABLED\\_ON\\_MASTER](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011142](#); Symbol: [ER\\_SEMISYNC\\_RPL\\_ENABLED\\_ON\\_SOURCE](#); SQLSTATE: [HY000](#)  
  
Message: Semi-sync replication enabled on the source.  
  
[ER\\_SEMISYNC\\_RPL\\_ENABLED\\_ON\\_SOURCE](#) was added in 8.0.33.
  - Error number: [MY-011143](#); Symbol: [ER\\_SEMISYNC\\_MASTER\\_OOM](#); SQLSTATE: [HY000](#)

---

Message: Cannot allocate memory to enable semi-sync on the master.

[ER\\_SEMISYNC\\_MASTER\\_OOM](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011143](#); Symbol: [ER\\_SEMISYNC\\_SOURCE\\_OOM](#); SQLSTATE: [HY000](#)

Message: Cannot allocate memory to enable semi-sync on the source.

[ER\\_SEMISYNC\\_SOURCE\\_OOM](#) was added in 8.0.33.

- Error number: [MY-011144](#); Symbol: [ER\\_SEMISYNC\\_DISABLED\\_ON\\_MASTER](#); SQLSTATE: [HY000](#)

Message: Semi-sync replication disabled on the master.

[ER\\_SEMISYNC\\_DISABLED\\_ON\\_MASTER](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011144](#); Symbol: [ER\\_SEMISYNC\\_DISABLED\\_ON\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Semi-sync replication disabled on the source.

[ER\\_SEMISYNC\\_DISABLED\\_ON\\_SOURCE](#) was added in 8.0.33.

- Error number: [MY-011145](#); Symbol: [ER\\_SEMISYNC\\_FORCED\\_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: SEMISYNC: Forced shutdown. Some updates might not be replicated.

[ER\\_SEMISYNC\\_FORCED\\_SHUTDOWN](#) was added in 8.0.4.

- Error number: [MY-011146](#); Symbol: [ER\\_SEMISYNC\\_MASTER\\_GOT\\_REPLY\\_AT\\_POS](#); SQLSTATE: [HY000](#)

Message: %s: Got reply at (%s, %lu).

[ER\\_SEMISYNC\\_MASTER\\_GOT\\_REPLY\\_AT\\_POS](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011146](#); Symbol: [ER\\_SEMISYNC\\_SOURCE\\_GOT\\_REPLY\\_AT\\_POS](#); SQLSTATE: [HY000](#)

Message: %s: Got reply at (%s, %lu).

[ER\\_SEMISYNC\\_SOURCE\\_GOT\\_REPLY\\_AT\\_POS](#) was added in 8.0.33.

- Error number: [MY-011147](#); Symbol: [ER\\_SEMISYNC\\_MASTER\\_SIGNAL\\_ALL\\_WAITING\\_THREADS](#); SQLSTATE: [HY000](#)

Message: %s: signal all waiting threads.

[ER\\_SEMISYNC\\_MASTER\\_SIGNAL\\_ALL\\_WAITING\\_THREADS](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011147](#); Symbol: [ER\\_SEMISYNC\\_SOURCE\\_SIGNAL\\_ALL\\_WAITING\\_THREADS](#); SQLSTATE: [HY000](#)

Message: %s: signal all waiting threads.

[ER\\_SEMISYNC\\_SOURCE\\_SIGNAL\\_ALL\\_WAITING\\_THREADS](#) was added in 8.0.33.

- Error number: [MY-011148](#); Symbol: [ER\\_SEMISYNC\\_MASTER\\_TRX\\_WAIT\\_POS](#); SQLSTATE: [HY000](#)

Message: %s: wait pos (%s, %lu), repl(%d).



---

`ER_SEMISYNC_MASTER_TRX_WAIT_POS` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011148`; Symbol: `ER_SEMISYNC_SOURCE_TRX_WAIT_POS`; SQLSTATE: `HY000`  
Message: %s: wait pos (%s, %lu), repl(%d).

`ER_SEMISYNC_SOURCE_TRX_WAIT_POS` was added in 8.0.33.

- Error number: `MY-011149`; Symbol: `ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD`; SQLSTATE: `HY000`  
Message: %s: Binlog reply is ahead (%s, %lu).

`ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD` was added in 8.0.4.

- Error number: `MY-011150`; Symbol: `ER_SEMISYNC_MOVE_BACK_WAIT_POS`; SQLSTATE: `HY000`  
Message: %s: move back wait position (%s, %lu).

`ER_SEMISYNC_MOVE_BACK_WAIT_POS` was added in 8.0.4.

- Error number: `MY-011151`; Symbol: `ER_SEMISYNC_INIT_WAIT_POS`; SQLSTATE: `HY000`  
Message: %s: init wait position (%s, %lu).

`ER_SEMISYNC_INIT_WAIT_POS` was added in 8.0.4.

- Error number: `MY-011152`; Symbol: `ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT`; SQLSTATE: `HY000`  
Message: %s: wait %lu ms for binlog sent (%s, %lu).

`ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT` was added in 8.0.4.

- Error number: `MY-011153`; Symbol: `ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT`; SQLSTATE: `HY000`  
Message: Timeout waiting for reply of binlog (file: %s, pos: %lu), semi-sync up to file %s, position %lu.

`ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT` was added in 8.0.4.

- Error number: `MY-011154`; Symbol: `ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TRX_FAILED`; SQLSTATE: `HY000`  
Message: Assessment of waiting time for commitTrx failed at wait position (%s, %lu).

`ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TRX_FAILED` was added in 8.0.4.

- Error number: `MY-011155`; Symbol: `ER_SEMISYNC_RPL_SWITCHED_OFF`; SQLSTATE: `HY000`  
Message: Semi-sync replication switched OFF.

`ER_SEMISYNC_RPL_SWITCHED_OFF` was added in 8.0.4.

- Error number: `MY-011156`; Symbol: `ER_SEMISYNC_RPL_SWITCHED_ON`; SQLSTATE: `HY000`  
Message: Semi-sync replication switched ON at (%s, %lu).

`ER_SEMISYNC_RPL_SWITCHED_ON` was added in 8.0.4.

- 
- Error number: [MY-011157](#); Symbol: [ER\\_SEMISYNC\\_NO\\_SPACE\\_IN\\_THE\\_PKT](#); SQLSTATE: [HY000](#)  
Message: No enough space in the packet for semi-sync extra header, semi-sync replication disabled.  
[ER\\_SEMISYNC\\_NO\\_SPACE\\_IN\\_THE\\_PKT](#) was added in 8.0.4.
  - Error number: [MY-011158](#); Symbol: [ER\\_SEMISYNC\\_SYNC\\_HEADER\\_UPDATE\\_INFO](#); SQLSTATE: [HY000](#)  
Message: %s: server(%d), (%s, %lu) sync(%d), repl(%d).  
[ER\\_SEMISYNC\\_SYNC\\_HEADER\\_UPDATE\\_INFO](#) was added in 8.0.4.
  - Error number: [MY-011159](#); Symbol: [ER\\_SEMISYNC\\_FAILED\\_TO\\_INSERT\\_TRX\\_NODE](#); SQLSTATE: [HY000](#)  
Message: Semi-sync failed to insert tranx\_node for binlog file: %s, position: %lu.  
[ER\\_SEMISYNC\\_FAILED\\_TO\\_INSERT\\_TRX\\_NODE](#) was added in 8.0.4.
  - Error number: [MY-011160](#); Symbol: [ER\\_SEMISYNC\\_TRX\\_SKIPPED\\_AT\\_POS](#); SQLSTATE: [HY000](#)  
Message: %s: Transaction skipped at (%s, %lu).  
[ER\\_SEMISYNC\\_TRX\\_SKIPPED\\_AT\\_POS](#) was added in 8.0.4.
  - Error number: [MY-011161](#); Symbol: [ER\\_SEMISYNC\\_MASTER\\_FAILED\\_ON\\_NET\\_FLUSH](#); SQLSTATE: [HY000](#)  
Message: Semi-sync master failed on net\_flush() before waiting for replica reply.  
[ER\\_SEMISYNC\\_MASTER\\_FAILED\\_ON\\_NET\\_FLUSH](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011161](#); Symbol: [ER\\_SEMISYNC\\_SOURCE\\_FAILED\\_ON\\_NET\\_FLUSH](#); SQLSTATE: [HY000](#)  
Message: Semi-sync source failed on net\_flush() before waiting for replica reply.  
[ER\\_SEMISYNC\\_SOURCE\\_FAILED\\_ON\\_NET\\_FLUSH](#) was added in 8.0.33.
  - Error number: [MY-011162](#); Symbol: [ER\\_SEMISYNC\\_RECEIVED\\_ACK\\_IS\\_SMALLER](#); SQLSTATE: [HY000](#)  
Message: The received ack is smaller than m\_greatest\_ack.  
[ER\\_SEMISYNC\\_RECEIVED\\_ACK\\_IS\\_SMALLER](#) was added in 8.0.4.
  - Error number: [MY-011163](#); Symbol: [ER\\_SEMISYNC\\_ADD\\_ACK\\_TO\\_SLOT](#); SQLSTATE: [HY000](#)  
Message: Add the ack into slot %u.  
[ER\\_SEMISYNC\\_ADD\\_ACK\\_TO\\_SLOT](#) was added in 8.0.4.
  - Error number: [MY-011164](#); Symbol: [ER\\_SEMISYNC\\_UPDATE\\_EXISTING\\_SLAVE\\_ACK](#); SQLSTATE: [HY000](#)  
Message: Update an exsiting ack in slot %u.  
[ER\\_SEMISYNC\\_UPDATE\\_EXISTING\\_SLAVE\\_ACK](#) was added in 8.0.4, removed after 8.0.32.

- 
- Error number: [MY-011164](#); Symbol: [ER\\_SEMISYNC\\_UPDATE\\_EXISTING\\_REPLICA\\_ACK](#); SQLSTATE: [HY000](#)  
  
Message: Update an existing ack in slot %u.  
  
[ER\\_SEMISYNC\\_UPDATE\\_EXISTING\\_REPLICA\\_ACK](#) was added in 8.0.33.
  - Error number: [MY-011165](#); Symbol: [ER\\_SEMISYNC\\_FAILED\\_TO\\_START\\_ACK\\_RECEIVER\\_THD](#); SQLSTATE: [HY000](#)  
  
Message: Failed to start semi-sync ACK receiver thread, could not create thread(errno:%d).  
  
[ER\\_SEMISYNC\\_FAILED\\_TO\\_START\\_ACK\\_RECEIVER\\_THD](#) was added in 8.0.4.
  - Error number: [MY-011166](#); Symbol: [ER\\_SEMISYNC\\_STARTING\\_ACK\\_RECEIVER\\_THD](#); SQLSTATE: [HY000](#)  
  
Message: Starting ack receiver thread.  
  
[ER\\_SEMISYNC\\_STARTING\\_ACK\\_RECEIVER\\_THD](#) was added in 8.0.4.
  - Error number: [MY-011167](#); Symbol: [ER\\_SEMISYNC\\_FAILED\\_TO\\_WAIT\\_ON\\_DUMP\\_SOCKET](#); SQLSTATE: [HY000](#)  
  
Message: Failed to wait on semi-sync dump sockets, error: errno=%d.  
  
[ER\\_SEMISYNC\\_FAILED\\_TO\\_WAIT\\_ON\\_DUMP\\_SOCKET](#) was added in 8.0.4.
  - Error number: [MY-011168](#); Symbol: [ER\\_SEMISYNC\\_STOPPING\\_ACK\\_RECEIVER\\_THREAD](#); SQLSTATE: [HY000](#)  
  
Message: Stopping ack receiver thread.  
  
[ER\\_SEMISYNC\\_STOPPING\\_ACK\\_RECEIVER\\_THREAD](#) was added in 8.0.4.
  - Error number: [MY-011169](#); Symbol: [ER\\_SEMISYNC\\_FAILED\\_REGISTER\\_SLAVE\\_TO\\_RECEIVER](#); SQLSTATE: [HY000](#)  
  
Message: Failed to register slave to semi-sync ACK receiver thread.  
  
[ER\\_SEMISYNC\\_FAILED\\_REGISTER\\_SLAVE\\_TO\\_RECEIVER](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011169](#); Symbol: [ER\\_SEMISYNC\\_FAILED\\_REGISTER\\_REPLICA\\_TO\\_RECEIVER](#); SQLSTATE: [HY000](#)  
  
Message: Failed to register replica to semi-sync ACK receiver thread.  
  
[ER\\_SEMISYNC\\_FAILED\\_REGISTER\\_REPLICA\\_TO\\_RECEIVER](#) was added in 8.0.33.
  - Error number: [MY-011170](#); Symbol: [ER\\_SEMISYNC\\_START\\_BINLOG\\_DUMP\\_TO\\_SLAVE](#); SQLSTATE: [HY000](#)  
  
Message: Start %s binlog\_dump to slave (server\_id: %d), pos(%s, %lu).  
  
[ER\\_SEMISYNC\\_START\\_BINLOG\\_DUMP\\_TO\\_SLAVE](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011170](#); Symbol: [ER\\_SEMISYNC\\_START\\_BINLOG\\_DUMP\\_TO\\_REPLICA](#); SQLSTATE: [HY000](#)
-

---

Message: Start %s binlog\_dump to replica (server\_id: %d), pos(%s, %lu).

[ER\\_SEMISYNC\\_START\\_BINLOG\\_DUMP\\_TO\\_REPLICA](#) was added in 8.0.33.

- Error number: [MY-011171](#); Symbol: [ER\\_SEMISYNC\\_STOP\\_BINLOG\\_DUMP\\_TO\\_SLAVE](#); SQLSTATE: [HY000](#)

Message: Stop %s binlog\_dump to slave (server\_id: %d).

[ER\\_SEMISYNC\\_STOP\\_BINLOG\\_DUMP\\_TO\\_SLAVE](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011171](#); Symbol: [ER\\_SEMISYNC\\_STOP\\_BINLOG\\_DUMP\\_TO\\_REPLICA](#); SQLSTATE: [HY000](#)

Message: Stop %s binlog\_dump to replica (server\_id: %d).

[ER\\_SEMISYNC\\_STOP\\_BINLOG\\_DUMP\\_TO\\_REPLICA](#) was added in 8.0.33.

- Error number: [MY-011172](#); Symbol: [ER\\_SEMISYNC\\_UNREGISTER\\_TRX\\_OBSERVER\\_FAILED](#); SQLSTATE: [HY000](#)

Message: unregister\_trans\_observer failed.

[ER\\_SEMISYNC\\_UNREGISTER\\_TRX\\_OBSERVER\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-011173](#); Symbol: [ER\\_SEMISYNC\\_UNREGISTER\\_BINLOG\\_STORAGE\\_OBSERVER\\_FAILED](#); SQLSTATE: [HY000](#)

Message: unregister\_binlog\_storage\_observer failed.

[ER\\_SEMISYNC\\_UNREGISTER\\_BINLOG\\_STORAGE\\_OBSERVER\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-011174](#); Symbol: [ER\\_SEMISYNC\\_UNREGISTER\\_BINLOG\\_TRANSMIT\\_OBSERVER\\_FAILED](#); SQLSTATE: [HY000](#)

Message: unregister\_binlog\_transmit\_observer failed.

[ER\\_SEMISYNC\\_UNREGISTER\\_BINLOG\\_TRANSMIT\\_OBSERVER\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-011175](#); Symbol: [ER\\_SEMISYNC\\_UNREGISTERED\\_REPLICATOR](#); SQLSTATE: [HY000](#)

Message: unregister\_replicator OK.

[ER\\_SEMISYNC\\_UNREGISTERED\\_REPLICATOR](#) was added in 8.0.4.

- Error number: [MY-011176](#); Symbol: [ER\\_SEMISYNC\\_SOCKET\\_FD\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)

Message: Semisync replica socket fd is %u. select() cannot handle if the socket fd is bigger than %u (FD\_SETSIZE).

[ER\\_SEMISYNC\\_SOCKET\\_FD\\_TOO\\_LARGE](#) was added in 8.0.4.

- Error number: [MY-011177](#); Symbol: [ER\\_SEMISYNC\\_SLAVE\\_REPLY](#); SQLSTATE: [HY000](#)

Message: %s: reply - %d.

[ER\\_SEMISYNC\\_SLAVE\\_REPLY](#) was added in 8.0.4, removed after 8.0.32.

- 
- Error number: [MY-011177](#); Symbol: [ER\\_SEMISYNC\\_REPLICA\\_REPLY](#); SQLSTATE: [HY000](#)  
Message: %s: reply - %d.  
[ER\\_SEMISYNC\\_REPLICA\\_REPLY](#) was added in 8.0.33.
  - Error number: [MY-011178](#); Symbol: [ER\\_SEMISYNC\\_MISSING\\_MAGIC\\_NO\\_FOR\\_SEMISYNC\\_PKT](#); SQLSTATE: [HY000](#)  
Message: Missing magic number for semi-sync packet, packet len: %lu.  
[ER\\_SEMISYNC\\_MISSING\\_MAGIC\\_NO\\_FOR\\_SEMISYNC\\_PKT](#) was added in 8.0.4.
  - Error number: [MY-011179](#); Symbol: [ER\\_SEMISYNC\\_SLAVE\\_START](#); SQLSTATE: [HY000](#)  
Message: Slave I/O thread: Start %s replication to master '%s@%s:%d' in log '%s' at position %lu.  
[ER\\_SEMISYNC\\_SLAVE\\_START](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011179](#); Symbol: [ER\\_SEMISYNC\\_REPLICA\\_START](#); SQLSTATE: [HY000](#)  
Message: Replica I/O thread: Start %s replication to source '%s@%s:%d' in log '%s' at position %lu.  
[ER\\_SEMISYNC\\_REPLICA\\_START](#) was added in 8.0.33.
  - Error number: [MY-011180](#); Symbol: [ER\\_SEMISYNC\\_SLAVE\\_REPLY\\_WITH\\_BINLOG\\_INFO](#); SQLSTATE: [HY000](#)  
Message: %s: reply (%s, %lu).  
[ER\\_SEMISYNC\\_SLAVE\\_REPLY\\_WITH\\_BINLOG\\_INFO](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011180](#); Symbol: [ER\\_SEMISYNC\\_REPLICA\\_REPLY\\_WITH\\_BINLOG\\_INFO](#); SQLSTATE: [HY000](#)  
Message: %s: reply (%s, %lu).  
[ER\\_SEMISYNC\\_REPLICA\\_REPLY\\_WITH\\_BINLOG\\_INFO](#) was added in 8.0.33.
  - Error number: [MY-011181](#); Symbol: [ER\\_SEMISYNC\\_SLAVE\\_NET\\_FLUSH\\_REPLY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Semi-sync slave net\_flush() reply failed.  
[ER\\_SEMISYNC\\_SLAVE\\_NET\\_FLUSH\\_REPLY\\_FAILED](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011181](#); Symbol: [ER\\_SEMISYNC\\_REPLICA\\_NET\\_FLUSH\\_REPLY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Semi-sync replica net\_flush() reply failed.  
[ER\\_SEMISYNC\\_REPLICA\\_NET\\_FLUSH\\_REPLY\\_FAILED](#) was added in 8.0.33.
  - Error number: [MY-011182](#); Symbol: [ER\\_SEMISYNC\\_SLAVE\\_SEND\\_REPLY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Semi-sync slave send reply failed: %s (%d).  
[ER\\_SEMISYNC\\_SLAVE\\_SEND\\_REPLY\\_FAILED](#) was added in 8.0.4, removed after 8.0.32.

- 
- Error number: [MY-011182](#); Symbol: [ER\\_SEMISYNC\\_REPLICA\\_SEND\\_REPLY\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Semi-sync replica send reply failed: %s (%d).  
  
[ER\\_SEMISYNC\\_REPLICA\\_SEND\\_REPLY\\_FAILED](#) was added in 8.0.33.
  - Error number: [MY-011183](#); Symbol: [ER\\_SEMISYNC\\_EXECUTION\\_FAILED\\_ON\\_MASTER](#); SQLSTATE: [HY000](#)  
  
Message: Execution failed on master: %s; error %d  
  
[ER\\_SEMISYNC\\_EXECUTION\\_FAILED\\_ON\\_MASTER](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011183](#); Symbol: [ER\\_SEMISYNC\\_EXECUTION\\_FAILED\\_ON\\_SOURCE](#); SQLSTATE: [HY000](#)  
  
Message: Execution failed on source: %s; error %d  
  
[ER\\_SEMISYNC\\_EXECUTION\\_FAILED\\_ON\\_SOURCE](#) was added in 8.0.33.
  - Error number: [MY-011184](#); Symbol: [ER\\_SEMISYNC\\_NOT\\_SUPPORTED\\_BY\\_MASTER](#); SQLSTATE: [HY000](#)  
  
Message: Master server does not support semi-sync, fallback to asynchronous replication  
  
[ER\\_SEMISYNC\\_NOT\\_SUPPORTED\\_BY\\_MASTER](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011184](#); Symbol: [ER\\_SEMISYNC\\_NOT\\_SUPPORTED\\_BY\\_SOURCE](#); SQLSTATE: [HY000](#)  
  
Message: Source server does not support semi-sync, fallback to asynchronous replication  
  
[ER\\_SEMISYNC\\_NOT\\_SUPPORTED\\_BY\\_SOURCE](#) was added in 8.0.33.
  - Error number: [MY-011185](#); Symbol: [ER\\_SEMISYNC\\_SLAVE\\_SET\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Set 'rpl\_semi\_sync\_replica=1' on master failed  
  
[ER\\_SEMISYNC\\_SLAVE\\_SET\\_FAILED](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011185](#); Symbol: [ER\\_SEMISYNC\\_REPLICA\\_SET\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Set 'rpl\_semi\_sync\_replica=1' on source failed  
  
[ER\\_SEMISYNC\\_REPLICA\\_SET\\_FAILED](#) was added in 8.0.33.
  - Error number: [MY-011186](#); Symbol: [ER\\_SEMISYNC\\_FAILED\\_TO\\_STOP\\_ACK\\_RECEIVER\\_THD](#); SQLSTATE: [HY000](#)  
  
Message: Failed to stop ack receiver thread on my\_thread\_join, errno(%d).  
  
[ER\\_SEMISYNC\\_FAILED\\_TO\\_STOP\\_ACK\\_RECEIVER\\_THD](#) was added in 8.0.4.

- 
- Error number: [MY-011187](#); Symbol: [ER\\_FIREWALL\\_FAILED\\_TO\\_READ\\_FIREWALL\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: Failed to read the firewall tables  
[ER\\_FIREWALL\\_FAILED\\_TO\\_READ\\_FIREWALL\\_TABLES](#) was added in 8.0.4.
  - Error number: [MY-011188](#); Symbol: [ER\\_FIREWALL\\_FAILED\\_TO\\_REG\\_DYNAMIC\\_PRIVILEGES](#); SQLSTATE: [HY000](#)  
Message: Failed to register dynamic privileges  
[ER\\_FIREWALL\\_FAILED\\_TO\\_REG\\_DYNAMIC\\_PRIVILEGES](#) was added in 8.0.4.
  - Error number: [MY-011189](#); Symbol: [ER\\_FIREWALL\\_RECORDING\\_STMT\\_WAS\\_TRUNCATED](#); SQLSTATE: [HY000](#)  
Message: Statement was truncated and not recorded: %s  
[ER\\_FIREWALL\\_RECORDING\\_STMT\\_WAS\\_TRUNCATED](#) was added in 8.0.4.
  - Error number: [MY-011190](#); Symbol: [ER\\_FIREWALL\\_RECORDING\\_STMT\\_WITHOUT\\_TEXT](#); SQLSTATE: [HY000](#)  
Message: Statement with no text was not recorded  
[ER\\_FIREWALL\\_RECORDING\\_STMT\\_WITHOUT\\_TEXT](#) was added in 8.0.4.
  - Error number: [MY-011191](#); Symbol: [ER\\_FIREWALL\\_SUSPICIOUS\\_STMT](#); SQLSTATE: [HY000](#)  
Message: SUSPICIOUS STATEMENT from '%s'. Reason: %s Statement: %s  
[ER\\_FIREWALL\\_SUSPICIOUS\\_STMT](#) was added in 8.0.4.
  - Error number: [MY-011192](#); Symbol: [ER\\_FIREWALL\\_ACCESS\\_DENIED](#); SQLSTATE: [HY000](#)  
Message: ACCESS DENIED for '%s'. Reason: %s Statement: %s  
[ER\\_FIREWALL\\_ACCESS\\_DENIED](#) was added in 8.0.4.
  - Error number: [MY-011193](#); Symbol: [ER\\_FIREWALL\\_SKIPPED\\_UNKNOWN\\_USER\\_MODE](#); SQLSTATE: [HY000](#)  
Message: Skipped unknown user mode '%s'  
[ER\\_FIREWALL\\_SKIPPED\\_UNKNOWN\\_USER\\_MODE](#) was added in 8.0.4.
  - Error number: [MY-011194](#); Symbol: [ER\\_FIREWALL\\_RELOADING\\_CACHE](#); SQLSTATE: [HY000](#)  
Message: Reloading cache from disk  
[ER\\_FIREWALL\\_RELOADING\\_CACHE](#) was added in 8.0.4.
  - Error number: [MY-011195](#); Symbol: [ER\\_FIREWALL\\_RESET\\_FOR\\_USER](#); SQLSTATE: [HY000](#)  
Message: FIREWALL RESET for '%s'  
[ER\\_FIREWALL\\_RESET\\_FOR\\_USER](#) was added in 8.0.4.
  - Error number: [MY-011196](#); Symbol: [ER\\_FIREWALL\\_STATUS\\_FLUSHED](#); SQLSTATE: [HY000](#)

---

Message: Counters are reset to zero

`ER_FIREWALL_STATUS_FLUSHED` was added in 8.0.4.

- Error number: `MY-011197`; Symbol: `ER_KEYRING_LOGGER_ERROR_MSG`; SQLSTATE: `HY000`

Message: %s

`ER_KEYRING_LOGGER_ERROR_MSG` was added in 8.0.4.

- Error number: `MY-011198`; Symbol: `ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED`; SQLSTATE: `HY000`

Message: Audit Log plugin supports filtering mode, which has not been installed yet. Audit Log plugin will run in the legacy mode, which will be removed in the next release.

`ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED` was added in 8.0.4.

- Error number: `MY-011199`; Symbol: `ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST`; SQLSTATE: `HY000`

Message: Previously exclude list is used, now we start using include list, exclude list is set to NULL.

`ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST` was added in 8.0.4.

- Error number: `MY-011200`; Symbol: `ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICIES`; SQLSTATE: `HY000`

Message: Cannot set `audit_log_policy` simultaneously with either `audit_log_connection_policy` or `audit_log_statement_policy`, setting `audit_log_connection_policy` and `audit_log_statement_policy` based on `audit_log_policy`.

`ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICIES` was added in 8.0.4.

- Error number: `MY-011201`; Symbol: `ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED`; SQLSTATE: `HY000`

Message: Both include and exclude lists provided, include list is preferred, exclude list is set to NULL.

`ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED` was added in 8.0.4.

- Error number: `MY-011202`; Symbol: `ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR`; SQLSTATE: `HY000`

Message: Could not access '%s' directory.

`ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR` was added in 8.0.4.

- Error number: `MY-011203`; Symbol: `ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED`; SQLSTATE: `HY000`

Message: Could not rename file from '%s' to '%s'.

`ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED` was added in 8.0.4.

- Error number: `MY-011204`; Symbol: `ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS`; SQLSTATE: `HY000`



---

Message: File '%s' should not exist. It may be incomplete. The server crashed.

[ER\\_AUDIT\\_LOG\\_WRITER\\_DEST\\_FILE\\_ALREADY\\_EXISTS](#) was added in 8.0.4.

- Error number: [MY-011205](#); Symbol: [ER\\_AUDIT\\_LOG\\_WRITER\\_RENAME\\_FILE\\_FAILED\\_REMOVE\\_FILE\\_MANUALLY](#); SQLSTATE: [HY000](#)

Message: Could not rename file from '%s' to '%s'. Remove the file manually.

[ER\\_AUDIT\\_LOG\\_WRITER\\_RENAME\\_FILE\\_FAILED\\_REMOVE\\_FILE\\_MANUALLY](#) was added in 8.0.4.

- Error number: [MY-011206](#); Symbol: [ER\\_AUDIT\\_LOG\\_WRITER\\_INCOMPLETE\\_FILE\\_RENAMED](#); SQLSTATE: [HY000](#)

Message: Incomplete file renamed from '%s' to '%s'.

[ER\\_AUDIT\\_LOG\\_WRITER\\_INCOMPLETE\\_FILE\\_RENAMED](#) was added in 8.0.4.

- Error number: [MY-011207](#); Symbol: [ER\\_AUDIT\\_LOG\\_WRITER\\_FAILED\\_TO\\_WRITE\\_TO\\_FILE](#); SQLSTATE: [HY000](#)

Message: Error writing file '%s' (errno: %d - %s).

[ER\\_AUDIT\\_LOG\\_WRITER\\_FAILED\\_TO\\_WRITE\\_TO\\_FILE](#) was added in 8.0.4.

- Error number: [MY-011208](#); Symbol: [ER\\_AUDIT\\_LOG\\_EC\\_WRITER\\_FAILED\\_TO\\_INIT\\_ENCRYPTION](#); SQLSTATE: [HY000](#)

Message: Could not initialize audit log file encryption.

[ER\\_AUDIT\\_LOG\\_EC\\_WRITER\\_FAILED\\_TO\\_INIT\\_ENCRYPTION](#) was added in 8.0.4.

- Error number: [MY-011209](#); Symbol: [ER\\_AUDIT\\_LOG\\_EC\\_WRITER\\_FAILED\\_TO\\_INIT\\_COMPRESSION](#); SQLSTATE: [HY000](#)

Message: Could not initialize audit log file compression.

[ER\\_AUDIT\\_LOG\\_EC\\_WRITER\\_FAILED\\_TO\\_INIT\\_COMPRESSION](#) was added in 8.0.4.

- Error number: [MY-011210](#); Symbol: [ER\\_AUDIT\\_LOG\\_EC\\_WRITER\\_FAILED\\_TO\\_CREATE\\_FILE](#); SQLSTATE: [HY000](#)

Message: Could not create '%s' file for audit logging.

[ER\\_AUDIT\\_LOG\\_EC\\_WRITER\\_FAILED\\_TO\\_CREATE\\_FILE](#) was added in 8.0.4.

- Error number: [MY-011211](#); Symbol: [ER\\_AUDIT\\_LOG\\_RENAME\\_LOG\\_FILE\\_BEFORE\\_FLUSH](#); SQLSTATE: [HY000](#)

Message: Audit log file (%s) must be manually renamed before audit\_log\_flush is set to true.

[ER\\_AUDIT\\_LOG\\_RENAME\\_LOG\\_FILE\\_BEFORE\\_FLUSH](#) was added in 8.0.4.

- Error number: [MY-011212](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_RESULT\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_AUDIT\\_LOG\\_FILTER\\_RESULT\\_MSG](#) was added in 8.0.4.

- 
- Error number: [MY-011213](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_FAILED\\_TO\\_PARSE](#); SQLSTATE: [HY000](#)  
  
Message: Error parsing JSON event. Event not accessible.  
  
[ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_FAILED\\_TO\\_PARSE](#) was added in 8.0.4.
  - Error number: [MY-011214](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_BUF\\_TOO\\_SMALL](#); SQLSTATE: [HY000](#)  
  
Message: Buffer is too small to hold JSON event. Number of events skipped: %zu.  
  
[ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_BUF\\_TOO\\_SMALL](#) was added in 8.0.4.
  - Error number: [MY-011215](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_FAILED\\_TO\\_OPEN\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: Could not open JSON file for reading. Reading next file if exists.  
  
[ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_FAILED\\_TO\\_OPEN\\_FILE](#) was added in 8.0.4.
  - Error number: [MY-011216](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_FILE\\_PARSING\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: JSON file parsing error. Reading next file if exists  
  
[ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_FILE\\_PARSING\\_ERROR](#) was added in 8.0.4.
  - Error number: [MY-011217](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_INVALID\\_COLUMN\\_COUNT](#); SQLSTATE: [HY000](#)  
  
Message: Invalid column count in the '%s.%s' table.  
  
[ER\\_AUDIT\\_LOG\\_FILTER\\_INVALID\\_COLUMN\\_COUNT](#) was added in 8.0.4, removed after 8.0.25.
  - Error number: [MY-011218](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_INVALID\\_COLUMN\\_DEFINITION](#); SQLSTATE: [HY000](#)  
  
Message: Invalid column definition of the '%s.%s' table.  
  
[ER\\_AUDIT\\_LOG\\_FILTER\\_INVALID\\_COLUMN\\_DEFINITION](#) was added in 8.0.4, removed after 8.0.25.
  - Error number: [MY-011219](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_STORE\\_TABLE\\_FLDS](#); SQLSTATE: [HY000](#)  
  
Message: Could not store field of the %s table.  
  
[ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_STORE\\_TABLE\\_FLDS](#) was added in 8.0.4.
  - Error number: [MY-011220](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_UPDATE\\_TABLE](#); SQLSTATE: [HY000](#)  
  
Message: Could not update %s table.  
  
[ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_UPDATE\\_TABLE](#) was added in 8.0.4.
  - Error number: [MY-011221](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_INSERT\\_INTO\\_TABLE](#); SQLSTATE: [HY000](#)

---

Message: Could not insert into %s table.

[ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_INSERT\\_INTO\\_TABLE](#) was added in 8.0.4.

- Error number: [MY-011222](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_DELETE\\_FROM\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not delete from %s table.

[ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_DELETE\\_FROM\\_TABLE](#) was added in 8.0.4.

- Error number: [MY-011223](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_INIT\\_TABLE\\_FOR\\_READ](#); SQLSTATE: [HY000](#)

Message: Could not initialize %s table for reading.

[ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_INIT\\_TABLE\\_FOR\\_READ](#) was added in 8.0.4.

- Error number: [MY-011224](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_READ\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not read %s table.

[ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_READ\\_TABLE](#) was added in 8.0.4.

- Error number: [MY-011225](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_CLOSE\\_TABLE\\_AFTER\\_READING](#); SQLSTATE: [HY000](#)

Message: Could not close %s table reading.

[ER\\_AUDIT\\_LOG\\_FILTER\\_FAILED\\_TO\\_CLOSE\\_TABLE\\_AFTER\\_READING](#) was added in 8.0.4.

- Error number: [MY-011226](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_USER\\_AND\\_HOST\\_CANNOT\\_BE\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: Both user and host columns of %s table cannot be empty.

[ER\\_AUDIT\\_LOG\\_FILTER\\_USER\\_AND\\_HOST\\_CANNOT\\_BE\\_EMPTY](#) was added in 8.0.4.

- Error number: [MY-011227](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_FLD\\_FILTERNAME\\_CANNOT\\_BE\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: Filtername column of %s table cannot be empty.

[ER\\_AUDIT\\_LOG\\_FILTER\\_FLD\\_FILTERNAME\\_CANNOT\\_BE\\_EMPTY](#) was added in 8.0.4.

- Error number: [MY-011228](#); Symbol: [ER\\_VALIDATE\\_PWD\\_DICT\\_FILE\\_NOT\\_SPECIFIED](#); SQLSTATE: [HY000](#)

Message: Dictionary file not specified

[ER\\_VALIDATE\\_PWD\\_DICT\\_FILE\\_NOT\\_SPECIFIED](#) was added in 8.0.4.

- 
- Error number: `MY-011229`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED`; SQLSTATE: `HY000`  
Message: Dictionary file not loaded  
`ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED` was added in 8.0.4.
  - Error number: `MY-011230`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_TOO_BIG`; SQLSTATE: `HY000`  
Message: Dictionary file size exceeded `MAX_DICTIONARY_FILE_LENGTH`, not loaded  
`ER_VALIDATE_PWD_DICT_FILE_TOO_BIG` was added in 8.0.4.
  - Error number: `MY-011231`; Symbol: `ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE`; SQLSTATE: `HY000`  
Message: Exception while reading the dictionary file  
`ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE` was added in 8.0.4.
  - Error number: `MY-011232`; Symbol: `ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX`; SQLSTATE: `HY000`  
Message: Can't retrieve the %s from the security context  
`ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX` was added in 8.0.4.
  - Error number: `MY-011233`; Symbol: `ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX`; SQLSTATE: `HY000`  
Message: Can't retrieve the security context  
`ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX` was added in 8.0.4.
  - Error number: `MY-011234`; Symbol: `ER_VALIDATE_PWD_LENGTH_CHANGED`; SQLSTATE: `HY000`  
Message: Effective value of `validate_password_length` is changed. New value is %d  
`ER_VALIDATE_PWD_LENGTH_CHANGED` was added in 8.0.4.
  - Error number: `MY-011235`; Symbol: `ER_REWRITER_QUERY_ERROR_MSG`; SQLSTATE: `HY000`  
Message: %s  
`ER_REWRITER_QUERY_ERROR_MSG` was added in 8.0.4.
  - Error number: `MY-011236`; Symbol: `ER_REWRITER_QUERY_FAILED`; SQLSTATE: `HY000`  
Message: Rewritten query failed to parse:%s  
`ER_REWRITER_QUERY_FAILED` was added in 8.0.4.
  - Error number: `MY-011237`; Symbol: `ER_XPLUGIN_STARTUP_FAILED`; SQLSTATE: `HY000`  
Message: Startup failed with error "%s"  
`ER_XPLUGIN_STARTUP_FAILED` was added in 8.0.4.
  - Error number: `MY-011238`; Symbol: `ER_XPLUGIN_SERVER_EXITING`; SQLSTATE: `HY000`

---

Message: Exiting

[ER\\_XPLUGIN\\_SERVER\\_EXITING](#) was added in 8.0.4, removed after 8.0.12.

- Error number: [MY-011239](#); Symbol: [ER\\_XPLUGIN\\_SERVER\\_EXITED](#); SQLSTATE: [HY000](#)

Message: Exit done

[ER\\_XPLUGIN\\_SERVER\\_EXITED](#) was added in 8.0.4, removed after 8.0.12.

- Error number: [MY-011240](#); Symbol: [ER\\_XPLUGIN\\_USING\\_SSL\\_CONF\\_FROM\\_SERVER](#); SQLSTATE: [HY000](#)

Message: Using SSL configuration from MySQL Server

[ER\\_XPLUGIN\\_USING\\_SSL\\_CONF\\_FROM\\_SERVER](#) was added in 8.0.4.

- Error number: [MY-011241](#); Symbol: [ER\\_XPLUGIN\\_USING\\_SSL\\_CONF\\_FROM\\_MYSQLX](#); SQLSTATE: [HY000](#)

Message: Using SSL configuration from Mysqlx Plugin

[ER\\_XPLUGIN\\_USING\\_SSL\\_CONF\\_FROM\\_MYSQLX](#) was added in 8.0.4.

- Error number: [MY-011242](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_USE\\_SSL\\_CONF](#); SQLSTATE: [HY000](#)

Message: Neither MySQL Server nor Mysqlx Plugin has valid SSL configuration

[ER\\_XPLUGIN\\_FAILED\\_TO\\_USE\\_SSL\\_CONF](#) was added in 8.0.4.

- Error number: [MY-011243](#); Symbol: [ER\\_XPLUGIN\\_USING\\_SSL\\_FOR\\_TLS\\_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Using %s for TLS connections

[ER\\_XPLUGIN\\_USING\\_SSL\\_FOR\\_TLS\\_CONNECTION](#) was added in 8.0.4.

- Error number: [MY-011244](#); Symbol: [ER\\_XPLUGIN\\_REFERENCE\\_TO\\_SECURE\\_CONN\\_WITH\\_XPLUGIN](#); SQLSTATE: [HY000](#)

Message: For more information, please see the Using Secure Connections with X Plugin section in the MySQL documentation

[ER\\_XPLUGIN\\_REFERENCE\\_TO\\_SECURE\\_CONN\\_WITH\\_XPLUGIN](#) was added in 8.0.4.

- Error number: [MY-011245](#); Symbol: [ER\\_XPLUGIN\\_ERROR\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_XPLUGIN\\_ERROR\\_MSG](#) was added in 8.0.4.

- Error number: [MY-011246](#); Symbol: [ER\\_SHA\\_PWD\\_FAILED\\_TO\\_PARSE\\_AUTH\\_STRING](#); SQLSTATE: [HY000](#)

Message: Failed to parse stored authentication string for %s. Please check if mysql.user table not corrupted

[ER\\_SHA\\_PWD\\_FAILED\\_TO\\_PARSE\\_AUTH\\_STRING](#) was added in 8.0.4.

- 
- Error number: [MY-011247](#); Symbol: [ER\\_SHA\\_PWD\\_FAILED\\_TO\\_GENERATE\\_MULTI\\_ROUND\\_HASH](#); SQLSTATE: [HY000](#)

Message: Error in generating multi-round hash for %. Plugin can not perform authentication without it. This may be a transient problem

[ER\\_SHA\\_PWD\\_FAILED\\_TO\\_GENERATE\\_MULTI\\_ROUND\\_HASH](#) was added in 8.0.4.

- Error number: [MY-011248](#); Symbol: [ER\\_SHA\\_PWD\\_AUTH\\_REQUIRES\\_RSA\\_OR\\_SSL](#); SQLSTATE: [HY000](#)

Message: Authentication requires either RSA keys or SSL encryption

[ER\\_SHA\\_PWD\\_AUTH\\_REQUIRES\\_RSA\\_OR\\_SSL](#) was added in 8.0.4.

- Error number: [MY-011249](#); Symbol: [ER\\_SHA\\_PWD\\_RSA\\_KEY\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)

Message: RSA key cipher length of %u is too long. Max value is %u

[ER\\_SHA\\_PWD\\_RSA\\_KEY\\_TOO\\_LONG](#) was added in 8.0.4.

- Error number: [MY-011250](#); Symbol: [ER\\_PLUGIN\\_COMMON\\_FAILED\\_TO\\_OPEN\\_FILTER\\_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open the %s filter tables

[ER\\_PLUGIN\\_COMMON\\_FAILED\\_TO\\_OPEN\\_FILTER\\_TABLES](#) was added in 8.0.4.

- Error number: [MY-011251](#); Symbol: [ER\\_PLUGIN\\_COMMON\\_FAILED\\_TO\\_OPEN\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to open '%s.%s' %s table

[ER\\_PLUGIN\\_COMMON\\_FAILED\\_TO\\_OPEN\\_TABLE](#) was added in 8.0.4.

- Error number: [MY-011252](#); Symbol: [ER\\_AUTH\\_LDAP\\_ERROR\\_LOGGER\\_ERROR\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_AUTH\\_LDAP\\_ERROR\\_LOGGER\\_ERROR\\_MSG](#) was added in 8.0.4.

- Error number: [MY-011253](#); Symbol: [ER\\_CONN\\_CONTROL\\_ERROR\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_CONN\\_CONTROL\\_ERROR\\_MSG](#) was added in 8.0.4.

- Error number: [MY-011254](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_GRP\\_RPL\\_ERROR\\_MSG](#) was added in 8.0.4.

- Error number: [MY-011255](#); Symbol: [ER\\_SHA\\_PWD\\_SALT\\_FOR\\_USER\\_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Password salt for user '%s' is corrupt

[ER\\_SHA\\_PWD\\_SALT\\_FOR\\_USER\\_CORRUPT](#) was added in 8.0.4.

- 
- Error number: [MY-011256](#); Symbol: [ER\\_SYS\\_VAR\\_COMPONENT\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Out of memory for component system variable '%s'.  
[ER\\_SYS\\_VAR\\_COMPONENT\\_OOM](#) was added in 8.0.4.
  - Error number: [MY-011257](#); Symbol: [ER\\_SYS\\_VAR\\_COMPONENT\\_VARIABLE\\_SET\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)  
Message: variable %s of component %s was forced to be read-only: string variable without update\_func and PLUGIN\_VAR\_MEMALLOC flag.  
[ER\\_SYS\\_VAR\\_COMPONENT\\_VARIABLE\\_SET\\_READ\\_ONLY](#) was added in 8.0.4.
  - Error number: [MY-011258](#); Symbol: [ER\\_SYS\\_VAR\\_COMPONENT\\_UNKNOWN\\_VARIABLE\\_TYPE](#); SQLSTATE: [HY000](#)  
Message: Unknown variable type code 0x%x in component '%s'.  
[ER\\_SYS\\_VAR\\_COMPONENT\\_UNKNOWN\\_VARIABLE\\_TYPE](#) was added in 8.0.4.
  - Error number: [MY-011259](#); Symbol: [ER\\_SYS\\_VAR\\_COMPONENT\\_FAILED\\_TO\\_PARSE\\_VARIABLE\\_OPTIONS](#); SQLSTATE: [HY000](#)  
Message: Parsing options for variable '%s' failed.  
[ER\\_SYS\\_VAR\\_COMPONENT\\_FAILED\\_TO\\_PARSE\\_VARIABLE\\_OPTIONS](#) was added in 8.0.4.
  - Error number: [MY-011260](#); Symbol: [ER\\_SYS\\_VAR\\_COMPONENT\\_FAILED\\_TO\\_MAKE\\_VARIABLE\\_PERSISTENT](#); SQLSTATE: [HY000](#)  
Message: Setting persistent options for component variable '%s' failed.  
[ER\\_SYS\\_VAR\\_COMPONENT\\_FAILED\\_TO\\_MAKE\\_VARIABLE\\_PERSISTENT](#) was added in 8.0.4.
  - Error number: [MY-011261](#); Symbol: [ER\\_COMPONENT\\_FILTER\\_CONFUSED](#); SQLSTATE: [HY000](#)  
Message: The log-filter component "%s" got confused at "%s" (state: %s) ...  
[ER\\_COMPONENT\\_FILTER\\_CONFUSED](#) was added in 8.0.4.
  - Error number: [MY-011262](#); Symbol: [ER\\_STOP\\_SLAVE\\_IO\\_THREAD\\_DISK\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Waiting until I/O thread for channel '%s' finish writing to disk before stopping. Free some disk space or use 'KILL' to abort I/O thread operation. Notice that aborting the I/O thread while rotating the relay log might corrupt the relay logs, requiring a server restart to fix it.  
[ER\\_STOP\\_SLAVE\\_IO\\_THREAD\\_DISK\\_SPACE](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-011262](#); Symbol: [ER\\_STOP\\_REPLICA\\_IO\\_THREAD\\_DISK\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Waiting until I/O thread for channel '%s' finish writing to disk before stopping. Free some disk space or use 'KILL' to abort I/O thread operation. Notice that aborting the I/O thread while rotating the relay log might corrupt the relay logs, requiring a server restart to fix it.  
[ER\\_STOP\\_REPLICA\\_IO\\_THREAD\\_DISK\\_SPACE](#) was added in 8.0.33.
  - Error number: [MY-011263](#); Symbol: [ER\\_LOG\\_FILE\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)

---

Message: Could not use %s for logging (error %d - %s). Turning logging off for the server process. To turn it on again: fix the cause, then %s restart the MySQL server.

`ER_LOG_FILE_CANNOT_OPEN` was added in 8.0.2.

- Error number: `MY-011268`; Symbol: `ER_PERSIST_OPTION_STATUS`; SQLSTATE: `HY000`

Message: Configuring persisted options failed: "%s".

`ER_PERSIST_OPTION_STATUS` was added in 8.0.11.

- Error number: `MY-011269`; Symbol: `ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS`; SQLSTATE: `HY000`

Message: The storage engine '%s' does not provide dynamic table statistics

`ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS` was added in 8.0.11.

- Error number: `MY-011272`; Symbol: `ER_SSL_FIPS_MODE_ERROR`; SQLSTATE: `HY000`

Message: SSL fips mode error: %s

`ER_SSL_FIPS_MODE_ERROR` was added in 8.0.11.

- Error number: `MY-011273`; Symbol: `ER_CONN_INIT_CONNECT_IGNORED`; SQLSTATE: `HY000`

Message: init\_connect variable is ignored for user: %s host: %s due to expired password.

`ER_CONN_INIT_CONNECT_IGNORED` was added in 8.0.11.

- Error number: `MY-011275`; Symbol: `ER_REWRITER_OOM`; SQLSTATE: `HY000`

Message: Out of memory.

`ER_REWRITER_OOM` was added in 8.0.11.

- Error number: `MY-011276`; Symbol: `ER_REWRITER_TABLE_MALFORMED_ERROR`; SQLSTATE: `HY000`

Message: Wrong column count or names when loading rules.

`ER_REWRITER_TABLE_MALFORMED_ERROR` was added in 8.0.11.

- Error number: `MY-011277`; Symbol: `ER_REWRITER_LOAD_FAILED`; SQLSTATE: `HY000`

Message: Some rules failed to load.

`ER_REWRITER_LOAD_FAILED` was added in 8.0.11.

- Error number: `MY-011278`; Symbol: `ER_REWRITER_READ_FAILED`; SQLSTATE: `HY000`

Message: Got error from storage engine while refreshing rewrite rules.

`ER_REWRITER_READ_FAILED` was added in 8.0.11.

- Error number: `MY-011279`; Symbol: `ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize Connection\_event\_coordinator



---

`ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED` was added in 8.0.11.

- Error number: `MY-011280`; Symbol: `ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_UPDATE_FAILED`; SQLSTATE: `HY000`

Message: Failed to update connection delay triggered stats

`ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_UPDATE_FAILED` was added in 8.0.11.

- Error number: `MY-011281`; Symbol: `ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESET_FAILED`; SQLSTATE: `HY000`

Message: Failed to reset connection delay triggered stats

`ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESET_FAILED` was added in 8.0.11.

- Error number: `MY-011282`; Symbol: `ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE`; SQLSTATE: `HY000`

Message: Unexpected option type for connection delay.

`ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE` was added in 8.0.11.

- Error number: `MY-011283`; Symbol: `ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize Connection\_delay\_action

`ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED` was added in 8.0.11.

- Error number: `MY-011284`; Symbol: `ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY`; SQLSTATE: `HY000`

Message: Could not set %s delay for connection delay.

`ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY` was added in 8.0.11.

- Error number: `MY-011285`; Symbol: `ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HASH`; SQLSTATE: `HY000`

Message: Failed to update connection delay hash for account : %s

`ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HASH` was added in 8.0.11.

- Error number: `MY-011286`; Symbol: `ER_XPLUGIN_FORCE_STOP_CLIENT`; SQLSTATE: `HY000`

Message: %s: Force stopping client because exception occurred: %s

`ER_XPLUGIN_FORCE_STOP_CLIENT` was added in 8.0.11.

- Error number: `MY-011287`; Symbol: `ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED`; SQLSTATE: `HY000`

Message: %s.%u: Maximum number of authentication attempts reached, login failed.

`ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED` was added in 8.0.11.

- 
- Error number: [MY-011288](#); Symbol: [ER\\_XPLUGIN\\_BUFFER\\_PAGE\\_ALLOC\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Error allocating Buffer\_page: %s  
[ER\\_XPLUGIN\\_BUFFER\\_PAGE\\_ALLOC\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011289](#); Symbol: [ER\\_XPLUGIN\\_DETECTED\\_HANGING\\_CLIENTS](#); SQLSTATE: [HY000](#)  
Message: Detected %u hanging client(s)  
[ER\\_XPLUGIN\\_DETECTED\\_HANGING\\_CLIENTS](#) was added in 8.0.11.
  - Error number: [MY-011290](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_ACCEPT\\_CLIENT](#); SQLSTATE: [HY000](#)  
Message: Error accepting client  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_ACCEPT\\_CLIENT](#) was added in 8.0.11.
  - Error number: [MY-011291](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_SCHEDULE\\_CLIENT](#); SQLSTATE: [HY000](#)  
Message: Internal error scheduling client for execution  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_SCHEDULE\\_CLIENT](#) was added in 8.0.11.
  - Error number: [MY-011292](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_PREPARE\\_IO\\_INTERFACES](#); SQLSTATE: [HY000](#)  
Message: Preparation of I/O interfaces failed, X Protocol won't be accessible  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_PREPARE\\_IO\\_INTERFACES](#) was added in 8.0.11.
  - Error number: [MY-011293](#); Symbol: [ER\\_XPLUGIN\\_SRV\\_SESSION\\_INIT\\_THREAD\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: srv\_session\_init\_thread returned error  
[ER\\_XPLUGIN\\_SRV\\_SESSION\\_INIT\\_THREAD\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011294](#); Symbol: [ER\\_XPLUGIN\\_UNABLE\\_TO\\_USE\\_USER\\_SESSION\\_ACCOUNT](#); SQLSTATE: [HY000](#)  
Message: Unable to use user mysql.session account when connecting the server for internal plugin requests.  
[ER\\_XPLUGIN\\_UNABLE\\_TO\\_USE\\_USER\\_SESSION\\_ACCOUNT](#) was added in 8.0.11.
  - Error number: [MY-011295](#); Symbol: [ER\\_XPLUGIN\\_REFERENCE\\_TO\\_USER\\_ACCOUNT\\_DOC\\_SECTION](#); SQLSTATE: [HY000](#)  
Message: For more information, please see the X Plugin User Account section in the MySQL documentation  
[ER\\_XPLUGIN\\_REFERENCE\\_TO\\_USER\\_ACCOUNT\\_DOC\\_SECTION](#) was added in 8.0.11.
  - Error number: [MY-011296](#); Symbol: [ER\\_XPLUGIN\\_UNEXPECTED\\_EXCEPTION\\_DISPATCHING\\_CMD](#); SQLSTATE: [HY000](#)

---

Message: %s: Unexpected exception dispatching command: %s

[ER\\_XPLUGIN\\_UNEXPECTED\\_EXCEPTION\\_DISPATCHING\\_CMD](#) was added in 8.0.11.

- Error number: [MY-011297](#); Symbol: [ER\\_XPLUGIN\\_EXCEPTION\\_IN\\_TASK\\_SCHEDULER](#); SQLSTATE: [HY000](#)

Message: Exception in post: %s

[ER\\_XPLUGIN\\_EXCEPTION\\_IN\\_TASK\\_SCHEDULER](#) was added in 8.0.11.

- Error number: [MY-011298](#); Symbol: [ER\\_XPLUGIN\\_TASK\\_SCHEDULING\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Internal error scheduling task

[ER\\_XPLUGIN\\_TASK\\_SCHEDULING\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011299](#); Symbol: [ER\\_XPLUGIN\\_EXCEPTION\\_IN\\_EVENT\\_LOOP](#); SQLSTATE: [HY000](#)

Message: Exception in event loop: "%s": %s

[ER\\_XPLUGIN\\_EXCEPTION\\_IN\\_EVENT\\_LOOP](#) was added in 8.0.11.

- Error number: [MY-011300](#); Symbol: [ER\\_XPLUGIN\\_LISTENER\\_SETUP\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Setup of %s failed, %s

[ER\\_XPLUGIN\\_LISTENER\\_SETUP\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011301](#); Symbol: [ER\\_XPLUING\\_NET\\_STARTUP\\_FAILED](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_XPLUING\\_NET\\_STARTUP\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011302](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_AT\\_SSL\\_CONF](#); SQLSTATE: [HY000](#)

Message: Failed at SSL configuration: "%s"

[ER\\_XPLUGIN\\_FAILED\\_AT\\_SSL\\_CONF](#) was added in 8.0.11.

- Error number: [MY-011303](#); Symbol: [ER\\_XPLUGIN\\_CLIENT\\_SSL\\_HANDSHAKE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error during SSL handshake for client connection (%i)

[ER\\_XPLUGIN\\_CLIENT\\_SSL\\_HANDSHAKE\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011304](#); Symbol: [ER\\_XPLUGIN\\_SSL\\_HANDSHAKE\\_WITH\\_SERVER\\_FAILED](#); SQLSTATE: [HY000](#)

Message: %s: Error during SSL handshake

[ER\\_XPLUGIN\\_SSL\\_HANDSHAKE\\_WITH\\_SERVER\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011305](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_CREATE\\_SESSION\\_FOR\\_CONN](#); SQLSTATE: [HY000](#)

Message: %s: Error creating session for connection from %s

---

`ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN` was added in 8.0.11.

- Error number: `MY-011306`; Symbol: `ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION`; SQLSTATE: `HY000`

Message: %s: Error initializing session for connection: %s

`ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION` was added in 8.0.11.

- Error number: `MY-011307`; Symbol: `ER_XPLUGIN_MESSAGE_TOO_LONG`; SQLSTATE: `HY000`

Message: %s: Message of size %u received, exceeding the limit of %i

`ER_XPLUGIN_MESSAGE_TOO_LONG` was added in 8.0.11.

- Error number: `MY-011308`; Symbol: `ER_XPLUGIN_UNINITIALIZED_MESSAGE`; SQLSTATE: `HY000`

Message: Message is not properly initialized: %s

`ER_XPLUGIN_UNINITIALIZED_MESSAGE` was added in 8.0.11.

- Error number: `MY-011309`; Symbol: `ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS`; SQLSTATE: `HY000`

Message: Unable to set minimal number of workers to %u; actual value is %i

`ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS` was added in 8.0.11.

- Error number: `MY-011310`; Symbol: `ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION`; SQLSTATE: `HY000`

Message: Unable to accept connection, disconnecting client

`ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION` was added in 8.0.11.

- Error number: `MY-011311`; Symbol: `ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED`; SQLSTATE: `HY000`

Message: All I/O interfaces are disabled, X Protocol won't be accessible

`ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED` was added in 8.0.11.

- Error number: `MY-011312`; Symbol: `ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT`; SQLSTATE: `HY000`

Message: %s: Invalid message %i received during client initialization

`ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011313`; Symbol: `ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN`; SQLSTATE: `HY000`

Message: %s: closing client because of shutdown (state: %i)

`ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011314`; Symbol: `ER_XPLUGIN_ERROR_READING_SOCKET`; SQLSTATE: `HY000`

Message: %s: Error reading from socket %s (%i)

---

`ER_XPLUGIN_ERROR_READING_SOCKET` was added in 8.0.11.

- Error number: `MY-011315`; Symbol: `ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG_BODY`; SQLSTATE: `HY000`  
Message: %s: peer disconnected while reading message body  
`ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG_BODY` was added in 8.0.11.
- Error number: `MY-011316`; Symbol: `ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION`; SQLSTATE: `HY000`  
Message: client\_id:%s - %s while reading from socket, closing connection  
`ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION` was added in 8.0.11.
- Error number: `MY-011317`; Symbol: `ER_XPLUGIN_INVALID_AUTH_METHOD`; SQLSTATE: `HY000`  
Message: %s.%u: Invalid authentication method %s  
`ER_XPLUGIN_INVALID_AUTH_METHOD` was added in 8.0.11, removed after 8.0.12.
- Error number: `MY-011318`; Symbol: `ER_XPLUGIN_UNEXPECTED_MSG_DURING_AUTHENTICATION`; SQLSTATE: `HY000`  
Message: %s: Unexpected message of type %i received during authentication  
`ER_XPLUGIN_UNEXPECTED_MSG_DURING_AUTHENTICATION` was added in 8.0.11, removed after 8.0.12.
- Error number: `MY-011319`; Symbol: `ER_XPLUGIN_ERROR_WRITING_TO_CLIENT`; SQLSTATE: `HY000`  
Message: Error writing to client: %s (%i)  
`ER_XPLUGIN_ERROR_WRITING_TO_CLIENT` was added in 8.0.11, removed after 8.0.12.
- Error number: `MY-011320`; Symbol: `ER_XPLUGIN_SCHEDULER_STARTED`; SQLSTATE: `HY000`  
Message: Scheduler "%s" started.  
`ER_XPLUGIN_SCHEDULER_STARTED` was added in 8.0.11, removed after 8.0.12.
- Error number: `MY-011321`; Symbol: `ER_XPLUGIN_SCHEDULER_STOPPED`; SQLSTATE: `HY000`  
Message: Scheduler "%s" stopped.  
`ER_XPLUGIN_SCHEDULER_STOPPED` was added in 8.0.11, removed after 8.0.12.
- Error number: `MY-011322`; Symbol: `ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR`; SQLSTATE: `HY000`  
Message: Please see the MySQL documentation for '%s' system variables to fix the error  
`ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR` was added in 8.0.11.
- Error number: `MY-011323`; Symbol: `ER_XPLUGIN_LISTENER_STATUS_MSG`; SQLSTATE: `HY000`  
Message: X Plugin ready for connections. %s

---

`ER_XPLUGIN_LISTENER_STATUS_MSG` was added in 8.0.11.

- Error number: `MY-011324`; Symbol: `ER_XPLUGIN_RETRYING_BIND_ON_PORT`; SQLSTATE: `HY000`

Message: Retrying `bind()` on TCP/IP port %i

`ER_XPLUGIN_RETRYING_BIND_ON_PORT` was added in 8.0.11.

- Error number: `MY-011325`; Symbol: `ER_XPLUGIN_SHUTDOWN_TRIGGERED`; SQLSTATE: `HY000`

Message: Shutdown triggered by mysqld abort flag

`ER_XPLUGIN_SHUTDOWN_TRIGGERED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011326`; Symbol: `ER_XPLUGIN_USER_ACCOUNT_WITH_ALL_PERMISSIONS`; SQLSTATE: `HY000`

Message: Using %s account for authentication which has all required permissions

`ER_XPLUGIN_USER_ACCOUNT_WITH_ALL_PERMISSIONS` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011327`; Symbol: `ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE_GRANTS`; SQLSTATE: `HY000`

Message: Using existing %s account for authentication. Incomplete grants will be fixed

`ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE_GRANTS` was added in 8.0.11.

- Error number: `MY-011328`; Symbol: `ER_XPLUGIN_SERVER_STARTS_HANDLING_CONNECTIONS`; SQLSTATE: `HY000`

Message: Server starts handling incoming connections

`ER_XPLUGIN_SERVER_STARTS_HANDLING_CONNECTIONS` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011329`; Symbol: `ER_XPLUGIN_SERVER_STOPPED_HANDLING_CONNECTIONS`; SQLSTATE: `HY000`

Message: Stopped handling incoming connections

`ER_XPLUGIN_SERVER_STOPPED_HANDLING_CONNECTIONS` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011330`; Symbol: `ER_XPLUGIN_FAILED_TO_INTERRUPT_SESSION`; SQLSTATE: `HY000`

Message: %s: Could not interrupt client session

`ER_XPLUGIN_FAILED_TO_INTERRUPT_SESSION` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011331`; Symbol: `ER_XPLUGIN_CLIENT_RELEASE_TRIGGERED`; SQLSTATE: `HY000`

Message: %s: release triggered by timeout in state:%i

`ER_XPLUGIN_CLIENT_RELEASE_TRIGGERED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011332`; Symbol: `ER_XPLUGIN_IPv6_AVAILABLE`; SQLSTATE: `HY000`

---

Message: IPv6 is available

`ER_XPLUGIN_IPv6_AVAILABLE` was added in 8.0.11.

- Error number: `MY-011333`; Symbol: `ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED`; SQLSTATE: `HY000`

Message: UNIX socket not configured

`ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011334`; Symbol: `ER_XPLUGIN_CLIENT_KILL_MSG`; SQLSTATE: `HY000`

Message: Kill client: %i %s

`ER_XPLUGIN_CLIENT_KILL_MSG` was added in 8.0.11.

- Error number: `MY-011335`; Symbol: `ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX`; SQLSTATE: `HY000`

Message: Could not get security context for session

`ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX` was added in 8.0.11.

- Error number: `MY-011336`; Symbol: `ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX_TO_ROOT`; SQLSTATE: `HY000`

Message: Unable to switch security context to root

`ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX_TO_ROOT` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011337`; Symbol: `ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION`; SQLSTATE: `HY000`

Message: Error closing SQL session

`ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION` was added in 8.0.11.

- Error number: `MY-011338`; Symbol: `ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD`; SQLSTATE: `HY000`

Message: Error executing admin command %s: %s

`ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD` was added in 8.0.11.

- Error number: `MY-011339`; Symbol: `ER_XPLUGIN_EMPTY_ADMIN_CMD`; SQLSTATE: `HY000`

Message: Error executing empty admin command

`ER_XPLUGIN_EMPTY_ADMIN_CMD` was added in 8.0.11.

- Error number: `MY-011340`; Symbol: `ER_XPLUGIN_FAILED_TO_GET_SYS_VAR`; SQLSTATE: `HY000`

Message: Unable to retrieve system variable '%s'

`ER_XPLUGIN_FAILED_TO_GET_SYS_VAR` was added in 8.0.11.

- 
- Error number: [MY-011341](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_GET\\_CREATION\\_STMT](#); SQLSTATE: [HY000](#)  
  
Message: Unable to get creation stmt for collection '%s\'; query result size: %lu  
  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_GET\\_CREATION\\_STMT](#) was added in 8.0.11.
  - Error number: [MY-011342](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_GET\\_ENGINE\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Unable to get engine info for collection '%s\'; creation stmt: %s  
  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_GET\\_ENGINE\\_INFO](#) was added in 8.0.11.
  - Error number: [MY-011343](#); Symbol: [ER\\_XPLUGIN\\_FAIL\\_TO\\_GET\\_RESULT\\_DATA](#); SQLSTATE: [HY000](#)  
  
Message: Error getting result data: %s  
  
[ER\\_XPLUGIN\\_FAIL\\_TO\\_GET\\_RESULT\\_DATA](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011344](#); Symbol: [ER\\_XPLUGIN\\_CAPABILITY\\_EXPIRED\\_PASSWORD](#); SQLSTATE: [HY000](#)  
  
Message: Capability expired password failed with error: %s  
  
[ER\\_XPLUGIN\\_CAPABILITY\\_EXPIRED\\_PASSWORD](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011345](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_SET\\_SO\\_REUSEADDR\\_FLAG](#); SQLSTATE: [HY000](#)  
  
Message: Failed to set SO\_REUSEADDR flag (error: %d).  
  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_SET\\_SO\\_REUSEADDR\\_FLAG](#) was added in 8.0.11.
  - Error number: [MY-011346](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_OPEN\\_INTERNAL\\_SESSION](#); SQLSTATE: [HY000](#)  
  
Message: Could not open internal MySQL session  
  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_OPEN\\_INTERNAL\\_SESSION](#) was added in 8.0.11.
  - Error number: [MY-011347](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_SWITCH\\_CONTEXT](#); SQLSTATE: [HY000](#)  
  
Message: Unable to switch context to user %s  
  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_SWITCH\\_CONTEXT](#) was added in 8.0.11.
  - Error number: [MY-011348](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_UNREGISTER\\_UDF](#); SQLSTATE: [HY000](#)  
  
Message: Can't unregister '%s\'; user defined function  
  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_UNREGISTER\\_UDF](#) was added in 8.0.11.



- 
- Error number: [MY-011349](#); Symbol: [ER\\_XPLUGIN\\_GET\\_PEER\\_ADDRESS\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: %s: get peer address failed, can't resolve IP to hostname  
[ER\\_XPLUGIN\\_GET\\_PEER\\_ADDRESS\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011350](#); Symbol: [ER\\_XPLUGIN\\_CAPABILITY\\_CLIENT\\_INTERACTIVE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Capability client interactive failed with error: %s  
[ER\\_XPLUGIN\\_CAPABILITY\\_CLIENT\\_INTERACTIVE\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011351](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_RESET\\_IPV6\\_V6ONLY\\_FLAG](#); SQLSTATE: [HY000](#)  
Message: Failed to reset IPV6\_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_RESET\\_IPV6\\_V6ONLY\\_FLAG](#) was added in 8.0.11.
  - Error number: [MY-011352](#); Symbol: [ER\\_KEYRING\\_INVALID\\_KEY\\_TYPE](#); SQLSTATE: [HY000](#)  
Message: Invalid key type  
[ER\\_KEYRING\\_INVALID\\_KEY\\_TYPE](#) was added in 8.0.11.
  - Error number: [MY-011353](#); Symbol: [ER\\_KEYRING\\_INVALID\\_KEY\\_LENGTH](#); SQLSTATE: [HY000](#)  
Message: Invalid key length for given block cipher  
[ER\\_KEYRING\\_INVALID\\_KEY\\_LENGTH](#) was added in 8.0.11.
  - Error number: [MY-011354](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_CREATE\\_KEYRING\\_DIR](#); SQLSTATE: [HY000](#)  
Message: Could not create keyring directory. The keyring\_file will stay unusable until correct path to the keyring directory gets provided  
[ER\\_KEYRING\\_FAILED\\_TO\\_CREATE\\_KEYRING\\_DIR](#) was added in 8.0.11.
  - Error number: [MY-011355](#); Symbol: [ER\\_KEYRING\\_FILE\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: keyring\_file initialization failure. Please check if the keyring\_file\_data points to readable keyring file or keyring file can be created in the specified location. The keyring\_file will stay unusable until correct path to the keyring file gets provided  
[ER\\_KEYRING\\_FILE\\_INIT\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011356](#); Symbol: [ER\\_KEYRING\\_INTERNAL\\_EXCEPTION\\_FAILED\\_FILE\\_INIT](#); SQLSTATE: [HY000](#)  
Message: keyring\_file initialization failure due to internal exception inside the plugin.  
[ER\\_KEYRING\\_INTERNAL\\_EXCEPTION\\_FAILED\\_FILE\\_INIT](#) was added in 8.0.11.
  - Error number: [MY-011357](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_GENERATE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Failed to generate a key due to internal exception inside keyring\_file plugin

---

`ER_KEYRING_FAILED_TO_GENERATE_KEY` was added in 8.0.11.

- Error number: `MY-011358`; Symbol: `ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY`; SQLSTATE: `HY000`

Message: Error while %s key: invalid key\_type

`ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY` was added in 8.0.11.

- Error number: `MY-011359`; Symbol: `ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID`; SQLSTATE: `HY000`

Message: Error while %s key: key\_id cannot be empty

`ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID` was added in 8.0.11.

- Error number: `MY-011360`; Symbol: `ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: Failed to %s due to internal exception inside %s plugin

`ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.

- Error number: `MY-011361`; Symbol: `ER_KEYRING_INCORRECT_FILE`; SQLSTATE: `HY000`

Message: Incorrect Keyring file

`ER_KEYRING_INCORRECT_FILE` was added in 8.0.11.

- Error number: `MY-011362`; Symbol: `ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE`; SQLSTATE: `HY000`

Message: Found malformed keyring backup file - removing it

`ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE` was added in 8.0.11.

- Error number: `MY-011363`; Symbol: `ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE`; SQLSTATE: `HY000`

Message: Error while restoring keyring from backup file cannot overwrite keyring with backup

`ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE` was added in 8.0.11.

- Error number: `MY-011364`; Symbol: `ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE`; SQLSTATE: `HY000`

Message: Error while flushing in-memory keyring into keyring file

`ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE` was added in 8.0.11.

- Error number: `MY-011365`; Symbol: `ER_KEYRING_FAILED_TO_GET_FILE_STAT`; SQLSTATE: `HY000`

Message: Error while reading stat for %s. Please check if file %s was not removed. OS returned this error: %s

`ER_KEYRING_FAILED_TO_GET_FILE_STAT` was added in 8.0.11.

- Error number: `MY-011366`; Symbol: `ER_KEYRING_FAILED_TO_REMOVE_FILE`; SQLSTATE: `HY000`

---

Message: Could not remove file %s OS returned this error: %s

[ER\\_KEYRING\\_FAILED\\_TO\\_REMOVE\\_FILE](#) was added in 8.0.11.

- Error number: [MY-011367](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_TRUNCATE\\_FILE](#); SQLSTATE: [HY000](#)

Message: Could not truncate file %s. OS returned this error: %s

[ER\\_KEYRING\\_FAILED\\_TO\\_TRUNCATE\\_FILE](#) was added in 8.0.11.

- Error number: [MY-011368](#); Symbol: [ER\\_KEYRING\\_UNKNOWN\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Unknown error %d

[ER\\_KEYRING\\_UNKNOWN\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011369](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_SET\\_KEYRING\\_FILE\\_DATA](#); SQLSTATE: [HY000](#)

Message: keyring\_file\_data cannot be set to new value as the keyring file cannot be created/accessed in the provided path

[ER\\_KEYRING\\_FAILED\\_TO\\_SET\\_KEYRING\\_FILE\\_DATA](#) was added in 8.0.11.

- Error number: [MY-011370](#); Symbol: [ER\\_KEYRING\\_FILE\\_IO\\_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_KEYRING\\_FILE\\_IO\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011371](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_LOAD\\_KEYRING\\_CONTENT](#); SQLSTATE: [HY000](#)

Message: Error while loading keyring content. The keyring might be malformed

[ER\\_KEYRING\\_FAILED\\_TO\\_LOAD\\_KEYRING\\_CONTENT](#) was added in 8.0.11.

- Error number: [MY-011372](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_FLUSH\\_KEYS\\_TO\\_KEYRING](#); SQLSTATE: [HY000](#)

Message: Could not flush keys to keyring

[ER\\_KEYRING\\_FAILED\\_TO\\_FLUSH\\_KEYS\\_TO\\_KEYRING](#) was added in 8.0.11.

- Error number: [MY-011373](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_FLUSH\\_KEYS\\_TO\\_KEYRING\\_BACKUP](#); SQLSTATE: [HY000](#)

Message: Could not flush keys to keyring's backup

[ER\\_KEYRING\\_FAILED\\_TO\\_FLUSH\\_KEYS\\_TO\\_KEYRING\\_BACKUP](#) was added in 8.0.11.

- Error number: [MY-011374](#); Symbol: [ER\\_KEYRING\\_KEY\\_FETCH\\_FAILED\\_DUE\\_TO\\_EMPTY\\_KEY\\_ID](#); SQLSTATE: [HY000](#)

Message: Error while fetching key: key\_id cannot be empty

[ER\\_KEYRING\\_KEY\\_FETCH\\_FAILED\\_DUE\\_TO\\_EMPTY\\_KEY\\_ID](#) was added in 8.0.11.

- 
- Error number: [MY-011375](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_REMOVE\\_KEY\\_DUE\\_TO\\_EMPTY\\_ID](#); SQLSTATE: [HY000](#)

Message: Error while removing key: key\_id cannot be empty

[ER\\_KEYRING\\_FAILED\\_TO\\_REMOVE\\_KEY\\_DUE\\_TO\\_EMPTY\\_ID](#) was added in 8.0.11.

- Error number: [MY-011376](#); Symbol: [ER\\_KEYRING\\_OKV\\_INCORRECT\\_KEY\\_VAULT\\_CONFIGURED](#); SQLSTATE: [HY000](#)

Message: For keyring\_okv to be initialized, please point keyring\_okv\_conf\_dir variable to a directory with Oracle Key Vault configuration file and ssl materials

[ER\\_KEYRING\\_OKV\\_INCORRECT\\_KEY\\_VAULT\\_CONFIGURED](#) was added in 8.0.11.

- Error number: [MY-011377](#); Symbol: [ER\\_KEYRING\\_OKV\\_INIT\\_FAILED\\_DUE\\_TO\\_INCORRECT\\_CONF](#); SQLSTATE: [HY000](#)

Message: keyring\_okv initialization failure. Please check that the keyring\_okv\_conf\_dir points to a readable directory and that the directory contains Oracle Key Vault configuration file and ssl materials. Please also check that Oracle Key Vault is up and running.

[ER\\_KEYRING\\_OKV\\_INIT\\_FAILED\\_DUE\\_TO\\_INCORRECT\\_CONF](#) was added in 8.0.11.

- Error number: [MY-011378](#); Symbol: [ER\\_KEYRING\\_OKV\\_INIT\\_FAILED\\_DUE\\_TO\\_INTERNAL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: keyring\_okv initialization failure due to internal exception inside the plugin

[ER\\_KEYRING\\_OKV\\_INIT\\_FAILED\\_DUE\\_TO\\_INTERNAL\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011379](#); Symbol: [ER\\_KEYRING\\_OKV\\_INVALID\\_KEY\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Invalid key type

[ER\\_KEYRING\\_OKV\\_INVALID\\_KEY\\_TYPE](#) was added in 8.0.11.

- Error number: [MY-011380](#); Symbol: [ER\\_KEYRING\\_OKV\\_INVALID\\_KEY\\_LENGTH\\_FOR\\_CIPHER](#); SQLSTATE: [HY000](#)

Message: Invalid key length for given block cipher

[ER\\_KEYRING\\_OKV\\_INVALID\\_KEY\\_LENGTH\\_FOR\\_CIPHER](#) was added in 8.0.11.

- Error number: [MY-011381](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_GENERATE\\_KEY\\_DUE\\_TO\\_INTERNAL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to generate a key due to internal exception inside keyring\_okv plugin

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_GENERATE\\_KEY\\_DUE\\_TO\\_INTERNAL\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011382](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_FIND\\_SERVER\\_ENTRY](#); SQLSTATE: [HY000](#)

Message: Could not find entry for server in configuration file %s

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_FIND\\_SERVER\\_ENTRY](#) was added in 8.0.11.

- 
- Error number: [MY-011383](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_FIND\\_STANDBY\\_SERVER\\_ENTRY](#); SQLSTATE: [HY000](#)  
Message: Could not find entry for standby server in configuration file %s  
[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_FIND\\_STANDBY\\_SERVER\\_ENTRY](#) was added in 8.0.11.
  - Error number: [MY-011384](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_PARSE\\_CONF\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Could not parse the %s file provided  
[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_PARSE\\_CONF\\_FILE](#) was added in 8.0.11.
  - Error number: [MY-011385](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_LOAD\\_KEY\\_UID](#); SQLSTATE: [HY000](#)  
Message: Could not load keys' uids from the OKV server  
[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_LOAD\\_KEY\\_UID](#) was added in 8.0.11.
  - Error number: [MY-011386](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_INIT\\_SSL\\_LAYER](#); SQLSTATE: [HY000](#)  
Message: Could not initialize ssl layer  
[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_INIT\\_SSL\\_LAYER](#) was added in 8.0.11.
  - Error number: [MY-011387](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_INIT\\_CLIENT](#); SQLSTATE: [HY000](#)  
Message: Could not initialize OKV client  
[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_INIT\\_CLIENT](#) was added in 8.0.11.
  - Error number: [MY-011388](#); Symbol: [ER\\_KEYRING\\_OKV\\_CONNECTION\\_TO\\_SERVER\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Could not connect to the OKV server  
[ER\\_KEYRING\\_OKV\\_CONNECTION\\_TO\\_SERVER\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011389](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_REMOVE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Could not remove the key  
[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_REMOVE\\_KEY](#) was added in 8.0.11.
  - Error number: [MY-011390](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_ADD\\_ATTRIBUTE](#); SQLSTATE: [HY000](#)  
Message: Could not add attribute, attribute\_name=%s attribute value=%s  
[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_ADD\\_ATTRIBUTE](#) was added in 8.0.11.
  - Error number: [MY-011391](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_GENERATE\\_KEY](#); SQLSTATE: [HY000](#)

---

Message: Could not generate the key.

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_GENERATE\\_KEY](#) was added in 8.0.11.

- Error number: [MY-011392](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_STORE\\_KEY](#); SQLSTATE: [HY000](#)

Message: Could not store the key.

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_STORE\\_KEY](#) was added in 8.0.11.

- Error number: [MY-011393](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_ACTIVATE\\_KEYS](#); SQLSTATE: [HY000](#)

Message: Could not activate the key.

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_ACTIVATE\\_KEYS](#) was added in 8.0.11.

- Error number: [MY-011394](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_FETCH\\_KEY](#); SQLSTATE: [HY000](#)

Message: Could not fetch generated key

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_FETCH\\_KEY](#) was added in 8.0.11.

- Error number: [MY-011395](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_STORE\\_OR\\_GENERATE\\_KEY](#); SQLSTATE: [HY000](#)

Message: Could not store/generate the key - failed to set key attribute x-key-ready

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_STORE\\_OR\\_GENERATE\\_KEY](#) was added in 8.0.11.

- Error number: [MY-011396](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_RETRIEVE\\_KEY\\_SIGNATURE](#); SQLSTATE: [HY000](#)

Message: Could not retrieve key signature from custom attributes

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_RETRIEVE\\_KEY\\_SIGNATURE](#) was added in 8.0.11.

- Error number: [MY-011397](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_RETRIEVE\\_KEY](#); SQLSTATE: [HY000](#)

Message: Could not retrieve key from OKV

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_RETRIEVE\\_KEY](#) was added in 8.0.11.

- Error number: [MY-011398](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_LOAD\\_SSL\\_TRUST\\_STORE](#); SQLSTATE: [HY000](#)

Message: Error loading trust store

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_LOAD\\_SSL\\_TRUST\\_STORE](#) was added in 8.0.11.

- Error number: [MY-011399](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_SET\\_CERTIFICATE\\_FILE](#); SQLSTATE: [HY000](#)

Message: Error setting the certificate file.

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_SET\\_CERTIFICATE\\_FILE](#) was added in 8.0.11.

- 
- Error number: `MY-011400`; Symbol: `ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE`; SQLSTATE: `HY000`  
  
Message: Error setting the key file.  
  
`ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE` was added in 8.0.11.
  - Error number: `MY-011401`; Symbol: `ER_KEYRING_OKV_KEY_MISMATCH`; SQLSTATE: `HY000`  
  
Message: Private key does not match the certificate public key  
  
`ER_KEYRING_OKV_KEY_MISMATCH` was added in 8.0.11.
  - Error number: `MY-011402`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE`; SQLSTATE: `HY000`  
  
Message: Incorrect Keyring file  
  
`ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE` was added in 8.0.11.
  - Error number: `MY-011403`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED`; SQLSTATE: `HY000`  
  
Message: Keyring\_encrypted\_file decryption failed. Please verify --keyring-encrypted-file-password option value.  
  
`ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED` was added in 8.0.11.
  - Error number: `MY-011404`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE`; SQLSTATE: `HY000`  
  
Message: Found malformed keyring backup file - removing it  
  
`ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE` was added in 8.0.11.
  - Error number: `MY-011405`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING`; SQLSTATE: `HY000`  
  
Message: Error while restoring keyring from backup file cannot overwrite keyring with backup  
  
`ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING` was added in 8.0.11.
  - Error number: `MY-011406`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING`; SQLSTATE: `HY000`  
  
Message: Error while flushing in-memory keyring into keyring file  
  
`ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING` was added in 8.0.11.
  - Error number: `MY-011407`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED`; SQLSTATE: `HY000`  
  
Message: Keyring\_encrypted\_file encryption failed. Please verify --keyring-encrypted-file-password option value.  
  
`ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED` was added in 8.0.11.
  - Error number: `MY-011408`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR`; SQLSTATE: `HY000`

---

Message: keyring\_encrypted\_file\_data cannot be set to new value as the keyring file cannot be created/ accessed in the provided path

ER\_KEYRING\_ENCRYPTED\_FILE\_INVALID\_KEYRING\_DIR was added in 8.0.11.

- Error number: MY-011409; Symbol: ER\_KEYRING\_ENCRYPTED\_FILE\_FAILED\_TO\_CREATE\_KEYRING\_DIR; SQLSTATE: HY000

Message: Could not create keyring directory The keyring\_encrypted\_file will stay unusable until correct path to the keyring directory gets provided

ER\_KEYRING\_ENCRYPTED\_FILE\_FAILED\_TO\_CREATE\_KEYRING\_DIR was added in 8.0.11.

- Error number: MY-011410; Symbol: ER\_KEYRING\_ENCRYPTED\_FILE\_PASSWORD\_IS\_INVALID; SQLSTATE: HY000

Message: The keyring\_encrypted\_file\_password must be set to a valid value.

ER\_KEYRING\_ENCRYPTED\_FILE\_PASSWORD\_IS\_INVALID was added in 8.0.11.

- Error number: MY-011411; Symbol: ER\_KEYRING\_ENCRYPTED\_FILE\_PASSWORD\_IS\_TOO\_LONG; SQLSTATE: HY000

Message: Too long keyring\_encrypted\_file\_password value.

ER\_KEYRING\_ENCRYPTED\_FILE\_PASSWORD\_IS\_TOO\_LONG was added in 8.0.11.

- Error number: MY-011412; Symbol: ER\_KEYRING\_ENCRYPTED\_FILE\_INIT\_FAILURE; SQLSTATE: HY000

Message: keyring\_encrypted\_file initialization failure. Please check if the keyring\_encrypted\_file\_data points to readable keyring file or keyring file can be created in the specified location or password to decrypt keyring file is correct.

ER\_KEYRING\_ENCRYPTED\_FILE\_INIT\_FAILURE was added in 8.0.11.

- Error number: MY-011413; Symbol: ER\_KEYRING\_ENCRYPTED\_FILE\_INIT\_FAILED\_DUE\_TO\_INTERNAL\_ERROR; SQLSTATE: HY000

Message: keyring\_encrypted\_file initialization failure due to internal exception inside the plugin

ER\_KEYRING\_ENCRYPTED\_FILE\_INIT\_FAILED\_DUE\_TO\_INTERNAL\_ERROR was added in 8.0.11.

- Error number: MY-011414; Symbol: ER\_KEYRING\_ENCRYPTED\_FILE\_GEN\_KEY\_FAILED\_DUE\_TO\_INTERNAL\_ERROR; SQLSTATE: HY000

Message: Failed to generate a key due to internal exception inside keyring\_encrypted\_file plugin

ER\_KEYRING\_ENCRYPTED\_FILE\_GEN\_KEY\_FAILED\_DUE\_TO\_INTERNAL\_ERROR was added in 8.0.11.

- Error number: MY-011415; Symbol: ER\_KEYRING\_AWS\_FAILED\_TO\_SET\_CMK\_ID; SQLSTATE: HY000

Message: keyring\_aws\_cmk\_id cannot be set to the new value as AWS KMS seems to not understand the id provided. Please check that CMK id provided is correct.



---

`ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID` was added in 8.0.11.

- Error number: `MY-011416`; Symbol: `ER_KEYRING_AWS_FAILED_TO_SET_REGION`; SQLSTATE: `HY000`

Message: `keyring_aws_region` cannot be set to the new value as AWS KMS seems to not understand the region provided. Please check that region provided is correct.

`ER_KEYRING_AWS_FAILED_TO_SET_REGION` was added in 8.0.11.

- Error number: `MY-011417`; Symbol: `ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not open `keyring_aws` configuration file: %s. OS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE` was added in 8.0.11.

- Error number: `MY-011418`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not read AWS access key id from `keyring_aws` configuration file: %s. OS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE` was added in 8.0.11.

- Error number: `MY-011419`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not read AWS access key from `keyring_aws` configuration file: %s. OS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE` was added in 8.0.11.

- Error number: `MY-011420`; Symbol: `ER_KEYRING_AWS_INVALID_CONF_FILE_PATH`; SQLSTATE: `HY000`

Message: Path to `keyring_aws` configuration file cannot be empty

`ER_KEYRING_AWS_INVALID_CONF_FILE_PATH` was added in 8.0.11.

- Error number: `MY-011421`; Symbol: `ER_KEYRING_AWS_INVALID_DATA_FILE_PATH`; SQLSTATE: `HY000`

Message: Path to `keyring_aws` storage file cannot be empty.

`ER_KEYRING_AWS_INVALID_DATA_FILE_PATH` was added in 8.0.11.

- Error number: `MY-011422`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR`; SQLSTATE: `HY000`

Message: Unable to create/access `keyring` directory.

`ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR` was added in 8.0.11.

- 
- Error number: `MY-011423`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE`; SQLSTATE: `HY000`  
  
Message: Unable to create/access keyring\_aws storage file. Please check if keyring\_aws\_data\_file points to location where keyring file can be created/accessed. Please also make sure that MySQL server's user has high enough privileges to access this location.  
  
`ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE` was added in 8.0.11.
  - Error number: `MY-011424`; Symbol: `ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`  
  
Message: keyring\_aws initialization failed due to internal error when initializing synchronization primitive - %s. OS returned this error: %s:  
  
`ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.
  - Error number: `MY-011425`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE`; SQLSTATE: `HY000`  
  
Message: Could not access keyring\_aws storage file in the path provided. Please check if the keyring\_aws directory can be accessed by MySQL Server  
  
`ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE` was added in 8.0.11.
  - Error number: `MY-011426`; Symbol: `ER_KEYRING_AWS_CMK_ID_NOT_SET`; SQLSTATE: `HY000`  
  
Message: keyring\_aws\_cmek\_id has to be set  
  
`ER_KEYRING_AWS_CMK_ID_NOT_SET` was added in 8.0.11.
  - Error number: `MY-011427`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FROM_CONF_FILE`; SQLSTATE: `HY000`  
  
Message: Could not get AWS KMS credentials from the configuration file  
  
`ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FROM_CONF_FILE` was added in 8.0.11.
  - Error number: `MY-011428`; Symbol: `ER_KEYRING_AWS_INIT_FAILURE`; SQLSTATE: `HY000`  
  
Message: keyring\_aws initialization failure.  
  
`ER_KEYRING_AWS_INIT_FAILURE` was added in 8.0.11.
  - Error number: `MY-011429`; Symbol: `ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR`; SQLSTATE: `HY000`  
  
Message: keyring\_aws initialization failure due to internal exception inside the plugin  
  
`ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR` was added in 8.0.11.
  - Error number: `MY-011430`; Symbol: `ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER`; SQLSTATE: `HY000`  
  
Message: Invalid key length for given block cipher  
  
`ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER` was added in 8.0.11.

- 
- Error number: `MY-011431`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`  
Message: Failed to generate a key due to internal exception inside keyring\_file plugin  
`ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.
  - Error number: `MY-011432`; Symbol: `ER_KEYRING_AWS_INCORRECT_FILE`; SQLSTATE: `HY000`  
Message: Incorrect Keyring file  
`ER_KEYRING_AWS_INCORRECT_FILE` was added in 8.0.11.
  - Error number: `MY-011433`; Symbol: `ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE`; SQLSTATE: `HY000`  
Message: Found malformed keyring backup file - removing it  
`ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE` was added in 8.0.11.
  - Error number: `MY-011434`; Symbol: `ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE`; SQLSTATE: `HY000`  
Message: Error while restoring keyring from backup file cannot overwrite keyring with backup  
`ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE` was added in 8.0.11.
  - Error number: `MY-011435`; Symbol: `ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE`; SQLSTATE: `HY000`  
Message: Error while flushing in-memory keyring into keyring file  
`ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE` was added in 8.0.11.
  - Error number: `MY-011436`; Symbol: `ER_KEYRING_AWS_INCORRECT_REGION`; SQLSTATE: `HY000`  
Message: Wrong region  
`ER_KEYRING_AWS_INCORRECT_REGION` was added in 8.0.11.
  - Error number: `MY-011437`; Symbol: `ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS`; SQLSTATE: `HY000`  
Message: Could not connect to AWS KMS with the credentials provided. Please make sure they are correct. AWS KMS returned this error: %s  
`ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS` was added in 8.0.11.
  - Error number: `MY-011438`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY`; SQLSTATE: `HY000`  
Message: Could not generate a new key. AWS KMS returned this error: %s  
`ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY` was added in 8.0.11.
  - Error number: `MY-011439`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY`; SQLSTATE: `HY000`  
Message: Could not encrypt key. AWS KMS returned this error: %s

---

`ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY` was added in 8.0.11.

- Error number: `MY-011440`; Symbol: `ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY`; SQLSTATE: `HY000`

Message: Could not re-encrypt key. AWS KMS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY` was added in 8.0.11.

- Error number: `MY-011441`; Symbol: `ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY`; SQLSTATE: `HY000`

Message: Could not decrypt key. AWS KMS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY` was added in 8.0.11.

- Error number: `MY-011442`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK`; SQLSTATE: `HY000`

Message: Could not rotate the CMK. AWS KMS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK` was added in 8.0.11.

- Error number: `MY-011443`; Symbol: `ER_GRP_RPL_GTID_ALREADY_USED`; SQLSTATE: `HY000`

Message: The requested GTID '%s:%lld' was already used, the transaction will rollback.

`ER_GRP_RPL_GTID_ALREADY_USED` was added in 8.0.11.

- Error number: `MY-011444`; Symbol: `ER_GRP_RPL_APPLIER_THD_KILLED`; SQLSTATE: `HY000`

Message: The group replication applier thread was killed.

`ER_GRP_RPL_APPLIER_THD_KILLED` was added in 8.0.11.

- Error number: `MY-011445`; Symbol: `ER_GRP_RPL_EVENT_HANDLING_ERROR`; SQLSTATE: `HY000`

Message: Error at event handling! Got error: %d.

`ER_GRP_RPL_EVENT_HANDLING_ERROR` was added in 8.0.11.

- Error number: `MY-011446`; Symbol: `ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO`; SQLSTATE: `HY000`

Message: Error when extracting group GTID execution information, some recovery operations may face future issues.

`ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO` was added in 8.0.11.

- Error number: `MY-011447`; Symbol: `ER_GRP_RPL_CERTIFICATE_SIZE_ERROR`; SQLSTATE: `HY000`

Message: An error occurred when trying to reduce the Certification information size for transmission.

`ER_GRP_RPL_CERTIFICATE_SIZE_ERROR` was added in 8.0.11.

- Error number: `MY-011448`; Symbol: `ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR`; SQLSTATE: `HY000`

Message: Failed to create group replication pipeline applier cache!

---

`ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR` was added in 8.0.11.

- Error number: `MY-011449`; Symbol: `ER_GRP_RPL_UNBLOCK_WAITING_THD`; SQLSTATE: `HY000`

Message: Unblocking the group replication thread waiting for applier to start, as the start group replication was killed.

`ER_GRP_RPL_UNBLOCK_WAITING_THD` was added in 8.0.11.

- Error number: `MY-011450`; Symbol: `ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED`; SQLSTATE: `HY000`

Message: The group replication applier pipeline was not properly disposed. Check the error log for further info.

`ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED` was added in 8.0.11.

- Error number: `MY-011451`; Symbol: `ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED`; SQLSTATE: `HY000`

Message: The applier thread execution was aborted. Unable to process more transactions, this member will now leave the group.

`ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED` was added in 8.0.11.

- Error number: `MY-011452`; Symbol: `ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR`; SQLSTATE: `HY000`

Message: Fatal error during execution on the Applier process of Group Replication. The server will now leave the group.

`ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR` was added in 8.0.11.

- Error number: `MY-011453`; Symbol: `ER_GRP_RPL_ERROR_STOPPING_CHANNELS`; SQLSTATE: `HY000`

Message: Error stopping all replication channels while server was leaving the group. %s

`ER_GRP_RPL_ERROR_STOPPING_CHANNELS` was added in 8.0.11.

- Error number: `MY-011454`; Symbol: `ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG`; SQLSTATE: `HY000`

Message: Error sending single primary message informing that primary did apply relay logs.

`ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG` was added in 8.0.11.

- Error number: `MY-011455`; Symbol: `ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VER_ERROR`; SQLSTATE: `HY000`

Message: Error updating transaction snapshot version after transaction being positively certified.

`ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VER_ERROR` was added in 8.0.11.

- Error number: `MY-011456`; Symbol: `ER_GRP_RPL_SIDNO_FETCH_ERROR`; SQLSTATE: `HY000`

Message: Error fetching transaction sidno after transaction being positively certified.

`ER_GRP_RPL_SIDNO_FETCH_ERROR` was added in 8.0.11.

- 
- Error number: [MY-011457](#); Symbol: [ER\\_GRP\\_RPL\\_BROADCAST\\_COMMIT\\_TRANS\\_MSSG\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Broadcast of committed transactions message failed.  
  
[ER\\_GRP\\_RPL\\_BROADCAST\\_COMMIT\\_TRANS\\_MSSG\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011458](#); Symbol: [ER\\_GRP\\_RPL\\_GROUP\\_NAME\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Unable to parse the group\_replication\_group\_name during the Certification module initialization.  
  
[ER\\_GRP\\_RPL\\_GROUP\\_NAME\\_PARSE\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011459](#); Symbol: [ER\\_GRP\\_RPL\\_ADD\\_GRPSID\\_TO\\_GRPGTIDSID\\_MAP\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Unable to add the group\_sid in the group\_gtid\_sid\_map during the Certification module initialization.  
  
[ER\\_GRP\\_RPL\\_ADD\\_GRPSID\\_TO\\_GRPGTIDSID\\_MAP\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011460](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_GRPGTID\\_EXECUTED\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error updating group\_gtid\_executed GTID set during the Certification module initialization.  
  
[ER\\_GRP\\_RPL\\_UPDATE\\_GRPGTID\\_EXECUTED\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011461](#); Symbol: [ER\\_GRP\\_RPL\\_DONOR\\_TRANS\\_INFO\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Unable to handle the donor's transaction information when initializing the conflict detection component. Possible out of memory error.  
  
[ER\\_GRP\\_RPL\\_DONOR\\_TRANS\\_INFO\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011462](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_CONN\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error when establishing a server connection during the Certification module initialization.  
  
[ER\\_GRP\\_RPL\\_SERVER\\_CONN\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011463](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_FETCHING\\_GTID\\_EXECUTED\\_SET](#); SQLSTATE: [HY000](#)  
  
Message: Error when extracting this member GTID executed set. Certification module can't be properly initialized.  
  
[ER\\_GRP\\_RPL\\_ERROR\\_FETCHING\\_GTID\\_EXECUTED\\_SET](#) was added in 8.0.11.
  - Error number: [MY-011464](#); Symbol: [ER\\_GRP\\_RPL\\_ADD\\_GTID\\_TO\\_GRPGTID\\_EXECUTED\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error while adding the server GTID EXECUTED set to the group\_gtid\_execute during the Certification module initialization.  
  
[ER\\_GRP\\_RPL\\_ADD\\_GTID\\_TO\\_GRPGTID\\_EXECUTED\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011465](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_FETCHING\\_GTID\\_SET](#); SQLSTATE: [HY000](#)

---

Message: Error when extracting this member retrieved set for its applier. Certification module can't be properly initialized.

[ER\\_GRP\\_RPL\\_ERROR\\_FETCHING\\_GTID\\_SET](#) was added in 8.0.11.

- Error number: [MY-011466](#); Symbol: [ER\\_GRP\\_RPL\\_ADD\\_RETRIEVED\\_SET\\_TO\\_GRP\\_GTID\\_EXECUTED\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while adding the member retrieved set to the group\_gtid\_executed during the Certification module initialization.

[ER\\_GRP\\_RPL\\_ADD\\_RETRIEVED\\_SET\\_TO\\_GRP\\_GTID\\_EXECUTED\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011467](#); Symbol: [ER\\_GRP\\_RPL\\_CERTIFICATION\\_INITIALIZATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error during Certification module initialization.

[ER\\_GRP\\_RPL\\_CERTIFICATION\\_INITIALIZATION\\_FAILURE](#) was added in 8.0.11.

- Error number: [MY-011468](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_LAST\\_CONFLICT\\_FREE\\_TRANS\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to update last conflict free transaction, this transaction will not be tracked on performance\_schema.replication\_group\_member\_stats.last\_conflict\_free\_transaction.

[ER\\_GRP\\_RPL\\_UPDATE\\_LAST\\_CONFLICT\\_FREE\\_TRANS\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011469](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_TRANS\\_SNAPSHOT\\_REF\\_VER\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating transaction snapshot version reference for internal storage.

[ER\\_GRP\\_RPL\\_UPDATE\\_TRANS\\_SNAPSHOT\\_REF\\_VER\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011470](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_SIDNO\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error fetching transaction sidno while adding to the group\_gtid\_executed set.

[ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_SIDNO\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011471](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_VERIFYING\\_SIDNO](#); SQLSTATE: [HY000](#)

Message: Error while ensuring the sidno be present in the group\_gtid\_executed.

[ER\\_GRP\\_RPL\\_ERROR\\_VERIFYING\\_SIDNO](#) was added in 8.0.11.

- Error number: [MY-011472](#); Symbol: [ER\\_GRP\\_RPL\\_CANT\\_GENERATE\\_GTID](#); SQLSTATE: [HY000](#)

Message: Impossible to generate Global Transaction Identifier: the integer component reached the maximal value. Restart the group with a new group\_replication\_group\_name.

[ER\\_GRP\\_RPL\\_CANT\\_GENERATE\\_GTID](#) was added in 8.0.11.

- 
- Error number: [MY-011473](#); Symbol: [ER\\_GRP\\_RPL\\_INVALID\\_GTID\\_SET](#); SQLSTATE: [HY000](#)

Message: Invalid stable transactions set.

[ER\\_GRP\\_RPL\\_INVALID\\_GTID\\_SET](#) was added in 8.0.11.

- Error number: [MY-011474](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_GTID\\_SET\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating stable transactions set.

[ER\\_GRP\\_RPL\\_UPDATE\\_GTID\\_SET\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011475](#); Symbol: [ER\\_GRP\\_RPL\\_RECEIVED\\_SET\\_MISSING\\_GTIDS](#); SQLSTATE: [HY000](#)

Message: There was an error when filling the missing GTIDs on the applier channel received set. Despite not critical, on the long run this may cause performance issues.

[ER\\_GRP\\_RPL\\_RECEIVED\\_SET\\_MISSING\\_GTIDS](#) was added in 8.0.11.

- Error number: [MY-011476](#); Symbol: [ER\\_GRP\\_RPL\\_SKIP\\_COMPUTATION\\_TRANS\\_COMMITTED](#); SQLSTATE: [HY000](#)

Message: Skipping the computation of the Transactions\_committed\_all\_members field as an older instance of this computation is still ongoing.

[ER\\_GRP\\_RPL\\_SKIP\\_COMPUTATION\\_TRANS\\_COMMITTED](#) was added in 8.0.11, removed after 8.0.26.

- Error number: [MY-011477](#); Symbol: [ER\\_GRP\\_RPL\\_NULL\\_PACKET](#); SQLSTATE: [HY000](#)

Message: Null packet on certifier's queue.

[ER\\_GRP\\_RPL\\_NULL\\_PACKET](#) was added in 8.0.11.

- Error number: [MY-011478](#); Symbol: [ER\\_GRP\\_RPL\\_CANT\\_READ\\_GTID](#); SQLSTATE: [HY000](#)

Message: Error reading GTIDs from the message.

[ER\\_GRP\\_RPL\\_CANT\\_READ\\_GTID](#) was added in 8.0.11.

- Error number: [MY-011479](#); Symbol: [ER\\_GRP\\_RPL\\_PROCESS\\_GTID\\_SET\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing stable transactions set.

[ER\\_GRP\\_RPL\\_PROCESS\\_GTID\\_SET\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011480](#); Symbol: [ER\\_GRP\\_RPL\\_PROCESS\\_INTERSECTION\\_GTID\\_SET\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing intersection of stable transactions set.

[ER\\_GRP\\_RPL\\_PROCESS\\_INTERSECTION\\_GTID\\_SET\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011481](#); Symbol: [ER\\_GRP\\_RPL\\_SET\\_STABLE\\_TRANS\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error setting stable transactions set.

[ER\\_GRP\\_RPL\\_SET\\_STABLE\\_TRANS\\_ERROR](#) was added in 8.0.11.



- 
- Error number: [MY-011482](#); Symbol: [ER\\_GRP\\_RPL\\_CANT\\_READ\\_GRP\\_GTID\\_EXTRACTED](#); SQLSTATE: [HY000](#)  
  
Message: Error reading group\_gtid\_extracted from the View\_change\_log\_event.  
  
[ER\\_GRP\\_RPL\\_CANT\\_READ\\_GRP\\_GTID\\_EXTRACTED](#) was added in 8.0.11.
  - Error number: [MY-011483](#); Symbol: [ER\\_GRP\\_RPL\\_CANT\\_READ\\_WRITE\\_SET\\_ITEM](#); SQLSTATE: [HY000](#)  
  
Message: Error reading the write set item '%s' from the View\_change\_log\_event.  
  
[ER\\_GRP\\_RPL\\_CANT\\_READ\\_WRITE\\_SET\\_ITEM](#) was added in 8.0.11.
  - Error number: [MY-011484](#); Symbol: [ER\\_GRP\\_RPL\\_INIT\\_CERTIFICATION\\_INFO\\_FAILURE](#); SQLSTATE: [HY000](#)  
  
Message: Error during certification\_info initialization.  
  
[ER\\_GRP\\_RPL\\_INIT\\_CERTIFICATION\\_INFO\\_FAILURE](#) was added in 8.0.11.
  - Error number: [MY-011485](#); Symbol: [ER\\_GRP\\_RPL\\_CONFLICT\\_DETECTION\\_DISABLED](#); SQLSTATE: [HY000](#)  
  
Message: Primary had applied all relay logs, disabled conflict detection.  
  
[ER\\_GRP\\_RPL\\_CONFLICT\\_DETECTION\\_DISABLED](#) was added in 8.0.11.
  - Error number: [MY-011486](#); Symbol: [ER\\_GRP\\_RPL\\_MSG\\_DISCARDED](#); SQLSTATE: [HY000](#)  
  
Message: Message received while the plugin is not ready, message discarded.  
  
[ER\\_GRP\\_RPL\\_MSG\\_DISCARDED](#) was added in 8.0.11.
  - Error number: [MY-011487](#); Symbol: [ER\\_GRP\\_RPL\\_MISSING\\_GRP\\_RPL\\_APPLIER](#); SQLSTATE: [HY000](#)  
  
Message: Message received without a proper group replication applier.  
  
[ER\\_GRP\\_RPL\\_MISSING\\_GRP\\_RPL\\_APPLIER](#) was added in 8.0.11.
  - Error number: [MY-011488](#); Symbol: [ER\\_GRP\\_RPL\\_CERTIFIER\\_MSSG\\_PROCESS\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error processing message in Certifier.  
  
[ER\\_GRP\\_RPL\\_CERTIFIER\\_MSSG\\_PROCESS\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011489](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_NOT\\_ONLINE](#); SQLSTATE: [HY000](#)  
  
Message: This server was not declared online since it is on status %s.  
  
[ER\\_GRP\\_RPL\\_SRV\\_NOT\\_ONLINE](#) was added in 8.0.11.
  - Error number: [MY-011490](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_ONLINE](#); SQLSTATE: [HY000](#)  
  
Message: This server was declared online within the replication group.

- 
- Error number: [MY-011491](#); Symbol: [ER\\_GRP\\_RPL\\_DISABLE\\_SRV\\_READ\\_MODE\\_RESTRICTED](#); SQLSTATE: [HY000](#)

Message: When declaring the plugin online it was not possible to disable the server read mode settings. Try to disable it manually.

[ER\\_GRP\\_RPL\\_DISABLE\\_SRV\\_READ\\_MODE\\_RESTRICTED](#) was added in 8.0.11.

- Error number: [MY-011492](#); Symbol: [ER\\_GRP\\_RPL\\_MEM\\_ONLINE](#); SQLSTATE: [HY000](#)

Message: The member with address %s:%u was declared online within the replication group.

[ER\\_GRP\\_RPL\\_MEM\\_ONLINE](#) was added in 8.0.11.

- Error number: [MY-011493](#); Symbol: [ER\\_GRP\\_RPL\\_MEM\\_UNREACHABLE](#); SQLSTATE: [HY000](#)

Message: Member with address %s:%u has become unreachable.

[ER\\_GRP\\_RPL\\_MEM\\_UNREACHABLE](#) was added in 8.0.11.

- Error number: [MY-011494](#); Symbol: [ER\\_GRP\\_RPL\\_MEM\\_REACHABLE](#); SQLSTATE: [HY000](#)

Message: Member with address %s:%u is reachable again.

[ER\\_GRP\\_RPL\\_MEM\\_REACHABLE](#) was added in 8.0.11.

- Error number: [MY-011495](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_BLOCKED](#); SQLSTATE: [HY000](#)

Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked until contact with the majority is restored. It is possible to use `group_replication_force_members` to force a new group membership.

[ER\\_GRP\\_RPL\\_SRV\\_BLOCKED](#) was added in 8.0.11.

- Error number: [MY-011496](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_BLOCKED\\_FOR\\_SECS](#); SQLSTATE: [HY000](#)

Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked for the next %u seconds. Unless contact with the majority is restored, after this time the member will error out and leave the group. It is possible to use `group_replication_force_members` to force a new group membership.

[ER\\_GRP\\_RPL\\_SRV\\_BLOCKED\\_FOR\\_SECS](#) was added in 8.0.11.

- Error number: [MY-011497](#); Symbol: [ER\\_GRP\\_RPL\\_CHANGE\\_GRP\\_MEM\\_NOT\\_PROCESSED](#); SQLSTATE: [HY000](#)

Message: A group membership change was received but the plugin is already leaving due to the configured timeout on `group_replication_unreachable_majority_timeout` option.

[ER\\_GRP\\_RPL\\_CHANGE\\_GRP\\_MEM\\_NOT\\_PROCESSED](#) was added in 8.0.11.

- Error number: [MY-011498](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_CONTACT\\_RESTORED](#); SQLSTATE: [HY000](#)

Message: The member has resumed contact with a majority of the members in the group. Regular operation is restored and transactions are unblocked.

[ER\\_GRP\\_RPL\\_MEMBER\\_CONTACT\\_RESTORED](#) was added in 8.0.11.

- Error number: [MY-011499](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_REMOVED](#); SQLSTATE: [HY000](#)

---

Message: Members removed from the group: %s

`ER_GRP_RPL_MEMBER_REMOVED` was added in 8.0.11.

- Error number: `MY-011500`; Symbol: `ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP`; SQLSTATE: `HY000`

Message: Primary server with address %s left the group. Electing new Primary.

`ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP` was added in 8.0.11.

- Error number: `MY-011501`; Symbol: `ER_GRP_RPL_MEMBER_ADDED`; SQLSTATE: `HY000`

Message: Members joined the group: %s

`ER_GRP_RPL_MEMBER_ADDED` was added in 8.0.11.

- Error number: `MY-011502`; Symbol: `ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR`; SQLSTATE: `HY000`

Message: There was a previous plugin error while the member joined the group. The member will now exit the group.

`ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR` was added in 8.0.11.

- Error number: `MY-011503`; Symbol: `ER_GRP_RPL_MEMBER_CHANGE`; SQLSTATE: `HY000`

Message: Group membership changed to %s on view %s.

`ER_GRP_RPL_MEMBER_CHANGE` was added in 8.0.11.

- Error number: `MY-011504`; Symbol: `ER_GRP_RPL_MEMBER_LEFT_GRP`; SQLSTATE: `HY000`

Message: Group membership changed: This member has left the group.

`ER_GRP_RPL_MEMBER_LEFT_GRP` was added in 8.0.11.

- Error number: `MY-011505`; Symbol: `ER_GRP_RPL_MEMBER_EXPELLED`; SQLSTATE: `HY000`

Message: Member was expelled from the group due to network failures, changing member status to ERROR.

`ER_GRP_RPL_MEMBER_EXPELLED` was added in 8.0.11.

- Error number: `MY-011506`; Symbol: `ER_GRP_RPL_SESSION_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Unable to open session to (re)set read only mode. Skipping.

`ER_GRP_RPL_SESSION_OPEN_FAILED` was added in 8.0.11.

- Error number: `MY-011507`; Symbol: `ER_GRP_RPL_NEW_PRIMARY_ELECTED`; SQLSTATE: `HY000`

Message: A new primary with address %s:%u was elected. %s

`ER_GRP_RPL_NEW_PRIMARY_ELECTED` was added in 8.0.11.

- Error number: `MY-011508`; Symbol: `ER_GRP_RPL_DISABLE_READ_ONLY_FAILED`; SQLSTATE: `HY000`

Message: Unable to disable super read only flag. Try to disable it manually

---

`ER_GRP_RPL_DISABLE_READ_ONLY_FAILED` was added in 8.0.11.

- Error number: `MY-011509`; Symbol: `ER_GRP_RPL_ENABLE_READ_ONLY_FAILED`; SQLSTATE: `HY000`

Message: Unable to set super read only flag. Try to set it manually.

`ER_GRP_RPL_ENABLE_READ_ONLY_FAILED` was added in 8.0.11.

- Error number: `MY-011510`; Symbol: `ER_GRP_RPL_SRV_PRIMARY_MEM`; SQLSTATE: `HY000`

Message: This server is working as primary member.

`ER_GRP_RPL_SRV_PRIMARY_MEM` was added in 8.0.11.

- Error number: `MY-011511`; Symbol: `ER_GRP_RPL_SRV_SECONDARY_MEM`; SQLSTATE: `HY000`

Message: This server is working as secondary member with primary member address %s:%u.

`ER_GRP_RPL_SRV_SECONDARY_MEM` was added in 8.0.11.

- Error number: `MY-011512`; Symbol: `ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM`; SQLSTATE: `HY000`

Message: Unable to set any member as primary. No suitable candidate.

`ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM` was added in 8.0.11.

- Error number: `MY-011513`; Symbol: `ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR`; SQLSTATE: `HY000`

Message: Error when activating super\_read\_only mode on start. The member will now exit the group.

`ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR` was added in 8.0.11.

- Error number: `MY-011514`; Symbol: `ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE`; SQLSTATE: `HY000`

Message: Group contains %lu members which is greater than group\_replication\_auto\_increment\_increment value of %lu. This can lead to a higher transactional abort rate.

`ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE` was added in 8.0.11.

- Error number: `MY-011515`; Symbol: `ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM`; SQLSTATE: `HY000`

Message: Member with address '%s:%u' didn't provide any data during the last group change. Group information can be outdated and lead to errors on recovery.

`ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM` was added in 8.0.11.

- Error number: `MY-011516`; Symbol: `ER_GRP_RPL_MEMBER_ALREADY_EXISTS`; SQLSTATE: `HY000`

Message: There is already a member with server\_uuid %s. The member will now exit the group.

`ER_GRP_RPL_MEMBER_ALREADY_EXISTS` was added in 8.0.11.

- 
- Error number: [MY-011517](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_CHANGE\\_INFO\\_EXTRACT\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when extracting information for group change. Operations and checks made to group joiners may be incomplete.

[ER\\_GRP\\_RPL\\_GRP\\_CHANGE\\_INFO\\_EXTRACT\\_ERROR](#) was added in 8.0.11, removed after 8.0.26.

- Error number: [MY-011518](#); Symbol: [ER\\_GRP\\_RPL\\_GTID\\_EXECUTED\\_EXTRACT\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member GTID executed set. Operations and checks made to group joiners may be incomplete.

[ER\\_GRP\\_RPL\\_GTID\\_EXECUTED\\_EXTRACT\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011519](#); Symbol: [ER\\_GRP\\_RPL\\_GTID\\_SET\\_EXTRACT\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member retrieved set for its applier. Operations and checks made to group joiners may be incomplete.

[ER\\_GRP\\_RPL\\_GTID\\_SET\\_EXTRACT\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011520](#); Symbol: [ER\\_GRP\\_RPL\\_START\\_FAILED](#); SQLSTATE: [HY000](#)

Message: The START GROUP\_REPLICATION command failed since the group already has 9 members.

[ER\\_GRP\\_RPL\\_START\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011521](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_VER\\_INCOMPATIBLE](#); SQLSTATE: [HY000](#)

Message: Member version is incompatible with the group.

[ER\\_GRP\\_RPL\\_MEMBER\\_VER\\_INCOMPATIBLE](#) was added in 8.0.11.

- Error number: [MY-011522](#); Symbol: [ER\\_GRP\\_RPL\\_TRANS\\_NOT\\_PRESENT\\_IN\\_GRP](#); SQLSTATE: [HY000](#)

Message: The member contains transactions not present in the group. The member will now exit the group.

[ER\\_GRP\\_RPL\\_TRANS\\_NOT\\_PRESENT\\_IN\\_GRP](#) was added in 8.0.11.

- Error number: [MY-011523](#); Symbol: [ER\\_GRP\\_RPL\\_TRANS\\_GREATER\\_THAN\\_GRP](#); SQLSTATE: [HY000](#)

Message: It was not possible to assess if the member has more transactions than the group. The member will now exit the group.

[ER\\_GRP\\_RPL\\_TRANS\\_GREATER\\_THAN\\_GRP](#) was added in 8.0.11.

- Error number: [MY-011524](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_VERSION\\_LOWER\\_THAN\\_GRP](#); SQLSTATE: [HY000](#)

Message: Member version is lower than some group member, but since option 'group\_replication\_allow\_local\_lower\_version\_join' is enabled, member will be allowed to join.

[ER\\_GRP\\_RPL\\_MEMBER\\_VERSION\\_LOWER\\_THAN\\_GRP](#) was added in 8.0.11.

- 
- Error number: [MY-011525](#); Symbol: [ER\\_GRP\\_RPL\\_LOCAL\\_GTID\\_SETS\\_PROCESS\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error processing local GTID sets when comparing this member transactions against the group.  
  
[ER\\_GRP\\_RPL\\_LOCAL\\_GTID\\_SETS\\_PROCESS\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011526](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_TRANS\\_GREATER\\_THAN\\_GRP](#); SQLSTATE: [HY000](#)  
  
Message: This member has more executed transactions than those present in the group. Local transactions: %s > Group transactions: %s  
  
[ER\\_GRP\\_RPL\\_MEMBER\\_TRANS\\_GREATER\\_THAN\\_GRP](#) was added in 8.0.11.
  - Error number: [MY-011527](#); Symbol: [ER\\_GRP\\_RPL\\_BLOCK\\_SIZE\\_DIFF\\_FROM\\_GRP](#); SQLSTATE: [HY000](#)  
  
Message: The member is configured with a group\_replication\_gtid\_assignment\_block\_size option value '%llu' different from the group '%llu'. The member will now exit the group.  
  
[ER\\_GRP\\_RPL\\_BLOCK\\_SIZE\\_DIFF\\_FROM\\_GRP](#) was added in 8.0.11.
  - Error number: [MY-011528](#); Symbol: [ER\\_GRP\\_RPL\\_TRANS\\_WRITE\\_SET\\_EXTRACT\\_DIFF\\_FROM\\_GRP](#); SQLSTATE: [HY000](#)  
  
Message: The member is configured with a transaction-write-set-extraction option value '%s' different from the group '%s'. The member will now exit the group.  
  
[ER\\_GRP\\_RPL\\_TRANS\\_WRITE\\_SET\\_EXTRACT\\_DIFF\\_FROM\\_GRP](#) was added in 8.0.11.
  - Error number: [MY-011529](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_CFG\\_INCOMPATIBLE\\_WITH\\_GRP\\_CFG](#); SQLSTATE: [HY000](#)  
  
Message: The member configuration is not compatible with the group configuration. Variables such as group\_replication\_single\_primary\_mode or group\_replication\_enforce\_update\_everywhere\_checks must have the same value on every server in the group. (member configuration option: [%s], group configuration option: [%s]).  
  
[ER\\_GRP\\_RPL\\_MEMBER\\_CFG\\_INCOMPATIBLE\\_WITH\\_GRP\\_CFG](#) was added in 8.0.11.
  - Error number: [MY-011530](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_STOP\\_RPL\\_CHANNELS\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error stopping all replication channels while server was leaving the group. %s  
  
[ER\\_GRP\\_RPL\\_MEMBER\\_STOP\\_RPL\\_CHANNELS\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011531](#); Symbol: [ER\\_GRP\\_RPL\\_PURGE\\_APPLIER\\_LOGS](#); SQLSTATE: [HY000](#)  
  
Message: Detected previous RESET SOURCE invocation or an issue exists in the group replication applier relay log. Purging existing applier logs.  
  
[ER\\_GRP\\_RPL\\_PURGE\\_APPLIER\\_LOGS](#) was added in 8.0.11.
  - Error number: [MY-011532](#); Symbol: [ER\\_GRP\\_RPL\\_RESET\\_APPLIER\\_MODULE\\_LOGS\\_ERROR](#); SQLSTATE: [HY000](#)

---

Message: Unknown error occurred while resetting applier's module logs.

[ER\\_GRP\\_RPL\\_RESET\\_APPLIER\\_MODULE\\_LOGS\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011533](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_SETUP\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to setup the group replication applier thread.

[ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_SETUP\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011534](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_START\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while starting the group replication applier thread

[ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_START\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011535](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_STOP\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to stop the group replication applier thread.

[ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_STOP\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011536](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_DATA\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch transaction data containing required transaction info for applier

[ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_DATA\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011537](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THD\\_PRIMARY\\_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start slave IO THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THD\\_PRIMARY\\_UNKNOWN](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-011537](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THD\\_PRIMARY\\_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start replica IO THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THD\\_PRIMARY\\_UNKNOWN](#) was added in 8.0.33.

- Error number: [MY-011538](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THD\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start replica IO THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

[ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THD\\_ON\\_SECONDARY\\_MEMBER](#) was added in 8.0.11.

- 
- Error number: [MY-011539](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_SQL\\_THD\\_PRIMARY\\_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start slave SQL THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER\\_GRP\\_RPL\\_SLAVE\\_SQL\\_THD\\_PRIMARY\\_UNKNOWN](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-011539](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_SQL\\_THD\\_PRIMARY\\_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start replica SQL THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER\\_GRP\\_RPL\\_REPLICA\\_SQL\\_THD\\_PRIMARY\\_UNKNOWN](#) was added in 8.0.33.

- Error number: [MY-011540](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_SQL\\_THD\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start slave SQL THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

[ER\\_GRP\\_RPL\\_SLAVE\\_SQL\\_THD\\_ON\\_SECONDARY\\_MEMBER](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-011540](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_SQL\\_THD\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start replica SQL THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

[ER\\_GRP\\_RPL\\_REPLICA\\_SQL\\_THD\\_ON\\_SECONDARY\\_MEMBER](#) was added in 8.0.33.

- Error number: [MY-011541](#); Symbol: [ER\\_GRP\\_RPL\\_NEEDS\\_INNODB\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Table %s does not use the InnoDB storage engine. This is not compatible with Group Replication.

[ER\\_GRP\\_RPL\\_NEEDS\\_INNODB\\_TABLE](#) was added in 8.0.11.

- Error number: [MY-011542](#); Symbol: [ER\\_GRP\\_RPL\\_PRIMARY\\_KEY\\_NOT\\_DEFINED](#); SQLSTATE: [HY000](#)

Message: Table %s does not have any PRIMARY KEY. This is not compatible with Group Replication.

[ER\\_GRP\\_RPL\\_PRIMARY\\_KEY\\_NOT\\_DEFINED](#) was added in 8.0.11.

- Error number: [MY-011543](#); Symbol: [ER\\_GRP\\_RPL\\_FK\\_WITH\\_CASCADE\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Table %s has a foreign key with 'CASCADE', 'SET NULL' or 'SET DEFAULT' clause. This is not compatible with Group Replication.

[ER\\_GRP\\_RPL\\_FK\\_WITH\\_CASCADE\\_UNSUPPORTED](#) was added in 8.0.11.

- Error number: [MY-011544](#); Symbol: [ER\\_GRP\\_RPL\\_AUTO\\_INC\\_RESET](#); SQLSTATE: [HY000](#)

Message: group\_replication\_auto\_increment\_increment is reset to %lu

[ER\\_GRP\\_RPL\\_AUTO\\_INC\\_RESET](#) was added in 8.0.11.



- 
- Error number: [MY-011545](#); Symbol: [ER\\_GRP\\_RPL\\_AUTO\\_INC\\_OFFSET\\_RESET](#); SQLSTATE: [HY000](#)  
Message: auto\_increment\_offset is reset to %lu  
[ER\\_GRP\\_RPL\\_AUTO\\_INC\\_OFFSET\\_RESET](#) was added in 8.0.11.
  - Error number: [MY-011546](#); Symbol: [ER\\_GRP\\_RPL\\_AUTO\\_INC\\_SET](#); SQLSTATE: [HY000](#)  
Message: group\_replication\_auto\_increment\_increment is set to %lu  
[ER\\_GRP\\_RPL\\_AUTO\\_INC\\_SET](#) was added in 8.0.11.
  - Error number: [MY-011547](#); Symbol: [ER\\_GRP\\_RPL\\_AUTO\\_INC\\_OFFSET\\_SET](#); SQLSTATE: [HY000](#)  
Message: auto\_increment\_offset is set to %lu  
[ER\\_GRP\\_RPL\\_AUTO\\_INC\\_OFFSET\\_SET](#) was added in 8.0.11.
  - Error number: [MY-011548](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_CONTEXT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to fetch transaction context containing required transaction info for certification  
[ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_CONTEXT\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011549](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_FORMAT\\_DESC\\_LOG\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to fetch Format\_description\_log\_event containing required server info for applier  
[ER\\_GRP\\_RPL\\_FETCH\\_FORMAT\\_DESC\\_LOG\\_EVENT\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011550](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_CONTEXT\\_LOG\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to fetch Transaction\_context\_log\_event containing required transaction info for certification  
[ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_CONTEXT\\_LOG\\_EVENT\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011551](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_SNAPSHOT\\_VERSION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to read snapshot version from transaction context event required for certification  
[ER\\_GRP\\_RPL\\_FETCH\\_SNAPSHOT\\_VERSION\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011552](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_GTID\\_LOG\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to fetch Gtid\_log\_event containing required transaction info for certification  
[ER\\_GRP\\_RPL\\_FETCH\\_GTID\\_LOG\\_EVENT\\_FAILED](#) was added in 8.0.11.

- 
- Error number: `MY-011553`; Symbol: `ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED`; SQLSTATE: `HY000`  
  
Message: Unable to update certification result on server side, thread\_id: %lu  
  
`ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED` was added in 8.0.11.
  - Error number: `MY-011554`; Symbol: `ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED`; SQLSTATE: `HY000`  
  
Message: Unable to add gtid information to the group\_gtid\_executed set when gtid was provided for local transactions  
  
`ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED` was added in 8.0.11.
  - Error number: `MY-011555`; Symbol: `ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED`; SQLSTATE: `HY000`  
  
Message: Unable to add gtid information to the group\_gtid\_executed set when no gtid was provided for local transactions  
  
`ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED` was added in 8.0.11.
  - Error number: `MY-011556`; Symbol: `ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED`; SQLSTATE: `HY000`  
  
Message: Failed to notify certification outcome  
  
`ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED` was added in 8.0.11.
  - Error number: `MY-011557`; Symbol: `ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED`; SQLSTATE: `HY000`  
  
Message: Unable to add gtid information to the group\_gtid\_executed set when gtid was provided for remote transactions  
  
`ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED` was added in 8.0.11.
  - Error number: `MY-011558`; Symbol: `ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED`; SQLSTATE: `HY000`  
  
Message: Unable to add gtid information to the group\_gtid\_executed set when gtid was not provided for remote transactions  
  
`ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED` was added in 8.0.11.
  - Error number: `MY-011559`; Symbol: `ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED`; SQLSTATE: `HY000`  
  
Message: Failed to fetch View\_change\_log\_event containing required info for certification  
  
`ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED` was added in 8.0.11.
  - Error number: `MY-011560`; Symbol: `ER_GRP_RPL_CONTACT_WITH_SRV_FAILED`; SQLSTATE: `HY000`  
  
Message: Error when contacting the server to ensure the proper logging of a group change in the binlog  
  
`ER_GRP_RPL_CONTACT_WITH_SRV_FAILED` was added in 8.0.11, removed after 8.0.31.

- 
- Error number: [MY-011561](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_WAIT\\_TIME\\_OUT](#); SQLSTATE: [HY000](#)  
Message: Timeout when waiting for the server to execute local transactions in order assure the group change proper logging  
[ER\\_GRP\\_RPL\\_SRV\\_WAIT\\_TIME\\_OUT](#) was added in 8.0.11, removed after 8.0.31.
  - Error number: [MY-011562](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_LOG\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to fetch Log\_event containing required server info for applier  
[ER\\_GRP\\_RPL\\_FETCH\\_LOG\\_EVENT\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011563](#); Symbol: [ER\\_GRP\\_RPL\\_START\\_GRP\\_RPL\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with --initialize, --initialize-insecure or --upgrade=MINIMAL on a server upgrade.  
[ER\\_GRP\\_RPL\\_START\\_GRP\\_RPL\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011564](#); Symbol: [ER\\_GRP\\_RPL\\_CONN\\_INTERNAL\\_PLUGIN\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to establish an internal server connection to execute plugin operations  
[ER\\_GRP\\_RPL\\_CONN\\_INTERNAL\\_PLUGIN\\_FAIL](#) was added in 8.0.11.
  - Error number: [MY-011565](#); Symbol: [ER\\_GRP\\_RPL\\_SUPER\\_READ\\_ON](#); SQLSTATE: [HY000](#)  
Message: Setting super\_read\_only=ON.  
[ER\\_GRP\\_RPL\\_SUPER\\_READ\\_ON](#) was added in 8.0.11.
  - Error number: [MY-011566](#); Symbol: [ER\\_GRP\\_RPL\\_SUPER\\_READ\\_OFF](#); SQLSTATE: [HY000](#)  
Message: Setting super\_read\_only=OFF.  
[ER\\_GRP\\_RPL\\_SUPER\\_READ\\_OFF](#) was added in 8.0.11.
  - Error number: [MY-011567](#); Symbol: [ER\\_GRP\\_RPL\\_KILLED\\_SESSION\\_ID](#); SQLSTATE: [HY000](#)  
Message: killed session id: %d status: %d  
[ER\\_GRP\\_RPL\\_KILLED\\_SESSION\\_ID](#) was added in 8.0.11.
  - Error number: [MY-011568](#); Symbol: [ER\\_GRP\\_RPL\\_KILLED\\_FAILED\\_ID](#); SQLSTATE: [HY000](#)  
Message: killed failed id: %d failed: %d  
[ER\\_GRP\\_RPL\\_KILLED\\_FAILED\\_ID](#) was added in 8.0.11.
  - Error number: [MY-011569](#); Symbol: [ER\\_GRP\\_RPL\\_INTERNAL\\_QUERY](#); SQLSTATE: [HY000](#)  
Message: Internal query: %s result in error. Error number: %ld  
[ER\\_GRP\\_RPL\\_INTERNAL\\_QUERY](#) was added in 8.0.11.
  - Error number: [MY-011570](#); Symbol: [ER\\_GRP\\_RPL\\_COPY\\_FROM\\_EMPTY\\_STRING](#); SQLSTATE: [HY000](#)  
Message: Error copying from empty string

---

`ER_GRP_RPL_COPY_FROM_EMPTY_STRING` was added in 8.0.11.

- Error number: `MY-011571`; Symbol: `ER_GRP_RPL_QUERY_FAIL`; SQLSTATE: `HY000`

Message: Query execution resulted in failure. errno: %d

`ER_GRP_RPL_QUERY_FAIL` was added in 8.0.11.

- Error number: `MY-011572`; Symbol: `ER_GRP_RPL_CREATE_SESSION_UNABLE`; SQLSTATE: `HY000`

Message: Unable to create a session for executing the queries on the server

`ER_GRP_RPL_CREATE_SESSION_UNABLE` was added in 8.0.11.

- Error number: `MY-011573`; Symbol: `ER_GRP_RPL_MEMBER_NOT_FOUND`; SQLSTATE: `HY000`

Message: The member with address %s:%u has unexpectedly disappeared, killing the current group replication recovery connection

`ER_GRP_RPL_MEMBER_NOT_FOUND` was added in 8.0.11.

- Error number: `MY-011574`; Symbol: `ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED`; SQLSTATE: `HY000`

Message: Maximum number of retries when trying to connect to a donor reached. Aborting group replication incremental recovery.

`ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED` was added in 8.0.11.

- Error number: `MY-011575`; Symbol: `ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY`; SQLSTATE: `HY000`

Message: All donors left. Aborting group replication incremental recovery.

`ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY` was added in 8.0.11.

- Error number: `MY-011576`; Symbol: `ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR`; SQLSTATE: `HY000`

Message: Establishing group recovery connection with a possible donor. Attempt %d/%d

`ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR` was added in 8.0.11.

- Error number: `MY-011577`; Symbol: `ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR`; SQLSTATE: `HY000`

Message: Retrying group recovery connection with another donor. Attempt %d/%d

`ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR` was added in 8.0.11.

- Error number: `MY-011578`; Symbol: `ER_GRP_RPL_NO_VALID_DONOR`; SQLSTATE: `HY000`

Message: No valid donors exist in the group, retrying

`ER_GRP_RPL_NO_VALID_DONOR` was added in 8.0.11.

- Error number: `MY-011579`; Symbol: `ER_GRP_RPL_CONFIG_RECOVERY`; SQLSTATE: `HY000`

Message: Error when configuring the asynchronous recovery channel connection to the donor.

---

`ER_GRP_RPL_CONFIG_RECOVERY` was added in 8.0.11.

- Error number: `MY-011580`; Symbol: `ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR`; SQLSTATE: `HY000`

Message: Establishing connection to a group replication recovery donor %s at %s port: %d.

`ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR` was added in 8.0.11.

- Error number: `MY-011581`; Symbol: `ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL`; SQLSTATE: `HY000`

Message: Error while creating the group replication recovery channel with donor %s at %s port: %d.

`ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL` was added in 8.0.11.

- Error number: `MY-011582`; Symbol: `ER_GRP_RPL_DONOR_SERVER_CONN`; SQLSTATE: `HY000`

Message: There was an error when connecting to the donor server. Please check that group\_replication\_recovery channel credentials and all MEMBER\_HOST column values of performance\_schema.replication\_group\_members table are correct and DNS resolvable.

`ER_GRP_RPL_DONOR_SERVER_CONN` was added in 8.0.11.

- Error number: `MY-011583`; Symbol: `ER_GRP_RPL_CHECK_STATUS_TABLE`; SQLSTATE: `HY000`

Message: For details please check performance\_schema.replication\_connection\_status table and error log messages of Replica I/O for channel group\_replication\_recovery.

`ER_GRP_RPL_CHECK_STATUS_TABLE` was added in 8.0.11.

- Error number: `MY-011584`; Symbol: `ER_GRP_RPL_STARTING_GRP_REC`; SQLSTATE: `HY000`

Message: Error while starting the group replication incremental recovery receiver/applier threads

`ER_GRP_RPL_STARTING_GRP_REC` was added in 8.0.11.

- Error number: `MY-011585`; Symbol: `ER_GRP_RPL_DONOR_CONN_TERMINATION`; SQLSTATE: `HY000`

Message: Terminating existing group replication donor connection and purging the corresponding logs.

`ER_GRP_RPL_DONOR_CONN_TERMINATION` was added in 8.0.11.

- Error number: `MY-011586`; Symbol: `ER_GRP_RPL_STOPPING_GRP_REC`; SQLSTATE: `HY000`

Message: Error when stopping the group replication incremental recovery's donor connection

`ER_GRP_RPL_STOPPING_GRP_REC` was added in 8.0.11.

- Error number: `MY-011587`; Symbol: `ER_GRP_RPL_PURGE_REC`; SQLSTATE: `HY000`

Message: Error when purging the group replication recovery's relay logs

`ER_GRP_RPL_PURGE_REC` was added in 8.0.11.

- 
- Error number: [MY-011588](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_KILL\\_CONN\\_REC\\_DONOR\\_APPLIER](#); SQLSTATE: [HY000](#)  
  
Message: Unable to kill the current group replication recovery donor connection after an applier error. Incremental recovery will shutdown.  
  
[ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_KILL\\_CONN\\_REC\\_DONOR\\_APPLIER](#) was added in 8.0.11.
  - Error number: [MY-011589](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_KILL\\_CONN\\_REC\\_DONOR\\_FAILOVER](#); SQLSTATE: [HY000](#)  
  
Message: Unable to kill the current group replication recovery donor connection during failover. Incremental recovery will shutdown.  
  
[ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_KILL\\_CONN\\_REC\\_DONOR\\_FAILOVER](#) was added in 8.0.11.
  - Error number: [MY-011590](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_NOTIFY\\_GRP\\_MEMBERSHIP\\_EVENT](#); SQLSTATE: [HY000](#)  
  
Message: Unexpected error when notifying an internal component named %s regarding a group membership event.  
  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_NOTIFY\\_GRP\\_MEMBERSHIP\\_EVENT](#) was added in 8.0.11.
  - Error number: [MY-011591](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_BROADCAST\\_GRP\\_MEMBERSHIP\\_NOTIFICATION](#); SQLSTATE: [HY000](#)  
  
Message: An undefined error was found while broadcasting an internal group membership notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!  
  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_BROADCAST\\_GRP\\_MEMBERSHIP\\_NOTIFICATION](#) was added in 8.0.11.
  - Error number: [MY-011592](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_BROADCAST\\_MEMBER\\_STATUS\\_NOTIFICATION](#); SQLSTATE: [HY000](#)  
  
Message: An undefined error was found while broadcasting an internal group member status notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!  
  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_BROADCAST\\_MEMBER\\_STATUS\\_NOTIFICATION](#) was added in 8.0.11.
  - Error number: [MY-011593](#); Symbol: [ER\\_GRP\\_RPL\\_OOM\\_FAILED\\_TO\\_GENERATE\\_IDENTIFICATION\\_HASH](#); SQLSTATE: [HY000](#)  
  
Message: No memory to generate write identification hash  
  
[ER\\_GRP\\_RPL\\_OOM\\_FAILED\\_TO\\_GENERATE\\_IDENTIFICATION\\_HASH](#) was added in 8.0.11.
  - Error number: [MY-011594](#); Symbol: [ER\\_GRP\\_RPL\\_WRITE\\_IDENT\\_HASH\\_BASE64\\_ENCODING\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Base 64 encoding of the write identification hash failed  
  
[ER\\_GRP\\_RPL\\_WRITE\\_IDENT\\_HASH\\_BASE64\\_ENCODING\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011595](#); Symbol: [ER\\_GRP\\_RPL\\_INVALID\\_BINLOG\\_FORMAT](#); SQLSTATE: [HY000](#)  
  
Message: Binlog format should be ROW for Group Replication  
  
[ER\\_GRP\\_RPL\\_INVALID\\_BINLOG\\_FORMAT](#) was added in 8.0.11.

- 
- Error number: [MY-011596](#); Symbol: [ER\\_GRP\\_RPL\\_BINLOG\\_CHECKSUM\\_SET](#); SQLSTATE: [HY000](#)  
Message: binlog\_checksum should be NONE for Group Replication  
[ER\\_GRP\\_RPL\\_BINLOG\\_CHECKSUM\\_SET](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-011597](#); Symbol: [ER\\_GRP\\_RPL\\_TRANS\\_WRITE\\_SET\\_EXTRACTION\\_NOT\\_SET](#); SQLSTATE: [HY000](#)  
Message: A transaction\_write\_set\_extraction algorithm should be selected when running Group Replication  
[ER\\_GRP\\_RPL\\_TRANS\\_WRITE\\_SET\\_EXTRACTION\\_NOT\\_SET](#) was added in 8.0.11.
  - Error number: [MY-011598](#); Symbol: [ER\\_GRP\\_RPL\\_UNSUPPORTED\\_TRANS\\_ISOLATION](#); SQLSTATE: [HY000](#)  
Message: Transaction isolation level (tx\_isolation) is set to SERIALIZABLE, which is not compatible with Group Replication  
[ER\\_GRP\\_RPL\\_UNSUPPORTED\\_TRANS\\_ISOLATION](#) was added in 8.0.11.
  - Error number: [MY-011599](#); Symbol: [ER\\_GRP\\_RPL\\_CANNOT\\_EXECUTE\\_TRANS\\_WHILE\\_STOPPING](#); SQLSTATE: [HY000](#)  
Message: Transaction cannot be executed while Group Replication is stopping.  
[ER\\_GRP\\_RPL\\_CANNOT\\_EXECUTE\\_TRANS\\_WHILE\\_STOPPING](#) was added in 8.0.11.
  - Error number: [MY-011600](#); Symbol: [ER\\_GRP\\_RPL\\_CANNOT\\_EXECUTE\\_TRANS\\_WHILE\\_RECOVERING](#); SQLSTATE: [HY000](#)  
Message: Transaction cannot be executed while Group Replication is recovering. Try again when the server is ONLINE.  
[ER\\_GRP\\_RPL\\_CANNOT\\_EXECUTE\\_TRANS\\_WHILE\\_RECOVERING](#) was added in 8.0.11.
  - Error number: [MY-011601](#); Symbol: [ER\\_GRP\\_RPL\\_CANNOT\\_EXECUTE\\_TRANS\\_IN\\_ERROR\\_STATE](#); SQLSTATE: [HY000](#)  
Message: Transaction cannot be executed while Group Replication is on ERROR state. Check for errors and restart the plugin  
[ER\\_GRP\\_RPL\\_CANNOT\\_EXECUTE\\_TRANS\\_IN\\_ERROR\\_STATE](#) was added in 8.0.11.
  - Error number: [MY-011602](#); Symbol: [ER\\_GRP\\_RPL\\_CANNOT\\_EXECUTE\\_TRANS\\_IN\\_OFFLINE\\_MODE](#); SQLSTATE: [HY000](#)  
Message: Transaction cannot be executed while Group Replication is OFFLINE. Check for errors and restart the plugin  
[ER\\_GRP\\_RPL\\_CANNOT\\_EXECUTE\\_TRANS\\_IN\\_OFFLINE\\_MODE](#) was added in 8.0.11.
  - Error number: [MY-011603](#); Symbol: [ER\\_GRP\\_RPL\\_MULTIPLE\\_CACHE\\_TYPE\\_NOT\\_SUPPORTED\\_FOR\\_SESSION](#); SQLSTATE: [HY000](#)  
Message: We can only use one cache type at a time on session %u  
[ER\\_GRP\\_RPL\\_MULTIPLE\\_CACHE\\_TYPE\\_NOT\\_SUPPORTED\\_FOR\\_SESSION](#) was added in 8.0.11.

- 
- Error number: [MY-011604](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_REINIT\\_BINLOG\\_CACHE\\_FOR\\_READ](#); SQLSTATE: [HY000](#)  
  
Message: Failed to reinit binlog cache log for read on session %u  
  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_REINIT\\_BINLOG\\_CACHE\\_FOR\\_READ](#) was added in 8.0.11.
  - Error number: [MY-011605](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_CREATE\\_TRANS\\_CONTEXT](#); SQLSTATE: [HY000](#)  
  
Message: Failed to create the context of the current transaction on session %u  
  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_CREATE\\_TRANS\\_CONTEXT](#) was added in 8.0.11.
  - Error number: [MY-011606](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_EXTRACT\\_TRANS\\_WRITE\\_SET](#); SQLSTATE: [HY000](#)  
  
Message: Failed to extract the set of items written during the execution of the current transaction on session %u  
  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_EXTRACT\\_TRANS\\_WRITE\\_SET](#) was added in 8.0.11.
  - Error number: [MY-011607](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_GATHER\\_TRANS\\_WRITE\\_SET](#); SQLSTATE: [HY000](#)  
  
Message: Failed to gather the set of items written during the execution of the current transaction on session %u  
  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_GATHER\\_TRANS\\_WRITE\\_SET](#) was added in 8.0.11.
  - Error number: [MY-011608](#); Symbol: [ER\\_GRP\\_RPL\\_TRANS\\_SIZE\\_EXCEEDS\\_LIMIT](#); SQLSTATE: [HY000](#)  
  
Message: Error on session %u. Transaction of size %llu exceeds specified limit %lu. To increase the limit please adjust group\_replication\_transaction\_size\_limit option.  
  
[ER\\_GRP\\_RPL\\_TRANS\\_SIZE\\_EXCEEDS\\_LIMIT](#) was added in 8.0.11.
  - Error number: [MY-011609](#); Symbol: [ER\\_GRP\\_RPL\\_REINIT\\_OF\\_INTERNAL\\_CACHE\\_FOR\\_READ\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Error while re-initializing an internal cache, for read operations, on session %u  
  
[ER\\_GRP\\_RPL\\_REINIT\\_OF\\_INTERNAL\\_CACHE\\_FOR\\_READ\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011610](#); Symbol: [ER\\_GRP\\_RPL\\_APPENDING\\_DATA\\_TO\\_INTERNAL\\_CACHE\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Error while appending data to an internal cache on session %u  
  
[ER\\_GRP\\_RPL\\_APPENDING\\_DATA\\_TO\\_INTERNAL\\_CACHE\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011611](#); Symbol: [ER\\_GRP\\_RPL\\_WRITE\\_TO\\_BINLOG\\_CACHE\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Error while writing binary log cache on session %u



---

`ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011611`; Symbol: `ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED`; SQLSTATE: `HY000`

Message: Error while writing to transaction message on session %u

`ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED` was added in 8.0.13.

- Error number: `MY-011612`; Symbol: `ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION`; SQLSTATE: `HY000`

Message: Unable to register for getting notifications regarding the outcome of the transaction on session %u

`ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION` was added in 8.0.11.

- Error number: `MY-011613`; Symbol: `ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_FAILED`; SQLSTATE: `HY000`

Message: Error broadcasting transaction to the group on session %u. Message is too big.

`ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_FAILED` was added in 8.0.11.

- Error number: `MY-011614`; Symbol: `ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED`; SQLSTATE: `HY000`

Message: Error while broadcasting the transaction to the group on session %u

`ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED` was added in 8.0.11.

- Error number: `MY-011615`; Symbol: `ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_DETECTION`; SQLSTATE: `HY000`

Message: Error while waiting for conflict detection procedure to finish on session %u

`ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_DETECTION` was added in 8.0.11.

- Error number: `MY-011616`; Symbol: `ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITE_FAILED`; SQLSTATE: `HY000`

Message: Error while re-initializing an internal cache, for write operations, on session %u

`ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITE_FAILED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011617`; Symbol: `ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE`; SQLSTATE: `HY000`

Message: Failed to create group replication commit cache on session %u

`ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011618`; Symbol: `ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITE_FAILED`; SQLSTATE: `HY000`

Message: Failed to reinit group replication commit cache for write on session %u

---

`ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITE_FAILED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011619`; Symbol: `ER_GRP_RPL_PREV_REC_SESSION_RUNNING`; SQLSTATE: `HY000`

Message: A previous recovery session is still running. Please stop the group replication plugin and wait for it to stop

`ER_GRP_RPL_PREV_REC_SESSION_RUNNING` was added in 8.0.11, removed after 8.0.22.

- Error number: `MY-011620`; Symbol: `ER_GRP_RPL_FATAL_REC_PROCESS`; SQLSTATE: `HY000`

Message: Fatal error during the incremental recovery process of Group Replication. The server will leave the group.

`ER_GRP_RPL_FATAL_REC_PROCESS` was added in 8.0.11.

- Error number: `MY-011621`; Symbol: `ER_GRP_RPL_WHILE_STOPPING_REP_CHANNEL`; SQLSTATE: `HY000`

Message: Error stopping all replication channels while server was leaving the group. %s

`ER_GRP_RPL_WHILE_STOPPING_REP_CHANNEL` was added in 8.0.11, removed after 8.0.17.

- Error number: `MY-011622`; Symbol: `ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS`; SQLSTATE: `HY000`

Message: Unable to evaluate the group replication applier execution status. Group replication recovery will shutdown to avoid data corruption.

`ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS` was added in 8.0.11.

- Error number: `MY-011623`; Symbol: `ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE`; SQLSTATE: `HY000`

Message: Only one server alive. Declaring this server as online within the replication group

`ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE` was added in 8.0.11.

- Error number: `MY-011624`; Symbol: `ER_GRP_RPL_CERTIFICATION_REC_PROCESS`; SQLSTATE: `HY000`

Message: Error when processing certification information in the incremental recovery process

`ER_GRP_RPL_CERTIFICATION_REC_PROCESS` was added in 8.0.11.

- Error number: `MY-011625`; Symbol: `ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC`; SQLSTATE: `HY000`

Message: Unable to ensure the execution of group transactions received during recovery.

`ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC` was added in 8.0.11.

- Error number: `MY-011626`; Symbol: `ER_GRP_RPL_WHILE_SENDING_MSG_REC`; SQLSTATE: `HY000`

Message: Error while sending message in the group replication incremental recovery process.

`ER_GRP_RPL_WHILE_SENDING_MSG_REC` was added in 8.0.11.

- 
- Error number: [MY-011627](#); Symbol: [ER\\_GRP\\_RPL\\_READ\\_UNABLE\\_FOR\\_SUPER\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)  
  
Message: Unable to read the server value for the super\_read\_only variable.  
  
[ER\\_GRP\\_RPL\\_READ\\_UNABLE\\_FOR\\_SUPER\\_READ\\_ONLY](#) was added in 8.0.11, removed after 8.0.31.
  - Error number: [MY-011628](#); Symbol: [ER\\_GRP\\_RPL\\_READ\\_UNABLE\\_FOR\\_READ\\_ONLY\\_SUPER\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)  
  
Message: Unable to read the server values for the read\_only and super\_read\_only variables.  
  
[ER\\_GRP\\_RPL\\_READ\\_UNABLE\\_FOR\\_READ\\_ONLY\\_SUPER\\_READ\\_ONLY](#) was added in 8.0.11.
  - Error number: [MY-011629](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_RESET\\_SERVER\\_READ\\_MODE](#); SQLSTATE: [HY000](#)  
  
Message: Unable to reset the server read mode settings. Try to reset them manually.  
  
[ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_RESET\\_SERVER\\_READ\\_MODE](#) was added in 8.0.11.
  - Error number: [MY-011630](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_CERTIFY\\_PLUGIN\\_TRANS](#); SQLSTATE: [HY000](#)  
  
Message: Due to a plugin error, some transactions were unable to be certified and will now rollback.  
  
[ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_CERTIFY\\_PLUGIN\\_TRANS](#) was added in 8.0.11.
  - Error number: [MY-011631](#); Symbol: [ER\\_GRP\\_RPL\\_UNBLOCK\\_CERTIFIED\\_TRANS](#); SQLSTATE: [HY000](#)  
  
Message: Error when trying to unblock non certified or consistent transactions. Check for consistency errors when restarting the service  
  
[ER\\_GRP\\_RPL\\_UNBLOCK\\_CERTIFIED\\_TRANS](#) was added in 8.0.11.
  - Error number: [MY-011632](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_WORKING\\_AS\\_SECONDARY](#); SQLSTATE: [HY000](#)  
  
Message: This server is working as secondary member with primary member address %s:%u.  
  
[ER\\_GRP\\_RPL\\_SERVER\\_WORKING\\_AS\\_SECONDARY](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-011633](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_START\\_WITH\\_INVALID\\_SERVER\\_ID](#); SQLSTATE: [HY000](#)  
  
Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with server\_id=0. Please, restart the server with server\_id larger than 0.  
  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_START\\_WITH\\_INVALID\\_SERVER\\_ID](#) was added in 8.0.11.
  - Error number: [MY-011634](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBERS\\_MUST\\_BE\\_EMPTY](#); SQLSTATE: [HY000](#)  
  
Message: group\_replication\_force\_members must be empty on group start. Current value: '%s'  
  
[ER\\_GRP\\_RPL\\_FORCE\\_MEMBERS\\_MUST\\_BE\\_EMPTY](#) was added in 8.0.11.
  - Error number: [MY-011635](#); Symbol: [ER\\_GRP\\_RPL\\_PLUGIN\\_STRUCT\\_INIT\\_NOT\\_POSSIBLE\\_ON\\_SERVER\\_START](#); SQLSTATE: [HY000](#)

---

Message: It was not possible to guarantee the initialization of plugin structures on server start

[ER\\_GRP\\_RPL\\_PLUGIN\\_STRUCT\\_INIT\\_NOT\\_POSSIBLE\\_ON\\_SERVER\\_START](#) was added in 8.0.11.

- Error number: [MY-011636](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_ENABLE\\_SUPER\\_READ\\_ONLY\\_MODE](#); SQLSTATE: [HY000](#)

Message: Could not enable the server read only mode and guarantee a safe recovery execution

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_ENABLE\\_SUPER\\_READ\\_ONLY\\_MODE](#) was added in 8.0.11.

- Error number: [MY-011637](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INIT\\_COMMUNICATION\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Error on group communication engine initialization

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INIT\\_COMMUNICATION\\_ENGINE](#) was added in 8.0.11.

- Error number: [MY-011638](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_START\\_ON\\_SECONDARY\\_WITH\\_ASYNC\\_CHANNELS](#); SQLSTATE: [HY000](#)

Message: Can't start group replication on secondary member with single-primary mode while asynchronous replication channels are running.

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_START\\_ON\\_SECONDARY\\_WITH\\_ASYNC\\_CHANNELS](#) was added in 8.0.11.

- Error number: [MY-011639](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_START\\_COMMUNICATION\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Error on group communication engine start

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_START\\_COMMUNICATION\\_ENGINE](#) was added in 8.0.11.

- Error number: [MY-011640](#); Symbol: [ER\\_GRP\\_RPL\\_TIMEOUT\\_ON\\_VIEW\\_AFTER\\_JOINING\\_GRP](#); SQLSTATE: [HY000](#)

Message: Timeout on wait for view after joining group

[ER\\_GRP\\_RPL\\_TIMEOUT\\_ON\\_VIEW\\_AFTER\\_JOINING\\_GRP](#) was added in 8.0.11.

- Error number: [MY-011641](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_CALL\\_GRP\\_COMMUNICATION\\_INTERFACE](#); SQLSTATE: [HY000](#)

Message: Error calling group communication interfaces

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_CALL\\_GRP\\_COMMUNICATION\\_INTERFACE](#) was added in 8.0.11.

- Error number: [MY-011642](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_SERVER\\_UUID\\_IS\\_INCOMPATIBLE\\_WITH\\_GRP](#); SQLSTATE: [HY000](#)

Message: Member server\_uuid is incompatible with the group. Server\_uuid %s matches group\_replication\_group\_name %s.

[ER\\_GRP\\_RPL\\_MEMBER\\_SERVER\\_UUID\\_IS\\_INCOMPATIBLE\\_WITH\\_GRP](#) was added in 8.0.11.

- 
- Error number: [MY-011643](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_CONF\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Member configuration: member\_id: %lu; member\_uuid: "%s"; single-primary mode: "%s"; group\_replication\_auto\_increment\_increment: %lu; group\_replication\_view\_change\_uuid: "%s";  
  
[ER\\_GRP\\_RPL\\_MEMBER\\_CONF\\_INFO](#) was added in 8.0.11.
  - Error number: [MY-011644](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_CONFIRM\\_IF\\_SERVER\\_LEFT\\_GRP](#); SQLSTATE: [HY000](#)  
  
Message: Unable to confirm whether the server has left the group or not. Check performance\_schema.replication\_group\_members to check group membership information.  
  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_CONFIRM\\_IF\\_SERVER\\_LEFT\\_GRP](#) was added in 8.0.11.
  - Error number: [MY-011645](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_IS\\_ALREADY\\_LEAVING](#); SQLSTATE: [HY000](#)  
  
Message: Skipping leave operation: concurrent attempt to leave the group is on-going.  
  
[ER\\_GRP\\_RPL\\_SERVER\\_IS\\_ALREADY\\_LEAVING](#) was added in 8.0.11.
  - Error number: [MY-011646](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_ALREADY\\_LEFT](#); SQLSTATE: [HY000](#)  
  
Message: Skipping leave operation: member already left the group.  
  
[ER\\_GRP\\_RPL\\_SERVER\\_ALREADY\\_LEFT](#) was added in 8.0.11.
  - Error number: [MY-011647](#); Symbol: [ER\\_GRP\\_RPL\\_WAITING\\_FOR\\_VIEW\\_UPDATE](#); SQLSTATE: [HY000](#)  
  
Message: Going to wait for view modification  
  
[ER\\_GRP\\_RPL\\_WAITING\\_FOR\\_VIEW\\_UPDATE](#) was added in 8.0.11.
  - Error number: [MY-011648](#); Symbol: [ER\\_GRP\\_RPL\\_TIMEOUT\\_RECEIVING\\_VIEW\\_CHANGE\\_ON\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
  
Message: While leaving the group due to a stop, shutdown or failure there was a timeout receiving a view change. This can lead to a possible inconsistent state. Check the log for more details  
  
[ER\\_GRP\\_RPL\\_TIMEOUT\\_RECEIVING\\_VIEW\\_CHANGE\\_ON\\_SHUTDOWN](#) was added in 8.0.11.
  - Error number: [MY-011649](#); Symbol: [ER\\_GRP\\_RPL\\_REQUESTING\\_NON\\_MEMBER\\_SERVER\\_TO\\_LEAVE](#); SQLSTATE: [HY000](#)  
  
Message: Requesting to leave the group despite of not being a member  
  
[ER\\_GRP\\_RPL\\_REQUESTING\\_NON\\_MEMBER\\_SERVER\\_TO\\_LEAVE](#) was added in 8.0.11.
  - Error number: [MY-011650](#); Symbol: [ER\\_GRP\\_RPL\\_IS\\_STOPPING](#); SQLSTATE: [HY000](#)  
  
Message: Plugin 'group\_replication' is stopping.  
  
[ER\\_GRP\\_RPL\\_IS\\_STOPPING](#) was added in 8.0.11.
-

- 
- Error number: [MY-011651](#); Symbol: [ER\\_GRP\\_RPL\\_IS\\_STOPPED](#); SQLSTATE: [HY000](#)  
Message: Plugin 'group\_replication' has been stopped.  
[ER\\_GRP\\_RPL\\_IS\\_STOPPED](#) was added in 8.0.11.
  - Error number: [MY-011652](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_ENABLE\\_READ\\_ONLY\\_MODE\\_ON\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: On plugin shutdown it was not possible to enable the server read only mode. Local transactions will be accepted and committed.  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_ENABLE\\_READ\\_ONLY\\_MODE\\_ON\\_SHUTDOWN](#) was added in 8.0.11.
  - Error number: [MY-011653](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_MODULE\\_TERMINATION\\_TIMED\\_OUT\\_ON\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: On shutdown there was a timeout on the Group Replication recovery module termination. Check the log for more details  
[ER\\_GRP\\_RPL\\_RECOVERY\\_MODULE\\_TERMINATION\\_TIMED\\_OUT\\_ON\\_SHUTDOWN](#) was added in 8.0.11.
  - Error number: [MY-011654](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_TERMINATION\\_TIMED\\_OUT\\_ON\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: On shutdown there was a timeout on the Group Replication applier termination.  
[ER\\_GRP\\_RPL\\_APPLIER\\_TERMINATION\\_TIMED\\_OUT\\_ON\\_SHUTDOWN](#) was added in 8.0.11.
  - Error number: [MY-011655](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_SHUTDOWN\\_REGISTRY\\_MODULE](#); SQLSTATE: [HY000](#)  
Message: Unexpected failure while shutting down registry module!  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_SHUTDOWN\\_REGISTRY\\_MODULE](#) was added in 8.0.11.
  - Error number: [MY-011656](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INIT\\_HANDLER](#); SQLSTATE: [HY000](#)  
Message: Failure during Group Replication handler initialization  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INIT\\_HANDLER](#) was added in 8.0.11.
  - Error number: [MY-011657](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_REGISTER\\_SERVER\\_STATE\\_OBSERVER](#); SQLSTATE: [HY000](#)  
Message: Failure when registering the server state observers  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_REGISTER\\_SERVER\\_STATE\\_OBSERVER](#) was added in 8.0.11.
  - Error number: [MY-011658](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_REGISTER\\_TRANS\\_STATE\\_OBSERVER](#); SQLSTATE: [HY000](#)  
Message: Failure when registering the transactions state observers  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_REGISTER\\_TRANS\\_STATE\\_OBSERVER](#) was added in 8.0.11.
  - Error number: [MY-011659](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_REGISTER\\_BINLOG\\_STATE\\_OBSERVER](#); SQLSTATE: [HY000](#)

---

Message: Failure when registering the binlog state observers

`ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011660`; Symbol: `ER_GRP_RPL_FAILED_TO_START_ON_BOOT`; SQLSTATE: `HY000`

Message: Unable to start Group Replication on boot

`ER_GRP_RPL_FAILED_TO_START_ON_BOOT` was added in 8.0.11.

- Error number: `MY-011661`; Symbol: `ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL`; SQLSTATE: `HY000`

Message: Failure when stopping Group Replication on plugin uninstall

`ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL` was added in 8.0.11.

- Error number: `MY-011662`; Symbol: `ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER`; SQLSTATE: `HY000`

Message: Failure when unregistering the server state observers

`ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011663`; Symbol: `ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER`; SQLSTATE: `HY000`

Message: Failure when unregistering the transactions state observers

`ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011664`; Symbol: `ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER`; SQLSTATE: `HY000`

Message: Failure when unregistering the binlog state observers

`ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011665`; Symbol: `ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED`; SQLSTATE: `HY000`

Message: All Group Replication server observers have been successfully unregistered

`ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED` was added in 8.0.11.

- Error number: `MY-011666`; Symbol: `ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME`; SQLSTATE: `HY000`

Message: Unable to parse the group\_replication\_group\_name.

`ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME` was added in 8.0.11.

- Error number: `MY-011667`; Symbol: `ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP`; SQLSTATE: `HY000`

Message: Unable to parse the group\_replication\_group\_name.

`ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP` was added in 8.0.11.

- 
- Error number: [MY-011668](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_NOT\\_STARTED\\_DUE\\_TO\\_RUNNING\\_PREV\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
  
Message: Cannot start the Group Replication applier as a previous shutdown is still running: The thread will stop once its task is complete.  
  
[ER\\_GRP\\_RPL\\_APPLIER\\_NOT\\_STARTED\\_DUE\\_TO\\_RUNNING\\_PREV\\_SHUTDOWN](#) was added in 8.0.11.
  - Error number: [MY-011669](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INIT\\_APPLIER\\_MODULE](#); SQLSTATE: [HY000](#)  
  
Message: Unable to initialize the Group Replication applier module.  
  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INIT\\_APPLIER\\_MODULE](#) was added in 8.0.11.
  - Error number: [MY-011670](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_INITIALIZED](#); SQLSTATE: [HY000](#)  
  
Message: Group Replication applier module successfully initialized!  
  
[ER\\_GRP\\_RPL\\_APPLIER\\_INITIALIZED](#) was added in 8.0.11.
  - Error number: [MY-011671](#); Symbol: [ER\\_GRP\\_RPL\\_COMMUNICATION\\_SSL\\_CONF\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Group communication SSL configuration: group\_replication\_ssl\_mode: "%s"; server\_key\_file: "%s"; server\_cert\_file: "%s"; client\_key\_file: "%s"; client\_cert\_file: "%s"; ca\_file: "%s"; ca\_path: "%s"; cipher: "%s"; tls\_version: "%s"; tls\_ciphersuites: "%s"; crl\_file: "%s"; crl\_path: "%s"; ssl\_fips\_mode: "%s"  
  
[ER\\_GRP\\_RPL\\_COMMUNICATION\\_SSL\\_CONF\\_INFO](#) was added in 8.0.11.
  - Error number: [MY-011672](#); Symbol: [ER\\_GRP\\_RPL\\_ABORTS\\_AS\\_SSL\\_NOT\\_SUPPORTED\\_BY\\_MYSQLD](#); SQLSTATE: [HY000](#)  
  
Message: MySQL server does not have SSL support and group\_replication\_ssl\_mode is "%s", START GROUP\_REPLICATION will abort  
  
[ER\\_GRP\\_RPL\\_ABORTS\\_AS\\_SSL\\_NOT\\_SUPPORTED\\_BY\\_MYSQLD](#) was added in 8.0.11.
  - Error number: [MY-011673](#); Symbol: [ER\\_GRP\\_RPL\\_SSL\\_DISABLED](#); SQLSTATE: [HY000](#)  
  
Message: Group communication SSL configuration: group\_replication\_ssl\_mode: "%s"  
  
[ER\\_GRP\\_RPL\\_SSL\\_DISABLED](#) was added in 8.0.11.
  - Error number: [MY-011674](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_INIT\\_COMMUNICATION\\_ENGINE](#); SQLSTATE: [HY000](#)  
  
Message: Unable to initialize the group communication engine  
  
[ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_INIT\\_COMMUNICATION\\_ENGINE](#) was added in 8.0.11.
  - Error number: [MY-011675](#); Symbol: [ER\\_GRP\\_RPL\\_BINLOG\\_DISABLED](#); SQLSTATE: [HY000](#)  
  
Message: Binlog must be enabled for Group Replication  
  
[ER\\_GRP\\_RPL\\_BINLOG\\_DISABLED](#) was added in 8.0.11.
  - Error number: [MY-011676](#); Symbol: [ER\\_GRP\\_RPL\\_GTID\\_MODE\\_OFF](#); SQLSTATE: [HY000](#)



---

Message: Gtid mode should be ON for Group Replication

[ER\\_GRP\\_RPL\\_GTID\\_MODE\\_OFF](#) was added in 8.0.11.

- Error number: [MY-011677](#); Symbol: [ER\\_GRP\\_RPL\\_LOG\\_SLAVE\\_UPDATES\\_NOT\\_SET](#); SQLSTATE: [HY000](#)

Message: LOG\_SLAVE\_UPDATES should be ON for Group Replication

[ER\\_GRP\\_RPL\\_LOG\\_SLAVE\\_UPDATES\\_NOT\\_SET](#) was added in 8.0.11, removed after 8.0.25.

- Error number: [MY-011677](#); Symbol: [ER\\_GRP\\_RPL\\_LOG\\_REPLICA\\_UPDATES\\_NOT\\_SET](#); SQLSTATE: [HY000](#)

Message: LOG\_REPLICA\_UPDATES should be ON for Group Replication

[ER\\_GRP\\_RPL\\_LOG\\_REPLICA\\_UPDATES\\_NOT\\_SET](#) was added in 8.0.26.

- Error number: [MY-011678](#); Symbol: [ER\\_GRP\\_RPL\\_INVALID\\_TRANS\\_WRITE\\_SET\\_EXTRACTION\\_VALUE](#); SQLSTATE: [HY000](#)

Message: Extraction of transaction write sets requires an hash algorithm configuration. Please, double check that the parameter transaction-write-set-extraction is set to a valid algorithm.

[ER\\_GRP\\_RPL\\_INVALID\\_TRANS\\_WRITE\\_SET\\_EXTRACTION\\_VALUE](#) was added in 8.0.11.

- Error number: [MY-011679](#); Symbol: [ER\\_GRP\\_RPL\\_RELAY\\_LOG\\_INFO\\_REPO\\_MUST\\_BE\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Relay log info repository must be set to TABLE

[ER\\_GRP\\_RPL\\_RELAY\\_LOG\\_INFO\\_REPO\\_MUST\\_BE\\_TABLE](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-011679](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_METADATA\\_REPO\\_MUST\\_BE\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Applier metadata repository must be set to TABLE

[ER\\_GRP\\_RPL\\_APPLIER\\_METADATA\\_REPO\\_MUST\\_BE\\_TABLE](#) was added in 8.0.33.

- Error number: [MY-011680](#); Symbol: [ER\\_GRP\\_RPL\\_MASTER\\_INFO\\_REPO\\_MUST\\_BE\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Master info repository must be set to TABLE.

[ER\\_GRP\\_RPL\\_MASTER\\_INFO\\_REPO\\_MUST\\_BE\\_TABLE](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-011680](#); Symbol: [ER\\_GRP\\_RPL\\_CONNECTION\\_METADATA\\_REPO\\_MUST\\_BE\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Connection metadata repository must be set to TABLE.

[ER\\_GRP\\_RPL\\_CONNECTION\\_METADATA\\_REPO\\_MUST\\_BE\\_TABLE](#) was added in 8.0.33.

- 
- Error number: [MY-011681](#); Symbol: [ER\\_GRP\\_RPL\\_INCORRECT\\_TYPE\\_SET\\_FOR\\_PARALLEL\\_APPLIER](#); SQLSTATE: [HY000](#)  
  
Message: In order to use parallel applier on Group Replication, parameter replica-parallel-type must be set to 'LOGICAL\_CLOCK'.  
  
[ER\\_GRP\\_RPL\\_INCORRECT\\_TYPE\\_SET\\_FOR\\_PARALLEL\\_APPLIER](#) was added in 8.0.11.
  - Error number: [MY-011682](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_PRESERVE\\_COMMIT\\_ORDER\\_NOT\\_SET](#); SQLSTATE: [HY000](#)  
  
Message: Group Replication requires slave-preserve-commit-order to be set to ON when using more than 1 applier threads.  
  
[ER\\_GRP\\_RPL\\_SLAVE\\_PRESERVE\\_COMMIT\\_ORDER\\_NOT\\_SET](#) was added in 8.0.11, removed after 8.0.25.
  - Error number: [MY-011682](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_PRESERVE\\_COMMIT\\_ORDER\\_NOT\\_SET](#); SQLSTATE: [HY000](#)  
  
Message: Group Replication requires replica-preserve-commit-order to be set to ON when using more than 1 applier threads.  
  
[ER\\_GRP\\_RPL\\_REPLICA\\_PRESERVE\\_COMMIT\\_ORDER\\_NOT\\_SET](#) was added in 8.0.26.
  - Error number: [MY-011683](#); Symbol: [ER\\_GRP\\_RPL\\_SINGLE\\_PRIM\\_MODE\\_NOT\\_ALLOWED\\_WITH\\_UPDATE\\_EVERYWHERE](#); SQLSTATE: [HY000](#)  
  
Message: It is not allowed to run single primary mode with 'group\_replication\_enforce\_update\_everywhere\_checks' enabled.  
  
[ER\\_GRP\\_RPL\\_SINGLE\\_PRIM\\_MODE\\_NOT\\_ALLOWED\\_WITH\\_UPDATE\\_EVERYWHERE](#) was added in 8.0.11.
  - Error number: [MY-011684](#); Symbol: [ER\\_GRP\\_RPL\\_MODULE\\_TERMINATE\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: error\_message: %s  
  
[ER\\_GRP\\_RPL\\_MODULE\\_TERMINATE\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011685](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_NAME\\_OPTION\\_MANDATORY](#); SQLSTATE: [HY000](#)  
  
Message: The group\_replication\_group\_name option is mandatory  
  
[ER\\_GRP\\_RPL\\_GRP\\_NAME\\_OPTION\\_MANDATORY](#) was added in 8.0.11.
  - Error number: [MY-011686](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_NAME\\_IS\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
  
Message: The group\_replication\_group\_name '%s' is not a valid UUID, its length is too big  
  
[ER\\_GRP\\_RPL\\_GRP\\_NAME\\_IS\\_TOO\\_LONG](#) was added in 8.0.11.
  - Error number: [MY-011687](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_NAME\\_IS\\_NOT\\_VALID\\_UUID](#); SQLSTATE: [HY000](#)  
  
Message: The group\_replication\_group\_name '%s' is not a valid UUID

---

`ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID` was added in 8.0.11.

- Error number: `MY-011688`; Symbol: `ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA`; SQLSTATE: `HY000`

Message: group\_replication\_flow\_control\_min\_quota cannot be larger than group\_replication\_flow\_control\_max\_quota

`ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA` was added in 8.0.11.

- Error number: `MY-011689`; Symbol: `ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA`; SQLSTATE: `HY000`

Message: group\_replication\_flow\_control\_min\_recovery\_quota cannot be larger than group\_replication\_flow\_control\_max\_quota

`ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA` was added in 8.0.11.

- Error number: `MY-011690`; Symbol: `ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN_QUOTAS`; SQLSTATE: `HY000`

Message: group\_replication\_flow\_control\_max\_quota cannot be smaller than group\_replication\_flow\_control\_min\_quota or group\_replication\_flow\_control\_min\_recovery\_quota

`ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN_QUOTAS` was added in 8.0.11.

- Error number: `MY-011691`; Symbol: `ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING`; SQLSTATE: `HY000`

Message: The given value for recovery ssl option 'group\_replication\_%s' is invalid as its length is beyond the limit

`ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING` was added in 8.0.11.

- Error number: `MY-011692`; Symbol: `ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBERS_SET`; SQLSTATE: `HY000`

Message: There is one group\_replication\_force\_members operation already ongoing

`ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBERS_SET` was added in 8.0.11, removed after 8.0.30.

- Error number: `MY-011693`; Symbol: `ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: group\_replication\_force\_members can only be updated when Group Replication is running and a majority of the members are unreachable

`ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED` was added in 8.0.11, removed after 8.0.30.

- 
- Error number: [MY-011694](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_COMMUNICATION\\_INIT\\_WITH\\_CONF](#); SQLSTATE: [HY000](#)

Message: Initialized group communication with configuration: group\_replication\_group\_name: '%s'; group\_replication\_local\_address: '%s'; group\_replication\_group\_seeds: '%s'; group\_replication\_bootstrap\_group: '%s'; group\_replication\_poll\_spin\_loops: %lu; group\_replication\_compression\_threshold: %lu; group\_replication\_ip\_allowlist: '%s'; group\_replication\_communication\_debug\_options: '%s'; group\_replication\_member\_expel\_timeout: '%lu'; group\_replication\_communication\_max\_message\_size: %lu; group\_replication\_message\_cache\_size: '%luu'; group\_replication\_communication\_stack: '%lu'

[ER\\_GRP\\_RPL\\_GRP\\_COMMUNICATION\\_INIT\\_WITH\\_CONF](#) was added in 8.0.11.

- Error number: [MY-011695](#); Symbol: [ER\\_GRP\\_RPL\\_UNKNOWN\\_GRP\\_RPL\\_APPLIER\\_PIPELINE\\_REQUESTED](#); SQLSTATE: [HY000](#)

Message: Unknown group replication applier pipeline requested

[ER\\_GRP\\_RPL\\_UNKNOWN\\_GRP\\_RPL\\_APPLIER\\_PIPELINE\\_REQUESTED](#) was added in 8.0.11.

- Error number: [MY-011696](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_BOOTSTRAP\\_EVENT\\_HANDLING\\_INFRASTRUCTURE](#); SQLSTATE: [HY000](#)

Message: Unable to bootstrap group replication event handling infrastructure. Unknown handler type: %d

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_BOOTSTRAP\\_EVENT\\_HANDLING\\_INFRASTRUCTURE](#) was added in 8.0.11.

- Error number: [MY-011697](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_HANDLER\\_NOT\\_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: One of the group replication applier handlers is null due to an initialization error

[ER\\_GRP\\_RPL\\_APPLIER\\_HANDLER\\_NOT\\_INITIALIZED](#) was added in 8.0.11.

- Error number: [MY-011698](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_HANDLER\\_IS\\_IN\\_USE](#); SQLSTATE: [HY000](#)

Message: A group replication applier handler, marked as unique, is already in use.

[ER\\_GRP\\_RPL\\_APPLIER\\_HANDLER\\_IS\\_IN\\_USE](#) was added in 8.0.11.

- Error number: [MY-011699](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_HANDLER\\_ROLE\\_IS\\_IN\\_USE](#); SQLSTATE: [HY000](#)

Message: A group replication applier handler role, that was marked as unique, is already in use.

[ER\\_GRP\\_RPL\\_APPLIER\\_HANDLER\\_ROLE\\_IS\\_IN\\_USE](#) was added in 8.0.11.

- Error number: [MY-011700](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INIT\\_APPLIER\\_HANDLER](#); SQLSTATE: [HY000](#)

Message: Error on group replication applier handler initialization

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INIT\\_APPLIER\\_HANDLER](#) was added in 8.0.11.

- Error number: [MY-011701](#); Symbol: [ER\\_GRP\\_RPL\\_SQL\\_SERVICE\\_FAILED\\_TO\\_INIT\\_SESSION\\_THREAD](#); SQLSTATE: [HY000](#)

---

Message: Error when initializing a session thread for internal server connection.

`ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREAD` was added in 8.0.11.

- Error number: `MY-011702`; Symbol: `ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. The internal server communication session is not initialized

`ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED` was added in 8.0.11.

- Error number: `MY-011703`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. The internal server session was killed or server is shutting down.

`ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED` was added in 8.0.11.

- Error number: `MY-011704`; Symbol: `ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. Got internal SQL error: %s(%d)

`ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY` was added in 8.0.11.

- Error number: `MY-011705`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. Internal failure.

`ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE` was added in 8.0.11.

- Error number: `MY-011706`; Symbol: `ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE`; SQLSTATE: `HY000`

Message: Error, maximum number of retries exceeded when waiting for the internal server session state to be operating

`ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE` was added in 8.0.11.

- Error number: `MY-011707`; Symbol: `ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CTX`; SQLSTATE: `HY000`

Message: Error when trying to fetch security context when contacting the server for internal plugin requests.

`ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CTX` was added in 8.0.11.

- Error number: `MY-011708`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER`; SQLSTATE: `HY000`

Message: There was an error when trying to access the server with user: %s. Make sure the user is present in the server and that the MySQL upgrade procedure was run correctly.

`ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER` was added in 8.0.11.

- 
- Error number: `MY-011709`; Symbol: `ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER`; SQLSTATE: `HY000`

Message: Failed to establish an internal server connection to execute plugin operations since the server does not have available connections, please increase @@GLOBAL.MAX\_CONNECTIONS. Server error: %i.

`ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER` was added in 8.0.11.

- Error number: `MY-011710`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN`; SQLSTATE: `HY000`

Message: Failed to establish an internal server connection to execute plugin operations. Server error: %i. Server error message: %s

`ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN` was added in 8.0.11.

- Error number: `MY-011711`; Symbol: `ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER`; SQLSTATE: `HY000`

Message: This member could not reach a majority of the members for more than %ld seconds. The member will now leave the group as instructed by the group\_replication\_unreachable\_majority\_timeout option.

`ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER` was added in 8.0.11.

- Error number: `MY-011712`; Symbol: `ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS`; SQLSTATE: `HY000`

Message: The server was automatically set into read only mode after an error was detected.

`ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS` was added in 8.0.11.

- Error number: `MY-011713`; Symbol: `ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION`; SQLSTATE: `HY000`

Message: Unable to log notification to table (errno: %lu) (res: %d)! Message: %s

`ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION` was added in 8.0.11.

- Error number: `MY-011714`; Symbol: `ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failure in group communication engine '%s' initialization

`ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED` was added in 8.0.11.

- Error number: `MY-011715`; Symbol: `ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FAILED`; SQLSTATE: `HY000`

Message: Unable to set the group communication engine logger

`ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FAILED` was added in 8.0.11.

- Error number: `MY-011716`; Symbol: `ER_GRP_RPL_DEBUG_OPTIONS`; SQLSTATE: `HY000`

Message: Current debug options are: '%s'.

`ER_GRP_RPL_DEBUG_OPTIONS` was added in 8.0.11.

- 
- Error number: [MY-011717](#); Symbol: [ER\\_GRP\\_RPL\\_INVALID\\_DEBUG\\_OPTIONS](#); SQLSTATE: [HY000](#)  
Message: Some debug options in '%s' are not valid.  
[ER\\_GRP\\_RPL\\_INVALID\\_DEBUG\\_OPTIONS](#) was added in 8.0.11.
  - Error number: [MY-011718](#); Symbol: [ER\\_GRP\\_RPL\\_EXIT\\_GRP\\_GCS\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error calling group communication interfaces while trying to leave the group  
[ER\\_GRP\\_RPL\\_EXIT\\_GRP\\_GCS\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011719](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_MEMBER\\_OFFLINE](#); SQLSTATE: [HY000](#)  
Message: Member is not ONLINE, it is not possible to force a new group membership  
[ER\\_GRP\\_RPL\\_GRP\\_MEMBER\\_OFFLINE](#) was added in 8.0.11.
  - Error number: [MY-011720](#); Symbol: [ER\\_GRP\\_RPL\\_GCS\\_INTERFACE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error calling group communication interfaces  
[ER\\_GRP\\_RPL\\_GCS\\_INTERFACE\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011721](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_SET\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error setting group\_replication\_force\_members value '%s' on group communication interfaces  
[ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_SET\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011722](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_SET](#); SQLSTATE: [HY000](#)  
Message: The group\_replication\_force\_members value '%s' was set in the group communication interfaces  
[ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_SET](#) was added in 8.0.11.
  - Error number: [MY-011723](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_TIME\\_OUT](#); SQLSTATE: [HY000](#)  
Message: Timeout on wait for view after setting group\_replication\_force\_members value '%s' into group communication interfaces  
[ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_TIME\\_OUT](#) was added in 8.0.11.
  - Error number: [MY-011724](#); Symbol: [ER\\_GRP\\_RPL\\_BROADCAST\\_COMMIT\\_MSSG\\_TOO\\_BIG](#); SQLSTATE: [HY000](#)  
Message: Broadcast of committed transactions message failed. Message is too big.  
[ER\\_GRP\\_RPL\\_BROADCAST\\_COMMIT\\_MSSG\\_TOO\\_BIG](#) was added in 8.0.11.
  - Error number: [MY-011725](#); Symbol: [ER\\_GRP\\_RPL\\_SEND\\_STATS\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error while sending stats message  
[ER\\_GRP\\_RPL\\_SEND\\_STATS\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011726](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_STATS\\_INFO](#); SQLSTATE: [HY000](#)

---

Message: Flow control - update member stats: %s stats certifier\_queue %d, applier\_queue %d certified %ld (%ld), applied %ld (%ld), local %ld (%ld), quota %ld (%ld) mode=%d

[ER\\_GRP\\_RPL\\_MEMBER\\_STATS\\_INFO](#) was added in 8.0.11.

- Error number: [MY-011727](#); Symbol: [ER\\_GRP\\_RPL\\_FLOW\\_CONTROL\\_STATS](#); SQLSTATE: [HY000](#)

Message: Flow control: throttling to %ld commits per %ld sec, with %d writing and %d non-recovering members, min capacity %lld, lim throttle %lld

[ER\\_GRP\\_RPL\\_FLOW\\_CONTROL\\_STATS](#) was added in 8.0.11.

- Error number: [MY-011728](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_CONVERT\\_PACKET\\_TO\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to convert a packet into an event on the applier. Error: %s

[ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_CONVERT\\_PACKET\\_TO\\_EVENT](#) was added in 8.0.11.

- Error number: [MY-011729](#); Symbol: [ER\\_GRP\\_RPL\\_PIPELINE\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create group replication pipeline cache.

[ER\\_GRP\\_RPL\\_PIPELINE\\_CREATE\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011730](#); Symbol: [ER\\_GRP\\_RPL\\_PIPELINE\\_REINIT\\_FAILED\\_WRITE](#); SQLSTATE: [HY000](#)

Message: Failed to reinit group replication pipeline cache for write.

[ER\\_GRP\\_RPL\\_PIPELINE\\_REINIT\\_FAILED\\_WRITE](#) was added in 8.0.11.

- Error number: [MY-011731](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_CONVERT\\_EVENT\\_TO\\_PACKET](#); SQLSTATE: [HY000](#)

Message: Unable to convert the event into a packet on the applier. Error: %s

[ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_CONVERT\\_EVENT\\_TO\\_PACKET](#) was added in 8.0.11.

- Error number: [MY-011732](#); Symbol: [ER\\_GRP\\_RPL\\_PIPELINE\\_FLUSH\\_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to flush group replication pipeline cache.

[ER\\_GRP\\_RPL\\_PIPELINE\\_FLUSH\\_FAIL](#) was added in 8.0.11.

- Error number: [MY-011733](#); Symbol: [ER\\_GRP\\_RPL\\_PIPELINE\\_REINIT\\_FAILED\\_READ](#); SQLSTATE: [HY000](#)

Message: Failed to reinit group replication pipeline cache for read.

[ER\\_GRP\\_RPL\\_PIPELINE\\_REINIT\\_FAILED\\_READ](#) was added in 8.0.11.

- Error number: [MY-011734](#); Symbol: [ER\\_GRP\\_RPL\\_STOP\\_REP\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Error stopping all replication channels while server was leaving the group. Got error: %d. Please check the error log for more details.

[ER\\_GRP\\_RPL\\_STOP\\_REP\\_CHANNEL](#) was added in 8.0.11, removed after 8.0.17.



- 
- Error number: [MY-011735](#); Symbol: [ER\\_GRP\\_RPL\\_GCS\\_GR\\_ERROR\\_MSG](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_GRP\\_RPL\\_GCS\\_GR\\_ERROR\\_MSG](#) was added in 8.0.11.
  - Error number: [MY-011736](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THREAD\\_UNBLOCKED](#); SQLSTATE: [HY000](#)  
Message: The slave IO thread of channel '%s' is unblocked as the member is declared ONLINE now.  
[ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THREAD\\_UNBLOCKED](#) was added in 8.0.11, removed after 8.0.32.
  - Error number: [MY-011736](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THREAD\\_UNBLOCKED](#); SQLSTATE: [HY000](#)  
Message: The replica IO thread of channel '%s' is unblocked as the member is declared ONLINE now.  
[ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THREAD\\_UNBLOCKED](#) was added in 8.0.33.
  - Error number: [MY-011737](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THREAD\\_ERROR\\_OUT](#); SQLSTATE: [HY000](#)  
Message: The slave IO thread of channel '%s' will error out as the member failed to come ONLINE.  
[ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THREAD\\_ERROR\\_OUT](#) was added in 8.0.11, removed after 8.0.32.
  - Error number: [MY-011737](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THREAD\\_ERROR\\_OUT](#); SQLSTATE: [HY000](#)  
Message: The replica IO thread of channel '%s' will error out as the member failed to come ONLINE.  
[ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THREAD\\_ERROR\\_OUT](#) was added in 8.0.33.
  - Error number: [MY-011738](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_APPLIER\\_THREAD\\_UNBLOCKED](#); SQLSTATE: [HY000](#)  
Message: The slave applier thread of channel '%s' is unblocked as the member is declared ONLINE now.  
[ER\\_GRP\\_RPL\\_SLAVE\\_APPLIER\\_THREAD\\_UNBLOCKED](#) was added in 8.0.11, removed after 8.0.32.
  - Error number: [MY-011738](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_APPLIER\\_THREAD\\_UNBLOCKED](#); SQLSTATE: [HY000](#)  
Message: The replica applier thread of channel '%s' is unblocked as the member is declared ONLINE now.  
[ER\\_GRP\\_RPL\\_REPLICA\\_APPLIER\\_THREAD\\_UNBLOCKED](#) was added in 8.0.33.
  - Error number: [MY-011739](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_APPLIER\\_THREAD\\_ERROR\\_OUT](#); SQLSTATE: [HY000](#)  
Message: The slave applier thread of channel '%s' will error out as the member failed to come ONLINE.  
[ER\\_GRP\\_RPL\\_SLAVE\\_APPLIER\\_THREAD\\_ERROR\\_OUT](#) was added in 8.0.11, removed after 8.0.32.
  - Error number: [MY-011739](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_APPLIER\\_THREAD\\_ERROR\\_OUT](#); SQLSTATE: [HY000](#)

---

Message: The replica applier thread of channel '%s' will error out as the member failed to come ONLINE.

[ER\\_GRP\\_RPL\\_REPLICA\\_APPLIER\\_THREAD\\_ERROR\\_OUT](#) was added in 8.0.33.

- Error number: [MY-011740](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_CREATE\\_OR\\_GET\\_CONNECTION](#); SQLSTATE: [HY000](#)

Message: LDAP authentication initialize: failed to create/ get connection from the pool.

[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_CREATE\\_OR\\_GET\\_CONNECTION](#) was added in 8.0.11.

- Error number: [MY-011741](#); Symbol: [ER\\_LDAP\\_AUTH\\_DEINIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: LDAP authentication de\_initialize Failed

[ER\\_LDAP\\_AUTH\\_DEINIT\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011742](#); Symbol: [ER\\_LDAP\\_AUTH\\_SKIPPING\\_USER\\_GROUP\\_SEARCH](#); SQLSTATE: [HY000](#)

Message: Skipping group search, No group attribute mentioned

[ER\\_LDAP\\_AUTH\\_SKIPPING\\_USER\\_GROUP\\_SEARCH](#) was added in 8.0.11.

- Error number: [MY-011743](#); Symbol: [ER\\_LDAP\\_AUTH\\_POOL\\_DISABLE\\_MAX\\_SIZE\\_ZERO](#); SQLSTATE: [HY000](#)

Message: Pool max size is 0, connection pool is disabled

[ER\\_LDAP\\_AUTH\\_POOL\\_DISABLE\\_MAX\\_SIZE\\_ZERO](#) was added in 8.0.11.

- Error number: [MY-011744](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_CREATE\\_LDAP\\_OBJECT\\_CREATOR](#); SQLSTATE: [HY000](#)

Message: Connection pool initialization, failed to create LDAP object creator

[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_CREATE\\_LDAP\\_OBJECT\\_CREATOR](#) was added in 8.0.11.

- Error number: [MY-011745](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_CREATE\\_LDAP\\_OBJECT](#); SQLSTATE: [HY000](#)

Message: Connection pool initialization, failed to create LDAP object

[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_CREATE\\_LDAP\\_OBJECT](#) was added in 8.0.11.

- Error number: [MY-011746](#); Symbol: [ER\\_LDAP\\_AUTH\\_TLS\\_CONF](#); SQLSTATE: [HY000](#)

Message: LDAP TLS configuration

[ER\\_LDAP\\_AUTH\\_TLS\\_CONF](#) was added in 8.0.11.

- Error number: [MY-011747](#); Symbol: [ER\\_LDAP\\_AUTH\\_TLS\\_CONNECTION](#); SQLSTATE: [HY000](#)

Message: LDAP TLS connection

[ER\\_LDAP\\_AUTH\\_TLS\\_CONNECTION](#) was added in 8.0.11.

- Error number: [MY-011748](#); Symbol: [ER\\_LDAP\\_AUTH\\_CONN\\_POOL\\_NOT\\_CREATED](#); SQLSTATE: [HY000](#)

---

Message: LDAP pool is not created.

[ER\\_LDAP\\_AUTH\\_CONN\\_POOL\\_NOT\\_CREATED](#) was added in 8.0.11.

- Error number: [MY-011749](#); Symbol: [ER\\_LDAP\\_AUTH\\_CONN\\_POOL\\_INITIALIZING](#); SQLSTATE: [HY000](#)

Message: LDAP pool is initializing

[ER\\_LDAP\\_AUTH\\_CONN\\_POOL\\_INITIALIZING](#) was added in 8.0.11.

- Error number: [MY-011750](#); Symbol: [ER\\_LDAP\\_AUTH\\_CONN\\_POOL\\_DEINITIALIZING](#); SQLSTATE: [HY000](#)

Message: LDAP pool is de-initializing

[ER\\_LDAP\\_AUTH\\_CONN\\_POOL\\_DEINITIALIZING](#) was added in 8.0.11.

- Error number: [MY-011751](#); Symbol: [ER\\_LDAP\\_AUTH\\_ZERO\\_MAX\\_POOL\\_SIZE\\_UNCHANGED](#); SQLSTATE: [HY000](#)

Message: Pool max size old and new values are 0

[ER\\_LDAP\\_AUTH\\_ZERO\\_MAX\\_POOL\\_SIZE\\_UNCHANGED](#) was added in 8.0.11.

- Error number: [MY-011752](#); Symbol: [ER\\_LDAP\\_AUTH\\_POOL\\_REINITIALIZING](#); SQLSTATE: [HY000](#)

Message: LDAP pool is re-initializing

[ER\\_LDAP\\_AUTH\\_POOL\\_REINITIALIZING](#) was added in 8.0.11.

- Error number: [MY-011753](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_WRITE\\_PACKET](#); SQLSTATE: [HY000](#)

Message: Plug-in has failed to write the packet.

[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_WRITE\\_PACKET](#) was added in 8.0.11.

- Error number: [MY-011754](#); Symbol: [ER\\_LDAP\\_AUTH\\_SETTING\\_USERNAME](#); SQLSTATE: [HY000](#)

Message: Setting LDAP user name as : %s

[ER\\_LDAP\\_AUTH\\_SETTING\\_USERNAME](#) was added in 8.0.11.

- Error number: [MY-011755](#); Symbol: [ER\\_LDAP\\_AUTH\\_USER\\_AUTH\\_DATA](#); SQLSTATE: [HY000](#)

Message: User authentication data: %s size: %lu

[ER\\_LDAP\\_AUTH\\_USER\\_AUTH\\_DATA](#) was added in 8.0.11.

- Error number: [MY-011756](#); Symbol: [ER\\_LDAP\\_AUTH\\_INFO\\_FOR\\_USER](#); SQLSTATE: [HY000](#)

Message: User is authenticated as: %s external user: %s

[ER\\_LDAP\\_AUTH\\_INFO\\_FOR\\_USER](#) was added in 8.0.11.

- Error number: [MY-011757](#); Symbol: [ER\\_LDAP\\_AUTH\\_USER\\_GROUP\\_SEARCH\\_INFO](#); SQLSTATE: [HY000](#)

---

Message: Group search information base DN: %s scope: %d filter: %s attribute: %s

[ER\\_LDAP\\_AUTH\\_USER\\_GROUP\\_SEARCH\\_INFO](#) was added in 8.0.11.

- Error number: MY-011758; Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_SEARCH\\_SPECIAL\\_HDL](#); SQLSTATE: HY000

Message: Special handling for group search, {GA} found

[ER\\_LDAP\\_AUTH\\_GRP\\_SEARCH\\_SPECIAL\\_HDL](#) was added in 8.0.11.

- Error number: MY-011759; Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_IS\\_FULL\\_DN](#); SQLSTATE: HY000

Message: Group search special handling, group full DN found.

[ER\\_LDAP\\_AUTH\\_GRP\\_IS\\_FULL\\_DN](#) was added in 8.0.11.

- Error number: MY-011760; Symbol: [ER\\_LDAP\\_AUTH\\_USER\\_NOT\\_FOUND\\_IN\\_ANY\\_GRP](#); SQLSTATE: HY000

Message: User %s is not member of any group.

[ER\\_LDAP\\_AUTH\\_USER\\_NOT\\_FOUND\\_IN\\_ANY\\_GRP](#) was added in 8.0.11.

- Error number: MY-011761; Symbol: [ER\\_LDAP\\_AUTH\\_USER\\_FOUND\\_IN\\_MANY\\_GRPS](#); SQLSTATE: HY000

Message: User %s is member of more than one group

[ER\\_LDAP\\_AUTH\\_USER\\_FOUND\\_IN\\_MANY\\_GRPS](#) was added in 8.0.11.

- Error number: MY-011762; Symbol: [ER\\_LDAP\\_AUTH\\_USER\\_HAS\\_MULTIPLE\\_GRP\\_NAMES](#); SQLSTATE: HY000

Message: For user %s has multiple user group names. Please check if group attribute name is correct

[ER\\_LDAP\\_AUTH\\_USER\\_HAS\\_MULTIPLE\\_GRP\\_NAMES](#) was added in 8.0.11.

- Error number: MY-011763; Symbol: [ER\\_LDAP\\_AUTH\\_SEARCHED\\_USER\\_GRP\\_NAME](#); SQLSTATE: HY000

Message: Searched group name: %s

[ER\\_LDAP\\_AUTH\\_SEARCHED\\_USER\\_GRP\\_NAME](#) was added in 8.0.11.

- Error number: MY-011764; Symbol: [ER\\_LDAP\\_AUTH\\_OBJECT\\_CREATE\\_TIMESTAMP](#); SQLSTATE: HY000

Message: LDAP authentication object creation time\_stamp: %s dn: %s

[ER\\_LDAP\\_AUTH\\_OBJECT\\_CREATE\\_TIMESTAMP](#) was added in 8.0.11.

- Error number: MY-011765; Symbol: [ER\\_LDAP\\_AUTH\\_CERTIFICATE\\_NAME](#); SQLSTATE: HY000

Message: Certificate name: %s

[ER\\_LDAP\\_AUTH\\_CERTIFICATE\\_NAME](#) was added in 8.0.11.

- Error number: MY-011766; Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_POOL\\_DEINIT](#); SQLSTATE: HY000

---

Message: Failed to pool de-initialized: pool is already reconstructing

`ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT` was added in 8.0.11.

- Error number: `MY-011767`; Symbol:  
`ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCTING`; SQLSTATE: `HY000`

Message: Pool initialization failed: pool is already initialized

`ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCTING` was added in 8.0.11.

- Error number: `MY-011768`; Symbol:  
`ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT_STATE`; SQLSTATE: `HY000`

Message: Pool initialization failed: pool is initializing

`ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT_STATE` was added in 8.0.11.

- Error number: `MY-011769`; Symbol:  
`ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT_STATE`; SQLSTATE: `HY000`

Message: Pool initialization failed: pool is de-initializing

`ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT_STATE` was added in 8.0.11.

- Error number: `MY-011770`; Symbol:  
`ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONSTRUCT_STATE`; SQLSTATE: `HY000`

Message: Failed to pool deinitialized: pool is already reconstructing

`ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONSTRUCT_STATE` was added in 8.0.11.

- Error number: `MY-011771`; Symbol:  
`ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL`; SQLSTATE: `HY000`

Message: Failed to pool deinitialized : pool is not ready

`ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL` was added in 8.0.11.

- Error number: `MY-011772`; Symbol:  
`ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN_NOT_READY`; SQLSTATE: `HY000`

Message: `Ldap_connection_pool::get`: Failed to return connection as plug-in is not ready/initializing/de-initializing

`ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN_NOT_READY` was added in 8.0.11.

- Error number: `MY-011773`; Symbol: `ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED`; SQLSTATE: `HY000`

Message: Connection pool has failed to initialized

`ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED` was added in 8.0.11.

- 
- Error number: [MY-011774](#); Symbol: [ER\\_LDAP\\_AUTH\\_MAX\\_ALLOWED\\_CONNECTION\\_LIMIT\\_HIT](#); SQLSTATE: [HY000](#)

Message: Ldap\_connexion\_pool::get LDAP maximum connection allowed size is reached. Increase the maximum limit.

[ER\\_LDAP\\_AUTH\\_MAX\\_ALLOWED\\_CONNECTION\\_LIMIT\\_HIT](#) was added in 8.0.11.

- Error number: [MY-011775](#); Symbol: [ER\\_LDAP\\_AUTH\\_MAX\\_POOL\\_SIZE\\_SET\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Set max pool size failed.

[ER\\_LDAP\\_AUTH\\_MAX\\_POOL\\_SIZE\\_SET\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011776](#); Symbol: [ER\\_LDAP\\_AUTH\\_PLUGIN\\_FAILED\\_TO\\_READ\\_PACKET](#); SQLSTATE: [HY000](#)

Message: Plug-in has failed to read the packet from client

[ER\\_LDAP\\_AUTH\\_PLUGIN\\_FAILED\\_TO\\_READ\\_PACKET](#) was added in 8.0.11.

- Error number: [MY-011777](#); Symbol: [ER\\_LDAP\\_AUTH\\_CREATING\\_LDAP\\_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Ldap\_authentication::initialize: creating new LDAP connection.

[ER\\_LDAP\\_AUTH\\_CREATING\\_LDAP\\_CONNECTION](#) was added in 8.0.11.

- Error number: [MY-011778](#); Symbol: [ER\\_LDAP\\_AUTH\\_GETTING\\_CONNECTION\\_FROM\\_POOL](#); SQLSTATE: [HY000](#)

Message: Ldap\_authentication::initialize: getting connection from pool.

[ER\\_LDAP\\_AUTH\\_GETTING\\_CONNECTION\\_FROM\\_POOL](#) was added in 8.0.11.

- Error number: [MY-011779](#); Symbol: [ER\\_LDAP\\_AUTH\\_RETURNING\\_CONNECTION\\_TO\\_POOL](#); SQLSTATE: [HY000](#)

Message: Ldap\_authentication::de\_initialize putting back connection in the pool

[ER\\_LDAP\\_AUTH\\_RETURNING\\_CONNECTION\\_TO\\_POOL](#) was added in 8.0.11.

- Error number: [MY-011780](#); Symbol: [ER\\_LDAP\\_AUTH\\_SEARCH\\_USER\\_GROUP\\_ATTR\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Ldap\_authentication::search\_user\_group no group attribute found

[ER\\_LDAP\\_AUTH\\_SEARCH\\_USER\\_GROUP\\_ATTR\\_NOT\\_FOUND](#) was added in 8.0.11.

- Error number: [MY-011781](#); Symbol: [ER\\_LDAP\\_AUTH\\_LDAP\\_INFO\\_NULL](#); SQLSTATE: [HY000](#)

Message: Ldap\_connexion\_pool::put ldap info null

[ER\\_LDAP\\_AUTH\\_LDAP\\_INFO\\_NULL](#) was added in 8.0.11.

- Error number: [MY-011782](#); Symbol: [ER\\_LDAP\\_AUTH\\_FREEING\\_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Ldap\_connection\_pool::put connection is freeing.

---

`ER_LDAP_AUTH_FREEING_CONNECTION` was added in 8.0.11.

- Error number: `MY-011783`; Symbol: `ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL`; SQLSTATE: `HY000`

Message: `Ldap_connection_pool::put` connection in pushed in the pool

`ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL` was added in 8.0.11.

- Error number: `MY-011784`; Symbol: `ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER`; SQLSTATE: `HY000`

Message: `Ldap_connection_creator::Ldap_connection_creator`

`ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER` was added in 8.0.11.

- Error number: `MY-011785`; Symbol: `ER_LDAP_AUTH_STARTING_TLS`; SQLSTATE: `HY000`

Message: starting TLS

`ER_LDAP_AUTH_STARTING_TLS` was added in 8.0.11.

- Error number: `MY-011786`; Symbol: `ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL`; SQLSTATE: `HY000`

Message: `Ldap_connection_pool::get`: (`ldap_info == NULL`)| (`*ldap_info`)

`ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL` was added in 8.0.11.

- Error number: `MY-011787`; Symbol: `ER_LDAP_AUTH_DELETING_CONNECTION_KEY`; SQLSTATE: `HY000`

Message: `Ldap_connection_pool::deinit`: deleting connection key %s

`ER_LDAP_AUTH_DELETING_CONNECTION_KEY` was added in 8.0.11.

- Error number: `MY-011788`; Symbol: `ER_LDAP_AUTH_POOLED_CONNECTION_KEY`; SQLSTATE: `HY000`

Message: `Ldap_connection_pool::get` pooled connection key: %s

`ER_LDAP_AUTH_POOLED_CONNECTION_KEY` was added in 8.0.11.

- Error number: `MY-011789`; Symbol: `ER_LDAP_AUTH_CREATE_CONNECTION_KEY`; SQLSTATE: `HY000`

Message: `Ldap_connection_pool::get` create connection key: %s

`ER_LDAP_AUTH_CREATE_CONNECTION_KEY` was added in 8.0.11.

- Error number: `MY-011790`; Symbol: `ER_LDAP_AUTH_COMMUNICATION_HOST_INFO`; SQLSTATE: `HY000`

Message: LDAP communication host %s port %u

`ER_LDAP_AUTH_COMMUNICATION_HOST_INFO` was added in 8.0.11.

- Error number: `MY-011791`; Symbol: `ER_LDAP_AUTH_METHOD_TO_CLIENT`; SQLSTATE: `HY000`

Message: Sending authentication method to client : %s

---

`ER_LDAP_AUTH_METHOD_TO_CLIENT` was added in 8.0.11.

- Error number: `MY-011792`; Symbol: `ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT`; SQLSTATE: `HY000`

Message: SASL request received from mysql client: %s

`ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT` was added in 8.0.11.

- Error number: `MY-011793`; Symbol: `ER_LDAP_AUTH_SASL_PROCESS_SASL`; SQLSTATE: `HY000`

Message: `Ldap_sasl_authentication::process_sasl rc: %s`

`ER_LDAP_AUTH_SASL_PROCESS_SASL` was added in 8.0.11.

- Error number: `MY-011794`; Symbol: `ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO`; SQLSTATE: `HY000`

Message: `Ldap_sasl_authentication::process_sasl sasl bind succeed. dn: %s method: %s server credential: %s`

`ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO` was added in 8.0.11.

- Error number: `MY-011795`; Symbol: `ER_LDAP_AUTH_STARTED_FOR_USER`; SQLSTATE: `HY000`

Message: LDAP authentication started for user name: %s

`ER_LDAP_AUTH_STARTED_FOR_USER` was added in 8.0.11.

- Error number: `MY-011796`; Symbol: `ER_LDAP_AUTH_DISTINGUISHED_NAME`; SQLSTATE: `HY000`

Message: %s

`ER_LDAP_AUTH_DISTINGUISHED_NAME` was added in 8.0.11.

- Error number: `MY-011797`; Symbol: `ER_LDAP_AUTH_INIT_FAILED`; SQLSTATE: `HY000`

Message: LDAP authentication initialize is failed with: %s

`ER_LDAP_AUTH_INIT_FAILED` was added in 8.0.11.

- Error number: `MY-011798`; Symbol: `ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED`; SQLSTATE: `HY000`

Message: LDAP authentication failed or group retrieval failed: %s

`ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED` was added in 8.0.11.

- Error number: `MY-011799`; Symbol: `ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED`; SQLSTATE: `HY000`

Message: Search user group has failed: %s

`ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED` was added in 8.0.11.

- Error number: `MY-011800`; Symbol: `ER_LDAP_AUTH_USER_BIND_FAILED`; SQLSTATE: `HY000`

Message: LDAP user bind has failed: %s



---

`ER_LDAP_AUTH_USER_BIND_FAILED` was added in 8.0.11.

- Error number: `MY-011801`; Symbol: `ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION`; SQLSTATE: `HY000`

Message: Connection pool get: Failed to create LDAP connection. %s

`ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION` was added in 8.0.11.

- Error number: `MY-011802`; Symbol: `ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION`; SQLSTATE: `HY000`

Message: Failed to create new LDAP connection: %s

`ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION` was added in 8.0.11.

- Error number: `MY-011803`; Symbol: `ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION`; SQLSTATE: `HY000`

Message: Failed to establish TLS connection: %s

`ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION` was added in 8.0.11.

- Error number: `MY-011804`; Symbol: `ER_LDAP_AUTH_FAILED_TO_SEARCH_DN`; SQLSTATE: `HY000`

Message: Failed to search user full dn: %s

`ER_LDAP_AUTH_FAILED_TO_SEARCH_DN` was added in 8.0.11.

- Error number: `MY-011805`; Symbol: `ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER`; SQLSTATE: `HY000`

Message: Ldap\_connection\_pool::reinit

`ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER` was added in 8.0.11.

- Error number: `MY-011806`; Symbol: `ER_SYSTEMD_NOTIFY_PATH_TOO_LONG`; SQLSTATE: `HY000`

Message: The path '%s', from the NOTIFY\_SOCKET environment variable, is too long. At %u bytes it exceeds the limit of %u bytes for an AF\_UNIX socket.

`ER_SYSTEMD_NOTIFY_PATH_TOO_LONG` was added in 8.0.11.

- Error number: `MY-011807`; Symbol: `ER_SYSTEMD_NOTIFY_CONNECT_FAILED`; SQLSTATE: `HY000`

Message: Failed to connect to systemd notification socket named %s. Error: '%s'

`ER_SYSTEMD_NOTIFY_CONNECT_FAILED` was added in 8.0.11.

- Error number: `MY-011808`; Symbol: `ER_SYSTEMD_NOTIFY_WRITE_FAILED`; SQLSTATE: `HY000`

Message: Failed to write '%s' to systemd notification. Error: '%s'

`ER_SYSTEMD_NOTIFY_WRITE_FAILED` was added in 8.0.11.

- Error number: `MY-011809`; Symbol: `ER_FOUND_MISSING_GTIDS`; SQLSTATE: `HY000`

Message: Cannot replicate to server with server\_uuid='%s' because the present server has purged required binary logs. The connecting server needs to replicate the missing transactions from elsewhere,

---

or be replaced by a new server created from a more recent backup. To prevent this error in the future, consider increasing the binary log expiration period on the present server. %s.

`ER_FOUND_MISSING_GTIDS` was added in 8.0.11.

- Error number: `MY-011810`; Symbol: `ER_PID_FILE_PRIV_DIRECTORY_INSECURE`; SQLSTATE: `HY000`

Message: Insecure configuration for --pid-file: Location '%s' in the path is accessible to all OS users. Consider choosing a different directory.

`ER_PID_FILE_PRIV_DIRECTORY_INSECURE` was added in 8.0.11.

- Error number: `MY-011811`; Symbol: `ER_CANT_CHECK_PID_PATH`; SQLSTATE: `HY000`

Message: Can't start server: can't check PID filepath: %s

`ER_CANT_CHECK_PID_PATH` was added in 8.0.11.

- Error number: `MY-011812`; Symbol: `ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: validate\_password status variables registration failed.

`ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED` was added in 8.0.11.

- Error number: `MY-011813`; Symbol: `ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: validate\_password status variables unregistration failed.

`ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED` was added in 8.0.11.

- Error number: `MY-011814`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Dictionary file open failed

`ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED` was added in 8.0.11.

- Error number: `MY-011815`; Symbol: `ER_VALIDATE_PWD_COULD_BE_NULL`; SQLSTATE: `HY000`

Message: given password string could be null

`ER_VALIDATE_PWD_COULD_BE_NULL` was added in 8.0.11.

- Error number: `MY-011816`; Symbol: `ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED`; SQLSTATE: `HY000`

Message: failed to convert the password string to lower case

`ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED` was added in 8.0.11.

- Error number: `MY-011817`; Symbol: `ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED`; SQLSTATE: `HY000`

Message: failed to convert the password string into a buffer

`ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED` was added in 8.0.11.

- 
- Error number: [MY-011818](#); Symbol: [ER\\_VALIDATE\\_PWD\\_STRING\\_HANDLER\\_MEM\\_ALLOCATION\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: memory allocation failed for string handler  
  
[ER\\_VALIDATE\\_PWD\\_STRING\\_HANDLER\\_MEM\\_ALLOCATION\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011819](#); Symbol: [ER\\_VALIDATE\\_PWD\\_STRONG\\_POLICY\\_DICT\\_FILE\\_UNSPECIFIED](#); SQLSTATE: [HY000](#)  
  
Message: Since the validate\_password\_policy is mentioned as Strong, dictionary file must be specified  
  
[ER\\_VALIDATE\\_PWD\\_STRONG\\_POLICY\\_DICT\\_FILE\\_UNSPECIFIED](#) was added in 8.0.11.
  - Error number: [MY-011820](#); Symbol: [ER\\_VALIDATE\\_PWD\\_CONVERT\\_TO\\_BUFFER\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: convert\_to\_buffer service failed  
  
[ER\\_VALIDATE\\_PWD\\_CONVERT\\_TO\\_BUFFER\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011821](#); Symbol: [ER\\_VALIDATE\\_PWD\\_VARIABLE\\_REGISTRATION\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: %s variable registration failed.  
  
[ER\\_VALIDATE\\_PWD\\_VARIABLE\\_REGISTRATION\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011822](#); Symbol: [ER\\_VALIDATE\\_PWD\\_VARIABLE\\_UNREGISTRATION\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: %s variable unregistration failed.  
  
[ER\\_VALIDATE\\_PWD\\_VARIABLE\\_UNREGISTRATION\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011823](#); Symbol: [ER\\_KEYRING\\_MIGRATION\\_EXTRA\\_OPTIONS](#); SQLSTATE: [HY000](#)  
  
Message: Please specify options specific to keyring migration. Any additional options can be ignored.  
NOTE: Although some options are valid, migration tool can still report error example: plugin variables for which plugin is not loaded yet.  
  
[ER\\_KEYRING\\_MIGRATION\\_EXTRA\\_OPTIONS](#) was added in 8.0.11.
  - Error number: [MY-011825](#); Symbol: [ER\\_IB\\_MSG\\_0](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_IB\\_MSG\\_0](#) was added in 8.0.11.
  - Error number: [MY-011826](#); Symbol: [ER\\_IB\\_MSG\\_1](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_IB\\_MSG\\_1](#) was added in 8.0.11.

- 
- Error number: [MY-011827](#); Symbol: [ER\\_IB\\_MSG\\_2](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_2](#) was added in 8.0.11.
  - Error number: [MY-011828](#); Symbol: [ER\\_IB\\_MSG\\_3](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_3](#) was added in 8.0.11.
  - Error number: [MY-011829](#); Symbol: [ER\\_IB\\_MSG\\_4](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_4](#) was added in 8.0.11.
  - Error number: [MY-011830](#); Symbol: [ER\\_IB\\_MSG\\_5](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_5](#) was added in 8.0.11.
  - Error number: [MY-011831](#); Symbol: [ER\\_IB\\_MSG\\_6](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_6](#) was added in 8.0.11.
  - Error number: [MY-011832](#); Symbol: [ER\\_IB\\_MSG\\_7](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_7](#) was added in 8.0.11.
  - Error number: [MY-011833](#); Symbol: [ER\\_IB\\_MSG\\_8](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_8](#) was added in 8.0.11.
  - Error number: [MY-011834](#); Symbol: [ER\\_IB\\_MSG\\_9](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_9](#) was added in 8.0.11.
  - Error number: [MY-011835](#); Symbol: [ER\\_IB\\_MSG\\_10](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_10](#) was added in 8.0.11.
  - Error number: [MY-011836](#); Symbol: [ER\\_IB\\_MSG\\_11](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_11](#) was added in 8.0.11.

- 
- Error number: [MY-011837](#); Symbol: [ER\\_IB\\_MSG\\_12](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_12](#) was added in 8.0.11.
  - Error number: [MY-011838](#); Symbol: [ER\\_IB\\_MSG\\_13](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_13](#) was added in 8.0.11.
  - Error number: [MY-011839](#); Symbol: [ER\\_IB\\_MSG\\_14](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_14](#) was added in 8.0.11.
  - Error number: [MY-011840](#); Symbol: [ER\\_IB\\_MSG\\_15](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_15](#) was added in 8.0.11.
  - Error number: [MY-011841](#); Symbol: [ER\\_IB\\_MSG\\_16](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_16](#) was added in 8.0.11.
  - Error number: [MY-011842](#); Symbol: [ER\\_IB\\_MSG\\_17](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_17](#) was added in 8.0.11.
  - Error number: [MY-011843](#); Symbol: [ER\\_IB\\_MSG\\_18](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_18](#) was added in 8.0.11.
  - Error number: [MY-011844](#); Symbol: [ER\\_IB\\_MSG\\_19](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_19](#) was added in 8.0.11.
  - Error number: [MY-011845](#); Symbol: [ER\\_IB\\_MSG\\_20](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_20](#) was added in 8.0.11.
  - Error number: [MY-011846](#); Symbol: [ER\\_IB\\_MSG\\_21](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_21](#) was added in 8.0.11.

- 
- Error number: [MY-011847](#); Symbol: [ER\\_IB\\_MSG\\_22](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_22](#) was added in 8.0.11.
  - Error number: [MY-011848](#); Symbol: [ER\\_IB\\_MSG\\_23](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_23](#) was added in 8.0.11.
  - Error number: [MY-011849](#); Symbol: [ER\\_IB\\_MSG\\_24](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_24](#) was added in 8.0.11.
  - Error number: [MY-011850](#); Symbol: [ER\\_IB\\_MSG\\_25](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_25](#) was added in 8.0.11.
  - Error number: [MY-011851](#); Symbol: [ER\\_IB\\_MSG\\_26](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_26](#) was added in 8.0.11.
  - Error number: [MY-011852](#); Symbol: [ER\\_IB\\_MSG\\_27](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_27](#) was added in 8.0.11.
  - Error number: [MY-011853](#); Symbol: [ER\\_IB\\_MSG\\_28](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_28](#) was added in 8.0.11.
  - Error number: [MY-011854](#); Symbol: [ER\\_IB\\_MSG\\_29](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_29](#) was added in 8.0.11.
  - Error number: [MY-011855](#); Symbol: [ER\\_IB\\_MSG\\_30](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_30](#) was added in 8.0.11.
  - Error number: [MY-011856](#); Symbol: [ER\\_IB\\_MSG\\_31](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_31](#) was added in 8.0.11.

- 
- Error number: [MY-011857](#); Symbol: [ER\\_IB\\_MSG\\_32](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_32](#) was added in 8.0.11.
  - Error number: [MY-011858](#); Symbol: [ER\\_IB\\_MSG\\_33](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_33](#) was added in 8.0.11.
  - Error number: [MY-011859](#); Symbol: [ER\\_IB\\_MSG\\_34](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_34](#) was added in 8.0.11.
  - Error number: [MY-011860](#); Symbol: [ER\\_IB\\_MSG\\_35](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_35](#) was added in 8.0.11.
  - Error number: [MY-011861](#); Symbol: [ER\\_IB\\_MSG\\_36](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_36](#) was added in 8.0.11.
  - Error number: [MY-011862](#); Symbol: [ER\\_IB\\_MSG\\_37](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_37](#) was added in 8.0.11.
  - Error number: [MY-011863](#); Symbol: [ER\\_IB\\_MSG\\_38](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_38](#) was added in 8.0.11.
  - Error number: [MY-011864](#); Symbol: [ER\\_IB\\_MSG\\_39](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_39](#) was added in 8.0.11.
  - Error number: [MY-011865](#); Symbol: [ER\\_IB\\_MSG\\_40](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_40](#) was added in 8.0.11.
  - Error number: [MY-011866](#); Symbol: [ER\\_IB\\_MSG\\_41](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_41](#) was added in 8.0.11.

- 
- Error number: [MY-011867](#); Symbol: [ER\\_IB\\_MSG\\_42](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_42](#) was added in 8.0.11.
  - Error number: [MY-011868](#); Symbol: [ER\\_IB\\_MSG\\_43](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_43](#) was added in 8.0.11.
  - Error number: [MY-011869](#); Symbol: [ER\\_IB\\_MSG\\_44](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_44](#) was added in 8.0.11.
  - Error number: [MY-011870](#); Symbol: [ER\\_IB\\_MSG\\_45](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_45](#) was added in 8.0.11.
  - Error number: [MY-011871](#); Symbol: [ER\\_IB\\_MSG\\_46](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_46](#) was added in 8.0.11.
  - Error number: [MY-011872](#); Symbol: [ER\\_IB\\_MSG\\_47](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_47](#) was added in 8.0.11.
  - Error number: [MY-011873](#); Symbol: [ER\\_IB\\_MSG\\_48](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_48](#) was added in 8.0.11.
  - Error number: [MY-011874](#); Symbol: [ER\\_IB\\_MSG\\_49](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_49](#) was added in 8.0.11.
  - Error number: [MY-011875](#); Symbol: [ER\\_IB\\_MSG\\_50](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_50](#) was added in 8.0.11.
  - Error number: [MY-011876](#); Symbol: [ER\\_IB\\_MSG\\_51](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_51](#) was added in 8.0.11.



- 
- Error number: [MY-011877](#); Symbol: [ER\\_IB\\_MSG\\_52](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_52](#) was added in 8.0.11.
  - Error number: [MY-011878](#); Symbol: [ER\\_IB\\_MSG\\_53](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_53](#) was added in 8.0.11.
  - Error number: [MY-011879](#); Symbol: [ER\\_IB\\_MSG\\_54](#); SQLSTATE: [HY000](#)  
Message: Failed to set NUMA memory policy of buffer pool page frames with mbind(%p,%zu,%s,...,..., %s) failed with %s  
[ER\\_IB\\_MSG\\_54](#) was added in 8.0.11.
  - Error number: [MY-011880](#); Symbol: [ER\\_IB\\_MSG\\_55](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_55](#) was added in 8.0.11.
  - Error number: [MY-011881](#); Symbol: [ER\\_IB\\_MSG\\_56](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_56](#) was added in 8.0.11.
  - Error number: [MY-011882](#); Symbol: [ER\\_IB\\_MSG\\_57](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_57](#) was added in 8.0.11.
  - Error number: [MY-011883](#); Symbol: [ER\\_IB\\_MSG\\_58](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_58](#) was added in 8.0.11.
  - Error number: [MY-011884](#); Symbol: [ER\\_IB\\_MSG\\_59](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_59](#) was added in 8.0.11.
  - Error number: [MY-011885](#); Symbol: [ER\\_IB\\_MSG\\_60](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_60](#) was added in 8.0.11.
  - Error number: [MY-011886](#); Symbol: [ER\\_IB\\_MSG\\_61](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_61](#) was added in 8.0.11.

- 
- Error number: [MY-011887](#); Symbol: [ER\\_IB\\_MSG\\_62](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_62](#) was added in 8.0.11.
  - Error number: [MY-011888](#); Symbol: [ER\\_IB\\_MSG\\_63](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_63](#) was added in 8.0.11.
  - Error number: [MY-011889](#); Symbol: [ER\\_IB\\_MSG\\_64](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_64](#) was added in 8.0.11.
  - Error number: [MY-011890](#); Symbol: [ER\\_IB\\_MSG\\_65](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_65](#) was added in 8.0.11.
  - Error number: [MY-011891](#); Symbol: [ER\\_IB\\_MSG\\_66](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_66](#) was added in 8.0.11.
  - Error number: [MY-011892](#); Symbol: [ER\\_IB\\_MSG\\_67](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_67](#) was added in 8.0.11.
  - Error number: [MY-011893](#); Symbol: [ER\\_IB\\_MSG\\_68](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_68](#) was added in 8.0.11.
  - Error number: [MY-011894](#); Symbol: [ER\\_IB\\_MSG\\_69](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_69](#) was added in 8.0.11.
  - Error number: [MY-011895](#); Symbol: [ER\\_IB\\_MSG\\_70](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_70](#) was added in 8.0.11.
  - Error number: [MY-011896](#); Symbol: [ER\\_IB\\_MSG\\_71](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_71](#) was added in 8.0.11.

- 
- Error number: [MY-011897](#); Symbol: [ER\\_IB\\_MSG\\_72](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_72](#) was added in 8.0.11.
  - Error number: [MY-011898](#); Symbol: [ER\\_IB\\_MSG\\_73](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_73](#) was added in 8.0.11.
  - Error number: [MY-011899](#); Symbol: [ER\\_IB\\_MSG\\_74](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_74](#) was added in 8.0.11.
  - Error number: [MY-011900](#); Symbol: [ER\\_IB\\_MSG\\_75](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_75](#) was added in 8.0.11.
  - Error number: [MY-011901](#); Symbol: [ER\\_IB\\_MSG\\_76](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_76](#) was added in 8.0.11.
  - Error number: [MY-011902](#); Symbol: [ER\\_IB\\_MSG\\_77](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_77](#) was added in 8.0.11.
  - Error number: [MY-011903](#); Symbol: [ER\\_IB\\_MSG\\_78](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_78](#) was added in 8.0.11.
  - Error number: [MY-011904](#); Symbol: [ER\\_IB\\_MSG\\_79](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_79](#) was added in 8.0.11.
  - Error number: [MY-011905](#); Symbol: [ER\\_IB\\_MSG\\_80](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_80](#) was added in 8.0.11.
  - Error number: [MY-011906](#); Symbol: [ER\\_IB\\_MSG\\_81](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_81](#) was added in 8.0.11.

- 
- Error number: [MY-011907](#); Symbol: [ER\\_IB\\_MSG\\_82](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_82](#) was added in 8.0.11.
  - Error number: [MY-011908](#); Symbol: [ER\\_IB\\_MSG\\_83](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_83](#) was added in 8.0.11, removed after 8.0.41.
  - Error number: [MY-011908](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_DIRTY\\_AT\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: Page still fixed or dirty at shutdown. %s  
[ER\\_IB\\_ERR\\_PAGE\\_DIRTY\\_AT\\_SHUTDOWN](#) was added in 8.0.42.
  - Error number: [MY-011909](#); Symbol: [ER\\_IB\\_MSG\\_84](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_84](#) was added in 8.0.11.
  - Error number: [MY-011910](#); Symbol: [ER\\_IB\\_MSG\\_85](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_85](#) was added in 8.0.11.
  - Error number: [MY-011911](#); Symbol: [ER\\_IB\\_MSG\\_86](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_86](#) was added in 8.0.11.
  - Error number: [MY-011912](#); Symbol: [ER\\_IB\\_MSG\\_87](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_87](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011913](#); Symbol: [ER\\_IB\\_MSG\\_88](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_88](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011914](#); Symbol: [ER\\_IB\\_MSG\\_89](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_89](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011915](#); Symbol: [ER\\_IB\\_MSG\\_90](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_90](#) was added in 8.0.11, removed after 8.0.13.

- 
- Error number: [MY-011916](#); Symbol: [ER\\_IB\\_MSG\\_91](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_91](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011917](#); Symbol: [ER\\_IB\\_MSG\\_92](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_92](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011918](#); Symbol: [ER\\_IB\\_MSG\\_93](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_93](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011919](#); Symbol: [ER\\_IB\\_MSG\\_94](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_94](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011920](#); Symbol: [ER\\_IB\\_MSG\\_95](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_95](#) was added in 8.0.11.
  - Error number: [MY-011921](#); Symbol: [ER\\_IB\\_MSG\\_96](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_96](#) was added in 8.0.11.
  - Error number: [MY-011922](#); Symbol: [ER\\_IB\\_MSG\\_97](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_97](#) was added in 8.0.11.
  - Error number: [MY-011923](#); Symbol: [ER\\_IB\\_MSG\\_98](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_98](#) was added in 8.0.11.
  - Error number: [MY-011924](#); Symbol: [ER\\_IB\\_MSG\\_99](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_99](#) was added in 8.0.11.
  - Error number: [MY-011925](#); Symbol: [ER\\_IB\\_MSG\\_100](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_100](#) was added in 8.0.11.

- 
- Error number: [MY-011926](#); Symbol: [ER\\_IB\\_MSG\\_101](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_101](#) was added in 8.0.11.
  - Error number: [MY-011927](#); Symbol: [ER\\_IB\\_MSG\\_102](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_102](#) was added in 8.0.11.
  - Error number: [MY-011928](#); Symbol: [ER\\_IB\\_MSG\\_103](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_103](#) was added in 8.0.11.
  - Error number: [MY-011929](#); Symbol: [ER\\_IB\\_MSG\\_104](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_104](#) was added in 8.0.11.
  - Error number: [MY-011930](#); Symbol: [ER\\_IB\\_MSG\\_105](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_105](#) was added in 8.0.11.
  - Error number: [MY-011931](#); Symbol: [ER\\_IB\\_MSG\\_106](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_106](#) was added in 8.0.11.
  - Error number: [MY-011932](#); Symbol: [ER\\_IB\\_MSG\\_107](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_107](#) was added in 8.0.11.
  - Error number: [MY-011933](#); Symbol: [ER\\_IB\\_MSG\\_108](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_108](#) was added in 8.0.11.
  - Error number: [MY-011934](#); Symbol: [ER\\_IB\\_MSG\\_109](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_109](#) was added in 8.0.11.
  - Error number: [MY-011935](#); Symbol: [ER\\_IB\\_MSG\\_110](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_110](#) was added in 8.0.11.

- 
- Error number: [MY-011936](#); Symbol: [ER\\_IB\\_MSG\\_111](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_111](#) was added in 8.0.11.
  - Error number: [MY-011937](#); Symbol: [ER\\_IB\\_MSG\\_112](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_112](#) was added in 8.0.11.
  - Error number: [MY-011938](#); Symbol: [ER\\_IB\\_MSG\\_113](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_113](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011939](#); Symbol: [ER\\_IB\\_MSG\\_114](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_114](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011940](#); Symbol: [ER\\_IB\\_MSG\\_115](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_115](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011941](#); Symbol: [ER\\_IB\\_MSG\\_116](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_116](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011942](#); Symbol: [ER\\_IB\\_MSG\\_117](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_117](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011943](#); Symbol: [ER\\_IB\\_MSG\\_118](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_118](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011944](#); Symbol: [ER\\_IB\\_MSG\\_119](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_119](#) was added in 8.0.11.
  - Error number: [MY-011945](#); Symbol: [ER\\_IB\\_MSG\\_120](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_120](#) was added in 8.0.11.

- 
- Error number: [MY-011946](#); Symbol: [ER\\_IB\\_MSG\\_121](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_121](#) was added in 8.0.11.
  - Error number: [MY-011947](#); Symbol: [ER\\_IB\\_MSG\\_122](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_122](#) was added in 8.0.11.
  - Error number: [MY-011948](#); Symbol: [ER\\_IB\\_MSG\\_123](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_123](#) was added in 8.0.11.
  - Error number: [MY-011949](#); Symbol: [ER\\_IB\\_MSG\\_124](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_124](#) was added in 8.0.11.
  - Error number: [MY-011950](#); Symbol: [ER\\_IB\\_MSG\\_125](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_125](#) was added in 8.0.11.
  - Error number: [MY-011951](#); Symbol: [ER\\_IB\\_MSG\\_126](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_126](#) was added in 8.0.11.
  - Error number: [MY-011952](#); Symbol: [ER\\_IB\\_MSG\\_127](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_127](#) was added in 8.0.11.
  - Error number: [MY-011953](#); Symbol: [ER\\_IB\\_MSG\\_128](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_128](#) was added in 8.0.11.
  - Error number: [MY-011954](#); Symbol: [ER\\_IB\\_MSG\\_129](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_129](#) was added in 8.0.11.
  - Error number: [MY-011955](#); Symbol: [ER\\_IB\\_MSG\\_130](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_130](#) was added in 8.0.11.



- 
- Error number: [MY-011956](#); Symbol: [ER\\_IB\\_MSG\\_131](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_131](#) was added in 8.0.11.
  - Error number: [MY-011957](#); Symbol: [ER\\_IB\\_MSG\\_132](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_132](#) was added in 8.0.11.
  - Error number: [MY-011958](#); Symbol: [ER\\_IB\\_MSG\\_133](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_133](#) was added in 8.0.11.
  - Error number: [MY-011959](#); Symbol: [ER\\_IB\\_MSG\\_134](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_134](#) was added in 8.0.11.
  - Error number: [MY-011960](#); Symbol: [ER\\_IB\\_MSG\\_135](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_135](#) was added in 8.0.11.
  - Error number: [MY-011961](#); Symbol: [ER\\_IB\\_MSG\\_136](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_136](#) was added in 8.0.11.
  - Error number: [MY-011962](#); Symbol: [ER\\_IB\\_MSG\\_137](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_137](#) was added in 8.0.11.
  - Error number: [MY-011963](#); Symbol: [ER\\_IB\\_MSG\\_138](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_138](#) was added in 8.0.11.
  - Error number: [MY-011964](#); Symbol: [ER\\_IB\\_MSG\\_139](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_139](#) was added in 8.0.11.
  - Error number: [MY-011965](#); Symbol: [ER\\_IB\\_MSG\\_140](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_140](#) was added in 8.0.11.

- 
- Error number: [MY-011966](#); Symbol: [ER\\_IB\\_MSG\\_141](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_141](#) was added in 8.0.11.
  - Error number: [MY-011967](#); Symbol: [ER\\_IB\\_MSG\\_142](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_142](#) was added in 8.0.11.
  - Error number: [MY-011968](#); Symbol: [ER\\_IB\\_MSG\\_143](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_143](#) was added in 8.0.11.
  - Error number: [MY-011969](#); Symbol: [ER\\_IB\\_MSG\\_144](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_144](#) was added in 8.0.11.
  - Error number: [MY-011970](#); Symbol: [ER\\_IB\\_MSG\\_145](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_145](#) was added in 8.0.11.
  - Error number: [MY-011971](#); Symbol: [ER\\_IB\\_MSG\\_146](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_146](#) was added in 8.0.11.
  - Error number: [MY-011972](#); Symbol: [ER\\_IB\\_MSG\\_147](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_147](#) was added in 8.0.11.
  - Error number: [MY-011973](#); Symbol: [ER\\_IB\\_MSG\\_148](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_148](#) was added in 8.0.11.
  - Error number: [MY-011974](#); Symbol: [ER\\_IB\\_MSG\\_149](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_149](#) was added in 8.0.11, removed after 8.0.16.
  - Error number: [MY-011974](#); Symbol: [ER\\_IB\\_CLONE\\_INTERNAL](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_INTERNAL](#) was added in 8.0.17.

- 
- Error number: [MY-011975](#); Symbol: [ER\\_IB\\_MSG\\_150](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_150](#) was added in 8.0.11, removed after 8.0.16.
  - Error number: [MY-011975](#); Symbol: [ER\\_IB\\_CLONE\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_TIMEOUT](#) was added in 8.0.17.
  - Error number: [MY-011976](#); Symbol: [ER\\_IB\\_MSG\\_151](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_151](#) was added in 8.0.11, removed after 8.0.16.
  - Error number: [MY-011976](#); Symbol: [ER\\_IB\\_CLONE\\_STATUS\\_FILE](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_STATUS\\_FILE](#) was added in 8.0.17.
  - Error number: [MY-011977](#); Symbol: [ER\\_IB\\_MSG\\_152](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_152](#) was added in 8.0.11, removed after 8.0.16.
  - Error number: [MY-011977](#); Symbol: [ER\\_IB\\_CLONE\\_SQL](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_SQL](#) was added in 8.0.17.
  - Error number: [MY-011978](#); Symbol: [ER\\_IB\\_MSG\\_153](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_153](#) was added in 8.0.11, removed after 8.0.16.
  - Error number: [MY-011978](#); Symbol: [ER\\_IB\\_CLONE\\_VALIDATE](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_VALIDATE](#) was added in 8.0.17.
  - Error number: [MY-011979](#); Symbol: [ER\\_IB\\_MSG\\_154](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_154](#) was added in 8.0.11, removed after 8.0.16.
  - Error number: [MY-011979](#); Symbol: [ER\\_IB\\_CLONE\\_PUNCH\\_HOLE](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_PUNCH\\_HOLE](#) was added in 8.0.17.

- 
- Error number: [MY-011980](#); Symbol: [ER\\_IB\\_MSG\\_155](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_155](#) was added in 8.0.11, removed after 8.0.16.
  - Error number: [MY-011980](#); Symbol: [ER\\_IB\\_CLONE\\_GTID\\_PERSIST](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_GTID\\_PERSIST](#) was added in 8.0.17.
  - Error number: [MY-011981](#); Symbol: [ER\\_IB\\_MSG\\_156](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_156](#) was added in 8.0.11.
  - Error number: [MY-011982](#); Symbol: [ER\\_IB\\_MSG\\_157](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_157](#) was added in 8.0.11.
  - Error number: [MY-011983](#); Symbol: [ER\\_IB\\_MSG\\_158](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_158](#) was added in 8.0.11.
  - Error number: [MY-011984](#); Symbol: [ER\\_IB\\_MSG\\_159](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_159](#) was added in 8.0.11.
  - Error number: [MY-011985](#); Symbol: [ER\\_IB\\_MSG\\_160](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_160](#) was added in 8.0.11.
  - Error number: [MY-011986](#); Symbol: [ER\\_IB\\_MSG\\_161](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_161](#) was added in 8.0.11.
  - Error number: [MY-011987](#); Symbol: [ER\\_IB\\_MSG\\_162](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_162](#) was added in 8.0.11.
  - Error number: [MY-011988](#); Symbol: [ER\\_IB\\_MSG\\_163](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_163](#) was added in 8.0.11.

- 
- Error number: [MY-011989](#); Symbol: [ER\\_IB\\_MSG\\_164](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_164](#) was added in 8.0.11.
  - Error number: [MY-011990](#); Symbol: [ER\\_IB\\_MSG\\_165](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_165](#) was added in 8.0.11.
  - Error number: [MY-011991](#); Symbol: [ER\\_IB\\_MSG\\_166](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_166](#) was added in 8.0.11.
  - Error number: [MY-011992](#); Symbol: [ER\\_IB\\_MSG\\_167](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_167](#) was added in 8.0.11.
  - Error number: [MY-011993](#); Symbol: [ER\\_IB\\_MSG\\_168](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_168](#) was added in 8.0.11.
  - Error number: [MY-011994](#); Symbol: [ER\\_IB\\_MSG\\_169](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_169](#) was added in 8.0.11.
  - Error number: [MY-011995](#); Symbol: [ER\\_IB\\_MSG\\_170](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_170](#) was added in 8.0.11.
  - Error number: [MY-011996](#); Symbol: [ER\\_IB\\_MSG\\_171](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_171](#) was added in 8.0.11.
  - Error number: [MY-011997](#); Symbol: [ER\\_IB\\_MSG\\_172](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_172](#) was added in 8.0.11.
  - Error number: [MY-011998](#); Symbol: [ER\\_IB\\_MSG\\_173](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_173](#) was added in 8.0.11.

- 
- Error number: [MY-011999](#); Symbol: [ER\\_IB\\_MSG\\_174](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_174](#) was added in 8.0.11.
  - Error number: [MY-012000](#); Symbol: [ER\\_IB\\_MSG\\_175](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_175](#) was added in 8.0.11.
  - Error number: [MY-012001](#); Symbol: [ER\\_IB\\_MSG\\_176](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_176](#) was added in 8.0.11.
  - Error number: [MY-012002](#); Symbol: [ER\\_IB\\_MSG\\_177](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_177](#) was added in 8.0.11.
  - Error number: [MY-012003](#); Symbol: [ER\\_IB\\_MSG\\_178](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_178](#) was added in 8.0.11.
  - Error number: [MY-012004](#); Symbol: [ER\\_IB\\_MSG\\_179](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_179](#) was added in 8.0.11.
  - Error number: [MY-012005](#); Symbol: [ER\\_IB\\_MSG\\_180](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_180](#) was added in 8.0.11.
  - Error number: [MY-012006](#); Symbol: [ER\\_IB\\_MSG\\_181](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_181](#) was added in 8.0.11, removed after 8.0.31.
  - Error number: [MY-012006](#); Symbol: [ER\\_IB\\_LONG\\_AHI\\_DISABLE\\_WAIT](#); SQLSTATE: [HY000](#)  
Message: Waited for %u secs for hash index ref\_count (%zu) to drop to 0. index: "%s" table: "%s"  
[ER\\_IB\\_LONG\\_AHI\\_DISABLE\\_WAIT](#) was added in 8.0.32.
  - Error number: [MY-012007](#); Symbol: [ER\\_IB\\_MSG\\_182](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_182](#) was added in 8.0.11.

- 
- Error number: [MY-012008](#); Symbol: [ER\\_IB\\_MSG\\_183](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_183](#) was added in 8.0.11.
  - Error number: [MY-012009](#); Symbol: [ER\\_IB\\_MSG\\_184](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_184](#) was added in 8.0.11.
  - Error number: [MY-012010](#); Symbol: [ER\\_IB\\_MSG\\_185](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_185](#) was added in 8.0.11.
  - Error number: [MY-012011](#); Symbol: [ER\\_IB\\_MSG\\_186](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_186](#) was added in 8.0.11.
  - Error number: [MY-012012](#); Symbol: [ER\\_IB\\_MSG\\_187](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_187](#) was added in 8.0.11.
  - Error number: [MY-012013](#); Symbol: [ER\\_IB\\_MSG\\_188](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_188](#) was added in 8.0.11.
  - Error number: [MY-012014](#); Symbol: [ER\\_IB\\_MSG\\_189](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_189](#) was added in 8.0.11.
  - Error number: [MY-012015](#); Symbol: [ER\\_IB\\_MSG\\_190](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_190](#) was added in 8.0.11.
  - Error number: [MY-012016](#); Symbol: [ER\\_IB\\_MSG\\_191](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_191](#) was added in 8.0.11.
  - Error number: [MY-012017](#); Symbol: [ER\\_IB\\_MSG\\_192](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_192](#) was added in 8.0.11.

- 
- Error number: [MY-012018](#); Symbol: [ER\\_IB\\_MSG\\_193](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_193](#) was added in 8.0.11.
  - Error number: [MY-012019](#); Symbol: [ER\\_IB\\_MSG\\_194](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_194](#) was added in 8.0.11.
  - Error number: [MY-012020](#); Symbol: [ER\\_IB\\_MSG\\_195](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_195](#) was added in 8.0.11.
  - Error number: [MY-012021](#); Symbol: [ER\\_IB\\_MSG\\_196](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_196](#) was added in 8.0.11.
  - Error number: [MY-012022](#); Symbol: [ER\\_IB\\_MSG\\_197](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_197](#) was added in 8.0.11.
  - Error number: [MY-012023](#); Symbol: [ER\\_IB\\_MSG\\_198](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_198](#) was added in 8.0.11.
  - Error number: [MY-012024](#); Symbol: [ER\\_IB\\_MSG\\_199](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_199](#) was added in 8.0.11.
  - Error number: [MY-012025](#); Symbol: [ER\\_IB\\_MSG\\_200](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_200](#) was added in 8.0.11.
  - Error number: [MY-012026](#); Symbol: [ER\\_IB\\_MSG\\_201](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_201](#) was added in 8.0.11.
  - Error number: [MY-012027](#); Symbol: [ER\\_IB\\_MSG\\_202](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_202](#) was added in 8.0.11.



- 
- Error number: [MY-012028](#); Symbol: [ER\\_IB\\_MSG\\_203](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_203](#) was added in 8.0.11.
  - Error number: [MY-012029](#); Symbol: [ER\\_IB\\_MSG\\_204](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_204](#) was added in 8.0.11.
  - Error number: [MY-012030](#); Symbol: [ER\\_IB\\_MSG\\_205](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_205](#) was added in 8.0.11.
  - Error number: [MY-012031](#); Symbol: [ER\\_IB\\_MSG\\_206](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_206](#) was added in 8.0.11.
  - Error number: [MY-012032](#); Symbol: [ER\\_IB\\_MSG\\_207](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_207](#) was added in 8.0.11.
  - Error number: [MY-012033](#); Symbol: [ER\\_IB\\_MSG\\_208](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_208](#) was added in 8.0.11.
  - Error number: [MY-012034](#); Symbol: [ER\\_IB\\_MSG\\_209](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_209](#) was added in 8.0.11.
  - Error number: [MY-012035](#); Symbol: [ER\\_IB\\_MSG\\_210](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_210](#) was added in 8.0.11.
  - Error number: [MY-012036](#); Symbol: [ER\\_IB\\_MSG\\_211](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_211](#) was added in 8.0.11.
  - Error number: [MY-012037](#); Symbol: [ER\\_IB\\_MSG\\_212](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_212](#) was added in 8.0.11.

- 
- Error number: [MY-012038](#); Symbol: [ER\\_IB\\_MSG\\_213](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_213](#) was added in 8.0.11.
  - Error number: [MY-012039](#); Symbol: [ER\\_IB\\_MSG\\_214](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_214](#) was added in 8.0.11.
  - Error number: [MY-012040](#); Symbol: [ER\\_IB\\_MSG\\_215](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_215](#) was added in 8.0.11.
  - Error number: [MY-012041](#); Symbol: [ER\\_IB\\_MSG\\_216](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_216](#) was added in 8.0.11.
  - Error number: [MY-012042](#); Symbol: [ER\\_IB\\_MSG\\_217](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_217](#) was added in 8.0.11.
  - Error number: [MY-012043](#); Symbol: [ER\\_IB\\_MSG\\_218](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_218](#) was added in 8.0.11.
  - Error number: [MY-012044](#); Symbol: [ER\\_IB\\_MSG\\_219](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_219](#) was added in 8.0.11.
  - Error number: [MY-012045](#); Symbol: [ER\\_IB\\_MSG\\_220](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_220](#) was added in 8.0.11.
  - Error number: [MY-012046](#); Symbol: [ER\\_IB\\_MSG\\_221](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_221](#) was added in 8.0.11.
  - Error number: [MY-012047](#); Symbol: [ER\\_IB\\_MSG\\_222](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_222](#) was added in 8.0.11.

- 
- Error number: [MY-012048](#); Symbol: [ER\\_IB\\_MSG\\_223](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_223](#) was added in 8.0.11.
  - Error number: [MY-012049](#); Symbol: [ER\\_IB\\_MSG\\_224](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_224](#) was added in 8.0.11.
  - Error number: [MY-012050](#); Symbol: [ER\\_IB\\_MSG\\_225](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_225](#) was added in 8.0.11.
  - Error number: [MY-012051](#); Symbol: [ER\\_IB\\_MSG\\_226](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_226](#) was added in 8.0.11.
  - Error number: [MY-012052](#); Symbol: [ER\\_IB\\_MSG\\_227](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_227](#) was added in 8.0.11.
  - Error number: [MY-012053](#); Symbol: [ER\\_IB\\_MSG\\_228](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_228](#) was added in 8.0.11.
  - Error number: [MY-012054](#); Symbol: [ER\\_IB\\_MSG\\_229](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_229](#) was added in 8.0.11.
  - Error number: [MY-012055](#); Symbol: [ER\\_IB\\_MSG\\_230](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_230](#) was added in 8.0.11.
  - Error number: [MY-012056](#); Symbol: [ER\\_IB\\_MSG\\_231](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_231](#) was added in 8.0.11.
  - Error number: [MY-012057](#); Symbol: [ER\\_IB\\_MSG\\_232](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_232](#) was added in 8.0.11.

- 
- Error number: [MY-012058](#); Symbol: [ER\\_IB\\_MSG\\_233](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_233](#) was added in 8.0.11.
  - Error number: [MY-012059](#); Symbol: [ER\\_IB\\_MSG\\_234](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_234](#) was added in 8.0.11.
  - Error number: [MY-012060](#); Symbol: [ER\\_IB\\_MSG\\_235](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_235](#) was added in 8.0.11.
  - Error number: [MY-012061](#); Symbol: [ER\\_IB\\_MSG\\_236](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_236](#) was added in 8.0.11.
  - Error number: [MY-012062](#); Symbol: [ER\\_IB\\_MSG\\_237](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_237](#) was added in 8.0.11.
  - Error number: [MY-012063](#); Symbol: [ER\\_IB\\_MSG\\_238](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_238](#) was added in 8.0.11.
  - Error number: [MY-012064](#); Symbol: [ER\\_IB\\_MSG\\_239](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_239](#) was added in 8.0.11.
  - Error number: [MY-012065](#); Symbol: [ER\\_IB\\_MSG\\_240](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_240](#) was added in 8.0.11.
  - Error number: [MY-012066](#); Symbol: [ER\\_IB\\_MSG\\_241](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_241](#) was added in 8.0.11.
  - Error number: [MY-012067](#); Symbol: [ER\\_IB\\_MSG\\_242](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_242](#) was added in 8.0.11.

- 
- Error number: [MY-012068](#); Symbol: [ER\\_IB\\_MSG\\_243](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_243](#) was added in 8.0.11.
  - Error number: [MY-012069](#); Symbol: [ER\\_IB\\_MSG\\_244](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_244](#) was added in 8.0.11.
  - Error number: [MY-012070](#); Symbol: [ER\\_IB\\_MSG\\_245](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_245](#) was added in 8.0.11.
  - Error number: [MY-012071](#); Symbol: [ER\\_IB\\_MSG\\_246](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_246](#) was added in 8.0.11.
  - Error number: [MY-012072](#); Symbol: [ER\\_IB\\_MSG\\_247](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_247](#) was added in 8.0.11.
  - Error number: [MY-012073](#); Symbol: [ER\\_IB\\_MSG\\_248](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_248](#) was added in 8.0.11.
  - Error number: [MY-012074](#); Symbol: [ER\\_IB\\_MSG\\_249](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_249](#) was added in 8.0.11.
  - Error number: [MY-012075](#); Symbol: [ER\\_IB\\_MSG\\_250](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_250](#) was added in 8.0.11.
  - Error number: [MY-012076](#); Symbol: [ER\\_IB\\_MSG\\_251](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_251](#) was added in 8.0.11.
  - Error number: [MY-012077](#); Symbol: [ER\\_IB\\_MSG\\_252](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_252](#) was added in 8.0.11.

- 
- Error number: [MY-012078](#); Symbol: [ER\\_IB\\_MSG\\_253](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_253](#) was added in 8.0.11.
  - Error number: [MY-012079](#); Symbol: [ER\\_IB\\_MSG\\_254](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_254](#) was added in 8.0.11.
  - Error number: [MY-012080](#); Symbol: [ER\\_IB\\_MSG\\_255](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_255](#) was added in 8.0.11.
  - Error number: [MY-012081](#); Symbol: [ER\\_IB\\_MSG\\_256](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_256](#) was added in 8.0.11.
  - Error number: [MY-012082](#); Symbol: [ER\\_IB\\_MSG\\_257](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_257](#) was added in 8.0.11.
  - Error number: [MY-012083](#); Symbol: [ER\\_IB\\_MSG\\_258](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_258](#) was added in 8.0.11.
  - Error number: [MY-012084](#); Symbol: [ER\\_IB\\_MSG\\_259](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_259](#) was added in 8.0.11.
  - Error number: [MY-012085](#); Symbol: [ER\\_IB\\_MSG\\_260](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_260](#) was added in 8.0.11.
  - Error number: [MY-012086](#); Symbol: [ER\\_IB\\_MSG\\_261](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_261](#) was added in 8.0.11.
  - Error number: [MY-012087](#); Symbol: [ER\\_IB\\_MSG\\_262](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_262](#) was added in 8.0.11.

- 
- Error number: [MY-012088](#); Symbol: [ER\\_IB\\_MSG\\_263](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_263](#) was added in 8.0.11.
  - Error number: [MY-012089](#); Symbol: [ER\\_IB\\_MSG\\_264](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_264](#) was added in 8.0.11.
  - Error number: [MY-012090](#); Symbol: [ER\\_IB\\_MSG\\_265](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_265](#) was added in 8.0.11.
  - Error number: [MY-012091](#); Symbol: [ER\\_IB\\_MSG\\_266](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_266](#) was added in 8.0.11.
  - Error number: [MY-012092](#); Symbol: [ER\\_IB\\_MSG\\_267](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_267](#) was added in 8.0.11.
  - Error number: [MY-012093](#); Symbol: [ER\\_IB\\_MSG\\_268](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_268](#) was added in 8.0.11.
  - Error number: [MY-012094](#); Symbol: [ER\\_IB\\_MSG\\_269](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_269](#) was added in 8.0.11.
  - Error number: [MY-012095](#); Symbol: [ER\\_IB\\_MSG\\_270](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_270](#) was added in 8.0.11.
  - Error number: [MY-012096](#); Symbol: [ER\\_IB\\_MSG\\_271](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_271](#) was added in 8.0.11.
  - Error number: [MY-012097](#); Symbol: [ER\\_IB\\_MSG\\_272](#); SQLSTATE: [HY000](#)  
Message: Table flags are 0x%lx in the data dictionary but the flags in file %s are 0x%llx!  
[ER\\_IB\\_MSG\\_272](#) was added in 8.0.11.

- 
- Error number: [MY-012098](#); Symbol: [ER\\_IB\\_MSG\\_273](#); SQLSTATE: [HY000](#)  
Message: Can't read encryption key from file %s!  
[ER\\_IB\\_MSG\\_273](#) was added in 8.0.11.
  - Error number: [MY-012099](#); Symbol: [ER\\_IB\\_MSG\\_274](#); SQLSTATE: [HY000](#)  
Message: Cannot close file %s, because n\_pending\_flushes %zu  
[ER\\_IB\\_MSG\\_274](#) was added in 8.0.11, removed after 8.0.27.
  - Error number: [MY-012100](#); Symbol: [ER\\_IB\\_MSG\\_275](#); SQLSTATE: [HY000](#)  
Message: Cannot close file %s, because modification count %lld != flush count %lld  
[ER\\_IB\\_MSG\\_275](#) was added in 8.0.11, removed after 8.0.27.
  - Error number: [MY-012101](#); Symbol: [ER\\_IB\\_MSG\\_276](#); SQLSTATE: [HY000](#)  
Message: Cannot close file %s, because it is in use  
[ER\\_IB\\_MSG\\_276](#) was added in 8.0.11, removed after 8.0.27.
  - Error number: [MY-012102](#); Symbol: [ER\\_IB\\_MSG\\_277](#); SQLSTATE: [HY000](#)  
Message: Open file list len in shard %zu is %llu  
[ER\\_IB\\_MSG\\_277](#) was added in 8.0.11, removed after 8.0.27.
  - Error number: [MY-012103](#); Symbol: [ER\\_IB\\_MSG\\_278](#); SQLSTATE: [HY000](#)  
Message: Tablespace %s, waiting for IO to stop for %lld seconds  
[ER\\_IB\\_MSG\\_278](#) was added in 8.0.11.
  - Error number: [MY-012104](#); Symbol: [ER\\_IB\\_MSG\\_279](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_279](#) was added in 8.0.11, removed after 8.0.27.
  - Error number: [MY-012105](#); Symbol: [ER\\_IB\\_MSG\\_280](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_280](#) was added in 8.0.11.
  - Error number: [MY-012106](#); Symbol: [ER\\_IB\\_MSG\\_281](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_281](#) was added in 8.0.11.
  - Error number: [MY-012107](#); Symbol: [ER\\_IB\\_MSG\\_282](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_282](#) was added in 8.0.11.



- 
- Error number: [MY-012108](#); Symbol: [ER\\_IB\\_MSG\\_283](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_283](#) was added in 8.0.11.
  - Error number: [MY-012109](#); Symbol: [ER\\_IB\\_MSG\\_284](#); SQLSTATE: [HY000](#)  
Message: You must raise the value of innodb\_open\_files in my.cnf! Remember that InnoDB keeps all redo log files and all system tablespace files open for the whole time mysqld is running, and needs to open also some .ibd files if the file-per-table storage model is used. Current open files %zu, max allowed open files %zu.  
[ER\\_IB\\_MSG\\_284](#) was added in 8.0.11.
  - Error number: [MY-012110](#); Symbol: [ER\\_IB\\_MSG\\_285](#); SQLSTATE: [HY000](#)  
Message: Max tablespace id is too high, %lu  
[ER\\_IB\\_MSG\\_285](#) was added in 8.0.11.
  - Error number: [MY-012111](#); Symbol: [ER\\_IB\\_MSG\\_286](#); SQLSTATE: [HY000](#)  
Message: Trying to access missing tablespace %lu  
[ER\\_IB\\_MSG\\_286](#) was added in 8.0.11, removed after 8.0.27.
  - Error number: [MY-012111](#); Symbol: [ER\\_IB\\_WARN\\_ACCESSING\\_NONEXISTINC\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Trying to access missing tablespace %lu  
[ER\\_IB\\_WARN\\_ACCESSING\\_NONEXISTINC\\_SPACE](#) was added in 8.0.28.
  - Error number: [MY-012112](#); Symbol: [ER\\_IB\\_MSG\\_287](#); SQLSTATE: [HY000](#)  
Message: Trying to close/delete tablespace '%s' but there are %lu pending operations on it.  
[ER\\_IB\\_MSG\\_287](#) was added in 8.0.11.
  - Error number: [MY-012113](#); Symbol: [ER\\_IB\\_MSG\\_288](#); SQLSTATE: [HY000](#)  
Message: Trying to delete/close tablespace '%s' but there are %lu flushes and %zu pending I/O's on it.  
[ER\\_IB\\_MSG\\_288](#) was added in 8.0.11.
  - Error number: [MY-012114](#); Symbol: [ER\\_IB\\_MSG\\_289](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_289](#) was added in 8.0.11.
  - Error number: [MY-012115](#); Symbol: [ER\\_IB\\_MSG\\_290](#); SQLSTATE: [HY000](#)  
Message: Cannot delete tablespace %lu because it is not found in the tablespace memory cache.  
[ER\\_IB\\_MSG\\_290](#) was added in 8.0.11, removed after 8.0.17.
  - Error number: [MY-012116](#); Symbol: [ER\\_IB\\_MSG\\_291](#); SQLSTATE: [HY000](#)

---

Message: While deleting tablespace %lu in DISCARD TABLESPACE. File rename/delete failed: %s

[ER\\_IB\\_MSG\\_291](#) was added in 8.0.11.

- Error number: [MY-012117](#); Symbol: [ER\\_IB\\_MSG\\_292](#); SQLSTATE: [HY000](#)

Message: Cannot delete tablespace %lu in DISCARD TABLESPACE: %s

[ER\\_IB\\_MSG\\_292](#) was added in 8.0.11.

- Error number: [MY-012118](#); Symbol: [ER\\_IB\\_MSG\\_293](#); SQLSTATE: [HY000](#)

Message: Cannot rename '%s' to '%s' for space ID %lu because the source file does not exist.

[ER\\_IB\\_MSG\\_293](#) was added in 8.0.11.

- Error number: [MY-012119](#); Symbol: [ER\\_IB\\_MSG\\_294](#); SQLSTATE: [HY000](#)

Message: Cannot rename '%s' to '%s' for space ID %lu because the target file exists. Remove the target file and try again.

[ER\\_IB\\_MSG\\_294](#) was added in 8.0.11.

- Error number: [MY-012120](#); Symbol: [ER\\_IB\\_MSG\\_295](#); SQLSTATE: [HY000](#)

Message: Cannot rename file '%s' (space id %lu) retried %llu times. There are either pending IOs or flushes or the file is being extended.

[ER\\_IB\\_MSG\\_295](#) was added in 8.0.11.

- Error number: [MY-012121](#); Symbol: [ER\\_IB\\_MSG\\_296](#); SQLSTATE: [HY000](#)

Message: Cannot find space id %lu in the tablespace memory cache, though the file '%s' in a rename operation should have that ID.

[ER\\_IB\\_MSG\\_296](#) was added in 8.0.11.

- Error number: [MY-012122](#); Symbol: [ER\\_IB\\_MSG\\_297](#); SQLSTATE: [HY000](#)

Message: Rename waiting for IO to resume

[ER\\_IB\\_MSG\\_297](#) was added in 8.0.11.

- Error number: [MY-012123](#); Symbol: [ER\\_IB\\_MSG\\_298](#); SQLSTATE: [HY000](#)

Message: Cannot find tablespace for '%s' in the tablespace memory cache

[ER\\_IB\\_MSG\\_298](#) was added in 8.0.11.

- Error number: [MY-012124](#); Symbol: [ER\\_IB\\_MSG\\_299](#); SQLSTATE: [HY000](#)

Message: Cannot find tablespace for '%s' in the tablespace memory cache

[ER\\_IB\\_MSG\\_299](#) was added in 8.0.11.

- Error number: [MY-012125](#); Symbol: [ER\\_IB\\_MSG\\_300](#); SQLSTATE: [HY000](#)

Message: Tablespace '%s' is already in the tablespace memory cache

---

[ER\\_IB\\_MSG\\_300](#) was added in 8.0.11.

- Error number: [MY-012126](#); Symbol: [ER\\_IB\\_MSG\\_301](#); SQLSTATE: [HY000](#)

Message: Cannot create file '%s'

[ER\\_IB\\_MSG\\_301](#) was added in 8.0.11.

- Error number: [MY-012127](#); Symbol: [ER\\_IB\\_MSG\\_302](#); SQLSTATE: [HY000](#)

Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.

[ER\\_IB\\_MSG\\_302](#) was added in 8.0.11, removed after 8.0.16.

- Error number: [MY-012127](#); Symbol: [ER\\_IB\\_MSG\\_UNEXPECTED\\_FILE\\_EXISTS](#); SQLSTATE: [HY000](#)

Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.

[ER\\_IB\\_MSG\\_UNEXPECTED\\_FILE\\_EXISTS](#) was added in 8.0.17.

- Error number: [MY-012128](#); Symbol: [ER\\_IB\\_MSG\\_303](#); SQLSTATE: [HY000](#)

Message: posix\_fallocate(): Failed to preallocate data for file %s, desired size %llu Operating system error number %d - %s. Check that the disk is not full or a disk quota exceeded. Make sure the file system supports this function. Refer to your operating system documentation for operating system error code information.

[ER\\_IB\\_MSG\\_303](#) was added in 8.0.11.

- Error number: [MY-012129](#); Symbol: [ER\\_IB\\_MSG\\_304](#); SQLSTATE: [HY000](#)

Message: Could not write the first page to tablespace '%s'

[ER\\_IB\\_MSG\\_304](#) was added in 8.0.11.

- Error number: [MY-012130](#); Symbol: [ER\\_IB\\_MSG\\_305](#); SQLSTATE: [HY000](#)

Message: File flush of tablespace '%s' failed

[ER\\_IB\\_MSG\\_305](#) was added in 8.0.11.

- Error number: [MY-012131](#); Symbol: [ER\\_IB\\_MSG\\_306](#); SQLSTATE: [HY000](#)

Message: Could not find a valid tablespace file for '%s'. %s

[ER\\_IB\\_MSG\\_306](#) was added in 8.0.11.

- Error number: [MY-012132](#); Symbol: [ER\\_IB\\_MSG\\_307](#); SQLSTATE: [HY000](#)

Message: Ignoring data file '%s' with space ID %lu. Another data file called '%s' exists with the same space ID

---

[ER\\_IB\\_MSG\\_307](#) was added in 8.0.11.

- Error number: [MY-012133](#); Symbol: [ER\\_IB\\_MSG\\_308](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_308](#) was added in 8.0.11.

- Error number: [MY-012134](#); Symbol: [ER\\_IB\\_MSG\\_309](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_309](#) was added in 8.0.11.

- Error number: [MY-012135](#); Symbol: [ER\\_IB\\_MSG\\_310](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_310](#) was added in 8.0.11.

- Error number: [MY-012136](#); Symbol: [ER\\_IB\\_MSG\\_311](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_311](#) was added in 8.0.11.

- Error number: [MY-012137](#); Symbol: [ER\\_IB\\_MSG\\_312](#); SQLSTATE: [HY000](#)

Message: Can't set encryption information for tablespace %s!

[ER\\_IB\\_MSG\\_312](#) was added in 8.0.11.

- Error number: [MY-012138](#); Symbol: [ER\\_IB\\_MSG\\_313](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_313](#) was added in 8.0.11.

- Error number: [MY-012139](#); Symbol: [ER\\_IB\\_MSG\\_314](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_314](#) was added in 8.0.11.

- Error number: [MY-012140](#); Symbol: [ER\\_IB\\_MSG\\_315](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_315](#) was added in 8.0.11.

- Error number: [MY-012141](#); Symbol: [ER\\_IB\\_MSG\\_316](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_316](#) was added in 8.0.11.

- Error number: [MY-012142](#); Symbol: [ER\\_IB\\_MSG\\_317](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_317](#) was added in 8.0.11.

- Error number: [MY-012143](#); Symbol: [ER\\_IB\\_MSG\\_318](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_318](#) was added in 8.0.11.

- Error number: [MY-012144](#); Symbol: [ER\\_IB\\_MSG\\_319](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_319](#) was added in 8.0.11.

- Error number: [MY-012145](#); Symbol: [ER\\_IB\\_MSG\\_320](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_320](#) was added in 8.0.11.

- Error number: [MY-012146](#); Symbol: [ER\\_IB\\_MSG\\_321](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_321](#) was added in 8.0.11.

- Error number: [MY-012147](#); Symbol: [ER\\_IB\\_MSG\\_322](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_322](#) was added in 8.0.11.

- Error number: [MY-012148](#); Symbol: [ER\\_IB\\_MSG\\_323](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_323](#) was added in 8.0.11.

- Error number: [MY-012149](#); Symbol: [ER\\_IB\\_MSG\\_324](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_324](#) was added in 8.0.11.

- Error number: [MY-012150](#); Symbol: [ER\\_IB\\_MSG\\_325](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_325](#) was added in 8.0.11.

- Error number: [MY-012151](#); Symbol: [ER\\_IB\\_MSG\\_326](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_326](#) was added in 8.0.11.

- Error number: [MY-012152](#); Symbol: [ER\\_IB\\_MSG\\_327](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_327](#) was added in 8.0.11, removed after 8.0.27.

- Error number: [MY-012153](#); Symbol: [ER\\_IB\\_MSG\\_328](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_328](#) was added in 8.0.11.

- Error number: [MY-012154](#); Symbol: [ER\\_IB\\_MSG\\_329](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_329](#) was added in 8.0.11.

- Error number: [MY-012155](#); Symbol: [ER\\_IB\\_MSG\\_330](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_330](#) was added in 8.0.11.

- Error number: [MY-012156](#); Symbol: [ER\\_IB\\_MSG\\_331](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_331](#) was added in 8.0.11.

- Error number: [MY-012157](#); Symbol: [ER\\_IB\\_MSG\\_332](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_332](#) was added in 8.0.11.

- Error number: [MY-012158](#); Symbol: [ER\\_IB\\_MSG\\_333](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_333](#) was added in 8.0.11.

- Error number: [MY-012159](#); Symbol: [ER\\_IB\\_MSG\\_334](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_334](#) was added in 8.0.11.

- Error number: [MY-012160](#); Symbol: [ER\\_IB\\_MSG\\_335](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_335](#) was added in 8.0.11.

- Error number: [MY-012161](#); Symbol: [ER\\_IB\\_MSG\\_336](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_336](#) was added in 8.0.11.

- Error number: [MY-012162](#); Symbol: [ER\\_IB\\_MSG\\_337](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_337](#) was added in 8.0.11.

- Error number: [MY-012163](#); Symbol: [ER\\_IB\\_MSG\\_338](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_338](#) was added in 8.0.11.

- Error number: [MY-012164](#); Symbol: [ER\\_IB\\_MSG\\_339](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_339](#) was added in 8.0.11.

- Error number: [MY-012165](#); Symbol: [ER\\_IB\\_MSG\\_340](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_340](#) was added in 8.0.11.

- Error number: [MY-012166](#); Symbol: [ER\\_IB\\_MSG\\_341](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_341](#) was added in 8.0.11.

- Error number: [MY-012167](#); Symbol: [ER\\_IB\\_MSG\\_342](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_342](#) was added in 8.0.11.

- Error number: [MY-012168](#); Symbol: [ER\\_IB\\_MSG\\_343](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_343](#) was added in 8.0.11.

- Error number: [MY-012169](#); Symbol: [ER\\_IB\\_MSG\\_344](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_344](#) was added in 8.0.11.

- Error number: [MY-012170](#); Symbol: [ER\\_IB\\_MSG\\_345](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_345](#) was added in 8.0.11.

- Error number: [MY-012171](#); Symbol: [ER\\_IB\\_MSG\\_346](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_346](#) was added in 8.0.11.

- Error number: [MY-012172](#); Symbol: [ER\\_IB\\_MSG\\_347](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_347](#) was added in 8.0.11.

- Error number: [MY-012173](#); Symbol: [ER\\_IB\\_MSG\\_348](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_348](#) was added in 8.0.11.

- Error number: [MY-012174](#); Symbol: [ER\\_IB\\_MSG\\_349](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_349](#) was added in 8.0.11.

- Error number: [MY-012175](#); Symbol: [ER\\_IB\\_MSG\\_350](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_350](#) was added in 8.0.11.

- Error number: [MY-012176](#); Symbol: [ER\\_IB\\_MSG\\_351](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_351](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012177](#); Symbol: [ER\\_IB\\_MSG\\_352](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_352](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012177](#); Symbol: [ER\\_IB\\_MSG\\_UNPROTECTED\\_LOCATION\\_ALLOWED](#); SQLSTATE: [HY000](#)

Message: The datafile '%s' for tablespace %s is in an unprotected location. This file cannot be recovered after a crash until this location is added to innodb\_directories.

[ER\\_IB\\_MSG\\_UNPROTECTED\\_LOCATION\\_ALLOWED](#) was added in 8.0.21.

- Error number: [MY-012178](#); Symbol: [ER\\_IB\\_MSG\\_353](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_353](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012179](#); Symbol: [ER\\_IB\\_MSG\\_354](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_354](#) was added in 8.0.11.

- Error number: [MY-012180](#); Symbol: [ER\\_IB\\_MSG\\_355](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_355](#) was added in 8.0.11.

- Error number: [MY-012181](#); Symbol: [ER\\_IB\\_MSG\\_356](#); SQLSTATE: [HY000](#)



---

Message: %s

[ER\\_IB\\_MSG\\_356](#) was added in 8.0.11.

- Error number: [MY-012182](#); Symbol: [ER\\_IB\\_MSG\\_357](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_357](#) was added in 8.0.11.

- Error number: [MY-012183](#); Symbol: [ER\\_IB\\_MSG\\_358](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_358](#) was added in 8.0.11.

- Error number: [MY-012184](#); Symbol: [ER\\_IB\\_MSG\\_359](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_359](#) was added in 8.0.11.

- Error number: [MY-012185](#); Symbol: [ER\\_IB\\_MSG\\_360](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_360](#) was added in 8.0.11.

- Error number: [MY-012186](#); Symbol: [ER\\_IB\\_MSG\\_361](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_361](#) was added in 8.0.11.

- Error number: [MY-012187](#); Symbol: [ER\\_IB\\_MSG\\_362](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_362](#) was added in 8.0.11.

- Error number: [MY-012188](#); Symbol: [ER\\_IB\\_MSG\\_363](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_363](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012189](#); Symbol: [ER\\_IB\\_MSG\\_364](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_364](#) was added in 8.0.11.

- Error number: [MY-012190](#); Symbol: [ER\\_IB\\_MSG\\_365](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_365](#) was added in 8.0.11.

- Error number: [MY-012191](#); Symbol: [ER\\_IB\\_MSG\\_366](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_366](#) was added in 8.0.11, removed after 8.0.18.

- Error number: [MY-012191](#); Symbol: [ER\\_IB\\_MSG\\_IGNORE\\_SCAN\\_PATH](#); SQLSTATE: [HY000](#)

Message: Scan path '%s' is ignored because %s

[ER\\_IB\\_MSG\\_IGNORE\\_SCAN\\_PATH](#) was added in 8.0.19.

- Error number: [MY-012192](#); Symbol: [ER\\_IB\\_MSG\\_367](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_367](#) was added in 8.0.11.

- Error number: [MY-012193](#); Symbol: [ER\\_IB\\_MSG\\_368](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_368](#) was added in 8.0.11.

- Error number: [MY-012194](#); Symbol: [ER\\_IB\\_MSG\\_369](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_369](#) was added in 8.0.11.

- Error number: [MY-012195](#); Symbol: [ER\\_IB\\_MSG\\_370](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_370](#) was added in 8.0.11.

- Error number: [MY-012196](#); Symbol: [ER\\_IB\\_MSG\\_371](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_371](#) was added in 8.0.11.

- Error number: [MY-012197](#); Symbol: [ER\\_IB\\_MSG\\_372](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_372](#) was added in 8.0.11.

- Error number: [MY-012198](#); Symbol: [ER\\_IB\\_MSG\\_373](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_373](#) was added in 8.0.11.

- Error number: [MY-012199](#); Symbol: [ER\\_IB\\_MSG\\_374](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_374](#) was added in 8.0.11.

- Error number: [MY-012200](#); Symbol: [ER\\_IB\\_MSG\\_375](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_375](#) was added in 8.0.11.

- Error number: [MY-012201](#); Symbol: [ER\\_IB\\_MSG\\_376](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_376](#) was added in 8.0.11.

- Error number: [MY-012202](#); Symbol: [ER\\_IB\\_MSG\\_377](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_377](#) was added in 8.0.11.

- Error number: [MY-012203](#); Symbol: [ER\\_IB\\_MSG\\_378](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_378](#) was added in 8.0.11.

- Error number: [MY-012204](#); Symbol: [ER\\_IB\\_MSG\\_379](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_379](#) was added in 8.0.11.

- Error number: [MY-012205](#); Symbol: [ER\\_IB\\_MSG\\_380](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_380](#) was added in 8.0.11.

- Error number: [MY-012206](#); Symbol: [ER\\_IB\\_MSG\\_381](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_381](#) was added in 8.0.11.

- Error number: [MY-012207](#); Symbol: [ER\\_IB\\_MSG\\_382](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_382](#) was added in 8.0.11.

- Error number: [MY-012208](#); Symbol: [ER\\_IB\\_MSG\\_383](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_383](#) was added in 8.0.11.

- Error number: [MY-012209](#); Symbol: [ER\\_IB\\_MSG\\_384](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_384](#) was added in 8.0.11.

- Error number: [MY-012210](#); Symbol: [ER\\_IB\\_MSG\\_385](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_385](#) was added in 8.0.11.

- Error number: [MY-012211](#); Symbol: [ER\\_IB\\_MSG\\_386](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_386](#) was added in 8.0.11.

- Error number: [MY-012212](#); Symbol: [ER\\_IB\\_MSG\\_387](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_387](#) was added in 8.0.11.

- Error number: [MY-012213](#); Symbol: [ER\\_IB\\_MSG\\_388](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_388](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012213](#); Symbol: [ER\\_IB\\_MSG\\_GENERAL\\_TABLESPACE\\_UNDER\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: A general tablespace cannot be located under the datadir. Cannot open file '%s'.

[ER\\_IB\\_MSG\\_GENERAL\\_TABLESPACE\\_UNDER\\_DATADIR](#) was added in 8.0.21.

- Error number: [MY-012214](#); Symbol: [ER\\_IB\\_MSG\\_389](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_389](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012214](#); Symbol: [ER\\_IB\\_MSG\\_IMPLICIT\\_TABLESPACE\\_IN\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: A file-per-table tablespace cannot be located in the datadir. Cannot open file '%s'.

[ER\\_IB\\_MSG\\_IMPLICIT\\_TABLESPACE\\_IN\\_DATADIR](#) was added in 8.0.21.

- Error number: [MY-012215](#); Symbol: [ER\\_IB\\_MSG\\_390](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_390](#) was added in 8.0.11.

- Error number: [MY-012216](#); Symbol: [ER\\_IB\\_MSG\\_391](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_391](#) was added in 8.0.11.

- Error number: [MY-012217](#); Symbol: [ER\\_IB\\_MSG\\_392](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_392](#) was added in 8.0.11.

- 
- Error number: [MY-012218](#); Symbol: [ER\\_IB\\_MSG\\_393](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_393](#) was added in 8.0.11.
  - Error number: [MY-012219](#); Symbol: [ER\\_IB\\_MSG\\_394](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_394](#) was added in 8.0.11.
  - Error number: [MY-012220](#); Symbol: [ER\\_IB\\_MSG\\_395](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_395](#) was added in 8.0.11.
  - Error number: [MY-012221](#); Symbol: [ER\\_IB\\_MSG\\_396](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_396](#) was added in 8.0.11.
  - Error number: [MY-012222](#); Symbol: [ER\\_IB\\_MSG\\_397](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_397](#) was added in 8.0.11.
  - Error number: [MY-012223](#); Symbol: [ER\\_IB\\_MSG\\_398](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_398](#) was added in 8.0.11.
  - Error number: [MY-012224](#); Symbol: [ER\\_IB\\_MSG\\_399](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_399](#) was added in 8.0.11.
  - Error number: [MY-012225](#); Symbol: [ER\\_IB\\_MSG\\_400](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_400](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012226](#); Symbol: [ER\\_IB\\_MSG\\_401](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_401](#) was added in 8.0.11.
  - Error number: [MY-012227](#); Symbol: [ER\\_IB\\_MSG\\_402](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_402](#) was added in 8.0.11.

- 
- Error number: [MY-012228](#); Symbol: [ER\\_IB\\_MSG\\_403](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_403](#) was added in 8.0.11.
  - Error number: [MY-012229](#); Symbol: [ER\\_IB\\_MSG\\_404](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_404](#) was added in 8.0.11.
  - Error number: [MY-012230](#); Symbol: [ER\\_IB\\_MSG\\_405](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_405](#) was added in 8.0.11.
  - Error number: [MY-012231](#); Symbol: [ER\\_IB\\_MSG\\_406](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_406](#) was added in 8.0.11.
  - Error number: [MY-012232](#); Symbol: [ER\\_IB\\_MSG\\_407](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_407](#) was added in 8.0.11.
  - Error number: [MY-012233](#); Symbol: [ER\\_IB\\_MSG\\_408](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_408](#) was added in 8.0.11.
  - Error number: [MY-012234](#); Symbol: [ER\\_IB\\_MSG\\_409](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_409](#) was added in 8.0.11.
  - Error number: [MY-012235](#); Symbol: [ER\\_IB\\_MSG\\_410](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_410](#) was added in 8.0.11.
  - Error number: [MY-012236](#); Symbol: [ER\\_IB\\_MSG\\_411](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_411](#) was added in 8.0.11.
  - Error number: [MY-012237](#); Symbol: [ER\\_IB\\_MSG\\_412](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_412](#) was added in 8.0.11.

- 
- Error number: [MY-012238](#); Symbol: [ER\\_IB\\_MSG\\_413](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_413](#) was added in 8.0.11.
  - Error number: [MY-012239](#); Symbol: [ER\\_IB\\_MSG\\_414](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_414](#) was added in 8.0.11.
  - Error number: [MY-012240](#); Symbol: [ER\\_IB\\_MSG\\_415](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_415](#) was added in 8.0.11.
  - Error number: [MY-012241](#); Symbol: [ER\\_IB\\_MSG\\_416](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_416](#) was added in 8.0.11.
  - Error number: [MY-012242](#); Symbol: [ER\\_IB\\_MSG\\_417](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_417](#) was added in 8.0.11.
  - Error number: [MY-012243](#); Symbol: [ER\\_IB\\_MSG\\_418](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_418](#) was added in 8.0.11.
  - Error number: [MY-012244](#); Symbol: [ER\\_IB\\_MSG\\_419](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_419](#) was added in 8.0.11.
  - Error number: [MY-012245](#); Symbol: [ER\\_IB\\_MSG\\_420](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_420](#) was added in 8.0.11.
  - Error number: [MY-012246](#); Symbol: [ER\\_IB\\_MSG\\_421](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_421](#) was added in 8.0.11.
  - Error number: [MY-012247](#); Symbol: [ER\\_IB\\_MSG\\_422](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_422](#) was added in 8.0.11.

- 
- Error number: [MY-012248](#); Symbol: [ER\\_IB\\_MSG\\_423](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_423](#) was added in 8.0.11.
  - Error number: [MY-012249](#); Symbol: [ER\\_IB\\_MSG\\_424](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_424](#) was added in 8.0.11.
  - Error number: [MY-012250](#); Symbol: [ER\\_IB\\_MSG\\_425](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_425](#) was added in 8.0.11.
  - Error number: [MY-012251](#); Symbol: [ER\\_IB\\_MSG\\_426](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_426](#) was added in 8.0.11.
  - Error number: [MY-012252](#); Symbol: [ER\\_IB\\_MSG\\_427](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_427](#) was added in 8.0.11.
  - Error number: [MY-012253](#); Symbol: [ER\\_IB\\_MSG\\_428](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_428](#) was added in 8.0.11.
  - Error number: [MY-012254](#); Symbol: [ER\\_IB\\_MSG\\_429](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_429](#) was added in 8.0.11.
  - Error number: [MY-012255](#); Symbol: [ER\\_IB\\_MSG\\_430](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_430](#) was added in 8.0.11.
  - Error number: [MY-012256](#); Symbol: [ER\\_IB\\_MSG\\_431](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_431](#) was added in 8.0.11.
  - Error number: [MY-012257](#); Symbol: [ER\\_IB\\_MSG\\_432](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_432](#) was added in 8.0.11.



- 
- Error number: [MY-012258](#); Symbol: [ER\\_IB\\_MSG\\_433](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_433](#) was added in 8.0.11.
  - Error number: [MY-012259](#); Symbol: [ER\\_IB\\_MSG\\_434](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_434](#) was added in 8.0.11.
  - Error number: [MY-012260](#); Symbol: [ER\\_IB\\_MSG\\_435](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_435](#) was added in 8.0.11.
  - Error number: [MY-012261](#); Symbol: [ER\\_IB\\_MSG\\_436](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_436](#) was added in 8.0.11.
  - Error number: [MY-012262](#); Symbol: [ER\\_IB\\_MSG\\_437](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_437](#) was added in 8.0.11.
  - Error number: [MY-012263](#); Symbol: [ER\\_IB\\_MSG\\_438](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_438](#) was added in 8.0.11.
  - Error number: [MY-012264](#); Symbol: [ER\\_IB\\_MSG\\_439](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_439](#) was added in 8.0.11.
  - Error number: [MY-012265](#); Symbol: [ER\\_IB\\_MSG\\_440](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_440](#) was added in 8.0.11.
  - Error number: [MY-012266](#); Symbol: [ER\\_IB\\_MSG\\_441](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_441](#) was added in 8.0.11.
  - Error number: [MY-012267](#); Symbol: [ER\\_IB\\_MSG\\_442](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_442](#) was added in 8.0.11.

- 
- Error number: [MY-012268](#); Symbol: [ER\\_IB\\_MSG\\_443](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_443](#) was added in 8.0.11.
  - Error number: [MY-012269](#); Symbol: [ER\\_IB\\_MSG\\_444](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_444](#) was added in 8.0.11, removed after 8.0.36.
  - Error number: [MY-012270](#); Symbol: [ER\\_IB\\_MSG\\_445](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_445](#) was added in 8.0.11.
  - Error number: [MY-012271](#); Symbol: [ER\\_IB\\_MSG\\_446](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_446](#) was added in 8.0.11.
  - Error number: [MY-012272](#); Symbol: [ER\\_IB\\_MSG\\_447](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_447](#) was added in 8.0.11.
  - Error number: [MY-012273](#); Symbol: [ER\\_IB\\_MSG\\_448](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_448](#) was added in 8.0.11.
  - Error number: [MY-012274](#); Symbol: [ER\\_IB\\_MSG\\_449](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_449](#) was added in 8.0.11.
  - Error number: [MY-012275](#); Symbol: [ER\\_IB\\_MSG\\_450](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_450](#) was added in 8.0.11.
  - Error number: [MY-012276](#); Symbol: [ER\\_IB\\_MSG\\_451](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_451](#) was added in 8.0.11.
  - Error number: [MY-012277](#); Symbol: [ER\\_IB\\_MSG\\_452](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_452](#) was added in 8.0.11.

- 
- Error number: [MY-012278](#); Symbol: [ER\\_IB\\_MSG\\_453](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_453](#) was added in 8.0.11.
  - Error number: [MY-012279](#); Symbol: [ER\\_IB\\_MSG\\_454](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_454](#) was added in 8.0.11.
  - Error number: [MY-012280](#); Symbol: [ER\\_IB\\_MSG\\_455](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_455](#) was added in 8.0.11.
  - Error number: [MY-012281](#); Symbol: [ER\\_IB\\_MSG\\_456](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_456](#) was added in 8.0.11.
  - Error number: [MY-012282](#); Symbol: [ER\\_IB\\_MSG\\_457](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_457](#) was added in 8.0.11.
  - Error number: [MY-012283](#); Symbol: [ER\\_IB\\_MSG\\_458](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_458](#) was added in 8.0.11.
  - Error number: [MY-012284](#); Symbol: [ER\\_IB\\_MSG\\_459](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_459](#) was added in 8.0.11.
  - Error number: [MY-012285](#); Symbol: [ER\\_IB\\_MSG\\_460](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_460](#) was added in 8.0.11.
  - Error number: [MY-012286](#); Symbol: [ER\\_IB\\_MSG\\_461](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_461](#) was added in 8.0.11.
  - Error number: [MY-012287](#); Symbol: [ER\\_IB\\_MSG\\_462](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_462](#) was added in 8.0.11.

- 
- Error number: [MY-012288](#); Symbol: [ER\\_IB\\_MSG\\_463](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_463](#) was added in 8.0.11.
  - Error number: [MY-012289](#); Symbol: [ER\\_IB\\_MSG\\_464](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_464](#) was added in 8.0.11.
  - Error number: [MY-012290](#); Symbol: [ER\\_IB\\_MSG\\_465](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_465](#) was added in 8.0.11.
  - Error number: [MY-012291](#); Symbol: [ER\\_IB\\_MSG\\_466](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_466](#) was added in 8.0.11.
  - Error number: [MY-012292](#); Symbol: [ER\\_IB\\_MSG\\_467](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_467](#) was added in 8.0.11.
  - Error number: [MY-012293](#); Symbol: [ER\\_IB\\_MSG\\_468](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_468](#) was added in 8.0.11.
  - Error number: [MY-012294](#); Symbol: [ER\\_IB\\_MSG\\_469](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_469](#) was added in 8.0.11.
  - Error number: [MY-012295](#); Symbol: [ER\\_IB\\_MSG\\_470](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_470](#) was added in 8.0.11.
  - Error number: [MY-012296](#); Symbol: [ER\\_IB\\_MSG\\_471](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_471](#) was added in 8.0.11.
  - Error number: [MY-012297](#); Symbol: [ER\\_IB\\_MSG\\_472](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_472](#) was added in 8.0.11.

- 
- Error number: [MY-012298](#); Symbol: [ER\\_IB\\_MSG\\_473](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_473](#) was added in 8.0.11.
  - Error number: [MY-012299](#); Symbol: [ER\\_IB\\_MSG\\_474](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_474](#) was added in 8.0.11.
  - Error number: [MY-012300](#); Symbol: [ER\\_IB\\_MSG\\_475](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_475](#) was added in 8.0.11.
  - Error number: [MY-012301](#); Symbol: [ER\\_IB\\_MSG\\_476](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_476](#) was added in 8.0.11.
  - Error number: [MY-012302](#); Symbol: [ER\\_IB\\_MSG\\_477](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_477](#) was added in 8.0.11.
  - Error number: [MY-012303](#); Symbol: [ER\\_IB\\_MSG\\_478](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_478](#) was added in 8.0.11.
  - Error number: [MY-012304](#); Symbol: [ER\\_IB\\_MSG\\_479](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_479](#) was added in 8.0.11.
  - Error number: [MY-012305](#); Symbol: [ER\\_IB\\_MSG\\_480](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_480](#) was added in 8.0.11.
  - Error number: [MY-012306](#); Symbol: [ER\\_IB\\_MSG\\_481](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_481](#) was added in 8.0.11.
  - Error number: [MY-012307](#); Symbol: [ER\\_IB\\_MSG\\_482](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_482](#) was added in 8.0.11.

- 
- Error number: [MY-012308](#); Symbol: [ER\\_IB\\_MSG\\_483](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_483](#) was added in 8.0.11.
  - Error number: [MY-012309](#); Symbol: [ER\\_IB\\_MSG\\_484](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_484](#) was added in 8.0.11.
  - Error number: [MY-012310](#); Symbol: [ER\\_IB\\_MSG\\_485](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_485](#) was added in 8.0.11.
  - Error number: [MY-012311](#); Symbol: [ER\\_IB\\_MSG\\_486](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_486](#) was added in 8.0.11.
  - Error number: [MY-012312](#); Symbol: [ER\\_IB\\_MSG\\_487](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_487](#) was added in 8.0.11.
  - Error number: [MY-012313](#); Symbol: [ER\\_IB\\_MSG\\_488](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_488](#) was added in 8.0.11.
  - Error number: [MY-012314](#); Symbol: [ER\\_IB\\_MSG\\_489](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_489](#) was added in 8.0.11.
  - Error number: [MY-012315](#); Symbol: [ER\\_IB\\_MSG\\_490](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_490](#) was added in 8.0.11.
  - Error number: [MY-012316](#); Symbol: [ER\\_IB\\_MSG\\_491](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_491](#) was added in 8.0.11.
  - Error number: [MY-012317](#); Symbol: [ER\\_IB\\_MSG\\_492](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_492](#) was added in 8.0.11.

- 
- Error number: [MY-012318](#); Symbol: [ER\\_IB\\_MSG\\_493](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_493](#) was added in 8.0.11.
  - Error number: [MY-012319](#); Symbol: [ER\\_IB\\_MSG\\_494](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_494](#) was added in 8.0.11.
  - Error number: [MY-012320](#); Symbol: [ER\\_IB\\_MSG\\_495](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_495](#) was added in 8.0.11.
  - Error number: [MY-012321](#); Symbol: [ER\\_IB\\_MSG\\_496](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_496](#) was added in 8.0.11.
  - Error number: [MY-012322](#); Symbol: [ER\\_IB\\_MSG\\_497](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_497](#) was added in 8.0.11.
  - Error number: [MY-012323](#); Symbol: [ER\\_IB\\_MSG\\_498](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_498](#) was added in 8.0.11.
  - Error number: [MY-012324](#); Symbol: [ER\\_IB\\_MSG\\_499](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_499](#) was added in 8.0.11.
  - Error number: [MY-012325](#); Symbol: [ER\\_IB\\_MSG\\_500](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_500](#) was added in 8.0.11.
  - Error number: [MY-012326](#); Symbol: [ER\\_IB\\_MSG\\_501](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_501](#) was added in 8.0.11.
  - Error number: [MY-012327](#); Symbol: [ER\\_IB\\_MSG\\_502](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_502](#) was added in 8.0.11.

- 
- Error number: [MY-012328](#); Symbol: [ER\\_IB\\_MSG\\_503](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_503](#) was added in 8.0.11.
  - Error number: [MY-012329](#); Symbol: [ER\\_IB\\_MSG\\_504](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_504](#) was added in 8.0.11.
  - Error number: [MY-012330](#); Symbol: [ER\\_IB\\_MSG\\_505](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_505](#) was added in 8.0.11.
  - Error number: [MY-012331](#); Symbol: [ER\\_IB\\_MSG\\_506](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_506](#) was added in 8.0.11.
  - Error number: [MY-012332](#); Symbol: [ER\\_IB\\_MSG\\_507](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_507](#) was added in 8.0.11.
  - Error number: [MY-012333](#); Symbol: [ER\\_IB\\_MSG\\_508](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_508](#) was added in 8.0.11.
  - Error number: [MY-012334](#); Symbol: [ER\\_IB\\_MSG\\_509](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_509](#) was added in 8.0.11.
  - Error number: [MY-012335](#); Symbol: [ER\\_IB\\_MSG\\_510](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_510](#) was added in 8.0.11.
  - Error number: [MY-012336](#); Symbol: [ER\\_IB\\_MSG\\_511](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_511](#) was added in 8.0.11.
  - Error number: [MY-012337](#); Symbol: [ER\\_IB\\_MSG\\_512](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_512](#) was added in 8.0.11.



- 
- Error number: [MY-012338](#); Symbol: [ER\\_IB\\_MSG\\_513](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_513](#) was added in 8.0.11.
  - Error number: [MY-012339](#); Symbol: [ER\\_IB\\_MSG\\_514](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_514](#) was added in 8.0.11.
  - Error number: [MY-012340](#); Symbol: [ER\\_IB\\_MSG\\_515](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_515](#) was added in 8.0.11.
  - Error number: [MY-012341](#); Symbol: [ER\\_IB\\_MSG\\_516](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_516](#) was added in 8.0.11.
  - Error number: [MY-012342](#); Symbol: [ER\\_IB\\_MSG\\_517](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_517](#) was added in 8.0.11.
  - Error number: [MY-012343](#); Symbol: [ER\\_IB\\_MSG\\_518](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_518](#) was added in 8.0.11.
  - Error number: [MY-012344](#); Symbol: [ER\\_IB\\_MSG\\_519](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_519](#) was added in 8.0.11.
  - Error number: [MY-012345](#); Symbol: [ER\\_IB\\_MSG\\_520](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_520](#) was added in 8.0.11.
  - Error number: [MY-012346](#); Symbol: [ER\\_IB\\_MSG\\_521](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_521](#) was added in 8.0.11.
  - Error number: [MY-012347](#); Symbol: [ER\\_IB\\_MSG\\_522](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_522](#) was added in 8.0.11.

- 
- Error number: [MY-012348](#); Symbol: [ER\\_IB\\_MSG\\_523](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_523](#) was added in 8.0.11.
  - Error number: [MY-012349](#); Symbol: [ER\\_IB\\_MSG\\_524](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_524](#) was added in 8.0.11.
  - Error number: [MY-012350](#); Symbol: [ER\\_IB\\_MSG\\_525](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_525](#) was added in 8.0.11.
  - Error number: [MY-012351](#); Symbol: [ER\\_IB\\_MSG\\_526](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_526](#) was added in 8.0.11.
  - Error number: [MY-012352](#); Symbol: [ER\\_IB\\_MSG\\_527](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_527](#) was added in 8.0.11.
  - Error number: [MY-012353](#); Symbol: [ER\\_IB\\_MSG\\_528](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_528](#) was added in 8.0.11, removed after 8.0.18.
  - Error number: [MY-012354](#); Symbol: [ER\\_IB\\_MSG\\_529](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_529](#) was added in 8.0.11, removed after 8.0.18.
  - Error number: [MY-012355](#); Symbol: [ER\\_IB\\_MSG\\_530](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_530](#) was added in 8.0.11.
  - Error number: [MY-012356](#); Symbol: [ER\\_IB\\_MSG\\_531](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_531](#) was added in 8.0.11.
  - Error number: [MY-012357](#); Symbol: [ER\\_IB\\_MSG\\_532](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_532](#) was added in 8.0.11.

- 
- Error number: [MY-012358](#); Symbol: [ER\\_IB\\_MSG\\_533](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_533](#) was added in 8.0.11.
  - Error number: [MY-012359](#); Symbol: [ER\\_IB\\_MSG\\_534](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_534](#) was added in 8.0.11.
  - Error number: [MY-012360](#); Symbol: [ER\\_IB\\_MSG\\_535](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_535](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012361](#); Symbol: [ER\\_IB\\_MSG\\_536](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_536](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012362](#); Symbol: [ER\\_IB\\_MSG\\_537](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_537](#) was added in 8.0.11.
  - Error number: [MY-012363](#); Symbol: [ER\\_IB\\_MSG\\_538](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_538](#) was added in 8.0.11.
  - Error number: [MY-012364](#); Symbol: [ER\\_IB\\_MSG\\_539](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_539](#) was added in 8.0.11.
  - Error number: [MY-012365](#); Symbol: [ER\\_IB\\_MSG\\_540](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_540](#) was added in 8.0.11.
  - Error number: [MY-012366](#); Symbol: [ER\\_IB\\_MSG\\_541](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_541](#) was added in 8.0.11.
  - Error number: [MY-012367](#); Symbol: [ER\\_IB\\_MSG\\_542](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_542](#) was added in 8.0.11.

- 
- Error number: [MY-012368](#); Symbol: [ER\\_IB\\_MSG\\_543](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_543](#) was added in 8.0.11.
  - Error number: [MY-012369](#); Symbol: [ER\\_IB\\_MSG\\_544](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_544](#) was added in 8.0.11.
  - Error number: [MY-012370](#); Symbol: [ER\\_IB\\_MSG\\_545](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_545](#) was added in 8.0.11.
  - Error number: [MY-012371](#); Symbol: [ER\\_IB\\_MSG\\_546](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_546](#) was added in 8.0.11.
  - Error number: [MY-012372](#); Symbol: [ER\\_IB\\_MSG\\_547](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_547](#) was added in 8.0.11.
  - Error number: [MY-012373](#); Symbol: [ER\\_IB\\_MSG\\_548](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_548](#) was added in 8.0.11.
  - Error number: [MY-012374](#); Symbol: [ER\\_IB\\_MSG\\_549](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_549](#) was added in 8.0.11.
  - Error number: [MY-012375](#); Symbol: [ER\\_IB\\_MSG\\_550](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_550](#) was added in 8.0.11.
  - Error number: [MY-012376](#); Symbol: [ER\\_IB\\_MSG\\_551](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_551](#) was added in 8.0.11.
  - Error number: [MY-012377](#); Symbol: [ER\\_IB\\_MSG\\_552](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_552](#) was added in 8.0.11.

- 
- Error number: [MY-012378](#); Symbol: [ER\\_IB\\_MSG\\_553](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_553](#) was added in 8.0.11.
  - Error number: [MY-012379](#); Symbol: [ER\\_IB\\_MSG\\_554](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_554](#) was added in 8.0.11.
  - Error number: [MY-012380](#); Symbol: [ER\\_IB\\_MSG\\_555](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_555](#) was added in 8.0.11.
  - Error number: [MY-012381](#); Symbol: [ER\\_IB\\_MSG\\_556](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_556](#) was added in 8.0.11.
  - Error number: [MY-012382](#); Symbol: [ER\\_IB\\_MSG\\_557](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_557](#) was added in 8.0.11.
  - Error number: [MY-012383](#); Symbol: [ER\\_IB\\_MSG\\_558](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_558](#) was added in 8.0.11.
  - Error number: [MY-012384](#); Symbol: [ER\\_IB\\_MSG\\_559](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_559](#) was added in 8.0.11.
  - Error number: [MY-012385](#); Symbol: [ER\\_IB\\_MSG\\_560](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_560](#) was added in 8.0.11.
  - Error number: [MY-012386](#); Symbol: [ER\\_IB\\_MSG\\_561](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_561](#) was added in 8.0.11.
  - Error number: [MY-012387](#); Symbol: [ER\\_IB\\_MSG\\_562](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_562](#) was added in 8.0.11.

- 
- Error number: [MY-012388](#); Symbol: [ER\\_IB\\_MSG\\_563](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_563](#) was added in 8.0.11.
  - Error number: [MY-012389](#); Symbol: [ER\\_IB\\_MSG\\_564](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_564](#) was added in 8.0.11.
  - Error number: [MY-012390](#); Symbol: [ER\\_IB\\_MSG\\_565](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_565](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012390](#); Symbol: [ER\\_IB\\_MSG\\_INVALID\\_LOCATION\\_FOR\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot create a tablespace for table %s because the directory is not a valid location. %s  
[ER\\_IB\\_MSG\\_INVALID\\_LOCATION\\_FOR\\_TABLE](#) was added in 8.0.21.
  - Error number: [MY-012391](#); Symbol: [ER\\_IB\\_MSG\\_566](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_566](#) was added in 8.0.11.
  - Error number: [MY-012392](#); Symbol: [ER\\_IB\\_MSG\\_567](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_567](#) was added in 8.0.11.
  - Error number: [MY-012393](#); Symbol: [ER\\_IB\\_MSG\\_568](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_568](#) was added in 8.0.11.
  - Error number: [MY-012394](#); Symbol: [ER\\_IB\\_MSG\\_569](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_569](#) was added in 8.0.11.
  - Error number: [MY-012395](#); Symbol: [ER\\_IB\\_MSG\\_570](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_570](#) was added in 8.0.11.
  - Error number: [MY-012396](#); Symbol: [ER\\_IB\\_MSG\\_571](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_571](#) was added in 8.0.11.

- 
- Error number: [MY-012397](#); Symbol: [ER\\_IB\\_MSG\\_572](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_572](#) was added in 8.0.11, removed after 8.0.18.
  - Error number: [MY-012398](#); Symbol: [ER\\_IB\\_MSG\\_573](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_573](#) was added in 8.0.11.
  - Error number: [MY-012399](#); Symbol: [ER\\_IB\\_MSG\\_574](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_574](#) was added in 8.0.11.
  - Error number: [MY-012400](#); Symbol: [ER\\_IB\\_MSG\\_575](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_575](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012401](#); Symbol: [ER\\_IB\\_MSG\\_576](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_576](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012402](#); Symbol: [ER\\_IB\\_MSG\\_577](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_577](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012403](#); Symbol: [ER\\_IB\\_MSG\\_578](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_578](#) was added in 8.0.11.
  - Error number: [MY-012404](#); Symbol: [ER\\_IB\\_MSG\\_579](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_579](#) was added in 8.0.11.
  - Error number: [MY-012405](#); Symbol: [ER\\_IB\\_MSG\\_580](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_580](#) was added in 8.0.11.
  - Error number: [MY-012406](#); Symbol: [ER\\_IB\\_MSG\\_581](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_581](#) was added in 8.0.11.

- 
- Error number: [MY-012407](#); Symbol: [ER\\_IB\\_MSG\\_582](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_582](#) was added in 8.0.11.
  - Error number: [MY-012408](#); Symbol: [ER\\_IB\\_MSG\\_583](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_583](#) was added in 8.0.11.
  - Error number: [MY-012409](#); Symbol: [ER\\_IB\\_MSG\\_584](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_584](#) was added in 8.0.11.
  - Error number: [MY-012410](#); Symbol: [ER\\_IB\\_MSG\\_585](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_585](#) was added in 8.0.11.
  - Error number: [MY-012411](#); Symbol: [ER\\_IB\\_MSG\\_586](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_586](#) was added in 8.0.11.
  - Error number: [MY-012412](#); Symbol: [ER\\_IB\\_MSG\\_587](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_587](#) was added in 8.0.11.
  - Error number: [MY-012413](#); Symbol: [ER\\_IB\\_MSG\\_588](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_588](#) was added in 8.0.11.
  - Error number: [MY-012414](#); Symbol: [ER\\_IB\\_MSG\\_589](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_589](#) was added in 8.0.11.
  - Error number: [MY-012415](#); Symbol: [ER\\_IB\\_MSG\\_590](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_590](#) was added in 8.0.11.
  - Error number: [MY-012416](#); Symbol: [ER\\_IB\\_MSG\\_591](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_591](#) was added in 8.0.11.



- 
- Error number: [MY-012417](#); Symbol: [ER\\_IB\\_MSG\\_592](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_592](#) was added in 8.0.11.
  - Error number: [MY-012418](#); Symbol: [ER\\_IB\\_MSG\\_593](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_593](#) was added in 8.0.11.
  - Error number: [MY-012419](#); Symbol: [ER\\_IB\\_MSG\\_594](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_594](#) was added in 8.0.11.
  - Error number: [MY-012420](#); Symbol: [ER\\_IB\\_MSG\\_595](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_595](#) was added in 8.0.11.
  - Error number: [MY-012421](#); Symbol: [ER\\_IB\\_MSG\\_596](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_596](#) was added in 8.0.11.
  - Error number: [MY-012422](#); Symbol: [ER\\_IB\\_MSG\\_597](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_597](#) was added in 8.0.11.
  - Error number: [MY-012423](#); Symbol: [ER\\_IB\\_MSG\\_598](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_598](#) was added in 8.0.11.
  - Error number: [MY-012424](#); Symbol: [ER\\_IB\\_MSG\\_599](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_599](#) was added in 8.0.11.
  - Error number: [MY-012425](#); Symbol: [ER\\_IB\\_MSG\\_600](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_600](#) was added in 8.0.11.
  - Error number: [MY-012426](#); Symbol: [ER\\_IB\\_MSG\\_601](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_601](#) was added in 8.0.11.

- 
- Error number: [MY-012427](#); Symbol: [ER\\_IB\\_MSG\\_602](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_602](#) was added in 8.0.11.
  - Error number: [MY-012428](#); Symbol: [ER\\_IB\\_MSG\\_603](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_603](#) was added in 8.0.11.
  - Error number: [MY-012429](#); Symbol: [ER\\_IB\\_MSG\\_604](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_604](#) was added in 8.0.11.
  - Error number: [MY-012430](#); Symbol: [ER\\_IB\\_MSG\\_605](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_605](#) was added in 8.0.11.
  - Error number: [MY-012431](#); Symbol: [ER\\_IB\\_MSG\\_606](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_606](#) was added in 8.0.11.
  - Error number: [MY-012432](#); Symbol: [ER\\_IB\\_MSG\\_607](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_607](#) was added in 8.0.11.
  - Error number: [MY-012433](#); Symbol: [ER\\_IB\\_MSG\\_608](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_608](#) was added in 8.0.11.
  - Error number: [MY-012434](#); Symbol: [ER\\_IB\\_MSG\\_609](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_609](#) was added in 8.0.11.
  - Error number: [MY-012435](#); Symbol: [ER\\_IB\\_MSG\\_610](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_610](#) was added in 8.0.11.
  - Error number: [MY-012436](#); Symbol: [ER\\_IB\\_MSG\\_611](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_611](#) was added in 8.0.11.

- 
- Error number: [MY-012437](#); Symbol: [ER\\_IB\\_MSG\\_612](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_612](#) was added in 8.0.11.
  - Error number: [MY-012438](#); Symbol: [ER\\_IB\\_MSG\\_613](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_613](#) was added in 8.0.11.
  - Error number: [MY-012439](#); Symbol: [ER\\_IB\\_MSG\\_614](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_614](#) was added in 8.0.11.
  - Error number: [MY-012440](#); Symbol: [ER\\_IB\\_MSG\\_615](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_615](#) was added in 8.0.11.
  - Error number: [MY-012441](#); Symbol: [ER\\_IB\\_MSG\\_616](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_616](#) was added in 8.0.11.
  - Error number: [MY-012442](#); Symbol: [ER\\_IB\\_MSG\\_617](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_617](#) was added in 8.0.11.
  - Error number: [MY-012443](#); Symbol: [ER\\_IB\\_MSG\\_618](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_618](#) was added in 8.0.11.
  - Error number: [MY-012444](#); Symbol: [ER\\_IB\\_MSG\\_619](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_619](#) was added in 8.0.11.
  - Error number: [MY-012445](#); Symbol: [ER\\_IB\\_MSG\\_620](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_620](#) was added in 8.0.11.
  - Error number: [MY-012446](#); Symbol: [ER\\_IB\\_MSG\\_621](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_621](#) was added in 8.0.11.

- 
- Error number: [MY-012447](#); Symbol: [ER\\_IB\\_MSG\\_622](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_622](#) was added in 8.0.11.
  - Error number: [MY-012448](#); Symbol: [ER\\_IB\\_MSG\\_623](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_623](#) was added in 8.0.11.
  - Error number: [MY-012449](#); Symbol: [ER\\_IB\\_MSG\\_624](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_624](#) was added in 8.0.11.
  - Error number: [MY-012450](#); Symbol: [ER\\_IB\\_MSG\\_625](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_625](#) was added in 8.0.11.
  - Error number: [MY-012451](#); Symbol: [ER\\_IB\\_MSG\\_626](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_626](#) was added in 8.0.11.
  - Error number: [MY-012452](#); Symbol: [ER\\_IB\\_MSG\\_627](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_627](#) was added in 8.0.11.
  - Error number: [MY-012453](#); Symbol: [ER\\_IB\\_MSG\\_628](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_628](#) was added in 8.0.11.
  - Error number: [MY-012454](#); Symbol: [ER\\_IB\\_MSG\\_629](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_629](#) was added in 8.0.11.
  - Error number: [MY-012455](#); Symbol: [ER\\_IB\\_MSG\\_630](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_630](#) was added in 8.0.11.
  - Error number: [MY-012456](#); Symbol: [ER\\_IB\\_MSG\\_631](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_631](#) was added in 8.0.11.

- 
- Error number: [MY-012457](#); Symbol: [ER\\_IB\\_MSG\\_632](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_632](#) was added in 8.0.11.
  - Error number: [MY-012458](#); Symbol: [ER\\_IB\\_MSG\\_633](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_633](#) was added in 8.0.11.
  - Error number: [MY-012459](#); Symbol: [ER\\_IB\\_MSG\\_634](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_634](#) was added in 8.0.11.
  - Error number: [MY-012460](#); Symbol: [ER\\_IB\\_MSG\\_635](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_635](#) was added in 8.0.11.
  - Error number: [MY-012461](#); Symbol: [ER\\_IB\\_MSG\\_636](#); SQLSTATE: [HY000](#)  
Message: Blocked High Priority Transaction (ID %llu, Thread ID %s) forces rollback of the blocking transaction (ID %llu - %s).  
[ER\\_IB\\_MSG\\_636](#) was added in 8.0.11.
  - Error number: [MY-012462](#); Symbol: [ER\\_IB\\_MSG\\_637](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_637](#) was added in 8.0.11.
  - Error number: [MY-012463](#); Symbol: [ER\\_IB\\_MSG\\_638](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_638](#) was added in 8.0.11.
  - Error number: [MY-012464](#); Symbol: [ER\\_IB\\_MSG\\_639](#); SQLSTATE: [HY000](#)  
Message: Blocked High Priority Transaction (Thread ID %s) waking up the blocking transaction (ID %llu) by pretending it's a deadlock victim.  
[ER\\_IB\\_MSG\\_639](#) was added in 8.0.11.
  - Error number: [MY-012465](#); Symbol: [ER\\_IB\\_MSG\\_640](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_640](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012466](#); Symbol: [ER\\_IB\\_MSG\\_641](#); SQLSTATE: [HY000](#)  
Message: %s
-

---

[ER\\_IB\\_MSG\\_641](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012467](#); Symbol: [ER\\_IB\\_MSG\\_642](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_642](#) was added in 8.0.11.

- Error number: [MY-012468](#); Symbol: [ER\\_IB\\_MSG\\_643](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_643](#) was added in 8.0.11.

- Error number: [MY-012469](#); Symbol: [ER\\_IB\\_MSG\\_644](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_644](#) was added in 8.0.11.

- Error number: [MY-012470](#); Symbol: [ER\\_IB\\_MSG\\_645](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_645](#) was added in 8.0.11.

- Error number: [MY-012471](#); Symbol: [ER\\_IB\\_MSG\\_646](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_646](#) was added in 8.0.11.

- Error number: [MY-012472](#); Symbol: [ER\\_IB\\_MSG\\_647](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_647](#) was added in 8.0.11.

- Error number: [MY-012473](#); Symbol: [ER\\_IB\\_MSG\\_648](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_648](#) was added in 8.0.11.

- Error number: [MY-012474](#); Symbol: [ER\\_IB\\_MSG\\_649](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_649](#) was added in 8.0.11.

- Error number: [MY-012475](#); Symbol: [ER\\_IB\\_MSG\\_650](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_650](#) was added in 8.0.11.

- Error number: [MY-012476](#); Symbol: [ER\\_IB\\_MSG\\_651](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_651](#) was added in 8.0.11.

- Error number: [MY-012477](#); Symbol: [ER\\_IB\\_MSG\\_652](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_652](#) was added in 8.0.11.

- Error number: [MY-012478](#); Symbol: [ER\\_IB\\_MSG\\_653](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_653](#) was added in 8.0.11, removed after 8.0.15.

- Error number: [MY-012478](#); Symbol: [ER\\_IB\\_MSG\\_DDL\\_LOG\\_DELETE\\_BY\\_ID\\_OK](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_DDL\\_LOG\\_DELETE\\_BY\\_ID\\_OK](#) was added in 8.0.16.

- Error number: [MY-012479](#); Symbol: [ER\\_IB\\_MSG\\_654](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_654](#) was added in 8.0.11.

- Error number: [MY-012480](#); Symbol: [ER\\_IB\\_MSG\\_655](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_655](#) was added in 8.0.11.

- Error number: [MY-012481](#); Symbol: [ER\\_IB\\_MSG\\_656](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_656](#) was added in 8.0.11.

- Error number: [MY-012482](#); Symbol: [ER\\_IB\\_MSG\\_657](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_657](#) was added in 8.0.11.

- Error number: [MY-012483](#); Symbol: [ER\\_IB\\_MSG\\_658](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_658](#) was added in 8.0.11.

- Error number: [MY-012484](#); Symbol: [ER\\_IB\\_MSG\\_659](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_659](#) was added in 8.0.11.

- Error number: [MY-012485](#); Symbol: [ER\\_IB\\_MSG\\_660](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_660](#) was added in 8.0.11.

- Error number: [MY-012486](#); Symbol: [ER\\_IB\\_MSG\\_661](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_661](#) was added in 8.0.11.

- Error number: [MY-012487](#); Symbol: [ER\\_IB\\_MSG\\_662](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_662](#) was added in 8.0.11.

- Error number: [MY-012488](#); Symbol: [ER\\_IB\\_MSG\\_663](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_663](#) was added in 8.0.11.

- Error number: [MY-012489](#); Symbol: [ER\\_IB\\_MSG\\_664](#); SQLSTATE: [HY000](#)

Message: The transaction log size is too large for innodb\_log\_buffer\_size (%lu >= %lu / 2). Trying to extend it.

[ER\\_IB\\_MSG\\_664](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012490](#); Symbol: [ER\\_IB\\_MSG\\_665](#); SQLSTATE: [HY000](#)

Message: innodb\_log\_buffer\_size was extended to %lu bytes.

[ER\\_IB\\_MSG\\_665](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012491](#); Symbol: [ER\\_IB\\_MSG\\_666](#); SQLSTATE: [HY000](#)

Message: The transaction log files are too small for the single transaction log (size=%lu). So, the last checkpoint age might exceed the log group capacity %llu.

[ER\\_IB\\_MSG\\_666](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012492](#); Symbol: [ER\\_IB\\_MSG\\_667](#); SQLSTATE: [HY000](#)

Message: The age of the last checkpoint is %llu, which exceeds the log group capacity %llu.

[ER\\_IB\\_MSG\\_667](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012493](#); Symbol: [ER\\_IB\\_MSG\\_668](#); SQLSTATE: [HY000](#)

Message: Cannot continue operation. ib\_logfiles are too small for innodb\_thread\_concurrency %lu. The combined size of ib\_logfiles should be bigger than 200 kB \* innodb\_thread\_concurrency. To get mysqld to start up, set innodb\_thread\_concurrency in my.cnf to a lower value, for example, to 8. After an ERROR-FREE shutdown of mysqld you can adjust the size of ib\_logfiles. %s

[ER\\_IB\\_MSG\\_668](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012494](#); Symbol: [ER\\_IB\\_MSG\\_669](#); SQLSTATE: [HY000](#)

Message: Redo log was encrypted, but keyring plugin is not loaded.



---

[ER\\_IB\\_MSG\\_669](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012495](#); Symbol: [ER\\_IB\\_MSG\\_670](#); SQLSTATE: [HY000](#)

Message: Read redo log encryption metadata successful.

[ER\\_IB\\_MSG\\_670](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012496](#); Symbol: [ER\\_IB\\_MSG\\_671](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace encryption metadata.

[ER\\_IB\\_MSG\\_671](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012497](#); Symbol: [ER\\_IB\\_MSG\\_672](#); SQLSTATE: [HY000](#)

Message: Cannot read the encryption information in log file header, please check if keyring plugin loaded and the key file exists.

[ER\\_IB\\_MSG\\_672](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012498](#); Symbol: [ER\\_IB\\_MSG\\_673](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted in read-only mode.

[ER\\_IB\\_MSG\\_673](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012499](#); Symbol: [ER\\_IB\\_MSG\\_674](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted.

[ER\\_IB\\_MSG\\_674](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012500](#); Symbol: [ER\\_IB\\_MSG\\_675](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted.

[ER\\_IB\\_MSG\\_675](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012501](#); Symbol: [ER\\_IB\\_MSG\\_676](#); SQLSTATE: [HY000](#)

Message: Redo log encryption is enabled.

[ER\\_IB\\_MSG\\_676](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012502](#); Symbol: [ER\\_IB\\_MSG\\_677](#); SQLSTATE: [HY000](#)

Message: Flush Waiting for archiver to to catch up lag LSN: %llu

[ER\\_IB\\_MSG\\_677](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012503](#); Symbol: [ER\\_IB\\_MSG\\_678](#); SQLSTATE: [HY000](#)

Message: Flush overwriting data to archive - wait too long (1 minute) lag LSN: %llu

[ER\\_IB\\_MSG\\_678](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012504](#); Symbol: [ER\\_IB\\_MSG\\_679](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_679](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012505](#); Symbol: [ER\\_IB\\_MSG\\_680](#); SQLSTATE: [HY000](#)

Message: Starting shutdown...

[ER\\_IB\\_MSG\\_680](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012506](#); Symbol: [ER\\_IB\\_MSG\\_681](#); SQLSTATE: [HY000](#)

Message: Waiting for %s to exit

[ER\\_IB\\_MSG\\_681](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012507](#); Symbol: [ER\\_IB\\_MSG\\_682](#); SQLSTATE: [HY000](#)

Message: Waiting for %lu active transactions to finish

[ER\\_IB\\_MSG\\_682](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012508](#); Symbol: [ER\\_IB\\_MSG\\_683](#); SQLSTATE: [HY000](#)

Message: Waiting for master thread to be suspended

[ER\\_IB\\_MSG\\_683](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012509](#); Symbol: [ER\\_IB\\_MSG\\_684](#); SQLSTATE: [HY000](#)

Message: Waiting for page\_cleaner to finish flushing of buffer pool

[ER\\_IB\\_MSG\\_684](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012510](#); Symbol: [ER\\_IB\\_MSG\\_685](#); SQLSTATE: [HY000](#)

Message: Pending checkpoint\_writes: %lu. Pending log flush writes: %lu.

[ER\\_IB\\_MSG\\_685](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012511](#); Symbol: [ER\\_IB\\_MSG\\_686](#); SQLSTATE: [HY000](#)

Message: Waiting for %lu buffer page I/Os to complete

[ER\\_IB\\_MSG\\_686](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012512](#); Symbol: [ER\\_IB\\_MSG\\_687](#); SQLSTATE: [HY000](#)

Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to data files. At the next mysqld startup InnoDB will do a crash recovery!

[ER\\_IB\\_MSG\\_687](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012513](#); Symbol: [ER\\_IB\\_MSG\\_688](#); SQLSTATE: [HY000](#)

Message: Background thread %s woke up during shutdown

[ER\\_IB\\_MSG\\_688](#) was added in 8.0.11, removed after 8.0.13.

- 
- Error number: [MY-012514](#); Symbol: [ER\\_IB\\_MSG\\_689](#); SQLSTATE: [HY000](#)  
Message: Waiting for archiver to finish archiving page and log  
[ER\\_IB\\_MSG\\_689](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012515](#); Symbol: [ER\\_IB\\_MSG\\_690](#); SQLSTATE: [HY000](#)  
Message: Background thread %s woke up during shutdown  
[ER\\_IB\\_MSG\\_690](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012516](#); Symbol: [ER\\_IB\\_MSG\\_691](#); SQLSTATE: [HY000](#)  
Message: Waiting for dirty buffer pages to be flushed  
[ER\\_IB\\_MSG\\_691](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012517](#); Symbol: [ER\\_IB\\_MSG\\_692](#); SQLSTATE: [HY000](#)  
Message: Log sequence number at shutdown %llu is lower than at startup %llu!  
[ER\\_IB\\_MSG\\_692](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012518](#); Symbol: [ER\\_IB\\_MSG\\_693](#); SQLSTATE: [HY000](#)  
Message: Waiting for archiver to finish archiving page and log  
[ER\\_IB\\_MSG\\_693](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012519](#); Symbol: [ER\\_IB\\_MSG\\_694](#); SQLSTATE: [HY000](#)  
Message: ##### CORRUPT LOG RECORD FOUND #####  
[ER\\_IB\\_MSG\\_694](#) was added in 8.0.11.
  - Error number: [MY-012520](#); Symbol: [ER\\_IB\\_MSG\\_695](#); SQLSTATE: [HY000](#)  
Message: Log record type %d, page %lu:%lu. Log parsing proceeded successfully up to %llu. Previous log record type %d, is multi %llu Recv offset %zd, prev %llu  
[ER\\_IB\\_MSG\\_695](#) was added in 8.0.11.
  - Error number: [MY-012521](#); Symbol: [ER\\_IB\\_MSG\\_696](#); SQLSTATE: [HY000](#)  
Message: Hex dump starting %llu bytes before and ending %llu bytes after the corrupted record:  
[ER\\_IB\\_MSG\\_696](#) was added in 8.0.11.
  - Error number: [MY-012522](#); Symbol: [ER\\_IB\\_MSG\\_697](#); SQLSTATE: [HY000](#)  
Message: Set innodb\_force\_recovery to ignore this error.  
[ER\\_IB\\_MSG\\_697](#) was added in 8.0.11.
  - Error number: [MY-012523](#); Symbol: [ER\\_IB\\_MSG\\_698](#); SQLSTATE: [HY000](#)  
Message: The log file may have been corrupt and it is possible that the log scan did not proceed far enough in recovery! Please run CHECK TABLE on your InnoDB tables to check that they are ok! If mysqld crashes after this recovery; %s

---

[ER\\_IB\\_MSG\\_698](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012523](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_CORRUPT](#); SQLSTATE: [HY000](#)

Message: The redo log file may have been corrupt and it is possible that the log scan did not proceed far enough in recovery! Please run CHECK TABLE on your InnoDB tables to check that they are ok! If mysqld crashes after this recovery; %s

[ER\\_IB\\_MSG\\_LOG\\_CORRUPT](#) was added in 8.0.30.

- Error number: [MY-012524](#); Symbol: [ER\\_IB\\_MSG\\_699](#); SQLSTATE: [HY000](#)

Message: %llu pages with log records were left unprocessed!

[ER\\_IB\\_MSG\\_699](#) was added in 8.0.11.

- Error number: [MY-012525](#); Symbol: [ER\\_IB\\_MSG\\_700](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_700](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012525](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_OLD\\_AND\\_LOG\\_CORRUPTED](#); SQLSTATE: [HY000](#)

Message: Upgrade after a crash is not supported. This redo log was created with %s, and it appears corrupted. Please follow the instructions at %s

[ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_OLD\\_AND\\_LOG\\_CORRUPTED](#) was added in 8.0.30.

- Error number: [MY-012526](#); Symbol: [ER\\_IB\\_MSG\\_701](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_701](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012526](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_OLD\\_AND\\_NO\\_CLEAN\\_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Upgrade is not supported after a crash or shutdown with innodb\_fast\_shutdown = 2. This redo log was created with %s, and it appears logically non empty. Please follow the instructions at %s

[ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_OLD\\_AND\\_NO\\_CLEAN\\_SHUTDOWN](#) was added in 8.0.30.

- Error number: [MY-012527](#); Symbol: [ER\\_IB\\_MSG\\_702](#); SQLSTATE: [HY000](#)

Message: Invalid redo log header checksum.

[ER\\_IB\\_MSG\\_702](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012528](#); Symbol: [ER\\_IB\\_MSG\\_703](#); SQLSTATE: [HY000](#)

Message: Unsupported redo log format (%lu). The redo log was created before MySQL 5.7.9

[ER\\_IB\\_MSG\\_703](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012529](#); Symbol: [ER\\_IB\\_MSG\\_704](#); SQLSTATE: [HY000](#)

Message: Redo log format is v%lu. The redo log was created before MySQL 8.0.3.

---

[ER\\_IB\\_MSG\\_704](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012529](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_BEFORE\\_8\\_0\\_30](#); SQLSTATE: [HY000](#)  
Message: Redo log format is v%lu. The redo log was created before MySQL 8.0.30.

[ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_BEFORE\\_8\\_0\\_30](#) was added in 8.0.30.

- Error number: [MY-012530](#); Symbol: [ER\\_IB\\_MSG\\_705](#); SQLSTATE: [HY000](#)  
Message: Unknown redo log format (%lu). Please follow the instructions at %s upgrading-downgrading.html.

[ER\\_IB\\_MSG\\_705](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012530](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_FORMAT\\_UNKNOWN](#); SQLSTATE: [HY000](#)  
Message: Unknown redo log format (v%lu) in file %s. Please follow the instructions at %s

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_FORMAT\\_UNKNOWN](#) was added in 8.0.30.

- Error number: [MY-012531](#); Symbol: [ER\\_IB\\_MSG\\_706](#); SQLSTATE: [HY000](#)  
Message: No valid checkpoint found (corrupted redo log). You can try --innodb-force-recovery=6 as a last resort.

[ER\\_IB\\_MSG\\_706](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012531](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_CHECKPOINT\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: No valid checkpoint found (corrupted redo log). You can try --innodb-force-recovery=6 as a last resort.

[ER\\_IB\\_MSG\\_RECOVERY\\_CHECKPOINT\\_NOT\\_FOUND](#) was added in 8.0.30.

- Error number: [MY-012532](#); Symbol: [ER\\_IB\\_MSG\\_707](#); SQLSTATE: [HY000](#)  
Message: Applying a batch of %llu redo log records ...

[ER\\_IB\\_MSG\\_707](#) was added in 8.0.11.

- Error number: [MY-012533](#); Symbol: [ER\\_IB\\_MSG\\_708](#); SQLSTATE: [HY000](#)  
Message: %s

[ER\\_IB\\_MSG\\_708](#) was added in 8.0.11.

- Error number: [MY-012534](#); Symbol: [ER\\_IB\\_MSG\\_709](#); SQLSTATE: [HY000](#)  
Message: %s

[ER\\_IB\\_MSG\\_709](#) was added in 8.0.11.

- Error number: [MY-012535](#); Symbol: [ER\\_IB\\_MSG\\_710](#); SQLSTATE: [HY000](#)  
Message: Apply batch completed!

[ER\\_IB\\_MSG\\_710](#) was added in 8.0.11.

- 
- Error number: [MY-012536](#); Symbol: [ER\\_IB\\_MSG\\_711](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_711](#) was added in 8.0.11.
  - Error number: [MY-012537](#); Symbol: [ER\\_IB\\_MSG\\_712](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_712](#) was added in 8.0.11.
  - Error number: [MY-012538](#); Symbol: [ER\\_IB\\_MSG\\_713](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_713](#) was added in 8.0.11.
  - Error number: [MY-012539](#); Symbol: [ER\\_IB\\_MSG\\_714](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_714](#) was added in 8.0.11.
  - Error number: [MY-012540](#); Symbol: [ER\\_IB\\_MSG\\_715](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_715](#) was added in 8.0.11.
  - Error number: [MY-012541](#); Symbol: [ER\\_IB\\_MSG\\_716](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_716](#) was added in 8.0.11.
  - Error number: [MY-012542](#); Symbol: [ER\\_IB\\_MSG\\_717](#); SQLSTATE: [HY000](#)  
Message: An optimized(without redo logging) DDL operation has been performed. All modified pages may not have been flushed to the disk yet. This offline backup may not be consistent  
[ER\\_IB\\_MSG\\_717](#) was added in 8.0.11.
  - Error number: [MY-012543](#); Symbol: [ER\\_IB\\_MSG\\_718](#); SQLSTATE: [HY000](#)  
Message: Extending tablespace : %lu space name: %s to new size: %lu pages during recovery.  
[ER\\_IB\\_MSG\\_718](#) was added in 8.0.11.
  - Error number: [MY-012544](#); Symbol: [ER\\_IB\\_MSG\\_719](#); SQLSTATE: [HY000](#)  
Message: Could not extend tablespace: %lu space name: %s to new size: %lu pages during recovery.  
[ER\\_IB\\_MSG\\_719](#) was added in 8.0.11.
  - Error number: [MY-012545](#); Symbol: [ER\\_IB\\_MSG\\_720](#); SQLSTATE: [HY000](#)  
Message: Log block %lu at lsn %llu has valid header, but checksum field contains %lu, should be %lu.  
[ER\\_IB\\_MSG\\_720](#) was added in 8.0.11.

- 
- Error number: [MY-012546](#); Symbol: [ER\\_IB\\_MSG\\_721](#); SQLSTATE: [HY000](#)  
Message: Recovery skipped, --innodb-read-only set!  
[ER\\_IB\\_MSG\\_721](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012546](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_SKIPPED\\_IN\\_READ\\_ONLY\\_MODE](#); SQLSTATE: [HY000](#)  
Message: Recovery skipped, --innodb-read-only set!  
[ER\\_IB\\_MSG\\_RECOVERY\\_SKIPPED\\_IN\\_READ\\_ONLY\\_MODE](#) was added in 8.0.30.
  - Error number: [MY-012547](#); Symbol: [ER\\_IB\\_MSG\\_722](#); SQLSTATE: [HY000](#)  
Message: Log scan progressed past the checkpoint LSN %llu.  
[ER\\_IB\\_MSG\\_722](#) was added in 8.0.11.
  - Error number: [MY-012548](#); Symbol: [ER\\_IB\\_MSG\\_723](#); SQLSTATE: [HY000](#)  
Message: Log parsing buffer overflow. Recovery may have failed! Please set log\_buffer\_size to a value higher than %lu.  
[ER\\_IB\\_MSG\\_723](#) was added in 8.0.11.
  - Error number: [MY-012549](#); Symbol: [ER\\_IB\\_MSG\\_724](#); SQLSTATE: [HY000](#)  
Message: Set innodb\_force\_recovery to ignore this error.  
[ER\\_IB\\_MSG\\_724](#) was added in 8.0.11.
  - Error number: [MY-012550](#); Symbol: [ER\\_IB\\_MSG\\_725](#); SQLSTATE: [HY000](#)  
Message: Doing recovery: scanned up to log sequence number %llu  
[ER\\_IB\\_MSG\\_725](#) was added in 8.0.11.
  - Error number: [MY-012551](#); Symbol: [ER\\_IB\\_MSG\\_726](#); SQLSTATE: [HY000](#)  
Message: Database was not shutdown normally!  
[ER\\_IB\\_MSG\\_726](#) was added in 8.0.11.
  - Error number: [MY-012552](#); Symbol: [ER\\_IB\\_MSG\\_727](#); SQLSTATE: [HY000](#)  
Message: Starting crash recovery.  
[ER\\_IB\\_MSG\\_727](#) was added in 8.0.11.
  - Error number: [MY-012553](#); Symbol: [ER\\_IB\\_MSG\\_728](#); SQLSTATE: [HY000](#)  
Message: The user has set SRV\_FORCE\_NO\_LOG\_REDO on, skipping log redo  
[ER\\_IB\\_MSG\\_728](#) was added in 8.0.11.
  - Error number: [MY-012554](#); Symbol: [ER\\_IB\\_MSG\\_729](#); SQLSTATE: [HY000](#)  
Message: Cannot restore from mysqlbackup, InnoDB running in read-only mode!

---

`ER_IB_MSG_729` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012554`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY_MODE`; SQLSTATE: `HY000`

Message: Cannot restore from mysqlbackup, InnoDB running in read-only mode!

`ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY_MODE` was added in 8.0.30.

- Error number: `MY-012555`; Symbol: `ER_IB_MSG_730`; SQLSTATE: `HY000`

Message: The log file was created by mysqlbackup --apply-log at %s. The following crash recovery is part of a normal restore.

`ER_IB_MSG_730` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012555`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_MEB`; SQLSTATE: `HY000`

Message: The redo log file was created by mysqlbackup --apply-log at %s. The following crash recovery is part of a normal restore.

`ER_IB_MSG_LOG_FILES_CREATED_BY_MEB` was added in 8.0.30.

- Error number: `MY-012556`; Symbol: `ER_IB_MSG_731`; SQLSTATE: `HY000`

Message: Opening cloned database

`ER_IB_MSG_731` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012556`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE`; SQLSTATE: `HY000`

Message: Opening cloned database

`ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE` was added in 8.0.30.

- Error number: `MY-012557`; Symbol: `ER_IB_MSG_732`; SQLSTATE: `HY000`

Message: Redo log is from an earlier version, v%lu.

`ER_IB_MSG_732` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012557`; Symbol: `ER_IB_MSG_LOG_FORMAT_OLD`; SQLSTATE: `HY000`

Message: Redo log is from an earlier version, v%lu.

`ER_IB_MSG_LOG_FORMAT_OLD` was added in 8.0.30.

- Error number: `MY-012558`; Symbol: `ER_IB_MSG_733`; SQLSTATE: `HY000`

Message: Redo log format v%lu not supported. Current supported format is v%lu.

`ER_IB_MSG_733` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012558`; Symbol: `ER_IB_MSG_LOG_FORMAT_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Redo log format v%lu not supported. Current supported format is v%lu.

`ER_IB_MSG_LOG_FORMAT_NOT_SUPPORTED` was added in 8.0.30, removed after 8.0.32.



- 
- Error number: [MY-012559](#); Symbol: [ER\\_IB\\_MSG\\_734](#); SQLSTATE: [HY000](#)

Message: Are you sure you are using the right ib\_logfiles to start up the database? Log sequence number in the ib\_logfiles is %llu, less than the log sequence number in the first system tablespace file header, %llu.

[ER\\_IB\\_MSG\\_734](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012559](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_CHECKPOINT\\_FROM\\_BEFORE\\_CLEAN\\_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Are you sure you are using the right redo log files to start up the database? Log sequence number in the redo log files is %llu, less than the log sequence number in the first system tablespace file header, %llu.

[ER\\_IB\\_MSG\\_RECOVERY\\_CHECKPOINT\\_FROM\\_BEFORE\\_CLEAN\\_SHUTDOWN](#) was added in 8.0.30.

- Error number: [MY-012560](#); Symbol: [ER\\_IB\\_MSG\\_735](#); SQLSTATE: [HY000](#)

Message: The log sequence number %llu in the system tablespace does not match the log sequence number %llu in the ib\_logfiles!

[ER\\_IB\\_MSG\\_735](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012560](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_IS\\_NEEDED](#); SQLSTATE: [HY000](#)

Message: The log sequence number %llu in the system tablespace does not match the log sequence number %llu in the redo log files!

[ER\\_IB\\_MSG\\_RECOVERY\\_IS\\_NEEDED](#) was added in 8.0.30.

- Error number: [MY-012561](#); Symbol: [ER\\_IB\\_MSG\\_736](#); SQLSTATE: [HY000](#)

Message: Can't initiate database recovery, running in read-only-mode.

[ER\\_IB\\_MSG\\_736](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012561](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_IN\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)

Message: Can't initiate database recovery, running in read-only-mode.

[ER\\_IB\\_MSG\\_RECOVERY\\_IN\\_READ\\_ONLY](#) was added in 8.0.30.

- Error number: [MY-012562](#); Symbol: [ER\\_IB\\_MSG\\_737](#); SQLSTATE: [HY000](#)

Message: We scanned the log up to %llu. A checkpoint was at %llu and the maximum LSN on a database page was %llu. It is possible that the database is now corrupt!

[ER\\_IB\\_MSG\\_737](#) was added in 8.0.11.

- Error number: [MY-012563](#); Symbol: [ER\\_IB\\_MSG\\_738](#); SQLSTATE: [HY000](#)

Message: Waiting for recv\_writer to finish flushing of buffer pool

[ER\\_IB\\_MSG\\_738](#) was added in 8.0.11.

- Error number: [MY-012564](#); Symbol: [ER\\_IB\\_MSG\\_739](#); SQLSTATE: [HY000](#)

Message: Recovery parsing buffer extended to %zu.

---

[ER\\_IB\\_MSG\\_739](#) was added in 8.0.11.

- Error number: [MY-012565](#); Symbol: [ER\\_IB\\_MSG\\_740](#); SQLSTATE: [HY000](#)

Message: Out of memory while resizing recovery parsing buffer.

[ER\\_IB\\_MSG\\_740](#) was added in 8.0.11.

- Error number: [MY-012566](#); Symbol: [ER\\_IB\\_MSG\\_741](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_741](#) was added in 8.0.11.

- Error number: [MY-012567](#); Symbol: [ER\\_IB\\_MSG\\_742](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_742](#) was added in 8.0.11.

- Error number: [MY-012568](#); Symbol: [ER\\_IB\\_MSG\\_743](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_743](#) was added in 8.0.11.

- Error number: [MY-012569](#); Symbol: [ER\\_IB\\_MSG\\_744](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_744](#) was added in 8.0.11.

- Error number: [MY-012570](#); Symbol: [ER\\_IB\\_MSG\\_745](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_745](#) was added in 8.0.11.

- Error number: [MY-012571](#); Symbol: [ER\\_IB\\_MSG\\_746](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_746](#) was added in 8.0.11.

- Error number: [MY-012572](#); Symbol: [ER\\_IB\\_MSG\\_747](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_747](#) was added in 8.0.11.

- Error number: [MY-012573](#); Symbol: [ER\\_IB\\_MSG\\_748](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_748](#) was added in 8.0.11.

- Error number: [MY-012574](#); Symbol: [ER\\_IB\\_MSG\\_749](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_749](#) was added in 8.0.11.

- Error number: [MY-012575](#); Symbol: [ER\\_IB\\_MSG\\_750](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_750](#) was added in 8.0.11.

- Error number: [MY-012576](#); Symbol: [ER\\_IB\\_MSG\\_751](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_751](#) was added in 8.0.11.

- Error number: [MY-012577](#); Symbol: [ER\\_IB\\_MSG\\_752](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_752](#) was added in 8.0.11.

- Error number: [MY-012578](#); Symbol: [ER\\_IB\\_MSG\\_753](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_753](#) was added in 8.0.11.

- Error number: [MY-012579](#); Symbol: [ER\\_IB\\_MSG\\_754](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_754](#) was added in 8.0.11.

- Error number: [MY-012580](#); Symbol: [ER\\_IB\\_MSG\\_755](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_755](#) was added in 8.0.11.

- Error number: [MY-012581](#); Symbol: [ER\\_IB\\_MSG\\_756](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_756](#) was added in 8.0.11.

- Error number: [MY-012582](#); Symbol: [ER\\_IB\\_MSG\\_757](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_757](#) was added in 8.0.11.

- Error number: [MY-012583](#); Symbol: [ER\\_IB\\_MSG\\_758](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_758](#) was added in 8.0.11.

- Error number: [MY-012584](#); Symbol: [ER\\_IB\\_MSG\\_759](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_759](#) was added in 8.0.11.

- Error number: [MY-012585](#); Symbol: [ER\\_IB\\_MSG\\_760](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_760](#) was added in 8.0.11.

- Error number: [MY-012586](#); Symbol: [ER\\_IB\\_MSG\\_761](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_761](#) was added in 8.0.11.

- Error number: [MY-012587](#); Symbol: [ER\\_IB\\_MSG\\_762](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_762](#) was added in 8.0.11.

- Error number: [MY-012588](#); Symbol: [ER\\_IB\\_MSG\\_763](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_763](#) was added in 8.0.11.

- Error number: [MY-012589](#); Symbol: [ER\\_IB\\_MSG\\_764](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_764](#) was added in 8.0.11.

- Error number: [MY-012590](#); Symbol: [ER\\_IB\\_MSG\\_765](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_765](#) was added in 8.0.11.

- Error number: [MY-012591](#); Symbol: [ER\\_IB\\_MSG\\_766](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_766](#) was added in 8.0.11.

- Error number: [MY-012592](#); Symbol: [ER\\_IB\\_MSG\\_767](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_767](#) was added in 8.0.11.

- Error number: [MY-012593](#); Symbol: [ER\\_IB\\_MSG\\_768](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_768](#) was added in 8.0.11.

- Error number: [MY-012594](#); Symbol: [ER\\_IB\\_MSG\\_769](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_769](#) was added in 8.0.11.

- Error number: [MY-012595](#); Symbol: [ER\\_IB\\_MSG\\_770](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_770](#) was added in 8.0.11.

- Error number: [MY-012596](#); Symbol: [ER\\_IB\\_MSG\\_771](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_771](#) was added in 8.0.11.

- Error number: [MY-012597](#); Symbol: [ER\\_IB\\_MSG\\_772](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_772](#) was added in 8.0.11.

- Error number: [MY-012598](#); Symbol: [ER\\_IB\\_MSG\\_773](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_773](#) was added in 8.0.11.

- Error number: [MY-012599](#); Symbol: [ER\\_IB\\_MSG\\_774](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_774](#) was added in 8.0.11.

- Error number: [MY-012600](#); Symbol: [ER\\_IB\\_MSG\\_775](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_775](#) was added in 8.0.11.

- Error number: [MY-012601](#); Symbol: [ER\\_IB\\_MSG\\_776](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_776](#) was added in 8.0.11.

- Error number: [MY-012602](#); Symbol: [ER\\_IB\\_MSG\\_777](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_777](#) was added in 8.0.11.

- Error number: [MY-012603](#); Symbol: [ER\\_IB\\_MSG\\_778](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_778](#) was added in 8.0.11.

- Error number: [MY-012604](#); Symbol: [ER\\_IB\\_MSG\\_779](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_779](#) was added in 8.0.11.

- Error number: [MY-012605](#); Symbol: [ER\\_IB\\_MSG\\_780](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_780](#) was added in 8.0.11.

- Error number: [MY-012606](#); Symbol: [ER\\_IB\\_MSG\\_781](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_781](#) was added in 8.0.11.

- Error number: [MY-012607](#); Symbol: [ER\\_IB\\_MSG\\_782](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_782](#) was added in 8.0.11.

- Error number: [MY-012608](#); Symbol: [ER\\_IB\\_MSG\\_783](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_783](#) was added in 8.0.11.

- Error number: [MY-012609](#); Symbol: [ER\\_IB\\_MSG\\_784](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_784](#) was added in 8.0.11.

- Error number: [MY-012610](#); Symbol: [ER\\_IB\\_MSG\\_785](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_785](#) was added in 8.0.11.

- Error number: [MY-012611](#); Symbol: [ER\\_IB\\_MSG\\_786](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_786](#) was added in 8.0.11.

- Error number: [MY-012612](#); Symbol: [ER\\_IB\\_MSG\\_787](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_787](#) was added in 8.0.11.

- Error number: [MY-012613](#); Symbol: [ER\\_IB\\_MSG\\_788](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_788](#) was added in 8.0.11.

- Error number: [MY-012614](#); Symbol: [ER\\_IB\\_MSG\\_789](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_789](#) was added in 8.0.11.

- Error number: [MY-012615](#); Symbol: [ER\\_IB\\_MSG\\_790](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_790](#) was added in 8.0.11.

- Error number: [MY-012616](#); Symbol: [ER\\_IB\\_MSG\\_791](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_791](#) was added in 8.0.11.

- Error number: [MY-012617](#); Symbol: [ER\\_IB\\_MSG\\_792](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_792](#) was added in 8.0.11.

- Error number: [MY-012618](#); Symbol: [ER\\_IB\\_MSG\\_793](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_793](#) was added in 8.0.11.

- Error number: [MY-012619](#); Symbol: [ER\\_IB\\_MSG\\_794](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_794](#) was added in 8.0.11.

- Error number: [MY-012620](#); Symbol: [ER\\_IB\\_MSG\\_795](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_795](#) was added in 8.0.11.

- Error number: [MY-012621](#); Symbol: [ER\\_IB\\_MSG\\_796](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_796](#) was added in 8.0.11.

- Error number: [MY-012622](#); Symbol: [ER\\_IB\\_MSG\\_797](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_797](#) was added in 8.0.11.

- Error number: [MY-012623](#); Symbol: [ER\\_IB\\_MSG\\_798](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_798](#) was added in 8.0.11.

- Error number: [MY-012624](#); Symbol: [ER\\_IB\\_MSG\\_799](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_799](#) was added in 8.0.11.

- Error number: [MY-012625](#); Symbol: [ER\\_IB\\_MSG\\_800](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_800](#) was added in 8.0.11, removed after 8.0.39.

- Error number: [MY-012626](#); Symbol: [ER\\_IB\\_MSG\\_801](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_801](#) was added in 8.0.11.

- Error number: [MY-012627](#); Symbol: [ER\\_IB\\_MSG\\_802](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_802](#) was added in 8.0.11.

- Error number: [MY-012628](#); Symbol: [ER\\_IB\\_MSG\\_803](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_803](#) was added in 8.0.11.

- Error number: [MY-012629](#); Symbol: [ER\\_IB\\_MSG\\_804](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_804](#) was added in 8.0.11.

- Error number: [MY-012630](#); Symbol: [ER\\_IB\\_MSG\\_805](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_805](#) was added in 8.0.11.

- Error number: [MY-012631](#); Symbol: [ER\\_IB\\_MSG\\_806](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_806](#) was added in 8.0.11.

- Error number: [MY-012632](#); Symbol: [ER\\_IB\\_MSG\\_807](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_807](#) was added in 8.0.11.

- Error number: [MY-012633](#); Symbol: [ER\\_IB\\_MSG\\_808](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_808](#) was added in 8.0.11.

- Error number: [MY-012634](#); Symbol: [ER\\_IB\\_MSG\\_809](#); SQLSTATE: [HY000](#)

Message: %s



---

[ER\\_IB\\_MSG\\_809](#) was added in 8.0.11.

- Error number: [MY-012635](#); Symbol: [ER\\_IB\\_MSG\\_810](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_810](#) was added in 8.0.11.

- Error number: [MY-012636](#); Symbol: [ER\\_IB\\_MSG\\_811](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_811](#) was added in 8.0.11.

- Error number: [MY-012637](#); Symbol: [ER\\_IB\\_MSG\\_812](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_812](#) was added in 8.0.11.

- Error number: [MY-012638](#); Symbol: [ER\\_IB\\_MSG\\_813](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_813](#) was added in 8.0.11.

- Error number: [MY-012639](#); Symbol: [ER\\_IB\\_MSG\\_814](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_814](#) was added in 8.0.11.

- Error number: [MY-012640](#); Symbol: [ER\\_IB\\_MSG\\_815](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_815](#) was added in 8.0.11.

- Error number: [MY-012641](#); Symbol: [ER\\_IB\\_MSG\\_816](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_816](#) was added in 8.0.11.

- Error number: [MY-012642](#); Symbol: [ER\\_IB\\_MSG\\_817](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_817](#) was added in 8.0.11.

- Error number: [MY-012643](#); Symbol: [ER\\_IB\\_MSG\\_818](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_818](#) was added in 8.0.11.

- Error number: [MY-012644](#); Symbol: [ER\\_IB\\_MSG\\_819](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_819](#) was added in 8.0.11.

- Error number: [MY-012645](#); Symbol: [ER\\_IB\\_MSG\\_820](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_820](#) was added in 8.0.11.

- Error number: [MY-012646](#); Symbol: [ER\\_IB\\_MSG\\_821](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_821](#) was added in 8.0.11.

- Error number: [MY-012647](#); Symbol: [ER\\_IB\\_MSG\\_822](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_822](#) was added in 8.0.11.

- Error number: [MY-012648](#); Symbol: [ER\\_IB\\_MSG\\_823](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_823](#) was added in 8.0.11.

- Error number: [MY-012649](#); Symbol: [ER\\_IB\\_MSG\\_824](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_824](#) was added in 8.0.11.

- Error number: [MY-012650](#); Symbol: [ER\\_IB\\_MSG\\_825](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_825](#) was added in 8.0.11.

- Error number: [MY-012651](#); Symbol: [ER\\_IB\\_MSG\\_826](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_826](#) was added in 8.0.11.

- Error number: [MY-012652](#); Symbol: [ER\\_IB\\_MSG\\_827](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_827](#) was added in 8.0.11.

- Error number: [MY-012653](#); Symbol: [ER\\_IB\\_MSG\\_828](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_828](#) was added in 8.0.11.

- Error number: [MY-012654](#); Symbol: [ER\\_IB\\_MSG\\_829](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_829](#) was added in 8.0.11.

- Error number: [MY-012655](#); Symbol: [ER\\_IB\\_MSG\\_830](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_830](#) was added in 8.0.11.

- Error number: [MY-012656](#); Symbol: [ER\\_IB\\_MSG\\_831](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_831](#) was added in 8.0.11.

- Error number: [MY-012657](#); Symbol: [ER\\_IB\\_MSG\\_832](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_832](#) was added in 8.0.11.

- Error number: [MY-012658](#); Symbol: [ER\\_IB\\_MSG\\_833](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_833](#) was added in 8.0.11.

- Error number: [MY-012659](#); Symbol: [ER\\_IB\\_MSG\\_834](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_834](#) was added in 8.0.11.

- Error number: [MY-012660](#); Symbol: [ER\\_IB\\_MSG\\_835](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_835](#) was added in 8.0.11.

- Error number: [MY-012661](#); Symbol: [ER\\_IB\\_MSG\\_836](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_836](#) was added in 8.0.11.

- Error number: [MY-012662](#); Symbol: [ER\\_IB\\_MSG\\_837](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_837](#) was added in 8.0.11.

- Error number: [MY-012663](#); Symbol: [ER\\_IB\\_MSG\\_838](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_838](#) was added in 8.0.11.

- Error number: [MY-012664](#); Symbol: [ER\\_IB\\_MSG\\_839](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_839](#) was added in 8.0.11.

- Error number: [MY-012665](#); Symbol: [ER\\_IB\\_MSG\\_840](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_840](#) was added in 8.0.11.

- Error number: [MY-012666](#); Symbol: [ER\\_IB\\_MSG\\_841](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_841](#) was added in 8.0.11.

- Error number: [MY-012667](#); Symbol: [ER\\_IB\\_MSG\\_842](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_842](#) was added in 8.0.11.

- Error number: [MY-012668](#); Symbol: [ER\\_IB\\_MSG\\_843](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_843](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-012668](#); Symbol: [ER\\_IB\\_MSG\\_CANT\\_ENCRYPT\\_REDO\\_LOG\\_DATA](#); SQLSTATE: [HY000](#)

Message: Can't encrypt data of redo log

[ER\\_IB\\_MSG\\_CANT\\_ENCRYPT\\_REDO\\_LOG\\_DATA](#) was added in 8.0.33.

- Error number: [MY-012669](#); Symbol: [ER\\_IB\\_MSG\\_844](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_844](#) was added in 8.0.11.

- Error number: [MY-012670](#); Symbol: [ER\\_IB\\_MSG\\_845](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_845](#) was added in 8.0.11.

- Error number: [MY-012671](#); Symbol: [ER\\_IB\\_MSG\\_846](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_846](#) was added in 8.0.11, removed after 8.0.36.

- Error number: [MY-012671](#); Symbol: [ER\\_IB\\_MSG\\_CANT\\_DECRYPT\\_REDO\\_LOG](#); SQLSTATE: [HY000](#)

Message: Decryption of redo log block at offset %llu in file %s failed because there's no keyring configured

[ER\\_IB\\_MSG\\_CANT\\_DECRYPT\\_REDO\\_LOG](#) was added in 8.0.37.

- Error number: [MY-012672](#); Symbol: [ER\\_IB\\_MSG\\_847](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_847](#) was added in 8.0.11.

- Error number: [MY-012673](#); Symbol: [ER\\_IB\\_MSG\\_848](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_848](#) was added in 8.0.11.

- Error number: [MY-012674](#); Symbol: [ER\\_IB\\_MSG\\_849](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_849](#) was added in 8.0.11.

- Error number: [MY-012675](#); Symbol: [ER\\_IB\\_MSG\\_850](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_850](#) was added in 8.0.11.

- Error number: [MY-012676](#); Symbol: [ER\\_IB\\_MSG\\_851](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_851](#) was added in 8.0.11.

- Error number: [MY-012677](#); Symbol: [ER\\_IB\\_MSG\\_852](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_852](#) was added in 8.0.11.

- Error number: [MY-012678](#); Symbol: [ER\\_IB\\_MSG\\_853](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_853](#) was added in 8.0.11.

- Error number: [MY-012679](#); Symbol: [ER\\_IB\\_MSG\\_854](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_854](#) was added in 8.0.11.

- Error number: [MY-012680](#); Symbol: [ER\\_IB\\_MSG\\_855](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_855](#) was added in 8.0.11.

- Error number: [MY-012681](#); Symbol: [ER\\_IB\\_MSG\\_856](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_856](#) was added in 8.0.11.

- Error number: [MY-012682](#); Symbol: [ER\\_IB\\_MSG\\_857](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_857](#) was added in 8.0.11.

- Error number: [MY-012683](#); Symbol: [ER\\_IB\\_MSG\\_858](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_858](#) was added in 8.0.11.

- Error number: [MY-012684](#); Symbol: [ER\\_IB\\_MSG\\_859](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_859](#) was added in 8.0.11.

- Error number: [MY-012685](#); Symbol: [ER\\_IB\\_MSG\\_860](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_860](#) was added in 8.0.11.

- Error number: [MY-012686](#); Symbol: [ER\\_IB\\_MSG\\_861](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_861](#) was added in 8.0.11.

- Error number: [MY-012687](#); Symbol: [ER\\_IB\\_MSG\\_862](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_862](#) was added in 8.0.11.

- Error number: [MY-012688](#); Symbol: [ER\\_IB\\_MSG\\_863](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_863](#) was added in 8.0.11.

- Error number: [MY-012689](#); Symbol: [ER\\_IB\\_MSG\\_864](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_864](#) was added in 8.0.11.

- Error number: [MY-012690](#); Symbol: [ER\\_IB\\_MSG\\_865](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_865](#) was added in 8.0.11.

- Error number: [MY-012691](#); Symbol: [ER\\_IB\\_MSG\\_866](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_866](#) was added in 8.0.11.

- Error number: [MY-012692](#); Symbol: [ER\\_IB\\_MSG\\_867](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_867](#) was added in 8.0.11.

- Error number: [MY-012693](#); Symbol: [ER\\_IB\\_MSG\\_868](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_868](#) was added in 8.0.11.

- Error number: [MY-012694](#); Symbol: [ER\\_IB\\_MSG\\_869](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_869](#) was added in 8.0.11.

- Error number: [MY-012695](#); Symbol: [ER\\_IB\\_MSG\\_870](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_870](#) was added in 8.0.11.

- Error number: [MY-012696](#); Symbol: [ER\\_IB\\_MSG\\_871](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_871](#) was added in 8.0.11.

- Error number: [MY-012697](#); Symbol: [ER\\_IB\\_MSG\\_872](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_872](#) was added in 8.0.11.

- Error number: [MY-012698](#); Symbol: [ER\\_IB\\_MSG\\_873](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_873](#) was added in 8.0.11.

- Error number: [MY-012699](#); Symbol: [ER\\_IB\\_MSG\\_874](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_874](#) was added in 8.0.11.

- Error number: [MY-012700](#); Symbol: [ER\\_IB\\_MSG\\_875](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_875](#) was added in 8.0.11.

- Error number: [MY-012701](#); Symbol: [ER\\_IB\\_MSG\\_876](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_876](#) was added in 8.0.11.

- Error number: [MY-012702](#); Symbol: [ER\\_IB\\_MSG\\_877](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_877](#) was added in 8.0.11.

- Error number: [MY-012703](#); Symbol: [ER\\_IB\\_MSG\\_878](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_878](#) was added in 8.0.11.

- Error number: [MY-012704](#); Symbol: [ER\\_IB\\_MSG\\_879](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_879](#) was added in 8.0.11.

- Error number: [MY-012705](#); Symbol: [ER\\_IB\\_MSG\\_880](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_880](#) was added in 8.0.11.

- Error number: [MY-012706](#); Symbol: [ER\\_IB\\_MSG\\_881](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_881](#) was added in 8.0.11.

- Error number: [MY-012707](#); Symbol: [ER\\_IB\\_MSG\\_882](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_882](#) was added in 8.0.11.

- Error number: [MY-012708](#); Symbol: [ER\\_IB\\_MSG\\_883](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_883](#) was added in 8.0.11.

- Error number: [MY-012709](#); Symbol: [ER\\_IB\\_MSG\\_884](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_884](#) was added in 8.0.11.

- Error number: [MY-012710](#); Symbol: [ER\\_IB\\_MSG\\_885](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_885](#) was added in 8.0.11.

- Error number: [MY-012711](#); Symbol: [ER\\_IB\\_MSG\\_886](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_886](#) was added in 8.0.11.

- Error number: [MY-012712](#); Symbol: [ER\\_IB\\_MSG\\_887](#); SQLSTATE: [HY000](#)



---

Message: %s

[ER\\_IB\\_MSG\\_887](#) was added in 8.0.11.

- Error number: [MY-012713](#); Symbol: [ER\\_IB\\_MSG\\_888](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_888](#) was added in 8.0.11.

- Error number: [MY-012714](#); Symbol: [ER\\_IB\\_MSG\\_889](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_889](#) was added in 8.0.11.

- Error number: [MY-012715](#); Symbol: [ER\\_IB\\_MSG\\_890](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_890](#) was added in 8.0.11.

- Error number: [MY-012716](#); Symbol: [ER\\_IB\\_MSG\\_891](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_891](#) was added in 8.0.11.

- Error number: [MY-012717](#); Symbol: [ER\\_IB\\_MSG\\_892](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_892](#) was added in 8.0.11.

- Error number: [MY-012718](#); Symbol: [ER\\_IB\\_MSG\\_893](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_893](#) was added in 8.0.11.

- Error number: [MY-012719](#); Symbol: [ER\\_IB\\_MSG\\_894](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_894](#) was added in 8.0.11.

- Error number: [MY-012720](#); Symbol: [ER\\_IB\\_MSG\\_895](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_895](#) was added in 8.0.11.

- Error number: [MY-012721](#); Symbol: [ER\\_IB\\_MSG\\_896](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_896](#) was added in 8.0.11.

- Error number: [MY-012722](#); Symbol: [ER\\_IB\\_MSG\\_897](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_897](#) was added in 8.0.11.

- Error number: [MY-012723](#); Symbol: [ER\\_IB\\_MSG\\_898](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_898](#) was added in 8.0.11.

- Error number: [MY-012724](#); Symbol: [ER\\_IB\\_MSG\\_899](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_899](#) was added in 8.0.11.

- Error number: [MY-012725](#); Symbol: [ER\\_IB\\_MSG\\_900](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_900](#) was added in 8.0.11.

- Error number: [MY-012726](#); Symbol: [ER\\_IB\\_MSG\\_901](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_901](#) was added in 8.0.11.

- Error number: [MY-012727](#); Symbol: [ER\\_IB\\_MSG\\_902](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_902](#) was added in 8.0.11.

- Error number: [MY-012728](#); Symbol: [ER\\_IB\\_MSG\\_903](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_903](#) was added in 8.0.11.

- Error number: [MY-012729](#); Symbol: [ER\\_IB\\_MSG\\_904](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_904](#) was added in 8.0.11.

- Error number: [MY-012730](#); Symbol: [ER\\_IB\\_MSG\\_905](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_905](#) was added in 8.0.11.

- Error number: [MY-012731](#); Symbol: [ER\\_IB\\_MSG\\_906](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_906](#) was added in 8.0.11.

- Error number: [MY-012732](#); Symbol: [ER\\_IB\\_MSG\\_907](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_907](#) was added in 8.0.11.

- Error number: [MY-012733](#); Symbol: [ER\\_IB\\_MSG\\_908](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_908](#) was added in 8.0.11.

- Error number: [MY-012734](#); Symbol: [ER\\_IB\\_MSG\\_909](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_909](#) was added in 8.0.11.

- Error number: [MY-012735](#); Symbol: [ER\\_IB\\_MSG\\_910](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_910](#) was added in 8.0.11.

- Error number: [MY-012736](#); Symbol: [ER\\_IB\\_MSG\\_911](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_911](#) was added in 8.0.11.

- Error number: [MY-012737](#); Symbol: [ER\\_IB\\_MSG\\_912](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_912](#) was added in 8.0.11.

- Error number: [MY-012738](#); Symbol: [ER\\_IB\\_MSG\\_913](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_913](#) was added in 8.0.11.

- Error number: [MY-012739](#); Symbol: [ER\\_IB\\_MSG\\_914](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_914](#) was added in 8.0.11.

- Error number: [MY-012740](#); Symbol: [ER\\_IB\\_MSG\\_915](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_915](#) was added in 8.0.11.

- Error number: [MY-012741](#); Symbol: [ER\\_IB\\_MSG\\_916](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_916](#) was added in 8.0.11.

- Error number: [MY-012742](#); Symbol: [ER\\_IB\\_MSG\\_917](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_917](#) was added in 8.0.11.

- Error number: [MY-012743](#); Symbol: [ER\\_IB\\_MSG\\_918](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_918](#) was added in 8.0.11.

- Error number: [MY-012744](#); Symbol: [ER\\_IB\\_MSG\\_919](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_919](#) was added in 8.0.11.

- Error number: [MY-012745](#); Symbol: [ER\\_IB\\_MSG\\_920](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_920](#) was added in 8.0.11.

- Error number: [MY-012746](#); Symbol: [ER\\_IB\\_MSG\\_921](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_921](#) was added in 8.0.11.

- Error number: [MY-012747](#); Symbol: [ER\\_IB\\_MSG\\_922](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_922](#) was added in 8.0.11.

- Error number: [MY-012748](#); Symbol: [ER\\_IB\\_MSG\\_923](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_923](#) was added in 8.0.11.

- Error number: [MY-012749](#); Symbol: [ER\\_IB\\_MSG\\_924](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_924](#) was added in 8.0.11.

- Error number: [MY-012750](#); Symbol: [ER\\_IB\\_MSG\\_925](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_925](#) was added in 8.0.11.

- Error number: [MY-012751](#); Symbol: [ER\\_IB\\_MSG\\_926](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_926](#) was added in 8.0.11.

- Error number: [MY-012752](#); Symbol: [ER\\_IB\\_MSG\\_927](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_927](#) was added in 8.0.11.

- Error number: [MY-012753](#); Symbol: [ER\\_IB\\_MSG\\_928](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_928](#) was added in 8.0.11.

- Error number: [MY-012754](#); Symbol: [ER\\_IB\\_MSG\\_929](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_929](#) was added in 8.0.11.

- Error number: [MY-012755](#); Symbol: [ER\\_IB\\_MSG\\_930](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_930](#) was added in 8.0.11.

- Error number: [MY-012756](#); Symbol: [ER\\_IB\\_MSG\\_931](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_931](#) was added in 8.0.11.

- Error number: [MY-012757](#); Symbol: [ER\\_IB\\_MSG\\_932](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_932](#) was added in 8.0.11.

- Error number: [MY-012758](#); Symbol: [ER\\_IB\\_MSG\\_933](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_933](#) was added in 8.0.11.

- Error number: [MY-012759](#); Symbol: [ER\\_IB\\_MSG\\_934](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_934](#) was added in 8.0.11.

- Error number: [MY-012760](#); Symbol: [ER\\_IB\\_MSG\\_935](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_935](#) was added in 8.0.11.

- Error number: [MY-012761](#); Symbol: [ER\\_IB\\_MSG\\_936](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_936](#) was added in 8.0.11.

- Error number: [MY-012762](#); Symbol: [ER\\_IB\\_MSG\\_937](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_937](#) was added in 8.0.11.

- Error number: [MY-012763](#); Symbol: [ER\\_IB\\_MSG\\_938](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_938](#) was added in 8.0.11.

- Error number: [MY-012764](#); Symbol: [ER\\_IB\\_MSG\\_939](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_939](#) was added in 8.0.11.

- Error number: [MY-012765](#); Symbol: [ER\\_IB\\_MSG\\_940](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_940](#) was added in 8.0.11.

- Error number: [MY-012766](#); Symbol: [ER\\_IB\\_MSG\\_941](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_941](#) was added in 8.0.11.

- Error number: [MY-012767](#); Symbol: [ER\\_IB\\_MSG\\_942](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_942](#) was added in 8.0.11.

- Error number: [MY-012768](#); Symbol: [ER\\_IB\\_MSG\\_943](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_943](#) was added in 8.0.11.

- Error number: [MY-012769](#); Symbol: [ER\\_IB\\_MSG\\_944](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_944](#) was added in 8.0.11.

- Error number: [MY-012770](#); Symbol: [ER\\_IB\\_MSG\\_945](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_945](#) was added in 8.0.11.

- Error number: [MY-012771](#); Symbol: [ER\\_IB\\_MSG\\_946](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_946](#) was added in 8.0.11.

- Error number: [MY-012772](#); Symbol: [ER\\_IB\\_MSG\\_947](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_947](#) was added in 8.0.11.

- Error number: [MY-012773](#); Symbol: [ER\\_IB\\_MSG\\_948](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_948](#) was added in 8.0.11.

- Error number: [MY-012774](#); Symbol: [ER\\_IB\\_MSG\\_949](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_949](#) was added in 8.0.11.

- Error number: [MY-012775](#); Symbol: [ER\\_IB\\_MSG\\_950](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_950](#) was added in 8.0.11.

- Error number: [MY-012776](#); Symbol: [ER\\_IB\\_MSG\\_951](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_951](#) was added in 8.0.11.

- Error number: [MY-012777](#); Symbol: [ER\\_IB\\_MSG\\_952](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_952](#) was added in 8.0.11.

- Error number: [MY-012778](#); Symbol: [ER\\_IB\\_MSG\\_953](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_953](#) was added in 8.0.11.

- Error number: [MY-012779](#); Symbol: [ER\\_IB\\_MSG\\_954](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_954](#) was added in 8.0.11.

- Error number: [MY-012780](#); Symbol: [ER\\_IB\\_MSG\\_955](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_955](#) was added in 8.0.11.

- Error number: [MY-012781](#); Symbol: [ER\\_IB\\_MSG\\_956](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_956](#) was added in 8.0.11.

- Error number: [MY-012782](#); Symbol: [ER\\_IB\\_MSG\\_957](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_957](#) was added in 8.0.11.

- Error number: [MY-012783](#); Symbol: [ER\\_IB\\_MSG\\_958](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_958](#) was added in 8.0.11.

- Error number: [MY-012784](#); Symbol: [ER\\_IB\\_MSG\\_959](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_959](#) was added in 8.0.11.

- Error number: [MY-012785](#); Symbol: [ER\\_IB\\_MSG\\_960](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_960](#) was added in 8.0.11.

- Error number: [MY-012786](#); Symbol: [ER\\_IB\\_MSG\\_961](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_961](#) was added in 8.0.11.

- Error number: [MY-012787](#); Symbol: [ER\\_IB\\_MSG\\_962](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_962](#) was added in 8.0.11.

- Error number: [MY-012788](#); Symbol: [ER\\_IB\\_MSG\\_963](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_963](#) was added in 8.0.11.

- Error number: [MY-012789](#); Symbol: [ER\\_IB\\_MSG\\_964](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_964](#) was added in 8.0.11.

- Error number: [MY-012790](#); Symbol: [ER\\_IB\\_MSG\\_965](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_965](#) was added in 8.0.11.

- Error number: [MY-012791](#); Symbol: [ER\\_IB\\_MSG\\_966](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_966](#) was added in 8.0.11.

- Error number: [MY-012792](#); Symbol: [ER\\_IB\\_MSG\\_967](#); SQLSTATE: [HY000](#)



---

Message: %s

[ER\\_IB\\_MSG\\_967](#) was added in 8.0.11.

- Error number: [MY-012793](#); Symbol: [ER\\_IB\\_MSG\\_968](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_968](#) was added in 8.0.11.

- Error number: [MY-012794](#); Symbol: [ER\\_IB\\_MSG\\_969](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_969](#) was added in 8.0.11.

- Error number: [MY-012795](#); Symbol: [ER\\_IB\\_MSG\\_970](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_970](#) was added in 8.0.11.

- Error number: [MY-012796](#); Symbol: [ER\\_IB\\_MSG\\_971](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_971](#) was added in 8.0.11.

- Error number: [MY-012797](#); Symbol: [ER\\_IB\\_MSG\\_972](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_972](#) was added in 8.0.11.

- Error number: [MY-012798](#); Symbol: [ER\\_IB\\_MSG\\_973](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_973](#) was added in 8.0.11.

- Error number: [MY-012799](#); Symbol: [ER\\_IB\\_MSG\\_974](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_974](#) was added in 8.0.11.

- Error number: [MY-012800](#); Symbol: [ER\\_IB\\_MSG\\_975](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_975](#) was added in 8.0.11.

- Error number: [MY-012801](#); Symbol: [ER\\_IB\\_MSG\\_976](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_976](#) was added in 8.0.11.

- Error number: [MY-012802](#); Symbol: [ER\\_IB\\_MSG\\_977](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_977](#) was added in 8.0.11.

- Error number: [MY-012803](#); Symbol: [ER\\_IB\\_MSG\\_978](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_978](#) was added in 8.0.11.

- Error number: [MY-012804](#); Symbol: [ER\\_IB\\_MSG\\_979](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_979](#) was added in 8.0.11.

- Error number: [MY-012805](#); Symbol: [ER\\_IB\\_MSG\\_980](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_980](#) was added in 8.0.11.

- Error number: [MY-012806](#); Symbol: [ER\\_IB\\_MSG\\_981](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_981](#) was added in 8.0.11.

- Error number: [MY-012807](#); Symbol: [ER\\_IB\\_MSG\\_982](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_982](#) was added in 8.0.11.

- Error number: [MY-012808](#); Symbol: [ER\\_IB\\_MSG\\_983](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_983](#) was added in 8.0.11.

- Error number: [MY-012809](#); Symbol: [ER\\_IB\\_MSG\\_984](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_984](#) was added in 8.0.11.

- Error number: [MY-012810](#); Symbol: [ER\\_IB\\_MSG\\_985](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_985](#) was added in 8.0.11.

- Error number: [MY-012811](#); Symbol: [ER\\_IB\\_MSG\\_986](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_986](#) was added in 8.0.11.

- Error number: [MY-012812](#); Symbol: [ER\\_IB\\_MSG\\_987](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_987](#) was added in 8.0.11.

- Error number: [MY-012813](#); Symbol: [ER\\_IB\\_MSG\\_988](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_988](#) was added in 8.0.11.

- Error number: [MY-012814](#); Symbol: [ER\\_IB\\_MSG\\_989](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_989](#) was added in 8.0.11.

- Error number: [MY-012815](#); Symbol: [ER\\_IB\\_MSG\\_990](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_990](#) was added in 8.0.11.

- Error number: [MY-012816](#); Symbol: [ER\\_IB\\_MSG\\_991](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_991](#) was added in 8.0.11.

- Error number: [MY-012817](#); Symbol: [ER\\_IB\\_MSG\\_992](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_992](#) was added in 8.0.11.

- Error number: [MY-012818](#); Symbol: [ER\\_IB\\_MSG\\_993](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_993](#) was added in 8.0.11.

- Error number: [MY-012819](#); Symbol: [ER\\_IB\\_MSG\\_994](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_994](#) was added in 8.0.11.

- Error number: [MY-012820](#); Symbol: [ER\\_IB\\_MSG\\_995](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_995](#) was added in 8.0.11.

- Error number: [MY-012821](#); Symbol: [ER\\_IB\\_MSG\\_996](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_996](#) was added in 8.0.11.

- Error number: [MY-012822](#); Symbol: [ER\\_IB\\_MSG\\_997](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_997](#) was added in 8.0.11.

- Error number: [MY-012823](#); Symbol: [ER\\_IB\\_MSG\\_998](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_998](#) was added in 8.0.11.

- Error number: [MY-012824](#); Symbol: [ER\\_IB\\_MSG\\_999](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_999](#) was added in 8.0.11.

- Error number: [MY-012825](#); Symbol: [ER\\_IB\\_MSG\\_1000](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1000](#) was added in 8.0.11.

- Error number: [MY-012826](#); Symbol: [ER\\_IB\\_MSG\\_1001](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1001](#) was added in 8.0.11.

- Error number: [MY-012827](#); Symbol: [ER\\_IB\\_MSG\\_1002](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1002](#) was added in 8.0.11.

- Error number: [MY-012828](#); Symbol: [ER\\_IB\\_MSG\\_1003](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1003](#) was added in 8.0.11.

- Error number: [MY-012829](#); Symbol: [ER\\_IB\\_MSG\\_1004](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1004](#) was added in 8.0.11.

- Error number: [MY-012830](#); Symbol: [ER\\_IB\\_MSG\\_1005](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1005](#) was added in 8.0.11.

- Error number: [MY-012831](#); Symbol: [ER\\_IB\\_MSG\\_1006](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1006](#) was added in 8.0.11.

- Error number: [MY-012832](#); Symbol: [ER\\_IB\\_MSG\\_1007](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1007](#) was added in 8.0.11.

- Error number: [MY-012833](#); Symbol: [ER\\_IB\\_MSG\\_1008](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1008](#) was added in 8.0.11.

- Error number: [MY-012834](#); Symbol: [ER\\_IB\\_MSG\\_1009](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1009](#) was added in 8.0.11.

- Error number: [MY-012835](#); Symbol: [ER\\_IB\\_MSG\\_1010](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1010](#) was added in 8.0.11.

- Error number: [MY-012836](#); Symbol: [ER\\_IB\\_MSG\\_1011](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1011](#) was added in 8.0.11.

- Error number: [MY-012837](#); Symbol: [ER\\_IB\\_MSG\\_1012](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1012](#) was added in 8.0.11.

- Error number: [MY-012838](#); Symbol: [ER\\_IB\\_MSG\\_1013](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1013](#) was added in 8.0.11.

- Error number: [MY-012839](#); Symbol: [ER\\_IB\\_MSG\\_1014](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1014](#) was added in 8.0.11.

- Error number: [MY-012840](#); Symbol: [ER\\_IB\\_MSG\\_1015](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1015](#) was added in 8.0.11.

- Error number: [MY-012841](#); Symbol: [ER\\_IB\\_MSG\\_1016](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1016](#) was added in 8.0.11.

- Error number: [MY-012842](#); Symbol: [ER\\_IB\\_MSG\\_1017](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1017](#) was added in 8.0.11.

- Error number: [MY-012843](#); Symbol: [ER\\_IB\\_MSG\\_1018](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1018](#) was added in 8.0.11.

- Error number: [MY-012844](#); Symbol: [ER\\_IB\\_MSG\\_1019](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1019](#) was added in 8.0.11.

- Error number: [MY-012845](#); Symbol: [ER\\_IB\\_MSG\\_1020](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1020](#) was added in 8.0.11.

- Error number: [MY-012846](#); Symbol: [ER\\_IB\\_MSG\\_1021](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1021](#) was added in 8.0.11.

- Error number: [MY-012847](#); Symbol: [ER\\_IB\\_MSG\\_1022](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1022](#) was added in 8.0.11.

- Error number: [MY-012848](#); Symbol: [ER\\_IB\\_MSG\\_1023](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1023](#) was added in 8.0.11.

- Error number: [MY-012849](#); Symbol: [ER\\_IB\\_MSG\\_1024](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1024](#) was added in 8.0.11.

- Error number: [MY-012850](#); Symbol: [ER\\_IB\\_MSG\\_1025](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1025](#) was added in 8.0.11.

- Error number: [MY-012851](#); Symbol: [ER\\_IB\\_MSG\\_1026](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1026](#) was added in 8.0.11.

- Error number: [MY-012852](#); Symbol: [ER\\_IB\\_MSG\\_1027](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1027](#) was added in 8.0.11.

- Error number: [MY-012853](#); Symbol: [ER\\_IB\\_MSG\\_1028](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1028](#) was added in 8.0.11.

- Error number: [MY-012854](#); Symbol: [ER\\_IB\\_MSG\\_1029](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1029](#) was added in 8.0.11.

- Error number: [MY-012855](#); Symbol: [ER\\_IB\\_MSG\\_1030](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1030](#) was added in 8.0.11.

- Error number: [MY-012856](#); Symbol: [ER\\_IB\\_MSG\\_1031](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1031](#) was added in 8.0.11.

- Error number: [MY-012857](#); Symbol: [ER\\_IB\\_MSG\\_1032](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1032](#) was added in 8.0.11.

- Error number: [MY-012858](#); Symbol: [ER\\_IB\\_MSG\\_1033](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1033](#) was added in 8.0.11.

- Error number: [MY-012859](#); Symbol: [ER\\_IB\\_MSG\\_1034](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1034](#) was added in 8.0.11.

- Error number: [MY-012860](#); Symbol: [ER\\_IB\\_MSG\\_1035](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1035](#) was added in 8.0.11.

- Error number: [MY-012861](#); Symbol: [ER\\_IB\\_MSG\\_1036](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1036](#) was added in 8.0.11.

- Error number: [MY-012862](#); Symbol: [ER\\_IB\\_MSG\\_1037](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1037](#) was added in 8.0.11.

- Error number: [MY-012863](#); Symbol: [ER\\_IB\\_MSG\\_1038](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1038](#) was added in 8.0.11.

- Error number: [MY-012864](#); Symbol: [ER\\_IB\\_MSG\\_1039](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1039](#) was added in 8.0.11.

- Error number: [MY-012865](#); Symbol: [ER\\_IB\\_MSG\\_1040](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1040](#) was added in 8.0.11.

- Error number: [MY-012866](#); Symbol: [ER\\_IB\\_MSG\\_1041](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1041](#) was added in 8.0.11.

- Error number: [MY-012867](#); Symbol: [ER\\_IB\\_MSG\\_1042](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1042](#) was added in 8.0.11.

- Error number: [MY-012868](#); Symbol: [ER\\_IB\\_MSG\\_1043](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1043](#) was added in 8.0.11.

- Error number: [MY-012869](#); Symbol: [ER\\_IB\\_MSG\\_1044](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1044](#) was added in 8.0.11.

- Error number: [MY-012870](#); Symbol: [ER\\_IB\\_MSG\\_1045](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1045](#) was added in 8.0.11.

- Error number: [MY-012871](#); Symbol: [ER\\_IB\\_MSG\\_1046](#); SQLSTATE: [HY000](#)

Message: Old log sequence number %llu was greater than the new log sequence number %llu. Please submit a bug report to <http://bugs.mysql.com>

[ER\\_IB\\_MSG\\_1046](#) was added in 8.0.11.



- 
- Error number: [MY-012872](#); Symbol: [ER\\_IB\\_MSG\\_1047](#); SQLSTATE: [HY000](#)  
Message: Semaphore wait has lasted > %llu seconds. We intentionally crash the server because it appears to be hung.  
[ER\\_IB\\_MSG\\_1047](#) was added in 8.0.11.
  - Error number: [MY-012873](#); Symbol: [ER\\_IB\\_MSG\\_1048](#); SQLSTATE: [HY000](#)  
Message: Waiting for %llu table(s) to be dropped  
[ER\\_IB\\_MSG\\_1048](#) was added in 8.0.11.
  - Error number: [MY-012874](#); Symbol: [ER\\_IB\\_MSG\\_1049](#); SQLSTATE: [HY000](#)  
Message: Waiting for change buffer merge to complete number of bytes of change buffer just merged: %llu  
[ER\\_IB\\_MSG\\_1049](#) was added in 8.0.11.
  - Error number: [MY-012875](#); Symbol: [ER\\_IB\\_MSG\\_1050](#); SQLSTATE: [HY000](#)  
Message: Can't set undo tablespace(s) to be encrypted since --innodb\_undo\_tablespaces=0.  
[ER\\_IB\\_MSG\\_1050](#) was added in 8.0.11, removed after 8.0.15.
  - Error number: [MY-012876](#); Symbol: [ER\\_IB\\_MSG\\_1051](#); SQLSTATE: [HY000](#)  
Message: Can't set undo tablespace(s) to be encrypted in read-only-mode.  
[ER\\_IB\\_MSG\\_1051](#) was added in 8.0.11.
  - Error number: [MY-012877](#); Symbol: [ER\\_IB\\_MSG\\_1052](#); SQLSTATE: [HY000](#)  
Message: Can't set undo tablespace '%s' to be encrypted.  
[ER\\_IB\\_MSG\\_1052](#) was added in 8.0.11.
  - Error number: [MY-012878](#); Symbol: [ER\\_IB\\_MSG\\_1053](#); SQLSTATE: [HY000](#)  
Message: Can't set undo tablespace '%s' to be encrypted. Failed to write header page.  
[ER\\_IB\\_MSG\\_1053](#) was added in 8.0.11.
  - Error number: [MY-012879](#); Symbol: [ER\\_IB\\_MSG\\_1054](#); SQLSTATE: [HY000](#)  
Message: Can't set undo tablespace '%s' to be encrypted. Error %d - %s  
[ER\\_IB\\_MSG\\_1054](#) was added in 8.0.11.
  - Error number: [MY-012880](#); Symbol: [ER\\_IB\\_MSG\\_1055](#); SQLSTATE: [HY000](#)  
Message: Encryption is enabled for undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_1055](#) was added in 8.0.11.
  - Error number: [MY-012881](#); Symbol: [ER\\_IB\\_MSG\\_1056](#); SQLSTATE: [HY000](#)  
Message: Can't rotate encryption on undo tablespace '%s'.

---

[ER\\_IB\\_MSG\\_1056](#) was added in 8.0.11.

- Error number: [MY-012882](#); Symbol: [ER\\_IB\\_MSG\\_1057](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace '%s'.

[ER\\_IB\\_MSG\\_1057](#) was added in 8.0.11.

- Error number: [MY-012883](#); Symbol: [ER\\_IB\\_MSG\\_1058](#); SQLSTATE: [HY000](#)

Message: `os_file_get_status()` failed on '%s'. Can't determine file permissions.

[ER\\_IB\\_MSG\\_1058](#) was added in 8.0.11.

- Error number: [MY-012884](#); Symbol: [ER\\_IB\\_MSG\\_1059](#); SQLSTATE: [HY000](#)

Message: %s can't be opened in %s mode.

[ER\\_IB\\_MSG\\_1059](#) was added in 8.0.11.

- Error number: [MY-012885](#); Symbol: [ER\\_IB\\_MSG\\_1060](#); SQLSTATE: [HY000](#)

Message: '%s' not a regular file.

[ER\\_IB\\_MSG\\_1060](#) was added in 8.0.11.

- Error number: [MY-012886](#); Symbol: [ER\\_IB\\_MSG\\_1061](#); SQLSTATE: [HY000](#)

Message: Cannot create %s

[ER\\_IB\\_MSG\\_1061](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012886](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_OS\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Cannot create %s

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_OS\\_CREATE\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-012887](#); Symbol: [ER\\_IB\\_MSG\\_1062](#); SQLSTATE: [HY000](#)

Message: Setting log file %s size to %llu MB. Progress : %u%%

[ER\\_IB\\_MSG\\_1062](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012887](#); Symbol: [ER\\_IB\\_MSG\\_FILE\\_RESIZE](#); SQLSTATE: [HY000](#)

Message: Setting file %s size to %llu MB. Progress : %u%%

[ER\\_IB\\_MSG\\_FILE\\_RESIZE](#) was added in 8.0.30.

- Error number: [MY-012888](#); Symbol: [ER\\_IB\\_MSG\\_1063](#); SQLSTATE: [HY000](#)

Message: Cannot set log file %s to size %llu MB

[ER\\_IB\\_MSG\\_1063](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012888](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_RESIZE\\_FAILED](#); SQLSTATE: [HY000](#)

---

Message: Cannot resize redo log file %s to %llu MB (%s)

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_RESIZE\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-012889](#); Symbol: [ER\\_IB\\_MSG\\_1064](#); SQLSTATE: [HY000](#)

Message: Cannot create log files in read-only mode

[ER\\_IB\\_MSG\\_1064](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012889](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_CREATE\\_AND\\_READ\\_ONLY\\_MODE](#); SQLSTATE: [HY000](#)

Message: Cannot create redo log files in read-only mode (--innodb-read-only).

[ER\\_IB\\_MSG\\_LOG\\_FILES\\_CREATE\\_AND\\_READ\\_ONLY\\_MODE](#) was added in 8.0.30.

- Error number: [MY-012890](#); Symbol: [ER\\_IB\\_MSG\\_1065](#); SQLSTATE: [HY000](#)

Message: Redo log encryption is enabled, but the keyring is not loaded.

[ER\\_IB\\_MSG\\_1065](#) was added in 8.0.11.

- Error number: [MY-012891](#); Symbol: [ER\\_IB\\_MSG\\_1066](#); SQLSTATE: [HY000](#)

Message: Cannot create file for log file %s.

[ER\\_IB\\_MSG\\_1066](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012891](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_PREPARE\\_ON\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create redo log file %s (error: %d) for start LSN %llu

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_PREPARE\\_ON\\_CREATE\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-012892](#); Symbol: [ER\\_IB\\_MSG\\_1067](#); SQLSTATE: [HY000](#)

Message: Renaming log file %s to %s

[ER\\_IB\\_MSG\\_1067](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012893](#); Symbol: [ER\\_IB\\_MSG\\_1068](#); SQLSTATE: [HY000](#)

Message: New log files created, LSN=%llu

[ER\\_IB\\_MSG\\_1068](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012893](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: New redo log files created, LSN=%llu

[ER\\_IB\\_MSG\\_LOG\\_FILES\\_INITIALIZED](#) was added in 8.0.30.

- Error number: [MY-012894](#); Symbol: [ER\\_IB\\_MSG\\_1069](#); SQLSTATE: [HY000](#)

Message: Unable to open '%s'.

[ER\\_IB\\_MSG\\_1069](#) was added in 8.0.11, removed after 8.0.29.

- 
- Error number: [MY-012894](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_OPEN\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Unable to open '%s' (error: %d).  
[ER\\_IB\\_MSG\\_LOG\\_FILE\\_OPEN\\_FAILED](#) was added in 8.0.30.
  - Error number: [MY-012895](#); Symbol: [ER\\_IB\\_MSG\\_1070](#); SQLSTATE: [HY000](#)  
Message: Cannot create construction log file '%s' for undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_1070](#) was added in 8.0.11.
  - Error number: [MY-012896](#); Symbol: [ER\\_IB\\_MSG\\_1071](#); SQLSTATE: [HY000](#)  
Message: Creating UNDO Tablespace %s  
[ER\\_IB\\_MSG\\_1071](#) was added in 8.0.11.
  - Error number: [MY-012897](#); Symbol: [ER\\_IB\\_MSG\\_1072](#); SQLSTATE: [HY000](#)  
Message: Setting file %s size to %llu MB  
[ER\\_IB\\_MSG\\_1072](#) was added in 8.0.11.
  - Error number: [MY-012898](#); Symbol: [ER\\_IB\\_MSG\\_1073](#); SQLSTATE: [HY000](#)  
Message: Physically writing the file full  
[ER\\_IB\\_MSG\\_1073](#) was added in 8.0.11.
  - Error number: [MY-012899](#); Symbol: [ER\\_IB\\_MSG\\_1074](#); SQLSTATE: [HY000](#)  
Message: Error in creating %s: probably out of disk space  
[ER\\_IB\\_MSG\\_1074](#) was added in 8.0.11.
  - Error number: [MY-012900](#); Symbol: [ER\\_IB\\_MSG\\_1075](#); SQLSTATE: [HY000](#)  
Message: Can't set encryption metadata for space %s  
[ER\\_IB\\_MSG\\_1075](#) was added in 8.0.11.
  - Error number: [MY-012901](#); Symbol: [ER\\_IB\\_MSG\\_1076](#); SQLSTATE: [HY000](#)  
Message: Cannot read first page of '%s' - %s  
[ER\\_IB\\_MSG\\_1076](#) was added in 8.0.11.
  - Error number: [MY-012902](#); Symbol: [ER\\_IB\\_MSG\\_1077](#); SQLSTATE: [HY000](#)  
Message: Undo tablespace number %lu was being truncated when mysqld quit.  
[ER\\_IB\\_MSG\\_1077](#) was added in 8.0.11.
  - Error number: [MY-012903](#); Symbol: [ER\\_IB\\_MSG\\_1078](#); SQLSTATE: [HY000](#)  
Message: Cannot recover a truncated undo tablespace in read-only mode  
[ER\\_IB\\_MSG\\_1078](#) was added in 8.0.11.

- 
- Error number: [MY-012904](#); Symbol: [ER\\_IB\\_MSG\\_1079](#); SQLSTATE: [HY000](#)  
Message: Reconstructing undo tablespace number %lu.  
[ER\\_IB\\_MSG\\_1079](#) was added in 8.0.11.
  - Error number: [MY-012905](#); Symbol: [ER\\_IB\\_MSG\\_1080](#); SQLSTATE: [HY000](#)  
Message: Cannot create %s because %s already uses Space ID=%lu! Did you change innodb\_undo\_directory?  
[ER\\_IB\\_MSG\\_1080](#) was added in 8.0.11.
  - Error number: [MY-012906](#); Symbol: [ER\\_IB\\_MSG\\_1081](#); SQLSTATE: [HY000](#)  
Message: UNDO tablespace %s must be %s  
[ER\\_IB\\_MSG\\_1081](#) was added in 8.0.11.
  - Error number: [MY-012907](#); Symbol: [ER\\_IB\\_MSG\\_1082](#); SQLSTATE: [HY000](#)  
Message: Error creating file for %s  
[ER\\_IB\\_MSG\\_1082](#) was added in 8.0.11.
  - Error number: [MY-012908](#); Symbol: [ER\\_IB\\_MSG\\_1083](#); SQLSTATE: [HY000](#)  
Message: Error reading encryption for %s  
[ER\\_IB\\_MSG\\_1083](#) was added in 8.0.11.
  - Error number: [MY-012909](#); Symbol: [ER\\_IB\\_MSG\\_1084](#); SQLSTATE: [HY000](#)  
Message: Unable to open undo tablespace number %lu  
[ER\\_IB\\_MSG\\_1084](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012909](#); Symbol: [ER\\_IB\\_MSG\\_CANNOT\\_OPEN\\_57\\_UNDO](#); SQLSTATE: [HY000](#)  
Message: Unable to open undo tablespace number %lu  
[ER\\_IB\\_MSG\\_CANNOT\\_OPEN\\_57\\_UNDO](#) was added in 8.0.21.
  - Error number: [MY-012910](#); Symbol: [ER\\_IB\\_MSG\\_1085](#); SQLSTATE: [HY000](#)  
Message: Opened %llu existing undo tablespaces.  
[ER\\_IB\\_MSG\\_1085](#) was added in 8.0.11.
  - Error number: [MY-012911](#); Symbol: [ER\\_IB\\_MSG\\_1086](#); SQLSTATE: [HY000](#)  
Message: Cannot create undo tablespaces since innodb\_%s has been set. Using %llu existing undo tablespaces.  
[ER\\_IB\\_MSG\\_1086](#) was added in 8.0.11.
  - Error number: [MY-012912](#); Symbol: [ER\\_IB\\_MSG\\_1087](#); SQLSTATE: [HY000](#)  
Message: Cannot continue InnoDB startup in %s mode because there are no existing undo tablespaces found.

---

[ER\\_IB\\_MSG\\_1087](#) was added in 8.0.11.

- Error number: [MY-012913](#); Symbol: [ER\\_IB\\_MSG\\_1088](#); SQLSTATE: [HY000](#)

Message: Could not create undo tablespace '%s'.

[ER\\_IB\\_MSG\\_1088](#) was added in 8.0.11.

- Error number: [MY-012914](#); Symbol: [ER\\_IB\\_MSG\\_1089](#); SQLSTATE: [HY000](#)

Message: Error %d - %s - opening newly created undo tablespace '%s'.

[ER\\_IB\\_MSG\\_1089](#) was added in 8.0.11.

- Error number: [MY-012915](#); Symbol: [ER\\_IB\\_MSG\\_1090](#); SQLSTATE: [HY000](#)

Message: Created %llu undo tablespaces.

[ER\\_IB\\_MSG\\_1090](#) was added in 8.0.11.

- Error number: [MY-012916](#); Symbol: [ER\\_IB\\_MSG\\_1091](#); SQLSTATE: [HY000](#)

Message: Unable to create encrypted undo tablespace number %lu. please check if the keyring is initialized correctly

[ER\\_IB\\_MSG\\_1091](#) was added in 8.0.11.

- Error number: [MY-012917](#); Symbol: [ER\\_IB\\_MSG\\_1092](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace number %lu.

[ER\\_IB\\_MSG\\_1092](#) was added in 8.0.11.

- Error number: [MY-012918](#); Symbol: [ER\\_IB\\_MSG\\_1093](#); SQLSTATE: [HY000](#)

Message: Unable to initialize the header page in undo tablespace number %lu.

[ER\\_IB\\_MSG\\_1093](#) was added in 8.0.11.

- Error number: [MY-012919](#); Symbol: [ER\\_IB\\_MSG\\_1094](#); SQLSTATE: [HY000](#)

Message: Cannot delete old undo tablespaces because they contain undo logs for XA PREPARED transactions.

[ER\\_IB\\_MSG\\_1094](#) was added in 8.0.11.

- Error number: [MY-012920](#); Symbol: [ER\\_IB\\_MSG\\_1095](#); SQLSTATE: [HY000](#)

Message: Upgrading %zu existing undo tablespaces that were tracked in the system tablespace to %lu new independent undo tablespaces.

[ER\\_IB\\_MSG\\_1095](#) was added in 8.0.11.

- Error number: [MY-012921](#); Symbol: [ER\\_IB\\_MSG\\_1096](#); SQLSTATE: [HY000](#)

Message: Deleting %llu new independent undo tablespaces that we just created.

[ER\\_IB\\_MSG\\_1096](#) was added in 8.0.11.

- 
- Error number: [MY-012922](#); Symbol: [ER\\_IB\\_MSG\\_1097](#); SQLSTATE: [HY000](#)  
Message: Waiting for purge to start  
[ER\\_IB\\_MSG\\_1097](#) was added in 8.0.11.
  - Error number: [MY-012923](#); Symbol: [ER\\_IB\\_MSG\\_1098](#); SQLSTATE: [HY000](#)  
Message: Creating shared tablespace for temporary tables  
[ER\\_IB\\_MSG\\_1098](#) was added in 8.0.11.
  - Error number: [MY-012924](#); Symbol: [ER\\_IB\\_MSG\\_1099](#); SQLSTATE: [HY000](#)  
Message: The %s data file must be writable!  
[ER\\_IB\\_MSG\\_1099](#) was added in 8.0.11.
  - Error number: [MY-012925](#); Symbol: [ER\\_IB\\_MSG\\_1100](#); SQLSTATE: [HY000](#)  
Message: Could not create the shared %s.  
[ER\\_IB\\_MSG\\_1100](#) was added in 8.0.11.
  - Error number: [MY-012926](#); Symbol: [ER\\_IB\\_MSG\\_1101](#); SQLSTATE: [HY000](#)  
Message: Unable to create the shared %s.  
[ER\\_IB\\_MSG\\_1101](#) was added in 8.0.11.
  - Error number: [MY-012927](#); Symbol: [ER\\_IB\\_MSG\\_1102](#); SQLSTATE: [HY000](#)  
Message: The %s data file cannot be re-opened after check\_file\_spec() succeeded!  
[ER\\_IB\\_MSG\\_1102](#) was added in 8.0.11.
  - Error number: [MY-012928](#); Symbol: [ER\\_IB\\_MSG\\_1103](#); SQLSTATE: [HY000](#)  
Message: %d threads created by InnoDB had not exited at shutdown!  
[ER\\_IB\\_MSG\\_1103](#) was added in 8.0.11.
  - Error number: [MY-012929](#); Symbol: [ER\\_IB\\_MSG\\_1104](#); SQLSTATE: [HY000](#)  
Message: InnoDB Database creation was aborted %swith error %s. You may need to delete the ibdata1 file before trying to start up again.  
[ER\\_IB\\_MSG\\_1104](#) was added in 8.0.11.
  - Error number: [MY-012930](#); Symbol: [ER\\_IB\\_MSG\\_1105](#); SQLSTATE: [HY000](#)  
Message: Plugin initialization aborted %swith error %s.  
[ER\\_IB\\_MSG\\_1105](#) was added in 8.0.11.
  - Error number: [MY-012931](#); Symbol: [ER\\_IB\\_MSG\\_1106](#); SQLSTATE: [HY000](#)  
Message: Waiting for %llu buffer page I/Os to complete  
[ER\\_IB\\_MSG\\_1106](#) was added in 8.0.11, removed after 8.0.29.

- 
- Error number: [MY-012931](#); Symbol: [ER\\_IB\\_MSG\\_BUF\\_PENDING\\_IO](#); SQLSTATE: [HY000](#)  
Message: Waiting for %zu buffer page I/Os to complete.  
[ER\\_IB\\_MSG\\_BUF\\_PENDING\\_IO](#) was added in 8.0.30.
  - Error number: [MY-012932](#); Symbol: [ER\\_IB\\_MSG\\_1107](#); SQLSTATE: [HY000](#)  
Message: PUNCH HOLE support available  
[ER\\_IB\\_MSG\\_1107](#) was added in 8.0.11.
  - Error number: [MY-012933](#); Symbol: [ER\\_IB\\_MSG\\_1108](#); SQLSTATE: [HY000](#)  
Message: PUNCH HOLE support not available  
[ER\\_IB\\_MSG\\_1108](#) was added in 8.0.11.
  - Error number: [MY-012934](#); Symbol: [ER\\_IB\\_MSG\\_1109](#); SQLSTATE: [HY000](#)  
Message: Size of InnoDB's ulint is %zu but size of void\* is %zu. The sizes should be the same so that on a 64-bit platforms you can allocate more than 4 GB of memory.  
[ER\\_IB\\_MSG\\_1109](#) was added in 8.0.11.
  - Error number: [MY-012935](#); Symbol: [ER\\_IB\\_MSG\\_1110](#); SQLSTATE: [HY000](#)  
Message: Database upgrade cannot be accomplished in read-only mode.  
[ER\\_IB\\_MSG\\_1110](#) was added in 8.0.11.
  - Error number: [MY-012936](#); Symbol: [ER\\_IB\\_MSG\\_1111](#); SQLSTATE: [HY000](#)  
Message: Database upgrade cannot be accomplished with innodb\_force\_recovery > 0  
[ER\\_IB\\_MSG\\_1111](#) was added in 8.0.11.
  - Error number: [MY-012937](#); Symbol: [ER\\_IB\\_MSG\\_1112](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1112](#) was added in 8.0.11.
  - Error number: [MY-012938](#); Symbol: [ER\\_IB\\_MSG\\_1113](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1113](#) was added in 8.0.11.
  - Error number: [MY-012939](#); Symbol: [ER\\_IB\\_MSG\\_1114](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1114](#) was added in 8.0.11.
  - Error number: [MY-012940](#); Symbol: [ER\\_IB\\_MSG\\_1115](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1115](#) was added in 8.0.11.



- 
- Error number: [MY-012941](#); Symbol: [ER\\_IB\\_MSG\\_1116](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1116](#) was added in 8.0.11.
  - Error number: [MY-012942](#); Symbol: [ER\\_IB\\_MSG\\_1117](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1117](#) was added in 8.0.11.
  - Error number: [MY-012943](#); Symbol: [ER\\_IB\\_MSG\\_1118](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1118](#) was added in 8.0.11, removed after 8.0.22.
  - Error number: [MY-012944](#); Symbol: [ER\\_IB\\_MSG\\_1119](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1119](#) was added in 8.0.11.
  - Error number: [MY-012945](#); Symbol: [ER\\_IB\\_MSG\\_1120](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1120](#) was added in 8.0.11.
  - Error number: [MY-012946](#); Symbol: [ER\\_IB\\_MSG\\_1121](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1121](#) was added in 8.0.11.
  - Error number: [MY-012947](#); Symbol: [ER\\_IB\\_MSG\\_1122](#); SQLSTATE: [HY000](#)  
Message: MySQL was built without a memory barrier capability on this architecture, which might allow a mutex/rw\_lock violation under high thread concurrency. This may cause a hang.  
[ER\\_IB\\_MSG\\_1122](#) was added in 8.0.11.
  - Error number: [MY-012948](#); Symbol: [ER\\_IB\\_MSG\\_1123](#); SQLSTATE: [HY000](#)  
Message: Compressed tables use zlib %s  
[ER\\_IB\\_MSG\\_1123](#) was added in 8.0.11.
  - Error number: [MY-012949](#); Symbol: [ER\\_IB\\_MSG\\_1124](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1124](#) was added in 8.0.11.
  - Error number: [MY-012950](#); Symbol: [ER\\_IB\\_MSG\\_1125](#); SQLSTATE: [HY000](#)  
Message: Startup called second time during the process lifetime. In the MySQL Embedded Server Library you cannot call server\_init() more than once during the process lifetime.

---

[ER\\_IB\\_MSG\\_1125](#) was added in 8.0.11.

- Error number: [MY-012951](#); Symbol: [ER\\_IB\\_MSG\\_1126](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1126](#) was added in 8.0.11.

- Error number: [MY-012952](#); Symbol: [ER\\_IB\\_MSG\\_1127](#); SQLSTATE: [HY000](#)

Message: Unable to create monitor file %s: %s

[ER\\_IB\\_MSG\\_1127](#) was added in 8.0.11.

- Error number: [MY-012953](#); Symbol: [ER\\_IB\\_MSG\\_1128](#); SQLSTATE: [HY000](#)

Message: Disabling background ibuf IO read threads.

[ER\\_IB\\_MSG\\_1128](#) was added in 8.0.11.

- Error number: [MY-012954](#); Symbol: [ER\\_IB\\_MSG\\_1129](#); SQLSTATE: [HY000](#)

Message: Cannot initialize AIO sub-system

[ER\\_IB\\_MSG\\_1129](#) was added in 8.0.11.

- Error number: [MY-012955](#); Symbol: [ER\\_IB\\_MSG\\_1130](#); SQLSTATE: [HY000](#)

Message: Initializing buffer pool, total size = %lf%c, instances = %lu, chunk size = %lf%c

[ER\\_IB\\_MSG\\_1130](#) was added in 8.0.11.

- Error number: [MY-012956](#); Symbol: [ER\\_IB\\_MSG\\_1131](#); SQLSTATE: [HY000](#)

Message: Cannot allocate memory for the buffer pool

[ER\\_IB\\_MSG\\_1131](#) was added in 8.0.11.

- Error number: [MY-012957](#); Symbol: [ER\\_IB\\_MSG\\_1132](#); SQLSTATE: [HY000](#)

Message: Completed initialization of buffer pool

[ER\\_IB\\_MSG\\_1132](#) was added in 8.0.11.

- Error number: [MY-012958](#); Symbol: [ER\\_IB\\_MSG\\_1133](#); SQLSTATE: [HY000](#)

Message: Small buffer pool size (%lluM), the flst\_validate() debug function can cause a deadlock if the buffer pool fills up.

[ER\\_IB\\_MSG\\_1133](#) was added in 8.0.11.

- Error number: [MY-012959](#); Symbol: [ER\\_IB\\_MSG\\_1134](#); SQLSTATE: [HY000](#)

Message: Could not open or create the system tablespace. If you tried to add new data files to the system tablespace, and it failed here, you should now edit innodb\_data\_file\_path in my.cnf back to what it was, and remove the new ibdata files InnoDB created in this failed attempt. InnoDB only wrote those files full of zeros, but did not yet use them in any way. But be careful: do not remove old data files which contain your precious data!

---

`ER_IB_MSG_1134` was added in 8.0.11.

- Error number: `MY-012960`; Symbol: `ER_IB_MSG_1135`; SQLSTATE: `HY000`

Message: Cannot create log files because data files are corrupt or the database was not shut down cleanly after creating the data files.

`ER_IB_MSG_1135` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012960`; Symbol: `ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED`; SQLSTATE: `HY000`

Message: Cannot create redo log files because data files are corrupt or the database was not shut down cleanly after creating the data files.

`ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED` was added in 8.0.30.

- Error number: `MY-012961`; Symbol: `ER_IB_MSG_1136`; SQLSTATE: `HY000`

Message: Only one log file found

`ER_IB_MSG_1136` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012961`; Symbol: `ER_IB_MSG_LOG_FILES_INVALID_SET`; SQLSTATE: `HY000`

Message: Only one redo log file found

`ER_IB_MSG_LOG_FILES_INVALID_SET` was added in 8.0.30.

- Error number: `MY-012962`; Symbol: `ER_IB_MSG_1137`; SQLSTATE: `HY000`

Message: Log file %s size %llu is not a multiple of innodb\_page\_size

`ER_IB_MSG_1137` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012962`; Symbol: `ER_IB_MSG_LOG_FILE_SIZE_INVALID`; SQLSTATE: `HY000`

Message: The redo log file %s size %llu is not a multiple of innodb\_page\_size

`ER_IB_MSG_LOG_FILE_SIZE_INVALID` was added in 8.0.30.

- Error number: `MY-012963`; Symbol: `ER_IB_MSG_1138`; SQLSTATE: `HY000`

Message: Log file %s is of different size %llu bytes than other log files %llu bytes!

`ER_IB_MSG_1138` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012963`; Symbol: `ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES`; SQLSTATE: `HY000`

Message: The redo log file %s is of different size %llu bytes than other log files %llu bytes!

`ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES` was added in 8.0.30.

- Error number: `MY-012964`; Symbol: `ER_IB_MSG_1139`; SQLSTATE: `HY000`

Message: Use --innodb-directories to find the tablespace files. If that fails then use --innodb-force-recovery=1 to ignore this and to permanently lose all changes to the missing tablespace(s)

---

`ER_IB_MSG_1139` was added in 8.0.11.

- Error number: `MY-012965`; Symbol: `ER_IB_MSG_1140`; SQLSTATE: `HY000`

Message: The log file may have been corrupt and it is possible that the log scan or parsing did not proceed far enough in recovery. Please run CHECK TABLE on your InnoDB tables to check that they are ok! It may be safest to recover your InnoDB database from a backup!

`ER_IB_MSG_1140` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012965`; Symbol: `ER_IB_MSG_RECOVERY_CORRUPT`; SQLSTATE: `HY000`

Message: The redo log file may have been corrupt and it is possible that the log scan or parsing did not proceed far enough in recovery. Please run CHECK TABLE on your InnoDB tables to check that they are ok! It may be safest to recover your InnoDB database from a backup!

`ER_IB_MSG_RECOVERY_CORRUPT` was added in 8.0.30.

- Error number: `MY-012966`; Symbol: `ER_IB_MSG_1141`; SQLSTATE: `HY000`

Message: Cannot resize log files in read-only mode.

`ER_IB_MSG_1141` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012966`; Symbol: `ER_IB_MSG_LOG_FILES_RESIZE_ON_START_IN_READ_ONLY_MODE`; SQLSTATE: `HY000`

Message: Cannot resize redo log files in read-only mode. Provide `--innodb_redo_log_capacity >= %luMB` or start without `--innodb-read-only`.

`ER_IB_MSG_LOG_FILES_RESIZE_ON_START_IN_READ_ONLY_MODE` was added in 8.0.30, removed after 8.0.32.

- Error number: `MY-012967`; Symbol: `ER_IB_MSG_1142`; SQLSTATE: `HY000`

Message: Cannot open DD tablespace.

`ER_IB_MSG_1142` was added in 8.0.11.

- Error number: `MY-012968`; Symbol: `ER_IB_MSG_1143`; SQLSTATE: `HY000`

Message: Starting to delete and rewrite log files.

`ER_IB_MSG_1143` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012968`; Symbol: `ER_IB_MSG_LOG_FILES_REWRITING`; SQLSTATE: `HY000`

Message: Starting to delete and rewrite redo log files.

`ER_IB_MSG_LOG_FILES_REWRITING` was added in 8.0.30.

- Error number: `MY-012969`; Symbol: `ER_IB_MSG_1144`; SQLSTATE: `HY000`

Message: Undo from 5.7 found. It will be purged

`ER_IB_MSG_1144` was added in 8.0.11.

- Error number: `MY-012970`; Symbol: `ER_IB_MSG_1145`; SQLSTATE: `HY000`

---

Message: %s

[ER\\_IB\\_MSG\\_1145](#) was added in 8.0.11.

- Error number: [MY-012971](#); Symbol: [ER\\_IB\\_MSG\\_1146](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1146](#) was added in 8.0.11.

- Error number: [MY-012972](#); Symbol: [ER\\_IB\\_MSG\\_1147](#); SQLSTATE: [HY000](#)

Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is %lu pages

[ER\\_IB\\_MSG\\_1147](#) was added in 8.0.11.

- Error number: [MY-012973](#); Symbol: [ER\\_IB\\_MSG\\_1148](#); SQLSTATE: [HY000](#)

Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited innodb\_data\_file\_path in my.cnf in an inappropriate way, removing ibdata files from there? You can set innodb\_force\_recovery=1 in my.cnf to force a startup if you are trying to recover a badly corrupt database.

[ER\\_IB\\_MSG\\_1148](#) was added in 8.0.11.

- Error number: [MY-012974](#); Symbol: [ER\\_IB\\_MSG\\_1149](#); SQLSTATE: [HY000](#)

Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is only %lu pages

[ER\\_IB\\_MSG\\_1149](#) was added in 8.0.11.

- Error number: [MY-012975](#); Symbol: [ER\\_IB\\_MSG\\_1150](#); SQLSTATE: [HY000](#)

Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited innodb\_data\_file\_path in my.cnf in an InnoDB: inappropriate way, removing ibdata files from there? You can set innodb\_force\_recovery=1 in my.cnf to force InnoDB: a startup if you are trying to recover a badly corrupt database.

[ER\\_IB\\_MSG\\_1150](#) was added in 8.0.11.

- Error number: [MY-012976](#); Symbol: [ER\\_IB\\_MSG\\_1151](#); SQLSTATE: [HY000](#)

Message: %s started; log sequence number %llu

[ER\\_IB\\_MSG\\_1151](#) was added in 8.0.11.

- Error number: [MY-012977](#); Symbol: [ER\\_IB\\_MSG\\_1152](#); SQLSTATE: [HY000](#)

Message: Waiting for purge to complete

[ER\\_IB\\_MSG\\_1152](#) was added in 8.0.11.

- Error number: [MY-012978](#); Symbol: [ER\\_IB\\_MSG\\_1153](#); SQLSTATE: [HY000](#)

Message: Waiting for dict\_stats\_thread to exit

[ER\\_IB\\_MSG\\_1153](#) was added in 8.0.11, removed after 8.0.20.

- 
- Error number: [MY-012979](#); Symbol: [ER\\_IB\\_MSG\\_1154](#); SQLSTATE: [HY000](#)  
Message: Query counter shows %lld queries still inside InnoDB at shutdown  
[ER\\_IB\\_MSG\\_1154](#) was added in 8.0.11.
  - Error number: [MY-012980](#); Symbol: [ER\\_IB\\_MSG\\_1155](#); SQLSTATE: [HY000](#)  
Message: Shutdown completed; log sequence number %llu  
[ER\\_IB\\_MSG\\_1155](#) was added in 8.0.11.
  - Error number: [MY-012981](#); Symbol: [ER\\_IB\\_MSG\\_1156](#); SQLSTATE: [HY000](#)  
Message: Cannot continue operation.  
[ER\\_IB\\_MSG\\_1156](#) was added in 8.0.11.
  - Error number: [MY-012982](#); Symbol: [ER\\_IB\\_MSG\\_1157](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1157](#) was added in 8.0.11.
  - Error number: [MY-012983](#); Symbol: [ER\\_IB\\_MSG\\_1158](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1158](#) was added in 8.0.11.
  - Error number: [MY-012984](#); Symbol: [ER\\_IB\\_MSG\\_1159](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1159](#) was added in 8.0.11.
  - Error number: [MY-012985](#); Symbol: [ER\\_IB\\_MSG\\_1160](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1160](#) was added in 8.0.11.
  - Error number: [MY-012986](#); Symbol: [ER\\_IB\\_MSG\\_1161](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1161](#) was added in 8.0.11.
  - Error number: [MY-012987](#); Symbol: [ER\\_IB\\_MSG\\_1162](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1162](#) was added in 8.0.11.
  - Error number: [MY-012988](#); Symbol: [ER\\_IB\\_MSG\\_1163](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1163](#) was added in 8.0.11.

- 
- Error number: [MY-012989](#); Symbol: [ER\\_IB\\_MSG\\_1164](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1164](#) was added in 8.0.11.
  - Error number: [MY-012990](#); Symbol: [ER\\_IB\\_MSG\\_1165](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1165](#) was added in 8.0.11.
  - Error number: [MY-012991](#); Symbol: [ER\\_IB\\_MSG\\_1166](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1166](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012991](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_FAIL\\_TO\\_READ\\_LOG\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Unable to read the existing undo truncate log file '%s'. The error is %s  
[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_FAIL\\_TO\\_READ\\_LOG\\_FILE](#) was added in 8.0.21.
  - Error number: [MY-012992](#); Symbol: [ER\\_IB\\_MSG\\_1167](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1167](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012992](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_MARKED\\_FOR\\_TRUNCATE](#); SQLSTATE: [HY000](#)  
Message: Undo tablespace %s is marked for truncate  
[ER\\_IB\\_MSG\\_UNDO\\_MARKED\\_FOR\\_TRUNCATE](#) was added in 8.0.21.
  - Error number: [MY-012993](#); Symbol: [ER\\_IB\\_MSG\\_1168](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1168](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012994](#); Symbol: [ER\\_IB\\_MSG\\_1169](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1169](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012994](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_START](#); SQLSTATE: [HY000](#)  
Message: Truncating UNDO tablespace %s  
[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_START](#) was added in 8.0.21.
  - Error number: [MY-012995](#); Symbol: [ER\\_IB\\_MSG\\_1170](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1170](#) was added in 8.0.11, removed after 8.0.20.

- 
- Error number: [MY-012996](#); Symbol: [ER\\_IB\\_MSG\\_1171](#); SQLSTATE: [HY000](#)  
Message: Cannot create truncate log for undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_1171](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012996](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_LOG\\_CREATE](#); SQLSTATE: [HY000](#)  
Message: Cannot create truncate log for undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_LOG\\_CREATE](#) was added in 8.0.21.
  - Error number: [MY-012997](#); Symbol: [ER\\_IB\\_MSG\\_1172](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1172](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012998](#); Symbol: [ER\\_IB\\_MSG\\_1173](#); SQLSTATE: [HY000](#)  
Message: Failed to truncate undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_1173](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012998](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Failed to truncate undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_FAILURE](#) was added in 8.0.21.
  - Error number: [MY-012999](#); Symbol: [ER\\_IB\\_MSG\\_1174](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1174](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-013000](#); Symbol: [ER\\_IB\\_MSG\\_1175](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1175](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-013000](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_COMPLETE](#); SQLSTATE: [HY000](#)  
Message: Completed truncate of undo tablespace %s.  
[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_COMPLETE](#) was added in 8.0.21.
  - Error number: [MY-013001](#); Symbol: [ER\\_IB\\_MSG\\_1176](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1176](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-013002](#); Symbol: [ER\\_IB\\_MSG\\_1177](#); SQLSTATE: [HY000](#)  
Message: %s



---

[ER\\_IB\\_MSG\\_1177](#) was added in 8.0.11.

- Error number: [MY-013003](#); Symbol: [ER\\_IB\\_MSG\\_1178](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1178](#) was added in 8.0.11.

- Error number: [MY-013004](#); Symbol: [ER\\_IB\\_MSG\\_1179](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1179](#) was added in 8.0.11.

- Error number: [MY-013005](#); Symbol: [ER\\_IB\\_MSG\\_1180](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1180](#) was added in 8.0.11.

- Error number: [MY-013006](#); Symbol: [ER\\_IB\\_MSG\\_1181](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1181](#) was added in 8.0.11.

- Error number: [MY-013007](#); Symbol: [ER\\_IB\\_MSG\\_1182](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1182](#) was added in 8.0.11.

- Error number: [MY-013008](#); Symbol: [ER\\_IB\\_MSG\\_1183](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1183](#) was added in 8.0.11.

- Error number: [MY-013009](#); Symbol: [ER\\_IB\\_MSG\\_1184](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1184](#) was added in 8.0.11.

- Error number: [MY-013010](#); Symbol: [ER\\_IB\\_MSG\\_1185](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1185](#) was added in 8.0.11.

- Error number: [MY-013011](#); Symbol: [ER\\_IB\\_MSG\\_1186](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1186](#) was added in 8.0.11.

- Error number: [MY-013012](#); Symbol: [ER\\_IB\\_MSG\\_1187](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_1187](#) was added in 8.0.11.

- Error number: [MY-013013](#); Symbol: [ER\\_IB\\_MSG\\_1188](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1188](#) was added in 8.0.11.

- Error number: [MY-013014](#); Symbol: [ER\\_IB\\_MSG\\_1189](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1189](#) was added in 8.0.11.

- Error number: [MY-013015](#); Symbol: [ER\\_IB\\_MSG\\_1190](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1190](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-013015](#); Symbol: [ER\\_IB\\_MSG\\_TRX\\_RECOVERY\\_ROLLBACK\\_COMPLETED](#); SQLSTATE: [HY000](#)

Message: Rollback of non-prepared transactions completed

[ER\\_IB\\_MSG\\_TRX\\_RECOVERY\\_ROLLBACK\\_COMPLETED](#) was added in 8.0.21.

- Error number: [MY-013016](#); Symbol: [ER\\_IB\\_MSG\\_1191](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1191](#) was added in 8.0.11.

- Error number: [MY-013017](#); Symbol: [ER\\_IB\\_MSG\\_1192](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1192](#) was added in 8.0.11.

- Error number: [MY-013018](#); Symbol: [ER\\_IB\\_MSG\\_1193](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1193](#) was added in 8.0.11.

- Error number: [MY-013019](#); Symbol: [ER\\_IB\\_MSG\\_1194](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1194](#) was added in 8.0.11.

- Error number: [MY-013020](#); Symbol: [ER\\_IB\\_MSG\\_1195](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1195](#) was added in 8.0.11.

- Error number: [MY-013021](#); Symbol: [ER\\_IB\\_MSG\\_1196](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1196](#) was added in 8.0.11.

- Error number: [MY-013022](#); Symbol: [ER\\_IB\\_MSG\\_1197](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1197](#) was added in 8.0.11.

- Error number: [MY-013023](#); Symbol: [ER\\_IB\\_MSG\\_1198](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1198](#) was added in 8.0.11.

- Error number: [MY-013024](#); Symbol: [ER\\_IB\\_MSG\\_1199](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1199](#) was added in 8.0.11.

- Error number: [MY-013025](#); Symbol: [ER\\_IB\\_MSG\\_1200](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1200](#) was added in 8.0.11.

- Error number: [MY-013026](#); Symbol: [ER\\_IB\\_MSG\\_1201](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1201](#) was added in 8.0.11.

- Error number: [MY-013027](#); Symbol: [ER\\_IB\\_MSG\\_1202](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1202](#) was added in 8.0.11.

- Error number: [MY-013028](#); Symbol: [ER\\_IB\\_MSG\\_1203](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1203](#) was added in 8.0.11.

- Error number: [MY-013029](#); Symbol: [ER\\_IB\\_MSG\\_1204](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1204](#) was added in 8.0.11.

- Error number: [MY-013030](#); Symbol: [ER\\_IB\\_MSG\\_1205](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1205](#) was added in 8.0.11.

- Error number: [MY-013031](#); Symbol: [ER\\_IB\\_MSG\\_1206](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1206](#) was added in 8.0.11.

- Error number: [MY-013032](#); Symbol: [ER\\_IB\\_MSG\\_1207](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1207](#) was added in 8.0.11.

- Error number: [MY-013033](#); Symbol: [ER\\_IB\\_MSG\\_1208](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1208](#) was added in 8.0.11.

- Error number: [MY-013034](#); Symbol: [ER\\_IB\\_MSG\\_1209](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1209](#) was added in 8.0.11.

- Error number: [MY-013035](#); Symbol: [ER\\_IB\\_MSG\\_1210](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1210](#) was added in 8.0.11.

- Error number: [MY-013036](#); Symbol: [ER\\_IB\\_MSG\\_1211](#); SQLSTATE: [HY000](#)

Message: Blocked High Priority Transaction (ID %llu, Thread ID %s) killed the blocking transaction (ID %llu - %s) by rolling it back.

[ER\\_IB\\_MSG\\_1211](#) was added in 8.0.11.

- Error number: [MY-013037](#); Symbol: [ER\\_IB\\_MSG\\_1212](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1212](#) was added in 8.0.11.

- Error number: [MY-013038](#); Symbol: [ER\\_IB\\_MSG\\_1213](#); SQLSTATE: [HY000](#)

Message: gettimeofday() failed: %s

[ER\\_IB\\_MSG\\_1213](#) was added in 8.0.11.

- Error number: [MY-013039](#); Symbol: [ER\\_IB\\_MSG\\_1214](#); SQLSTATE: [HY000](#)

Message: Can't create UNDO tablespace %s %s

[ER\\_IB\\_MSG\\_1214](#) was added in 8.0.11.

- Error number: [MY-013040](#); Symbol: [ER\\_IB\\_MSG\\_1215](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1215](#) was added in 8.0.11.

- 
- Error number: [MY-013041](#); Symbol: [ER\\_IB\\_MSG\\_1216](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1216](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-013041](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_RESIZE\\_ON\\_START](#); SQLSTATE: [HY000](#)  
Message: Resizing redo log from %lluM to %lluM (LSN=%llu) synchronously. If this takes too long, consider starting the server with large --innodb\_redo\_log\_capacity, and resizing the redo log online using SET.  
[ER\\_IB\\_MSG\\_LOG\\_FILES\\_RESIZE\\_ON\\_START](#) was added in 8.0.30.
  - Error number: [MY-013042](#); Symbol: [ER\\_IB\\_MSG\\_1217](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1217](#) was added in 8.0.11.
  - Error number: [MY-013043](#); Symbol: [ER\\_IB\\_MSG\\_1218](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1218](#) was added in 8.0.11.
  - Error number: [MY-013044](#); Symbol: [ER\\_IB\\_MSG\\_1219](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1219](#) was added in 8.0.11.
  - Error number: [MY-013045](#); Symbol: [ER\\_IB\\_MSG\\_1220](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1220](#) was added in 8.0.11.
  - Error number: [MY-013046](#); Symbol: [ER\\_IB\\_MSG\\_1221](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1221](#) was added in 8.0.11.
  - Error number: [MY-013047](#); Symbol: [ER\\_IB\\_MSG\\_1222](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1222](#) was added in 8.0.11.
  - Error number: [MY-013048](#); Symbol: [ER\\_IB\\_MSG\\_1223](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1223](#) was added in 8.0.11.
  - Error number: [MY-013049](#); Symbol: [ER\\_IB\\_MSG\\_1224](#); SQLSTATE: [HY000](#)  
Message: %s

---

[ER\\_IB\\_MSG\\_1224](#) was added in 8.0.11.

- Error number: [MY-013050](#); Symbol: [ER\\_IB\\_MSG\\_1225](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1225](#) was added in 8.0.11.

- Error number: [MY-013051](#); Symbol: [ER\\_IB\\_MSG\\_1226](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1226](#) was added in 8.0.11.

- Error number: [MY-013052](#); Symbol: [ER\\_IB\\_MSG\\_1227](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1227](#) was added in 8.0.11.

- Error number: [MY-013053](#); Symbol: [ER\\_IB\\_MSG\\_1228](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1228](#) was added in 8.0.11.

- Error number: [MY-013054](#); Symbol: [ER\\_IB\\_MSG\\_1229](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1229](#) was added in 8.0.11.

- Error number: [MY-013055](#); Symbol: [ER\\_IB\\_MSG\\_1230](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1230](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-013056](#); Symbol: [ER\\_IB\\_MSG\\_1231](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1231](#) was added in 8.0.11.

- Error number: [MY-013057](#); Symbol: [ER\\_IB\\_MSG\\_1232](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1232](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013058](#); Symbol: [ER\\_IB\\_MSG\\_1233](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1233](#) was added in 8.0.11.

- Error number: [MY-013059](#); Symbol: [ER\\_IB\\_MSG\\_1234](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_1234](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013059](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_WRITER\\_OUT\\_OF\\_SPACE](#); SQLSTATE: [HY000](#)

Message: Out of space in the redo log. Checkpoint LSN: %llu. Consider increasing innodb\_redo\_log\_capacity.

[ER\\_IB\\_MSG\\_LOG\\_WRITER\\_OUT\\_OF\\_SPACE](#) was added in 8.0.30.

- Error number: [MY-013060](#); Symbol: [ER\\_IB\\_MSG\\_1235](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1235](#) was added in 8.0.11.

- Error number: [MY-013061](#); Symbol: [ER\\_IB\\_MSG\\_1236](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1236](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013061](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_WRITER\\_ABORTS\\_LOG\\_ARCHIVER](#); SQLSTATE: [HY000](#)

Message: Log writer waited too long for redo-archiver to advance (1 second). There are unarchived: %llu bytes. Archiver LSN: %llu. Aborted the redo-archiver. Consider increasing innodb\_redo\_log\_capacity.

[ER\\_IB\\_MSG\\_LOG\\_WRITER\\_ABORTS\\_LOG\\_ARCHIVER](#) was added in 8.0.30.

- Error number: [MY-013062](#); Symbol: [ER\\_IB\\_MSG\\_1237](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1237](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013062](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_WRITER\\_WAITING\\_FOR\\_ARCHIVER](#); SQLSTATE: [HY000](#)

Message: Log writer is waiting for redo-archiver to catch up unarchived: %llu bytes. Archiver LSN: %llu. Consider increasing innodb\_redo\_log\_capacity.

[ER\\_IB\\_MSG\\_LOG\\_WRITER\\_WAITING\\_FOR\\_ARCHIVER](#) was added in 8.0.30.

- Error number: [MY-013063](#); Symbol: [ER\\_IB\\_MSG\\_1238](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1238](#) was added in 8.0.11.

- Error number: [MY-013064](#); Symbol: [ER\\_IB\\_MSG\\_1239](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1239](#) was added in 8.0.11.

- Error number: [MY-013065](#); Symbol: [ER\\_IB\\_MSG\\_1240](#); SQLSTATE: [HY000](#)

Message: %s

---

`ER_IB_MSG_1240` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-013066`; Symbol: `ER_IB_MSG_1241`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1241` was added in 8.0.11.

- Error number: `MY-013067`; Symbol: `ER_IB_MSG_1242`; SQLSTATE: `HY000`

Message: Can't set redo log tablespace to be encrypted in read-only mode.

`ER_IB_MSG_1242` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-013067`; Symbol: `ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY`; SQLSTATE: `HY000`

Message: Can't set redo log files to be encrypted in read-only mode.

`ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY` was added in 8.0.30.

- Error number: `MY-013068`; Symbol: `ER_IB_MSG_1243`; SQLSTATE: `HY000`

Message: Can't set redo log tablespace to be encrypted.

`ER_IB_MSG_1243` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-013068`; Symbol: `ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED`; SQLSTATE: `HY000`

Message: Can't set redo log files to be encrypted.

`ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED` was added in 8.0.30.

- Error number: `MY-013069`; Symbol: `ER_IB_MSG_1244`; SQLSTATE: `HY000`

Message: Can't set redo log tablespace to be encrypted.

`ER_IB_MSG_1244` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-013070`; Symbol: `ER_IB_MSG_1245`; SQLSTATE: `HY000`

Message: Redo log encryption is enabled.

`ER_IB_MSG_1245` was added in 8.0.11.

- Error number: `MY-013071`; Symbol: `ER_IB_MSG_1246`; SQLSTATE: `HY000`

Message: Waiting for archiver to finish archiving page and log

`ER_IB_MSG_1246` was added in 8.0.11.

- Error number: `MY-013072`; Symbol: `ER_IB_MSG_1247`; SQLSTATE: `HY000`

Message: Starting shutdown...

`ER_IB_MSG_1247` was added in 8.0.11.

- Error number: `MY-013073`; Symbol: `ER_IB_MSG_1248`; SQLSTATE: `HY000`



---

Message: Waiting for %s to exit.

[ER\\_IB\\_MSG\\_1248](#) was added in 8.0.11.

- Error number: [MY-013074](#); Symbol: [ER\\_IB\\_MSG\\_1249](#); SQLSTATE: [HY000](#)

Message: Waiting for rollback of %zu recovered transactions, before shutdown.

[ER\\_IB\\_MSG\\_1249](#) was added in 8.0.11.

- Error number: [MY-013075](#); Symbol: [ER\\_IB\\_MSG\\_1250](#); SQLSTATE: [HY000](#)

Message: Waiting for master thread to be suspended.

[ER\\_IB\\_MSG\\_1250](#) was added in 8.0.11.

- Error number: [MY-013076](#); Symbol: [ER\\_IB\\_MSG\\_1251](#); SQLSTATE: [HY000](#)

Message: Waiting for page\_cleaner to finish flushing of buffer pool.

[ER\\_IB\\_MSG\\_1251](#) was added in 8.0.11.

- Error number: [MY-013077](#); Symbol: [ER\\_IB\\_MSG\\_1252](#); SQLSTATE: [HY000](#)

Message: Waiting for %lu buffer page I/Os to complete.

[ER\\_IB\\_MSG\\_1252](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013077](#); Symbol: [ER\\_IB\\_MSG\\_BUF\\_PENDING\\_IO\\_ON\\_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Shutdown is waiting for %zu buffer page I/Os to complete.

[ER\\_IB\\_MSG\\_BUF\\_PENDING\\_IO\\_ON\\_SHUTDOWN](#) was added in 8.0.30.

- Error number: [MY-013078](#); Symbol: [ER\\_IB\\_MSG\\_1253](#); SQLSTATE: [HY000](#)

Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to data files. At the next mysqld startup InnoDB will do a crash recovery!

[ER\\_IB\\_MSG\\_1253](#) was added in 8.0.11.

- Error number: [MY-013079](#); Symbol: [ER\\_IB\\_MSG\\_1254](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1254](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-013080](#); Symbol: [ER\\_IB\\_MSG\\_1255](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1255](#) was added in 8.0.11.

- Error number: [MY-013081](#); Symbol: [ER\\_IB\\_MSG\\_1256](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1256](#) was added in 8.0.11.

- 
- Error number: [MY-013082](#); Symbol: [ER\\_IB\\_MSG\\_1257](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1257](#) was added in 8.0.11.
  - Error number: [MY-013083](#); Symbol: [ER\\_IB\\_MSG\\_1258](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1258](#) was added in 8.0.11.
  - Error number: [MY-013084](#); Symbol: [ER\\_IB\\_MSG\\_1259](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1259](#) was added in 8.0.11.
  - Error number: [MY-013085](#); Symbol: [ER\\_IB\\_MSG\\_1260](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1260](#) was added in 8.0.11.
  - Error number: [MY-013086](#); Symbol: [ER\\_IB\\_MSG\\_1261](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1261](#) was added in 8.0.11.
  - Error number: [MY-013087](#); Symbol: [ER\\_IB\\_MSG\\_1262](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1262](#) was added in 8.0.11.
  - Error number: [MY-013088](#); Symbol: [ER\\_IB\\_MSG\\_1263](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1263](#) was added in 8.0.11.
  - Error number: [MY-013089](#); Symbol: [ER\\_IB\\_MSG\\_1264](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1264](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-013089](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_HEADER\\_INVALID\\_CHECKSUM](#); SQLSTATE: [HY000](#)  
Message: Invalid redo log header checksum.  
[ER\\_IB\\_MSG\\_LOG\\_FILE\\_HEADER\\_INVALID\\_CHECKSUM](#) was added in 8.0.30.
  - Error number: [MY-013090](#); Symbol: [ER\\_IB\\_MSG\\_1265](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1265](#) was added in 8.0.11, removed after 8.0.29.

- 
- Error number: [MY-013090](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_BEFORE\\_5\\_7\\_9](#); SQLSTATE: [HY000](#)  
Message: Unsupported redo log format (v%lu). The redo log was created before MySQL 5.7.9  
[ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_BEFORE\\_5\\_7\\_9](#) was added in 8.0.30.
  - Error number: [MY-013091](#); Symbol: [ER\\_IB\\_MSG\\_1266](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1266](#) was added in 8.0.11.
  - Error number: [MY-013092](#); Symbol: [ER\\_IB\\_MSG\\_1267](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1267](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-013092](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_CONCURRENCY\\_MARGIN\\_UNSAFE](#); SQLSTATE: [HY000](#)  
Message: Cannot continue operation. The innodb\_redo\_log\_capacity=%lluM is too small for the innodb\_thread\_concurrency=%lu. The capacity of redo should be >= %lluM. To get mysqld running, set innodb\_thread\_concurrency to a smaller value or increase innodb\_redo\_log\_capacity. %s  
[ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_CONCURRENCY\\_MARGIN\\_UNSAFE](#) was added in 8.0.30.
  - Error number: [MY-013093](#); Symbol: [ER\\_IB\\_MSG\\_1268](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1268](#) was added in 8.0.11.
  - Error number: [MY-013094](#); Symbol: [ER\\_IB\\_MSG\\_1269](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1269](#) was added in 8.0.11.
  - Error number: [MY-013095](#); Symbol: [ER\\_IB\\_MSG\\_1270](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1270](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-013095](#); Symbol: [ER\\_IB\\_MSG\\_THREAD\\_CONCURRENCY\\_CHANGED](#); SQLSTATE: [HY000](#)  
Message: User has set innodb\_thread\_concurrency to %lu.  
[ER\\_IB\\_MSG\\_THREAD\\_CONCURRENCY\\_CHANGED](#) was added in 8.0.30.
  - Error number: [MY-013096](#); Symbol: [ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_STOP\\_CMD\\_EXEC\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
Message: STOP SLAVE command execution is incomplete: Slave SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.  
[ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_STOP\\_CMD\\_EXEC\\_TIMEOUT](#) was added in 8.0.11, removed after 8.0.32.

- 
- Error number: [MY-013096](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STOP\\_CMD\\_EXEC\\_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP REPLICA command execution is incomplete: Replica SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.

[ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STOP\\_CMD\\_EXEC\\_TIMEOUT](#) was added in 8.0.33.

- Error number: [MY-013097](#); Symbol: [ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_STOP\\_CMD\\_EXEC\\_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP SLAVE command execution is incomplete: Slave IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.

[ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_STOP\\_CMD\\_EXEC\\_TIMEOUT](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-013097](#); Symbol: [ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_STOP\\_CMD\\_EXEC\\_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP REPLICA command execution is incomplete: Replica IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.

[ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_STOP\\_CMD\\_EXEC\\_TIMEOUT](#) was added in 8.0.33.

- Error number: [MY-013098](#); Symbol: [ER\\_RPL\\_GTID\\_UNSAFE\\_STMT\\_ON\\_NON\\_TRANS\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.

[ER\\_RPL\\_GTID\\_UNSAFE\\_STMT\\_ON\\_NON\\_TRANS\\_TABLE](#) was added in 8.0.11.

- Error number: [MY-013099](#); Symbol: [ER\\_RPL\\_GTID\\_UNSAFE\\_STMT\\_CREATE\\_SELECT](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.

[ER\\_RPL\\_GTID\\_UNSAFE\\_STMT\\_CREATE\\_SELECT](#) was added in 8.0.11.

- Error number: [MY-013100](#); Symbol: [ER\\_RPL\\_GTID\\_UNSAFE\\_STMT\\_ON\\_TEMPORARY\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE can only be executed outside transactional context. These statements are also not allowed in a function or trigger because functions and triggers are also considered to be multi-statement transactions.

[ER\\_RPL\\_GTID\\_UNSAFE\\_STMT\\_ON\\_TEMPORARY\\_TABLE](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-013101](#); Symbol: [ER\\_BINLOG\\_ROW\\_VALUE\\_OPTION\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: When %s, the option binlog\_row\_value\_options=%s will be ignored and updates will be written in full format to binary log.

[ER\\_BINLOG\\_ROW\\_VALUE\\_OPTION\\_IGNORED](#) was added in 8.0.11.

- 
- Error number: [MY-013102](#); Symbol: [ER\\_BINLOG\\_USE\\_V1\\_ROW\\_EVENTS\\_IGNORED](#); SQLSTATE: [HY000](#)  
  
Message: When %s, the option log\_bin\_use\_v1\_row\_events=1 will be ignored and row events will be written in new format to binary log.  
  
[ER\\_BINLOG\\_USE\\_V1\\_ROW\\_EVENTS\\_IGNORED](#) was added in 8.0.11.
  - Error number: [MY-013103](#); Symbol: [ER\\_BINLOG\\_ROW\\_VALUE\\_OPTION\\_USED\\_ONLY\\_FOR\\_AFTER\\_IMAGES](#); SQLSTATE: [HY000](#)  
  
Message: When %s, the option binlog\_row\_value\_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog\_row\_value\_options is limited to less than 50%%.  
  
[ER\\_BINLOG\\_ROW\\_VALUE\\_OPTION\\_USED\\_ONLY\\_FOR\\_AFTER\\_IMAGES](#) was added in 8.0.11.
  - Error number: [MY-013104](#); Symbol: [ER\\_CONNECTION\\_ABORTED](#); SQLSTATE: [HY000](#)  
  
Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).  
  
[ER\\_CONNECTION\\_ABORTED](#) was added in 8.0.11.
  - Error number: [MY-013105](#); Symbol: [ER\\_NORMAL\\_SERVER\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
  
Message: %s: Normal shutdown.  
  
[ER\\_NORMAL\\_SERVER\\_SHUTDOWN](#) was added in 8.0.11.
  - Error number: [MY-013106](#); Symbol: [ER\\_KEYRING\\_MIGRATE\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Can not perform keyring migration : %s.  
  
[ER\\_KEYRING\\_MIGRATE\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-013107](#); Symbol: [ER\\_GRP\\_RPL\\_LOWER\\_CASE\\_TABLE\\_NAMES\\_DIFF\\_FROM\\_GRP](#); SQLSTATE: [HY000](#)  
  
Message: The member is configured with a lower\_case\_table\_names option value '%u' different from the group '%u'. The member will now exit the group. If there is existing data on member, it may be incompatible with group if it was created with a lower\_case\_table\_names value different from the group.  
  
[ER\\_GRP\\_RPL\\_LOWER\\_CASE\\_TABLE\\_NAMES\\_DIFF\\_FROM\\_GRP](#) was added in 8.0.11.
  - Error number: [MY-013108](#); Symbol: [ER\\_OOM\\_SAVE\\_GTIDS](#); SQLSTATE: [HY000](#)  
  
Message: An out-of-memory error occurred while saving the set of GTIDs from the last binary log into the mysql.gtid\_executed table  
  
[ER\\_OOM\\_SAVE\\_GTIDS](#) was added in 8.0.11.
  - Error number: [MY-013109](#); Symbol: [ER\\_LCTN\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
  
Message: The lower\_case\_table\_names setting for the data dictionary was not found. Starting the server using lower\_case\_table\_names = '%u'.  
  
[ER\\_LCTN\\_NOT\\_FOUND](#) was added in 8.0.11.
  - Error number: [MY-013111](#); Symbol: [ER\\_COMPONENT\\_FILTER\\_WRONG\\_VALUE](#); SQLSTATE: [HY000](#)

---

Message: Variable '%s' can't be set to the value of '%s'

[ER\\_COMPONENT\\_FILTER\\_WRONG\\_VALUE](#) was added in 8.0.11.

- Error number: [MY-013112](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_STOP\\_SERVICES](#); SQLSTATE: [HY000](#)

Message: Stopping services failed with error "%s"

[ER\\_XPLUGIN\\_FAILED\\_TO\\_STOP\\_SERVICES](#) was added in 8.0.11.

- Error number: [MY-013113](#); Symbol: [ER\\_INCONSISTENT\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Query caused different errors on source and replica. Error on source: message (format)='%s' error code=%d; Error on replica:actual message='%s', error code=%d. Default database:'%s'. Query:'%s'

- Error number: [MY-013114](#); Symbol: [ER\\_SERVER\\_MASTER\\_FATAL\\_ERROR\\_READING\\_BINLOG](#); SQLSTATE: [HY000](#)

Message: Got fatal error %d from master when reading data from binary log: '%s'

[ER\\_SERVER\\_MASTER\\_FATAL\\_ERROR\\_READING\\_BINLOG](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-013114](#); Symbol: [ER\\_SERVER\\_SOURCE\\_FATAL\\_ERROR\\_READING\\_BINLOG](#); SQLSTATE: [HY000](#)

Message: Got fatal error %d from source when reading data from binary log: '%s'

[ER\\_SERVER\\_SOURCE\\_FATAL\\_ERROR\\_READING\\_BINLOG](#) was added in 8.0.33.

- Error number: [MY-013115](#); Symbol: [ER\\_NETWORK\\_READ\\_EVENT\\_CHECKSUM\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Replication event checksum verification failed while reading from network.

- Error number: [MY-013116](#); Symbol: [ER\\_SLAVE\\_CREATE\\_EVENT\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to create %s

[ER\\_SLAVE\\_CREATE\\_EVENT\\_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013116](#); Symbol: [ER\\_REPLICA\\_CREATE\\_EVENT\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to create %s

[ER\\_REPLICA\\_CREATE\\_EVENT\\_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013117](#); Symbol: [ER\\_SLAVE\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error: %s

[ER\\_SLAVE\\_FATAL\\_ERROR](#) was removed after 8.0.32.

- Error number: [MY-013117](#); Symbol: [ER\\_REPLICA\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error: %s

[ER\\_REPLICA\\_FATAL\\_ERROR](#) was added in 8.0.33.

- Error number: [MY-013118](#); Symbol: [ER\\_SLAVE\\_HEARTBEAT\\_FAILURE](#); SQLSTATE: [HY000](#)

---

Message: Unexpected master's heartbeat data: %s

[ER\\_SLAVE\\_HEARTBEAT\\_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013118](#); Symbol: [ER\\_REPLICA\\_HEARTBEAT\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Unexpected source's heartbeat data: %s

[ER\\_REPLICA\\_HEARTBEAT\\_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013119](#); Symbol: [ER\\_SLAVE\\_INCIDENT](#); SQLSTATE: [HY000](#)

Message: The incident %s occurred on the master. Message: %s

[ER\\_SLAVE\\_INCIDENT](#) was removed after 8.0.32.

- Error number: [MY-013119](#); Symbol: [ER\\_REPLICA\\_INCIDENT](#); SQLSTATE: [HY000](#)

Message: The incident %s occurred on the source. Message: %s

[ER\\_REPLICA\\_INCIDENT](#) was added in 8.0.33.

- Error number: [MY-013120](#); Symbol: [ER\\_SLAVE\\_MASTER\\_COM\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Master command %s failed: %s

[ER\\_SLAVE\\_MASTER\\_COM\\_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013120](#); Symbol: [ER\\_REPLICA\\_SOURCE\\_COM\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Source command %s failed: %s

[ER\\_REPLICA\\_SOURCE\\_COM\\_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013121](#); Symbol: [ER\\_SLAVE\\_RELAY\\_LOG\\_READ\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log read failure: %s

[ER\\_SLAVE\\_RELAY\\_LOG\\_READ\\_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013121](#); Symbol: [ER\\_REPLICA\\_RELAY\\_LOG\\_READ\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log read failure: %s

[ER\\_REPLICA\\_RELAY\\_LOG\\_READ\\_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013122](#); Symbol: [ER\\_SLAVE\\_RELAY\\_LOG\\_WRITE\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log write failure: %s

[ER\\_SLAVE\\_RELAY\\_LOG\\_WRITE\\_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013122](#); Symbol: [ER\\_REPLICA\\_RELAY\\_LOG\\_WRITE\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log write failure: %s

[ER\\_REPLICA\\_RELAY\\_LOG\\_WRITE\\_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013123](#); Symbol: [ER\\_SERVER\\_SLAVE\\_MI\\_INIT\\_REPOSITORY](#); SQLSTATE: [HY000](#)

---

Message: Slave failed to initialize master info structure from the repository

`ER_SERVER_SLAVE_MI_INIT_REPOSITORY` was added in 8.0.11, removed after 8.0.32.

- Error number: `MY-013123`; Symbol: `ER_SERVER_REPLICA_CM_INIT_REPOSITORY`; SQLSTATE: `HY000`

Message: Replica failed to initialize connection metadata structure from the repository

`ER_SERVER_REPLICA_CM_INIT_REPOSITORY` was added in 8.0.33.

- Error number: `MY-013124`; Symbol: `ER_SERVER_SLAVE_RLI_INIT_REPOSITORY`; SQLSTATE: `HY000`

Message: Slave failed to initialize relay log info structure from the repository

`ER_SERVER_SLAVE_RLI_INIT_REPOSITORY` was added in 8.0.11, removed after 8.0.32.

- Error number: `MY-013124`; Symbol: `ER_SERVER_REPLICA_AM_INIT_REPOSITORY`; SQLSTATE: `HY000`

Message: Replica failed to initialize applier metadata structure from the repository

`ER_SERVER_REPLICA_AM_INIT_REPOSITORY` was added in 8.0.33.

- Error number: `MY-013125`; Symbol: `ER_SERVER_NET_PACKET_TOO_LARGE`; SQLSTATE: `HY000`

Message: Got a packet bigger than 'max\_allowed\_packet' bytes

`ER_SERVER_NET_PACKET_TOO_LARGE` was added in 8.0.11.

- Error number: `MY-013126`; Symbol: `ER_SERVER_NO_SYSTEM_TABLE_ACCESS`; SQLSTATE: `HY000`

Message: Access to %s '%s.%s' is rejected.

`ER_SERVER_NO_SYSTEM_TABLE_ACCESS` was added in 8.0.11.

- Error number: `MY-013127`; Symbol: `ER_SERVER_UNKNOWN_ERROR`; SQLSTATE: `HY000`

Message: Unknown error

`ER_SERVER_UNKNOWN_ERROR` was added in 8.0.11, removed after 8.0.32.

- Error number: `MY-013128`; Symbol: `ER_SERVER_UNKNOWN_SYSTEM_VARIABLE`; SQLSTATE: `HY000`

Message: Unknown system variable '%s'

`ER_SERVER_UNKNOWN_SYSTEM_VARIABLE` was added in 8.0.11.

- Error number: `MY-013129`; Symbol: `ER_SERVER_NO_SESSION_TO_SEND_TO`; SQLSTATE: `HY000`

Message: A message intended for a client cannot be sent there as no client-session is attached. Therefore, we're sending the information to the error-log instead: MY-%06d - %s

`ER_SERVER_NO_SESSION_TO_SEND_TO` was added in 8.0.11.

- Error number: `MY-013130`; Symbol: `ER_SERVER_NEW_ABORTING_CONNECTION`; SQLSTATE: `08S01`

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s; diagnostics area: MY-%06d - %s)



---

`ER_SERVER_NEW_ABORTING_CONNECTION` was added in 8.0.11.

- Error number: `MY-013131`; Symbol: `ER_SERVER_OUT_OF_SORTMEMORY`; SQLSTATE: `HY000`

Message: Out of sort memory, consider increasing server sort buffer size!

`ER_SERVER_OUT_OF_SORTMEMORY` was added in 8.0.11.

- Error number: `MY-013132`; Symbol: `ER_SERVER_RECORD_FILE_FULL`; SQLSTATE: `HY000`

Message: The table '%s' is full!

`ER_SERVER_RECORD_FILE_FULL` was added in 8.0.11.

- Error number: `MY-013133`; Symbol: `ER_SERVER_DISK_FULL_NOWAIT`; SQLSTATE: `HY000`

Message: Create table/tablespace '%s' failed, as disk is full.

`ER_SERVER_DISK_FULL_NOWAIT` was added in 8.0.11.

- Error number: `MY-013134`; Symbol: `ER_SERVER_HANDLER_ERROR`; SQLSTATE: `HY000`

Message: Handler reported error %d - %s

`ER_SERVER_HANDLER_ERROR` was added in 8.0.11.

- Error number: `MY-013135`; Symbol: `ER_SERVER_NOT_FORM_FILE`; SQLSTATE: `HY000`

Message: Incorrect information in file: '%s'

`ER_SERVER_NOT_FORM_FILE` was added in 8.0.11.

- Error number: `MY-013136`; Symbol: `ER_SERVER_CANT_OPEN_FILE`; SQLSTATE: `HY000`

Message: Can't open file: '%s' (OS errno: %d - %s)

`ER_SERVER_CANT_OPEN_FILE` was added in 8.0.11.

- Error number: `MY-013137`; Symbol: `ER_SERVER_FILE_NOT_FOUND`; SQLSTATE: `HY000`

Message: Can't find file: '%s' (OS errno: %d - %s)

`ER_SERVER_FILE_NOT_FOUND` was added in 8.0.11.

- Error number: `MY-013138`; Symbol: `ER_SERVER_FILE_USED`; SQLSTATE: `HY000`

Message: '%s' is locked against change (OS errno: %d - %s)

`ER_SERVER_FILE_USED` was added in 8.0.11.

- Error number: `MY-013139`; Symbol: `ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2`; SQLSTATE: `HY000`

Message: Cannot load from %s.%s. The table is probably corrupted!

`ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2` was added in 8.0.11.

- Error number: `MY-013140`; Symbol: `ER_ERROR_INFO_FROM_DA`; SQLSTATE: `HY000`

---

Message: Error in diagnostics area: MY-%06d - %s

[ER\\_ERROR\\_INFO\\_FROM\\_DA](#) was added in 8.0.11.

- Error number: [MY-013141](#); Symbol: [ER\\_SERVER\\_TABLE\\_CHECK\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Incorrect definition of table %s.%s: expected column '%s' at position %d, found '%s'.

[ER\\_SERVER\\_TABLE\\_CHECK\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-013142](#); Symbol: [ER\\_SERVER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_PLEASE\\_UPDATE\\_V2](#); SQLSTATE: [HY000](#)

Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

[ER\\_SERVER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_PLEASE\\_UPDATE\\_V2](#) was added in 8.0.11.

- Error number: [MY-013143](#); Symbol: [ER\\_SERVER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_CORRUPTED\\_V2](#); SQLSTATE: [HY000](#)

Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted

[ER\\_SERVER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_CORRUPTED\\_V2](#) was added in 8.0.11.

- Error number: [MY-013144](#); Symbol: [ER\\_SERVER\\_ACL\\_TABLE\\_ERROR](#); SQLSTATE: [HY000](#)

Message:

[ER\\_SERVER\\_ACL\\_TABLE\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-013145](#); Symbol: [ER\\_SERVER\\_SLAVE\\_INIT\\_QUERY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread aborted. Can't execute init\_replica query, MY-%06d - '%s'

[ER\\_SERVER\\_SLAVE\\_INIT\\_QUERY\\_FAILED](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-013145](#); Symbol: [ER\\_SERVER\\_REPLICA\\_INIT\\_QUERY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread aborted. Can't execute init\_replica query, MY-%06d - '%s'

[ER\\_SERVER\\_REPLICA\\_INIT\\_QUERY\\_FAILED](#) was added in 8.0.33.

- Error number: [MY-013146](#); Symbol: [ER\\_SERVER\\_SLAVE\\_CONVERSION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'

[ER\\_SERVER\\_SLAVE\\_CONVERSION\\_FAILED](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-013146](#); Symbol: [ER\\_SERVER\\_REPLICA\\_CONVERSION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'

[ER\\_SERVER\\_REPLICA\\_CONVERSION\\_FAILED](#) was added in 8.0.33.

- Error number: [MY-013147](#); Symbol: [ER\\_SERVER\\_SLAVE\\_IGNORED\\_TABLE](#); SQLSTATE: [HY000](#)

---

Message: Slave SQL thread ignored the query because of replicate-\*-table rules

[ER\\_SERVER\\_SLAVE\\_IGNORED\\_TABLE](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-013147](#); Symbol: [ER\\_SERVER\\_REPLICA\\_IGNORED\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread ignored the query because of replicate-\*-table rules

[ER\\_SERVER\\_REPLICA\\_IGNORED\\_TABLE](#) was added in 8.0.33.

- Error number: [MY-013148](#); Symbol: [ER\\_CANT\\_REPLICATE\\_ANONYMOUS\\_WITH\\_AUTO\\_POSITION](#); SQLSTATE: [HY000](#)

Message: Cannot replicate anonymous transaction when AUTO\_POSITION = 1, at file %s, position %lld.

- Error number: [MY-013149](#); Symbol: [ER\\_CANT\\_REPLICATE\\_ANONYMOUS\\_WITH\\_GTID\\_MODE\\_ON](#); SQLSTATE: [HY000](#)

Message: Cannot replicate anonymous transaction when @@GLOBAL.GTID\_MODE = ON, at file %s, position %lld.

- Error number: [MY-013150](#); Symbol: [ER\\_CANT\\_REPLICATE\\_GTID\\_WITH\\_GTID\\_MODE\\_OFF](#); SQLSTATE: [HY000](#)

Message: Cannot replicate GTID-transaction when @@GLOBAL.GTID\_MODE = OFF, at file %s, position %lld.

- Error number: [MY-013151](#); Symbol: [ER\\_SERVER\\_TEST\\_MESSAGE](#); SQLSTATE: [HY000](#)

Message: Simulated error

[ER\\_SERVER\\_TEST\\_MESSAGE](#) was added in 8.0.11.

- Error number: [MY-013152](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_FILTER\\_PARSING\\_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_AUDIT\\_LOG\\_JSON\\_FILTER\\_PARSING\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-013153](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_FILTERING\\_NOT\\_ENABLED](#); SQLSTATE: [HY000](#)

Message: Audit Log filtering has not been installed.

[ER\\_AUDIT\\_LOG\\_JSON\\_FILTERING\\_NOT\\_ENABLED](#) was added in 8.0.11.

- Error number: [MY-013154](#); Symbol: [ER\\_PLUGIN\\_FAILED\\_TO\\_OPEN\\_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open the %s filter tables.

[ER\\_PLUGIN\\_FAILED\\_TO\\_OPEN\\_TABLES](#) was added in 8.0.11.

- Error number: [MY-013155](#); Symbol: [ER\\_PLUGIN\\_FAILED\\_TO\\_OPEN\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to open '%s.%s' %s table.

[ER\\_PLUGIN\\_FAILED\\_TO\\_OPEN\\_TABLE](#) was added in 8.0.11.

- 
- Error number: [MY-013156](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_FILTER\\_NAME\\_CANNOT\\_BE\\_EMPTY](#); SQLSTATE: [HY000](#)  
  
Message: Filter name cannot be empty.  
  
[ER\\_AUDIT\\_LOG\\_JSON\\_FILTER\\_NAME\\_CANNOT\\_BE\\_EMPTY](#) was added in 8.0.11.
  - Error number: [MY-013157](#); Symbol: [ER\\_AUDIT\\_LOG\\_USER\\_NAME\\_INVALID\\_CHARACTER](#); SQLSTATE: [HY000](#)  
  
Message: Invalid character in the user name.  
  
[ER\\_AUDIT\\_LOG\\_USER\\_NAME\\_INVALID\\_CHARACTER](#) was added in 8.0.11.
  - Error number: [MY-013158](#); Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_INSUFFICIENT\\_PRIVILEGE](#); SQLSTATE: [HY000](#)  
  
Message: Request ignored for '%s'@'%s'. SUPER or AUDIT\_ADMIN needed to perform operation  
  
[ER\\_AUDIT\\_LOG\\_UDF\\_INSUFFICIENT\\_PRIVILEGE](#) was added in 8.0.11.
  - Error number: [MY-013159](#); Symbol: [ER\\_AUDIT\\_LOG\\_NO\\_KEYRING\\_PLUGIN\\_INSTALLED](#); SQLSTATE: [HY000](#)  
  
Message: No keyring installed.  
  
[ER\\_AUDIT\\_LOG\\_NO\\_KEYRING\\_PLUGIN\\_INSTALLED](#) was added in 8.0.11.
  - Error number: [MY-013160](#); Symbol: [ER\\_AUDIT\\_LOG\\_HOST\\_NAME\\_INVALID\\_CHARACTER](#); SQLSTATE: [HY000](#)  
  
Message: Invalid character in the host name.  
  
[ER\\_AUDIT\\_LOG\\_HOST\\_NAME\\_INVALID\\_CHARACTER](#) was added in 8.0.11.
  - Error number: [MY-013161](#); Symbol: [ER\\_AUDIT\\_LOG\\_ENCRYPTION\\_PASSWORD\\_HAS\\_NOT\\_BEEN\\_SET](#); SQLSTATE: [HY000](#)  
  
Message: Audit log encryption password has not been set; it will be generated automatically. Use `audit_log_encryption_password_get` to obtain the password or `audit_log_encryption_password_set` to set a new one.  
  
[ER\\_AUDIT\\_LOG\\_ENCRYPTION\\_PASSWORD\\_HAS\\_NOT\\_BEEN\\_SET](#) was added in 8.0.11.
  - Error number: [MY-013162](#); Symbol: [ER\\_AUDIT\\_LOG\\_COULD\\_NOT\\_CREATE\\_AES\\_KEY](#); SQLSTATE: [HY000](#)  
  
Message: Could not create AES key. OpenSSL's `EVP_BytesToKey` function failed.  
  
[ER\\_AUDIT\\_LOG\\_COULD\\_NOT\\_CREATE\\_AES\\_KEY](#) was added in 8.0.11.
  - Error number: [MY-013163](#); Symbol: [ER\\_AUDIT\\_LOG\\_ENCRYPTION\\_PASSWORD\\_CANNOT\\_BE\\_FETCHED](#); SQLSTATE: [HY000](#)  
  
Message: Audit log encryption password cannot be fetched from the keyring. Password used so far is used for encryption.  
  
[ER\\_AUDIT\\_LOG\\_ENCRYPTION\\_PASSWORD\\_CANNOT\\_BE\\_FETCHED](#) was added in 8.0.11.

- 
- Error number: [MY-013164](#); Symbol: [ER\\_COULD\\_NOT\\_REINITIALIZE\\_AUDIT\\_LOG\\_FILTERS](#); SQLSTATE: [HY000](#)  
Message: Could not reinitialize audit log filters.  
[ER\\_COULD\\_NOT\\_REINITIALIZE\\_AUDIT\\_LOG\\_FILTERS](#) was added in 8.0.11.
  - Error number: [MY-013165](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_USER\\_NAME\\_CANNOT\\_BE\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: User cannot be empty.  
[ER\\_AUDIT\\_LOG\\_JSON\\_USER\\_NAME\\_CANNOT\\_BE\\_EMPTY](#) was added in 8.0.11.
  - Error number: [MY-013166](#); Symbol: [ER\\_AUDIT\\_LOG\\_USER\\_FIRST\\_CHARACTER\\_MUST\\_BE\\_ALPHANUMERIC](#); SQLSTATE: [HY000](#)  
Message: First character of the user name must be alphanumeric.  
[ER\\_AUDIT\\_LOG\\_USER\\_FIRST\\_CHARACTER\\_MUST\\_BE\\_ALPHANUMERIC](#) was added in 8.0.11.
  - Error number: [MY-013167](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_FILTER\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: Specified filter has not been found.  
[ER\\_AUDIT\\_LOG\\_JSON\\_FILTER\\_DOES\\_NOT\\_EXIST](#) was added in 8.0.11.
  - Error number: [MY-013168](#); Symbol: [ER\\_IB\\_MSG\\_1271](#); SQLSTATE: [HY000](#)  
Message: Cannot upgrade server earlier than 5.7 to 8.0  
[ER\\_IB\\_MSG\\_1271](#) was added in 8.0.11.
  - Error number: [MY-013169](#); Symbol: [ER\\_STARTING\\_INIT](#); SQLSTATE: [HY000](#)  
Message: %s (mysqld %s) initializing of server in progress as process %lu  
[ER\\_STARTING\\_INIT](#) was added in 8.0.11.
  - Error number: [MY-013170](#); Symbol: [ER\\_ENDING\\_INIT](#); SQLSTATE: [HY000](#)  
Message: %s (mysqld %s) initializing of server has completed  
[ER\\_ENDING\\_INIT](#) was added in 8.0.11.
  - Error number: [MY-013171](#); Symbol: [ER\\_IB\\_MSG\\_1272](#); SQLSTATE: [HY000](#)  
Message: Cannot boot server version %lu on data directory built by version %llu. Downgrade is not supported  
[ER\\_IB\\_MSG\\_1272](#) was added in 8.0.11.
  - Error number: [MY-013172](#); Symbol: [ER\\_SERVER\\_SHUTDOWN\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Received SHUTDOWN from user %s. Shutting down mysqld (Version: %s).  
[ER\\_SERVER\\_SHUTDOWN\\_INFO](#) was added in 8.0.12.
  - Error number: [MY-013173](#); Symbol: [ER\\_GRP\\_RPL\\_PLUGIN\\_ABORT](#); SQLSTATE: [HY000](#)

---

Message: The plugin encountered a critical error and will abort: %s

[ER\\_GRP\\_RPL\\_PLUGIN\\_ABORT](#) was added in 8.0.12.

- Error number: [MY-013177](#); Symbol: [ER\\_AUDIT\\_LOG\\_TABLE\\_DEFINITION\\_NOT\\_UPDATED](#); SQLSTATE: [HY000](#)

Message: '%s.%s' table definition has not been upgraded; Please perform the MySQL upgrade procedure.

[ER\\_AUDIT\\_LOG\\_TABLE\\_DEFINITION\\_NOT\\_UPDATED](#) was added in 8.0.12.

- Error number: [MY-013178](#); Symbol: [ER\\_DD\\_INITIALIZE\\_SQL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Execution of server-side SQL statement '%s' failed with error code = %d, error message = '%s'.

[ER\\_DD\\_INITIALIZE\\_SQL\\_ERROR](#) was added in 8.0.12.

- Error number: [MY-013179](#); Symbol: [ER\\_NO\\_PATH\\_FOR\\_SHARED\\_LIBRARY](#); SQLSTATE: [HY000](#)

Message: No paths allowed for shared library.

[ER\\_NO\\_PATH\\_FOR\\_SHARED\\_LIBRARY](#) was added in 8.0.13.

- Error number: [MY-013180](#); Symbol: [ER\\_UDF\\_ALREADY\\_EXISTS](#); SQLSTATE: [HY000](#)

Message: Function '%s' already exists.

[ER\\_UDF\\_ALREADY\\_EXISTS](#) was added in 8.0.13.

- Error number: [MY-013181](#); Symbol: [ER\\_SET\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Got Error: %ld from SetEvent.

[ER\\_SET\\_EVENT\\_FAILED](#) was added in 8.0.13.

- Error number: [MY-013182](#); Symbol: [ER\\_FAILED\\_TO\\_ALLOCATE\\_SSL\\_BIO](#); SQLSTATE: [HY000](#)

Message: Error allocating SSL BIO.

[ER\\_FAILED\\_TO\\_ALLOCATE\\_SSL\\_BIO](#) was added in 8.0.13.

- Error number: [MY-013183](#); Symbol: [ER\\_IB\\_MSG\\_1273](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1273](#) was added in 8.0.13.

- Error number: [MY-013184](#); Symbol: [ER\\_PID\\_FILEPATH\\_LOCATIONS\\_INACCESSIBLE](#); SQLSTATE: [HY000](#)

Message: One or several locations were inaccessible while checking PID filepath.

[ER\\_PID\\_FILEPATH\\_LOCATIONS\\_INACCESSIBLE](#) was added in 8.0.13.

- Error number: [MY-013185](#); Symbol: [ER\\_UNKNOWN\\_VARIABLE\\_IN\\_PERSISTED\\_CONFIG\\_FILE](#); SQLSTATE: [HY000](#)

---

Message: Currently unknown variable '%s' was read from the persisted config file.

[ER\\_UNKNOWN\\_VARIABLE\\_IN\\_PERSISTED\\_CONFIG\\_FILE](#) was added in 8.0.13.

- Error number: [MY-013186](#); Symbol: [ER\\_FAILED\\_TO\\_HANDLE\\_DEFAULTS\\_FILE](#); SQLSTATE: [HY000](#)

Message: Fatal error in defaults handling. Program aborted!

[ER\\_FAILED\\_TO\\_HANDLE\\_DEFAULTS\\_FILE](#) was added in 8.0.13.

- Error number: [MY-013187](#); Symbol: [ER\\_DUPLICATE\\_SYS\\_VAR](#); SQLSTATE: [HY000](#)

Message: Duplicate variable name '%s'.

[ER\\_DUPLICATE\\_SYS\\_VAR](#) was added in 8.0.13.

- Error number: [MY-013188](#); Symbol: [ER\\_FAILED\\_TO\\_INIT\\_SYS\\_VAR](#); SQLSTATE: [HY000](#)

Message: Failed to initialize system variables.

[ER\\_FAILED\\_TO\\_INIT\\_SYS\\_VAR](#) was added in 8.0.13.

- Error number: [MY-013189](#); Symbol: [ER\\_SYS\\_VAR\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Variable name '%s' not found.

[ER\\_SYS\\_VAR\\_NOT\\_FOUND](#) was added in 8.0.13.

- Error number: [MY-013190](#); Symbol: [ER\\_IB\\_MSG\\_1274](#); SQLSTATE: [HY000](#)

Message: Some (%d) threads are still active

[ER\\_IB\\_MSG\\_1274](#) was added in 8.0.13.

- Error number: [MY-013191](#); Symbol: [ER\\_IB\\_MSG\\_1275](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1275](#) was added in 8.0.13.

- Error number: [MY-013192](#); Symbol: [ER\\_TARGET\\_TS\\_UNENCRYPTED](#); SQLSTATE: [HY000](#)

Message: Source tablespace is encrypted but target tablespace is not.

[ER\\_TARGET\\_TS\\_UNENCRYPTED](#) was added in 8.0.13, removed after 8.0.15.

- Error number: [MY-013193](#); Symbol: [ER\\_IB\\_MSG\\_1276](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1276](#) was added in 8.0.13, removed after 8.0.13.

- Error number: [MY-013193](#); Symbol: [ER\\_IB\\_MSG\\_WAIT\\_FOR\\_ENCRYPT\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Waiting for tablespace\_alter\_encrypt\_thread to exit

[ER\\_IB\\_MSG\\_WAIT\\_FOR\\_ENCRYPT\\_THREAD](#) was added in 8.0.14.

- Error number: [MY-013194](#); Symbol: [ER\\_IB\\_MSG\\_1277](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1277](#) was added in 8.0.13.

- Error number: [MY-013195](#); Symbol: [ER\\_IB\\_MSG\\_1278](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1278](#) was added in 8.0.13, removed after 8.0.13.

- Error number: [MY-013195](#); Symbol: [ER\\_IB\\_MSG\\_NO\\_ENCRYPT\\_PROGRESS\\_FOUND](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_NO\\_ENCRYPT\\_PROGRESS\\_FOUND](#) was added in 8.0.14.

- Error number: [MY-013196](#); Symbol: [ER\\_IB\\_MSG\\_1279](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1279](#) was added in 8.0.13, removed after 8.0.13.

- Error number: [MY-013196](#); Symbol: [ER\\_IB\\_MSG\\_RESUME\\_OP\\_FOR\\_SPACE](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_RESUME\\_OP\\_FOR\\_SPACE](#) was added in 8.0.14.

- Error number: [MY-013197](#); Symbol: [ER\\_IB\\_MSG\\_1280](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1280](#) was added in 8.0.13.

- Error number: [MY-013198](#); Symbol: [ER\\_IB\\_MSG\\_1281](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1281](#) was added in 8.0.13.

- Error number: [MY-013199](#); Symbol: [ER\\_IB\\_MSG\\_1282](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1282](#) was added in 8.0.13.

- Error number: [MY-013200](#); Symbol: [ER\\_IB\\_MSG\\_1283](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1283](#) was added in 8.0.13.

- Error number: [MY-013201](#); Symbol: [ER\\_IB\\_MSG\\_1284](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1284](#) was added in 8.0.13.



- 
- Error number: `MY-013202`; Symbol: `ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE`; SQLSTATE: `HY000`  
  
Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.  
  
`ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE` was added in 8.0.13.
  - Error number: `MY-013203`; Symbol: `ER_INVALID_VALUE_OF_BIND_ADDRESSES`; SQLSTATE: `HY000`  
  
Message: Invalid value for command line option bind-addresses: '%s'  
  
`ER_INVALID_VALUE_OF_BIND_ADDRESSES` was added in 8.0.13.
  - Error number: `MY-013204`; Symbol: `ER_RELAY_LOG_SPACE_LIMIT_DISABLED`; SQLSTATE: `HY000`  
  
Message: Ignoring the @@global.relay\_log\_space\_limit option because @@global.relay\_log\_purge is disabled.  
  
`ER_RELAY_LOG_SPACE_LIMIT_DISABLED` was added in 8.0.13.
  - Error number: `MY-013205`; Symbol: `ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION`; SQLSTATE: `HY000`  
  
Message: Error when extracting GTID execution information: %s  
  
`ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION` was added in 8.0.13.
  - Error number: `MY-013206`; Symbol: `ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR`; SQLSTATE: `HY000`  
  
Message: Message received without a proper group coordinator module.  
  
`ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR` was added in 8.0.13.
  - Error number: `MY-013207`; Symbol: `ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING`; SQLSTATE: `HY000`  
  
Message: A member cannot join the group while a group configuration operation '%s' is running initiated by '%s'.  
  
`ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING` was added in 8.0.13.
  - Error number: `MY-013208`; Symbol: `ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING`; SQLSTATE: `HY000`  
  
Message: A member is joining the group while a group configuration operation '%s' is running initiated by '%s'. The member will now leave the group.  
  
`ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING` was added in 8.0.13.
  - Error number: `MY-013209`; Symbol: `ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING`; SQLSTATE: `HY000`  
  
Message: Can't start %s for channel '%s' when group replication is running a group configuration operation '%s' initiated by '%s'.  
  
`ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING` was added in 8.0.13.

- 
- Error number: [MY-013210](#); Symbol: [ER\\_GRP\\_RPL\\_APPOINTED\\_PRIMARY\\_NOT\\_PRESENT](#); SQLSTATE: [HY000](#)

Message: A primary election was invoked but the requested primary member is not in the group.  
Request ignored.

[ER\\_GRP\\_RPL\\_APPOINTED\\_PRIMARY\\_NOT\\_PRESENT](#) was added in 8.0.13.

- Error number: [MY-013211](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_ON\\_MESSAGE\\_SENDING](#); SQLSTATE: [HY000](#)

Message: Error while sending message. Context: %s

[ER\\_GRP\\_RPL\\_ERROR\\_ON\\_MESSAGE\\_SENDING](#) was added in 8.0.13.

- Error number: [MY-013212](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while executing a group configuration operation: %s

[ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_ERROR](#) was added in 8.0.13.

- Error number: [MY-013213](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_LOCAL\\_TERMINATION](#); SQLSTATE: [HY000](#)

Message: Configuration operation '%s' terminated. %s

[ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_LOCAL\\_TERMINATION](#) was added in 8.0.13.

- Error number: [MY-013214](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_START](#); SQLSTATE: [HY000](#)

Message: Starting group operation local execution: %s

[ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_START](#) was added in 8.0.13.

- Error number: [MY-013215](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_END](#); SQLSTATE: [HY000](#)

Message: Termination of group operation local execution: %s

[ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_END](#) was added in 8.0.13.

- Error number: [MY-013216](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_KILLED\\_ERROR](#); SQLSTATE: [HY000](#)

Message: A configuration change was killed in this member. The member will now leave the group as its configuration may have diverged.

[ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_KILLED\\_ERROR](#) was added in 8.0.13.

- Error number: [MY-013217](#); Symbol: [ER\\_GRP\\_RPL\\_PRIMARY\\_ELECTION\\_PROCESS\\_ERROR](#); SQLSTATE: [HY000](#)

Message: There was an issue on the primary election process: %s The member will now leave the group.

[ER\\_GRP\\_RPL\\_PRIMARY\\_ELECTION\\_PROCESS\\_ERROR](#) was added in 8.0.13.

- 
- Error number: [MY-013218](#); Symbol: [ER\\_GRP\\_RPL\\_PRIMARY\\_ELECTION\\_STOP\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: There was an issue when stopping a previous election process: %s  
  
[ER\\_GRP\\_RPL\\_PRIMARY\\_ELECTION\\_STOP\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013219](#); Symbol: [ER\\_GRP\\_RPL\\_NO\\_STAGE\\_SERVICE](#); SQLSTATE: [HY000](#)  
  
Message: It was not possible to initialize stage logging for this task. The operation will still run without stage tracking.  
  
[ER\\_GRP\\_RPL\\_NO\\_STAGE\\_SERVICE](#) was added in 8.0.13.
  - Error number: [MY-013220](#); Symbol: [ER\\_GRP\\_RPL\\_UDF\\_REGISTER\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Could not execute the installation of Group Replication UDF function: %s. Check if the function is already present, if so, try to remove it  
  
[ER\\_GRP\\_RPL\\_UDF\\_REGISTER\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013221](#); Symbol: [ER\\_GRP\\_RPL\\_UDF\\_UNREGISTER\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Could not uninstall Group Replication UDF functions. Try to remove them manually if present.  
  
[ER\\_GRP\\_RPL\\_UDF\\_UNREGISTER\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013222](#); Symbol: [ER\\_GRP\\_RPL\\_UDF\\_REGISTER\\_SERVICE\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Could not execute the installation of Group Replication UDF functions. Check for other errors in the log and try to reinstall the plugin  
  
[ER\\_GRP\\_RPL\\_UDF\\_REGISTER\\_SERVICE\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013223](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_UDF\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: The function '%s' failed. %s  
  
[ER\\_GRP\\_RPL\\_SERVER\\_UDF\\_ERROR](#) was added in 8.0.17.
  - Error number: [MY-013227](#); Symbol: [ER\\_SERVER\\_WRONG\\_VALUE\\_FOR\\_VAR](#); SQLSTATE: [HY000](#)  
  
Message: Variable '%s' can't be set to the value of '%s'  
  
[ER\\_SERVER\\_WRONG\\_VALUE\\_FOR\\_VAR](#) was added in 8.0.13.
  - Error number: [MY-013228](#); Symbol: [ER\\_COULD\\_NOT\\_CREATE\\_WINDOWS\\_REGISTRY\\_KEY](#); SQLSTATE: [HY000](#)  
  
Message: %s was unable to create a new Windows registry key %s for %s; continuing to use the previous ident.  
  
[ER\\_COULD\\_NOT\\_CREATE\\_WINDOWS\\_REGISTRY\\_KEY](#) was added in 8.0.13.

- 
- Error number: [MY-013229](#); Symbol: [ER\\_SERVER\\_GTID\\_UNSAFE\\_CREATE\\_DROP\\_TEMP\\_TABLE\\_IN\\_TRX\\_IN\\_SBR](#); SQLSTATE: [HY000](#)  
  
Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog\_format=STATEMENT.  
  
[ER\\_SERVER\\_GTID\\_UNSAFE\\_CREATE\\_DROP\\_TEMP\\_TABLE\\_IN\\_TRX\\_IN\\_SBR](#) was added in 8.0.13.
  - Error number: [MY-013233](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_SWITCH\\_SECURITY\\_CTX](#); SQLSTATE: [HY000](#)  
  
Message: Unable to switch security context to user: %s  
  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_SWITCH\\_SECURITY\\_CTX](#) was added in 8.0.13.
  - Error number: [MY-013234](#); Symbol: [ER\\_RPL\\_GTID\\_UNSAFE\\_ALTER\\_ADD\\_COL\\_WITH\\_DEFAULT\\_EXPRESSION](#); SQLSTATE: [HY000](#)  
  
Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.  
  
[ER\\_RPL\\_GTID\\_UNSAFE\\_ALTER\\_ADD\\_COL\\_WITH\\_DEFAULT\\_EXPRESSION](#) was added in 8.0.13.
  - Error number: [MY-013235](#); Symbol: [ER\\_UPGRADE\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error in parsing %s '%s'.'%s' during upgrade. %s  
  
[ER\\_UPGRADE\\_PARSE\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013236](#); Symbol: [ER\\_DATA\\_DIRECTORY\\_UNUSABLE](#); SQLSTATE: [HY000](#)  
  
Message: The designated data directory %s is unusable. You can remove all files that the server added to it.  
  
[ER\\_DATA\\_DIRECTORY\\_UNUSABLE](#) was added in 8.0.13.
  - Error number: [MY-013237](#); Symbol: [ER\\_LDAP\\_AUTH\\_USER\\_GROUP\\_SEARCH\\_ROOT\\_BIND](#); SQLSTATE: [HY000](#)  
  
Message: Group search rebinding via root DN: %s  
  
[ER\\_LDAP\\_AUTH\\_USER\\_GROUP\\_SEARCH\\_ROOT\\_BIND](#) was added in 8.0.13.
  - Error number: [MY-013238](#); Symbol: [ER\\_PLUGIN\\_INSTALL\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error installing plugin '%s': %s  
  
[ER\\_PLUGIN\\_INSTALL\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013239](#); Symbol: [ER\\_PLUGIN\\_UNINSTALL\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error uninstalling plugin '%s': %s  
  
[ER\\_PLUGIN\\_UNINSTALL\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013240](#); Symbol: [ER\\_SHARED\\_TABLESPACE\\_USED\\_BY\\_PARTITIONED\\_TABLE](#); SQLSTATE: [HY000](#)

---

Message: Partitioned table '%s' is not allowed to use shared tablespace '%s'. Please move all partitions to file-per-table tablespaces before upgrade.

[ER\\_SHARED\\_TABLESPACE\\_USED\\_BY\\_PARTITIONED\\_TABLE](#) was added in 8.0.13.

- Error number: [MY-013241](#); Symbol: [ER\\_UNKNOWN\\_TABLESPACE\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Cannot determine the type of the tablespace named '%s'.

[ER\\_UNKNOWN\\_TABLESPACE\\_TYPE](#) was added in 8.0.13.

- Error number: [MY-013242](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_UTF8\\_ALIAS\\_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.

[ER\\_WARN\\_DEPRECATED\\_UTF8\\_ALIAS\\_OPTION](#) was added in 8.0.13.

- Error number: [MY-013243](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_CHARSET\\_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: The character set UTF8MB3 is deprecated and will be removed in a future release. Please consider using UTF8MB4 instead.

[ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_CHARSET\\_OPTION](#) was added in 8.0.13.

- Error number: [MY-013244](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_COLLATION\\_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.

[ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_COLLATION\\_OPTION](#) was added in 8.0.13.

- Error number: [MY-013245](#); Symbol: [ER\\_SSL\\_MEMORY\\_INSTRUMENTATION\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: The SSL library function %s failed. This is typically caused by the SSL library already being used. As a result the SSL memory allocation will not be instrumented.

[ER\\_SSL\\_MEMORY\\_INSTRUMENTATION\\_INIT\\_FAILED](#) was added in 8.0.13.

- Error number: [MY-013246](#); Symbol: [ER\\_IB\\_MSG\\_MADV\\_DONTDUMP\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Disabling @@core\_file because @@innodb\_buffer\_pool\_in\_core\_file is disabled, yet MADV\_DONTDUMP is not supported on this platform

[ER\\_IB\\_MSG\\_MADV\\_DONTDUMP\\_UNSUPPORTED](#) was added in 8.0.14.

- Error number: [MY-013247](#); Symbol: [ER\\_IB\\_MSG\\_MADVISE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Disabling @@core\_file because @@innodb\_buffer\_pool\_in\_core\_file is disabled, yet madvise(%p,%zu,%s) failed with %s

[ER\\_IB\\_MSG\\_MADVISE\\_FAILED](#) was added in 8.0.14.

- 
- Error number: [MY-013249](#); Symbol: [ER\\_WARN\\_REMOVED\\_SQL\\_MODE](#); SQLSTATE: [HY000](#)  
Message: sql\_mode=0x%08x has been removed and will be ignored  
[ER\\_WARN\\_REMOVED\\_SQL\\_MODE](#) was added in 8.0.14.
  - Error number: [MY-013250](#); Symbol: [ER\\_IB\\_MSG\\_FAILED\\_TO\\_ALLOCATE\\_WAIT](#); SQLSTATE: [HY000](#)  
Message: Failed to allocate memory for a pool of size %zu bytes. Will wait for %zu seconds for a thread to free a resource.  
[ER\\_IB\\_MSG\\_FAILED\\_TO\\_ALLOCATE\\_WAIT](#) was added in 8.0.14.
  - Error number: [MY-013251](#); Symbol: [ER\\_IB\\_MSG\\_NUM\\_POOLS](#); SQLSTATE: [HY000](#)  
Message: Number of pools: %zu  
[ER\\_IB\\_MSG\\_NUM\\_POOLS](#) was added in 8.0.14, removed after 8.0.30.
  - Error number: [MY-013252](#); Symbol: [ER\\_IB\\_MSG\\_USING\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Using undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_USING\\_UNDO\\_SPACE](#) was added in 8.0.14.
  - Error number: [MY-013253](#); Symbol: [ER\\_IB\\_MSG\\_FAIL\\_TO\\_SAVE\\_SPACE\\_STATE](#); SQLSTATE: [HY000](#)  
Message: %s Unable to save the current state of tablespace '%s' to the data dictionary  
[ER\\_IB\\_MSG\\_FAIL\\_TO\\_SAVE\\_SPACE\\_STATE](#) was added in 8.0.14.
  - Error number: [MY-013254](#); Symbol: [ER\\_IB\\_MSG\\_MAX\\_UNDO\\_SPACES\\_REACHED](#); SQLSTATE: [HY000](#)  
Message: Cannot create undo tablespace %s at %s because %d undo tablespaces already exist.  
[ER\\_IB\\_MSG\\_MAX\\_UNDO\\_SPACES\\_REACHED](#) was added in 8.0.14.
  - Error number: [MY-013255](#); Symbol: [ER\\_IB\\_MSG\\_ERROR\\_OPENING\\_NEW\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Error %d opening newly created undo tablespace %s.  
[ER\\_IB\\_MSG\\_ERROR\\_OPENING\\_NEW\\_UNDO\\_SPACE](#) was added in 8.0.14.
  - Error number: [MY-013256](#); Symbol: [ER\\_IB\\_MSG\\_FAILED\\_SDI\\_Z\\_BUF\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: SDI Compression failed, Z\_BUF\_ERROR  
[ER\\_IB\\_MSG\\_FAILED\\_SDI\\_Z\\_BUF\\_ERROR](#) was added in 8.0.14.
  - Error number: [MY-013257](#); Symbol: [ER\\_IB\\_MSG\\_FAILED\\_SDI\\_Z\\_MEM\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: SDI Compression failed, Z\_MEM\_ERROR  
[ER\\_IB\\_MSG\\_FAILED\\_SDI\\_Z\\_MEM\\_ERROR](#) was added in 8.0.14.
  - Error number: [MY-013258](#); Symbol: [ER\\_IB\\_MSG\\_SDI\\_Z\\_STREAM\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: SDI Compression failed, Z\_STREAM\_ERROR

---

`ER_IB_MSG_SDI_Z_STREAM_ERROR` was added in 8.0.14.

- Error number: `MY-013259`; Symbol: `ER_IB_MSG_SDI_Z_UNKNOWN_ERROR`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_SDI_Z_UNKNOWN_ERROR` was added in 8.0.14.

- Error number: `MY-013260`; Symbol: `ER_IB_MSG_FOUND_WRONG_UNDO_SPACE`; SQLSTATE: `HY000`

Message: Expected to find undo tablespace '%s' for Space ID=%lu, but found '%s' instead! Did you change innodb\_undo\_directory?

`ER_IB_MSG_FOUND_WRONG_UNDO_SPACE` was added in 8.0.14.

- Error number: `MY-013261`; Symbol: `ER_IB_MSG_NOT_END_WITH_IBU`; SQLSTATE: `HY000`

Message: Cannot use %s as an undo tablespace because it does not end with '.ibu'.

`ER_IB_MSG_NOT_END_WITH_IBU` was added in 8.0.14.

- Error number: `MY-013262`; Symbol: `ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE`; SQLSTATE: `HY000`

Message: ib\_undo\_trunc\_empty\_file

`ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE` was added in 8.0.14, removed after 8.0.20.

- Error number: `MY-013263`; Symbol: `ER_IB_MSG_UNDO_TRUNC_BEFORE_DD_UPDATE`; SQLSTATE: `HY000`

Message: ib\_undo\_trunc\_before\_dd\_update

`ER_IB_MSG_UNDO_TRUNC_BEFORE_DD_UPDATE` was added in 8.0.14, removed after 8.0.20.

- Error number: `MY-013264`; Symbol: `ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING`; SQLSTATE: `HY000`

Message: ib\_undo\_trunc\_before\_done\_logging

`ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING` was added in 8.0.14, removed after 8.0.20.

- Error number: `MY-013265`; Symbol: `ER_IB_MSG_UNDO_TRUNC_BEFORE_RSEG`; SQLSTATE: `HY000`

Message: ib\_undo\_trunc\_before\_rsegs

`ER_IB_MSG_UNDO_TRUNC_BEFORE_RSEG` was added in 8.0.14, removed after 8.0.20.

- Error number: `MY-013266`; Symbol: `ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE`; SQLSTATE: `HY000`

Message: %s Failed to finish truncating Undo Tablespace '%s'

`ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE` was added in 8.0.14.

- 
- Error number: [MY-013267](#); Symbol: [ER\\_IB\\_MSG\\_DEPRECATED\\_INNODB\\_UNDO\\_TABLESPACES](#); SQLSTATE: [HY000](#)

Message: The setting INNODB\_UNDO\_TABLESPACES is deprecated and is no longer used. InnoDB always creates 2 undo tablespaces to start with. If you need more, please use CREATE UNDO TABLESPACE.

[ER\\_IB\\_MSG\\_DEPRECATED\\_INNODB\\_UNDO\\_TABLESPACES](#) was added in 8.0.14.

- Error number: [MY-013268](#); Symbol: [ER\\_IB\\_MSG\\_DIR\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)

Message: The directory '%s' does not exist.

[ER\\_IB\\_MSG\\_DIR\\_DOES\\_NOT\\_EXIST](#) was added in 8.0.14, removed after 8.0.20.

- Error number: [MY-013268](#); Symbol: [ER\\_IB\\_MSG\\_WRONG\\_TABLESPACE\\_DIR](#); SQLSTATE: [HY000](#)

Message: The directory for tablespace %s does not exist or is incorrect.

[ER\\_IB\\_MSG\\_WRONG\\_TABLESPACE\\_DIR](#) was added in 8.0.21.

- Error number: [MY-013269](#); Symbol: [ER\\_IB\\_MSG\\_LOCK\\_FREE\\_HASH\\_USAGE\\_STATS](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_LOCK\\_FREE\\_HASH\\_USAGE\\_STATS](#) was added in 8.0.14.

- Error number: [MY-013270](#); Symbol: [ER\\_CLONE\\_REMOTE\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Clone Remote Error: %s.

[ER\\_CLONE\\_REMOTE\\_ERROR](#) was added in 8.0.14, removed after 8.0.16.

- Error number: [MY-013270](#); Symbol: [ER\\_CLONE\\_DONOR\\_TRACE](#); SQLSTATE: [HY000](#)

Message: Clone donor reported : %s.

[ER\\_CLONE\\_DONOR\\_TRACE](#) was added in 8.0.17.

- Error number: [MY-013271](#); Symbol: [ER\\_CLONE\\_PROTOCOL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Clone Protocol Error: %s.

[ER\\_CLONE\\_PROTOCOL\\_ERROR](#) was added in 8.0.14, removed after 8.0.16.

- Error number: [MY-013271](#); Symbol: [ER\\_CLONE\\_PROTOCOL\\_TRACE](#); SQLSTATE: [HY000](#)

Message: Clone received unexpected response from donor : %s.

[ER\\_CLONE\\_PROTOCOL\\_TRACE](#) was added in 8.0.17.

- Error number: [MY-013272](#); Symbol: [ER\\_CLONE\\_INFO\\_CLIENT](#); SQLSTATE: [HY000](#)

Message: Client: %s.

[ER\\_CLONE\\_INFO\\_CLIENT](#) was added in 8.0.14, removed after 8.0.16.

- Error number: [MY-013272](#); Symbol: [ER\\_CLONE\\_CLIENT\\_TRACE](#); SQLSTATE: [HY000](#)



---

Message: Client: %s.

[ER\\_CLONE\\_CLIENT\\_TRACE](#) was added in 8.0.17.

- Error number: [MY-013273](#); Symbol: [ER\\_CLONE\\_INFO\\_SERVER](#); SQLSTATE: [HY000](#)

Message: Server: %s.

[ER\\_CLONE\\_INFO\\_SERVER](#) was added in 8.0.14, removed after 8.0.16.

- Error number: [MY-013273](#); Symbol: [ER\\_CLONE\\_SERVER\\_TRACE](#); SQLSTATE: [HY000](#)

Message: Server: %s.

[ER\\_CLONE\\_SERVER\\_TRACE](#) was added in 8.0.17.

- Error number: [MY-013274](#); Symbol: [ER\\_THREAD\\_POOL\\_PFS\\_TABLES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize the performance schema tables service.

[ER\\_THREAD\\_POOL\\_PFS\\_TABLES\\_INIT\\_FAILED](#) was added in 8.0.14.

- Error number: [MY-013275](#); Symbol: [ER\\_THREAD\\_POOL\\_PFS\\_TABLES\\_ADD\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to add thread pool performance schema tables.

[ER\\_THREAD\\_POOL\\_PFS\\_TABLES\\_ADD\\_FAILED](#) was added in 8.0.14.

- Error number: [MY-013276](#); Symbol: [ER\\_CANT\\_SET\\_DATA\\_DIR](#); SQLSTATE: [HY000](#)

Message: Failed to set datadir to '%s' (OS errno: %d - %s)

[ER\\_CANT\\_SET\\_DATA\\_DIR](#) was added in 8.0.14.

- Error number: [MY-013277](#); Symbol: [ER\\_INNOODB\\_INVALID\\_INNOODB\\_UNDO\\_DIRECTORY\\_LOCATION](#); SQLSTATE: [HY000](#)

Message: The innodb\_undo\_directory is not allowed to be an ancestor of the datadir.

[ER\\_INNOODB\\_INVALID\\_INNOODB\\_UNDO\\_DIRECTORY\\_LOCATION](#) was added in 8.0.14.

- Error number: [MY-013278](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_FETCH\\_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to fetch key from keyring, please check if keyring is loaded.

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_FETCH\\_KEY](#) was added in 8.0.14.

- Error number: [MY-013279](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_KEY\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_KEY\\_NOT\\_FOUND](#) was added in 8.0.14.

- 
- Error number: [MY-013280](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_KEYRING\\_INVALID\\_KEY](#); SQLSTATE: [HY000](#)  
  
Message: Fetched an invalid key from keyring.  
  
[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_KEYRING\\_INVALID\\_KEY](#) was added in 8.0.14.
  - Error number: [MY-013281](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_HEADER\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error reading a replication log encryption header: %s.  
  
[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_HEADER\\_ERROR](#) was added in 8.0.14.
  - Error number: [MY-013282](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_ROTATE\\_LOGS](#); SQLSTATE: [HY000](#)  
  
Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.  
  
[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_ROTATE\\_LOGS](#) was added in 8.0.14.
  - Error number: [MY-013283](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_KEY\\_EXISTS\\_UNEXPECTED](#); SQLSTATE: [HY000](#)  
  
Message: Key %s exists unexpectedly.  
  
[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_KEY\\_EXISTS\\_UNEXPECTED](#) was added in 8.0.14.
  - Error number: [MY-013284](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_GENERATE\\_KEY](#); SQLSTATE: [HY000](#)  
  
Message: Failed to generate key, please check if keyring is loaded.  
  
[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_GENERATE\\_KEY](#) was added in 8.0.14.
  - Error number: [MY-013285](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_STORE\\_KEY](#); SQLSTATE: [HY000](#)  
  
Message: Failed to store key, please check if keyring is loaded.  
  
[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_STORE\\_KEY](#) was added in 8.0.14.
  - Error number: [MY-013286](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_REMOVE\\_KEY](#); SQLSTATE: [HY000](#)  
  
Message: Failed to remove key, please check if keyring is loaded.  
  
[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_REMOVE\\_KEY](#) was added in 8.0.14.
  - Error number: [MY-013287](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_MASTER\\_KEY\\_RECOVERY\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Unable to recover binlog encryption master key, please check if keyring is loaded.  
  
[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_MASTER\\_KEY\\_RECOVERY\\_FAILED](#) was added in 8.0.14.
  - Error number: [MY-013288](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_UNABLE\\_TO\\_INITIALIZE](#); SQLSTATE: [HY000](#)

---

Message: Failed to initialize binlog encryption, please check if keyring is loaded.

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_UNABLE\\_TO\\_INITIALIZE](#) was added in 8.0.14.

- Error number: [MY-013289](#); Symbol:

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_UNABLE\\_TO\\_ROTATE\\_MASTER\\_KEY\\_AT\\_STARTUP](#); SQLSTATE: [HY000](#)

Message: Failed to rotate binlog encryption master key at startup, please check if keyring is loaded.

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_UNABLE\\_TO\\_ROTATE\\_MASTER\\_KEY\\_AT\\_STARTUP](#) was added in 8.0.14.

- Error number: [MY-013290](#); Symbol:

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_IGNORE\\_ROTATE\\_MASTER\\_KEY\\_AT\\_STARTUP](#); SQLSTATE: [HY000](#)

Message: Ignoring binlog\_rotate\_encryption\_master\_key\_at\_startup because binlog\_encryption option is disabled.

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_IGNORE\\_ROTATE\\_MASTER\\_KEY\\_AT\\_STARTUP](#) was added in 8.0.14.

- Error number: [MY-013291](#); Symbol: [ER\\_INVALID\\_ADMIN\\_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Invalid value for command line option admin-address: '%s'

[ER\\_INVALID\\_ADMIN\\_ADDRESS](#) was added in 8.0.14.

- Error number: [MY-013292](#); Symbol: [ER\\_SERVER\\_STARTUP\\_ADMIN\\_INTERFACE](#); SQLSTATE: [HY000](#)

Message: Admin interface ready for connections, address: '%s' port: %d

[ER\\_SERVER\\_STARTUP\\_ADMIN\\_INTERFACE](#) was added in 8.0.14.

- Error number: [MY-013293](#); Symbol: [ER\\_CANT\\_CREATE\\_ADMIN\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create thread to handle admin connections (errno= %d)

[ER\\_CANT\\_CREATE\\_ADMIN\\_THREAD](#) was added in 8.0.14.

- Error number: [MY-013294](#); Symbol: [ER\\_WARNING\\_RETAIN\\_CURRENT\\_PASSWORD\\_CLAUSE\\_VOID](#); SQLSTATE: [HY000](#)

Message: RETAIN CURRENT PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.

[ER\\_WARNING\\_RETAIN\\_CURRENT\\_PASSWORD\\_CLAUSE\\_VOID](#) was added in 8.0.14.

- Error number: [MY-013295](#); Symbol: [ER\\_WARNING\\_DISCARD\\_OLD\\_PASSWORD\\_CLAUSE\\_VOID](#); SQLSTATE: [HY000](#)

Message: DISCARD OLD PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.

[ER\\_WARNING\\_DISCARD\\_OLD\\_PASSWORD\\_CLAUSE\\_VOID](#) was added in 8.0.14.

- Error number: [MY-013299](#); Symbol: [ER\\_WARNING\\_AUTHCACHE\\_INVALID\\_USER\\_ATTRIBUTES](#); SQLSTATE: [HY000](#)

---

Message: Can not read and process value of User\_attributes column from mysql.user table for user: '%s@%s'; Ignoring user.

[ER\\_WARNING\\_AUTHCACHE\\_INVALID\\_USER\\_ATTRIBUTES](#) was added in 8.0.14.

- Error number: [MY-013300](#); Symbol: [ER\\_MYSQL\\_NATIVE\\_PASSWORD\\_SECOND\\_PASSWORD\\_USED\\_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Second password was used for login by user: '%s'@'%s'.

[ER\\_MYSQL\\_NATIVE\\_PASSWORD\\_SECOND\\_PASSWORD\\_USED\\_INFORMATION](#) was added in 8.0.14.

- Error number: [MY-013301](#); Symbol: [ER\\_SHA256\\_PASSWORD\\_SECOND\\_PASSWORD\\_USED\\_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Second password was used for login by user: '%s'@'%s'.

[ER\\_SHA256\\_PASSWORD\\_SECOND\\_PASSWORD\\_USED\\_INFORMATION](#) was added in 8.0.14.

- Error number: [MY-013302](#); Symbol: [ER\\_CACHING\\_SHA2\\_PASSWORD\\_SECOND\\_PASSWORD\\_USED\\_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Second password was used for login by user: '%s'@'%s'.

[ER\\_CACHING\\_SHA2\\_PASSWORD\\_SECOND\\_PASSWORD\\_USED\\_INFORMATION](#) was added in 8.0.14.

- Error number: [MY-013303](#); Symbol: [ER\\_GRP\\_RPL\\_SEND\\_TRX\\_PREPARED\\_MESSAGE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error sending transaction '%d:%lld' prepared message from session '%u'.

[ER\\_GRP\\_RPL\\_SEND\\_TRX\\_PREPARED\\_MESSAGE\\_FAILED](#) was added in 8.0.14.

- Error number: [MY-013304](#); Symbol: [ER\\_GRP\\_RPL\\_RELEASE\\_COMMIT\\_AFTER\\_GROUP\\_PREPARE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error releasing transaction '%d:%lld' for commit on session '%u' after being prepared on all group members.

[ER\\_GRP\\_RPL\\_RELEASE\\_COMMIT\\_AFTER\\_GROUP\\_PREPARE\\_FAILED](#) was added in 8.0.14.

- Error number: [MY-013305](#); Symbol: [ER\\_GRP\\_RPL\\_TRX\\_ALREADY\\_EXISTS\\_ON\\_TCM\\_ON\\_AFTER\\_CERTIFICATION](#); SQLSTATE: [HY000](#)

Message: Transaction '%d:%lld' already exists on Group Replication consistency manager while being registered after conflict detection.

[ER\\_GRP\\_RPL\\_TRX\\_ALREADY\\_EXISTS\\_ON\\_TCM\\_ON\\_AFTER\\_CERTIFICATION](#) was added in 8.0.14.

- Error number: [MY-013306](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INSERT\\_TRX\\_ON\\_TCM\\_ON\\_AFTER\\_CERTIFICATION](#); SQLSTATE: [HY000](#)

Message: Error registering transaction '%d:%lld' on Group Replication consistency manager after conflict detection.

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INSERT\\_TRX\\_ON\\_TCM\\_ON\\_AFTER\\_CERTIFICATION](#) was added in 8.0.14.

- 
- Error number: [MY-013307](#); Symbol: [ER\\_GRP\\_RPL\\_REGISTER\\_TRX\\_TO\\_WAIT\\_FOR\\_GROUP\\_PREPARE\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Error registering transaction '%d:%lld' from session '%u' to wait for being prepared on all group members.  
  
[ER\\_GRP\\_RPL\\_REGISTER\\_TRX\\_TO\\_WAIT\\_FOR\\_GROUP\\_PREPARE\\_FAILED](#) was added in 8.0.14.
  - Error number: [MY-013308](#); Symbol: [ER\\_GRP\\_RPL\\_TRX\\_WAIT\\_FOR\\_GROUP\\_PREPARE\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Error on transaction '%d:%lld' from session '%u' while waiting for being prepared on all group members.  
  
[ER\\_GRP\\_RPL\\_TRX\\_WAIT\\_FOR\\_GROUP\\_PREPARE\\_FAILED](#) was added in 8.0.14.
  - Error number: [MY-013309](#); Symbol: [ER\\_GRP\\_RPL\\_TRX\\_DOES\\_NOT\\_EXIST\\_ON\\_TCM\\_ON\\_HANDLE\\_REMOTE\\_PREPARE](#); SQLSTATE: [HY000](#)  
  
Message: Transaction '%d:%lld' does not exist on Group Replication consistency manager while receiving remote transaction prepare.  
  
[ER\\_GRP\\_RPL\\_TRX\\_DOES\\_NOT\\_EXIST\\_ON\\_TCM\\_ON\\_HANDLE\\_REMOTE\\_PREPARE](#) was added in 8.0.14.
  - Error number: [MY-013310](#); Symbol: [ER\\_GRP\\_RPL\\_RELEASE\\_BEGIN\\_TRX\\_AFTER\\_DEPENDENCIES\\_COMMIT\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Error releasing transaction '%d:%lld' for execution on session '%u' after its dependencies did complete commit.  
  
[ER\\_GRP\\_RPL\\_RELEASE\\_BEGIN\\_TRX\\_AFTER\\_DEPENDENCIES\\_COMMIT\\_FAILED](#) was added in 8.0.14.
  - Error number: [MY-013311](#); Symbol: [ER\\_GRP\\_RPL\\_REGISTER\\_TRX\\_TO\\_WAIT\\_FOR\\_DEPENDENCIES\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Error registering transaction from session '%u' to wait for its dependencies to complete commit.  
  
[ER\\_GRP\\_RPL\\_REGISTER\\_TRX\\_TO\\_WAIT\\_FOR\\_DEPENDENCIES\\_FAILED](#) was added in 8.0.14.
  - Error number: [MY-013312](#); Symbol: [ER\\_GRP\\_RPL\\_WAIT\\_FOR\\_DEPENDENCIES\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Error on session '%u' while waiting for its dependencies to complete commit.  
  
[ER\\_GRP\\_RPL\\_WAIT\\_FOR\\_DEPENDENCIES\\_FAILED](#) was added in 8.0.14.
  - Error number: [MY-013313](#); Symbol: [ER\\_GRP\\_RPL\\_REGISTER\\_TRX\\_TO\\_WAIT\\_FOR\\_SYNC\\_BEFORE\\_EXECUTION\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Error registering transaction from session '%u' to wait for sync before execution.  
  
[ER\\_GRP\\_RPL\\_REGISTER\\_TRX\\_TO\\_WAIT\\_FOR\\_SYNC\\_BEFORE\\_EXECUTION\\_FAILED](#) was added in 8.0.14.
  - Error number: [MY-013314](#); Symbol: [ER\\_GRP\\_RPL\\_SEND\\_TRX\\_SYNC\\_BEFORE\\_EXECUTION\\_FAILED](#); SQLSTATE: [HY000](#)

---

Message: Error sending sync before execution message from session '%u'.

[ER\\_GRP\\_RPL\\_SEND\\_TRX\\_SYNC\\_BEFORE\\_EXECUTION\\_FAILED](#) was added in 8.0.14.

- Error number: [MY-013315](#); Symbol: [ER\\_GRP\\_RPL\\_TRX\\_WAIT\\_FOR\\_SYNC\\_BEFORE\\_EXECUTION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error on transaction from session '%u' while waiting for sync before execution.

[ER\\_GRP\\_RPL\\_TRX\\_WAIT\\_FOR\\_SYNC\\_BEFORE\\_EXECUTION\\_FAILED](#) was added in 8.0.14.

- Error number: [MY-013316](#); Symbol: [ER\\_GRP\\_RPL\\_RELEASE\\_BEGIN\\_TRX\\_AFTER\\_WAIT\\_FOR\\_SYNC\\_BEFORE\\_EXEC](#); SQLSTATE: [HY000](#)

Message: Error releasing transaction for execution on session '%u' after wait for sync before execution.

[ER\\_GRP\\_RPL\\_RELEASE\\_BEGIN\\_TRX\\_AFTER\\_WAIT\\_FOR\\_SYNC\\_BEFORE\\_EXEC](#) was added in 8.0.14.

- Error number: [MY-013317](#); Symbol: [ER\\_GRP\\_RPL\\_TRX\\_WAIT\\_FOR\\_GROUP\\_GTID\\_EXECUTED](#); SQLSTATE: [HY000](#)

Message: Error waiting for group executed transactions commit on session '%u'.

[ER\\_GRP\\_RPL\\_TRX\\_WAIT\\_FOR\\_GROUP\\_GTID\\_EXECUTED](#) was added in 8.0.14.

- Error number: [MY-013320](#); Symbol: [ER\\_WARN\\_PROPERTY\\_STRING\\_PARSE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Could not parse key-value pairs in property string '%s'

[ER\\_WARN\\_PROPERTY\\_STRING\\_PARSE\\_FAILED](#) was added in 8.0.14.

- Error number: [MY-013321](#); Symbol: [ER\\_INVALID\\_PROPERTY\\_KEY](#); SQLSTATE: [HY000](#)

Message: Property key '%s' is invalid.

[ER\\_INVALID\\_PROPERTY\\_KEY](#) was added in 8.0.14.

- Error number: [MY-013322](#); Symbol: [ER\\_GRP\\_RPL\\_GTID\\_SET\\_EXTRACT\\_ERROR\\_DURING\\_RECOVERY](#); SQLSTATE: [HY000](#)

Message: Error when extracting the group\_replication\_applier channel received transactions set. Unable to ensure the execution of group transactions received during recovery.

[ER\\_GRP\\_RPL\\_GTID\\_SET\\_EXTRACT\\_ERROR\\_DURING\\_RECOVERY](#) was added in 8.0.14.

- Error number: [MY-013323](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_ENCRYPT](#); SQLSTATE: [HY000](#)

Message: Failed to encrypt content to write into binlog file: %s.

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_ENCRYPT](#) was added in 8.0.14.

- 
- Error number: [MY-013324](#); Symbol: [ER\\_CANNOT\\_GET\\_SERVER\\_VERSION\\_FROM\\_TABLESPACE\\_HEADER](#); SQLSTATE: [HY000](#)  
  
Message: Cannot get the server version number from the dictionary tablespace header.  
  
[ER\\_CANNOT\\_GET\\_SERVER\\_VERSION\\_FROM\\_TABLESPACE\\_HEADER](#) was added in 8.0.14.
  - Error number: [MY-013325](#); Symbol: [ER\\_CANNOT\\_SET\\_SERVER\\_VERSION\\_IN\\_TABLESPACE\\_HEADER](#); SQLSTATE: [HY000](#)  
  
Message: Cannot set the server version number in the dictionary tablespace header.  
  
[ER\\_CANNOT\\_SET\\_SERVER\\_VERSION\\_IN\\_TABLESPACE\\_HEADER](#) was added in 8.0.14.
  - Error number: [MY-013326](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_VERSION\\_NOT\\_SUPPORTED](#); SQLSTATE: [HY000](#)  
  
Message: Upgrading the server from server version '%u' is not supported.  
  
[ER\\_SERVER\\_UPGRADE\\_VERSION\\_NOT\\_SUPPORTED](#) was added in 8.0.14.
  - Error number: [MY-013327](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_FROM\\_VERSION](#); SQLSTATE: [HY000](#)  
  
Message: MySQL server upgrading from version '%u' to '%u'.  
  
[ER\\_SERVER\\_UPGRADE\\_FROM\\_VERSION](#) was added in 8.0.14.
  - Error number: [MY-013328](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_ON\\_CERT\\_DB\\_INSTALL](#); SQLSTATE: [HY000](#)  
  
Message: The certification information could not be set in this server: '%s'  
  
[ER\\_GRP\\_RPL\\_ERROR\\_ON\\_CERT\\_DB\\_INSTALL](#) was added in 8.0.14.
  - Error number: [MY-013329](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBERS\\_WHEN\\_LEAVING](#); SQLSTATE: [HY000](#)  
  
Message: A request to force a new group membership was issued when the member is leaving the group.  
  
[ER\\_GRP\\_RPL\\_FORCE\\_MEMBERS\\_WHEN\\_LEAVING](#) was added in 8.0.14.
  - Error number: [MY-013330](#); Symbol: [ER\\_TRG\\_WRONG\\_ORDER](#); SQLSTATE: [HY000](#)  
  
Message: Trigger %s.%s for table %s.%s is listed in wrong order. Please drop and recreate all triggers for the table.  
  
[ER\\_TRG\\_WRONG\\_ORDER](#) was added in 8.0.14.
  - Error number: [MY-013332](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_SEARCH\\_NOT\\_SPECIAL\\_HDL](#); SQLSTATE: [HY000](#)  
  
Message: Special handling for group search, {GA} not found  
  
[ER\\_LDAP\\_AUTH\\_GRP\\_SEARCH\\_NOT\\_SPECIAL\\_HDL](#) was added in 8.0.14.
  - Error number: [MY-013333](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_USER\\_OBJECT\\_HAS\\_GROUP\\_INFO](#); SQLSTATE: [HY000](#)

---

Message: User group retrieval: User object has group information

[ER\\_LDAP\\_AUTH\\_GRP\\_USER\\_OBJECT\\_HAS\\_GROUP\\_INFO](#) was added in 8.0.14.

- Error number: [MY-013334](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_INFO\\_FOUND\\_IN\\_MANY\\_OBJECTS](#); SQLSTATE: [HY000](#)

Message: Group information found in multiple user objects. Search filter configuration is incorrect.

[ER\\_LDAP\\_AUTH\\_GRP\\_INFO\\_FOUND\\_IN\\_MANY\\_OBJECTS](#) was added in 8.0.14.

- Error number: [MY-013335](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_INCORRECT\\_ATTRIBUTE](#); SQLSTATE: [HY000](#)

Message: User group retrieval: no group attribute found. Incorrect group search attribute.

[ER\\_LDAP\\_AUTH\\_GRP\\_INCORRECT\\_ATTRIBUTE](#) was added in 8.0.14.

- Error number: [MY-013336](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_NULL\\_ATTRIBUTE\\_VALUE](#); SQLSTATE: [HY000](#)

Message: User group retrieval: Group attribute values is NULL.

[ER\\_LDAP\\_AUTH\\_GRP\\_NULL\\_ATTRIBUTE\\_VALUE](#) was added in 8.0.14.

- Error number: [MY-013337](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_DN\\_PARSING\\_FAILED](#); SQLSTATE: [HY000](#)

Message: User group retrieval: parsing DN failed.

[ER\\_LDAP\\_AUTH\\_GRP\\_DN\\_PARSING\\_FAILED](#) was added in 8.0.14.

- Error number: [MY-013338](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_OBJECT\\_HAS\\_USER\\_INFO](#); SQLSTATE: [HY000](#)

Message: User group retrieval: Group object has user information

[ER\\_LDAP\\_AUTH\\_GRP\\_OBJECT\\_HAS\\_USER\\_INFO](#) was added in 8.0.14.

- Error number: [MY-013339](#); Symbol: [ER\\_LDAP\\_AUTH\\_LDAPS](#); SQLSTATE: [HY000](#)

Message: Reserved port for ldaps using ldaps

[ER\\_LDAP\\_AUTH\\_LDAPS](#) was added in 8.0.14.

- Error number: [MY-013340](#); Symbol: [ER\\_LDAP\\_MAPPING\\_GET\\_USER\\_PROXY](#); SQLSTATE: [HY000](#)

Message: Get user proxy

[ER\\_LDAP\\_MAPPING\\_GET\\_USER\\_PROXY](#) was added in 8.0.14.

- Error number: [MY-013341](#); Symbol: [ER\\_LDAP\\_MAPPING\\_USER\\_DONT\\_BELONG\\_GROUP](#); SQLSTATE: [HY000](#)

Message: Get user proxy: User doesn't belongs to any group, user name will be treated as authenticated user.

[ER\\_LDAP\\_MAPPING\\_USER\\_DONT\\_BELONG\\_GROUP](#) was added in 8.0.14.

- Error number: [MY-013342](#); Symbol: [ER\\_LDAP\\_MAPPING\\_INFO](#); SQLSTATE: [HY000](#)



---

Message: Get user proxy: configured mapping info: %s

[ER\\_LDAP\\_MAPPING\\_INFO](#) was added in 8.0.14.

- Error number: [MY-013343](#); Symbol: [ER\\_LDAP\\_MAPPING\\_EMPTY\\_MAPPING](#); SQLSTATE: [HY000](#)

Message: Get user proxy: User doesn't have group mapping information, First LDAP group will be treated as authenticated user.

[ER\\_LDAP\\_MAPPING\\_EMPTY\\_MAPPING](#) was added in 8.0.14.

- Error number: [MY-013344](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PROCESS\\_MAPPING](#); SQLSTATE: [HY000](#)

Message: Process group proxy mapping

[ER\\_LDAP\\_MAPPING\\_PROCESS\\_MAPPING](#) was added in 8.0.14.

- Error number: [MY-013345](#); Symbol: [ER\\_LDAP\\_MAPPING\\_CHECK\\_DELIMI\\_QUOTE](#); SQLSTATE: [HY000](#)

Message: Check delimiter after quote

[ER\\_LDAP\\_MAPPING\\_CHECK\\_DELIMI\\_QUOTE](#) was added in 8.0.14.

- Error number: [MY-013346](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER](#); SQLSTATE: [HY000](#)

Message: Processing delimiter

[ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER](#) was added in 8.0.14.

- Error number: [MY-013347](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER\\_EQUAL\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Processing delimiter, separator = not found, resetting position

[ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER\\_EQUAL\\_NOT\\_FOUND](#) was added in 8.0.14.

- Error number: [MY-013348](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER\\_TRY\\_COMMA](#); SQLSTATE: [HY000](#)

Message: "Processing delimiter, failed to get data for = separator try for separator ,."

[ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER\\_TRY\\_COMMA](#) was added in 8.0.14.

- Error number: [MY-013349](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER\\_COMMA\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Processing delimiter, separator , not found, resetting position

[ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER\\_COMMA\\_NOT\\_FOUND](#) was added in 8.0.14.

- Error number: [MY-013350](#); Symbol: [ER\\_LDAP\\_MAPPING\\_NO\\_SEPEARATOR\\_END\\_OF\\_GROUP](#); SQLSTATE: [HY000](#)

Message: Processing delimiter: No mapping separator is found, end of group information

[ER\\_LDAP\\_MAPPING\\_NO\\_SEPEARATOR\\_END\\_OF\\_GROUP](#) was added in 8.0.14.

- Error number: [MY-013351](#); Symbol: [ER\\_LDAP\\_MAPPING\\_GETTING\\_NEXT\\_MAPPING](#); SQLSTATE: [HY000](#)

---

Message: Getting next mapping information

[ER\\_LDAP\\_MAPPING\\_GETTING\\_NEXT\\_MAPPING](#) was added in 8.0.14.

- Error number: [MY-013352](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PARSING\\_CURRENT\\_STATE](#); SQLSTATE: [HY000](#)

Message: Parsing mapping, current state: %d delimiter char: %c

[ER\\_LDAP\\_MAPPING\\_PARSING\\_CURRENT\\_STATE](#) was added in 8.0.14.

- Error number: [MY-013353](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PARSING\\_MAPPING\\_INFO](#); SQLSTATE: [HY000](#)

Message: Parsing mapping info, LDAP group: %s MySQL proxy: %s

[ER\\_LDAP\\_MAPPING\\_PARSING\\_MAPPING\\_INFO](#) was added in 8.0.14.

- Error number: [MY-013354](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PARSING\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Mapping parsing error

[ER\\_LDAP\\_MAPPING\\_PARSING\\_ERROR](#) was added in 8.0.14.

- Error number: [MY-013355](#); Symbol: [ER\\_LDAP\\_MAPPING\\_TRIMMING\\_SPACES](#); SQLSTATE: [HY000](#)

Message: Trimming left spaces

[ER\\_LDAP\\_MAPPING\\_TRIMMING\\_SPACES](#) was added in 8.0.14.

- Error number: [MY-013356](#); Symbol: [ER\\_LDAP\\_MAPPING\\_IS\\_QUOTE](#); SQLSTATE: [HY000](#)

Message: Checking if current characters is quote

[ER\\_LDAP\\_MAPPING\\_IS\\_QUOTE](#) was added in 8.0.14.

- Error number: [MY-013357](#); Symbol: [ER\\_LDAP\\_MAPPING\\_NON\\_DESIRED\\_STATE](#); SQLSTATE: [HY000](#)

Message: Not desired state or un-defined states.

[ER\\_LDAP\\_MAPPING\\_NON\\_DESIRED\\_STATE](#) was added in 8.0.14.

- Error number: [MY-013358](#); Symbol: [ER\\_INVALID\\_NAMED\\_PIPE\\_FULL\\_ACCESS\\_GROUP](#); SQLSTATE: [HY000](#)

Message: Invalid value for named\_pipe\_full\_access\_group.

[ER\\_INVALID\\_NAMED\\_PIPE\\_FULL\\_ACCESS\\_GROUP](#) was added in 8.0.14.

- Error number: [MY-013359](#); Symbol: [ER\\_PREPARE\\_FOR\\_SECONDARY\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Retry the statement using a secondary storage engine.

[ER\\_PREPARE\\_FOR\\_SECONDARY\\_ENGINE](#) was added in 8.0.16.

- Error number: [MY-013360](#); Symbol: [ER\\_SERVER\\_WARN\\_DEPRECATED](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead

---

`ER_SERVER_WARN_DEPRECATED` was added in 8.0.16.

- Error number: `MY-013361`; Symbol: `ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES`; SQLSTATE: `HY000`

Message: Cannot set mandatory\_roles: AuthId '%s'@'%s' has '%s' privilege.

`ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES` was added in 8.0.16.

- Error number: `MY-013362`; Symbol: `ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION`; SQLSTATE: `HY000`

Message: Unable to recover binary log master key, the combination of new\_master\_key\_seqno=%u, master\_key\_seqno=%u and old\_master\_key\_seqno=%u are wrong.

`ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION` was added in 8.0.16.

- Error number: `MY-013363`; Symbol: `ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY`; SQLSTATE: `HY000`

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

`ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY` was added in 8.0.16.

- Error number: `MY-013368`; Symbol: `ER_TURNING_ON_PARTIAL_REVOKES`; SQLSTATE: `HY000`

Message: At least one partial revoke exists on a database. Turning ON the system variable '@@partial\_revokes'.

`ER_TURNING_ON_PARTIAL_REVOKES` was added in 8.0.16.

- Error number: `MY-013369`; Symbol: `ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT`; SQLSTATE: `HY000`

Message: For user '%s'@'%s', one or more privileges granted through mysql.db for database '%s', conflict with partial revoke. It could mean 'mysql' schema is corrupted.

`ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT` was added in 8.0.16.

- Error number: `MY-013370`; Symbol: `ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS`; SQLSTATE: `HY000`

Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as these are not valid database privileges.

`ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS` was added in 8.0.16.

- Error number: `MY-013371`; Symbol: `ER_WARN_INVALID_DB_RESTRICTIONS`; SQLSTATE: `HY000`

Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as corresponding global privilege(s) are not granted.

`ER_WARN_INVALID_DB_RESTRICTIONS` was added in 8.0.16.

- 
- Error number: [MY-013372](#); Symbol: [ER\\_GRP\\_RPL\\_INVALID\\_COMMUNICATION\\_PROTOCOL](#); SQLSTATE: [HY000](#)  
  
Message: '%s' is an invalid value for group\_replication\_communication\_protocol\_join, please use a MySQL version between 5.7.14 and this server's version  
  
[ER\\_GRP\\_RPL\\_INVALID\\_COMMUNICATION\\_PROTOCOL](#) was added in 8.0.16.
  - Error number: [MY-013373](#); Symbol: [ER\\_GRP\\_RPL\\_STARTED\\_AUTO\\_REJOIN](#); SQLSTATE: [HY000](#)  
  
Message: Started auto-rejoin procedure attempt %lu of %lu  
  
[ER\\_GRP\\_RPL\\_STARTED\\_AUTO\\_REJOIN](#) was added in 8.0.16.
  - Error number: [MY-013374](#); Symbol: [ER\\_GRP\\_RPL\\_TIMEOUT\\_RECEIVED\\_VC\\_ON\\_REJOIN](#); SQLSTATE: [HY000](#)  
  
Message: Timeout while waiting for a view change event during the auto-rejoin procedure  
  
[ER\\_GRP\\_RPL\\_TIMEOUT\\_RECEIVED\\_VC\\_ON\\_REJOIN](#) was added in 8.0.16.
  - Error number: [MY-013375](#); Symbol: [ER\\_GRP\\_RPL\\_FINISHED\\_AUTO\\_REJOIN](#); SQLSTATE: [HY000](#)  
  
Message: Auto-rejoin procedure attempt %lu of %lu finished. Member was%s able to join the group.  
  
[ER\\_GRP\\_RPL\\_FINISHED\\_AUTO\\_REJOIN](#) was added in 8.0.16.
  - Error number: [MY-013376](#); Symbol: [ER\\_GRP\\_RPL\\_DEFAULT\\_TABLE\\_ENCRYPTION\\_DIFF\\_FROM\\_GRP](#); SQLSTATE: [HY000](#)  
  
Message: The member is configured with a default\_table\_encryption option value '%d' different from the group '%d'. The member will now exit the group.  
  
[ER\\_GRP\\_RPL\\_DEFAULT\\_TABLE\\_ENCRYPTION\\_DIFF\\_FROM\\_GRP](#) was added in 8.0.16.
  - Error number: [MY-013377](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_OFF](#); SQLSTATE: [HY000](#)  
  
Message: Server shutting down because upgrade is required, yet prohibited by the command line option '--upgrade=NONE'.  
  
[ER\\_SERVER\\_UPGRADE\\_OFF](#) was added in 8.0.16.
  - Error number: [MY-013378](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SKIP](#); SQLSTATE: [HY000](#)  
  
Message: Server upgrade is required, but skipped by command line option '--upgrade=MINIMAL'.  
  
[ER\\_SERVER\\_UPGRADE\\_SKIP](#) was added in 8.0.16.
  - Error number: [MY-013379](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_PENDING](#); SQLSTATE: [HY000](#)  
  
Message: Server upgrade started with version %d, but server upgrade of version %d is still pending.  
  
[ER\\_SERVER\\_UPGRADE\\_PENDING](#) was added in 8.0.16.
  - Error number: [MY-013380](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Failed to upgrade server.  
  
[ER\\_SERVER\\_UPGRADE\\_FAILED](#) was added in 8.0.16.

- 
- Error number: [MY-013381](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_STATUS](#); SQLSTATE: [HY000](#)  
Message: Server upgrade from '%d' to '%d' %s.  
[ER\\_SERVER\\_UPGRADE\\_STATUS](#) was added in 8.0.16.
  - Error number: [MY-013382](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_REPAIR\\_REQUIRED](#); SQLSTATE: [HY000](#)  
Message: Table '%s' requires repair.  
[ER\\_SERVER\\_UPGRADE\\_REPAIR\\_REQUIRED](#) was added in 8.0.16.
  - Error number: [MY-013383](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_REPAIR\\_STATUS](#); SQLSTATE: [HY000](#)  
Message: Table '%s' repair %s.  
[ER\\_SERVER\\_UPGRADE\\_REPAIR\\_STATUS](#) was added in 8.0.16.
  - Error number: [MY-013384](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_INFO\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Could not open server upgrade info file '%s' for writing. Please make sure the file is writable.  
[ER\\_SERVER\\_UPGRADE\\_INFO\\_FILE](#) was added in 8.0.16.
  - Error number: [MY-013385](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SYS\\_SCHEMA](#); SQLSTATE: [HY000](#)  
Message: Upgrading the sys schema.  
[ER\\_SERVER\\_UPGRADE\\_SYS\\_SCHEMA](#) was added in 8.0.16.
  - Error number: [MY-013386](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_MYSQL\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: Running queries to upgrade MySQL server.  
[ER\\_SERVER\\_UPGRADE\\_MYSQL\\_TABLES](#) was added in 8.0.16.
  - Error number: [MY-013387](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SYSTEM\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: Upgrading system table data.  
[ER\\_SERVER\\_UPGRADE\\_SYSTEM\\_TABLES](#) was added in 8.0.16.
  - Error number: [MY-013388](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_EMPTY\\_SYS](#); SQLSTATE: [HY000](#)  
Message: Found empty sys database. Installing the sys schema.  
[ER\\_SERVER\\_UPGRADE\\_EMPTY\\_SYS](#) was added in 8.0.16.
  - Error number: [MY-013389](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_NO\\_SYS\\_VERSION](#); SQLSTATE: [HY000](#)  
Message: A sys schema exists with no sys.version view. If you have a user created sys schema, this must be renamed for the upgrade to succeed.  
[ER\\_SERVER\\_UPGRADE\\_NO\\_SYS\\_VERSION](#) was added in 8.0.16.
  - Error number: [MY-013390](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SYS\\_VERSION\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: A sys schema exists with a sys.version view, but it returns no results.

---

`ER_SERVER_UPGRADE_SYS_VERSION_EMPTY` was added in 8.0.16.

- Error number: `MY-013391`; Symbol: `ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED`; SQLSTATE: `HY000`

Message: Found outdated sys schema version %s.

`ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED` was added in 8.0.16.

- Error number: `MY-013392`; Symbol: `ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE`; SQLSTATE: `HY000`

Message: The sys schema is already up to date (version %s).

`ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE` was added in 8.0.16.

- Error number: `MY-013393`; Symbol: `ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT`; SQLSTATE: `HY000`

Message: Found %d sys %s, but expected %d. Re-installing the sys schema.

`ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT` was added in 8.0.16.

- Error number: `MY-013394`; Symbol: `ER_SERVER_UPGRADE_CHECKING_DB`; SQLSTATE: `HY000`

Message: Checking '%s' schema.

`ER_SERVER_UPGRADE_CHECKING_DB` was added in 8.0.16.

- Error number: `MY-013395`; Symbol: `ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT`; SQLSTATE: `HY000`

Message: Too many concurrent transactions while clearing the DDL Log. Please increase the number of Rollback Segments.

`ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT` was added in 8.0.16.

- Error number: `MY-013396`; Symbol: `ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER`; SQLSTATE: `HY000`

Message: Error in DDL Log recovery during Post-Recovery processing.

`ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER` was added in 8.0.16.

- Error number: `MY-013397`; Symbol: `ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT`; SQLSTATE: `HY000`

Message: Error in Post-Tablespace-Encryption during Post-Recovery processing.

`ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT` was added in 8.0.16.

- Error number: `MY-013398`; Symbol: `ER_IB_MSG_DDL_LOG_FAIL_POST_DDL`; SQLSTATE: `HY000`

Message: Error in DLL Log cleanup during Post-DDL processing.

`ER_IB_MSG_DDL_LOG_FAIL_POST_DDL` was added in 8.0.16.

- 
- Error number: [MY-013399](#); Symbol: [ER\\_SERVER\\_BINLOG\\_UNSAFE\\_SYSTEM\\_FUNCTION](#); SQLSTATE: [HY000](#)  
  
Message: '%s' statement is unsafe because it uses a system function that may return a different value on the replica.  
  
[ER\\_SERVER\\_BINLOG\\_UNSAFE\\_SYSTEM\\_FUNCTION](#) was added in 8.0.16.
  - Error number: [MY-013400](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_HELP\\_TABLE\\_STATUS](#); SQLSTATE: [HY000](#)  
  
Message: Upgrade of help tables %s.  
  
[ER\\_SERVER\\_UPGRADE\\_HELP\\_TABLE\\_STATUS](#) was added in 8.0.16.
  - Error number: [MY-013401](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_GTID\\_WAIT\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error when waiting for the server to execute local transactions in order assure the group change proper logging  
  
[ER\\_GRP\\_RPL\\_SRV\\_GTID\\_WAIT\\_ERROR](#) was added in 8.0.16, removed after 8.0.31.
  - Error number: [MY-013402](#); Symbol: [ER\\_GRP\\_DELAYED\\_VCLE\\_LOGGING](#); SQLSTATE: [HY000](#)  
  
Message: Unable to log the group change View log event in its exaction position in the log. This will not however affect the group replication recovery process or the overall plugin process.  
  
[ER\\_GRP\\_DELAYED\\_VCLE\\_LOGGING](#) was added in 8.0.16, removed after 8.0.31.
  - Error number: [MY-013404](#); Symbol: [ER\\_BINLOG\\_UNABLE\\_TO\\_ROTATE\\_GTID\\_TABLE\\_READONLY](#); SQLSTATE: [HY000](#)  
  
Message: Unable to create a new binlog file: Table `mysql.gtid\_executed` couldn't be opened. %s  
  
[ER\\_BINLOG\\_UNABLE\\_TO\\_ROTATE\\_GTID\\_TABLE\\_READONLY](#) was added in 8.0.16.
  - Error number: [MY-013405](#); Symbol: [ER\\_NETWORK\\_NAMESPACES\\_NOT\\_SUPPORTED](#); SQLSTATE: [HY000](#)  
  
Message: Network Namespaces is not supported on this platform  
  
[ER\\_NETWORK\\_NAMESPACES\\_NOT\\_SUPPORTED](#) was added in 8.0.16.
  - Error number: [MY-013406](#); Symbol: [ER\\_UNKNOWN\\_NETWORK\\_NAMESPACE](#); SQLSTATE: [HY000](#)  
  
Message: Unknown network namespace '%s'  
  
[ER\\_UNKNOWN\\_NETWORK\\_NAMESPACE](#) was added in 8.0.16.
  - Error number: [MY-013407](#); Symbol: [ER\\_NETWORK\\_NAMESPACE\\_NOT\\_ALLOWED\\_FOR\\_WILDCARD\\_ADDRESS](#); SQLSTATE: [HY000](#)  
  
Message: Network namespace not allowed for wildcard interface address  
  
[ER\\_NETWORK\\_NAMESPACE\\_NOT\\_ALLOWED\\_FOR\\_WILDCARD\\_ADDRESS](#) was added in 8.0.16.
  - Error number: [MY-013408](#); Symbol: [ER\\_SETNS\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: setns() failed with error '%s'

---

`ER_SETNS_FAILED` was added in 8.0.16.

- Error number: `MY-013409`; Symbol: `ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND`; SQLSTATE: `HY000`

Message: Wildcard address value not allowed for multivalued bind address

`ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND` was added in 8.0.16.

- Error number: `MY-013410`; Symbol: `ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG`; SQLSTATE: `HY000`

Message: The path to a special network namespace file is too long. (got %u > max %u)

`ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG` was added in 8.0.16.

- Error number: `MY-013411`; Symbol: `ER_IB_MSG_TOO_LONG_PATH`; SQLSTATE: `HY000`

Message: Cannot create tablespace '%s'. The filepath is too long for this OS.

`ER_IB_MSG_TOO_LONG_PATH` was added in 8.0.16.

- Error number: `MY-013412`; Symbol: `ER_IB_RECV_FIRST_REC_GROUP_INVALID`; SQLSTATE: `HY000`

Message: The last block of redo had corrupted first\_rec\_group and became fixed (%u -> %u).

`ER_IB_RECV_FIRST_REC_GROUP_INVALID` was added in 8.0.16.

- Error number: `MY-013413`; Symbol: `ER_DD_UPGRADE_COMPLETED`; SQLSTATE: `HY000`

Message: Data dictionary upgrade from version '%u' to '%u' completed.

`ER_DD_UPGRADE_COMPLETED` was added in 8.0.16.

- Error number: `MY-013414`; Symbol: `ER_SSL_SERVER_CERT_VERIFY_FAILED`; SQLSTATE: `HY000`

Message: Server SSL certificate doesn't verify: %s

`ER_SSL_SERVER_CERT_VERIFY_FAILED` was added in 8.0.16.

- Error number: `MY-013415`; Symbol: `ER_PERSIST_OPTION_USER_TRUNCATED`; SQLSTATE: `HY000`

Message: Truncated a user name for %s that was too long while reading the persisted variables file

`ER_PERSIST_OPTION_USER_TRUNCATED` was added in 8.0.16.

- Error number: `MY-013416`; Symbol: `ER_PERSIST_OPTION_HOST_TRUNCATED`; SQLSTATE: `HY000`

Message: Truncated a host name for %s that was too long while reading the persisted variables file

`ER_PERSIST_OPTION_HOST_TRUNCATED` was added in 8.0.16.

- Error number: `MY-013417`; Symbol: `ER_NET_WAIT_ERROR`; SQLSTATE: `HY000`

Message: The wait\_timeout period was exceeded, the idle time since last command was too long.

`ER_NET_WAIT_ERROR` was added in 8.0.16.

- Error number: `MY-013418`; Symbol: `ER_IB_MSG_1285`; SQLSTATE: `HY000`



---

Message: '%s' found not encrypted while '%s' is ON. Trying to encrypt it now.

[ER\\_IB\\_MSG\\_1285](#) was added in 8.0.16.

- Error number: [MY-013419](#); Symbol: [ER\\_IB\\_MSG\\_CLOCK\\_MONOTONIC\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: CLOCK\_MONOTONIC is unsupported, so do not change the system time when MySQL is running !

[ER\\_IB\\_MSG\\_CLOCK\\_MONOTONIC\\_UNSUPPORTED](#) was added in 8.0.16.

- Error number: [MY-013420](#); Symbol: [ER\\_IB\\_MSG\\_CLOCK\\_GETTIME\\_FAILED](#); SQLSTATE: [HY000](#)

Message: clock\_gettime() failed: %s

[ER\\_IB\\_MSG\\_CLOCK\\_GETTIME\\_FAILED](#) was added in 8.0.16.

- Error number: [MY-013421](#); Symbol: [ER\\_PLUGIN\\_NOT\\_EARLY\\_DUP](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.

[ER\\_PLUGIN\\_NOT\\_EARLY\\_DUP](#) was added in 8.0.16.

- Error number: [MY-013422](#); Symbol: [ER\\_PLUGIN\\_NO\\_INSTALL\\_DUP](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.

[ER\\_PLUGIN\\_NO\\_INSTALL\\_DUP](#) was added in 8.0.16.

- Error number: [MY-013425](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_DEFAULT\\_EXPRESSION\\_IN\\_SUBSTATEMENT](#); SQLSTATE: [HY000](#)

Message: The statement is unsafe because it invokes a trigger or a stored function that modifies a table that has a column with a DEFAULT expression that may return a different value on the replica.

[ER\\_BINLOG\\_UNSAFE\\_DEFAULT\\_EXPRESSION\\_IN\\_SUBSTATEMENT](#) was added in 8.0.16.

- Error number: [MY-013426](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_VER\\_READ\\_COMPATIBLE](#); SQLSTATE: [HY000](#)

Message: Member version is read compatible with the group.

[ER\\_GRP\\_RPL\\_MEMBER\\_VER\\_READ\\_COMPATIBLE](#) was added in 8.0.16.

- Error number: [MY-013427](#); Symbol: [ER\\_LOCK\\_ORDER\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Lock order disabled (reason: init failed).

[ER\\_LOCK\\_ORDER\\_INIT\\_FAILED](#) was added in 8.0.16.

- Error number: [MY-013428](#); Symbol: [ER\\_AUDIT\\_LOG\\_KEYRING\\_ID\\_TIMESTAMP\\_VALUE\\_IS\\_INVALID](#); SQLSTATE: [HY000](#)

Message: Keyring ID timestamp value is invalid: '%s'

[ER\\_AUDIT\\_LOG\\_KEYRING\\_ID\\_TIMESTAMP\\_VALUE\\_IS\\_INVALID](#) was added in 8.0.16.

- 
- Error number: `MY-013429`; Symbol: `ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING_OR_INVALID`; SQLSTATE: `HY000`  
Message: Cannot process audit log file. File name timestamp value is missing or invalid: '%s'  
`ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING_OR_INVALID` was added in 8.0.16.
  - Error number: `MY-013430`; Symbol: `ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT`; SQLSTATE: `HY000`  
Message: Cannot process audit log file. File name does not have required format: '%s'  
`ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT` was added in 8.0.16.
  - Error number: `MY-013431`; Symbol: `ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING`; SQLSTATE: `HY000`  
Message: Cannot process audit log file. File name keyring ID value is missing: '%s'  
`ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING` was added in 8.0.16.
  - Error number: `MY-013432`; Symbol: `ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSED`; SQLSTATE: `HY000`  
Message: Audit log file has been successfully processed: '%s'  
`ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSED` was added in 8.0.16.
  - Error number: `MY-013433`; Symbol: `ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING`; SQLSTATE: `HY000`  
Message: Could not open audit log file for reading: '%s'  
`ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING` was added in 8.0.16.
  - Error number: `MY-013434`; Symbol: `ER_AUDIT_LOG_INVALID_FILE_CONTENT`; SQLSTATE: `HY000`  
Message: Invalid audit log file content: '%s'  
`ER_AUDIT_LOG_INVALID_FILE_CONTENT` was added in 8.0.16.
  - Error number: `MY-013435`; Symbol: `ER_AUDIT_LOG_CANNOT_READ_PASSWORD`; SQLSTATE: `HY000`  
Message: Cannot read password: '%s'.  
`ER_AUDIT_LOG_CANNOT_READ_PASSWORD` was added in 8.0.16.
  - Error number: `MY-013436`; Symbol: `ER_AUDIT_LOG_CANNOT_STORE_PASSWORD`; SQLSTATE: `HY000`  
Message: Cannot store password: '%s'.  
`ER_AUDIT_LOG_CANNOT_STORE_PASSWORD` was added in 8.0.16.
  - Error number: `MY-013437`; Symbol: `ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD`; SQLSTATE: `HY000`  
Message: Cannot remove password: '%s'.  
`ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD` was added in 8.0.16.

- 
- Error number: [MY-013438](#); Symbol: [ER\\_AUDIT\\_LOG\\_PASSWORD\\_HAS\\_BEEN\\_COPIED](#); SQLSTATE: [HY000](#)  
  
Message: 'audit\_log' password has been copied into '%s' and will be removed with first purged password.  
  
[ER\\_AUDIT\\_LOG\\_PASSWORD\\_HAS\\_BEEN\\_COPIED](#) was added in 8.0.16.
  - Error number: [MY-013447](#); Symbol: [ER\\_LDAP\\_EMPTY\\_USERDN\\_PASSWORD](#); SQLSTATE: [HY000](#)  
  
Message: Empty user dn or password is not allowed, not attempting LDAP bind.  
  
[ER\\_LDAP\\_EMPTY\\_USERDN\\_PASSWORD](#) was added in 8.0.16.
  - Error number: [MY-013449](#); Symbol: [ER\\_ACL\\_WRONG\\_OR\\_MISSING\\_ACL\\_TABLES\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: The current layout of the ACL tables does not conform to the server's expected layout. They're either altered, missing or not upgraded from a previous version. However a best effort attempt to read data from these tables will still be made.  
  
[ER\\_ACL\\_WRONG\\_OR\\_MISSING\\_ACL\\_TABLES\\_LOG](#) was added in 8.0.17.
  - Error number: [MY-013450](#); Symbol: [ER\\_LOCK\\_ORDER\\_FAILED\\_WRITE\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: LOCK\_ORDER: Failed to write to file <%s>.  
  
[ER\\_LOCK\\_ORDER\\_FAILED\\_WRITE\\_FILE](#) was added in 8.0.17.
  - Error number: [MY-013451](#); Symbol: [ER\\_LOCK\\_ORDER\\_FAILED\\_READ\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: LOCK\_ORDER: Failed to read from file <%s>.  
  
[ER\\_LOCK\\_ORDER\\_FAILED\\_READ\\_FILE](#) was added in 8.0.17.
  - Error number: [MY-013452](#); Symbol: [ER\\_LOCK\\_ORDER\\_MESSAGE](#); SQLSTATE: [HY000](#)  
  
Message: LOCK\_ORDER message: %s  
  
[ER\\_LOCK\\_ORDER\\_MESSAGE](#) was added in 8.0.17.
  - Error number: [MY-013453](#); Symbol: [ER\\_LOCK\\_ORDER\\_DEPENDENCIES\\_SYNTAX](#); SQLSTATE: [HY000](#)  
  
Message: Lock order dependencies file <%s> (%d:%d) - (%d:%d) : %s  
  
[ER\\_LOCK\\_ORDER\\_DEPENDENCIES\\_SYNTAX](#) was added in 8.0.17.
  - Error number: [MY-013454](#); Symbol: [ER\\_LOCK\\_ORDER\\_SCANNER\\_SYNTAX](#); SQLSTATE: [HY000](#)  
  
Message: Lock order scanner: (%d:%d) - (%d:%d) : %s  
  
[ER\\_LOCK\\_ORDER\\_SCANNER\\_SYNTAX](#) was added in 8.0.17.
  - Error number: [MY-013455](#); Symbol: [ER\\_DATA\\_DIRECTORY\\_UNUSABLE\\_DELETABLE](#); SQLSTATE: [HY000](#)  
  
Message: The newly created data directory %s by --initialize is unusable. You can remove it.  
  
[ER\\_DATA\\_DIRECTORY\\_UNUSABLE\\_DELETABLE](#) was added in 8.0.17.

- 
- Error number: [MY-013456](#); Symbol: [ER\\_IB\\_MSG\\_BTREE\\_LEVEL\\_LIMIT\\_EXCEEDED](#); SQLSTATE: [HY000](#)

Message: No. of B-tree level created for index %s has crossed the permissible limit. If debug option `innodb_limit_optimistic_insert_debug` is being used try tweaking it to include more records in a page.

[ER\\_IB\\_MSG\\_BTREE\\_LEVEL\\_LIMIT\\_EXCEEDED](#) was added in 8.0.17.

- Error number: [MY-013457](#); Symbol: [ER\\_IB\\_CLONE\\_START\\_STOP](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_CLONE\\_START\\_STOP](#) was added in 8.0.17.

- Error number: [MY-013458](#); Symbol: [ER\\_IB\\_CLONE\\_OPERATION](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_CLONE\\_OPERATION](#) was added in 8.0.17.

- Error number: [MY-013459](#); Symbol: [ER\\_IB\\_CLONE\\_RESTART](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_CLONE\\_RESTART](#) was added in 8.0.17.

- Error number: [MY-013460](#); Symbol: [ER\\_IB\\_CLONE\\_USER\\_DATA](#); SQLSTATE: [HY000](#)

Message: Clone removing all user data for provisioning: %s

[ER\\_IB\\_CLONE\\_USER\\_DATA](#) was added in 8.0.17.

- Error number: [MY-013461](#); Symbol: [ER\\_IB\\_CLONE\\_NON\\_INNODB\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Non innodb table: %s.%s is not cloned and is empty.

[ER\\_IB\\_CLONE\\_NON\\_INNODB\\_TABLE](#) was added in 8.0.17.

- Error number: [MY-013462](#); Symbol: [ER\\_CLONE\\_SHUTDOWN\\_TRACE](#); SQLSTATE: [HY000](#)

Message: Clone shutting down server as RESTART failed. Please start server to complete clone operation.

[ER\\_CLONE\\_SHUTDOWN\\_TRACE](#) was added in 8.0.17.

- Error number: [MY-013463](#); Symbol: [ER\\_GRP\\_RPL\\_GTID\\_PURGED\\_EXTRACT\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member GTID purged set. Operations and checks made to group joiners may be incomplete.

[ER\\_GRP\\_RPL\\_GTID\\_PURGED\\_EXTRACT\\_ERROR](#) was added in 8.0.17.

- Error number: [MY-013464](#); Symbol: [ER\\_GRP\\_RPL\\_CLONE\\_PROCESS\\_PREPARE\\_ERROR](#); SQLSTATE: [HY000](#)

Message: There was an issue when configuring the remote cloning process: %s

[ER\\_GRP\\_RPL\\_CLONE\\_PROCESS\\_PREPARE\\_ERROR](#) was added in 8.0.17.

- 
- Error number: [MY-013465](#); Symbol: [ER\\_GRP\\_RPL\\_CLONE\\_PROCESS\\_EXEC\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: There was an issue when cloning from another server: %s  
  
[ER\\_GRP\\_RPL\\_CLONE\\_PROCESS\\_EXEC\\_ERROR](#) was added in 8.0.17.
  - Error number: [MY-013466](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_EVAL\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: There was an issue when trying to evaluate the best distributed recovery strategy while joining.%s  
  
[ER\\_GRP\\_RPL\\_RECOVERY\\_EVAL\\_ERROR](#) was added in 8.0.17.
  - Error number: [MY-013467](#); Symbol: [ER\\_GRP\\_RPL\\_NO\\_POSSIBLE\\_RECOVERY](#); SQLSTATE: [HY000](#)  
  
Message: No valid or ONLINE members exist to get the missing data from the group. For cloning check if donors of the same version and with clone plugin installed exist. For incremental recovery check if you have donors where the required data was not purged from the binary logs.  
  
[ER\\_GRP\\_RPL\\_NO\\_POSSIBLE\\_RECOVERY](#) was added in 8.0.17.
  - Error number: [MY-013468](#); Symbol: [ER\\_GRP\\_RPL\\_CANT\\_KILL\\_THREAD](#); SQLSTATE: [HY000](#)  
  
Message: The group replication plugin could not kill the plugin routine for %s. %s  
  
[ER\\_GRP\\_RPL\\_CANT\\_KILL\\_THREAD](#) was added in 8.0.17.
  - Error number: [MY-013469](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_CLONE\\_THRESHOLD](#); SQLSTATE: [HY000](#)  
  
Message: This member will start distributed recovery using clone. It is due to the number of missing transactions being higher than the configured threshold of %llu.  
  
[ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_CLONE\\_THRESHOLD](#) was added in 8.0.17.
  - Error number: [MY-013470](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_CLONE\\_PURGED](#); SQLSTATE: [HY000](#)  
  
Message: This member will start distributed recovery using clone. It is due to no ONLINE member has the missing data for recovering in its binary logs.  
  
[ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_CLONE\\_PURGED](#) was added in 8.0.17.
  - Error number: [MY-013471](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_CHOICE](#); SQLSTATE: [HY000](#)  
  
Message: Distributed recovery will transfer data using: %s  
  
[ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_CHOICE](#) was added in 8.0.17.
  - Error number: [MY-013472](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_FALLBACK](#); SQLSTATE: [HY000](#)  
  
Message: Due to some issue on the previous step distributed recovery is now executing: %s  
  
[ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_FALLBACK](#) was added in 8.0.17.
  - Error number: [MY-013473](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_NO\\_FALLBACK](#); SQLSTATE: [HY000](#)

---

Message: Due to a critical cloning error or lack of donors, distributed recovery cannot be executed. The member will now leave the group.

[ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_NO\\_FALLBACK](#) was added in 8.0.17.

- Error number: [MY-013474](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_THREAD\\_ERROR\\_ON\\_CLONE](#); SQLSTATE: [HY000](#)

Message: The '%s' thread of channel '%s' will error out as the server will attempt to clone another server

[ER\\_GRP\\_RPL\\_SLAVE\\_THREAD\\_ERROR\\_ON\\_CLONE](#) was added in 8.0.17, removed after 8.0.32.

- Error number: [MY-013474](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_THREAD\\_ERROR\\_ON\\_CLONE](#); SQLSTATE: [HY000](#)

Message: The '%s' thread of channel '%s' will error out as the server will attempt to clone another server

[ER\\_GRP\\_RPL\\_REPLICA\\_THREAD\\_ERROR\\_ON\\_CLONE](#) was added in 8.0.33.

- Error number: [MY-013475](#); Symbol: [ER\\_UNKNOWN\\_TABLE\\_IN\\_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Unknown table '%s'

[ER\\_UNKNOWN\\_TABLE\\_IN\\_UPGRADE](#) was added in 8.0.17.

- Error number: [MY-013476](#); Symbol: [ER\\_IDENT\\_CAUSES\\_TOO\\_LONG\\_PATH\\_IN\\_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.

[ER\\_IDENT\\_CAUSES\\_TOO\\_LONG\\_PATH\\_IN\\_UPGRADE](#) was added in 8.0.17.

- Error number: [MY-013477](#); Symbol: [ER\\_XA\\_CANT\\_CREATE\\_MDL\\_BACKUP](#); SQLSTATE: [HY000](#)

Message: XA: Failed to take MDL Lock backup of PREPARED XA transaction during client disconnect.

[ER\\_XA\\_CANT\\_CREATE\\_MDL\\_BACKUP](#) was added in 8.0.13.

- Error number: [MY-013478](#); Symbol: [ER\\_AUDIT\\_LOG\\_SUPER\\_PRIVILEGE\\_REQUIRED](#); SQLSTATE: [HY000](#)

Message: SUPER privilege or AUDIT\_ADMIN role required for '%s'@'%s' user.

[ER\\_AUDIT\\_LOG\\_SUPER\\_PRIVILEGE\\_REQUIRED](#) was added in 8.0.11.

- Error number: [MY-013479](#); Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_INVALID\\_ARGUMENT\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Invalid argument type

[ER\\_AUDIT\\_LOG\\_UDF\\_INVALID\\_ARGUMENT\\_TYPE](#) was added in 8.0.11.

- 
- Error number: [MY-013480](#); Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_INVALID\\_ARGUMENT\\_COUNT](#); SQLSTATE: [HY000](#)  
  
Message: Invalid argument count  
  
[ER\\_AUDIT\\_LOG\\_UDF\\_INVALID\\_ARGUMENT\\_COUNT](#) was added in 8.0.11.
  - Error number: [MY-013481](#); Symbol: [ER\\_AUDIT\\_LOG\\_HAS\\_NOT\\_BEEN\\_INSTALLED](#); SQLSTATE: [HY000](#)  
  
Message: audit\_log plugin has not been installed using INSTALL PLUGIN syntax.  
  
[ER\\_AUDIT\\_LOG\\_HAS\\_NOT\\_BEEN\\_INSTALLED](#) was added in 8.0.11.
  - Error number: [MY-013482](#); Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_READ\\_INVALID\\_MAX\\_ARRAY\\_LENGTH\\_ARG\\_TYPE](#); SQLSTATE: [HY000](#)  
  
Message: Invalid "max\_array\_length" argument type.  
  
[ER\\_AUDIT\\_LOG\\_UDF\\_READ\\_INVALID\\_MAX\\_ARRAY\\_LENGTH\\_ARG\\_TYPE](#) was added in 8.0.11.
  - Error number: [MY-013483](#); Symbol: [ER\\_LOG\\_CANNOT\\_WRITE\\_EXTENDED](#); SQLSTATE: [HY000](#)  
  
Message: Failed to write to %s: %s (%s)  
  
[ER\\_LOG\\_CANNOT\\_WRITE\\_EXTENDED](#) was added in 8.0.17.
  - Error number: [MY-013484](#); Symbol: [ER\\_UPGRADE\\_WITH\\_PARTITIONED\\_TABLES\\_REJECTED](#); SQLSTATE: [HY000](#)  
  
Message: Upgrading from server version %d with partitioned tables and lower\_case\_table\_names == 1 on a case sensitive file system may cause issues, and is therefore prohibited. To upgrade anyway, restart the new server version with the command line option 'upgrade=FORCE'. When upgrade is completed, please execute 'RENAME TABLE <part\_table\_name> TO <new\_table\_name>; RENAME TABLE <new\_table\_name> TO <part\_table\_name>;' for each of the partitioned tables. Please see the documentation for further information.  
  
[ER\\_UPGRADE\\_WITH\\_PARTITIONED\\_TABLES\\_REJECTED](#) was added in 8.0.17, removed after 8.0.18.
  - Error number: [MY-013485](#); Symbol: [ER\\_KEYRING\\_AWS\\_INCORRECT\\_PROXY](#); SQLSTATE: [HY000](#)  
  
Message: Incorrect environment variable %s, invalid port: %s  
  
[ER\\_KEYRING\\_AWS\\_INCORRECT\\_PROXY](#) was added in 8.0.18.
  - Error number: [MY-013486](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_SET\\_TO\\_OFFLINE\\_MODE\\_DUE\\_TO\\_ERRORS](#); SQLSTATE: [HY000](#)  
  
Message: The server was automatically set into offline mode after an error was detected.  
  
[ER\\_GRP\\_RPL\\_SERVER\\_SET\\_TO\\_OFFLINE\\_MODE\\_DUE\\_TO\\_ERRORS](#) was added in 8.0.18.
  - Error number: [MY-013487](#); Symbol: [ER\\_GRP\\_RPL\\_MESSAGE\\_SERVICE\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: A message sent through the Group Replication message deliver service was not delivered successfully. The server will now leave the group. Try to add the server back to the group and check if the problem persists, or check previous messages in the log for hints of what could be the problem.

---

`ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR` was added in 8.0.18.

- Error number: `MY-013488`; Symbol: `ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG`; SQLSTATE: `HY000`

Message: Invalid `SOURCE_COMPRESSION_ALGORITHMS` '%s' found in repository for channel '%s'. Resetting to 'uncompressed' (no compression).

`ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG` was added in 8.0.18.

- Error number: `MY-013489`; Symbol: `ER_WARN_WRONG_COMPRESSION_LEVEL_LOG`; SQLSTATE: `HY000`

Message: Invalid `SOURCE_ZSTD_COMPRESSION_LEVEL` found in repository for channel '%s'. Resetting to %u.

`ER_WARN_WRONG_COMPRESSION_LEVEL_LOG` was added in 8.0.18.

- Error number: `MY-013490`; Symbol: `ER_PROTOCOL_COMPRESSION_RESET_LOG`; SQLSTATE: `HY000`

Message: Option `--protocol-compression-algorithms` is reset to default value.

`ER_PROTOCOL_COMPRESSION_RESET_LOG` was added in 8.0.18.

- Error number: `MY-013491`; Symbol: `ER_XPLUGIN_COMPRESSION_ERROR`; SQLSTATE: `HY000`

Message: Fatal error while compressing outgoing data - %s

`ER_XPLUGIN_COMPRESSION_ERROR` was added in 8.0.18.

- Error number: `MY-013492`; Symbol: `ER_MYSQLBACKUP_MSG`; SQLSTATE: `HY000`

Message: %s

`ER_MYSQLBACKUP_MSG` was added in 8.0.18.

- Error number: `MY-013493`; Symbol: `ER_WARN_UNKNOWN_KEYRING_AWS_REGION`; SQLSTATE: `HY000`

Message: Unknown keyring\_aws\_region '%s'. Connection to AWS KMS may fail.

`ER_WARN_UNKNOWN_KEYRING_AWS_REGION` was added in 8.0.18.

- Error number: `MY-013494`; Symbol: `ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST`; SQLSTATE: `HY000`

Message: `PRIVILEGE_CHECKS_USER` for replication channel '%s' was set to '%s'@'%s', but this is not an existing user. Correct this before starting replication threads.

`ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST` was added in 8.0.18.

- Error number: `MY-013495`; Symbol: `ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT`; SQLSTATE: `HY000`

Message: Invalid, corrupted `PRIVILEGE_CHECKS_USER` was found in the replication configuration repository for channel '%s'. Use `CHANGE REPLICATION SOURCE TO PRIVILEGE_CHECKS_USER` to correct the configuration.

`ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT` was added in 8.0.18.



- 
- Error number: [MY-013496](#); Symbol: [ER\\_WARN\\_LOG\\_PRIVILEGE\\_CHECKS\\_USER\\_NEEDS\\_RPL\\_APPLIER\\_PRIV](#); SQLSTATE: [HY000](#)  
  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to '%s'@'%s', but this user does not have REPLICATION\_APPLIER privilege. Correct this before starting the replication threads.  
  
[ER\\_WARN\\_LOG\\_PRIVILEGE\\_CHECKS\\_USER\\_NEEDS\\_RPL\\_APPLIER\\_PRIV](#) was added in 8.0.18.
  - Error number: [MY-013497](#); Symbol: [ER\\_FILE\\_PRIVILEGE\\_FOR\\_REPLICATION\\_CHECKS](#); SQLSTATE: [HY000](#)  
  
Message: The PRIVILEGE\_CHECKS\_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog\_format=ROW on master. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE\_CHECKS\_USER.  
  
[ER\\_FILE\\_PRIVILEGE\\_FOR\\_REPLICATION\\_CHECKS](#) was added in 8.0.18, removed after 8.0.30.
  - Error number: [MY-013497](#); Symbol: [ER\\_OBSOLETE\\_FILE\\_PRIVILEGE\\_FOR\\_REPLICATION\\_CHECKS](#); SQLSTATE: [HY000](#)  
  
Message: The PRIVILEGE\_CHECKS\_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog\_format=ROW on source. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE\_CHECKS\_USER.  
  
[ER\\_OBSOLETE\\_FILE\\_PRIVILEGE\\_FOR\\_REPLICATION\\_CHECKS](#) was added in 8.0.31.
  - Error number: [MY-013498](#); Symbol: [ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_STARTING\\_WITH\\_PRIVILEGE\\_CHECKS](#); SQLSTATE: [HY000](#)  
  
Message: Slave SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s, user: '%s'@'%s', roles: %s  
  
[ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_STARTING\\_WITH\\_PRIVILEGE\\_CHECKS](#) was added in 8.0.18, removed after 8.0.32.
  - Error number: [MY-013498](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STARTING\\_WITH\\_PRIVILEGE\\_CHECKS](#); SQLSTATE: [HY000](#)  
  
Message: Replica SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s, user: '%s'@'%s', roles: %s  
  
[ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STARTING\\_WITH\\_PRIVILEGE\\_CHECKS](#) was added in 8.0.33.
  - Error number: [MY-013499](#); Symbol: [ER\\_AUDIT\\_LOG\\_CANNOT\\_GENERATE\\_PASSWORD](#); SQLSTATE: [HY000](#)  
  
Message: Cannot generate password: '%s'  
  
[ER\\_AUDIT\\_LOG\\_CANNOT\\_GENERATE\\_PASSWORD](#) was added in 8.0.18.
  - Error number: [MY-013500](#); Symbol: [ER\\_INIT\\_FAILED\\_TO\\_GENERATE\\_ROOT\\_PASSWORD](#); SQLSTATE: [HY000](#)  
  
Message: Failed to generate a random password for root. Probabably not enough entropy.  
  
[ER\\_INIT\\_FAILED\\_TO\\_GENERATE\\_ROOT\\_PASSWORD](#) was added in 8.0.18.
-

- 
- Error number: [MY-013501](#); Symbol: [ER\\_PLUGIN\\_LOAD\\_OPTIONS\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: Ignoring --plugin-load[\_add] list as the server is running with --initialize(-insecure).

[ER\\_PLUGIN\\_LOAD\\_OPTIONS\\_IGNORED](#) was added in 8.0.18.

- Error number: [MY-013502](#); Symbol: [ER\\_WARN\\_AUTH\\_ID\\_WITH\\_SYSTEM\\_USER\\_PRIV\\_IN\\_MANDATORY\\_ROLES](#); SQLSTATE: [HY000](#)

Message: Cannot set mandatory\_roles: AuthId '%s'@'%s' has '%s' privilege. AuthId(s) set in the mandatory\_roles are ignored.

[ER\\_WARN\\_AUTH\\_ID\\_WITH\\_SYSTEM\\_USER\\_PRIV\\_IN\\_MANDATORY\\_ROLES](#) was added in 8.0.18.

- Error number: [MY-013503](#); Symbol: [ER\\_IB\\_MSG\\_SKIP\\_HIDDEN\\_DIR](#); SQLSTATE: [HY000](#)

Message: Directory '%s' will not be scanned because it is a hidden directory.

[ER\\_IB\\_MSG\\_SKIP\\_HIDDEN\\_DIR](#) was added in 8.0.18.

- Error number: [MY-013504](#); Symbol: [ER\\_WARN\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_MASTER\\_EOF](#); SQLSTATE: [HY000](#)

Message: Server was not able to find a rotate event from master server to initialize relay log recovery for channel '%s'. Skipping relay log recovery for the channel.

[ER\\_WARN\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_MASTER\\_EOF](#) was added in 8.0.19, removed after 8.0.32.

- Error number: [MY-013504](#); Symbol: [ER\\_WARN\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_SOURCE\\_EOF](#); SQLSTATE: [HY000](#)

Message: Server was not able to find a rotate event from source server to initialize relay log recovery for channel '%s'. Skipping relay log recovery for the channel.

[ER\\_WARN\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_SOURCE\\_EOF](#) was added in 8.0.33.

- Error number: [MY-013505](#); Symbol: [ER\\_IB\\_LOB\\_ROLLBACK\\_INDEX\\_LEN](#); SQLSTATE: [HY000](#)

Message: Rolling back LOB for transaction %llu undo number %llu : current index length %llu. (iteration %llu)

[ER\\_IB\\_LOB\\_ROLLBACK\\_INDEX\\_LEN](#) was added in 8.0.19.

- Error number: [MY-013506](#); Symbol: [ER\\_CANT\\_PROCESS\\_EXPRESSION\\_FOR\\_GENERATED\\_COLUMN\\_TO\\_DD](#); SQLSTATE: [HY000](#)

Message: Error in processing (possibly deprecated) expression or function '%s' for generated column %s.%s.%s

[ER\\_CANT\\_PROCESS\\_EXPRESSION\\_FOR\\_GENERATED\\_COLUMN\\_TO\\_DD](#) was added in 8.0.19.

- 
- Error number: [MY-013507](#); Symbol: [ER\\_RPL\\_SLAVE\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#); SQLSTATE: [HY000](#)  
  
Message: The queue event failed for channel '%s' as an invalid event according to REQUIRE\_ROW\_FORMAT was found.  
  
[ER\\_RPL\\_SLAVE\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#) was added in 8.0.19, removed after 8.0.32.
  - Error number: [MY-013507](#); Symbol: [ER\\_RPL\\_REPLICA\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#); SQLSTATE: [HY000](#)  
  
Message: The queue event failed for channel '%s' as an invalid event according to REQUIRE\_ROW\_FORMAT was found.  
  
[ER\\_RPL\\_REPLICA\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#) was added in 8.0.33.
  - Error number: [MY-013508](#); Symbol: [ER\\_RPL\\_SLAVE\\_APPLY\\_LOG\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#); SQLSTATE: [HY000](#)  
  
Message: The application of relay events failed for channel '%s' as an invalid event according to REQUIRE\_ROW\_FORMAT was found.  
  
[ER\\_RPL\\_SLAVE\\_APPLY\\_LOG\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#) was added in 8.0.19, removed after 8.0.30.
  - Error number: [MY-013508](#); Symbol: [ER\\_OBSOLETE\\_REQUIRE\\_ROW\\_FORMAT\\_VIOLATION](#); SQLSTATE: [HY000](#)  
  
Message: The application of relay events failed for channel '%s' as an invalid event according to REQUIRE\_ROW\_FORMAT was found.  
  
[ER\\_OBSOLETE\\_REQUIRE\\_ROW\\_FORMAT\\_VIOLATION](#) was added in 8.0.31.
  - Error number: [MY-013509](#); Symbol: [ER\\_LOG\\_PRIV\\_CHECKS\\_REQUIRE\\_ROW\\_FORMAT\\_NOT\\_SET](#); SQLSTATE: [HY000](#)  
  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' can't be set to `%s`@`%s` unless REQUIRE\_ROW\_FORMAT is also set to %d.  
  
[ER\\_LOG\\_PRIV\\_CHECKS\\_REQUIRE\\_ROW\\_FORMAT\\_NOT\\_SET](#) was added in 8.0.19.
  - Error number: [MY-013510](#); Symbol: [ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#); SQLSTATE: [HY000](#)  
  
Message: An unexpected event sequence was detected by the SQL thread while applying an event.  
  
[ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#) was added in 8.0.19, removed after 8.0.32.
  - Error number: [MY-013510](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#); SQLSTATE: [HY000](#)  
  
Message: An unexpected event sequence was detected by the SQL thread while applying an event.  
  
[ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#) was added in 8.0.33.
  - Error number: [MY-013511](#); Symbol: [ER\\_IB\\_MSG\\_UPGRADE\\_PARTITION\\_FILE](#); SQLSTATE: [HY000](#)

---

Message: Updating partition file name '%s' to '%s' and all other partition files during upgrade

[ER\\_IB\\_MSG\\_UPGRADE\\_PARTITION\\_FILE](#) was added in 8.0.19.

- Error number: [MY-013512](#); Symbol: [ER\\_IB\\_MSG\\_DOWNGRADE\\_PARTITION\\_FILE](#); SQLSTATE: [HY000](#)

Message: Updating partition file name '%s' to '%s' and all other partition files during downgrade

[ER\\_IB\\_MSG\\_DOWNGRADE\\_PARTITION\\_FILE](#) was added in 8.0.19.

- Error number: [MY-013513](#); Symbol: [ER\\_IB\\_MSG\\_UPGRADE\\_PARTITION\\_FILE\\_IMPORT](#); SQLSTATE: [HY000](#)

Message: Updating partition file name '%s' to '%s' for import

[ER\\_IB\\_MSG\\_UPGRADE\\_PARTITION\\_FILE\\_IMPORT](#) was added in 8.0.19.

- Error number: [MY-013514](#); Symbol: [ER\\_IB\\_WARN\\_OPEN\\_PARTITION\\_FILE](#); SQLSTATE: [HY000](#)

Message: Unable to open partition file with new name '%s'. Please check if innodb\_directories is set to include all external file paths

[ER\\_IB\\_WARN\\_OPEN\\_PARTITION\\_FILE](#) was added in 8.0.19.

- Error number: [MY-013515](#); Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CORRECTED](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Partition tablespace %u, name '%s' is corrected to '%s'

[ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CORRECTED](#) was added in 8.0.19.

- Error number: [MY-013516](#); Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CHANGED\\_PATH](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Tablespace %u, name '%s', '%s' is moved to '%s'

[ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CHANGED\\_PATH](#) was added in 8.0.19.

- Error number: [MY-013517](#); Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CHANGED\\_NAME](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Partition tablespace %u, name '%s', '%s' is updated to '%s'

[ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CHANGED\\_NAME](#) was added in 8.0.19.

- Error number: [MY-013518](#); Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_TOO\\_MANY](#); SQLSTATE: [HY000](#)

Message: %s Too many files have been moved, disabling logging of detailed messages

[ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_TOO\\_MANY](#) was added in 8.0.19.

- Error number: [MY-013519](#); Symbol: [ER\\_GR\\_ELECTED\\_PRIMARY\\_GTID\\_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Elected primary member %s: %s

[ER\\_GR\\_ELECTED\\_PRIMARY\\_GTID\\_INFORMATION](#) was added in 8.0.19.

- 
- Error number: [MY-013520](#); Symbol: [ER\\_SCHEMA\\_NAME\\_IN\\_UPPER\\_CASE\\_NOT\\_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Schema name '%s' containing upper case characters is not allowed with lower\_case\_table\_names = 1.

[ER\\_SCHEMA\\_NAME\\_IN\\_UPPER\\_CASE\\_NOT\\_ALLOWED](#) was added in 8.0.19.

- Error number: [MY-013521](#); Symbol: [ER\\_TABLE\\_NAME\\_IN\\_UPPER\\_CASE\\_NOT\\_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Table name '%s.%s' containing upper case characters is not allowed with lower\_case\_table\_names = 1.

[ER\\_TABLE\\_NAME\\_IN\\_UPPER\\_CASE\\_NOT\\_ALLOWED](#) was added in 8.0.19.

- Error number: [MY-013522](#); Symbol: [ER\\_SCHEMA\\_NAME\\_IN\\_UPPER\\_CASE\\_NOT\\_ALLOWED\\_FOR\\_FK](#); SQLSTATE: [HY000](#)

Message: Schema name '%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with lower\_case\_table\_names = 1.

[ER\\_SCHEMA\\_NAME\\_IN\\_UPPER\\_CASE\\_NOT\\_ALLOWED\\_FOR\\_FK](#) was added in 8.0.19.

- Error number: [MY-013523](#); Symbol: [ER\\_TABLE\\_NAME\\_IN\\_UPPER\\_CASE\\_NOT\\_ALLOWED\\_FOR\\_FK](#); SQLSTATE: [HY000](#)

Message: Table name '%s.%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with lower\_case\_table\_names = 1.

[ER\\_TABLE\\_NAME\\_IN\\_UPPER\\_CASE\\_NOT\\_ALLOWED\\_FOR\\_FK](#) was added in 8.0.19.

- Error number: [MY-013524](#); Symbol: [ER\\_IB\\_MSG\\_DICT\\_PARTITION\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Table Partition: %s is not found in InnoDB dictionary

[ER\\_IB\\_MSG\\_DICT\\_PARTITION\\_NOT\\_FOUND](#) was added in 8.0.19.

- Error number: [MY-013525](#); Symbol: [ER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_BLOCKED\\_BY\\_PASSWORD\\_LOCK](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins. Use FLUSH PRIVILEGES or ALTER USER to reset.

[ER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_BLOCKED\\_BY\\_PASSWORD\\_LOCK](#) was added in 8.0.19.

- Error number: [MY-013526](#); Symbol: [ER\\_INNOODB\\_OUT\\_OF\\_RESOURCES](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_INNOODB\\_OUT\\_OF\\_RESOURCES](#) was added in 8.0.19.

- Error number: [MY-013527](#); Symbol: [ER\\_DD\\_UPGRADE\\_FOUND\\_PREPARED\\_XA\\_TRANSACTION](#); SQLSTATE: [HY000](#)

Message: Upgrade cannot proceed due to an existing prepared XA transaction.

[ER\\_DD\\_UPGRADE\\_FOUND\\_PREPARED\\_XA\\_TRANSACTION](#) was added in 8.0.19.

- 
- Error number: [MY-013528](#); Symbol: [ER\\_MIGRATE\\_TABLE\\_TO\\_DD\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Could not allocate memory for key\_info when migrating table %s.%s  
[ER\\_MIGRATE\\_TABLE\\_TO\\_DD\\_OOM](#) was added in 8.0.19.
  - Error number: [MY-013529](#); Symbol: [ER\\_RPL\\_RELAY\\_LOG\\_RECOVERY\\_INFO\\_AFTER\\_CLONE](#); SQLSTATE: [HY000](#)  
Message: Applier metadata information for channel '%s' was found after a clone operation. Relay log recovery will be executed to adjust positions and file information for this new server. Should that automatic procedure fail please adjust the positions through 'CHANGE REPLICATION SOURCE TO'  
[ER\\_RPL\\_RELAY\\_LOG\\_RECOVERY\\_INFO\\_AFTER\\_CLONE](#) was added in 8.0.19.
  - Error number: [MY-013530](#); Symbol: [ER\\_IB\\_MSG\\_57\\_UNDO\\_SPACE\\_DELETE\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to delete 5.7 undo tablespace: %s during upgrade  
[ER\\_IB\\_MSG\\_57\\_UNDO\\_SPACE\\_DELETE\\_FAIL](#) was added in 8.0.19.
  - Error number: [MY-013531](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1285](#); SQLSTATE: [HY000](#)  
Message: Empty doublewrite file: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1285](#) was added in 8.0.20.
  - Error number: [MY-013532](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1286](#); SQLSTATE: [HY000](#)  
Message: Using '%s' for doublewrite  
[ER\\_IB\\_MSG\\_DBLWR\\_1286](#) was added in 8.0.20.
  - Error number: [MY-013533](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1287](#); SQLSTATE: [HY000](#)  
Message: Error reading doublewrite buffer from the system tablespace  
[ER\\_IB\\_MSG\\_DBLWR\\_1287](#) was added in 8.0.20.
  - Error number: [MY-013534](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1288](#); SQLSTATE: [HY000](#)  
Message: Cannot create doublewrite buffer: you must increase your buffer pool size. Cannot continue operation.  
[ER\\_IB\\_MSG\\_DBLWR\\_1288](#) was added in 8.0.20.
  - Error number: [MY-013535](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1290](#); SQLSTATE: [HY000](#)  
Message: The page in the doublewrite file is corrupt. Cannot continue operation. You can try to recover the database with innodb\_force\_recovery=6  
[ER\\_IB\\_MSG\\_DBLWR\\_1290](#) was added in 8.0.20.
  - Error number: [MY-013536](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1291](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1291](#) was added in 8.0.20, removed after 8.0.20.

- 
- Error number: [MY-013536](#); Symbol: [ER\\_IB\\_MSG\\_BAD\\_DBLWR\\_FILE\\_NAME](#); SQLSTATE: [HY000](#)  
Message: The doublewrite filename '%s' is incorrect.  
[ER\\_IB\\_MSG\\_BAD\\_DBLWR\\_FILE\\_NAME](#) was added in 8.0.21.
  - Error number: [MY-013537](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1292](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1292](#) was added in 8.0.20, removed after 8.0.20.
  - Error number: [MY-013538](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1293](#); SQLSTATE: [HY000](#)  
Message: Doublewrite file create failed: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1293](#) was added in 8.0.20.
  - Error number: [MY-013539](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1294](#); SQLSTATE: [HY000](#)  
Message: DBLWRThread: pthread\_setaffinity() failed!  
[ER\\_IB\\_MSG\\_DBLWR\\_1294](#) was added in 8.0.20.
  - Error number: [MY-013540](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1295](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1295](#) was added in 8.0.20.
  - Error number: [MY-013541](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1296](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1296](#) was added in 8.0.20.
  - Error number: [MY-013542](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1297](#); SQLSTATE: [HY000](#)  
Message: Doublewrite file read failed: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1297](#) was added in 8.0.20.
  - Error number: [MY-013543](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1298](#); SQLSTATE: [HY000](#)  
Message: Dump of the data file page:  
[ER\\_IB\\_MSG\\_DBLWR\\_1298](#) was added in 8.0.20.
  - Error number: [MY-013544](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1300](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1300](#) was added in 8.0.20.
  - Error number: [MY-013545](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1301](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1301](#) was added in 8.0.20.

- 
- Error number: [MY-013546](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1304](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1304](#) was added in 8.0.20.
  - Error number: [MY-013547](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1305](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1305](#) was added in 8.0.20.
  - Error number: [MY-013548](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1306](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1306](#) was added in 8.0.20.
  - Error number: [MY-013549](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1307](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1307](#) was added in 8.0.20.
  - Error number: [MY-013550](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1308](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1308](#) was added in 8.0.20.
  - Error number: [MY-013551](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1309](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1309](#) was added in 8.0.20.
  - Error number: [MY-013552](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1310](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1310](#) was added in 8.0.20.
  - Error number: [MY-013553](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1311](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1311](#) was added in 8.0.20.
  - Error number: [MY-013554](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1312](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1312](#) was added in 8.0.20.
  - Error number: [MY-013555](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1313](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1313](#) was added in 8.0.20.



- 
- Error number: [MY-013556](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1314](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1314](#) was added in 8.0.20.
  - Error number: [MY-013557](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1315](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1315](#) was added in 8.0.20.
  - Error number: [MY-013558](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1316](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1316](#) was added in 8.0.20.
  - Error number: [MY-013559](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1317](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1317](#) was added in 8.0.20.
  - Error number: [MY-013560](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1318](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1318](#) was added in 8.0.20.
  - Error number: [MY-013561](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1319](#); SQLSTATE: [HY000](#)  
Message: Doublewrite load file %s size %lu is not a multiple of the configured page size %lu"  
[ER\\_IB\\_MSG\\_DBLWR\\_1319](#) was added in 8.0.20.
  - Error number: [MY-013562](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1320](#); SQLSTATE: [HY000](#)  
Message: Doublewrite file %s truncate failed  
[ER\\_IB\\_MSG\\_DBLWR\\_1320](#) was added in 8.0.20.
  - Error number: [MY-013563](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1321](#); SQLSTATE: [HY000](#)  
Message: Doublewrite file %s failed to writ zeros  
[ER\\_IB\\_MSG\\_DBLWR\\_1321](#) was added in 8.0.20.
  - Error number: [MY-013564](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1322](#); SQLSTATE: [HY000](#)  
Message: Doublewrite create file %s size %lu is not a multiple of the configured page size %lu"  
[ER\\_IB\\_MSG\\_DBLWR\\_1322](#) was added in 8.0.20.
  - Error number: [MY-013565](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1323](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1323](#) was added in 8.0.20.

- 
- Error number: [MY-013566](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1324](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1324](#) was added in 8.0.20.
  - Error number: [MY-013567](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1325](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1325](#) was added in 8.0.20.
  - Error number: [MY-013568](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1326](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1326](#) was added in 8.0.20.
  - Error number: [MY-013569](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1327](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1327](#) was added in 8.0.20.
  - Error number: [MY-013570](#); Symbol: [ER\\_IB\\_MSG\\_GTID\\_FLUSH\\_AT\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: Could not flush all GTIDs during slow shutdown. Will recover GTIDs when server restarts.  
[ER\\_IB\\_MSG\\_GTID\\_FLUSH\\_AT\\_SHUTDOWN](#) was added in 8.0.20.
  - Error number: [MY-013571](#); Symbol: [ER\\_IB\\_MSG\\_57\\_STAT\\_SPACE\\_DELETE\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to delete 5.7 stat tablespace: %s during upgrade  
[ER\\_IB\\_MSG\\_57\\_STAT\\_SPACE\\_DELETE\\_FAIL](#) was added in 8.0.20.
  - Error number: [MY-013572](#); Symbol: [ER\\_NDBINFO\\_UPGRADING\\_SCHEMA](#); SQLSTATE: [HY000](#)  
Message: Installing ndbinfo schema version %s  
[ER\\_NDBINFO\\_UPGRADING\\_SCHEMA](#) was added in 8.0.20.
  - Error number: [MY-013573](#); Symbol: [ER\\_NDBINFO\\_NOT\\_UPGRADING\\_SCHEMA](#); SQLSTATE: [HY000](#)  
Message: Installed ndbinfo schema is current. Not upgrading.  
[ER\\_NDBINFO\\_NOT\\_UPGRADING\\_SCHEMA](#) was added in 8.0.20.
  - Error number: [MY-013574](#); Symbol: [ER\\_NDBINFO\\_UPGRADING\\_SCHEMA\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to upgrade ndbinfo schema.  
[ER\\_NDBINFO\\_UPGRADING\\_SCHEMA\\_FAIL](#) was added in 8.0.20.
  - Error number: [MY-013575](#); Symbol: [ER\\_IB\\_MSG\\_CREATE\\_LOG\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Creating log file %s  
[ER\\_IB\\_MSG\\_CREATE\\_LOG\\_FILE](#) was added in 8.0.20, removed after 8.0.29.

- 
- Error number: [MY-013576](#); Symbol: [ER\\_IB\\_MSG\\_INNODB\\_START\\_INITIALIZE](#); SQLSTATE: [HY000](#)  
Message: InnoDB initialization has started.  
[ER\\_IB\\_MSG\\_INNODB\\_START\\_INITIALIZE](#) was added in 8.0.20.
  - Error number: [MY-013577](#); Symbol: [ER\\_IB\\_MSG\\_INNODB\\_END\\_INITIALIZE](#); SQLSTATE: [HY000](#)  
Message: InnoDB initialization has ended.  
[ER\\_IB\\_MSG\\_INNODB\\_END\\_INITIALIZE](#) was added in 8.0.20.
  - Error number: [MY-013578](#); Symbol: [ER\\_IB\\_MSG\\_PAGE\\_ARCH\\_NO\\_RESET\\_POINTS](#); SQLSTATE: [HY000](#)  
Message: Could not find appropriate reset points.  
[ER\\_IB\\_MSG\\_PAGE\\_ARCH\\_NO\\_RESET\\_POINTS](#) was added in 8.0.20.
  - Error number: [MY-013579](#); Symbol: [ER\\_IB\\_WRN\\_PAGE\\_ARCH\\_FLUSH\\_DATA](#); SQLSTATE: [HY000](#)  
Message: Unable to flush. Page archiving data may be corrupt in case of a crash.  
[ER\\_IB\\_WRN\\_PAGE\\_ARCH\\_FLUSH\\_DATA](#) was added in 8.0.20.
  - Error number: [MY-013580](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_INVALID\\_DOUBLE\\_WRITE\\_BUF](#); SQLSTATE: [HY000](#)  
Message: Page archiver's doublewrite buffer for %ld is not valid.  
[ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_INVALID\\_DOUBLE\\_WRITE\\_BUF](#) was added in 8.0.20.
  - Error number: [MY-013581](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_RECOVERY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Page archiver system's recovery failed.  
[ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_RECOVERY\\_FAILED](#) was added in 8.0.20.
  - Error number: [MY-013582](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_INVALID\\_FORMAT](#); SQLSTATE: [HY000](#)  
Message: Invalid archived file name format. The archived file is supposed to have the format %s + [0-9]\*.  
[ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_INVALID\\_FORMAT](#) was added in 8.0.20.
  - Error number: [MY-013583](#); Symbol: [ER\\_INVALID\\_XPLUGIN\\_SOCKET\\_SAME\\_AS\\_SERVER](#); SQLSTATE: [HY000](#)  
Message: X Plugins UNIX socket must use different file than MySQL server. X Plugin won't be accessible through UNIX socket  
[ER\\_INVALID\\_XPLUGIN\\_SOCKET\\_SAME\\_AS\\_SERVER](#) was added in 8.0.20.
  - Error number: [MY-013584](#); Symbol: [ER\\_INNODB\\_UNABLE\\_TO\\_ACQUIRE\\_DD\\_OBJECT](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_INNODB\\_UNABLE\\_TO\\_ACQUIRE\\_DD\\_OBJECT](#) was added in 8.0.20.

- 
- Error number: [MY-013585](#); Symbol: [ER\\_WARN\\_LOG\\_DEPRECATED\\_PARTITION\\_PREFIX\\_KEY](#); SQLSTATE: [HY000](#)

Message: Column '%s.%s.%s' having prefix key part '%s(%u)' is ignored by the partitioning function. Use of prefixed columns in the PARTITION BY KEY() clause is deprecated and will be removed in a future release.

[ER\\_WARN\\_LOG\\_DEPRECATED\\_PARTITION\\_PREFIX\\_KEY](#) was added in 8.0.21.

- Error number: [MY-013586](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_TOO\\_OFTEN](#); SQLSTATE: [HY000](#)

Message: Undo Truncation is occurring too often. Consider increasing --innodb-max-undo-log-size.

[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_TOO\\_OFTEN](#) was added in 8.0.21.

- Error number: [MY-013587](#); Symbol: [ER\\_GRP\\_RPL\\_IS\\_STARTING](#); SQLSTATE: [HY000](#)

Message: Plugin 'group\_replication' is starting.

[ER\\_GRP\\_RPL\\_IS\\_STARTING](#) was added in 8.0.21.

- Error number: [MY-013588](#); Symbol: [ER\\_IB\\_MSG\\_INVALID\\_LOCATION\\_FOR\\_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Cannot create tablespace %s because the directory is not a valid location. %s

[ER\\_IB\\_MSG\\_INVALID\\_LOCATION\\_FOR\\_TABLESPACE](#) was added in 8.0.21.

- Error number: [MY-013589](#); Symbol: [ER\\_IB\\_MSG\\_INVALID\\_LOCATION\\_WRONG\\_DB](#); SQLSTATE: [HY000](#)

Message: Scanned file '%s' for tablespace %s cannot be opened because it is not in a sub-directory named for the schema.

[ER\\_IB\\_MSG\\_INVALID\\_LOCATION\\_WRONG\\_DB](#) was added in 8.0.21.

- Error number: [MY-013590](#); Symbol: [ER\\_IB\\_MSG\\_CANNOT\\_FIND\\_DD\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)

Message: Cannot find undo tablespace %s with filename '%s' as indicated by the Data Dictionary. Did you move or delete this tablespace? Any undo logs in it cannot be used.

[ER\\_IB\\_MSG\\_CANNOT\\_FIND\\_DD\\_UNDO\\_SPACE](#) was added in 8.0.21.

- Error number: [MY-013591](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_FORMAT](#); SQLSTATE: [HY000](#)

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port)

[ER\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_FORMAT](#) was added in 8.0.21.

- Error number: [MY-013592](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_INVALID](#); SQLSTATE: [HY000](#)

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

[ER\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_INVALID](#) was added in 8.0.21.

- 
- Error number: [MY-013593](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_INVALID\\_DONOR\\_ENDPOINT](#); SQLSTATE: [HY000](#)  
  
Message: Received invalid recovery endpoints configuration from donor. This member is not a valid donor for recovery, so it will be skipped.  
  
[ER\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_INVALID\\_DONOR\\_ENDPOINT](#) was added in 8.0.21.
  - Error number: [MY-013594](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_INTERFACES\\_IPS](#); SQLSTATE: [HY000](#)  
  
Message: Failed to retrieve IP addresses from enabled host network interfaces.  
  
[ER\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_INTERFACES\\_IPS](#) was added in 8.0.21.
  - Error number: [MY-013595](#); Symbol: [ER\\_WARN\\_TLS\\_CHANNEL\\_INITIALIZATION\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Failed to initialize TLS for channel: %s. See below for the description of exact issue.  
  
[ER\\_WARN\\_TLS\\_CHANNEL\\_INITIALIZATION\\_ERROR](#) was added in 8.0.21.
  - Error number: [MY-013596](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_VALIDATE\\_ADDRESS](#); SQLSTATE: [HY000](#)  
  
Message: Validation of value '%s' set to `Mysqlx\_bind\_address` failed: %s. Skipping this value.  
  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_VALIDATE\\_ADDRESS](#) was added in 8.0.21.
  - Error number: [MY-013597](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_BIND\\_INTERFACE\\_ADDRESS](#); SQLSTATE: [HY000](#)  
  
Message: Value '%s' set to `Mysqlx\_bind\_address`, X Plugin can't bind to it. Skipping this value.  
  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_BIND\\_INTERFACE\\_ADDRESS](#) was added in 8.0.21.
  - Error number: [MY-013598](#); Symbol: [ER\\_IB\\_ERR\\_RECOVERY\\_REDO\\_DISABLED](#); SQLSTATE: [HY000](#)  
  
Message: Server was killed when InnoDB redo logging was disabled. Data files could be corrupt. You can try to restart the database with innodb\_force\_recovery=6  
  
[ER\\_IB\\_ERR\\_RECOVERY\\_REDO\\_DISABLED](#) was added in 8.0.21.
  - Error number: [MY-013599](#); Symbol: [ER\\_IB\\_WRN\\_FAST\\_SHUTDOWN\\_REDO\\_DISABLED](#); SQLSTATE: [HY000](#)  
  
Message: InnoDB cannot do cold shutdown 'innodb\_fast\_shutdown = 2' and is forcing 'innodb\_fast\_shutdown = 1' as redo logging is disabled. InnoDB would flush all dirty pages to ensure physical data consistency.  
  
[ER\\_IB\\_WRN\\_FAST\\_SHUTDOWN\\_REDO\\_DISABLED](#) was added in 8.0.21.
  - Error number: [MY-013600](#); Symbol: [ER\\_IB\\_WRN\\_REDO\\_DISABLED](#); SQLSTATE: [HY000](#)  
  
Message: InnoDB redo logging is disabled. All data could be lost in case of a server crash.  
  
[ER\\_IB\\_WRN\\_REDO\\_DISABLED](#) was added in 8.0.21.
  - Error number: [MY-013601](#); Symbol: [ER\\_IB\\_WRN\\_REDO\\_ENABLED](#); SQLSTATE: [HY000](#)

---

Message: InnoDB redo logging is enabled. Data is now safe and can be recovered in case of a server crash.

`ER_IB_WRN_REDO_ENABLED` was added in 8.0.21.

- Error number: `MY-013602`; Symbol: `ER_TLS_CONFIGURED_FOR_CHANNEL`; SQLSTATE: `HY000`

Message: Channel %s configured to support TLS. Encrypted connections are now supported for this channel.

`ER_TLS_CONFIGURED_FOR_CHANNEL` was added in 8.0.21.

- Error number: `MY-013603`; Symbol: `ER_TLS_CONFIGURATION_REUSED`; SQLSTATE: `HY000`

Message: No TLS configuration was given for channel %s; re-using TLS configuration of channel %s.

`ER_TLS_CONFIGURATION_REUSED` was added in 8.0.21.

- Error number: `MY-013604`; Symbol: `ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED`; SQLSTATE: `HY000`

Message: Skipping InnoDB tablespace path validation. Manually moved tablespace files will not be detected!

`ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED` was added in 8.0.21.

- Error number: `MY-013605`; Symbol: `ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES`; SQLSTATE: `HY000`

Message: Upgrade failed because database contains discarded tablespaces.

`ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES` was added in 8.0.21.

- Error number: `MY-013606`; Symbol: `ER_USERNAME_TRUNCATED`; SQLSTATE: `HY000`

Message: The user name '%s' exceeds the maximum number of allowed characters %d and is truncated.

`ER_USERNAME_TRUNCATED` was added in 8.0.21.

- Error number: `MY-013607`; Symbol: `ER_HOSTNAME_TRUNCATED`; SQLSTATE: `HY000`

Message: The host name '%s' exceeds the maximum number of allowed characters %d and is truncated.

`ER_HOSTNAME_TRUNCATED` was added in 8.0.21.

- Error number: `MY-013608`; Symbol: `ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED`; SQLSTATE: `HY000`

Message: Rollback of non-prepared transactions not completed, due to fast shutdown

`ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED` was added in 8.0.21.

- Error number: `MY-013609`; Symbol: `ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME`; SQLSTATE: `HY000`

Message: Found an entry in the 'role\_edges' table with empty authorization ID; Skipped

---

`ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME` was added in 8.0.21.

- Error number: `MY-013610`; Symbol: `ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION_ID`; SQLSTATE: `HY000`

Message: Found an entry in the 'role\_edges' table with unknown authorization ID '%s'; Skipped

`ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION_ID` was added in 8.0.21.

- Error number: `MY-013611`; Symbol: `ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME`; SQLSTATE: `HY000`

Message: Found an entry in the 'default\_roles' table with empty authorization ID; Skipped

`ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME` was added in 8.0.21.

- Error number: `MY-013612`; Symbol: `ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION_ID`; SQLSTATE: `HY000`

Message: Found an entry in the 'default\_roles' table with unknown authorization ID '%s'; Skipped

`ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION_ID` was added in 8.0.21.

- Error number: `MY-013613`; Symbol: `ER_IB_ERR_DDL_LOG_INSERT_FAILURE`; SQLSTATE: `HY000`

Message: Couldn't insert entry in ddl log for ddl.

`ER_IB_ERR_DDL_LOG_INSERT_FAILURE` was added in 8.0.21.

- Error number: `MY-013614`; Symbol: `ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION`; SQLSTATE: `HY000`

Message: %s

`ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION` was added in 8.0.21.

- Error number: `MY-013615`; Symbol: `ER_IB_RELOCK_LATCH_ORDER_VIOLATION`; SQLSTATE: `HY000`

Message: %s

`ER_IB_RELOCK_LATCH_ORDER_VIOLATION` was added in 8.0.21.

- Error number: `MY-013621`; Symbol: `ER_IB_MSG_1357`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1357` was added in 8.0.21.

- Error number: `MY-013622`; Symbol: `ER_IB_MSG_1358`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1358` was added in 8.0.21.

- Error number: `MY-013623`; Symbol: `ER_IB_MSG_1359`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1359` was added in 8.0.21.

- 
- Error number: `MY-013624`; Symbol: `ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE`; SQLSTATE: `HY000`  
  
Message: %s  
  
`ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE` was added in 8.0.21.
  - Error number: `MY-013625`; Symbol: `ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE_POOL`; SQLSTATE: `HY000`  
  
Message: %s  
  
`ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE_POOL` was added in 8.0.21.
  - Error number: `MY-013626`; Symbol: `ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY`; SQLSTATE: `HY000`  
  
Message: %s  
  
`ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY` was added in 8.0.21.
  - Error number: `MY-013627`; Symbol: `ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR`; SQLSTATE: `HY000`  
  
Message: %s  
  
`ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR` was added in 8.0.21.
  - Error number: `MY-013628`; Symbol: `ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST`; SQLSTATE: `HY000`  
  
Message: %s  
  
`ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST` was added in 8.0.21.
  - Error number: `MY-013629`; Symbol: `ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY`; SQLSTATE: `HY000`  
  
Message: %s  
  
`ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY` was added in 8.0.21.
  - Error number: `MY-013630`; Symbol: `ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLON`; SQLSTATE: `HY000`  
  
Message: %s  
  
`ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLON` was added in 8.0.21.
  - Error number: `MY-013631`; Symbol: `ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATADIR`; SQLSTATE: `HY000`  
  
Message: %s  
  
`ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATADIR` was added in 8.0.21.
  - Error number: `MY-013632`; Symbol: `ER_IB_ERR_SCHED_SETAFFINITY_FAILED`; SQLSTATE: `HY000`



---

Message: %s

[ER\\_IB\\_ERR\\_SCHED\\_SETAFFINITY\\_FAILED](#) was added in 8.0.21.

- Error number: [MY-013633](#); Symbol: [ER\\_IB\\_ERR\\_UNKNOWN\\_PAGE\\_FETCH\\_MODE](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_ERR\\_UNKNOWN\\_PAGE\\_FETCH\\_MODE](#) was added in 8.0.21.

- Error number: [MY-013634](#); Symbol: [ER\\_IB\\_ERR\\_LOG\\_PARSING\\_BUFFER\\_OVERFLOW](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_ERR\\_LOG\\_PARSING\\_BUFFER\\_OVERFLOW](#) was added in 8.0.21.

- Error number: [MY-013635](#); Symbol: [ER\\_IB\\_ERR\\_NOT\\_ENOUGH\\_MEMORY\\_FOR\\_PARSE\\_BUFFER](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_ERR\\_NOT\\_ENOUGH\\_MEMORY\\_FOR\\_PARSE\\_BUFFER](#) was added in 8.0.21.

- Error number: [MY-013636](#); Symbol: [ER\\_IB\\_MSG\\_1372](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1372](#) was added in 8.0.21.

- Error number: [MY-013637](#); Symbol: [ER\\_IB\\_MSG\\_1373](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1373](#) was added in 8.0.21.

- Error number: [MY-013638](#); Symbol: [ER\\_IB\\_MSG\\_1374](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1374](#) was added in 8.0.21.

- Error number: [MY-013639](#); Symbol: [ER\\_IB\\_MSG\\_1375](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1375](#) was added in 8.0.21.

- Error number: [MY-013640](#); Symbol: [ER\\_IB\\_ERR\\_ZLIB\\_UNCOMPRESS\\_FAILED](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_ERR\\_ZLIB\\_UNCOMPRESS\\_FAILED](#) was added in 8.0.21.

- Error number: [MY-013641](#); Symbol: [ER\\_IB\\_ERR\\_ZLIB\\_BUF\\_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_ERR\\_ZLIB\\_BUF\\_ERROR](#) was added in 8.0.21.

- 
- Error number: [MY-013642](#); Symbol: [ER\\_IB\\_ERR\\_ZLIB\\_MEM\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_ERR\\_ZLIB\\_MEM\\_ERROR](#) was added in 8.0.21.
  - Error number: [MY-013643](#); Symbol: [ER\\_IB\\_ERR\\_ZLIB\\_DATA\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_ERR\\_ZLIB\\_DATA\\_ERROR](#) was added in 8.0.21.
  - Error number: [MY-013644](#); Symbol: [ER\\_IB\\_ERR\\_ZLIB\\_UNKNOWN\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_ERR\\_ZLIB\\_UNKNOWN\\_ERROR](#) was added in 8.0.21.
  - Error number: [MY-013645](#); Symbol: [ER\\_IB\\_MSG\\_1381](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1381](#) was added in 8.0.21.
  - Error number: [MY-013646](#); Symbol: [ER\\_IB\\_ERR\\_INDEX\\_RECORDS\\_WRONG\\_ORDER](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_ERR\\_INDEX\\_RECORDS\\_WRONG\\_ORDER](#) was added in 8.0.21.
  - Error number: [MY-013647](#); Symbol: [ER\\_IB\\_ERR\\_INDEX\\_DUPLICATE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_ERR\\_INDEX\\_DUPLICATE\\_KEY](#) was added in 8.0.21.
  - Error number: [MY-013648](#); Symbol: [ER\\_IB\\_ERR\\_FOUND\\_N\\_DUPLICATE\\_KEYS](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_ERR\\_FOUND\\_N\\_DUPLICATE\\_KEYS](#) was added in 8.0.21.
  - Error number: [MY-013649](#); Symbol: [ER\\_IB\\_ERR\\_FOUND\\_N\\_RECORDS\\_WRONG\\_ORDER](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_ERR\\_FOUND\\_N\\_RECORDS\\_WRONG\\_ORDER](#) was added in 8.0.21.
  - Error number: [MY-013650](#); Symbol: [ER\\_IB\\_ERR\\_PARALLEL\\_READ\\_OOM](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_ERR\\_PARALLEL\\_READ\\_OOM](#) was added in 8.0.21.
  - Error number: [MY-013651](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_MARKED\\_ACTIVE](#); SQLSTATE: [HY000](#)  
Message: The state of undo tablespace %s is set to active implicitly.

---

`ER_IB_MSG_UNDO_MARKED_ACTIVE` was added in 8.0.21.

- Error number: `MY-013652`; Symbol: `ER_IB_MSG_UNDO_ALTERED_ACTIVE`; SQLSTATE: `HY000`

Message: The state of undo tablespace %s is set to 'active' by ALTER TABLESPACE.

`ER_IB_MSG_UNDO_ALTERED_ACTIVE` was added in 8.0.21.

- Error number: `MY-013653`; Symbol: `ER_IB_MSG_UNDO_ALTERED_INACTIVE`; SQLSTATE: `HY000`

Message: The state of undo tablespace %s is set to 'inactive' by ALTER TABLESPACE.

`ER_IB_MSG_UNDO_ALTERED_INACTIVE` was added in 8.0.21.

- Error number: `MY-013654`; Symbol: `ER_IB_MSG_UNDO_MARKED_EMPTY`; SQLSTATE: `HY000`

Message: The state of undo tablespace %s is set to 'empty'.

`ER_IB_MSG_UNDO_MARKED_EMPTY` was added in 8.0.21.

- Error number: `MY-013655`; Symbol: `ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE`; SQLSTATE: `HY000`

Message: Delaying truncate of undo tablespace %s due to clone activity.

`ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE` was added in 8.0.21.

- Error number: `MY-013656`; Symbol: `ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL`; SQLSTATE: `HY000`

Message: Delaying truncate of undo tablespace %s due to a metadata lock.

`ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL` was added in 8.0.21.

- Error number: `MY-013657`; Symbol: `ER_IB_MSG_UNDO_INJECT_CRASH`; SQLSTATE: `HY000`

Message: Injected debug crash point: %s

`ER_IB_MSG_UNDO_INJECT_CRASH` was added in 8.0.21, removed after 8.0.21.

- Error number: `MY-013657`; Symbol: `ER_IB_MSG_INJECT_CRASH`; SQLSTATE: `HY000`

Message: Injected debug crash point: %s

`ER_IB_MSG_INJECT_CRASH` was added in 8.0.22.

- Error number: `MY-013658`; Symbol: `ER_IB_MSG_UNDO_INJECT_FAILURE`; SQLSTATE: `HY000`

Message: Injected debug failure point: %s

`ER_IB_MSG_UNDO_INJECT_FAILURE` was added in 8.0.21, removed after 8.0.21.

- Error number: `MY-013658`; Symbol: `ER_IB_MSG_INJECT_FAILURE`; SQLSTATE: `HY000`

Message: Injected debug failure point: %s

`ER_IB_MSG_INJECT_FAILURE` was added in 8.0.22.

- 
- Error number: [MY-013659](#); Symbol: [ER\\_GRP\\_RPL\\_TIMEOUT\\_RECEIVED\\_VC\\_LEAVE\\_ON\\_REJOIN](#); SQLSTATE: [HY000](#)

Message: Timeout while waiting for a view change event during the leave step before a auto-rejoin attempt.

[ER\\_GRP\\_RPL\\_TIMEOUT\\_RECEIVED\\_VC\\_LEAVE\\_ON\\_REJOIN](#) was added in 8.0.22.

- Error number: [MY-013660](#); Symbol: [ER\\_RPL\\_ASYNC\\_RECONNECT\\_FAIL\\_NO\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Failed to automatically re-connect to a different source, for channel '%s', because %s. To fix this %s.

[ER\\_RPL\\_ASYNC\\_RECONNECT\\_FAIL\\_NO\\_SOURCE](#) was added in 8.0.22.

- Error number: [MY-013661](#); Symbol: [ER\\_UDF\\_REGISTER\\_SERVICE\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not execute the installation of UDF functions. Check for other errors in the log

[ER\\_UDF\\_REGISTER\\_SERVICE\\_ERROR](#) was added in 8.0.22.

- Error number: [MY-013662](#); Symbol: [ER\\_UDF\\_REGISTER\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not execute the installation of UDF function: %s. Check if the function is already present, if so, try to remove it.

[ER\\_UDF\\_REGISTER\\_ERROR](#) was added in 8.0.22.

- Error number: [MY-013663](#); Symbol: [ER\\_UDF\\_UNREGISTER\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not uninstall UDF functions. Try to remove them manually if present.

[ER\\_UDF\\_UNREGISTER\\_ERROR](#) was added in 8.0.22.

- Error number: [MY-013664](#); Symbol: [ER\\_EMPTY\\_PRIVILEGE\\_NAME\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: An empty or illegal privilege identifier was ignored when global privileges were read from disk.

[ER\\_EMPTY\\_PRIVILEGE\\_NAME\\_IGNORED](#) was added in 8.0.22.

- Error number: [MY-013665](#); Symbol: [ER\\_IB\\_MSG\\_INCORRECT\\_SIZE](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_INCORRECT\\_SIZE](#) was added in 8.0.22.

- Error number: [MY-013666](#); Symbol: [ER\\_TMPDIR\\_PATH\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)

Message: A tmpdir temporary path "%s" is too long (> %zu) for this OS. This would not leave enough space for a temporary filename of length %zu within it.

[ER\\_TMPDIR\\_PATH\\_TOO\\_LONG](#) was added in 8.0.22.

- 
- Error number: [MY-013667](#); Symbol: [ER\\_ERROR\\_LOG\\_DESTINATION\\_NOT\\_A\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: Error-log destination "%s" is not a file. Can not restore error log messages from previous run.  
  
[ER\\_ERROR\\_LOG\\_DESTINATION\\_NOT\\_A\\_FILE](#) was added in 8.0.22.
  - Error number: [MY-013668](#); Symbol: [ER\\_NO\\_ERROR\\_LOG\\_PARSER\\_CONFIGURED](#); SQLSTATE: [HY000](#)  
  
Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance\_schema.error\_log.  
  
[ER\\_NO\\_ERROR\\_LOG\\_PARSER\\_CONFIGURED](#) was added in 8.0.22.
  - Error number: [MY-013669](#); Symbol: [ER\\_UPGRADE\\_NONEXISTENT\\_SCHEMA](#); SQLSTATE: [HY000](#)  
  
Message: The schema "%s" referenced by %s "%s" does not exist. Please clean up any orphan %s before upgrading.  
  
[ER\\_UPGRADE\\_NONEXISTENT\\_SCHEMA](#) was added in 8.0.22.
  - Error number: [MY-013670](#); Symbol: [ER\\_IB\\_MSG\\_CREATED\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
  
Message: Created undo tablespace '%s'.  
  
[ER\\_IB\\_MSG\\_CREATED\\_UNDO\\_SPACE](#) was added in 8.0.22.
  - Error number: [MY-013671](#); Symbol: [ER\\_IB\\_MSG\\_DROPPED\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
  
Message: Dropped undo tablespace '%s'.  
  
[ER\\_IB\\_MSG\\_DROPPED\\_UNDO\\_SPACE](#) was added in 8.0.22.
  - Error number: [MY-013672](#); Symbol: [ER\\_IB\\_MSG\\_MASTER\\_KEY\\_ROTATED](#); SQLSTATE: [HY000](#)  
  
Message: The InnoDB Encryption Master Key has been rotated in %d tablespaces.  
  
[ER\\_IB\\_MSG\\_MASTER\\_KEY\\_ROTATED](#) was added in 8.0.22.
  - Error number: [MY-013673](#); Symbol: [ER\\_IB\\_DBLWR\\_DECOMPRESS\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Failed to decompress a DBLWR page (err=%d). The original size is %d. Reporting the dblwr page as corrupted.  
  
[ER\\_IB\\_DBLWR\\_DECOMPRESS\\_FAILED](#) was added in 8.0.23.
  - Error number: [MY-013674](#); Symbol: [ER\\_IB\\_DBLWR\\_DECRYPT\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Decrypting a page in doublewrite file failed: %s.  
  
[ER\\_IB\\_DBLWR\\_DECRYPT\\_FAILED](#) was added in 8.0.23.
  - Error number: [MY-013675](#); Symbol: [ER\\_IB\\_DBLWR\\_KEY\\_MISSING](#); SQLSTATE: [HY000](#)  
  
Message: Encryption key missing: %s.  
  
[ER\\_IB\\_DBLWR\\_KEY\\_MISSING](#) was added in 8.0.23.
  - Error number: [MY-013676](#); Symbol: [ER\\_INNODB\\_IO\\_WRITE\\_ERROR\\_RETRYING](#); SQLSTATE: [HY000](#)

---

Message: I/O error while writing to file: %s. Retrying ...

[ER\\_INNODB\\_IO\\_WRITE\\_ERROR\\_RETRYING](#) was added in 8.0.23.

- Error number: [MY-013677](#); Symbol: [ER\\_INNODB\\_IO\\_WRITE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to write data to file: %s

[ER\\_INNODB\\_IO\\_WRITE\\_FAILED](#) was added in 8.0.23.

- Error number: [MY-013678](#); Symbol: [ER\\_LOG\\_COMPONENT\\_CANNOT\\_INIT](#); SQLSTATE: [HY000](#)

Message: Log component %s failed to initialize.

[ER\\_LOG\\_COMPONENT\\_CANNOT\\_INIT](#) was added in 8.0.23.

- Error number: [MY-013679](#); Symbol: [ER\\_RPL\\_ASYNC\\_CHANNEL\\_CANT\\_CONNECT](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread failed to connect to the source (host:%s port:%u network\_namespace:%s) for channel '%s', thence it will try to connect to another source.

[ER\\_RPL\\_ASYNC\\_CHANNEL\\_CANT\\_CONNECT](#) was added in 8.0.23.

- Error number: [MY-013680](#); Symbol: [ER\\_RPL\\_ASYNC\\_SENDER\\_ADDED](#); SQLSTATE: [HY000](#)

Message: The source (host:%s port:%u network\_namespace:%s) for channel '%s' has joined the group (group\_name: %s), and so added its entry into replication\_asynchronous\_connection\_failover table.

[ER\\_RPL\\_ASYNC\\_SENDER\\_ADDED](#) was added in 8.0.23.

- Error number: [MY-013681](#); Symbol: [ER\\_RPL\\_ASYNC\\_SENDER\\_REMOVED](#); SQLSTATE: [HY000](#)

Message: The source (host:%s port:%u network\_namespace:%s) for channel '%s' has left the group (group\_name: %s), and so removed its entry from replication\_asynchronous\_connection\_failover table.

[ER\\_RPL\\_ASYNC\\_SENDER\\_REMOVED](#) was added in 8.0.23.

- Error number: [MY-013682](#); Symbol: [ER\\_RPL\\_ASYNC\\_CHANNEL\\_STOPPED\\_QUORUM\\_LOST](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread detected that the source (host:%s port:%u network\_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

[ER\\_RPL\\_ASYNC\\_CHANNEL\\_STOPPED\\_QUORUM\\_LOST](#) was added in 8.0.23.

- Error number: [MY-013683](#); Symbol: [ER\\_RPL\\_ASYNC\\_CHANNEL\\_CANT\\_CONNECT\\_NO\\_QUORUM](#); SQLSTATE: [HY000](#)

Message: The IO thread detected that the source (host:%s port:%u network\_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

[ER\\_RPL\\_ASYNC\\_CHANNEL\\_CANT\\_CONNECT\\_NO\\_QUORUM](#) was added in 8.0.23.

- Error number: [MY-013684](#); Symbol: [ER\\_RPL\\_ASYNC\\_EXECUTING\\_QUERY](#); SQLSTATE: [HY000](#)

Message: %s on the source (host:%s port:%u network\_namespace:%s) for channel '%s'.

[ER\\_RPL\\_ASYNC\\_EXECUTING\\_QUERY](#) was added in 8.0.23.

- 
- Error number: [MY-013685](#); Symbol: [ER\\_RPL\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_EXITING](#); SQLSTATE: [HY000](#)

Message: Replica Monitor IO thread exiting.

[ER\\_RPL\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_EXITING](#) was added in 8.0.23.

- Error number: [MY-013686](#); Symbol: [ER\\_RPL\\_ASYNC\\_MANAGED\\_NAME\\_REMOVED](#); SQLSTATE: [HY000](#)

Message: The group (group\_name: %s) for the channel '%s' has been removed, and so removed its entry from replication\_asynchronous\_connection\_failover\_managed and all the group members from replication\_asynchronous\_connection\_failover table.

[ER\\_RPL\\_ASYNC\\_MANAGED\\_NAME\\_REMOVED](#) was added in 8.0.23.

- Error number: [MY-013687](#); Symbol: [ER\\_RPL\\_ASYNC\\_MANAGED\\_NAME\\_ADDED](#); SQLSTATE: [HY000](#)

Message: The group (group\_name: %s) for the channel '%s' has been added, and so added its entry in replication\_asynchronous\_connection\_failover\_managed and source to replication\_asynchronous\_connection\_failover table.

[ER\\_RPL\\_ASYNC\\_MANAGED\\_NAME\\_ADDED](#) was added in 8.0.23.

- Error number: [MY-013688](#); Symbol: [ER\\_RPL\\_ASYNC\\_READ\\_FAILOVER\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Error reading failover sources for channel '%s' from replication\_asynchronous\_connection\_failover table.

[ER\\_RPL\\_ASYNC\\_READ\\_FAILOVER\\_TABLE](#) was added in 8.0.23.

- Error number: [MY-013689](#); Symbol: [ER\\_RPL\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_RECONNECT\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Error %s the channel '%s', the operation will be automatically retried.

[ER\\_RPL\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_RECONNECT\\_CHANNEL](#) was added in 8.0.23.

- Error number: [MY-013690](#); Symbol: [ER\\_SLAVE\\_ANONYMOUS\\_TO\\_GTID\\_IS\\_LOCAL\\_OR\\_UUID\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#); SQLSTATE: [HY000](#)

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'`, which is invalid when `GTID_MODE <> ON`. If you intend to use `GTID_MODE = ON` everywhere, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = OFF` and use the procedure for enabling GTIDs online (see the documentation). If you intend to use GTIDs on this replica and cannot enable GTIDs on the source, enable `GTID_MODE = ON` and leave `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`. If you intend to not use GTIDs at all in the replication topology, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS=OFF` and leave `GTID_MODE = '%s'`.

[ER\\_SLAVE\\_ANONYMOUS\\_TO\\_GTID\\_IS\\_LOCAL\\_OR\\_UUID\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#) was added in 8.0.23, removed after 8.0.32.

- 
- Error number: [MY-013690](#); Symbol: [ER\\_REPLICA\\_ANON\\_TO\\_GTID\\_IS\\_LOCAL\\_OR\\_UUID\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#); SQLSTATE: [HY000](#)  
  
Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'`, which is invalid when `GTID_MODE <> ON`. If you intend to use `GTID_MODE = ON` everywhere, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = OFF` and use the procedure for enabling GTIDs online (see the documentation). If you intend to use GTIDs on this replica and cannot enable GTIDs on the source, enable `GTID_MODE = ON` and leave `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`. If you intend to not use GTIDs at all in the replication topology, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS=OFF` and leave `GTID_MODE = '%s'`.  
  
[ER\\_REPLICA\\_ANON\\_TO\\_GTID\\_IS\\_LOCAL\\_OR\\_UUID\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#) was added in 8.0.33.
  - Error number: [MY-013691](#); Symbol: [ER\\_REPLICA\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_GROUP\\_NAME](#); SQLSTATE: [HY000](#)  
  
Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'` which is equal to `group_replication_group_name`. To fix this issue, either change the `group_replication_group_name` or use a different value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS`.  
  
[ER\\_REPLICA\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_GROUP\\_NAME](#) was added in 8.0.23.
  - Error number: [MY-013692](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_NAME\\_IS\\_SAME\\_AS\\_ANONYMOUS\\_TO\\_GTID\\_UUID](#); SQLSTATE: [HY000](#)  
  
Message: The `group_replication_group_name` '%s' is the same as the UUID value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS` in a server channel  
  
[ER\\_GRP\\_RPL\\_GRP\\_NAME\\_IS\\_SAME\\_AS\\_ANONYMOUS\\_TO\\_GTID\\_UUID](#) was added in 8.0.23.
  - Error number: [MY-013693](#); Symbol: [ER\\_WARN\\_GTID\\_THRESHOLD\\_BREACH](#); SQLSTATE: [HY000](#)  
  
Message: The integer component of the GTID number is high. Suggest restarting the server with a new `server_uuid` to prevent it from reaching the maximum number  $2^{63}-1$ , which will make it impossible to write the binary log and invoke the behavior specified by `binlog_error_action`.  
  
[ER\\_WARN\\_GTID\\_THRESHOLD\\_BREACH](#) was added in 8.0.23.
  - Error number: [MY-013694](#); Symbol: [ER\\_HEALTH\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_HEALTH\\_INFO](#) was added in 8.0.23.
  - Error number: [MY-013695](#); Symbol: [ER\\_HEALTH\\_WARNING](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_HEALTH\\_WARNING](#) was added in 8.0.23.
  - Error number: [MY-013696](#); Symbol: [ER\\_HEALTH\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_HEALTH\\_ERROR](#) was added in 8.0.23.



- 
- Error number: [MY-013697](#); Symbol: [ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_1](#); SQLSTATE: [HY000](#)  
  
Message: %s: Warning Level 1 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB  
  
[ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_1](#) was added in 8.0.23.
  - Error number: [MY-013698](#); Symbol: [ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_2](#); SQLSTATE: [HY000](#)  
  
Message: %s: Warning Level 2 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB  
  
[ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_2](#) was added in 8.0.23.
  - Error number: [MY-013699](#); Symbol: [ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_3](#); SQLSTATE: [HY000](#)  
  
Message: %s: Warning Level 3 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB  
  
[ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_3](#) was added in 8.0.23.
  - Error number: [MY-013700](#); Symbol: [ER\\_IB\\_INNODB\\_TBSP\\_OUT\\_OF\\_SPACE](#); SQLSTATE: [HY000](#)  
  
Message: InnoDB: Size of tablespace %s is more than the maximum size allowed.  
  
[ER\\_IB\\_INNODB\\_TBSP\\_OUT\\_OF\\_SPACE](#) was added in 8.0.23.
  - Error number: [MY-013701](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_CHANNEL\\_STILL\\_RUNNING](#); SQLSTATE: [HY000](#)  
  
Message: The group\_replication\_applier channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.  
  
[ER\\_GRP\\_RPL\\_APPLIER\\_CHANNEL\\_STILL\\_RUNNING](#) was added in 8.0.23.
  - Error number: [MY-013702](#); Symbol: [ER\\_RPL\\_ASYNC\\_RECONNECT\\_GTID\\_MODE\\_OFF\\_CHANNEL](#); SQLSTATE: [HY000](#)  
  
Message: Detected misconfiguration: replication channel '%s' was configured with `SOURCE_CONNECTION_AUTO_FAILOVER = 1`, but the server was started with a value other than `--gtid-mode = ON`. Either reconfigure replication using `CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 0 FOR CHANNEL '%s'`, or change `GTID_MODE` to value `ON`, before starting the replica receiver thread.  
  
[ER\\_RPL\\_ASYNC\\_RECONNECT\\_GTID\\_MODE\\_OFF\\_CHANNEL](#) was added in 8.0.23.
  - Error number: [MY-013703](#); Symbol: [ER\\_FIREWALL\\_SERVICES\\_NOT\\_ACQUIRED](#); SQLSTATE: [HY000](#)  
  
Message: Could not acquire required component services.  
  
[ER\\_FIREWALL\\_SERVICES\\_NOT\\_ACQUIRED](#) was added in 8.0.23.

- 
- Error number: [MY-013704](#); Symbol: [ER\\_FIREWALL\\_UDF\\_REGISTER\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Automatic registration of function(s) failed.  
[ER\\_FIREWALL\\_UDF\\_REGISTER\\_FAILED](#) was added in 8.0.23.
  - Error number: [MY-013705](#); Symbol: [ER\\_FIREWALL\\_PFS\\_TABLE\\_REGISTER\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Automatic registration of Performance schema table(s) failed.  
[ER\\_FIREWALL\\_PFS\\_TABLE\\_REGISTER\\_FAILED](#) was added in 8.0.23.
  - Error number: [MY-013706](#); Symbol: [ER\\_IB\\_MSG\\_STATS\\_SAMPLING\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_STATS\\_SAMPLING\\_TOO\\_LARGE](#) was added in 8.0.23.
  - Error number: [MY-013707](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILE\\_PRUNE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to auto-prune file '%s', Error (%d): %s  
[ER\\_AUDIT\\_LOG\\_FILE\\_PRUNE\\_FAILED](#) was added in 8.0.24.
  - Error number: [MY-013708](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILE\\_AUTO\\_PRUNED](#); SQLSTATE: [HY000](#)  
Message: File '%s' auto-pruned  
[ER\\_AUDIT\\_LOG\\_FILE\\_AUTO\\_PRUNED](#) was added in 8.0.24.
  - Error number: [MY-013709](#); Symbol: [ER\\_COMPONENTS\\_INFRASTRUCTURE\\_MANIFEST\\_INIT](#); SQLSTATE: [HY000](#)  
Message: Received an error while processing components from manifest file: %s  
[ER\\_COMPONENTS\\_INFRASTRUCTURE\\_MANIFEST\\_INIT](#) was added in 8.0.24.
  - Error number: [MY-013710](#); Symbol: [ER\\_COMPONENTS\\_INFRASTRUCTURE\\_MANIFEST\\_DEINIT](#); SQLSTATE: [HY000](#)  
Message: Received an error while unloading components read from manifest file: %s  
[ER\\_COMPONENTS\\_INFRASTRUCTURE\\_MANIFEST\\_DEINIT](#) was added in 8.0.24.
  - Error number: [MY-013711](#); Symbol: [ER\\_WARN\\_COMPONENTS\\_INFRASTRUCTURE\\_MANIFEST\\_NOT\\_RO](#); SQLSTATE: [HY000](#)  
Message: Manifest file '%s' is not read-only. For better security, please make sure that the file is read-only.  
[ER\\_WARN\\_COMPONENTS\\_INFRASTRUCTURE\\_MANIFEST\\_NOT\\_RO](#) was added in 8.0.24.
  - Error number: [MY-013712](#); Symbol: [ER\\_WARN\\_NO\\_KEYRING\\_COMPONENT\\_SERVICE\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: No suitable '%s' service implementation found to fulfill the request.  
[ER\\_WARN\\_NO\\_KEYRING\\_COMPONENT\\_SERVICE\\_FOUND](#) was added in 8.0.24.

- 
- Error number: `MY-013713`; Symbol: `ER_NOTE_KEYRING_COMPONENT_INITIALIZED`; SQLSTATE: `HY000`  
  
Message: Keyring component initialized successfully.  
  
`ER_NOTE_KEYRING_COMPONENT_INITIALIZED` was added in 8.0.24.
  - Error number: `MY-013714`; Symbol: `ER_KEYRING_COMPONENT_NOT_INITIALIZED`; SQLSTATE: `HY000`  
  
Message: The component is not initialized properly. Make sure that configuration is proper and use `ALTER INSTANCE RELOAD KEYRING` to reinitialize the component.  
  
`ER_KEYRING_COMPONENT_NOT_INITIALIZED` was added in 8.0.24.
  - Error number: `MY-013715`; Symbol: `ER_KEYRING_COMPONENT_EXCEPTION`; SQLSTATE: `HY000`  
  
Message: Keyring component encountered an exception while executing : '%s' API of service: '%s'  
  
`ER_KEYRING_COMPONENT_EXCEPTION` was added in 8.0.24.
  - Error number: `MY-013716`; Symbol: `ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR`; SQLSTATE: `HY000`  
  
Message: Failed to allocated memory for '%s' while executing: '%s' API of service: '%s'  
  
`ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR` was added in 8.0.24.
  - Error number: `MY-013717`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK_SIZE`; SQLSTATE: `HY000`  
  
Message: Empty or 0 values for AES encryption mode and/or block size are not permitted.  
  
`ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK_SIZE` was added in 8.0.24.
  - Error number: `MY-013718`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY`; SQLSTATE: `HY000`  
  
Message: A valid data identifier is required in order to fetch the key required for the AES operation.  
  
`ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY` was added in 8.0.24.
  - Error number: `MY-013719`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY`; SQLSTATE: `HY000`  
  
Message: Key identified by Data ID: '%s' and Auth ID: '%s' is not of type AES.  
  
`ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY` was added in 8.0.24.
  - Error number: `MY-013720`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR`; SQLSTATE: `HY000`  
  
Message: Encountered error: '%s' while executing '%s' API of keyring\_aes service. Key details are Data ID: '%s' and Auth ID: '%s'.  
  
`ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR` was added in 8.0.24.
  - Error number: `MY-013721`; Symbol: `ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND`; SQLSTATE: `HY000`

---

Message: Could not find the data corresponding to Data ID: '%s', Auth ID: '%s'.

ER\_NOTE\_KEYRING\_COMPONENT\_READ\_DATA\_NOT\_FOUND was added in 8.0.24.

- Error number: MY-013722; Symbol: ER\_NOTE\_KEYRING\_COMPONENT\_WRITE\_MAXIMUM\_DATA\_LENGTH; SQLSTATE: HY000

Message: Maximum permissible size of data is '%zu' bits

ER\_NOTE\_KEYRING\_COMPONENT\_WRITE\_MAXIMUM\_DATA\_LENGTH was added in 8.0.24.

- Error number: MY-013723; Symbol: ER\_NOTE\_KEYRING\_COMPONENT\_STORE\_FAILED; SQLSTATE: HY000

Message: Error writing data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.

ER\_NOTE\_KEYRING\_COMPONENT\_STORE\_FAILED was added in 8.0.24.

- Error number: MY-013724; Symbol: ER\_NOTE\_KEYRING\_COMPONENT\_REMOVE\_FAILED; SQLSTATE: HY000

Message: Error removing data for Data ID: '%s', Auth ID: '%s'. Either data does not exists with same identifier or keyring backend encountered an error.

ER\_NOTE\_KEYRING\_COMPONENT\_REMOVE\_FAILED was added in 8.0.24.

- Error number: MY-013725; Symbol: ER\_NOTE\_KEYRING\_COMPONENT\_GENERATE\_FAILED; SQLSTATE: HY000

Message: Error generating data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.

ER\_NOTE\_KEYRING\_COMPONENT\_GENERATE\_FAILED was added in 8.0.24.

- Error number: MY-013726; Symbol: ER\_NOTE\_KEYRING\_COMPONENT\_KEYS\_METADATA\_ITERATOR\_FETCH\_FAILED; SQLSTATE: HY000

Message: Failed to get metadata from current keys metadata iterator position.

ER\_NOTE\_KEYRING\_COMPONENT\_KEYS\_METADATA\_ITERATOR\_FETCH\_FAILED was added in 8.0.24.

- Error number: MY-013727; Symbol: ER\_NOTE\_KEYRING\_COMPONENT\_METADATA\_ITERATOR\_INVALID\_OUT\_PARAM; SQLSTATE: HY000

Message: Key and value length parameters must not be null.

ER\_NOTE\_KEYRING\_COMPONENT\_METADATA\_ITERATOR\_INVALID\_OUT\_PARAM was added in 8.0.24.

- Error number: MY-013728; Symbol: ER\_IB\_WRN\_FAILED\_TO\_ACQUIRE\_SERVICE; SQLSTATE: HY000

Message: Innodb could not acquire service : %s

ER\_IB\_WRN\_FAILED\_TO\_ACQUIRE\_SERVICE was added in 8.0.24.

- Error number: MY-013729; Symbol: ER\_IB\_WRN\_OLD\_GEOMETRY\_TYPE; SQLSTATE: HY000

---

Message: Column %s of type GEOMETRY is in old (5.6) format which could be deprecated in the future. To change the format to latest, please consider rebuilding the table after the upgrade.

[ER\\_IB\\_WRN\\_OLD\\_GEOMETRY\\_TYPE](#) was added in 8.0.24.

- Error number: [MY-013730](#); Symbol: [ER\\_NET\\_WAIT\\_ERROR2](#); SQLSTATE: [HY000](#)

Message: 'wait\_timeout' period of %s seconds was exceeded for %s. The idle time since last command was too long.

[ER\\_NET\\_WAIT\\_ERROR2](#) was added in 8.0.26.

- Error number: [MY-013731](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_TRIGGERED](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" will be run.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_TRIGGERED](#) was added in 8.0.26.

- Error number: [MY-013732](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_FAILURE\\_IGNORE](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" failed, this error is ignored as instructed. Please check previous messages in the error log for hints about what could have caused this failure.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_FAILURE\\_IGNORE](#) was added in 8.0.26.

- Error number: [MY-013733](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" failed. Please check previous messages in the error log for hints about what could have caused this failure.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_FAILURE](#) was added in 8.0.26.

- Error number: [MY-013734](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_PARSE\\_ON\\_RECEIVE](#); SQLSTATE: [HY000](#)

Message: Unable to parse the member actions configuration sent by the primary.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_PARSE\\_ON\\_RECEIVE](#) was added in 8.0.26.

- Error number: [MY-013735](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UPDATE\\_ACTIONS](#); SQLSTATE: [HY000](#)

Message: Unable to update the member actions configuration with the one sent by the primary. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version'.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UPDATE\\_ACTIONS](#) was added in 8.0.26.

- Error number: [MY-013736](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_GET\\_EXCHANGEABLE\\_DATA](#); SQLSTATE: [HY000](#)

Message: Unable to read the member actions configuration during group membership change. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version'.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_GET\\_EXCHANGEABLE\\_DATA](#) was added in 8.0.26.

- 
- Error number: [MY-013737](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_DEFAULT\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: This member joined a group on which all members do not support member actions, as such it did reset its member configuration to the default one.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_DEFAULT\\_CONFIGURATION](#) was added in 8.0.26.

- Error number: [MY-013738](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UNABLE\\_TO\\_SET\\_DEFAULT\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Unable to reset to member actions default configuration on member join. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version'.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UNABLE\\_TO\\_SET\\_DEFAULT\\_CONFIGURATION](#) was added in 8.0.26.

- Error number: [MY-013739](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_PARSE\\_ON\\_MEMBER\\_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to parse the member actions configuration sent by the group on member join.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_PARSE\\_ON\\_MEMBER\\_JOIN](#) was added in 8.0.26.

- Error number: [MY-013740](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UPDATE\\_ACTIONS\\_ON\\_MEMBER\\_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to update the member actions configuration on member join. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version'.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UPDATE\\_ACTIONS\\_ON\\_MEMBER\\_JOIN](#) was added in 8.0.26.

- Error number: [MY-013741](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_INVALID\\_ACTIONS\\_ON\\_MEMBER\\_JOIN](#); SQLSTATE: [HY000](#)

Message: The group members were unable to send their member actions configuration. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version' on all members.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_INVALID\\_ACTIONS\\_ON\\_MEMBER\\_JOIN](#) was added in 8.0.26.

- Error number: [MY-013742](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_ENABLED](#); SQLSTATE: [HY000](#)

Message: Member action enabled: "%s", type: "%s", event: "%s", priority: "%u", error\_handling: "%s".

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_ENABLED](#) was added in 8.0.26.

- Error number: [MY-013743](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_DISABLED](#); SQLSTATE: [HY000](#)

Message: Member action disabled: "%s", type: "%s", event: "%s", priority: "%u", error\_handling: "%s".

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_DISABLED](#) was added in 8.0.26.

- Error number: [MY-013744](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTIONS\\_RESET](#); SQLSTATE: [HY000](#)

Message: Member actions configuration was reset.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTIONS\\_RESET](#) was added in 8.0.26.

- Error number: [MY-013745](#); Symbol: [ER\\_DEPRECATED\\_TLS\\_VERSION\\_SESSION](#); SQLSTATE: [HY000](#)

---

Message: Accepted a connection with deprecated protocol '%s' for account '%s'@'%s' from host '%s'. Client supplied username '%s'

[ER\\_DEPRECATED\\_TLS\\_VERSION\\_SESSION](#) was added in 8.0.26, removed after 8.0.27.

- Error number: [MY-013746](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_TLS\\_VERSION\\_FOR\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: A deprecated TLS version %s is enabled for channel %s

[ER\\_WARN\\_DEPRECATED\\_TLS\\_VERSION\\_FOR\\_CHANNEL](#) was added in 8.0.26, removed after 8.0.27.

- Error number: [MY-013747](#); Symbol: [ER\\_FIREWALL\\_DEPRECATED\\_USER\\_PROFILE](#); SQLSTATE: [HY000](#)

Message: User profile '%s\ ' loaded. Firewall user profiles are deprecated, consider migrating to group profiles.

[ER\\_FIREWALL\\_DEPRECATED\\_USER\\_PROFILE](#) was added in 8.0.26.

- Error number: [MY-013748](#); Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_INVALID](#); SQLSTATE: [HY000](#)

Message: Invalid input value for group\_replication\_view\_change\_uuid '%s'. Please, provide a valid UUID.

[ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_INVALID](#) was added in 8.0.26.

- Error number: [MY-013749](#); Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_SAME\\_AS\\_GROUP\\_NAME](#); SQLSTATE: [HY000](#)

Message: Variable 'group\_replication\_view\_change\_uuid' cannot be set to the value of '%s'. If you want to use the UUID of 'group\_replication\_group\_name' for the UUID of View\_change\_log\_events, please set 'group\_replication\_view\_change\_uuid' to AUTOMATIC.

[ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_SAME\\_AS\\_GROUP\\_NAME](#) was added in 8.0.26.

- Error number: [MY-013750](#); Symbol: [ER\\_GRP\\_RPL\\_GROUP\\_NAME\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: [HY000](#)

Message: group\_replication\_group\_name '%s', which is the same as group\_replication\_view\_change\_uuid. Please change group\_replication\_view\_change\_uuid to AUTOMATIC

[ER\\_GRP\\_RPL\\_GROUP\\_NAME\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#) was added in 8.0.26.

- Error number: [MY-013751](#); Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_IS\\_SAME\\_AS\\_ANONYMOUS\\_TO\\_GTID\\_UUID](#); SQLSTATE: [HY000](#)

Message: The group\_replication\_view\_change\_uuid '%s' is the same as the UUID value for ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS in a server channel

[ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_IS\\_SAME\\_AS\\_ANONYMOUS\\_TO\\_GTID\\_UUID](#) was added in 8.0.26.

- Error number: [MY-013752](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_VIEW\\_CHANGE\\_UUID\\_IS\\_INCOMPATIBLE\\_WITH\\_SERVER\\_UUID](#); SQLSTATE: [HY000](#)

---

Message: group\_replication\_view\_change\_uuid is incompatible with group.  
group\_replication\_view\_change\_uuid %s matches server\_uuid %s.

[ER\\_GRP\\_RPL\\_GRP\\_VIEW\\_CHANGE\\_UUID\\_IS\\_INCOMPATIBLE\\_WITH\\_SERVER\\_UUID](#) was added in 8.0.26.

- Error number: [MY-013753](#); Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_DIFF\\_FROM\\_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a group\_replication\_view\_change\_uuid option value '%s' different from the group '%s'. The member will now exit the group.

[ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_DIFF\\_FROM\\_GRP](#) was added in 8.0.26.

- Error number: [MY-013754](#); Symbol: [ER\\_WARN\\_REPLICA\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: [HY000](#)

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'` which is equal to `group_replication_view_change_uuid`. To fix this issue, either change the `group_replication_view_change_uuid` or use a different value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS`.

[ER\\_WARN\\_REPLICA\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#) was added in 8.0.26.

- Error number: [MY-013755](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_PARSE\\_THE\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: [HY000](#)

Message: Unable to parse the `group_replication_view_change_uuid`.

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_PARSE\\_THE\\_VIEW\\_CHANGE\\_UUID](#) was added in 8.0.26.

- Error number: [MY-013756](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_GENERATE\\_SIDNO\\_FOR\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: [HY000](#)

Message: Unable to generate sidno for `group_replication_view_change_uuid`.

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_GENERATE\\_SIDNO\\_FOR\\_VIEW\\_CHANGE\\_UUID](#) was added in 8.0.26.

- Error number: [MY-013757](#); Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to parse the `group_replication_view_change_uuid` during the Certification module initialization.

[ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_PARSE\\_ERROR](#) was added in 8.0.26.

- Error number: [MY-013758](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_GRPGTID\\_VIEW\\_CHANGE\\_UUID\\_EXECUTED\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating `group_gtid_executed` GTID set with view change uuid during the Certification module initialization.

[ER\\_GRP\\_RPL\\_UPDATE\\_GRPGTID\\_VIEW\\_CHANGE\\_UUID\\_EXECUTED\\_ERROR](#) was added in 8.0.26.



- 
- Error number: [MY-013759](#); Symbol: [ER\\_GRP\\_RPL\\_ADD\\_VIEW\\_CHANGE\\_UUID\\_TO\\_GRP\\_SID\\_MAP\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Unable to add the group\_replication\_view\_change\_uuid sidno in the group\_gtid\_sid\_map during the Certification module initialization.  
  
[ER\\_GRP\\_RPL\\_ADD\\_VIEW\\_CHANGE\\_UUID\\_TO\\_GRP\\_SID\\_MAP\\_ERROR](#) was added in 8.0.26.
  - Error number: [MY-013760](#); Symbol: [ER\\_GRP\\_RPL\\_DONOR\\_VIEW\\_CHANGE\\_UUID\\_TRANS\\_INFO\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Unable to handle the donor's view change uuid transaction information when initializing the conflict detection component. Possible out of memory error.  
  
[ER\\_GRP\\_RPL\\_DONOR\\_VIEW\\_CHANGE\\_UUID\\_TRANS\\_INFO\\_ERROR](#) was added in 8.0.26.
  - Error number: [MY-013761](#); Symbol: [ER\\_WARN\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_FAIL\\_GET\\_VARIABLE](#); SQLSTATE: [HY000](#)  
  
Message: Unable to retrieve group\_replication\_view\_change\_uuid during server checks on replication operations.  
  
[ER\\_WARN\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_FAIL\\_GET\\_VARIABLE](#) was added in 8.0.26.
  - Error number: [MY-013762](#); Symbol: [ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_AND\\_PRUNE\\_SECONDS\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: Both audit\_log\_max\_size and audit\_log\_prune\_seconds are set to non-zero. audit\_log\_max\_size takes precedence and audit\_log\_prune\_seconds is ignored  
  
[ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_AND\\_PRUNE\\_SECONDS\\_LOG](#) was added in 8.0.26.
  - Error number: [MY-013763](#); Symbol: [ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_CLOSE\\_TO\\_ROTATE\\_ON\\_SIZE\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: audit\_log\_rotate\_on\_size is not granular enough for the value of audit\_log\_max\_size supplied. Should be at least %d times smaller.  
  
[ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_CLOSE\\_TO\\_ROTATE\\_ON\\_SIZE\\_LOG](#) was added in 8.0.26.
  - Error number: [MY-013764](#); Symbol: [ER\\_PLUGIN\\_INVALID\\_TABLE\\_DEFINITION](#); SQLSTATE: [HY000](#)  
  
Message: Invalid table definition for '%s.%s'.  
  
[ER\\_PLUGIN\\_INVALID\\_TABLE\\_DEFINITION](#) was added in 8.0.26.
  - Error number: [MY-013765](#); Symbol: [ER\\_AUTH\\_KERBEROS\\_LOGGER\\_GENERIC\\_MSG](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_AUTH\\_KERBEROS\\_LOGGER\\_GENERIC\\_MSG](#) was added in 8.0.26.
  - Error number: [MY-013766](#); Symbol: [ER\\_INSTALL\\_PLUGIN\\_CONFLICT\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: Cannot install the %s plugin when the %s plugin is installed.  
  
[ER\\_INSTALL\\_PLUGIN\\_CONFLICT\\_LOG](#) was added in 8.0.26.

- 
- Error number: [MY-013767](#); Symbol: [ER\\_DEPRECATED\\_PERSISTED\\_VARIABLE\\_WITH\\_ALIAS](#); SQLSTATE: [HY000](#)

Message: The variable %s has been renamed to %s, and the old name deprecated. Only the old name was found in the persisted variable file. Next time the file is saved, both names will be stored. Issue any SET PERSIST command to save the file, get rid of this warning, and prepare the persisted configuration for when the variable is removed in a future version.

[ER\\_DEPRECATED\\_PERSISTED\\_VARIABLE\\_WITH\\_ALIAS](#) was added in 8.0.26.

- Error number: [MY-013768](#); Symbol: [ER\\_LOG\\_COMPONENT\\_FLUSH\\_FAILED](#); SQLSTATE: [HY000](#)

Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.

[ER\\_LOG\\_COMPONENT\\_FLUSH\\_FAILED](#) was added in 8.0.26.

- Error number: [MY-013769](#); Symbol: [ER\\_IB\\_MSG\\_REENCRYPTED\\_TABLESPACE\\_KEY](#); SQLSTATE: [HY000](#)

Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you rebuild the table for better security.

[ER\\_IB\\_MSG\\_REENCRYPTED\\_TABLESPACE\\_KEY](#) was added in 8.0.26.

- Error number: [MY-013770](#); Symbol: [ER\\_IB\\_MSG\\_REENCRYPTED\\_GENERAL\\_TABLESPACE\\_KEY](#); SQLSTATE: [HY000](#)

Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you reencrypt the tablespace for better security.

[ER\\_IB\\_MSG\\_REENCRYPTED\\_GENERAL\\_TABLESPACE\\_KEY](#) was added in 8.0.26.

- Error number: [MY-013771](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_DBLWR\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Page Archiver's doublewrite buffer initialisation failed. Page tracking is at risk of losing tracked information.

[ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_DBLWR\\_INIT\\_FAILED](#) was added in 8.0.26.

- Error number: [MY-013772](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_NO\\_SPACE\\_IN\\_REDO\\_LOG\\_\\_SKIP\\_IBUF\\_MERGES](#); SQLSTATE: [HY000](#)

Message: There is not enough free space in the redo log during recovery to perform pending ibuf merges. Please retry starting MySQL with --innodb-force-recovery=4.

[ER\\_IB\\_MSG\\_RECOVERY\\_NO\\_SPACE\\_IN\\_REDO\\_LOG\\_\\_SKIP\\_IBUF\\_MERGES](#) was added in 8.0.26.

- Error number: [MY-013773](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_NO\\_SPACE\\_IN\\_REDO\\_LOG\\_\\_UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: There is not enough free space in the redo log during recovery, restore from backup (or retry with --innodb-force-recovery=6).

[ER\\_IB\\_MSG\\_RECOVERY\\_NO\\_SPACE\\_IN\\_REDO\\_LOG\\_\\_UNEXPECTED](#) was added in 8.0.26.

- 
- Error number: [MY-013774](#); Symbol: [ER\\_WARN\\_AUDIT\\_LOG\\_FORMAT\\_UNIX\\_TIMESTAMP\\_ONLY\\_WHEN\\_JSON\\_LOG](#); SQLSTATE: [HY000](#)  
Message: audit\_log\_format\_unix\_timestamp is applicable only when audit\_log\_format = JSON.  
[ER\\_WARN\\_AUDIT\\_LOG\\_FORMAT\\_UNIX\\_TIMESTAMP\\_ONLY\\_WHEN\\_JSON\\_LOG](#) was added in 8.0.26.
  - Error number: [MY-013775](#); Symbol: [ER\\_PREPARE\\_FOR\\_PRIMARY\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Retry the statement using the primary storage engine.  
[ER\\_PREPARE\\_FOR\\_PRIMARY\\_ENGINE](#) was added in 8.0.26.
  - Error number: [MY-013776](#); Symbol: [ER\\_IB\\_MSG\\_PAR\\_RSEG\\_INIT\\_COMPLETE\\_MSG](#); SQLSTATE: [HY000](#)  
Message: Parallel initialization of rseg complete  
[ER\\_IB\\_MSG\\_PAR\\_RSEG\\_INIT\\_COMPLETE\\_MSG](#) was added in 8.0.27.
  - Error number: [MY-013777](#); Symbol: [ER\\_IB\\_MSG\\_PAR\\_RSEG\\_INIT\\_TIME\\_MSG](#); SQLSTATE: [HY000](#)  
Message: Time taken to initialize rseg using %u thread: %u ms.  
[ER\\_IB\\_MSG\\_PAR\\_RSEG\\_INIT\\_TIME\\_MSG](#) was added in 8.0.27.
  - Error number: [MY-013778](#); Symbol: [ER\\_DDL\\_MSG\\_1](#); SQLSTATE: [HY000](#)  
Message: DDL failed to create a thread to load an index, fall back to single thread  
[ER\\_DDL\\_MSG\\_1](#) was added in 8.0.27.
  - Error number: [MY-013779](#); Symbol: [ER\\_MTR\\_MSG\\_1](#); SQLSTATE: [HY000](#)  
Message: Debug\_check\_no\_latching failed, slot->type=%d  
[ER\\_MTR\\_MSG\\_1](#) was added in 8.0.27.
  - Error number: [MY-013780](#); Symbol: [ER\\_GRP\\_RPL\\_MYSQL\\_NETWORK\\_PROVIDER\\_CLIENT\\_ERROR\\_CONN\\_ERR](#); SQLSTATE: [HY000](#)  
Message: Failed to establish MySQL client connection in Group Replication. Error establishing connection. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.  
[ER\\_GRP\\_RPL\\_MYSQL\\_NETWORK\\_PROVIDER\\_CLIENT\\_ERROR\\_CONN\\_ERR](#) was added in 8.0.27.
  - Error number: [MY-013781](#); Symbol: [ER\\_GRP\\_RPL\\_MYSQL\\_NETWORK\\_PROVIDER\\_CLIENT\\_ERROR\\_COMMAND\\_ERR](#); SQLSTATE: [HY000](#)  
Message: Failed to establish MySQL client connection in Group Replication. Error sending connection delegation command. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.  
[ER\\_GRP\\_RPL\\_MYSQL\\_NETWORK\\_PROVIDER\\_CLIENT\\_ERROR\\_COMMAND\\_ERR](#) was added in 8.0.27.
  - Error number: [MY-013782](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_GET\\_EXCHANGEABLE\\_DATA](#); SQLSTATE: [HY000](#)

---

Message: Unable to read the replication failover channels configuration during group membership change. Please check the tables 'mysql.replication\_asynchronous\_connection\_failover', 'mysql.replication\_asynchronous\_connection\_failover\_managed' and 'mysql.replication\_group\_configuration\_version'.

[ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_GET\\_EXCHANGEABLE\\_DATA](#) was added in 8.0.27.

- Error number: [MY-013783](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_DEFAULT\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: This member joined a group on which all members do not support replication failover channels integration on Group Replication, as such it did reset its replication failover channels configuration to the default one.

[ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_DEFAULT\\_CONFIGURATION](#) was added in 8.0.27.

- Error number: [MY-013784](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_UNABLE\\_TO\\_SET\\_DEFAULT\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Unable to reset to replication failover channels default configuration on member join. Please check the tables 'mysql.replication\_asynchronous\_connection\_failover', 'mysql.replication\_asynchronous\_connection\_failover\_managed' and 'mysql.replication\_group\_configuration\_version'.

[ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_UNABLE\\_TO\\_SET\\_DEFAULT\\_CONFIGURATION](#) was added in 8.0.27.

- Error number: [MY-013785](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_PARSE\\_ON\\_MEMBER\\_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to parse the replication failover channels configuration sent by the group on member join.

[ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_PARSE\\_ON\\_MEMBER\\_JOIN](#) was added in 8.0.27.

- Error number: [MY-013786](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_CHANNEL\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)

Message: Unable to set SOURCE\_CONNECTION\_AUTO\_FAILOVER on a non-existent or misconfigured replication channel '%s', please create the channel and rejoin the server to the group.

[ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_CHANNEL\\_DOES\\_NOT\\_EXIST](#) was added in 8.0.27.

- Error number: [MY-013787](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_REGISTER\\_MESSAGE\\_LISTENER\\_SERVICE](#); SQLSTATE: [HY000](#)

Message: Unable to register the listener 'replication\_asynchronous\_connection\_failover\_configuration' to the service 'group\_replication\_message\_service\_recv'.

[ER\\_GRP\\_RPL\\_FAILOVER\\_REGISTER\\_MESSAGE\\_LISTENER\\_SERVICE](#) was added in 8.0.27.

- Error number: [MY-013788](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_PRIMARY\\_WITHOUT\\_MAJORITY](#); SQLSTATE: [HY000](#)

Message: This server is not able to reach a majority of members in the group. This server will skip the replication failover channels handling until this server is back to the group majority.

[ER\\_GRP\\_RPL\\_FAILOVER\\_PRIMARY\\_WITHOUT\\_MAJORITY](#) was added in 8.0.27.

- 
- Error number: [MY-013789](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_PRIMARY\\_BACK\\_TO\\_MAJORITY](#); SQLSTATE: [HY000](#)

Message: This server is back to the group majority. Replication failover channels handling is resumed.

[ER\\_GRP\\_RPL\\_FAILOVER\\_PRIMARY\\_BACK\\_TO\\_MAJORITY](#) was added in 8.0.27.

- Error number: [MY-013790](#); Symbol: [ER\\_RPL\\_INCREMENTING\\_MEMBER\\_ACTION\\_VERSION](#); SQLSTATE: [HY000](#)

Message: Error incrementing member action configuration version for %s.%s table.

[ER\\_RPL\\_INCREMENTING\\_MEMBER\\_ACTION\\_VERSION](#) was added in 8.0.27.

- Error number: [MY-013791](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_THREAD\\_ERROR\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)

Message: The '%s' thread of channel '%s' will error out as this server is a group secondary.

[ER\\_GRP\\_RPL\\_SLAVE\\_THREAD\\_ERROR\\_ON\\_SECONDARY\\_MEMBER](#) was added in 8.0.27, removed after 8.0.32.

- Error number: [MY-013791](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_THREAD\\_ERROR\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)

Message: The '%s' thread of channel '%s' will error out as this server is a group secondary.

[ER\\_GRP\\_RPL\\_REPLICA\\_THREAD\\_ERROR\\_ON\\_SECONDARY\\_MEMBER](#) was added in 8.0.33.

- Error number: [MY-013792](#); Symbol: [ER\\_IB\\_MSG\\_CLONE\\_DDL\\_NTFN](#); SQLSTATE: [HY000](#)

Message: Clone DDL Notification: %s

[ER\\_IB\\_MSG\\_CLONE\\_DDL\\_NTFN](#) was added in 8.0.27.

- Error number: [MY-013793](#); Symbol: [ER\\_IB\\_MSG\\_CLONE\\_DDL\\_APPLY](#); SQLSTATE: [HY000](#)

Message: Clone DDL APPLY: %s

[ER\\_IB\\_MSG\\_CLONE\\_DDL\\_APPLY](#) was added in 8.0.27.

- Error number: [MY-013794](#); Symbol: [ER\\_IB\\_MSG\\_CLONE\\_DDL\\_INVALIDATE](#); SQLSTATE: [HY000](#)

Message: Clone DDL Invalidate : %s

[ER\\_IB\\_MSG\\_CLONE\\_DDL\\_INVALIDATE](#) was added in 8.0.27.

- Error number: [MY-013795](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_ENCRYPTION\\_INFO\\_LOADED](#); SQLSTATE: [HY000](#)

Message: Encryption key is loaded for undo tablespace '%s'.

[ER\\_IB\\_MSG\\_UNDO\\_ENCRYPTION\\_INFO\\_LOADED](#) was added in 8.0.27.

- 
- Error number: [MY-013796](#); Symbol: [ER\\_IB\\_WRN\\_ENCRYPTION\\_INFO\\_SIZE\\_MISMATCH](#); SQLSTATE: [HY000](#)  
  
Message: Ignoring encryption INFO size in redo log: %zu, expected: %zu  
  
[ER\\_IB\\_WRN\\_ENCRYPTION\\_INFO\\_SIZE\\_MISMATCH](#) was added in 8.0.27.
  - Error number: [MY-013797](#); Symbol: [ER\\_INVALID\\_AUTHENTICATION\\_POLICY](#); SQLSTATE: [HY000](#)  
  
Message: Option --authentication-policy is set to an invalid value. Please check if the specified authentication plugins are valid.  
  
[ER\\_INVALID\\_AUTHENTICATION\\_POLICY](#) was added in 8.0.27.
  - Error number: [MY-013798](#); Symbol: [ER\\_AUTHENTICATION\\_PLUGIN\\_REGISTRATION\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Signature verification failed during registration.  
  
[ER\\_AUTHENTICATION\\_PLUGIN\\_REGISTRATION\\_FAILED](#) was added in 8.0.27.
  - Error number: [MY-013799](#); Symbol: [ER\\_AUTHENTICATION\\_PLUGIN\\_REGISTRATION\\_INSUFFICIENT\\_BUFFER](#); SQLSTATE: [HY000](#)  
  
Message: Buffer too small to hold registration challenge response.  
  
[ER\\_AUTHENTICATION\\_PLUGIN\\_REGISTRATION\\_INSUFFICIENT\\_BUFFER](#) was added in 8.0.27.
  - Error number: [MY-013800](#); Symbol: [ER\\_AUTHENTICATION\\_PLUGIN\\_AUTH\\_DATA\\_CORRUPT](#); SQLSTATE: [HY000](#)  
  
Message: FIDO device authenticator data corrupt.  
  
[ER\\_AUTHENTICATION\\_PLUGIN\\_AUTH\\_DATA\\_CORRUPT](#) was added in 8.0.27.
  - Error number: [MY-013801](#); Symbol: [ER\\_AUTHENTICATION\\_PLUGIN\\_SIGNATURE\\_CORRUPT](#); SQLSTATE: [HY000](#)  
  
Message: FIDO device signature corrupt.  
  
[ER\\_AUTHENTICATION\\_PLUGIN\\_SIGNATURE\\_CORRUPT](#) was added in 8.0.27.
  - Error number: [MY-013802](#); Symbol: [ER\\_AUTHENTICATION\\_PLUGIN\\_VERIFY\\_SIGNATURE\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Signature verification failed during authentication.  
  
[ER\\_AUTHENTICATION\\_PLUGIN\\_VERIFY\\_SIGNATURE\\_FAILED](#) was added in 8.0.27.
  - Error number: [MY-013803](#); Symbol: [ER\\_AUTHENTICATION\\_PLUGIN\\_OOM](#); SQLSTATE: [HY000](#)  
  
Message: Out of memory.  
  
[ER\\_AUTHENTICATION\\_PLUGIN\\_OOM](#) was added in 8.0.27.

- 
- Error number: [MY-013804](#); Symbol: [ER\\_AUTHENTICATION\\_PLUGIN\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Can't initialize logging service  
[ER\\_AUTHENTICATION\\_PLUGIN\\_LOG](#) was added in 8.0.27.
  - Error number: [MY-013805](#); Symbol: [ER\\_WARN\\_REPLICA\\_GTID\\_ONLY\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#); SQLSTATE: [HY000](#)  
Message: Replication channel '%s' is configured with GTID\_ONLY=1, which is invalid when GTID\_MODE <> ON. If you intend to disable GTIDs in the replication topology, change GTID\_ONLY to 0.  
[ER\\_WARN\\_REPLICA\\_GTID\\_ONLY\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#) was added in 8.0.27.
  - Error number: [MY-013806](#); Symbol: [ER\\_WARN\\_L\\_DISABLE\\_GTID\\_ONLY\\_WITH\\_SOURCE\\_AUTO\\_POS\\_INVALID\\_POS](#); SQLSTATE: [HY000](#)  
Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of GTID\_ONLY=1. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.  
[ER\\_WARN\\_L\\_DISABLE\\_GTID\\_ONLY\\_WITH\\_SOURCE\\_AUTO\\_POS\\_INVALID\\_POS](#) was added in 8.0.27.
  - Error number: [MY-013807](#); Symbol: [ER\\_RPL\\_CANNOT\\_OPEN\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Could not open relay log: %s  
[ER\\_RPL\\_CANNOT\\_OPEN\\_RELAY\\_LOG](#) was added in 8.0.27.
  - Error number: [MY-013808](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_PLUGIN\\_NOT\\_INITIALIZED](#); SQLSTATE: [HY000](#)  
Message: Authentication plugin not initialized.  
[ER\\_AUTHENTICATION\\_OCI\\_PLUGIN\\_NOT\\_INITIALIZED](#) was added in 8.0.27.
  - Error number: [MY-013809](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_PRIVATE\\_KEY\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Cannot use the generated private key file.  
[ER\\_AUTHENTICATION\\_OCI\\_PRIVATE\\_KEY\\_ERROR](#) was added in 8.0.27.
  - Error number: [MY-013810](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_DOWNLOAD\\_PUBLIC\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Unavailable public key with fingerprint %s for user %s in tenancy %s .  
[ER\\_AUTHENTICATION\\_OCI\\_DOWNLOAD\\_PUBLIC\\_KEY](#) was added in 8.0.27.
  - Error number: [MY-013811](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_IMDS](#); SQLSTATE: [HY000](#)  
Message: Cannot obtain the OCI configuration from the IMDS service.  
[ER\\_AUTHENTICATION\\_OCI\\_IMDS](#) was added in 8.0.27.
  - Error number: [MY-013812](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_IAM](#); SQLSTATE: [HY000](#)

---

Message: Cannot initialize the IAM service.

[ER\\_AUTHENTICATION\\_OCI\\_IAM](#) was added in 8.0.27.

- Error number: [MY-013813](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_INVALID\\_AUTHENTICATION\\_STRING](#); SQLSTATE: [HY000](#)

Message: Invalid authentication string details for user: `%s`@`%s`.

[ER\\_AUTHENTICATION\\_OCI\\_INVALID\\_AUTHENTICATION\\_STRING](#) was added in 8.0.27.

- Error number: [MY-013814](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_NO\\_MATCHING\\_GROUPS](#); SQLSTATE: [HY000](#)

Message: None of the groups returned by IAM matches any of the entries from authentication string.

[ER\\_AUTHENTICATION\\_OCI\\_NO\\_MATCHING\\_GROUPS](#) was added in 8.0.27.

- Error number: [MY-013815](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_NO\\_GROUPS\\_FOUND](#); SQLSTATE: [HY000](#)

Message: User is not part of any groups. However, account is configured to use group mapping.

[ER\\_AUTHENTICATION\\_OCI\\_NO\\_GROUPS\\_FOUND](#) was added in 8.0.27.

- Error number: [MY-013816](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_NONCE](#); SQLSTATE: [HY000](#)

Message: Received OpenSSL error: %s while authenticating user %s with fingerprint %s in tenancy %s .

[ER\\_AUTHENTICATION\\_OCI\\_NONCE](#) was added in 8.0.27.

- Error number: [MY-013817](#); Symbol: [ER\\_HEALTH\\_WARNING\\_MEMORY\\_USAGE\\_LEVEL\\_1](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 1 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqlid=%llu MiB

[ER\\_HEALTH\\_WARNING\\_MEMORY\\_USAGE\\_LEVEL\\_1](#) was added in 8.0.27.

- Error number: [MY-013818](#); Symbol: [ER\\_HEALTH\\_WARNING\\_MEMORY\\_USAGE\\_LEVEL\\_2](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 2 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqlid=%llu MiB

[ER\\_HEALTH\\_WARNING\\_MEMORY\\_USAGE\\_LEVEL\\_2](#) was added in 8.0.27.

- Error number: [MY-013819](#); Symbol: [ER\\_HEALTH\\_WARNING\\_MEMORY\\_USAGE\\_LEVEL\\_3](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 3 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqlid=%llu MiB

[ER\\_HEALTH\\_WARNING\\_MEMORY\\_USAGE\\_LEVEL\\_3](#) was added in 8.0.27.

- Error number: [MY-013820](#); Symbol: [ER\\_GRP\\_RPL\\_SET\\_SINGLE\\_CONSENSUS\\_LEADER](#); SQLSTATE: [HY000](#)



---

Message: The member %s:%u, with UUID: %s, was set as the single preferred consensus leader.

[ER\\_GRP\\_RPL\\_SET\\_SINGLE\\_CONSENSUS\\_LEADER](#) was added in 8.0.27.

- Error number: [MY-013821](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_SET\\_SINGLE\\_CONSENSUS\\_LEADER](#); SQLSTATE: [HY000](#)

Message: Something went wrong trying to set the member %s:%u, with UUID: %s, as the single preferred consensus leader. Please query the `performance_schema.replication_group_communication_information` table to see whether the operation took effect, i.e. whether the preferred consensus leader matches the current primary. If not, consider electing a different primary to try again. Please check the error log and `GCS_DEBUG_TRACE` for more information that may help understanding what went wrong.

[ER\\_GRP\\_RPL\\_ERROR\\_SET\\_SINGLE\\_CONSENSUS\\_LEADER](#) was added in 8.0.27.

- Error number: [MY-013822](#); Symbol: [ER\\_GRP\\_RPL\\_SET\\_MULTI\\_CONSENSUS\\_LEADER](#); SQLSTATE: [HY000](#)

Message: All members were set as consensus leaders.

[ER\\_GRP\\_RPL\\_SET\\_MULTI\\_CONSENSUS\\_LEADER](#) was added in 8.0.27.

- Error number: [MY-013823](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_SET\\_MULTI\\_CONSENSUS\\_LEADER](#); SQLSTATE: [HY000](#)

Message: Something went wrong trying to set all members as consensus leaders. Please query the `performance_schema.replication_group_communication_information` table to see whether the operation took effect, i.e. whether the consensus leaders match all members. If not, consider resetting the group communication protocol to a version < 8.0.22, or switch to single-primary mode and back again to multi-primary mode, to try again. Please check the error log and `GCS_DEBUG_TRACE` for more information that may help understanding what went wrong.

[ER\\_GRP\\_RPL\\_ERROR\\_SET\\_MULTI\\_CONSENSUS\\_LEADER](#) was added in 8.0.27.

- Error number: [MY-013824](#); Symbol: [ER\\_GRP\\_RPL\\_PAXOS\\_SINGLE\\_LEADER\\_DIFF\\_FROM\\_GRP](#); SQLSTATE: [HY000](#)

Message: This member is configured with a `group_replication_paxos_single_leader` option value of '%d' that is different from the group's value ('%d'). This member will now exit the group.

[ER\\_GRP\\_RPL\\_PAXOS\\_SINGLE\\_LEADER\\_DIFF\\_FROM\\_GRP](#) was added in 8.0.27.

- Error number: [MY-013825](#); Symbol: [ER\\_MFA\\_USER\\_ATTRIBUTES\\_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Invalid and/or corrupted multi factor authentication methods in `User_attributes` column in `mysql.user` table. "%s".

[ER\\_MFA\\_USER\\_ATTRIBUTES\\_CORRUPT](#) was added in 8.0.27.

- Error number: [MY-013826](#); Symbol: [ER\\_MFA\\_PLUGIN\\_NOT\\_LOADED](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is not loaded; Ignoring user

[ER\\_MFA\\_PLUGIN\\_NOT\\_LOADED](#) was added in 8.0.27.

- Error number: [MY-013827](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_CHARSET\\_OPTION](#); SQLSTATE: [HY000](#)

---

Message: %s: The character set %s is deprecated and will be removed in a future release. Please consider using %s instead.

[ER\\_WARN\\_DEPRECATED\\_CHARSET\\_OPTION](#) was added in 8.0.28.

- Error number: [MY-013828](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_COLLATION\\_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.

[ER\\_WARN\\_DEPRECATED\\_COLLATION\\_OPTION](#) was added in 8.0.28.

- Error number: [MY-013829](#); Symbol: [ER\\_REGEXP\\_MISSING\\_ICU\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: Missing data directory for ICU regular expressions: %s.

[ER\\_REGEXP\\_MISSING\\_ICU\\_DATADIR](#) was added in 8.0.28.

- Error number: [MY-013830](#); Symbol: [ER\\_IB\\_WARN\\_MANY\\_NON\\_LRU\\_FILES\\_OPENED](#); SQLSTATE: [HY000](#)

Message: More than 90%% of files opened out of the innodb\_open\_files limit are files that are not easy to close. The performance of system may degrade. Consider increasing value of the innodb\_open\_files system variable. There are %zu such files opened out of the total limit for all files opened of %zu.

[ER\\_IB\\_WARN\\_MANY\\_NON\\_LRU\\_FILES\\_OPENED](#) was added in 8.0.28.

- Error number: [MY-013831](#); Symbol: [ER\\_IB\\_MSG\\_TRYING\\_TO\\_OPEN\\_FILE\\_FOR\\_LONG\\_TIME](#); SQLSTATE: [HY000](#)

Message: Trying to open a file for %lld seconds. Configuration only allows for %zu open files. Consider setting innobase\_open\_files higher.

[ER\\_IB\\_MSG\\_TRYING\\_TO\\_OPEN\\_FILE\\_FOR\\_LONG\\_TIME](#) was added in 8.0.28.

- Error number: [MY-013832](#); Symbol: [ER\\_GLOBAL\\_CONN\\_LIMIT](#); SQLSTATE: [HY000](#)

Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.

[ER\\_GLOBAL\\_CONN\\_LIMIT](#) was added in 8.0.28.

- Error number: [MY-013833](#); Symbol: [ER\\_CONN\\_LIMIT](#); SQLSTATE: [HY000](#)

Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.

[ER\\_CONN\\_LIMIT](#) was added in 8.0.28.

- Error number: [MY-013834](#); Symbol: [ER\\_WARN\\_AUDIT\\_LOG\\_DISABLED](#); SQLSTATE: [HY000](#)

Message: Audit Log is disabled. Enable it with audit\_log\_disable = false.

[ER\\_WARN\\_AUDIT\\_LOG\\_DISABLED](#) was added in 8.0.28.

- Error number: [MY-013835](#); Symbol: [ER\\_INVALID\\_TLS\\_VERSION](#); SQLSTATE: [HY000](#)

Message: Option --tls-version or --admin-tls-version is set to an invalid value %s.

---

`ER_INVALID_TLS_VERSION` was added in 8.0.28.

- Error number: `MY-013836`; Symbol: `ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY`; SQLSTATE: `HY000`

Message: Relay log recovery on channel with `GTID_ONLY=1`. The channel will switch to a new relay log and the GTID protocol will be used to replicate unapplied transactions.

`ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY` was added in 8.0.28.

- Error number: `MY-013837`; Symbol: `ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED`; SQLSTATE: `HY000`

Message: Number of `STANDBY_SERVER` values exceeded maximum limit of 64.

`ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED` was added in 8.0.29.

- Error number: `MY-013838`; Symbol: `ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING`; SQLSTATE: `HY000`

Message: Source keyring does not have any keys to migrate.

`ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING` was added in 8.0.29.

- Error number: `MY-013839`; Symbol: `ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES`; SQLSTATE: `HY000`

Message: Cannot persist `SENSITIVE` system variables because keyring component support is unavailable and `persist_sensitive_variables_in_plaintext` is set to `OFF`. Please make sure that keyring services are active and required keys are available.

`ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES` was added in 8.0.29.

- Error number: `MY-013840`; Symbol: `ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES`; SQLSTATE: `HY000`

Message: Cannot interpret persisted `SENSITIVE` system variables. Please make sure that keyring services are active and required keys are available.

`ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES` was added in 8.0.29.

- Error number: `MY-013841`; Symbol: `ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED`; SQLSTATE: `HY000`

Message: Keyring has to be loaded through manifest file in order to support secure storage for persisted variables

`ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED` was added in 8.0.29.

- Error number: `MY-013842`; Symbol: `ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND`; SQLSTATE: `HY000`

Message: Could not find master key %s in keyring

`ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND` was added in 8.0.29.

- Error number: `MY-013843`; Symbol: `ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_GENERATED`; SQLSTATE: `HY000`

---

Message: A new master key %s could not be generated

[ER\\_PERSISTED\\_VARIABLES\\_MASTER\\_KEY\\_CANNOT\\_BE\\_GENERATED](#) was added in 8.0.29.

- Error number: [MY-013844](#); Symbol: [ER\\_PERSISTED\\_VARIABLES\\_ENCRYPTION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to encrypt %s using %s

[ER\\_PERSISTED\\_VARIABLES\\_ENCRYPTION\\_FAILED](#) was added in 8.0.29.

- Error number: [MY-013845](#); Symbol: [ER\\_PERSISTED\\_VARIABLES\\_DECRYPTION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to decrypt %s using %s

[ER\\_PERSISTED\\_VARIABLES\\_DECRYPTION\\_FAILED](#) was added in 8.0.29.

- Error number: [MY-013846](#); Symbol: [ER\\_PERSISTED\\_VARIABLES\\_LACK\\_KEYRING\\_SUPPORT](#); SQLSTATE: [HY000](#)

Message: Persisting SENSITIVE variables in encrypted form requires keyring component loaded through manifest file.

[ER\\_PERSISTED\\_VARIABLES\\_LACK\\_KEYRING\\_SUPPORT](#) was added in 8.0.29.

- Error number: [MY-013847](#); Symbol: [ER\\_MY\\_MALLOC\\_USING\\_JEMALLOC](#); SQLSTATE: [HY000](#)

Message: Using jemalloc.dll for my\_malloc and ut::malloc etc.

[ER\\_MY\\_MALLOC\\_USING\\_JEMALLOC](#) was added in 8.0.29.

- Error number: [MY-013848](#); Symbol: [ER\\_MY\\_MALLOC\\_USING\\_STD\\_MALLOC](#); SQLSTATE: [HY000](#)

Message: %s.

[ER\\_MY\\_MALLOC\\_USING\\_STD\\_MALLOC](#) was added in 8.0.29.

- Error number: [MY-013849](#); Symbol: [ER\\_MY\\_MALLOC\\_LOADLIBRARY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: %s.

[ER\\_MY\\_MALLOC\\_LOADLIBRARY\\_FAILED](#) was added in 8.0.29.

- Error number: [MY-013850](#); Symbol: [ER\\_MY\\_MALLOC\\_GETPROCADDRESS\\_FAILED](#); SQLSTATE: [HY000](#)

Message: %s.

[ER\\_MY\\_MALLOC\\_GETPROCADDRESS\\_FAILED](#) was added in 8.0.29.

- Error number: [MY-013851](#); Symbol: [ER\\_ACCOUNT\\_WITH\\_EXPIRED\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Password for the account '%s'@'%s' has expired. To log in, either change it using a client that supports expired passwords or send the change request to an administrator.

[ER\\_ACCOUNT\\_WITH\\_EXPIRED\\_PASSWORD](#) was added in 8.0.29.

- Error number: [MY-013852](#); Symbol: [ER\\_THREAD\\_POOL\\_PLUGIN\\_STARTED](#); SQLSTATE: [HY000](#)

---

Message: Thread pool plugin started successfully with parameters: %s

[ER\\_THREAD\\_POOL\\_PLUGIN\\_STARTED](#) was added in 8.0.4.

- Error number: [MY-013853](#); Symbol: [ER\\_THREAD\\_POOL\\_DEDICATED\\_LISTENERS\\_INVALID](#); SQLSTATE: [HY000](#)

Message: thread\_pool\_dedicated\_listeners cannot be set unless thread\_pool\_max\_transactions\_limit > 0

[ER\\_THREAD\\_POOL\\_DEDICATED\\_LISTENERS\\_INVALID](#) was added in 8.0.29.

- Error number: [MY-013854](#); Symbol: [ER\\_IB\\_DBLWR\\_BYTES\\_INFO](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_DBLWR\\_BYTES\\_INFO](#) was added in 8.0.30.

- Error number: [MY-013855](#); Symbol: [ER\\_IB\\_RDBLWR\\_BYTES\\_INFO](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_RDBLWR\\_BYTES\\_INFO](#) was added in 8.0.30.

- Error number: [MY-013856](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_IS\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is empty, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file or try recovering without the redo files, in read-only mode, by providing --innodb-force-recovery=6.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_IS\\_EMPTY](#) was added in 8.0.30.

- Error number: [MY-013857](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_TOO\\_SMALL](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is smaller than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_TOO\\_SMALL](#) was added in 8.0.30.

- Error number: [MY-013858](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_TOO\\_BIG](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is larger than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_TOO\\_BIG](#) was added in 8.0.30.

- Error number: [MY-013859](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_HEADER\\_READ\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to read header of the redo log file %s

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_HEADER\\_READ\\_FAILED](#) was added in 8.0.30.

- 
- Error number: MY-013860; Symbol: ER\_IB\_MSG\_LOG\_INIT\_DIR\_NOT\_EMPTY\_WONT\_INITIALIZE; SQLSTATE: HY000  
Message: --initialize specified but the redo log directory %s has redo log files inside. Aborting.  
ER\_IB\_MSG\_LOG\_INIT\_DIR\_NOT\_EMPTY\_WONT\_INITIALIZE was added in 8.0.30.
  - Error number: MY-013861; Symbol: ER\_IB\_MSG\_LOG\_INIT\_DIR\_LIST\_FAILED; SQLSTATE: HY000  
Message: Failed to list redo log files in the redo log directory %s  
ER\_IB\_MSG\_LOG\_INIT\_DIR\_LIST\_FAILED was added in 8.0.30.
  - Error number: MY-013862; Symbol: ER\_IB\_MSG\_LOG\_INIT\_DIR\_MISSING\_SUBDIR; SQLSTATE: HY000  
Message: Neither found %s subdirectory, nor %s\* files in %s  
ER\_IB\_MSG\_LOG\_INIT\_DIR\_MISSING\_SUBDIR was added in 8.0.30.
  - Error number: MY-013863; Symbol: ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_CLONE\_AND\_READ\_ONLY\_MODE; SQLSTATE: HY000  
Message: Cannot restore cloned data directory, InnoDB running in read-only mode!  
ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_CLONE\_AND\_READ\_ONLY\_MODE was added in 8.0.30.
  - Error number: MY-013864; Symbol: ER\_IB\_MSG\_LOG\_WRITER\_WRITE\_FAILED; SQLSTATE: HY000  
Message: Error %d encountered when writing to the redo log file: %s.  
ER\_IB\_MSG\_LOG\_WRITER\_WRITE\_FAILED was added in 8.0.30.
  - Error number: MY-013865; Symbol: ER\_IB\_MSG\_LOG\_WRITER\_WAIT\_ON\_NEW\_LOG\_FILE; SQLSTATE: HY000  
Message: Redo log writer is waiting for a new redo log file. Consider increasing innodb\_redo\_log\_capacity.  
ER\_IB\_MSG\_LOG\_WRITER\_WAIT\_ON\_NEW\_LOG\_FILE was added in 8.0.30.
  - Error number: MY-013866; Symbol: ER\_IB\_MSG\_RECOVERY\_CHECKPOINT\_OUTSIDE\_LOG\_FILE; SQLSTATE: HY000  
Message: Found checkpoint LSN %llu in a redo log file %s, but the file represents range of LSN values [%llu, %llu), so the file is corrupted.  
ER\_IB\_MSG\_RECOVERY\_CHECKPOINT\_OUTSIDE\_LOG\_FILE was added in 8.0.30.
  - Error number: MY-013867; Symbol: ER\_IB\_MSG\_LOG\_WRITER\_ENTERED\_EXTRA\_MARGIN; SQLSTATE: HY000  
Message: Redo log is running out of free space, pausing user threads... Consider increasing innodb\_redo\_log\_capacity.  
ER\_IB\_MSG\_LOG\_WRITER\_ENTERED\_EXTRA\_MARGIN was added in 8.0.30.
  - Error number: MY-013868; Symbol: ER\_IB\_MSG\_LOG\_WRITER\_EXITED\_EXTRA\_MARGIN; SQLSTATE: HY000

---

Message: Redo log reclaimed some free space, resuming user threads.

`ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN` was added in 8.0.30.

- Error number: `MY-013869`; Symbol: `ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED`; SQLSTATE: `HY000`

Message: Ignored deprecated configuration parameter `innodb_log_file_size`. Used `innodb_redo_log_capacity` instead.

`ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED` was added in 8.0.30.

- Error number: `MY-013870`; Symbol: `ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED`; SQLSTATE: `HY000`

Message: Ignored deprecated configuration parameter `innodb_log_files_in_group`. Used `innodb_redo_log_capacity` instead.

`ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED` was added in 8.0.30.

- Error number: `MY-013871`; Symbol: `ER_IB_MSG_LOG_UPGRADE_FORCED_RECV`; SQLSTATE: `HY000`

Message: Cannot upgrade format (v%lu) of redo log files when `innodb-force-recovery > 0`.

`ER_IB_MSG_LOG_UPGRADE_FORCED_RECV` was added in 8.0.30.

- Error number: `MY-013872`; Symbol: `ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE`; SQLSTATE: `HY000`

Message: Cannot upgrade format (v%lu) of redo log files in read-only mode (`--innodb-read-only`).

`ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE` was added in 8.0.30.

- Error number: `MY-013873`; Symbol: `ER_IB_MSG_LOG_UPGRADE_CLONED_DB`; SQLSTATE: `HY000`

Message: Cannot upgrade format (v%lu) of redo log files on cloned data directory. Please use an older version of MySQL - recover and shutdown (with `innodb-fast-shutdown < 2`).

`ER_IB_MSG_LOG_UPGRADE_CLONED_DB` was added in 8.0.30.

- Error number: `MY-013874`; Symbol: `ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES`; SQLSTATE: `HY000`

Message: Cannot upgrade format (v%lu) of redo log files because they are marked as uninitialized. Please use an older version of MySQL - recover and shutdown (with `innodb-fast-shutdown < 2`).

`ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES` was added in 8.0.30.

- Error number: `MY-013875`; Symbol: `ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED`; SQLSTATE: `HY000`

Message: Cannot upgrade format (v%lu) of redo log files when the redo log is corrupted. Please use an older version of MySQL - recover and shutdown (with `innodb-fast-shutdown < 2`).

`ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED` was added in 8.0.30.

- Error number: `MY-013876`; Symbol: `ER_IB_MSG_LOG_UPGRADE_NON_PERSISTED_DD_METADATA__UNEXPECTED`; SQLSTATE: `HY000`

---

Message: Cannot upgrade format (v%lu) of redo log files when there is non-persisted DD metadata in redo. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

[ER\\_IB\\_MSG\\_LOG\\_UPGRADE\\_NON\\_PERSISTED\\_DD\\_METADATA\\_\\_UNEXPECTED](#) was added in 8.0.30, removed after 8.0.32.

- Error number: [MY-013877](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_UPGRADE\\_FLUSH\\_FAILED\\_\\_UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: Cannot upgrade format (v%lu) of redo log files, because InnoDB failed to reach state in which redo log is logically empty. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

[ER\\_IB\\_MSG\\_LOG\\_UPGRADE\\_FLUSH\\_FAILED\\_\\_UNEXPECTED](#) was added in 8.0.30, removed after 8.0.32.

- Error number: [MY-013878](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_RESIZE\\_ON\\_START\\_FAILED\\_\\_UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: Failed to resize the redo log synchronously, because InnoDB failed to reach state in which redo log is logically empty. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

[ER\\_IB\\_MSG\\_LOG\\_FILES\\_RESIZE\\_ON\\_START\\_FAILED\\_\\_UNEXPECTED](#) was added in 8.0.30, removed after 8.0.32.

- Error number: [MY-013879](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_FOREIGN\\_UUID](#); SQLSTATE: [HY000](#)

Message: The redo log file %s comes from other data directory than redo log file %s.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_FOREIGN\\_UUID](#) was added in 8.0.30.

- Error number: [MY-013880](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_INVALID\\_START\\_LSN](#); SQLSTATE: [HY000](#)

Message: The redo log file %s has invalid start\_lsn %llu.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_INVALID\\_START\\_LSN](#) was added in 8.0.30.

- Error number: [MY-013881](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_INVALID\\_LSN\\_RANGES](#); SQLSTATE: [HY000](#)

Message: The redo log file %s has start\_lsn %llu but expected %llu (end\_lsn of the previous redo log file).

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_INVALID\\_LSN\\_RANGES](#) was added in 8.0.30.

- Error number: [MY-013882](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_MISSING\\_FOR\\_ID](#); SQLSTATE: [HY000](#)

Message: Missing redo log file %s (with start\_lsn = %llu).

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_MISSING\\_FOR\\_ID](#) was added in 8.0.30.

- Error number: [MY-013883](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_CHECKPOINT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: The latest found checkpoint is at lsn = %llu in redo log file %s.

[ER\\_IB\\_MSG\\_LOG\\_CHECKPOINT\\_FOUND](#) was added in 8.0.30.



- 
- Error number: `MY-013884`; Symbol: `ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED`; SQLSTATE: `HY000`  
  
Message: User has set innodb\_redo\_log\_capacity to %lluM.  
  
`ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED` was added in 8.0.30.
  - Error number: `MY-013885`; Symbol: `ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED`; SQLSTATE: `HY000`  
  
Message: Redo log has been requested to resize from %lluM to %lluM.  
  
`ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED` was added in 8.0.30.
  - Error number: `MY-013886`; Symbol: `ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED`; SQLSTATE: `HY000`  
  
Message: Redo log resize has been cancelled.  
  
`ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED` was added in 8.0.30.
  - Error number: `MY-013887`; Symbol: `ER_IB_MSG_LOG_FILES_RESIZE_FINISHED`; SQLSTATE: `HY000`  
  
Message: Redo log has been resized to %lluM.  
  
`ER_IB_MSG_LOG_FILES_RESIZE_FINISHED` was added in 8.0.30.
  - Error number: `MY-013888`; Symbol: `ER_IB_MSG_LOG_FILES_UPGRADE`; SQLSTATE: `HY000`  
  
Message: Upgrading redo log: %lluM, LSN=%llu.  
  
`ER_IB_MSG_LOG_FILES_UPGRADE` was added in 8.0.30.
  - Error number: `MY-013889`; Symbol: `ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE`; SQLSTATE: `HY000`  
  
Message: Marked the current redo log file %s as incomplete.  
  
`ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE` was added in 8.0.30.
  - Error number: `MY-013890`; Symbol: `ER_IB_MSG_LOG_FILE_REMOVE_FAILED`; SQLSTATE: `HY000`  
  
Message: Failed to remove redo log file %s.  
  
`ER_IB_MSG_LOG_FILE_REMOVE_FAILED` was added in 8.0.30.
  - Error number: `MY-013891`; Symbol: `ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED`; SQLSTATE: `HY000`  
  
Message: Failed to rename %s when creating redo log file %s (error: %d)  
  
`ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED` was added in 8.0.30.

- 
- Error number: [MY-013892](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_CREATED\\_BY\\_UNKNOWN\\_CREATOR](#); SQLSTATE: [HY000](#)

Message: Redo log files created by unknown creator %s.

[ER\\_IB\\_MSG\\_LOG\\_FILES\\_CREATED\\_BY\\_UNKNOWN\\_CREATOR](#) was added in 8.0.30.

- Error number: [MY-013893](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_FOUND\\_MISSING](#); SQLSTATE: [HY000](#)

Message: Found existing redo log files, but at least one is missing. It is unknown if recovery could reach physically consistent state. Please consider restoring from backup or providing --innodb-force-recovery > 0.

[ER\\_IB\\_MSG\\_LOG\\_FILES\\_FOUND\\_MISSING](#) was added in 8.0.30.

- Error number: [MY-013894](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_FORMAT\\_TOO\\_NEW](#); SQLSTATE: [HY000](#)

Message: Found redo log file %s which has format (v%lu) and is stored outside #innodb\_redo.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_FORMAT\\_TOO\\_NEW](#) was added in 8.0.30.

- Error number: [MY-013895](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_FORMAT\\_TOO\\_OLD](#); SQLSTATE: [HY000](#)

Message: Found redo log file %s which has format (v%lu) and is stored inside #innodb\_redo.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_FORMAT\\_TOO\\_OLD](#) was added in 8.0.30.

- Error number: [MY-013896](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_DIFFERENT\\_FORMATS](#); SQLSTATE: [HY000](#)

Message: Found redo log files with different formats: %s has format v%lu, %s has format v%lu.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_DIFFERENT\\_FORMATS](#) was added in 8.0.30.

- Error number: [MY-013897](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_PRE\\_8\\_0\\_30\\_MISSING\\_FILE0](#); SQLSTATE: [HY000](#)

Message: Missing ib\_logfile0 in the directory %s.

[ER\\_IB\\_MSG\\_LOG\\_PRE\\_8\\_0\\_30\\_MISSING\\_FILE0](#) was added in 8.0.30.

- Error number: [MY-013898](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_PFS\\_ACQUIRE\\_SERVICES\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize services required to handle redo log PFS tables.

[ER\\_IB\\_MSG\\_LOG\\_PFS\\_ACQUIRE\\_SERVICES\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-013899](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_PFS\\_CREATE\\_TABLES\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create redo log PFS tables.

[ER\\_IB\\_MSG\\_LOG\\_PFS\\_CREATE\\_TABLES\\_FAILED](#) was added in 8.0.30.

- 
- Error number: [MY-013900](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_TRUNCATE](#); SQLSTATE: [HY000](#)

Message: Truncating redo log file %s...

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_TRUNCATE](#) was added in 8.0.30.

- Error number: [MY-013901](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_RESIZE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to resize unused redo log file %s to %llu MB (%s).

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_RESIZE\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-013902](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_REMOVE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to remove unused redo log file %s.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_REMOVE\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-013903](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_RENAME\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to rename unused redo log file %s to %s.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_RENAME\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-013904](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_MARK\\_AS\\_IN\\_USE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to mark unused redo log file %s as in use (by renaming to %s).

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_MARK\\_AS\\_IN\\_USE\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-013905](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_MARK\\_AS\\_UNUSED\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to mark redo log file %s as unused (by renaming to %s).

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_MARK\\_AS\\_UNUSED\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-013906](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_DEDICATED\\_SERVER\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: Option `innodb_dedicated_server` is ignored for `innodb_redo_log_capacity`, because `innodb_redo_log_capacity`, `innodb_log_file_size` or `innodb_log_files_in_group` is specified explicitly. Redo log capacity: %lluM.

[ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_DEDICATED\\_SERVER\\_IGNORED](#) was added in 8.0.30.

- Error number: [MY-013907](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_LEGACY\\_USAGE](#); SQLSTATE: [HY000](#)

Message: Deprecated configuration parameters `innodb_log_file_size` and/or `innodb_log_files_in_group` have been used to compute `innodb_redo_log_capacity=%llu`. Please use `innodb_redo_log_capacity` instead.

[ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_LEGACY\\_USAGE](#) was added in 8.0.30.

- 
- Error number: [MY-013908](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_LOG\\_VIEW\\_CHANGE](#); SQLSTATE: [HY000](#)

Message: This member was unable to log the View\_change\_log\_event into the binary log, hence it will leave the group. Please check that there is available disk space and add the member back to the group.

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_LOG\\_VIEW\\_CHANGE](#) was added in 8.0.29.

- Error number: [MY-013909](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_MALFORMED\\_LOG](#); SQLSTATE: [HY000](#)

Message: Found invalid event sequence while recovering from binary log file '%s', between positions %llu and %llu: %s. The recovery process was stopped early and no transaction was recovered. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the binary log or, to release possibly acquired locks, disable the binary log during server recovery. Note that disabling the binary log may lead to loss of transactions that were already acknowledged as successful to client connections and may have been replicated to other servers in the topology.

[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_MALFORMED\\_LOG](#) was added in 8.0.30.

- Error number: [MY-013910](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ERROR\\_RETURNED\\_SE](#); SQLSTATE: [HY000](#)

Message: Storage engines failed to recover one or more transactions. The recovery process was stopped early, check previous messages for the details on failed transactions. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the storage engine (out-of-memory, no disk space, etc) or, to release possibly acquired locks held by XA transactions, disable the binary log during server recovery and check consistency between storage engines and binary log files.

[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ERROR\\_RETURNED\\_SE](#) was added in 8.0.30.

- Error number: [MY-013911](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ENGINE\\_RESULTS](#); SQLSTATE: [HY000](#)

Message: Crash recovery finished in %s engine. %s

[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ENGINE\\_RESULTS](#) was added in 8.0.30.

- Error number: [MY-013912](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_COMMIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to commit %s in %s, with failure code %s.

[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_COMMIT\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-013913](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ROLLBACK\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to rollback %s in %s, with failure code %s.

[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ROLLBACK\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-013914](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_PREPARE\\_FAILED](#); SQLSTATE: [HY000](#)

---

Message: Failed to prepare %s in %s, with failure code %s.

[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_PREPARE\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-013915](#); Symbol: [ER\\_COMPONENT\\_EE\\_SYS\\_VAR\\_REGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s'. Please check if it is not already registered by another component.

[ER\\_COMPONENT\\_EE\\_SYS\\_VAR\\_REGISTRATION\\_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013916](#); Symbol: [ER\\_COMPONENT\\_EE\\_SYS\\_VAR\\_DEREGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot unregister variable '%s'. Please check if it was registered properly in the first place.

[ER\\_COMPONENT\\_EE\\_SYS\\_VAR\\_DEREGISTRATION\\_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013917](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_REGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register function '%s'. Please check if it is not already registered.

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_REGISTRATION\\_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013918](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_DEREGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_DEREGISTRATION\\_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013919](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_INVALID\\_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: Invalid arguments to function '%s'. Expected values: %s.

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_INVALID\\_ARGUMENTS](#) was added in 8.0.30.

- Error number: [MY-013920](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_INVALID\\_ALGORITHM](#); SQLSTATE: [HY000](#)

Message: Invalid algorithm value '%s' in function %s.

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_INVALID\\_ALGORITHM](#) was added in 8.0.30.

- Error number: [MY-013921](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_KEY\\_LENGTH\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)

Message: Invalid key length '%d' for function '%s' with algorithm '%s'. Please provide a value between [%d, %d].

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_KEY\\_LENGTH\\_OUT\\_OF\\_RANGE](#) was added in 8.0.30.

- Error number: [MY-013922](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_PRIVATE\\_KEY\\_GENERATION\\_FAILURE](#); SQLSTATE: [HY000](#)

---

Message: Failed to generate private key of length '%d' with algorithm '%s' in function '%s'. More details about the error would have been logged before this message.

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_PRIVATE\\_KEY\\_GENERATION\\_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013923](#); Symbol:

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_PUBLIC\\_KEY\\_GENERATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to generate public key with algorithm '%s' for given private key in function '%s'. More details about the error would have been logged before this message.

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_PUBLIC\\_KEY\\_GENERATION\\_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013924](#); Symbol: [ER\\_COMPONENT\\_EE\\_DATA\\_LENGTH\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)

Message: Invalid data length '%d' (in bytes) for function '%s' with algorithm '%s'. The maximum support data length for given private key is %d (in bytes).

[ER\\_COMPONENT\\_EE\\_DATA\\_LENGTH\\_OUT\\_OF\\_RANGE](#) was added in 8.0.30.

- Error number: [MY-013925](#); Symbol: [ER\\_COMPONENT\\_EE\\_DATA\\_ENCRYPTION\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not encrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes. More details about the error would have been logged before this message.

[ER\\_COMPONENT\\_EE\\_DATA\\_ENCRYPTION\\_ERROR](#) was added in 8.0.30.

- Error number: [MY-013926](#); Symbol: [ER\\_COMPONENT\\_EE\\_DATA\\_DECRYPTION\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not decrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes. More details about the error would have been logged before this message.

[ER\\_COMPONENT\\_EE\\_DATA\\_DECRYPTION\\_ERROR](#) was added in 8.0.30.

- Error number: [MY-013927](#); Symbol: [ER\\_COMPONENT\\_EE\\_DATA\\_SIGN\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not sign data in function '%s' using algorithm '%s' and digest type '%s'. More details about the error would have logged before this message.

[ER\\_COMPONENT\\_EE\\_DATA\\_SIGN\\_ERROR](#) was added in 8.0.30.

- Error number: [MY-013928](#); Symbol: [ER\\_COMPONENT\\_EE\\_OPENSSL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Received OpenSSL error in function '%s' for algorithm '%s': '%s'

[ER\\_COMPONENT\\_EE\\_OPENSSL\\_ERROR](#) was added in 8.0.30.

- Error number: [MY-013929](#); Symbol: [ER\\_COMPONENT\\_EE\\_INSUFFICIENT\\_LENGTH](#); SQLSTATE: [HY000](#)

Message: In function '%s' with algorithm '%s': insufficient output buffer length '%zu'. Required length '%zu'.

[ER\\_COMPONENT\\_EE\\_INSUFFICIENT\\_LENGTH](#) was added in 8.0.30.

- 
- Error number: [MY-013930](#); Symbol: [ER\\_SYSTEMD\\_NOTIFY\\_DEBUG](#); SQLSTATE: [HY000](#)  
Message: %s%s  
[ER\\_SYSTEMD\\_NOTIFY\\_DEBUG](#) was added in 8.0.30.
  - Error number: [MY-013931](#); Symbol: [ER\\_TMP\\_SESSION\\_FOR\\_VAR](#); SQLSTATE: [HY000](#)  
Message: Setting session values for system variables only makes sense in a user session (failed to set '%s').  
[ER\\_TMP\\_SESSION\\_FOR\\_VAR](#) was added in 8.0.30.
  - Error number: [MY-013932](#); Symbol: [ER\\_BUILD\\_ID](#); SQLSTATE: [HY000](#)  
Message: BuildID[sha1]=%s  
[ER\\_BUILD\\_ID](#) was added in 8.0.30.
  - Error number: [MY-013933](#); Symbol: [ER\\_THREAD\\_POOL\\_CANNOT\\_REGISTER\\_DYNAMIC\\_PRIVILEGE](#); SQLSTATE: [HY000](#)  
Message: Failed to register dynamic privilege %s.  
[ER\\_THREAD\\_POOL\\_CANNOT\\_REGISTER\\_DYNAMIC\\_PRIVILEGE](#) was added in 8.0.30.
  - Error number: [MY-013934](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_WRITER\\_WAIT\\_ON\\_CONSUMER](#); SQLSTATE: [HY000](#)  
Message: Redo log writer is waiting for %s redo log consumer which is currently reading LSN=%llu preventing reclamation of subsequent portion of the redo log. Consider increasing innodb\_redo\_log\_capacity.  
[ER\\_IB\\_MSG\\_LOG\\_WRITER\\_WAIT\\_ON\\_CONSUMER](#) was added in 8.0.30.
  - Error number: [MY-013935](#); Symbol: [ER\\_CONDITIONAL\\_DEBUG](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_CONDITIONAL\\_DEBUG](#) was added in 8.0.30.
  - Error number: [MY-013936](#); Symbol: [ER\\_IB\\_MSG\\_PARSE\\_OLD\\_REDO\\_INDEX\\_VERSION](#); SQLSTATE: [HY000](#)  
Message: Recovery: Generating index information for INSTANT DDL Table in 8.0.29 format  
[ER\\_IB\\_MSG\\_PARSE\\_OLD\\_REDO\\_INDEX\\_VERSION](#) was added in 8.0.30.
  - Error number: [MY-013937](#); Symbol: [ER\\_RES\\_GRP\\_FAILED\\_TO\\_SWITCH\\_RESOURCE\\_GROUP](#); SQLSTATE: [HY000](#)  
Message: Failed to switch resource group. %s  
[ER\\_RES\\_GRP\\_FAILED\\_TO\\_SWITCH\\_RESOURCE\\_GROUP](#) was added in 8.0.30, removed after 8.0.31.
  - Error number: [MY-013938](#); Symbol: [ER\\_RES\\_GRP\\_SWITCH\\_FAILED\\_COULD\\_NOT\\_ACQUIRE\\_GLOBAL\\_LOCK](#); SQLSTATE: [HY000](#)  
Message: Failed to switch resource group. Could not acquire resource groups global lock.

---

`ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_GLOBAL_LOCK` was added in 8.0.30, removed after 8.0.31.

- Error number: `MY-013939`; Symbol: `ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_LOCK`; SQLSTATE: `HY000`

Message: Failed to switch resource group. Could not acquire lock on resource group %s.

`ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_LOCK` was added in 8.0.30, removed after 8.0.31.

- Error number: `MY-013940`; Symbol: `ER_RES_GRP_SWITCH_FAILED_UNABLE_TO_APPLY_RES_GRP`; SQLSTATE: `HY000`

Message: Failed to switch resource group. Unable to apply resource group controller %s.

`ER_RES_GRP_SWITCH_FAILED_UNABLE_TO_APPLY_RES_GRP` was added in 8.0.30, removed after 8.0.31.

- Error number: `MY-013941`; Symbol: `ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA`; SQLSTATE: `HY000`

Message: Failed to clear instant drop column metadata for table %s

`ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA` was added in 8.0.30.

- Error number: `MY-013942`; Symbol: `ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE`; SQLSTATE: `HY000`

Message: Cannot open signing key file %s.

`ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE` was added in 8.0.31.

- Error number: `MY-013943`; Symbol: `ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY`; SQLSTATE: `HY000`

Message: Out of memory! Cannot create private key.

`ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY` was added in 8.0.31.

- Error number: `MY-013944`; Symbol: `ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE`; SQLSTATE: `HY000`

Message: Cannot read signing key file %s.

`ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE` was added in 8.0.31.

- Error number: `MY-013945`; Symbol: `ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME_OR_TYPE`; SQLSTATE: `HY000`

Message: Incomplete key: missing Name/Type for the Key: %s.

`ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME_OR_TYPE` was added in 8.0.31.

- Error number: `MY-013946`; Symbol: `ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY`; SQLSTATE: `HY000`

Message: Duplicate key found in keyring with Name: %s and Owner: %s.



---

`ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY` was added in 8.0.31.

- Error number: `MY-013947`; Symbol: `ER_KEYRING_OCI_PARSE_JSON`; SQLSTATE: `HY000`  
Message: Error parsing JSON response %s.

`ER_KEYRING_OCI_PARSE_JSON` was added in 8.0.31.

- Error number: `MY-013948`; Symbol: `ER_KEYRING_OCI_INVALID_JSON`; SQLSTATE: `HY000`  
Message: Invalid JSON response!

`ER_KEYRING_OCI_INVALID_JSON` was added in 8.0.31.

- Error number: `MY-013949`; Symbol: `ER_KEYRING_OCI_HTTP_REQUEST`; SQLSTATE: `HY000`  
Message: HTTP request failed with error: '%s'

`ER_KEYRING_OCI_HTTP_REQUEST` was added in 8.0.31.

- Error number: `MY-013950`; Symbol: `ER_THREAD_POOL_SYSVAR_CHANGE`; SQLSTATE: `HY000`  
Message: Variable thread\_pool.%s was updated: %s

`ER_THREAD_POOL_SYSVAR_CHANGE` was added in 8.0.31.

- Error number: `MY-013951`; Symbol: `ER_STACK_BACKTRACE`; SQLSTATE: `HY000`  
Message: %s

`ER_STACK_BACKTRACE` was added in 8.0.31.

- Error number: `MY-013952`; Symbol: `ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CODE`; SQLSTATE: `HY000`  
Message: Status code %u: Completed

`ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CODE` was added in 8.0.31.

- Error number: `MY-013953`; Symbol: `ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE`; SQLSTATE: `HY000`  
Message: Status code %u: %u%% complete

`ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE` was added in 8.0.31.

- Error number: `MY-013954`; Symbol: `ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS`; SQLSTATE: `HY000`  
Message: Status code %u: %s

`ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS` was added in 8.0.31.

- Error number: `MY-013955`; Symbol: `ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID`; SQLSTATE: `HY000`  
Message: Invalid value set to thread\_pool\_query\_threads\_per\_group. Valid value range is %u - %u.

`ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID` was added in 8.0.31.

- 
- Error number: [MY-013956](#); Symbol: [ER\\_THREAD\\_POOL\\_QUERY\\_THRS\\_PER\\_GRP\\_EXCEEDS\\_TXN\\_THR\\_LIMIT](#); SQLSTATE: [HY000](#)  
  
Message: Query threads count(%u) exceeds transaction threads limit(%u) per group. Please use query threads count per group smaller or equal to max transaction threads limit per group  
  
[ER\\_THREAD\\_POOL\\_QUERY\\_THRS\\_PER\\_GRP\\_EXCEEDS\\_TXN\\_THR\\_LIMIT](#) was added in 8.0.31.
  - Error number: [MY-013957](#); Symbol: [ER\\_IB\\_MSG\\_INVALID\\_PAGE\\_TYPE](#); SQLSTATE: [HY000](#)  
  
Message: Found page type mismatch. Expected %u, found %u, in page: space\_id=%lu page\_no= %lu  
  
[ER\\_IB\\_MSG\\_INVALID\\_PAGE\\_TYPE](#) was added in 8.0.32.
  - Error number: [MY-013958](#); Symbol: [ER\\_IB\\_PARALLEL\\_READER\\_WORKER\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: preader: space\_id=%zu, table=%s, index=%s, scan\_ctx=%zu, ctx=%zu, thread\_id=%zu, n\_threads=%zu  
  
[ER\\_IB\\_PARALLEL\\_READER\\_WORKER\\_INFO](#) was added in 8.0.32.
  - Error number: [MY-013959](#); Symbol: [ER\\_IB\\_BULK\\_LOAD\\_SUBTREE\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: bulkload: space\_id=%zu, table=%s, index=%s, height=%zu, n\_extents=%zu, n\_pages=%zu  
  
[ER\\_IB\\_BULK\\_LOAD\\_SUBTREE\\_INFO](#) was added in 8.0.32.
  - Error number: [MY-013960](#); Symbol: [ER\\_IB\\_BULK\\_FLUSHER\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: bulkflusher: sleep\_count=%zu, sleep\_duration=%zu milliseconds, total\_sleep=%zu milliseconds, pages\_flushed=%zu  
  
[ER\\_IB\\_BULK\\_FLUSHER\\_INFO](#) was added in 8.0.32.
  - Error number: [MY-013961](#); Symbol: [ER\\_IB\\_BUFFER\\_POOL\\_OVERUSE](#); SQLSTATE: [HY000](#)  
  
Message: %s: Over 67 percent of the buffer pool (curr\_size=%zu MB) is occupied by lock heaps or the adaptive hash index or BUF\_BLOCK\_MEMORY pages. Check that your transactions do not set too many row locks. Maybe you should make the buffer pool bigger?. Starting the InnoDB Monitor to print diagnostics.  
  
[ER\\_IB\\_BUFFER\\_POOL\\_OVERUSE](#) was added in 8.0.32.
  - Error number: [MY-013962](#); Symbol: [ER\\_IB\\_BUFFER\\_POOL\\_FULL](#); SQLSTATE: [HY000](#)  
  
Message: %s: Over 95 percent of the buffer pool (curr\_size=%zu MB) is occupied by lock heaps or the adaptive hash index or BUF\_BLOCK\_MEMORY pages. Check that your transactions do not set too many row locks. Maybe you should make the buffer pool bigger?. We intentionally generate a seg fault to print a stack trace on Linux!  
  
[ER\\_IB\\_BUFFER\\_POOL\\_FULL](#) was added in 8.0.32.
  - Error number: [MY-013963](#); Symbol: [ER\\_IB\\_DUPLICATE\\_KEY](#); SQLSTATE: [HY000](#)  
  
Message: %s: table=%s, index=%s, n\_uniq=%zu, n\_fields=%zu, lhs=(%s), rhs=(%s)  
  
[ER\\_IB\\_DUPLICATE\\_KEY](#) was added in 8.0.32.

- 
- Error number: [MY-013964](#); Symbol: [ER\\_REPLICATION\\_INCOMPATIBLE\\_TABLE\\_WITH\\_GIPK](#); SQLSTATE: [HY000](#)

Message: Failed to apply row event with %d columns, originating from a server of version %s on table '%s.%s', which has %d columns, one of which is a generated implicit primary key. Replication is unsupported when the source server is older than 8.0.30, the replica table has a generated implicit primary key, and there is a difference in column count, not counting the replica's generated implicit primary key. Align the table schemas on source and replica, and restart replication.

[ER\\_REPLICATION\\_INCOMPATIBLE\\_TABLE\\_WITH\\_GIPK](#) was added in 8.0.32.

- Error number: [MY-013965](#); Symbol: [ER\\_BULK\\_EXECUTOR\\_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk executor: %s

[ER\\_BULK\\_EXECUTOR\\_INFO](#) was added in 8.0.32.

- Error number: [MY-013966](#); Symbol: [ER\\_BULK\\_LOADER\\_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk loader: %s

[ER\\_BULK\\_LOADER\\_INFO](#) was added in 8.0.32.

- Error number: [MY-013967](#); Symbol: [ER\\_BULK\\_LOADER\\_FILE\\_CONTAINS\\_LESS\\_LINES\\_THAN\\_IGNORE\\_CLAUSE\\_LOG](#); SQLSTATE: [HY000](#)

Message: The first file being loaded contained less lines than the ignore clause

[ER\\_BULK\\_LOADER\\_FILE\\_CONTAINS\\_LESS\\_LINES\\_THAN\\_IGNORE\\_CLAUSE\\_LOG](#) was added in 8.0.32.

- Error number: [MY-013968](#); Symbol: [ER\\_BULK\\_READER\\_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk reader: %s

[ER\\_BULK\\_READER\\_INFO](#) was added in 8.0.32.

- Error number: [MY-013969](#); Symbol: [ER\\_BULK\\_READER\\_LIBCURL\\_INIT\\_FAILED\\_LOG](#); SQLSTATE: [HY000](#)

Message: Bulk reader failed to initialize libcurl

[ER\\_BULK\\_READER\\_LIBCURL\\_INIT\\_FAILED\\_LOG](#) was added in 8.0.32.

- Error number: [MY-013970](#); Symbol: [ER\\_BULK\\_READER\\_LIBCURL\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)

Message: Bulk reader got libcurl error: %s

[ER\\_BULK\\_READER\\_LIBCURL\\_ERROR\\_LOG](#) was added in 8.0.32.

- Error number: [MY-013971](#); Symbol: [ER\\_BULK\\_READER\\_SERVER\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)

Message: Bulk reader got error response from server: %ld

[ER\\_BULK\\_READER\\_SERVER\\_ERROR\\_LOG](#) was added in 8.0.32.

- Error number: [MY-013972](#); Symbol: [ER\\_BULK\\_READER\\_COMMUNICATION\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)

---

Message: Bulk reader got error in communication with source server, check the error log for additional details

[ER\\_BULK\\_READER\\_COMMUNICATION\\_ERROR\\_LOG](#) was added in 8.0.32.

- Error number: [MY-013973](#); Symbol: [ER\\_BULK\\_PARSER\\_MISSING\\_ENCLOSED\\_BY\\_LOG](#); SQLSTATE: [HY000](#)

Message: Missing ENCLOSED BY character at row %ld in file %s. Add OPTIONALLY to the ENCLOSED BY clause to allow this input.

[ER\\_BULK\\_PARSER\\_MISSING\\_ENCLOSED\\_BY\\_LOG](#) was added in 8.0.32.

- Error number: [MY-013974](#); Symbol: [ER\\_BULK\\_PARSER\\_ROW\\_BUFFER\\_MAX\\_TOTAL\\_COLS\\_EXCEEDED\\_LOG](#); SQLSTATE: [HY000](#)

Message: The number of input columns that need to be buffered for parsing exceeded predefined buffer max size for file '%s'.

[ER\\_BULK\\_PARSER\\_ROW\\_BUFFER\\_MAX\\_TOTAL\\_COLS\\_EXCEEDED\\_LOG](#) was added in 8.0.32.

- Error number: [MY-013975](#); Symbol: [ER\\_BULK\\_PARSER\\_COPY\\_BUFFER\\_SIZE\\_EXCEEDED\\_LOG](#); SQLSTATE: [HY000](#)

Message: The column data that needed to be copied due to escaped characters exceeded the size of the internal copy buffer for file '%s'.

[ER\\_BULK\\_PARSER\\_COPY\\_BUFFER\\_SIZE\\_EXCEEDED\\_LOG](#) was added in 8.0.32.

- Error number: [MY-013976](#); Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_END\\_OF\\_INPUT\\_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected end of input found at row %ld in file '%s'. Data for some columns is missing.

[ER\\_BULK\\_PARSER\\_UNEXPECTED\\_END\\_OF\\_INPUT\\_LOG](#) was added in 8.0.32.

- Error number: [MY-013977](#); Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_ROW\\_TERMINATOR\\_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected row terminator found at row %ld in file '%s'. Data for some columns is missing.

[ER\\_BULK\\_PARSER\\_UNEXPECTED\\_ROW\\_TERMINATOR\\_LOG](#) was added in 8.0.32.

- Error number: [MY-013978](#); Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_ENDING\\_ENCLOSED\\_BY\\_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected characters after ending ENCLOSED BY character found at row %ld in file '%s'.

[ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_ENDING\\_ENCLOSED\\_BY\\_LOG](#) was added in 8.0.32.

- Error number: [MY-013979](#); Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_NULL\\_ESCAPE\\_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected characters after NULL escape (\N) found at row %ld in file '%s'.

[ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_NULL\\_ESCAPE\\_LOG](#) was added in 8.0.32.

- 
- Error number: [MY-013980](#); Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_COLUMN\\_TERMINATOR\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Unexpected characters after column terminator found at row %ld in file '%s'.  
[ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_COLUMN\\_TERMINATOR\\_LOG](#) was added in 8.0.32.
  - Error number: [MY-013981](#); Symbol: [ER\\_BULK\\_PARSER\\_INCOMPLETE\\_ESCAPE\\_SEQUENCE\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Unexpected end of input found at row %ld in file '%s' resulting in incomplete escape sequence.  
[ER\\_BULK\\_PARSER\\_INCOMPLETE\\_ESCAPE\\_SEQUENCE\\_LOG](#) was added in 8.0.32.
  - Error number: [MY-013982](#); Symbol: [ER\\_LOAD\\_BULK\\_DATA\\_WRONG\\_VALUE\\_FOR\\_FIELD\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Incorrect %s value: '%s' for column '%s' at row %ld in file '%s'  
[ER\\_LOAD\\_BULK\\_DATA\\_WRONG\\_VALUE\\_FOR\\_FIELD\\_LOG](#) was added in 8.0.32.
  - Error number: [MY-013983](#); Symbol: [ER\\_LOAD\\_BULK\\_DATA\\_WARN\\_NULL\\_TO\\_NOTNULL\\_LOG](#); SQLSTATE: [HY000](#)  
Message: NULL supplied to NOT NULL column '%s' at row %ld in file '%s'  
[ER\\_LOAD\\_BULK\\_DATA\\_WARN\\_NULL\\_TO\\_NOTNULL\\_LOG](#) was added in 8.0.32.
  - Error number: [MY-013984](#); Symbol: [ER\\_IB\\_BULK\\_LOAD\\_THREAD\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: %s: LOAD BULK DATA thread failure (err=%lu), table=%s, index=%s  
[ER\\_IB\\_BULK\\_LOAD\\_THREAD\\_FAIL](#) was added in 8.0.32.
  - Error number: [MY-013985](#); Symbol: [ER\\_IB\\_BULK\\_LOAD\\_MERGE\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: %s: Failed to merge sub-trees in LOAD BULK DATA, table=%s, index=%s, details=%s  
[ER\\_IB\\_BULK\\_LOAD\\_MERGE\\_FAIL](#) was added in 8.0.32.
  - Error number: [MY-013986](#); Symbol: [ER\\_IB\\_LOAD\\_BULK\\_CONCURRENCY\\_REDUCED](#); SQLSTATE: [HY000](#)  
Message: LOAD BULK DATA: Buffer pool size is %zu. Reducing concurrency from %zu to %zu. table=%s.  
[ER\\_IB\\_LOAD\\_BULK\\_CONCURRENCY\\_REDUCED](#) was added in 8.0.32.
  - Error number: [MY-013987](#); Symbol: [ER\\_PLUGIN\\_EXCEPTION\\_OPERATION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: C++ Exception caught while %s the %s plugin: [%s]  
[ER\\_PLUGIN\\_EXCEPTION\\_OPERATION\\_FAILED](#) was added in 8.0.32.
  - Error number: [MY-013988](#); Symbol: [ER\\_REQUIRE\\_TABLE\\_PRIMARY\\_KEY\\_CHECK\\_GENERATE\\_WITH\\_GR\\_IN\\_REPO](#); SQLSTATE: [HY000](#)
-

---

Message: Replication configuration appears to be corrupted. On Group Replication channel '%s', setting REQUIRE\_TABLE\_PRIMARY\_KEY\_CHECK to 'GENERATE' is not allowed. Run RESET REPLICA ALL to reset it.

[ER\\_REQUIRE\\_TABLE\\_PRIMARY\\_KEY\\_CHECK\\_GENERATE\\_WITH\\_GR\\_IN\\_REPO](#) was added in 8.0.32.

- Error number: [MY-013989](#); Symbol: [ER\\_CHECK\\_TABLE\\_INSTANT\\_VERSION\\_BIT\\_SET](#); SQLSTATE: [HY000](#)

Message: Record has both instant and version bit set.

[ER\\_CHECK\\_TABLE\\_INSTANT\\_VERSION\\_BIT\\_SET](#) was added in 8.0.32.

- Error number: [MY-013990](#); Symbol: [ER\\_GRP\\_RPL\\_PAXOS\\_SINGLE\\_LEADER\\_DIFF\\_FROM\\_OLD\\_GRP](#); SQLSTATE: [HY000](#)

Message: This member is configured with a group\_replication\_paxos\_single\_leader option value of 1 and it is trying to join a group with Communication Protocol Version below 8.0.27. In order to join this group, group\_replication\_paxos\_single\_leader value must be configured to the value 0. This member will now exit the group.

[ER\\_GRP\\_RPL\\_PAXOS\\_SINGLE\\_LEADER\\_DIFF\\_FROM\\_OLD\\_GRP](#) was added in 8.0.32.

- Error number: [MY-013991](#); Symbol: [ER\\_IB\\_WRN\\_IGNORE\\_REDO\\_LOG\\_CAPACITY](#); SQLSTATE: [HY000](#)

Message: Ignored the innodb-redo-log-capacity option in the Innodb read-only mode. Server is using active redo log files.

[ER\\_IB\\_WRN\\_IGNORE\\_REDO\\_LOG\\_CAPACITY](#) was added in 8.0.32.

- Error number: [MY-013992](#); Symbol: [ER\\_IB\\_PRIMARY\\_KEY\\_IS\\_INSTANT](#); SQLSTATE: [HY000](#)

Message: Unexpected INSTANTLY Added / Dropped column: '%s' at position %lu for Table '%s', Index '%s' while getting Primary Key for row logging

[ER\\_IB\\_PRIMARY\\_KEY\\_IS\\_INSTANT](#) was added in 8.0.32.

- Error number: [MY-013993](#); Symbol: [ER\\_THREAD\\_POOL\\_IDLE\\_CONNECTION\\_CLOSED](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_THREAD\\_POOL\\_IDLE\\_CONNECTION\\_CLOSED](#) was added in 8.0.32.

- Error number: [MY-013994](#); Symbol: [ER\\_IB\\_HIDDEN\\_NAME\\_CONFLICT](#); SQLSTATE: [HY000](#)

Message: Column name %s and internally generated INSTANT DROP column name %s is causing a conflict.

[ER\\_IB\\_HIDDEN\\_NAME\\_CONFLICT](#) was added in 8.0.32.

- Error number: [MY-013995](#); Symbol: [ER\\_IB\\_DICT\\_INVALID\\_COLUMN\\_POSITION](#); SQLSTATE: [HY000](#)

Message: Field number: %llu too large, Total fields in Record: %zu.

[ER\\_IB\\_DICT\\_INVALID\\_COLUMN\\_POSITION](#) was added in 8.0.32.

- Error number: [MY-013996](#); Symbol: [ER\\_IB\\_DICT\\_LOG\\_TABLE\\_INFO](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_DICT\\_LOG\\_TABLE\\_INFO](#) was added in 8.0.32.

- Error number: [MY-013997](#); Symbol: [ER\\_RPL\\_ASYNC\\_NEXT\\_FAILOVER\\_CHANNEL\\_SELECTED](#); SQLSTATE: [HY000](#)

Message: The connection has timed out after %lu retries connecting to '%s@%s:%d%s', and therefore the MySQL server is going to attempt an asynchronous replication connection failover, to '%s@%s:%d'

[ER\\_RPL\\_ASYNC\\_NEXT\\_FAILOVER\\_CHANNEL\\_SELECTED](#) was added in 8.0.33.

- Error number: [MY-013998](#); Symbol: [ER\\_RPL\\_REPLICA\\_SOURCE\\_UUID\\_HAS\\_NOT\\_CHANGED](#); SQLSTATE: [HY000](#)

Message: The Replica which was connected to source '%s:%d', is now connected to new source '%s:%d', but still has the same server\_uuid %s.

[ER\\_RPL\\_REPLICA\\_SOURCE\\_UUID\\_HAS\\_NOT\\_CHANGED](#) was added in 8.0.33.

- Error number: [MY-013999](#); Symbol: [ER\\_RPL\\_REPLICA\\_SOURCE\\_UUID\\_HAS\\_CHANGED\\_HOST\\_PORT\\_UNCHANGED](#); SQLSTATE: [HY000](#)

Message: The server\_uuid for source server '%s:%d' has changed from %s to %s. This should not happen unless you have changed it manually.

[ER\\_RPL\\_REPLICA\\_SOURCE\\_UUID\\_HAS\\_CHANGED\\_HOST\\_PORT\\_UNCHANGED](#) was added in 8.0.33.

- Error number: [MY-014000](#); Symbol: [ER\\_RPL\\_REPLICA\\_SOURCE\\_UUID\\_HOST\\_PORT\\_HAS\\_CHANGED](#); SQLSTATE: [HY000](#)

Message: The source server has changed from '%s:%d' with server\_uuid %s, to '%s:%d' with server\_uuid %s.

[ER\\_RPL\\_REPLICA\\_SOURCE\\_UUID\\_HOST\\_PORT\\_HAS\\_CHANGED](#) was added in 8.0.33.

- Error number: [MY-014001](#); Symbol: [ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_RPL\\_STARTED\\_FILE\\_BASED](#); SQLSTATE: [HY000](#)

Message: Replica receiver thread%s: connected to source '%s@%s:%d' with server\_uuid=%s, server\_id=%d. Starting replication from file '%s', position '%s'.

[ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_RPL\\_STARTED\\_FILE\\_BASED](#) was added in 8.0.33.

- Error number: [MY-014002](#); Symbol: [ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_RPL\\_STARTED\\_GTID\\_BASED](#); SQLSTATE: [HY000](#)

Message: Replica receiver thread%s: connected to source '%s@%s:%d' with server\_uuid=%s, server\_id=%d. Starting GTID-based replication.

[ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_RPL\\_STARTED\\_GTID\\_BASED](#) was added in 8.0.33.

- Error number: [MY-014003](#); Symbol: [ER\\_IB\\_INDEX\\_LOADER\\_DONE](#); SQLSTATE: [HY000](#)

Message: Loader::build\_all(): Completed building %zu indexes for old\_table=%s, new\_table=%s, err=%zu.

[ER\\_IB\\_INDEX\\_LOADER\\_DONE](#) was added in 8.0.32.

- 
- Error number: [MY-014004](#); Symbol: [ER\\_IB\\_INDEX\\_BUILDER\\_DONE](#); SQLSTATE: [HY000](#)  
  
Message: Builder::finish(): Completed building index=%s of table=%s, err=%zu.  
  
[ER\\_IB\\_INDEX\\_BUILDER\\_DONE](#) was added in 8.0.32.
  - Error number: [MY-014005](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_USER\\_DEFINED\\_COLLATIONS\\_OPTION](#); SQLSTATE: [HY000](#)  
  
Message: %s: '%s' is a user defined collation. User defined collations are deprecated and will be removed in a future release. Consider using a compiled collation instead.  
  
[ER\\_WARN\\_DEPRECATED\\_USER\\_DEFINED\\_COLLATIONS\\_OPTION](#) was added in 8.0.33.
  - Error number: [MY-014006](#); Symbol: [ER\\_IB\\_INDEX\\_BUILDER\\_INIT](#); SQLSTATE: [HY000](#)  
  
Message: Builder::init(): Initialize for building index=%s of table=%s, n\_threads=%zu, sort buffer size=%zu bytes, i/o buffer size=%zu bytes.  
  
[ER\\_IB\\_INDEX\\_BUILDER\\_INIT](#) was added in 8.0.33.
  - Error number: [MY-014007](#); Symbol: [ER\\_IB\\_SELECT\\_COUNT\\_STAR](#); SQLSTATE: [HY000](#)  
  
Message: SELECT COUNT(\*) FROM table=%s, n\_threads=%zu, n\_partitions=%zu.  
  
[ER\\_IB\\_SELECT\\_COUNT\\_STAR](#) was added in 8.0.33.
  - Error number: [MY-014008](#); Symbol: [ER\\_IB\\_INDEX\\_LOG\\_VERSION\\_MISMATCH](#); SQLSTATE: [HY000](#)  
  
Message: Index log version %u did not match. Max index version is %u. Recovery can't continue. Please make sure server is not starting up with the datadir generated in future version.  
  
[ER\\_IB\\_INDEX\\_LOG\\_VERSION\\_MISMATCH](#) was added in 8.0.33.
  - Error number: [MY-014009](#); Symbol: [ER\\_WARN\\_COMPONENTS\\_INFRASTRUCTURE\\_MANIFEST\\_MULTIPLE\\_KEYRING](#); SQLSTATE: [HY000](#)  
  
Message: Multiple keyring component URNs '%s' found in manifest file '%s'. Only one keyring component can be loaded at a time.  
  
[ER\\_WARN\\_COMPONENTS\\_INFRASTRUCTURE\\_MANIFEST\\_MULTIPLE\\_KEYRING](#) was added in 8.0.33.
  - Error number: [MY-014010](#); Symbol: [ER\\_GRP\\_RPL\\_HAS\\_STARTED](#); SQLSTATE: [HY000](#)  
  
Message: Plugin 'group\_replication' has been started.  
  
[ER\\_GRP\\_RPL\\_HAS\\_STARTED](#) was added in 8.0.33.
  - Error number: [MY-014011](#); Symbol: [ER\\_CHECK\\_TABLE\\_MIN\\_REC\\_FLAG\\_SET](#); SQLSTATE: [HY000](#)  
  
Message: Minimum record flag is wrongly set to rec on page '%lu' at level '%lu' for index '%s' of table '%s'.  
  
[ER\\_CHECK\\_TABLE\\_MIN\\_REC\\_FLAG\\_SET](#) was added in 8.0.33.



- 
- Error number: [MY-014012](#); Symbol: [ER\\_CHECK\\_TABLE\\_MIN\\_REC\\_FLAG\\_NOT\\_SET](#); SQLSTATE: [HY000](#)  
  
Message: Minimum record flag is not set to first rec on page '%lu' at level '%lu' for index '%s' of table '%s'.  
  
[ER\\_CHECK\\_TABLE\\_MIN\\_REC\\_FLAG\\_NOT\\_SET](#) was added in 8.0.33.
  - Error number: [MY-014013](#); Symbol: [ER\\_NOTE\\_COMPONENT\\_SLOT\\_REGISTRATION\\_SUCCESS](#); SQLSTATE: [HY000](#)  
  
Message: Successfully registered slot '%d' for component '%s'.  
  
[ER\\_NOTE\\_COMPONENT\\_SLOT\\_REGISTRATION\\_SUCCESS](#) was added in 8.0.33.
  - Error number: [MY-014014](#); Symbol: [ER\\_NOTE\\_COMPONENT\\_SLOT\\_DEREGISTRATION\\_SUCCESS](#); SQLSTATE: [HY000](#)  
  
Message: Successfully de-registered slot '%d' from component '%s'.  
  
[ER\\_NOTE\\_COMPONENT\\_SLOT\\_DEREGISTRATION\\_SUCCESS](#) was added in 8.0.33.
  - Error number: [MY-014015](#); Symbol: [ER\\_WARN\\_CANNOT\\_FREE\\_COMPONENT\\_DATA\\_DEALLOCATION\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Cannot free resources stored by component '%s' in thread with ID: '%d'. Component failed to free required resources.  
  
[ER\\_WARN\\_CANNOT\\_FREE\\_COMPONENT\\_DATA\\_DEALLOCATION\\_FAILED](#) was added in 8.0.33.
  - Error number: [MY-014016](#); Symbol: [ER\\_IB\\_RESURRECT\\_TRX\\_INSERT](#); SQLSTATE: [HY000](#)  
  
Message: Transaction ID: %lu found for resurrecting inserts  
  
[ER\\_IB\\_RESURRECT\\_TRX\\_INSERT](#) was added in 8.0.33.
  - Error number: [MY-014017](#); Symbol: [ER\\_IB\\_RESURRECT\\_TRX\\_UPDATE](#); SQLSTATE: [HY000](#)  
  
Message: Transaction ID: %lu found for resurrecting updates  
  
[ER\\_IB\\_RESURRECT\\_TRX\\_UPDATE](#) was added in 8.0.33.
  - Error number: [MY-014018](#); Symbol: [ER\\_IB\\_RESURRECT\\_IDENTIFY\\_TABLE\\_TO\\_LOCK](#); SQLSTATE: [HY000](#)  
  
Message: Identified table ID: %lu to acquire lock  
  
[ER\\_IB\\_RESURRECT\\_IDENTIFY\\_TABLE\\_TO\\_LOCK](#) was added in 8.0.33.
  - Error number: [MY-014019](#); Symbol: [ER\\_IB\\_RESURRECT\\_ACQUIRE\\_TABLE\\_LOCK](#); SQLSTATE: [HY000](#)  
  
Message: Acquired lock on table ID: %lu, name: %s  
  
[ER\\_IB\\_RESURRECT\\_ACQUIRE\\_TABLE\\_LOCK](#) was added in 8.0.33.

- 
- Error number: [MY-014020](#); Symbol: [ER\\_IB\\_RESURRECT\\_RECORD\\_PROGRESS](#); SQLSTATE: [HY000](#)  
Message: Records read: %lu - Pages read: %lu  
[ER\\_IB\\_RESURRECT\\_RECORD\\_PROGRESS](#) was added in 8.0.33.
  - Error number: [MY-014021](#); Symbol: [ER\\_IB\\_RESURRECT\\_RECORD\\_COMPLETE](#); SQLSTATE: [HY000](#)  
Message: Total records resurrected: %lu - Total pages read: %lu - Total tables acquired: %lu  
[ER\\_IB\\_RESURRECT\\_RECORD\\_COMPLETE](#) was added in 8.0.33.
  - Error number: [MY-014022](#); Symbol: [ER\\_IB\\_RESURRECT\\_TRX\\_INSERT\\_COMPLETE](#); SQLSTATE: [HY000](#)  
Message: Resurrected %lu transactions doing inserts.  
[ER\\_IB\\_RESURRECT\\_TRX\\_INSERT\\_COMPLETE](#) was added in 8.0.33.
  - Error number: [MY-014023](#); Symbol: [ER\\_IB\\_RESURRECT\\_TRX\\_UPDATE\\_COMPLETE](#); SQLSTATE: [HY000](#)  
Message: Resurrected %lu transactions doing updates.  
[ER\\_IB\\_RESURRECT\\_TRX\\_UPDATE\\_COMPLETE](#) was added in 8.0.33.
  - Error number: [MY-014024](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_INVALID\\_TOKEN](#); SQLSTATE: [HY000](#)  
Message: Invalid security token provided by '%s' for '%s'@'%s': %s.  
[ER\\_AUTHENTICATION\\_OCI\\_INVALID\\_TOKEN](#) was added in 8.0.33.
  - Error number: [MY-014025](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_TOKEN\\_DETAILS\\_MISMATCH](#); SQLSTATE: [HY000](#)  
Message: Unknown user/tenancy (user: %s tenancy: %s) found in security token provided by '%s' for '%s'@'%s'.  
[ER\\_AUTHENTICATION\\_OCI\\_TOKEN\\_DETAILS\\_MISMATCH](#) was added in 8.0.33.
  - Error number: [MY-014026](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_TOKEN\\_NOT\\_VERIFIED](#); SQLSTATE: [HY000](#)  
Message: Verification failed for security token provided by '%s' for '%s'@'%s' : %s.  
[ER\\_AUTHENTICATION\\_OCI\\_TOKEN\\_NOT\\_VERIFIED](#) was added in 8.0.33.
  - Error number: [MY-014027](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_DOWNLOAD\\_IDDP\\_PUBLIC\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Could not download IDDP Public key. Please check if security token provided by '%s' for '%s'@'%s' is valid.  
[ER\\_AUTHENTICATION\\_OCI\\_DOWNLOAD\\_IDDP\\_PUBLIC\\_KEY](#) was added in 8.0.33.
  - Error number: [MY-014028](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_NO\\_MATCHING\\_GROUPS\\_IN\\_TOKEN](#); SQLSTATE: [HY000](#)

---

Message: None of the groups extracted from security token matches any of the entries from authentication string.

[ER\\_AUTHENTICATION\\_OCI\\_NO\\_MATCHING\\_GROUPS\\_IN\\_TOKEN](#) was added in 8.0.33, removed after 8.0.33.

- Error number: [MY-014029](#); Symbol: [ER\\_SYS\\_VAR\\_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s'. Please check if it is not already registered by another component.

[ER\\_SYS\\_VAR\\_REGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014030](#); Symbol: [ER\\_SYS\\_VAR\\_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister variable '%s'. Please check if it was registered properly in the first place.

[ER\\_SYS\\_VAR\\_DEREGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014031](#); Symbol: [ER\\_UDF\\_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register function '%s'. Please check if it is not already registered by another component.

[ER\\_UDF\\_REGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014032](#); Symbol: [ER\\_UDF\\_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

[ER\\_UDF\\_DEREGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014033](#); Symbol: [ER\\_PRIVILEGE\\_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register privilege '%s'. Please check if it is not already registered.

[ER\\_PRIVILEGE\\_REGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014034](#); Symbol: [ER\\_PRIVILEGE\\_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister privilege '%s'. Please check if it was registered properly in the first place.

[ER\\_PRIVILEGE\\_DEREGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014035](#); Symbol: [ER\\_UDF\\_EXEC\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error while executing UDF %s.

[ER\\_UDF\\_EXEC\\_FAILURE](#) was added in 8.0.33.

- Error number: [MY-014036](#); Symbol: [ER\\_UDF\\_EXEC\\_FAILURE\\_REASON](#); SQLSTATE: [HY000](#)

Message: Error while executing UDF %s: %s.

[ER\\_UDF\\_EXEC\\_FAILURE\\_REASON](#) was added in 8.0.33.

- Error number: [MY-014037](#); Symbol: [ER\\_COMPONENT\\_SERVICE\\_CALL](#); SQLSTATE: [HY000](#)

Message: %s failed.

---

`ER_COMPONENT_SERVICE_CALL` was added in 8.0.33.

- Error number: `MY-014038`; Symbol: `ER_COMPONENT_SERVICE_CALL_RESULT`; SQLSTATE: `HY000`  
Message: %s failed with %u.

`ER_COMPONENT_SERVICE_CALL_RESULT` was added in 8.0.33.

- Error number: `MY-014039`; Symbol: `ER_COMPONENT_LOCK`; SQLSTATE: `HY000`  
Message: Lock failed at %s : %u.

`ER_COMPONENT_LOCK` was added in 8.0.33.

- Error number: `MY-014040`; Symbol: `ER_COMPONENT_UNLOCK`; SQLSTATE: `HY000`  
Message: Lock from %s : %u failed to unlock.

`ER_COMPONENT_UNLOCK` was added in 8.0.33.

- Error number: `MY-014041`; Symbol: `ER_COMPONENT_MASKING_OTHER_ERROR`; SQLSTATE: `HY000`  
Message: Masking component error: '%s'.

`ER_COMPONENT_MASKING_OTHER_ERROR` was added in 8.0.33.

- Error number: `MY-014042`; Symbol: `ER_COMPONENT_MASKING_ABI`; SQLSTATE: `HY000`  
Message: %s failed.

`ER_COMPONENT_MASKING_ABI` was added in 8.0.33.

- Error number: `MY-014043`; Symbol: `ER_COMPONENT_MASKING_ABI_REASON`; SQLSTATE: `HY000`  
Message: %s failed because %s.

`ER_COMPONENT_MASKING_ABI_REASON` was added in 8.0.33.

- Error number: `MY-014044`; Symbol: `ER_COMPONENT_MASKING_RANDOM_CREATE`; SQLSTATE: `HY000`  
Message: Creation of random context failed.

`ER_COMPONENT_MASKING_RANDOM_CREATE` was added in 8.0.33.

- Error number: `MY-014045`; Symbol: `ER_COMPONENT_MASKING_RANDOM_CREATE_REASON`; SQLSTATE: `HY000`  
Message: Creation of random context failed because %s.

`ER_COMPONENT_MASKING_RANDOM_CREATE_REASON` was added in 8.0.33.

- Error number: `MY-014046`; Symbol: `ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE`; SQLSTATE: `HY000`  
Message: Cannot access %s.%s table.

`ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE` was added in 8.0.33.

- Error number: `MY-014047`; Symbol: `ER_REDUCED_DBLWR_FILE_CORRUPTED`; SQLSTATE: `HY000`

---

Message: Cannot recover from detect\_only doublewrite buffer as page %u from batch doublewrite file is corrupted.

[ER\\_REDUCED\\_DBLWR\\_FILE\\_CORRUPTED](#) was added in 8.0.30.

- Error number: [MY-014048](#); Symbol: [ER\\_REDUCED\\_DBLWR\\_PAGE\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Database page corruption of tablespace %s space\_id: %u page\_num: %u. Cannot recover it from the doublewrite buffer because it was written in detect\_only-doublewrite mode.

[ER\\_REDUCED\\_DBLWR\\_PAGE\\_FOUND](#) was added in 8.0.30.

- Error number: [MY-014049](#); Symbol: [ER\\_CONN\\_INIT\\_CONNECT\\_IGNORED\\_MFA](#); SQLSTATE: [HY000](#)

Message: init\_connect variable is ignored for user: %s host: %s due to multi-factor registration required sandboxing

[ER\\_CONN\\_INIT\\_CONNECT\\_IGNORED\\_MFA](#) was added in 8.0.33.

- Error number: [MY-014050](#); Symbol: [ER\\_SECONDARY\\_ENGINE\\_DDL\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Execution of alter table %s %s failed because %s.

[ER\\_SECONDARY\\_ENGINE\\_DDL\\_FAILED](#) was added in 8.0.33.

- Error number: [MY-014051](#); Symbol: [ER\\_THREAD\\_POOL\\_CONNECTION\\_REPORT](#); SQLSTATE: [HY000](#)

Message: TP conn (port: managed(delta), active, opened, closed, added, dropped): %s

[ER\\_THREAD\\_POOL\\_CONNECTION\\_REPORT](#) was added in 8.0.33.

- Error number: [MY-014052](#); Symbol: [ER\\_WARN\\_SCHEDULED\\_TASK\\_RUN\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Scheduled run of task %s failed

[ER\\_WARN\\_SCHEDULED\\_TASK\\_RUN\\_FAILED](#) was added in 8.0.34.

- Error number: [MY-014053](#); Symbol: [ER\\_AUDIT\\_LOG\\_INVALID\\_FLUSH\\_INTERVAL\\_VALUE](#); SQLSTATE: [HY000](#)

Message: Invalid flush interval specified: %lu. Valid values are 0 (off) or greater than or equal to %d. Adjusting to %d

[ER\\_AUDIT\\_LOG\\_INVALID\\_FLUSH\\_INTERVAL\\_VALUE](#) was added in 8.0.34.

- Error number: [MY-014054](#); Symbol: [ER\\_LOG\\_CANNOT\\_PURGE\\_BINLOG\\_WITH\\_BACKUP\\_LOCK](#); SQLSTATE: [HY000](#)

Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.

[ER\\_LOG\\_CANNOT\\_PURGE\\_BINLOG\\_WITH\\_BACKUP\\_LOCK](#) was added in 8.0.34.

- Error number: [MY-014055](#); Symbol: [ER\\_CONVERT\\_MULTI\\_VALUE](#); SQLSTATE: [HY000](#)

Message: Multi-values cannot be converted to MySQL format: %s

[ER\\_CONVERT\\_MULTI\\_VALUE](#) was added in 8.0.35.

- 
- Error number: [MY-014056](#); Symbol: [ER\\_IB\\_DDL\\_CONVERT\\_HEAP\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: Heap required to convert columns is not present.  
[ER\\_IB\\_DDL\\_CONVERT\\_HEAP\\_NOT\\_FOUND](#) was added in 8.0.35.
  - Error number: [MY-014057](#); Symbol: [ER\\_SERVER\\_DOWNGRADE\\_FROM\\_VERSION](#); SQLSTATE: [HY000](#)  
Message: MySQL server downgrading from version '%u' to '%u'.  
[ER\\_SERVER\\_DOWNGRADE\\_FROM\\_VERSION](#) was added in 8.0.35.
  - Error number: [MY-014058](#); Symbol: [ER\\_BEYOND\\_SERVER\\_DOWNGRADE\\_THRESHOLD](#); SQLSTATE: [HY000](#)  
Message: Invalid MySQL server downgrade: Cannot downgrade from %u to %u. Target MySQL server version is lower than the server downgrade threshold %u.  
[ER\\_BEYOND\\_SERVER\\_DOWNGRADE\\_THRESHOLD](#) was added in 8.0.35.
  - Error number: [MY-014059](#); Symbol: [ER\\_BEYOND\\_SERVER\\_UPGRADE\\_THRESHOLD](#); SQLSTATE: [HY000](#)  
Message: Invalid MySQL server upgrade: Cannot upgrade from %u to %u. Target MySQL server version is lower than the server upgrade threshold %u.  
[ER\\_BEYOND\\_SERVER\\_UPGRADE\\_THRESHOLD](#) was added in 8.0.35.
  - Error number: [MY-014060](#); Symbol: [ER\\_INVALID\\_SERVER\\_UPGRADE\\_NOT\\_LTS](#); SQLSTATE: [HY000](#)  
Message: Invalid MySQL server upgrade: Cannot upgrade from %u to %u. Upgrade to next major version is only allowed from the last LTS release, which version %u is not.  
[ER\\_INVALID\\_SERVER\\_UPGRADE\\_NOT\\_LTS](#) was added in 8.0.35.
  - Error number: [MY-014061](#); Symbol: [ER\\_INVALID\\_SERVER\\_DOWNGRADE\\_NOT\\_PATCH](#); SQLSTATE: [HY000](#)  
Message: Invalid MySQL server downgrade: Cannot downgrade from %u to %u. Downgrade is only permitted between patch releases.  
[ER\\_INVALID\\_SERVER\\_DOWNGRADE\\_NOT\\_PATCH](#) was added in 8.0.35.
  - Error number: [MY-014062](#); Symbol: [ER\\_FAILED\\_GET\\_DD\\_PROPERTY](#); SQLSTATE: [HY000](#)  
Message: Failed to get the data dictionary property %s.  
[ER\\_FAILED\\_GET\\_DD\\_PROPERTY](#) was added in 8.0.35.
  - Error number: [MY-014063](#); Symbol: [ER\\_FAILED\\_SET\\_DD\\_PROPERTY](#); SQLSTATE: [HY000](#)  
Message: Failed to set the data dictionary property %s.  
[ER\\_FAILED\\_SET\\_DD\\_PROPERTY](#) was added in 8.0.35.
  - Error number: [MY-014064](#); Symbol: [ER\\_SERVER\\_DOWNGRADE\\_STATUS](#); SQLSTATE: [HY000](#)  
Message: Server downgrade from '%d' to '%d' %s.  
[ER\\_SERVER\\_DOWNGRADE\\_STATUS](#) was added in 8.0.35.

- 
- Error number: [MY-014065](#); Symbol: [ER\\_INFORMATION\\_SCHEMA\\_VERSION\\_CHANGE](#); SQLSTATE: [HY000](#)  
  
Message: %s information schema from version %u to %u.  
  
[ER\\_INFORMATION\\_SCHEMA\\_VERSION\\_CHANGE](#) was added in 8.0.35.
  - Error number: [MY-014066](#); Symbol: [ER\\_PERFORMANCE\\_SCHEMA\\_VERSION\\_CHANGE](#); SQLSTATE: [HY000](#)  
  
Message: %s performance schema from version %u to %u.  
  
[ER\\_PERFORMANCE\\_SCHEMA\\_VERSION\\_CHANGE](#) was added in 8.0.35.
  - Error number: [MY-014067](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_OR\\_BLOCKED\\_CIPHER](#); SQLSTATE: [HY000](#)  
  
Message: Value for option '%s' contains cipher '%s' that is either blocked or deprecated (and will be removed in a future release). Please refer to the documentation for more details.  
  
[ER\\_WARN\\_DEPRECATED\\_OR\\_BLOCKED\\_CIPHER](#) was added in 8.0.35.
  - Error number: [MY-014068](#); Symbol: [ER\\_IB\\_MSG\\_DDL\\_FAIL\\_NO\\_BUILDER](#); SQLSTATE: [HY000](#)  
  
Message: DDL failed as Builder is already freed. Builder: state=%u, error\_state=%u. Index: id=%zu, name='%s', space\_id=%u, page=%u. Table: old\_name='%s', new\_name='%s'.  
  
[ER\\_IB\\_MSG\\_DDL\\_FAIL\\_NO\\_BUILDER](#) was added in 8.0.36.
  - Error number: [MY-014069](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_INFO\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
  
Message: Member identified %s: '%s' does not exist on Group Replication membership during %s.  
  
[ER\\_GRP\\_RPL\\_MEMBER\\_INFO\\_DOES\\_NOT\\_EXIST](#) was added in 8.0.36.
  - Error number: [MY-014070](#); Symbol: [ER\\_USAGE\\_DEPRECATION\\_COUNTER](#); SQLSTATE: [HY000](#)  
  
Message: Deprecated '%s' used %s times, last time used '%s'.  
  
[ER\\_USAGE\\_DEPRECATION\\_COUNTER](#) was added in 8.0.36.
  - Error number: [MY-014071](#); Symbol: [ER\\_WAITING\\_FOR\\_NO\\_CONNECTIONS](#); SQLSTATE: [HY000](#)  
  
Message: Waiting for %u connections to be closed.  
  
[ER\\_WAITING\\_FOR\\_NO\\_CONNECTIONS](#) was added in 8.0.38.
  - Error number: [MY-014072](#); Symbol: [ER\\_WAITING\\_FOR\\_NO\\_THDS](#); SQLSTATE: [HY000](#)  
  
Message: Waiting for THDs in partition %u to be closed, %u still left. %u THDs left in total for all partitions.  
  
[ER\\_WAITING\\_FOR\\_NO\\_THDS](#) was added in 8.0.38.

- 
- Error number: [MY-014073](#); Symbol: [ER\\_IB\\_INDEX\\_PART\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)

Message: Index %s of %s.%s exceeds limit of %lu bytes per column.

[ER\\_IB\\_INDEX\\_PART\\_TOO\\_LONG](#) was added in 8.0.38.

- Error number: [MY-014074](#); Symbol: [ER\\_DD\\_UPDATE\\_DATADIR\\_FLAG\\_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to update data directory flag for dd table with tablespace id '%llu' when ibd file for '%s' is moved to new location '%s' during server shutdown

[ER\\_DD\\_UPDATE\\_DATADIR\\_FLAG\\_FAIL](#) was added in 8.0.38.

- Error number: [MY-014075](#); Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_PREV](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Tablespace %u, name '%s', found at '%s' outside default data directory, but DD misses info about DATA DIRECTORY

[ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_PREV](#) was added in 8.0.38.

- Error number: [MY-014075](#); Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_PREV\\_OR\\_HAS\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Tablespace %u, name '%s', found at '%s' outside default data directory. It is either moved or is created with 'DATA DIRECTORY'

[ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_PREV\\_OR\\_HAS\\_DATADIR](#) was added in 8.0.39, removed after 8.0.40.

- Error number: [MY-014076](#); Symbol: [ER\\_RPL\\_KILL\\_OLD\\_DUMP\\_THREAD\\_ENCOUNTED](#); SQLSTATE: [HY000](#)

Message: Upon reconnection with the replica, while initializing the dump thread for %s <%s>, an existing dump thread with the same %s was detected. The source is terminating the previous dump thread (%u), which is normal and expected.

[ER\\_RPL\\_KILL\\_OLD\\_DUMP\\_THREAD\\_ENCOUNTED](#) was added in 8.0.41.

- Error number: [MY-014077](#); Symbol: [ER\\_RPL\\_MTA\\_ALLOW\\_COMMIT\\_OUT\\_OF\\_ORDER](#); SQLSTATE: [HY000](#)

Message: The transaction '%s' will commit out of order with respect to its source to follow the group global order.

[ER\\_RPL\\_MTA\\_ALLOW\\_COMMIT\\_OUT\\_OF\\_ORDER](#) was added in 8.0.41.

- Error number: [MY-014078](#); Symbol: [ER\\_CHECK\\_TABLE\\_FUNCTIONS](#); SQLSTATE: [HY000](#)

Message: Can not open table '%s`.`%s`; functions in constraints, partitions, or virtual columns may have failed.

[ER\\_CHECK\\_TABLE\\_FUNCTIONS](#) was added in 8.0.42.

- Error number: [MY-014079](#); Symbol: [ER\\_CHECK\\_TABLE\\_FUNCTIONS\\_DETAIL](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_CHECK\\_TABLE\\_FUNCTIONS\\_DETAIL](#) was added in 8.0.42.



- 
- Error number: [MY-014080](#); Symbol: [ER\\_GRP\\_RPL\\_CERT\\_BROADCAST\\_THREAD\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Failed to create the Group Replication certifier broadcast thread (THD\_certifier\_broadcast).  
  
[ER\\_GRP\\_RPL\\_CERT\\_BROADCAST\\_THREAD\\_CREATE\\_FAILED](#) was added in 8.0.42.
  - Error number: [MY-014081](#); Symbol: [ER\\_GRP\\_RPL\\_CERT\\_BROADCAST\\_THREAD\\_STARTED](#); SQLSTATE: [HY000](#)  
  
Message: The Group Replication certifier broadcast thread (THD\_certifier\_broadcast) started.  
  
[ER\\_GRP\\_RPL\\_CERT\\_BROADCAST\\_THREAD\\_STARTED](#) was added in 8.0.42.
  - Error number: [MY-014082](#); Symbol: [ER\\_GRP\\_RPL\\_CERT\\_BROADCAST\\_THREAD\\_STOPPED](#); SQLSTATE: [HY000](#)  
  
Message: The Group Replication certifier broadcast thread (THD\_certifier\_broadcast) stopped.  
  
[ER\\_GRP\\_RPL\\_CERT\\_BROADCAST\\_THREAD\\_STOPPED](#) was added in 8.0.42.
  - Error number: [MY-014083](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_KILLED\\_BY\\_SQL\\_KILL](#); SQLSTATE: [HY000](#)  
  
Message: The group replication applier thread has received KILL request.  
  
[ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_KILLED\\_BY\\_SQL\\_KILL](#) was added in 8.0.43.
  - Error number: [MY-014084](#); Symbol: [ER\\_IB\\_MSG\\_WAITING\\_ON\\_LAGGING\\_REDO\\_LOG\\_CONSUMER](#); SQLSTATE: [HY000](#)  
  
Message: Threads are unable to reserve space in redo log which can't be reclaimed due to the '%s' consumer still lagging behind at LSN = %llu. Consider increasing innodb\_redo\_log\_capacity.  
  
[ER\\_IB\\_MSG\\_WAITING\\_ON\\_LAGGING\\_REDO\\_LOG\\_CONSUMER](#) was added in 8.0.43.
  - Error number: [MY-014085](#); Symbol: [ER\\_IB\\_MSG\\_ABORTING\\_LOG\\_ARCHIVER](#); SQLSTATE: [HY000](#)  
  
Message: The redo log archiver is aborted as it was lagging behind at LSN = %llu and unable to advance for more than 2 seconds. Consider increasing the innodb\_redo\_log\_capacity.  
  
[ER\\_IB\\_MSG\\_ABORTING\\_LOG\\_ARCHIVER](#) was added in 8.0.43.



---

## Chapter 3 Client Error Message Reference

Client error messages originate from within the MySQL client library. Here is an example client error message, as displayed by the `mysql` client:

```
$> mysql -h no-such-host
ERROR 2005 (HY000): Unknown MySQL server host 'no-such-host' (0)
```

Each client error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For client errors, the SQLSTATE value is always 'HY000' (general error), so it is not meaningful for distinguishing one client error from another.

The client library also makes available to host client programs any errors that originate on the server side and are received by the client from the server. For a list of server-side errors, see [Chapter 2, Server Error Message Reference](#).

In addition to the errors in the following list, the client library can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: `2000`; Symbol: `CR_UNKNOWN_ERROR`;  
Message: Unknown MySQL error
- Error number: `2001`; Symbol: `CR_SOCKET_CREATE_ERROR`;  
Message: Can't create UNIX socket (%d)
- Error number: `2002`; Symbol: `CR_CONNECTION_ERROR`;  
Message: Can't connect to local MySQL server through socket '%s' (%d)
- Error number: `2003`; Symbol: `CR_CONN_HOST_ERROR`;  
Message: Can't connect to MySQL server on '%s:%u' (%d)
- Error number: `2004`; Symbol: `CR_IPSOCK_ERROR`;  
Message: Can't create TCP/IP socket (%d)
- Error number: `2005`; Symbol: `CR_UNKNOWN_HOST`;  
Message: Unknown MySQL server host '%s' (%d)
- Error number: `2006`; Symbol: `CR_SERVER_GONE_ERROR`;  
Message: MySQL server has gone away
- Error number: `2007`; Symbol: `CR_VERSION_ERROR`;  
Message: Protocol mismatch; server version = %d, client version = %d
- Error number: `2008`; Symbol: `CR_OUT_OF_MEMORY`;  
Message: MySQL client ran out of memory
- Error number: `2009`; Symbol: `CR_WRONG_HOST_INFO`;  
Message: Wrong host info

- 
- Error number: [2010](#); Symbol: [CR\\_LOCALHOST\\_CONNECTION](#);  
Message: Localhost via UNIX socket
  - Error number: [2011](#); Symbol: [CR\\_TCP\\_CONNECTION](#);  
Message: %s via TCP/IP
  - Error number: [2012](#); Symbol: [CR\\_SERVER\\_HANDSHAKE\\_ERR](#);  
Message: Error in server handshake
  - Error number: [2013](#); Symbol: [CR\\_SERVER\\_LOST](#);  
Message: Lost connection to MySQL server during query
  - Error number: [2014](#); Symbol: [CR\\_COMMANDS\\_OUT\\_OF\\_SYNC](#);  
Message: Commands out of sync; you can't run this command now  
  
Commands were executed in an improper order. This error occurs when a function is called that is not appropriate for the current state of the connection. For example, if `mysql_stmt_fetch()` is not called enough times to read an entire result set (that is, enough times to return `MYSQL_NO_DATA`), this error may occur for the following C API call.
  - Error number: [2015](#); Symbol: [CR\\_NAMEDPIPE\\_CONNECTION](#);  
Message: Named pipe: %s
  - Error number: [2016](#); Symbol: [CR\\_NAMEDPIPEWAIT\\_ERROR](#);  
Message: Can't wait for named pipe to host: %s pipe: %s (%lu)
  - Error number: [2017](#); Symbol: [CR\\_NAMEDPIPEOPEN\\_ERROR](#);  
Message: Can't open named pipe to host: %s pipe: %s (%lu)
  - Error number: [2018](#); Symbol: [CR\\_NAMEDPIPESETSTATE\\_ERROR](#);  
Message: Can't set state of named pipe to host: %s pipe: %s (%lu)
  - Error number: [2019](#); Symbol: [CR\\_CANT\\_READ\\_CHARSET](#);  
Message: Can't initialize character set %s (path: %s)
  - Error number: [2020](#); Symbol: [CR\\_NET\\_PACKET\\_TOO\\_LARGE](#);  
Message: Got packet bigger than 'max\_allowed\_packet' bytes
  - Error number: [2021](#); Symbol: [CR\\_EMBEDDED\\_CONNECTION](#);  
Message: Embedded server
  - Error number: [2022](#); Symbol: [CR\\_PROBE\\_SLAVE\\_STATUS](#);  
Message: Error on SHOW SLAVE STATUS:  
  
[CR\\_PROBE\\_SLAVE\\_STATUS](#) was removed after 8.0.32.
  - Error number: [2022](#); Symbol: [CR\\_PROBE\\_REPLICA\\_STATUS](#);

---

Message: Error on SHOW REPLICA STATUS:

`CR_PROBE_REPLICA_STATUS` was added in 8.0.33.

- Error number: `2023`; Symbol: `CR_PROBE_SLAVE_HOSTS`;

Message: Error on SHOW SLAVE HOSTS:

`CR_PROBE_SLAVE_HOSTS` was removed after 8.0.32.

- Error number: `2023`; Symbol: `CR_PROBE_REPLICA_HOSTS`;

Message: Error on SHOW REPLICA HOSTS:

`CR_PROBE_REPLICA_HOSTS` was added in 8.0.33.

- Error number: `2024`; Symbol: `CR_PROBE_SLAVE_CONNECT`;

Message: Error connecting to slave:

`CR_PROBE_SLAVE_CONNECT` was removed after 8.0.32.

- Error number: `2024`; Symbol: `CR_PROBE_REPLICA_CONNECT`;

Message: Error connecting to replica:

`CR_PROBE_REPLICA_CONNECT` was added in 8.0.33.

- Error number: `2025`; Symbol: `CR_PROBE_MASTER_CONNECT`;

Message: Error connecting to master:

`CR_PROBE_MASTER_CONNECT` was removed after 8.0.32.

- Error number: `2025`; Symbol: `CR_PROBE_SOURCE_CONNECT`;

Message: Error connecting to source:

`CR_PROBE_SOURCE_CONNECT` was added in 8.0.33.

- Error number: `2026`; Symbol: `CR_SSL_CONNECTION_ERROR`;

Message: SSL connection error: %s

- Error number: `2027`; Symbol: `CR_MALFORMED_PACKET`;

Message: Malformed packet

- Error number: `2028`; Symbol: `CR_WRONG_LICENSE`;

Message: This client library is licensed only for use with MySQL servers having '%s' license

- Error number: `2029`; Symbol: `CR_NULL_POINTER`;

Message: Invalid use of null pointer

- Error number: `2030`; Symbol: `CR_NO_PREPARE_STMT`;

Message: Statement not prepared

- 
- Error number: 2031; Symbol: CR\_PARAMS\_NOT\_BOUND;  
Message: No data supplied for parameters in prepared statement
  - Error number: 2032; Symbol: CR\_DATA\_TRUNCATED;  
Message: Data truncated
  - Error number: 2033; Symbol: CR\_NO\_PARAMETERS\_EXISTS;  
Message: No parameters exist in the statement
  - Error number: 2034; Symbol: CR\_INVALID\_PARAMETER\_NO;  
Message: Invalid parameter number  
  
The column number for `mysql_stmt_fetch_column()` was invalid.  
  
The parameter number for `mysql_stmt_send_long_data()` was invalid.  
  
A key name was empty or the amount of connection attribute data for `mysql_options4()` exceeds the 64KB limit.
  - Error number: 2035; Symbol: CR\_INVALID\_BUFFER\_USE;  
Message: Can't send long data for non-string/non-binary data types (parameter: %d)
  - Error number: 2036; Symbol: CR\_UNSUPPORTED\_PARAM\_TYPE;  
Message: Using unsupported buffer type: %d (parameter: %d)
  - Error number: 2037; Symbol: CR\_SHARED\_MEMORY\_CONNECTION;  
Message: Shared memory: %s
  - Error number: 2038; Symbol: CR\_SHARED\_MEMORY\_CONNECT\_REQUEST\_ERROR;  
Message: Can't open shared memory; client could not create request event (%lu)
  - Error number: 2039; Symbol: CR\_SHARED\_MEMORY\_CONNECT\_ANSWER\_ERROR;  
Message: Can't open shared memory; no answer event received from server (%lu)
  - Error number: 2040; Symbol: CR\_SHARED\_MEMORY\_CONNECT\_FILE\_MAP\_ERROR;  
Message: Can't open shared memory; server could not allocate file mapping (%lu)
  - Error number: 2041; Symbol: CR\_SHARED\_MEMORY\_CONNECT\_MAP\_ERROR;  
Message: Can't open shared memory; server could not get pointer to file mapping (%lu)
  - Error number: 2042; Symbol: CR\_SHARED\_MEMORY\_FILE\_MAP\_ERROR;  
Message: Can't open shared memory; client could not allocate file mapping (%lu)
  - Error number: 2043; Symbol: CR\_SHARED\_MEMORY\_MAP\_ERROR;  
Message: Can't open shared memory; client could not get pointer to file mapping (%lu)
  - Error number: 2044; Symbol: CR\_SHARED\_MEMORY\_EVENT\_ERROR;

---

Message: Can't open shared memory; client could not create %s event (%lu)

- Error number: 2045; Symbol: CR\_SHARED\_MEMORY\_CONNECT\_ABANDONED\_ERROR;

Message: Can't open shared memory; no answer from server (%lu)

- Error number: 2046; Symbol: CR\_SHARED\_MEMORY\_CONNECT\_SET\_ERROR;

Message: Can't open shared memory; cannot send request event to server (%lu)

- Error number: 2047; Symbol: CR\_CONN\_UNKNOW\_PROTOCOL;

Message: Wrong or unknown protocol

- Error number: 2048; Symbol: CR\_INVALID\_CONN\_HANDLE;

Message: Invalid connection handle

- Error number: 2049; Symbol: CR\_UNUSED\_1;

Message: Connection using old (pre-4.1.1) authentication protocol refused (client option 'secure\_auth' enabled)

- Error number: 2050; Symbol: CR\_FETCH\_CANCELED;

Message: Row retrieval was canceled by mysql\_stmt\_close() call

- Error number: 2051; Symbol: CR\_NO\_DATA;

Message: Attempt to read column without prior row fetch

- Error number: 2052; Symbol: CR\_NO\_STMT\_METADATA;

Message: Prepared statement contains no metadata

- Error number: 2053; Symbol: CR\_NO\_RESULT\_SET;

Message: Attempt to read a row while there is no result set associated with the statement

- Error number: 2054; Symbol: CR\_NOT\_IMPLEMENTED;

Message: This feature is not implemented yet

- Error number: 2055; Symbol: CR\_SERVER\_LOST\_EXTENDED;

Message: Lost connection to MySQL server at '%s', system error: %d

- Error number: 2056; Symbol: CR\_STMT\_CLOSED;

Message: Statement closed indirectly because of a preceding %s() call

- Error number: 2057; Symbol: CR\_NEW\_STMT\_METADATA;

Message: The number of columns in the result set differs from the number of bound buffers. You must reset the statement, rebind the result set columns, and execute the statement again

- Error number: 2058; Symbol: CR\_ALREADY\_CONNECTED;

Message: This handle is already connected. Use a separate handle for each connection.

- 
- Error number: [2059](#); Symbol: [CR\\_AUTH\\_PLUGIN\\_CANNOT\\_LOAD](#);  
Message: Authentication plugin '%s' cannot be loaded: %s
  - Error number: [2060](#); Symbol: [CR\\_DUPLICATE\\_CONNECTION\\_ATTR](#);  
Message: There is an attribute with the same name already  
A duplicate connection attribute name was specified for `mysql_options4()`.
  - Error number: [2061](#); Symbol: [CR\\_AUTH\\_PLUGIN\\_ERR](#);  
Message: Authentication plugin '%s' reported error: %s
  - Error number: [2062](#); Symbol: [CR\\_INSECURE\\_API\\_ERR](#);  
Message: Insecure API function call: '%s' Use instead: '%s'  
An insecure function call was detected. Modify the application to use the suggested alternative function instead.
  - Error number: [2063](#); Symbol: [CR\\_FILE\\_NAME\\_TOO\\_LONG](#);  
Message: File name is too long  
[CR\\_FILE\\_NAME\\_TOO\\_LONG](#) was added in 8.0.1.
  - Error number: [2064](#); Symbol: [CR\\_SSL\\_FIPS\\_MODE\\_ERR](#);  
Message: Set FIPS mode ON/STRICT failed  
[CR\\_SSL\\_FIPS\\_MODE\\_ERR](#) was added in 8.0.11.
  - Error number: [2065](#); Symbol: [CR\\_COMPRESSION\\_NOT\\_SUPPORTED](#);  
Message: Compression protocol not supported with asynchronous protocol  
[CR\\_COMPRESSION\\_NOT\\_SUPPORTED](#) was added in 8.0.16, removed after 8.0.20.
  - Error number: [2065](#); Symbol: [CR\\_DEPRECATED\\_COMPRESSION\\_NOT\\_SUPPORTED](#);  
Message: Compression protocol not supported with asynchronous protocol  
[CR\\_DEPRECATED\\_COMPRESSION\\_NOT\\_SUPPORTED](#) was added in 8.0.21.
  - Error number: [2066](#); Symbol: [CR\\_COMPRESSION\\_WRONGLY\\_CONFIGURED](#);  
Message: Connection failed due to wrongly configured compression algorithm  
[CR\\_COMPRESSION\\_WRONGLY\\_CONFIGURED](#) was added in 8.0.18.
  - Error number: [2067](#); Symbol: [CR\\_KERBEROS\\_USER\\_NOT\\_FOUND](#);  
Message: SSO user not found, Please perform SSO authentication using kerberos.  
[CR\\_KERBEROS\\_USER\\_NOT\\_FOUND](#) was added in 8.0.20.
  - Error number: [2068](#); Symbol: [CR\\_LOAD\\_DATA\\_LOCAL\\_INFILE\\_REJECTED](#);  
Message: LOAD DATA LOCAL INFILE file request rejected due to restrictions on access.



---

`CR_LOAD_DATA_LOCAL_INFILE_REJECTED` was added in 8.0.21.

- Error number: `2069`; Symbol: `CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL`;

Message: Determining the real path for '%s' failed with error (%d): %s

`CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL` was added in 8.0.21.

- Error number: `2070`; Symbol: `CR_DNS_SRV_LOOKUP_FAILED`;

Message: DNS SRV lookup failed with error : %d

`CR_DNS_SRV_LOOKUP_FAILED` was added in 8.0.22.

- Error number: `2071`; Symbol: `CR_MANDATORY_TRACKER_NOT_FOUND`;

Message: Client does not recognise tracker type %d marked as mandatory by server.

`CR_MANDATORY_TRACKER_NOT_FOUND` was added in 8.0.27.

- Error number: `2072`; Symbol: `CR_INVALID_FACTOR_NO`;

Message: Invalid first argument for `MYSQL_OPT_USER_PASSWORD` option. Valid value should be between 1 and 3 inclusive.

`CR_INVALID_FACTOR_NO` was added in 8.0.27.

- Error number: `2073`; Symbol: `CR_CANT_GET_SESSION_DATA`;

Message: Can't get session data: %s

`CR_CANT_GET_SESSION_DATA` was added in 8.0.29.

- Error number: `2074`; Symbol: `CR_INVALID_CLIENT_CHARSET`;

Message: '%s' character set is having more than 1 byte minimum character length, which cannot be used as a client character set. Please use any of the single byte minimum ones, e.g. `utf8mb4`, `latin1` etc.

`CR_INVALID_CLIENT_CHARSET` was added in 8.0.33.



---

## Chapter 4 Global Error Message Reference

This document lists “global” error messages that are shared in the sense that they can be produced by the MySQL server or by MySQL client programs. These errors have error codes in the range from 1 to 999.

Each global error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For global errors, the SQLSTATE value is always 'HY000' (general error), so it is not meaningful for distinguishing one client error from another.

If the server writes a message to the error log that has a global error code, it pads the error code with leading zeros to six digits and adds a prefix of `MY-` (example: `MY-000022`). The following list displays error codes in that format.

If a client returns a message with a global error code, it adds no zero-padding or prefix to the error code.

- Error number: 1; Symbol: `EE_CANTCREATEFILE`;  
Message: Can't create/write to file '%s' (OS errno %d - %s)
- Error number: 2; Symbol: `EE_READ`;  
Message: Error reading file '%s' (OS errno %d - %s)
- Error number: 3; Symbol: `EE_WRITE`;  
Message: Error writing file '%s' (OS errno %d - %s)
- Error number: 4; Symbol: `EE_BADCLOSE`;  
Message: Error on close of '%s' (OS errno %d - %s)
- Error number: 5; Symbol: `EE_OUTOFMEMORY`;  
Message: Out of memory (Needed %u bytes)
- Error number: 6; Symbol: `EE_DELETE`;  
Message: Error on delete of '%s' (OS errno %d - %s)
- Error number: 7; Symbol: `EE_LINK`;  
Message: Error on rename of '%s' to '%s' (OS errno %d - %s)
- Error number: 9; Symbol: `EE_EOFERR`;  
Message: Unexpected EOF found when reading file '%s' (OS errno %d - %s)
- Error number: 10; Symbol: `EE_CANTLOCK`;  
Message: Can't lock file (OS errno %d - %s)
- Error number: 11; Symbol: `EE_CANTUNLOCK`;  
Message: Can't unlock file (OS errno %d - %s)
- Error number: 12; Symbol: `EE_DIR`;

- 
- Message: Can't read dir of '%s' (OS errno %d - %s)
  - Error number: 13; Symbol: `EE_STAT`;  
Message: Can't get stat of '%s' (OS errno %d - %s)
  - Error number: 14; Symbol: `EE_CANT_CHSIZE`;  
Message: Can't change size of file (OS errno %d - %s)
  - Error number: 15; Symbol: `EE_CANT_OPEN_STREAM`;  
Message: Can't open stream from handle (OS errno %d - %s)
  - Error number: 16; Symbol: `EE_GETWD`;  
Message: Can't get working directory (OS errno %d - %s)
  - Error number: 17; Symbol: `EE_SETWD`;  
Message: Can't change dir to '%s' (OS errno %d - %s)
  - Error number: 18; Symbol: `EE_LINK_WARNING`;  
Message: Warning: '%s' had %d links
  - Error number: 19; Symbol: `EE_OPEN_WARNING`;  
Message: Warning: %d files and %d streams are left open
  - Error number: 20; Symbol: `EE_DISK_FULL`;  
Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space...
  - Error number: 21; Symbol: `EE_CANT_MKDIR`;  
Message: Can't create directory '%s' (OS errno %d - %s)
  - Error number: 22; Symbol: `EE_UNKNOWN_CHARSET`;  
Message: Character set '%s' is not a compiled character set and is not specified in the '%s' file
  - Error number: 23; Symbol: `EE_OUT_OF_FILERESOURCES`;  
Message: Out of resources when opening file '%s' (OS errno %d - %s)
  - Error number: 24; Symbol: `EE_CANT_READLINK`;  
Message: Can't read value for symlink '%s' (Error %d - %s)
  - Error number: 25; Symbol: `EE_CANT_SYMLINK`;  
Message: Can't create symlink '%s' pointing at '%s' (Error %d - %s)
  - Error number: 26; Symbol: `EE_REALPATH`;  
Message: Error on realpath() on '%s' (Error %d - %s)
  - Error number: 27; Symbol: `EE_SYNC`;

---

Message: Can't sync file '%s' to disk (OS errno %d - %s)

- Error number: 28; Symbol: `EE_UNKNOWN_COLLATION`;

Message: Collation '%s' is not a compiled collation and is not specified in the '%s' file

- Error number: 29; Symbol: `EE_FILENOTFOUND`;

Message: File '%s' not found (OS errno %d - %s)

- Error number: 30; Symbol: `EE_FILE_NOT_CLOSED`;

Message: File '%s' (fileno: %d) was not closed

- Error number: 31; Symbol: `EE_CHANGE_OWNERSHIP`;

Message: Cannot change ownership of the file '%s' (OS errno %d - %s)

- Error number: 32; Symbol: `EE_CHANGE_PERMISSIONS`;

Message: Cannot change permissions of the file '%s' (OS errno %d - %s)

- Error number: 33; Symbol: `EE_CANT_SEEK`;

Message: Cannot seek in file '%s' (OS errno %d - %s)

- Error number: 34; Symbol: `EE_CAPACITY_EXCEEDED`;

Message: Memory capacity exceeded (capacity %llu bytes)

- Error number: 35; Symbol: `EE_DISK_FULL_WITH_RETRY_MSG`;

Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space... Retry in %d secs. Message reprinted in %d secs.

`EE_DISK_FULL_WITH_RETRY_MSG` was added in 8.0.13.

- Error number: 36; Symbol: `EE_FAILED_TO_CREATE_TIMER`;

Message: Failed to create timer (OS errno %d).

`EE_FAILED_TO_CREATE_TIMER` was added in 8.0.13.

- Error number: 37; Symbol: `EE_FAILED_TO_DELETE_TIMER`;

Message: Failed to delete timer (OS errno %d).

`EE_FAILED_TO_DELETE_TIMER` was added in 8.0.13.

- Error number: 38; Symbol: `EE_FAILED_TO_CREATE_TIMER_QUEUE`;

Message: Failed to create timer queue (OS errno %d).

`EE_FAILED_TO_CREATE_TIMER_QUEUE` was added in 8.0.13.

- Error number: 39; Symbol: `EE_FAILED_TO_START_TIMER_NOTIFY_THREAD`;

Message: Failed to start timer notify thread.

---

`EE_FAILED_TO_START_TIMER_NOTIFY_THREAD` was added in 8.0.13.

- Error number: 40; Symbol: `EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT`;  
Message: Failed to create event to interrupt timer notifier thread (OS errno %d).

`EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT` was added in 8.0.13.

- Error number: 41; Symbol: `EE_EXITING_TIMER_NOTIFY_THREAD`;  
Message: Failed to register timer event with queue (OS errno %d), exiting timer notifier thread.

`EE_EXITING_TIMER_NOTIFY_THREAD` was added in 8.0.13.

- Error number: 42; Symbol: `EE_WIN_LIBRARY_LOAD_FAILED`;  
Message: LoadLibrary("kernel32.dll") failed: GetLastError returns %lu.

`EE_WIN_LIBRARY_LOAD_FAILED` was added in 8.0.13.

- Error number: 43; Symbol: `EE_WIN_RUN_TIME_ERROR_CHECK`;  
Message: %s.

`EE_WIN_RUN_TIME_ERROR_CHECK` was added in 8.0.13.

- Error number: 44; Symbol: `EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE`;  
Message: Failed to determine large page size.

`EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE` was added in 8.0.13.

- Error number: 45; Symbol: `EE_FAILED_TO_KILL_ALL_THREADS`;  
Message: Error in my\_thread\_global\_end(): %d thread(s) did not exit.

`EE_FAILED_TO_KILL_ALL_THREADS` was added in 8.0.13.

- Error number: 46; Symbol: `EE_FAILED_TO_CREATE_IO_COMPLETION_PORT`;  
Message: Failed to create IO completion port (OS errno %d).

`EE_FAILED_TO_CREATE_IO_COMPLETION_PORT` was added in 8.0.13.

- Error number: 47; Symbol: `EE_FAILED_TO_OPEN_DEFAULTS_FILE`;  
Message: Failed to open required defaults file: %s

`EE_FAILED_TO_OPEN_DEFAULTS_FILE` was added in 8.0.13.

- Error number: 48; Symbol: `EE_FAILED_TO_HANDLE_DEFAULTS_FILE`;  
Message: Fatal error in defaults handling. Program aborted!

`EE_FAILED_TO_HANDLE_DEFAULTS_FILE` was added in 8.0.13.

- Error number: 49; Symbol: `EE_WRONG_DIRECTIVE_IN_CONFIG_FILE`;  
Message: Wrong '%s' directive in config file %s at line %d.

---

`EE_WRONG_DIRECTIVE_IN_CONFIG_FILE` was added in 8.0.13.

- Error number: 50; Symbol: `EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION`;  
Message: Skipping '%s' directive as maximum include recursion level was reached in file %s at line %d.  
`EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION` was added in 8.0.13.
- Error number: 51; Symbol: `EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE`;  
Message: Wrong group definition in config file %s at line %d.  
`EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE` was added in 8.0.13.
- Error number: 52; Symbol: `EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE`;  
Message: Found option without preceding group in config file %s at line %d.  
`EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE` was added in 8.0.13.
- Error number: 53; Symbol: `EE_CONFIG_FILE_PERMISSION_ERROR`;  
Message: %s should be readable/writable only by current user.  
`EE_CONFIG_FILE_PERMISSION_ERROR` was added in 8.0.13.
- Error number: 54; Symbol: `EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE`;  
Message: World-writable config file '%s' is ignored.  
`EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE` was added in 8.0.13.
- Error number: 55; Symbol: `EE_USING_DISABLED_OPTION`;  
Message: %s: Option '%s' was used, but is disabled.  
`EE_USING_DISABLED_OPTION` was added in 8.0.13.
- Error number: 56; Symbol: `EE_USING_DISABLED_SHORT_OPTION`;  
Message: %s: Option '-%c' was used, but is disabled.  
`EE_USING_DISABLED_SHORT_OPTION` was added in 8.0.13.
- Error number: 57; Symbol: `EE_USING_PASSWORD_ON_CLI_IS_INSECURE`;  
Message: Using a password on the command line interface can be insecure.  
`EE_USING_PASSWORD_ON_CLI_IS_INSECURE` was added in 8.0.13.
- Error number: 58; Symbol: `EE_UNKNOWN_SUFFIX_FOR_VARIABLE`;  
Message: Unknown suffix '%c' used for variable '%s' (value '%s').  
`EE_UNKNOWN_SUFFIX_FOR_VARIABLE` was added in 8.0.13.
- Error number: 59; Symbol: `EE_SSL_ERROR_FROM_FILE`;  
Message: SSL error: %s from '%s'.

---

`EE_SSL_ERROR_FROM_FILE` was added in 8.0.13.

- Error number: `60`; Symbol: `EE_SSL_ERROR`;

Message: SSL error: %s.

`EE_SSL_ERROR` was added in 8.0.13.

- Error number: `61`; Symbol: `EE_NET_SEND_ERROR_IN_BOOTSTRAP`;

Message: %d %s.

`EE_NET_SEND_ERROR_IN_BOOTSTRAP` was added in 8.0.13.

- Error number: `62`; Symbol: `EE_PACKETS_OUT_OF_ORDER`;

Message: Packets out of order (found %u, expected %u).

`EE_PACKETS_OUT_OF_ORDER` was added in 8.0.13.

- Error number: `63`; Symbol: `EE_UNKNOWN_PROTOCOL_OPTION`;

Message: Unknown option to protocol: %s.

`EE_UNKNOWN_PROTOCOL_OPTION` was added in 8.0.13.

- Error number: `64`; Symbol: `EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY`;

Message: Failed to locate server public key '%s'.

`EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY` was added in 8.0.13.

- Error number: `65`; Symbol: `EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT`;

Message: Public key is not in Privacy Enhanced Mail format: '%s'.

`EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT` was added in 8.0.13.

- Error number: `66`; Symbol: `EE_DEBUG_INFO`;

Message: %s.

`EE_DEBUG_INFO` was added in 8.0.13.

- Error number: `67`; Symbol: `EE_UNKNOWN_VARIABLE`;

Message: unknown variable '%s'.

`EE_UNKNOWN_VARIABLE` was added in 8.0.13.

- Error number: `68`; Symbol: `EE_UNKNOWN_OPTION`;

Message: unknown option '--%s'.

`EE_UNKNOWN_OPTION` was added in 8.0.13.

- Error number: `69`; Symbol: `EE_UNKNOWN_SHORT_OPTION`;

Message: %s: unknown option '-%c'.



---

`EE_UNKNOWN_SHORT_OPTION` was added in 8.0.13.

- Error number: 70; Symbol: `EE_OPTION_WITHOUT_ARGUMENT`;

Message: %s: option '--%s' cannot take an argument.

`EE_OPTION_WITHOUT_ARGUMENT` was added in 8.0.13.

- Error number: 71; Symbol: `EE_OPTION_REQUIRES_ARGUMENT`;

Message: %s: option '--%s' requires an argument.

`EE_OPTION_REQUIRES_ARGUMENT` was added in 8.0.13.

- Error number: 72; Symbol: `EE_SHORT_OPTION_REQUIRES_ARGUMENT`;

Message: %s: option '-%c' requires an argument.

`EE_SHORT_OPTION_REQUIRES_ARGUMENT` was added in 8.0.13.

- Error number: 73; Symbol: `EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE`;

Message: %s: ignoring option '--%s' due to invalid value '%s'.

`EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE` was added in 8.0.13.

- Error number: 74; Symbol: `EE_OPTION_WITH_EMPTY_VALUE`;

Message: %s: Empty value for '%s' specified.

`EE_OPTION_WITH_EMPTY_VALUE` was added in 8.0.13.

- Error number: 75; Symbol: `EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION`;

Message: %s: Maximum value of '%s' cannot be set.

`EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION` was added in 8.0.13.

- Error number: 76; Symbol: `EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION`;

Message: option '%s': boolean value '%s' was not recognized. Set to OFF.

`EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 77; Symbol: `EE_FAILED_TO_SET_OPTION_VALUE`;

Message: %s: Error while setting value '%s' to '%s'.

`EE_FAILED_TO_SET_OPTION_VALUE` was added in 8.0.13.

- Error number: 78; Symbol: `EE_INCORRECT_INT_VALUE_FOR_OPTION`;

Message: Incorrect integer value: '%s'.

`EE_INCORRECT_INT_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 79; Symbol: `EE_INCORRECT_UINT_VALUE_FOR_OPTION`;

Message: Incorrect unsigned integer value: '%s'.

---

`EE_INCORRECT_UINT_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 80; Symbol: `EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION`;

Message: option '%s': signed value %s adjusted to %s.

`EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 81; Symbol: `EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION`;

Message: option '%s': unsigned value %s adjusted to %s.

`EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 82; Symbol: `EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION`;

Message: option '%s': value %s adjusted to %s.

`EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 83; Symbol: `EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION`;

Message: option '%s': value %g adjusted to %g.

`EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 84; Symbol: `EE_INVALID_DECIMAL_VALUE_FOR_OPTION`;

Message: Invalid decimal value for option '%s'.

`EE_INVALID_DECIMAL_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 85; Symbol: `EE_COLLATION_PARSER_ERROR`;

Message: %s.

`EE_COLLATION_PARSER_ERROR` was added in 8.0.13.

- Error number: 86; Symbol: `EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE_CHAR`;

Message: Failed to reset before a primary ignorable character %s.

`EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE_CHAR` was added in 8.0.13.

- Error number: 87; Symbol: `EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE_CHAR`;

Message: Failed to reset before a tertiary ignorable character %s.

`EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE_CHAR` was added in 8.0.13.

- Error number: 88; Symbol: `EE_SHIFT_CHAR_OUT_OF_RANGE`;

Message: Shift character out of range: %s.

`EE_SHIFT_CHAR_OUT_OF_RANGE` was added in 8.0.13.

- Error number: 89; Symbol: `EE_RESET_CHAR_OUT_OF_RANGE`;

Message: Reset character out of range: %s.

---

`EE_RESET_CHAR_OUT_OF_RANGE` was added in 8.0.13.

- Error number: `90`; Symbol: `EE_UNKNOWN_LDML_TAG`;

Message: Unknown LDML tag: '%.\*s'.

`EE_UNKNOWN_LDML_TAG` was added in 8.0.13.

- Error number: `91`; Symbol: `EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE_CHAR`;

Message: Failed to reset before a secondary ignorable character %s.

`EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE_CHAR` was added in 8.0.16.

- Error number: `92`; Symbol: `EE_FAILED_PROCESSING_DIRECTIVE`;

Message: Stopped processing the '%s' directive in file %s at line %d.

`EE_FAILED_PROCESSING_DIRECTIVE` was added in 8.0.27.

- Error number: `93`; Symbol: `EE_PTHREAD_KILL_FAILED`;

Message: pthread\_kill(thread\_id:%lu, signal:%s) returned '%s'.

`EE_PTHREAD_KILL_FAILED` was added in 8.0.31.



---

# Index

## C

CR\_ALREADY\_CONNECTED error code, 649  
CR\_AUTH\_PLUGIN\_CANNOT\_LOAD error code, 650  
CR\_AUTH\_PLUGIN\_ERR error code, 650  
CR\_CANT\_GET\_SESSION\_DATA error code, 651  
CR\_CANT\_READ\_CHARSET error code, 646  
CR\_COMMANDS\_OUT\_OF\_SYNC error code, 646  
CR\_COMPRESSION\_NOT\_SUPPORTED error code, 650  
CR\_COMPRESSION\_WRONGLY\_CONFIGURED error code, 650  
CR\_CONNECTION\_ERROR error code, 645  
CR\_CONN\_HOST\_ERROR error code, 645  
CR\_CONN\_UNKNOW\_PROTOCOL error code, 649  
CR\_DATA\_TRUNCATED error code, 648  
CR\_DEPRECATED\_COMPRESSION\_NOT\_SUPPORTED error code, 650  
CR\_DNS\_SRV\_LOOKUP\_FAILED error code, 651  
CR\_DUPLICATE\_CONNECTION\_ATTR error code, 650  
CR\_EMBEDDED\_CONNECTION error code, 646  
CR\_FETCH\_CANCELED error code, 649  
CR\_FILE\_NAME\_TOO\_LONG error code, 650  
CR\_INSECURE\_API\_ERR error code, 650  
CR\_INVALID\_BUFFER\_USE error code, 648  
CR\_INVALID\_CLIENT\_CHARSET error code, 651  
CR\_INVALID\_CONN\_HANDLE error code, 649  
CR\_INVALID\_FACTOR\_NO error code, 651  
CR\_INVALID\_PARAMETER\_NO error code, 648  
CR\_IPSOCK\_ERROR error code, 645  
CR\_KERBEROS\_USER\_NOT\_FOUND error code, 650  
CR\_LOAD\_DATA\_LOCAL\_INFILE\_REALPATH\_FAIL error code, 651  
CR\_LOAD\_DATA\_LOCAL\_INFILE\_REJECTED error code, 651  
CR\_LOCALHOST\_CONNECTION error code, 646  
CR\_MALFORMED\_PACKET error code, 647  
CR\_MANDATORY\_TRACKER\_NOT\_FOUND error code, 651  
CR\_NAMEDPIPEOPEN\_ERROR error code, 646  
CR\_NAMEDPIPESETSTATE\_ERROR error code, 646  
CR\_NAMEDPIPEWAIT\_ERROR error code, 646  
CR\_NAMEDPIPE\_CONNECTION error code, 646  
CR\_NET\_PACKET\_TOO\_LARGE error code, 646  
CR\_NEW\_STMT\_METADATA error code, 649  
CR\_NOT\_IMPLEMENTED error code, 649  
CR\_NO\_DATA error code, 649  
CR\_NO\_PARAMETERS\_EXISTS error code, 648  
CR\_NO\_PREPARE\_STMT error code, 647  
CR\_NO\_RESULT\_SET error code, 649  
CR\_NO\_STMT\_METADATA error code, 649  
CR\_NULL\_POINTER error code, 647  
CR\_OUT\_OF\_MEMORY error code, 645  
CR\_PARAMS\_NOT\_BOUND error code, 648  
CR\_PROBE\_MASTER\_CONNECT error code, 647  
CR\_PROBE\_REPLICA\_CONNECT error code, 647  
CR\_PROBE\_REPLICA\_HOSTS error code, 647  
CR\_PROBE\_REPLICA\_STATUS error code, 647  
CR\_PROBE\_SLAVE\_CONNECT error code, 647  
CR\_PROBE\_SLAVE\_HOSTS error code, 647  
CR\_PROBE\_SLAVE\_STATUS error code, 646  
CR\_PROBE\_SOURCE\_CONNECT error code, 647  
CR\_SERVER\_GONE\_ERROR error code, 645  
CR\_SERVER\_HANDSHAKE\_ERR error code, 646  
CR\_SERVER\_LOST error code, 646  
CR\_SERVER\_LOST\_EXTENDED error code, 649  
CR\_SHARED\_MEMORY\_CONNECTION error code, 648  
CR\_SHARED\_MEMORY\_CONNECT\_ABANDONED\_ERROR error code, 649  
CR\_SHARED\_MEMORY\_CONNECT\_ANSWER\_ERROR error code, 648  
CR\_SHARED\_MEMORY\_CONNECT\_FILE\_MAP\_ERROR error code, 648  
CR\_SHARED\_MEMORY\_CONNECT\_MAP\_ERROR error code, 648  
CR\_SHARED\_MEMORY\_CONNECT\_REQUEST\_ERROR error code, 648  
CR\_SHARED\_MEMORY\_CONNECT\_SET\_ERROR error code, 649  
CR\_SHARED\_MEMORY\_EVENT\_ERROR error code, 649  
CR\_SHARED\_MEMORY\_FILE\_MAP\_ERROR error code, 648  
CR\_SHARED\_MEMORY\_MAP\_ERROR error code, 648  
CR\_SOCKET\_CREATE\_ERROR error code, 645  
CR\_SSL\_CONNECTION\_ERROR error code, 647  
CR\_SSL\_FIPS\_MODE\_ERR error code, 650  
CR\_STMT\_CLOSED error code, 649  
CR\_TCP\_CONNECTION error code, 646  
CR\_UNKNOWN\_ERROR error code, 645  
CR\_UNKNOWN\_HOST error code, 645  
CR\_UNSUPPORTED\_PARAM\_TYPE error code, 648  
CR\_UNUSED\_1 error code, 649  
CR\_VERSION\_ERROR error code, 645  
CR\_WRONG\_HOST\_INFO error code, 645  
CR\_WRONG\_LICENSE error code, 647

## E

EE\_ADJUSTED\_DOUBLE\_VALUE\_FOR\_OPTION error code, 660  
EE\_ADJUSTED\_SIGNED\_VALUE\_FOR\_OPTION error code, 660  
EE\_ADJUSTED\_ULONGLONG\_VALUE\_FOR\_OPTION error code, 660

---

EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION error code, 660	EE_FAILED_TO_START_TIMER_NOTIFY_THREAD error code, 656
EE_BADCLOSE error code, 653	EE_FILENOTFOUND error code, 655
EE_CANTCREATEFILE error code, 653	EE_FILE_NOT_CLOSED error code, 655
EE_CANTLOCK error code, 653	EE_GETWD error code, 654
EE_CANTUNLOCK error code, 653	EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE error code, 657
EE_CANT_CHSIZE error code, 654	EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION error code, 659
EE_CANT_MKDIR error code, 654	EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE error code, 657
EE_CANT_OPEN_STREAM error code, 654	EE_INCORRECT_INT_VALUE_FOR_OPTION error code, 659
EE_CANT_READLINK error code, 654	EE_INCORRECT_UINT_VALUE_FOR_OPTION error code, 660
EE_CANT_SEEK error code, 655	EE_INVALID_DECIMAL_VALUE_FOR_OPTION error code, 660
EE_CANT_SYMLINK error code, 654	EE_LINK error code, 653
EE_CAPACITY_EXCEEDED error code, 655	EE_LINK_WARNING error code, 654
EE_CHANGE_OWNERSHIP error code, 655	EE_NET_SEND_ERROR_IN_BOOTSTRAP error code, 658
EE_CHANGE_PERMISSIONS error code, 655	EE_OPEN_WARNING error code, 654
EE_COLLATION_PARSER_ERROR error code, 660	EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE error code, 659
EE_CONFIG_FILE_PERMISSION_ERROR error code, 657	EE_OPTION_REQUIRES_ARGUMENT error code, 659
EE_DEBUG_INFO error code, 658	EE_OPTION_WITHOUT_ARGUMENT error code, 659
EE_DELETE error code, 653	EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE error code, 657
EE_DIR error code, 654	EE_OPTION_WITH_EMPTY_VALUE error code, 659
EE_DISK_FULL error code, 654	EE_OUTOFMEMORY error code, 653
EE_DISK_FULL_WITH_RETRY_MSG error code, 655	EE_OUT_OF_FILERESOURCES error code, 654
EE_EOFERR error code, 653	EE_PACKETS_OUT_OF_ORDER error code, 658
EE_EXITING_TIMER_NOTIFY_THREAD error code, 656	EE_PTHREAD_KILL_FAILED error code, 661
EE_FAILED_PROCESSING_DIRECTIVE error code, 661	EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT error code, 658
EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION error code, 659	EE_READ error code, 653
EE_FAILED_TO_CREATE_IO_COMPLETION_PORT error code, 656	EE_REALPATH error code, 654
EE_FAILED_TO_CREATE_TIMER error code, 655	EE_RESET_CHAR_OUT_OF_RANGE error code, 661
EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT error code, 656	EE_SETWD error code, 654
EE_FAILED_TO_CREATE_TIMER_QUEUE error code, 655	EE_SHIFT_CHAR_OUT_OF_RANGE error code, 660
EE_FAILED_TO_DELETE_TIMER error code, 655	EE_SHORT_OPTION_REQUIRES_ARGUMENT error code, 659
EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE error code, 656	EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION error code, 657
EE_FAILED_TO_HANDLE_DEFAULTS_FILE error code, 656	EE_SSL_ERROR error code, 658
EE_FAILED_TO_KILL_ALL_THREADS error code, 656	EE_SSL_ERROR_FROM_FILE error code, 658
EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY error code, 658	EE_STAT error code, 654
EE_FAILED_TO_OPEN_DEFAULTS_FILE error code, 656	EE_SYMLINK error code, 655
EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE error code, 660	EE_UNKNOWN_CHARSET error code, 654
EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE error code, 661	EE_UNKNOWN_COLLATION error code, 655
EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE error code, 660	EE_UNKNOWN_LDML_TAG error code, 661
EE_FAILED_TO_SET_OPTION_VALUE error code, 659	EE_UNKNOWN_OPTION error code, 658
	EE_UNKNOWN_PROTOCOL_OPTION error code, 658
	EE_UNKNOWN_SHORT_OPTION error code, 659

---

---

EE_UNKNOWN_SUFFIX_FOR_VARIABLE error code, 657	CR_NOT_IMPLEMENTED, 649
EE_UNKNOWN_VARIABLE error code, 658	CR_NO_DATA, 649
EE_USING_DISABLED_OPTION error code, 657	CR_NO_PARAMETERS_EXISTS, 648
EE_USING_DISABLED_SHORT_OPTION error code, 657	CR_NO_PREPARE_STMT, 647
EE_USING_PASSWORD_ON_CLI_IS_INSECURE error code, 657	CR_NO_RESULT_SET, 649
EE_WIN_LIBRARY_LOAD_FAILED error code, 656	CR_NO_STMT_METADATA, 649
EE_WIN_RUN_TIME_ERROR_CHECK error code, 656	CR_NULL_POINTER, 647
EE_WRITE error code, 653	CR_OUT_OF_MEMORY, 645
EE_WRONG_DIRECTIVE_IN_CONFIG_FILE error code, 657	CR_PARAMS_NOT_BOUND, 648
error code	CR_PROBE_MASTER_CONNECT, 647
CR_ALREADY_CONNECTED, 649	CR_PROBE_REPLICA_CONNECT, 647
CR_AUTH_PLUGIN_CANNOT_LOAD, 650	CR_PROBE_REPLICA_HOSTS, 647
CR_AUTH_PLUGIN_ERR, 650	CR_PROBE_REPLICA_STATUS, 647
CR_CANT_GET_SESSION_DATA, 651	CR_PROBE_SLAVE_CONNECT, 647
CR_CANT_READ_CHARSET, 646	CR_PROBE_SLAVE_HOSTS, 647
CR_COMMANDS_OUT_OF_SYNC, 646	CR_PROBE_SLAVE_STATUS, 646
CR_COMPRESSION_NOT_SUPPORTED, 650	CR_PROBE_SOURCE_CONNECT, 647
CR_COMPRESSION_WRONGLY_CONFIGURED, 650	CR_SERVER_GONE_ERROR, 645
CR_CONNECTION_ERROR, 645	CR_SERVER_HANDSHAKE_ERR, 646
CR_CONN_HOST_ERROR, 645	CR_SERVER_LOST, 646
CR_CONN_UNKNOW_PROTOCOL, 649	CR_SERVER_LOST_EXTENDED, 649
CR_DATA_TRUNCATED, 648	CR_SHARED_MEMORY_CONNECTION, 648
CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED, 650	CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR, 649
CR_DNS_SRV_LOOKUP_FAILED, 651	CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR, 648
CR_DUPLICATE_CONNECTION_ATTR, 650	CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR, 648
CR_EMBEDDED_CONNECTION, 646	CR_SHARED_MEMORY_CONNECT_MAP_ERROR, 648
CR_FETCH_CANCELED, 649	CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR, 648
CR_FILE_NAME_TOO_LONG, 650	CR_SHARED_MEMORY_CONNECT_SET_ERROR, 649
CR_INSECURE_API_ERR, 650	CR_SHARED_MEMORY_EVENT_ERROR, 649
CR_INVALID_BUFFER_USE, 648	CR_SHARED_MEMORY_FILE_MAP_ERROR, 648
CR_INVALID_CLIENT_CHARSET, 651	CR_SHARED_MEMORY_MAP_ERROR, 648
CR_INVALID_CONN_HANDLE, 649	CR_SOCKET_CREATE_ERROR, 645
CR_INVALID_FACTOR_NO, 651	CR_SSL_CONNECTION_ERROR, 647
CR_INVALID_PARAMETER_NO, 648	CR_SSL_FIPS_MODE_ERR, 650
CR_IPSOCK_ERROR, 645	CR_STMT_CLOSED, 649
CR_KERBEROS_USER_NOT_FOUND, 650	CR_TCP_CONNECTION, 646
CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL, 651	CR_UNKNOWN_ERROR, 645
CR_LOAD_DATA_LOCAL_INFILE_REJECTED, 651	CR_UNKNOWN_HOST, 645
CR_LOCALHOST_CONNECTION, 646	CR_UNSUPPORTED_PARAM_TYPE, 648
CR_MALFORMED_PACKET, 647	CR_UNUSED_1, 649
CR_MANDATORY_TRACKER_NOT_FOUND, 651	CR_VERSION_ERROR, 645
CR_NAMEDPIPEOPEN_ERROR, 646	CR_WRONG_HOST_INFO, 645
CR_NAMEDPIPESETSTATE_ERROR, 646	CR_WRONG_LICENSE, 647
CR_NAMEDPIPEWAIT_ERROR, 646	EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION, 660
CR_NAMEDPIPE_CONNECTION, 646	EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION, 660
CR_NET_PACKET_TOO_LARGE, 646	
CR_NEW_STMT_METADATA, 649	

---

---

EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION, 660	EE_GETWD, 654
EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION, 660	EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE, 657
EE_BADCLOSE, 653	EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION, 659
EE_CANTCREATEFILE, 653	EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE, 657
EE_CANTLOCK, 653	EE_INCORRECT_INT_VALUE_FOR_OPTION, 659
EE_CANTUNLOCK, 653	EE_INCORRECT_UINT_VALUE_FOR_OPTION, 660
EE_CANT_CHSIZE, 654	EE_INVALID_DECIMAL_VALUE_FOR_OPTION, 660
EE_CANT_MKDIR, 654	EE_LINK, 653
EE_CANT_OPEN_STREAM, 654	EE_LINK_WARNING, 654
EE_CANT_READLINK, 654	EE_NET_SEND_ERROR_IN_BOOTSTRAP, 658
EE_CANT_SEEK, 655	EE_OPEN_WARNING, 654
EE_CANT_SYMLINK, 654	EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE, 659
EE_CAPACITY_EXCEEDED, 655	EE_OPTION_REQUIRES_ARGUMENT, 659
EE_CHANGE_OWNERSHIP, 655	EE_OPTION_WITHOUT_ARGUMENT, 659
EE_CHANGE_PERMISSIONS, 655	EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE, 657
EE_COLLATION_PARSER_ERROR, 660	EE_OPTION_WITH_EMPTY_VALUE, 659
EE_CONFIG_FILE_PERMISSION_ERROR, 657	EE_OUTOFMEMORY, 653
EE_DEBUG_INFO, 658	EE_OUT_OF_FILERESOURCES, 654
EE_DELETE, 653	EE_PACKETS_OUT_OF_ORDER, 658
EE_DIR, 654	EE_PTHREAD_KILL_FAILED, 661
EE_DISK_FULL, 654	EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT, 658
EE_DISK_FULL_WITH_RETRY_MSG, 655	EE_READ, 653
EE_EOFERR, 653	EE_REALPATH, 654
EE_EXITING_TIMER_NOTIFY_THREAD, 656	EE_RESET_CHAR_OUT_OF_RANGE, 661
EE_FAILED_PROCESSING_DIRECTIVE, 661	EE_SETWD, 654
EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION, 659	EE_SHIFT_CHAR_OUT_OF_RANGE, 660
EE_FAILED_TO_CREATE_IO_COMPLETION_PORT, 656	EE_SHORT_OPTION_REQUIRES_ARGUMENT, 659
EE_FAILED_TO_CREATE_TIMER, 655	EE_SHORT_OPTION_REQUIRES_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION, 657
EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPTING, 656	EE_SSL_ERROR, 658
EE_FAILED_TO_CREATE_TIMER_QUEUE, 655	EE_SSL_ERROR_FROM_FILE, 658
EE_FAILED_TO_DELETE_TIMER, 655	EE_STAT, 654
EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE, 656	EE_SYNC, 655
EE_FAILED_TO_HANDLE_DEFAULTS_FILE, 656	EE_UNKNOWN_CHARSET, 654
EE_FAILED_TO_KILL_ALL_THREADS, 656	EE_UNKNOWN_COLLATION, 655
EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY, 658	EE_UNKNOWN_LDML_TAG, 661
EE_FAILED_TO_OPEN_DEFAULTS_FILE, 656	EE_UNKNOWN_OPTION, 658
EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE_DIRECTIVE, 660	EE_UNKNOWN_PROTOCOL_OPTION, 658
EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE_DIRECTIVE, 661	EE_UNKNOWN_SHORT_OPTION, 659
EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE_DIRECTIVE, 660	EE_UNKNOWN_SUFFIX_FOR_VARIABLE, 657
EE_FAILED_TO_SET_OPTION_VALUE, 659	EE_UNKNOWN_VARIABLE, 658
EE_FAILED_TO_START_TIMER_NOTIFY_THREAD, 656	EE_USING_DISABLED_OPTION, 657
EE_FILENOTFOUND, 655	EE_USING_DISABLED_SHORT_OPTION, 657
EE_FILE_NOT_CLOSED, 655	EE_USING_PASSWORD_ON_CLI_IS_INSECURE, 657
	EE_WIN_LIBRARY_LOAD_FAILED, 656
	EE_WIN_RUN_TIME_ERROR_CHECK, 656
	EE_WRITE, 653
	EE_WRONG_DIRECTIVE_IN_CONFIG_FILE, 657



---

ER_ABORTING, 175	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK,
ER_ABORTING_CONNECTION, 14	64
ER_ABORTING_USER_CONNECTION, 278	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FTS,
ER_ACCESS_DENIED_CHANGE_USER_ERROR,	64
66	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS,
ER_ACCESS_DENIED_ERROR, 6	74
ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD,	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_HID,
279	64
ER_ACCESS_DENIED_ERROR_WITH_PASSWORD,	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NO,
280	64
ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED,	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NO,
575	65
ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED,	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PA,
280	64
ER_ACCESS_DENIED_NO_PASSWORD_ERROR,	ER_AMBIGUOUS_FIELD_TERM, 36
50	ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDAT,
ER_ACCOUNT_HAS_BEEN_LOCKED, 80	285
ER_ACCOUNT_WITH_EXPIRED_PASSWORD, 614	ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NA,
ER_ACL_OPERATION_FAILED, 87	145
ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG,	ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHAN,
565	147
ER_ADDRESSES_FOR_HOSTNAME_HEADER, 169	ER_APPLIER_LOG_EVENT_VALIDATION_ERROR,
ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM,	100
169	ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_R,
ER_ADD_PARTITION_NO_NEW_PARTITION, 38	144
ER_ADD_PARTITION_SUBPART_ERROR, 38	ER_ATTRIBUTE_IGNORED, 103
ER_ADMIN_WRONG_MRG_TABLE, 36	ER_AUDIT_API_ABORT, 84
ER_AES_INVALID_IV, 67	ER_AUDIT_CANT_ABORT_COMMAND, 276
ER_AES_INVALID_KDF_ITERATIONS, 87	ER_AUDIT_CANT_ABORT_EVENT, 276
ER_AES_INVALID_KDF_NAME, 87	ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD,
ER_AES_INVALID_KDF_OPTION_SIZE, 87	571
ER_AGGREGATE_IN_ORDER_NOT_SELECT, 74	ER_AUDIT_LOG_CANNOT_READ_PASSWORD,
ER_AGGREGATE_ORDER_FOR_UNION, 71	564
ER_AGGREGATE_ORDER_NON_AGG_QUERY, 71	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD,
ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED,	64
134	ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTH,
ER_ALTER_FILEGROUP_FAILED, 39	314
ER_ALTER_INFO, 9	ER_AUDIT_LOG_CANNOT_STORE_PASSWORD,
ER_ALTER_OPERATION_NOT_SUPPORTED, 64	564
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY,
64	534
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_A,	ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING,
64	564
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_C,	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE,
64	315
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_C,	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRES,
64	315
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_C,	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPT,
153	315
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_C,	ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE,
64	534
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_C,	ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BE,
64	534
	ER_AUDIT_LOG_FILE_AUTO_PRUNED, 596

---

ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSED,	ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE,
564	316
ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT,	ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE,
564	316
ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING,	ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR,
564	316
ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING_OR_INVALID,	ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY,
564	535
ER_AUDIT_LOG_FILE_PRUNE_FAILED,	ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID,
596	568
ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE,	ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED,
317	314
ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE,	ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED,
317	314
ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READING,	ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED,
317	565
ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE,	ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH,
317	315
ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE,	ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED,
317	568
ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FILTER,	ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST,
316	314
ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE,	ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED,
316	536
ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY,	ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE,
317	534
ER_AUDIT_LOG_FILTER_INVALID_COLUMN_COUNT,	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT,
316	569
ER_AUDIT_LOG_FILTER_INVALID_COLUMN_DEFINITION,	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE,
316	568
ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED,	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH,
314	569
ER_AUDIT_LOG_FILTER_RESULT_MSG,	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH,
315	87
ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY,	ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHA,
317	535
ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED,	ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER,
569	534
ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER,	ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS,
534	315
ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR,	ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE,
314	315
ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE,	ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED,
131	315
ER_AUDIT_LOG_INVALID_FILE_CONTENT,	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED,
564	314
ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE,	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_FILE,
639	315
ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED,	ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENT,
533	200
ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST,	ER_AUDIT_PLUGIN_HAS_INVALID_DATA,
535	200
ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY,	ER_AUDIT_WARNING,
534	276
ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR,	ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM,
533	197
ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL,	
316	

---

ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE TABLES, 197	ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS_IN, 637
ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE, 197	ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED, 609
ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME, 197	ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR, 609
ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE, 197	ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH, 636
ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME, 585	ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED, 636
ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION, 585	ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT, 608
ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED, 196	ER_AUTHENTICATION_PLUGIN_LOG, 609
ER_AUTHCACHE_PLUGIN_CONFIG, 195	ER_AUTHENTICATION_PLUGIN_OOM, 608
ER_AUTHCACHE_PLUGIN_MISSING, 195	ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED, 608
ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROUTINE, 197	ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT, 608
ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE, 197	ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT, 608
ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE, 195	ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED, 608
ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME, 585	ER_AUTHENTICATION_POLICY_MISMATCH, 149
ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION, 585	ER_AUTH_CANT_ACTIVATE_ROLE, 193
ER_AUTHCACHE_ROLE_TABLES_DODGY, 195	ER_AUTH_CANT_CREATE_RSA_PAIR, 194
ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE, 198	ER_AUTH_CANT_SET_DEFAULT_PLUGIN, 181
ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING, 197	ER_AUTH_CANT_WRITE_PRIVKEY, 194
ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD, 196	ER_AUTH_CANT_WRITE_PUBKEY, 194
ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD, 196	ER_AUTH_CERTS_SAVED_TO_DATADIR, 194
ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN, 196	ER_AUTH_CERT_GENERATION_DISABLED, 194
ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE, 196	ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY, 557
ER_AUTHCACHE_USER_TABLE_DODGY, 196	ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG, 603
ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY, 636	ER_AUTH_KEYS_SAVED_TO_DATADIR, 195
ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY, 609	ER_AUTH_KEY_GENERATION_DISABLED, 195
ER_AUTHENTICATION_OCI_IAM, 610	ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT, 195
ER_AUTHENTICATION_OCI_IMDS, 609	ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG, 320
ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_STRUNG, 610	ER_AUTH_RSA_CANT_FIND, 192
ER_AUTHENTICATION_OCI_INVALID_TOKEN, 636	ER_AUTH_RSA_CANT_PARSE, 192
ER_AUTHENTICATION_OCI_NONCE, 610	ER_AUTH_RSA_CANT_READ, 192
ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND, 610	ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION, 195
ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS, 610	ER_AUTH_RSA_FILES_NOT_FOUND, 193
	ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION, 194
	ER_AUTH_USING_EXISTING_CERTS, 194
	ER_AUTOINC_READ_FAILED, 35
	ER_AUTO_CONVERT, 21
	ER_AUTO_INCREMENT_CONFLICT, 66
	ER_AUTO_OPTIONS_FAILED, 182

---

---

ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF, 57	ER_BINLOG_CANT_OPEN_TMP_INDEX, 269
ER_BACK_IN_TIME, 174	ER_BINLOG_CANT_RESIZE_CACHE, 265
ER_BAD_DB_ERROR, 6	ER_BINLOG_CANT_SET_TMP_INDEX_NAME, 268
ER_BAD_FIELD_ERROR, 7	ER_BINLOG_CANT_TRIM_CRASHED_BINLOG, 272
ER_BAD_FT_COLUMN, 24	ER_BINLOG_CANT_USE_FOR_LOGGING, 267
ER_BAD_HOST_ERROR, 6	ER_BINLOG_CRASHED_BINLOG_TRIMMED, 272
ER_BAD_LOG_STATEMENT, 42	ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED, 622
ER_BAD_NULL_ERROR, 6	ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS, 622
ER_BAD_NULL_ERROR_NOT_IGNORED, 104	ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED_SE, 622
ER_BAD_REPLICA, 17	ER_BINLOG_CRASH_RECOVERY_FAILED, 272
ER_BAD_REPLICA_AUTO_POSITION, 57	ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG, 622
ER_BAD_REPLICA_UNTIL_COND, 23	ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED, 623
ER_BAD_SLAVE, 17	ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED, 622
ER_BAD_SLAVE_AUTO_POSITION, 57	ER_BINLOG_CREATE_ROUTINE_NEED_SUPER, 32
ER_BAD_SLAVE_UNTIL_COND, 23	ER_BINLOG_END, 175
ER_BAD_TABLE_ERROR, 6	ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX, 269
ER_BAD_TIMESTAMP_FORMAT, 157	ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG, 267
ER_BASE64_DECODE_ERROR, 42	ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG, 267
ER_BASEDIR_SET_TO, 282	ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA, 267
ER_BEFORE_DML_VALIDATION_ERROR, 78	ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO, 267
ER_BEG_INITFILE, 177	ER_BINLOG_EVENTS_READ_FROM_RELAY_LOG_INFO, 267
ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD, 640	ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING BINLOG, 283
ER_BEYOND_SERVER_UPGRADE_THRESHOLD, 640	ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER, 298
ER_BINLOG_ATTACHING_THREAD_MEMORY_FINALIZE_FAILED, 265	ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOGETHER, 105
ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX, 54	ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING BINLOG, 268
ER_BINLOG_CACHE_SIZE_TOO_LARGE, 277	ER_BINLOG_FAILED_TO_DELETE_LOG_FILE, 271
ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX, 268	ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING BINLOG, 268
ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG, 272	ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE, 270
ER_BINLOG_CANT_CLOSE_TMP_INDEX, 269	ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE, 269
ER_BINLOG_CANT_COPY_INDEX_TO_TMP, 269	ER_BINLOG_FAILED_TO_READ_REGISTER_FILE, 270
ER_BINLOG_CANT_CREATE_CACHE_FOR_LOG, 266	
ER_BINLOG_CANT_DELETE_FILE, 268	
ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX, 271	
ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILE, 271	
ER_BINLOG_CANT_FIND_LOG_IN_INDEX, 271	
ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME, 267	
ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES, 268	
ER_BINLOG_CANT_MOVE_TMP_TO_INDEX, 269	
ER_BINLOG_CANT_OPEN_CRASHED_BINLOG, 271	
ER_BINLOG_CANT_OPEN_FOR_LOGGING, 266	
ER_BINLOG_CANT_OPEN_LOG, 266	

---

ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE, 270	ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN, 269
ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE, 268	ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER, 269
ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK, 272	ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE, 270
ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK, 272	ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE, 269
ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME, 270	ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE, 270
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE, 266	ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG, 270
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN, 267	ER_BINLOG_PURGE_PROHIBITED, 30
ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLE, 255	ER_BINLOG_RECOVERING_AFTER_CRASH_USING, 271
ER_BINLOG_FATAL_ERROR, 43	ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE, 47
ER_BINLOG_FILE_BEING_READ_NOT_PURGED, 265	ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE, 48
ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED, 266	ER_BINLOG_ROW_INJECTION_AND_STMT_MODE, 48
ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LONG, 266	ER_BINLOG_ROW_LOGGING_FAILED, 40
ER_BINLOG_FILE_NAME_TOO_LONG, 266	ER_BINLOG_ROW_MODE_AND_STMT_ENGINE, 47
ER_BINLOG_FILE_OPEN_FAILED, 283	ER_BINLOG_ROW_VALUE_OPTION_IGNORED, 526
ER_BINLOG_IO_ERROR_READING_HEADER, 266	ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_A, 527
ER_BINLOG_LOGGING_IMPOSSIBLE, 43	ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX, 54
ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS, 271	ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE, 277
ER_BINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES, 271	ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES, 63
ER_BINLOG_LOGGING_NOT_POSSIBLE, 297	ER_BINLOG_STMT_MODE_AND_ROW_ENGINE, 48
ER_BINLOG_LOGICAL_CORRUPTION, 65	ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READON, 561
ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG, 299	ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL, 143
ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION, 119	ER_BINLOG_UNSAFE_AUTOINC_COLUMNS, 48
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP, 120	ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST, 53
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP, 120	ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT, 62
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE, 119	ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT, 52
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT, 120	ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC, 53
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE, 119	ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBST, 563
ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING, 48	ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN, 69
ER_BINLOG_NEEDS_SERVERID, 180	ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT, 52
ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING, 255	ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE, 52
ER_BINLOG_PURGE_EMFILE, 42	
ER_BINLOG_PURGE_FATAL_ERR, 30	

---

ER_BINLOG_UNSAFE_TWO_KEYS, 53	ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORED, 629
ER_BINLOG_UNSAFE_LIMIT, 48	ER_BULK_LOADER_INFO, 629
ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT, 278	ER_BULK_LOAD_DATA_FAILED, 159
ER_BINLOG_UNSAFE_MIXED_STATEMENT, 50	ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED, 160
ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE, 50	ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED_LOG, 630
ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS, 48	ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE, 160
ER_BINLOG_UNSAFE_NOWAIT, 93	ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE_LOG, 631
ER_BINLOG_UNSAFE_REPLACE_SELECT, 52	ER_BULK_PARSER_MISSING_ENCLOSED_BY, 159
ER_BINLOG_UNSAFE_ROUTINE, 32	ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG, 630
ER_BINLOG_UNSAFE_SKIP_LOCKED, 93	ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED, 159
ER_BINLOG_UNSAFE_STATEMENT, 43	ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED_LOG, 630
ER_BINLOG_UNSAFE_SYSTEM_FUNCTION, 48	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR, 160
ER_BINLOG_UNSAFE_SYSTEM_TABLE, 48	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR_LOG, 631
ER_BINLOG_UNSAFE_SYSTEM_VARIABLE, 48	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_IDENTIFIER, 160
ER_BINLOG_UNSAFE_UDF, 48	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_IDENTIFIER_LOG, 630
ER_BINLOG_UNSAFE_UPDATE_IGNORE, 52	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPED, 160
ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT, 53	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPED_LOG, 630
ER_BINLOG_UNSAFE_XA, 86	ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT, 160
ER_BINLOG_USE_V1_ROW_EVENTS_IGNORED, 527	ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT_LOG, 631
ER_BINLOG_WARNING_SUPPRESSED, 272	ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR, 160
ER_BLOBS_AND_NO_TERMINATED, 9	ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG, 630
ER_BLOB_CANT_HAVE_DEFAULT, 10	ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_EXCEPTION, 160
ER_BLOB_FIELD_IN_PART_FUNC_ERROR, 37	ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_EXCEPTION_LOG, 630
ER_BLOB_KEY_WITHOUT_LENGTH, 15	ER_BULK_READER_COMMUNICATION_ERROR, 159
ER_BLOB_USED_AS_KEY, 8	ER_BULK_READER_COMMUNICATION_ERROR_LOG, 630
ER_BOOST_GEOMETRY_CENTROID_EXCEPTION, 72	ER_BULK_READER_INFO, 629
ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION, 72	ER_BULK_READER_LIBCURL_ERROR, 159
ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION, 80	ER_BULK_READER_LIBCURL_ERROR_LOG, 629
ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION, 72	ER_BULK_READER_LIBCURL_INIT_FAILED, 158
ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION, 72	ER_BULK_READER_LIBCURL_INIT_FAILED_LOG, 629
ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION, 72	ER_BULK_READER_SERVER_ERROR, 159
ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION, 72	ER_BULK_READER_SERVER_ERROR_LOG, 629
ER_BOOTSTRAP_CANT_THREAD, 162	ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_USAGE_IGNORED, 159
ER_BUFPOOL_RESIZE_INPROGRESS, 84	ER_CALL_ME_LOCALHOST, 175
ER_BUILD_ID, 625	
ER_BULK_EXECUTOR_ERROR, 158	
ER_BULK_EXECUTOR_INFO, 629	
ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVER_BUFFER, 159	
ER_BULK_LOADER_COMPONENT_ERROR, 159	
ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORED, 159	

---

ER_CANNOT_ADD_FOREIGN, 19	ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTO
ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED, 86	143
ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL, 84	ER_CANT_CREATE_ADMIN_THREAD, 549
ER_CANNOT_ALTER_SRID_DUE_TO_INDEX, 101	ER_CANT_CREATE_CACHE_FOR_DB_OPT, 260
ER_CANNOT_CHANGE_TO_ROOT_DIR, 282	ER_CANT_CREATE_DB, 3
ER_CANNOT_CONVERT_STRING, 125	ER_CANT_CREATE_FILE, 3
ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT, 84	ER_CANT_CREATE_GEOMETRY_OBJECT, 32
ER_CANNOT_DISCARD_TEMPORARY_TABLE, 69	ER_CANT_CREATE_HANDLER_FILE, 37
ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX, 113	ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE, 259
ER_CANNOT_FIND_KEY_IN_KEYRING, 85	ER_CANT_CREATE_HANDLE_MGR_THREAD, 166
ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE, 553	ER_CANT_CREATE_INTERRUPT_THREAD, 173
ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER, 127	ER_CANT_CREATE_NAMED_PIPES_THREAD, 173
ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_USER, 129	ER_CANT_CREATE_PID_FILE, 172
ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES, 613	ER_CANT_CREATE_SCHEDULER_THREAD, 167
ER_CANNOT_LOAD_FROM_TABLE_V2, 53	ER_CANT_CREATE_SHM_THREAD, 173
ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES, 91	ER_CANT_CREATE_SHUTDOWN_THREAD, 172
ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GRID, 77	ER_CANT_CREATE_TABLE, 3
ER_CANNOT_PERSIST_SENSITIVE_VARIABLES, 154	ER_CANT_CREATE_TABLE_SHARE_FROM_FRM, 259
ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK, 153	ER_CANT_CREATE_TCPIP_THREAD, 173
ER_CANNOT_SET_DATABASE_ENCRYPTION, 122	ER_CANT_CREATE_TEST_FILE, 172
ER_CANNOT_SET_LOG_ERROR_SERVICES, 282	ER_CANT_CREATE_THREAD, 13
ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE, 553	ER_CANT_CREATE_USER_WITH_GRANT, 32
ER_CANNOT_SET_TABLESPACE_ENCRYPTION, 122	ER_CANT_CREATE_UUID, 170
ER_CANNOT_SET_TABLE_ENCRYPTION, 122	ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN, 217
ER_CANNOT_USER, 31	ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_N
ER_CANNOT_USER_REFERENCED_AS_DEFINER, 142	58
ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE, 145	ER_CANT_DO_THIS_DURING_AN_TRANSACTION, 15
ER_CANNOT_USE_ENCRYPTION_CLAUSE, 122	ER_CANT_DROP_FIELD_OR_KEY, 9
ER_CANT_ACCESS_CAPATH, 181	ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_TRANSACTION, 79
ER_CANT_AGGREGATE_2COLLATIONS, 22	ER_CANT_EXECUTE_COMMAND_WITH_ASSIGNED_GTID, 153
ER_CANT_AGGREGATE_3COLLATIONS, 22	ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION, 59
ER_CANT_AGGREGATE_NCOLLATIONS, 23	ER_CANT_FIND_DL_ENTRY, 12
ER_CANT_ALLOC_TABLE_OBJECT, 259	ER_CANT_FIND_SYSTEM_REC, 4
ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE, 161	ER_CANT_FIND_UDF, 12
ER_CANT_CHANGE_TX_CHARACTERISTICS, 41	ER_CANT_GET_STAT, 4
ER_CANT_CHECK_PID_PATH, 388	ER_CANT_HASH_DO_AND_IGNORE_RULES, 181
ER_CANT_CHOWN_DATADIR, 181	ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT, 261
	ER_CANT_INCREASE_MAX_OPEN_FILES, 177
	ER_CANT_INITIALIZE_BUILTIN_PLUGINS, 180
	ER_CANT_INITIALIZE_DYNAMIC_PLUGINS, 180
	ER_CANT_INITIALIZE_EARLY_PLUGINS, 180
	ER_CANT_INITIALIZE_GTID, 180
	ER_CANT_INITIALIZE_UDF, 12
	ER_CANT_INIT_DBS, 178
	ER_CANT_INIT_SCHEDULER_THREAD, 167
	ER_CANT_INIT_TC_LOG, 167

---

---

ER_CANT_INIT_TIMER, 182	ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_ON,
ER_CANT_JOIN_SHUTDOWN_THREAD, 181	58
ER_CANT_LOCK, 4	ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_ON,
ER_CANT_LOCK_LOG_TABLE, 40	58
ER_CANT_LOCK_TABLE, 259	ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID,
ER_CANT_LOCK_TABLESPACE, 260	59
ER_CANT_MODIFY_SRID_0, 108	ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS,
ER_CANT_MODIFY_SRS_USED_BY_COLUMN, 109	90
ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES,	ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS_INVALID,
200	63
ER_CANT_OPEN_CA, 181	ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS_IS_NOT_EMPTY,
ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE,	63
262	ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE,
ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET,	260
260	ER_CANT_SET_PATH_FOR, 262
ER_CANT_OPEN_DIR, 262	ER_CANT_SET_PERSISTED, 161
ER_CANT_OPEN_ERROR_LOG, 182	ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS,
ER_CANT_OPEN_FILE, 4	144
ER_CANT_OPEN_FRM_FILE, 199	ER_CANT_SET_UP_PERSISTED_VALUES, 181
ER_CANT_OPEN_LIBRARY, 12	ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID,
ER_CANT_OPEN_TABLE_MYSQL_PROC, 262	81
ER_CANT_PARSE_STORED_ROUTINE_BODY, 262	ER_CANT_START_ERROR_LOG_SERVICE, 281
ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED_COLUMN,	ER_CANT_START_DATADIR, 181
572	ER_CANT_STAT_FILE, 270
ER_CANT_READ_DIR, 4	ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT,
ER_CANT_READ_ERRMSG, 178	54
ER_CANT_READ_FRM_FILE, 200	ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG,
ER_CANT_READ_TABLE_MYSQL_PROC, 262	34
ER_CANT_REMOVE_ALL_FIELDS, 9	ER_CANT_UPDATE_WITH_READLOCK, 19
ER_CANT_REMOVE_PID_FILE, 172	ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD,
ER_CANT_RENAME_LOG_TABLE, 42	260
ER_CANT_REOPEN_TABLE, 13	ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_ON,
ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION,	513
533	ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF,
ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_ON,	513
533	ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON,
ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF,	151
533	ER_CANT_USE_OPTION_HERE, 20
ER_CANT_RESET_MASTER, 85	ER_CANT_USE_SAME_UUID_AS_GROUP_NAME,
ER_CANT_RESET_SOURCE, 85	145
ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY,	ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID,
162	147
ER_CANT_SAVE_GTIDS, 181	ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING_GTID,
ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_SQL_THD_AFTER_GTIDS,	84
144	ER_CAPACITY_EXCEEDED, 84
ER_CANT_SET_DATADIR, 180	ER_CAPACITY_EXCEEDED_IN_PARSER, 85
ER_CANT_SET_DATA_DIR, 547	ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER,
ER_CANT_SET_ERROR_LOG_SERVICE, 107	84
ER_CANT_SET_ERROR_SUPPRESSION_LIST, 111	ER_CA_SELF_SIGNED, 169
ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE,	ER_CHANGE_ENFORCE_GTID_CONSISTENCY,
539	166
ER_CANT_SET_GTID_MODE, 79	ER_CHANGED_GTID_MODE, 166
ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_OFF,	58
58	ER_CHANGED_MAX_OPEN_FILES, 177

---



---

ER_CHANGED_TABLE_OPEN_CACHE, 177	ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET,
ER_CHANGE_MASTER_PASSWORD_LENGTH, 73	632
ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CHECK_TABLE_MIN_REC_FLAG_NOT_SET,	635
132	
ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CHECK_TABLE_MIN_REC_FLAG_SET, 634	
132	ER_CLIENT_DOES_NOT_SUPPORT, 101
ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECK	
132	156
ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID_ONLY_UNSAFE_CREATE_DROP_TEMP_TABLE	
150	112
ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITIONS_WITH_GTID_ONLY, TIMEOUT, 146	
151	ER_CLIENT_KEYRING_UDF_KEY_INVALID, 133
ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITIONS_WITHOUT_POSITIONS, 133	
151	ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG, 133
ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITHOUT_POSITIONS,	
151	ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID,
ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROWS_FORMAT_WITH_GTID_ONLY,	
150	ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG,
ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_NO_PRIVILEGE_CHECKS_USER_CANNOT_BE_AN	
151	133
ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE,	ER_CLIENT_LOCAL_FILES_DISABLED, 135
54	133
ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE, PRIVILEGE_CHECKS_USER_CANNOT_BE_AN	
147	133
ER_CHANGE_SOURCE_PASSWORD_LENGTH, 73	ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST,
ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_CLIENT,	
132	ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPL
ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT,	
132	ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORM
ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT,	
132	ER_CLONE_CHARSET, 126
ER_CHARACTER_SET_MISMATCH, 141	ER_CLONE_CLIENT_TRACE, 547
ER_CHECKING_TABLE, 259	ER_CLONE_CONFIG, 126
ER_CHECKREAD, 4	ER_CLONE_CREATE_HANDLER_FAIL_TRACE, 293
ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION_ON_COLUMNS,	
121	ER_CLONE_DDL_IN_PROGRESS, 100
ER_CHECK_CONSTRAINT_DUP_NAME, 121	ER_CLONE_DISALLOWED, 127
ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED,	
120	ER_CLONE_DONOR, 126
ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED,	
120	ER_CLONE_DONOR_TRACE, 546
ER_CHECK_CONSTRAINT_NOT_FOUND, 121	ER_CLONE_DONOR_VERSION, 126
ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENTED_COLUMN,	
121	ER_CLONE_ENCRYPTION, 127
ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN,	
121	ER_CLONE_HANDLER_EXISTS, 293
ER_CHECK_CONSTRAINT_ROW_VALUE, 121	ER_CLONE_HANDLER_EXIST_TRACE, 293
ER_CHECK_CONSTRAINT_VARIABLES, 121	ER_CLONE_INFO_CLIENT, 546
ER_CHECK_CONSTRAINT_VIOLATED, 121	ER_CLONE_INFO_SERVER, 547
ER_CHECK_NOT_IMPLEMENTED, 15	ER_CLONE_IN_PROGRESS, 127
ER_CHECK_NO_SUCH_TABLE, 15	ER_CLONE_LOOPBACK, 127
ER_CHECK_TABLE_FUNCTIONS, 642	ER_CLONE_NETWORK_PACKET, 136
ER_CHECK_TABLE_FUNCTIONS_DETAIL, 642	ER_CLONE_OS, 126
	ER_CLONE_PLATFORM, 126
	ER_CLONE_PLUGIN_MATCH, 126
	ER_CLONE_PLUGIN_NOT_LOADED, 293
	ER_CLONE_PLUGIN_NOT_LOADED_TRACE, 293
	ER_CLONE_PROTOCOL, 126
	ER_CLONE_PROTOCOL_ERROR, 546
	ER_CLONE_PROTOCOL_TRACE, 546

---

---

ER_CLONE_REMOTE_ERROR, 546	ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP,
ER_CLONE_SERVER_TRACE, 547	90
ER_CLONE_SHUTDOWN_TRACE, 566	ER_COMPONENTS_UNLOAD_NOT_LOADED, 90
ER_CLONE_SYS_CONFIG, 126	ER_COMPONENT_EE_DATA_DECRYPTION_ERROR,
ER_CLONE_TOO_MANY_CONCURRENT_CLONES,	624
100	ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR,
ER_CMD_NEED_SUPER, 99	624
ER_COALESCE_ONLY_ON_HASH_PARTITION, 38	ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE,
ER_COALESCE_PARTITION_NO_PARTITION, 38	624
ER_COLLATION_CHARSET_MISMATCH, 21	ER_COMPONENT_EE_DATA_SIGN_ERROR, 624
ER_COLUMNACCESS_DENIED_ERROR, 13	ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE,
ER_COLUMN_CHANGE_SIZE, 128	623
ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMNS,	ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM,
120	623
ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2,	ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENTS,
61	623
ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE,	ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE,
41	623
ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2,	ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILURE,
69	624
ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CONTEXT,	ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_FAILURE,
156	624
ER_COMMAND_SERVICE_BACKEND_FAILED, 156	ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE,
ER_COMMENT_CONTAINS_INVALID_STRING, 153	623
ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG, 32	ER_COMPONENT_EE_INSUFFICIENT_LENGTH,
ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION,	624
90	ER_COMPONENT_EE_OPENSSL_ERROR, 624
ER_COMPONENTS_CANT_LOAD, 89	ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE,
ER_COMPONENTS_CANT_RELEASE_SERVICE, 90	623
ER_COMPONENTS_CANT_SATISFY_DEPENDENCY,	ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE,
90	623
ER_COMPONENTS_CANT_UNLOAD, 90	ER_COMPONENT_FILTER_CONFUSED, 321
ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION,	ER_COMPONENT_FILTER_DIAGNOSTICS, 107
298	ER_COMPONENT_FILTER_FLABBERGASTED, 98
ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP,	ER_COMPONENT_FILTER_WRONG_VALUE, 528
169	ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY,
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINITIALIZE,	526
596	ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE,
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT,	626
596	ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE,
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN,	626
169	ER_COMPONENT_LOCK, 638
ER_COMPONENTS_LOAD_CANT_INITIALIZE, 90	ER_COMPONENT_MANIPULATE_ROW_FAILED, 90
ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION,	ER_COMPONENT_MASKING_ABI, 638
90	ER_COMPONENT_MASKING_ABI_REASON, 638
ER_COMPONENTS_NO_SCHEME, 89	ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE,
ER_COMPONENTS_NO_SCHEME_SERVICE, 89	638
ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP,	ER_COMPONENT_MASKING_OTHER_ERROR, 638
169	ER_COMPONENT_MASKING_RANDOM_CREATE,
ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE,	638
90	ER_COMPONENT_MASKING_RANDOM_CREATE_REASON,
ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE,	638
90	ER_COMPONENT_SERVICE_CALL, 638
	ER_COMPONENT_SERVICE_CALL_RESULT, 638

---

---

ER_COMPONENT_TABLE_INCORRECT, 90	ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT, 189
ER_COMPONENT_UNLOCK, 638	ER_CONN_TCP_LISTEN_FAIL, 190
ER_CONCURRENT_PROCEDURE_USAGE, 152	ER_CONN_TCP_NO_SOCKET, 189
ER_CONDITIONAL_DEBUG, 625	ER_CONN_TCP_RESOLVE_INFO, 190
ER_COND_ITEM_TOO_LONG, 46	ER_CONN_TCP_START_FAIL, 190
ER_CONFIG_OPTION_WITHOUT_GROUP, 185	ER_CONN_TPC_BIND_FAIL, 190
ER_CONFIRMING_THE_FUTURE, 174	ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET, 190
ER_CONFLICTING_DECLARATIONS, 25	ER_CONN_UNIX_LISTEN_FAILED, 191
ER_CONFLICT_FN_PARSE_ERROR, 45	ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE, 192
ER_CONNECTION_ABORTED, 527	ER_CONN_UNIX_LOCK_FILE_CANT_CREATE, 191
ER_CONNECTION_HANDLING_OOM, 172	ER_CONN_UNIX_LOCK_FILE_CANT_DELETE, 192
ER_CONNECTION_METADATA, 17	ER_CONN_UNIX_LOCK_FILE_CANT_OPEN, 191
ER_CONNECT_TO_FOREIGN_DATA_SOURCE, 33	ER_CONN_UNIX_LOCK_FILE_CANT_READ, 191
ER_CONNECT_TO_MASTER, 19	ER_CONN_UNIX_LOCK_FILE_CANT_SYNC, 192
ER_CONNECT_TO_SOURCE, 19	ER_CONN_UNIX_LOCK_FILE_CANT_WRITE, 192
ER_CONN_ATTR_TRUNCATED, 193	ER_CONN_UNIX_LOCK_FILE_EMPTY, 191
ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED, 323	ER_CONN_UNIX_LOCK_FILE_FAIL, 191
ER_CONN_CONTROL_ERROR_MSG, 320	ER_CONN_UNIX_LOCK_FILE_GIVING_UP, 191
ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED, 322	ER_CONN_UNIX_LOCK_FILE_PIDLESS, 192
ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY, 323	ER_CONN_UNIX_NO_BIND_NO_START, 191
ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY, 323	ER_CONN_UNIX_NO_FD, 191
ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE, 323	ER_CONN_UNIX_PATH_TOO_LONG, 191
ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED, 323	ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE, 190
ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED, 323	ER_CONSECUTIVE_REORG_PARTITIONS, 39
ER_CONN_INIT_CONNECT_IGNORED, 322	ER_CONVERT_FAILED, NOT_FOUND, 134
ER_CONN_INIT_CONNECT_IGNORED_MFA, 639	ER_CONVERT_MULTI_VALUE, 639
ER_CONN_LIMIT, 612	ER_UPDATE_CANT_BE_UPDATED, 5
ER_CONN_PER_THREAD_NO_THREAD, 189	ER_UPDATE_CANT_BE_UPDATED, 5
ER_CONN_PIP_CANT_CREATE_EVENT, 188	ER_CORE_VALUES, 174
ER_CONN_PIP_CANT_CREATE_PIPE, 188	ER_CORRUPTED_JSON_DIFF, 102
ER_CONN_SHM_CANT_CREATE_CONNECTION, 188	ER_CORRUPT_HELP_DB, 21
ER_CONN_SHM_CANT_CREATE_SERVICE, 188	ER_COULD_NOT_APPLY_JSON_DIFF, 102
ER_CONN_SHM_LISTENER, 188	ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY, 541
ER_CONN_SOCKET_ACCEPT_FAILED, 192	ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS, 535
ER_CONN_SOCKET_SELECT_FAILED, 192	ER_CRASHED_ON_REPAIR, 17
ER_CONN_TCP_ADDRESS, 189	ER_CRASHED_ON_USAGE, 16
ER_CONN_TCP_BIND_FAIL, 190	ER_CREATED_SYSTEM_WITH_VERSION, 291
ER_CONN_TCP_BIND_RETRY, 190	ER_CREATE_FILEGROUP_FAILED, 39
ER_CONN_TCP_CANT_RESET_V6ONLY, 190	ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR, 156
ER_CONN_TCP_CANT_RESOLVE_HOSTNAME, 189	ER_CREATING_NEW_UUID, 170
ER_CONN_TCP_CREATED, 189	ER_CREATING_NEW_UUID_FIRST_START, 281
ER_CONN_TCP_ERROR_WITH_STRERROR, 189	ER_CREDENTIALLESS_AUTO_USER_BAD, 172
ER_CONN_TCP_IPV6_AVAILABLE, 189	ER_CREDENTIALS_CONTRADICT_TO_HISTORY, 100
ER_CONN_TCP_IPV6_UNAVAILABLE, 189	ER_CTE_MAX_RECURSION_DEPTH, 100
ER_CONN_TCP_IP_NOT_LOGGED, 190	ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER, 93
	ER_CTE_RECURSIVE_FORBIDS_AGGREGATION, 93

---

---

ER_CTE_RECURSIVE_NOT_UNION, 156	ER_DEBUG_CHECK_SHARES_OPEN, 222
ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST, 93	ER_DB_ACCESS_DENIED, 127
ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE, 94	ER_DB_CREATE_EXISTS, 4
ER_CTE_RECURSIVE_REQUIRES_UNION, 93	ER_DB_DROP_EXISTS, 4
ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED, 129	ER_DB_DROP_RMDIR, 4
ER_CURRENT_PASSWORD_NOT_REQUIRED, 129	ER_DB_DROP_RMDIR2, 97
ER_CUT_VALUE_GROUP_CONCAT, 22	ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET, 261
ER_CYCLE_TIMER_IS_NOT_AVAILABLE, 294	ER_DDL_IN_PROGRESS, 100
ER_DATABASE_NAME, 45	ER_DDL_LOG_ERROR, 41
ER_DATA_DIRECTORY_UNUSABLE, 542	ER_DDL_MSG_1, 605
ER_DATA_DIRECTORY_UNUSABLE_DELETABLE, 565	ER_DD_ABORTING_PARTIAL_UPGRADE, 198
ER_DATA_OUT_OF_RANGE, 50	ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN, 165
ER_DATA_TOO_LONG, 31	ER_DD_CANT_CREATE_OBJECT_KEY, 165
ER_DATETIME_FUNCTION_OVERFLOW, 34	ER_DD_CANT_CREATE_SP, 260
ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANIFEST, 127	ER_DD_CANT_FETCH_TABLE_DATA, 260
ER_DA_CANT_OPEN_ERROR_LOG, 142	ER_DD_CANT_FIX_SE_DATA, 260
ER_DA_CONN_LIMIT, 152	ER_DD_CANT_RESOLVE_VIEW, 183
ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED, 148	ER_DD_CREATED_FOR_UPGRADE, 198
ER_DA_ERROR_LOG_MULTIPLE_FILTERS, 142	ER_DD_ERROR_CREATING_ENTRY, 260
ER_DA_ERROR_LOG_TABLE_DISABLED, 142	ER_DD_FAILSAFE, 163
ER_DA_EXPIRE_LOGS_DAYS_IGNORED, 156	ER_DD_FRM_EXISTS_FOR_TABLE, 198
ER_DA_GLOBAL_CONN_LIMIT, 152	ER_DD_INITIALIZE, 299
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT, 138	ER_DD_INITIALIZE_SQL_ERROR, 536
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID, 139	ER_DD_INIT_FAILED, 164
ER_DA_GRP_RPL_STARTED_AUTO_REJOIN, 131	ER_DD_INIT_UPGRADE_FAILED, 164
ER_DA_INVALID_CONDITION_NUMBER, 56	ER_DD_METADATA_NOT_FOUND, 165
ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED, 142	ER_DD_MINOR_DOWNGRADE, 300
ER_DA_OOM, 135	ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED, 300
ER_DA_PLUGIN_INSTALL_ERROR, 128	ER_DD_NO_VERSION_FOUND, 300
ER_DA_RPL_GTID_TABLE_CANNOT_OPEN, 128	ER_DD_NO_WRITES_NO_REPOPULATION, 163
ER_DA_SSL_FIPS_MODE_ERROR, 151	ER_DD_OBJECT_RELEASER_REMAINS, 165
ER_DA_SSL_LIBRARY_ERROR, 128	ER_DD_OBJECT_REMAINS, 165
ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET, 136	ER_DD_OBJECT_REMAINS_IN_RELEASER, 165
ER_DA_UDF_INVALID_CHARSET, 134	ER_DD_POPULATING_TABLES_FAILED, 165
ER_DA_UDF_INVALID_CHARSET_SPECIFIED, 134	ER_DD_RESTART, 300
ER_DA_UDF_INVALID_COLLATION, 134	ER_DD_SCHEMA_NOT_FOUND, 198
ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE, 134	ER_DD_SE_INIT_FAILED, 198
ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET, 136	ER_DD_TABLESPACE_NOT_FOUND, 183
ER_DA_UNKNOWN_ERROR_NUMBER, 128	ER_DD_TABLE_NOT_FOUND, 198
ER_DBACCESS_DENIED_ERROR, 6	ER_DD_TRG_CANT_ADD, 183
ER_DEBUG_CHECK_SHARES_DROPPED, 223	ER_DD_TRG_CONNECTION_COLLATION_MISSING, 183
ER_DEBUG_CHECK_SHARES_INFO, 222	ER_DD_TRG_DB_COLLATION_MISSING, 183
	ER_DD_TRG_DEFINER_OOM, 183
	ER_DD_TRG_FILE_UNREADABLE, 183
	ER_DD_UPDATE_DATADIR_FLAG_FAIL, 642
	ER_DD_UPDATING_PLUGIN_MD_FAILED, 165
	ER_DD_UPGRADE, 300
	ER_DD_UPGRADE_COMPLETED, 562
	ER_DD_UPGRADE_DD_OPEN_FAILED, 288

---

---

ER_DD_UPGRADE_DD_POPULATED, 289	ER_DEBUG_SYNC_HIT_LIMIT, 46
ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR, 290	ER_DEBUG_SYNC_OOM, 167
ER_DD_UPGRADE_FAILED_INIT_DD_SE, 290	ER_DEBUG_SYNC_THREAD_MAX, 166
ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE, 288	ER_DEBUG_SYNC_TIMEOUT, 46
ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS, 290	ER_DEFAULT_AS_VAL_GENERATED, 115
ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS, 289	ER_DEFAULT_SE_UNAVAILABLE, 182
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES, 289	ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALL, 115
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES, 288	ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_I, 115
ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE, 288	ER_DEFAULT_VAL_GENERATED_NON_PRIOR, 115
ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE, 299	ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC, 115
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD, 290	ER_DEFAULT_VAL_GENERATED_ROW_VALUE, 115
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD, 290	ER_DEFINITION_CONTAINS_INVALID_STRING, 115
ER_DD_UPGRADE_FOUND_PREPARED_XA_TRANSACTION, 575	ER_ABORT, 115
ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED, 290	ER_DEPART_WITH_GRACE, 169
ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED, 289	ER_DEPENDENT_BY_CHECK_CONSTRAINT, 137
ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED, 289	ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE, 105
ER_DD_UPGRADE_OFF, 300	ER_DEPENDENT_BY_FUNCTIONAL_INDEX, 123
ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED, 288	ER_DEPENDENT_BY_GENERATED_COLUMN, 79
ER_DD_UPGRADE_SCHEMA_UNAVAILABLE, 300	ER_DEPENDENT_BY_PARTITION_FUNC, 125
ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED, 291	ER_DEPRECATED_NATIONAL, 109
ER_DD_UPGRADE_SE_LOGS_FAILED, 290	ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS, 604
ER_DD_UPGRADE_START, 290	ER_DEPRECATED_SYNTAX_NO_REPLACEMENT, 297
ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED, 289	ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT, 297
ER_DD_UPGRADE_TABLE_INTACT_ERROR, 296	ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS, 171
ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED, 290	ER_DEPRECATED_TLS_VERSION_SESSION, 601
ER_DD_UPGRADE_VERSION_NOT_SUPPORTED, 300	ER_DEPRECATED_UTF8_ALIAS, 109
ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG, 299	ER_DEPRECATE_MSG_NO_REPLACEMENT, 297
ER_DD_VERSION_FOUND, 163	ER_DEPRECATE_MSG_WITH_REPLACEMENT, 279
ER_DD_VERSION_INSTALLED, 163	ER_DERIVED_MUST_HAVE_ALIAS, 21
ER_DD_VERSION_UNSUPPORTED, 163	ER_DES_FILE_WRONG_KEY, 185
ER_DD_VIEW_CANT_ALLOC_CHARSET, 164	ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN, 217
ER_DD_VIEW_CANT_CREATE, 165	ER_DETACHING_SESSION_LEFT_BY_PLUGIN, 216
ER_DD_VIEW_WITHOUT_DEFINER, 183	ER_DIMENSION_UNSUPPORTED, 75
ER_DEBUG_SYNC_EXECUTED, 166	ER_DISABLED_STORAGE_ENGINE, 83
ER_DEBUG_SYNC_HIT, 166	ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT, 166
	ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECO, 141
	ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNE, 141
	ER_DISALLOWED_OPERATION, 102
	ER_DISCARD_FK_CHECKS_RUNNING, 61

---

---

ER_DISCONNECTING_REMAINING_CLIENTS, 175	ER_ERRMSG_LOADING_55_STYLE, 199
ER_DISK_FULL_NOWAIT, 104	ER_ERRMSG_MISSING_IN_FILE, 199
ER_DIVISION_BY_ZERO, 29	ER_ERRMSG_OOM, 199
ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT_ORDER, 71	ER_ERRMSG_REPLACEMENTS_FAILED, 275
ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER, 71	ER_ERRMSG_REPLACEMENT_DODGY, 275
ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY, 298	ER_ERROR_DURING_COMMIT, 15
ER_DROP_FILEGROUP_FAILED, 39	ER_ERROR_DURING_FLUSH_LOGS, 16
ER_DROP_INDEX_FK, 40	ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE, 298
ER_DROP_LAST_PARTITION, 38	ER_ERROR_DURING_OPTIMIZE_TABLE, 259
ER_DROP_PARTITION_NON_EXISTENT, 38	ER_ERROR_DURING_ROLLBACK, 15
ER_DROP_PK_COLUMN_TO_DROP_GIPK, 156	ER_ERROR_ENABLING_KEYS, 259
ER_DUPLICATED_VALUE_IN_TYPE, 24	ER_ERROR_INFO_FROM_DA, 532
ER_DUPLICATE_OPTION_KEY, 92	ER_ERROR_IN_TRIGGER_BODY, 52
ER_DUPLICATE_SYS_VAR, 537	ER_ERROR_IN_UNKNOWN_TRIGGER_BODY, 52
ER_DUPLICATE_TABLE_LOCK, 93	ER_ERROR_LOG_DESTINATION_NOT_A_FILE, 591
ER_DUP_ARGUMENT, 19	ER_ERROR_ON_MASTER, 68
ER_DUP_ENTRY, 7	ER_ERROR_ON_MODIFYING_GTID_EXECUTED_TABLE, 84
ER_DUP_ENTRY_AUTOINCREMENT_CASE, 41	ER_ERROR_ON_READ, 4
ER_DUP_ENTRY_WITH_KEY_NAME, 42	ER_ERROR_ON_RENAME, 5
ER_DUP_FD_OPEN_FAILED, 281	ER_ERROR_ON_SOURCE, 68
ER_DUP_FIELDNAME, 7	ER_ERROR_ON_WRITE, 5
ER_DUP_INDEX, 62	ER_ERROR_WHEN_EXECUTING_COMMAND, 19
ER_DUP_KEY, 4	ER_EVENT_ALREADY_EXISTS, 40
ER_DUP_KEYNAME, 7	ER_EVENT_CANNOT ALTER IN THE PAST, 42
ER_DUP_LIST_ENTRY, 71	ER_EVENT_CANNOT_CREATE IN THE PAST, 42
ER_DUP_SIGNAL_SET, 46	ER_EVENT_CANT_FIND_TIMEZONE, 261
ER_DUP_UNIQUE, 15	ER_EVENT_CANT_GET_CHARSET, 261
ER_DUP_UNKNOWN_IN_INDEX, 65	ER_EVENT_CANT_GET_COLLATION, 261
ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE, 107	ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT, 265
ER_EMPTY_PRIVILEGE_NAME_IGNORED, 590	ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD, 261
ER_EMPTY_QUERY, 8	ER_EVENT_CANT_INIT_QUEUE, 167
ER_ENDING_INIT, 535	ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT, 261
ER_END_INITFILE, 177	ER_EVENT_CANT_READ, 40
ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONLINE, 80	ER_EVENT_DOES_NOT_EXIST, 40
ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED, 139	ER_EVENT_DROPPING, 214
ER_ENGINE_CANT_DROP_MISSING_TABLE, 97	ER_EVENT_ENDS_BEFORE_STARTS, 40
ER_ENGINE_CANT_DROP_TABLE, 97	ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BINLOG, 264
ER_ENGINE_COST_FAILED_TO_READ, 213	ER_EVENT_ERROR_DURING_COMPILATION, 214
ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE, 213	ER_EVENT_ERROR_EXECUTION_FAILED, 167
ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE, 213	ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER, 214
ER_ENGINE_COST_UNKNOWN_COST_CONSTANT, 212	ER_EVENT_EXECUTION_FAILED_USER_LOST_EVEN_PRIVILEGE, 214
ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE, 213	ER_EVENT_EXEC_TIME_IN_THE_PAST, 40
ER_ENGINE_OUT_OF_MEMORY, 69	ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG, 40
ER_ERRMSG_CANT_FIND_FILE, 198	ER_EVENT_INVALID_CREATION_CTX, 43
ER_ERRMSG_CANT_READ, 199	ER_EVENT_LAST_EXECUTION, 167
	ER_EVENT_MESSAGE_STACK, 167

---

---

ER_EVENT_PURGING_QUEUE, 167	ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP,
ER_EVENT_RECURSION_FORBIDDEN, 42	285
ER_EVENT_SAME_NAME, 40	ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY,
ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT,	
265	ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST,
ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB,	135
265	ER_FAILED_TO_FIND_COLLATION_NAME, 280
ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE,	ER_FAILED_TO_FIND_DL_ENTRY, 277
265	ER_FAILED_TO_FIND_LOCALE_NAME, 280
ER_EVENT_SET_VAR_ERROR, 41	ER_FAILED_TO_FIND_MYSQLD_STATUS, 297
ER_EVENT_UNABLE_TO_DROP_EVENT, 265	ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE,
ER_EXCEEDED_MV_KEYS_NUM, 130	277
ER_EXCEEDED_MV_KEYS_SPACE, 130	ER_FAILED_TO_GET_ABSOLUTE_PATH, 281
ER_EXCEPTIONS_WRITE_ERROR, 45	ER_FAILED_TO_HANDLE_DEFAULTS_FILE, 537
ER_EXCESS_ARGUMENTS, 178	ER_FAILED_TO_INIT_SYS_VAR, 537
ER_EXPIRE_LOGS_DAYS_IGNORED, 298	ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE,
ER_EXPLAIN_NOT_SUPPORTED, 69	205
ER_FAILED_DEFAULT_ROLES, 89	ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THRE
ER_FAILED_GET_DD_PROPERTY, 640	205
ER_FAILED_READ_FROM_PAR_FILE, 50	ER_FAILED_TO_LOCK_MEM, 176
ER_FAILED_REVOKE_ROLE, 89	ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES,
ER_FAILED_ROLE_GRANT, 89	213
ER_FAILED_SET_DD_PROPERTY, 640	ER_FAILED_TO_OPEN_SHARED_LIBRARY, 277
ER_FAILED_START_MYSQLD_DAEMON, 282	ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA,
ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP,	285
286	ER_FAILED_TO_READ_FILE, 278
ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP,	ER_FAILED_TO_REMOVE_TEMP_TABLE, 255
286	ER_FAILED_TO_REPAIR_TABLE, 255
ER_FAILED_TO_ADD_RPL_FILTER, 292	ER_FAILED_TO_SET_PERSISTED_OPTIONS, 298
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP,	ER_FAILED_TO_START_REPLICA_THREAD, 292
286	ER_FAILED_TO_START_SLAVE_THREAD, 291
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP,	ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE,
286	289
ER_FAILED_TO_ALLOCATE_SSL_BIO, 536	ER_FAILED_TO_UPDATE_RESOURCE_GROUP,
ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROL,	285
286	ER_FAILED_TO_WRITE_TO_FILE, 278
ER_FAILED_TO_BINLOG_DROP_EVENT, 291	ER_FAIL_CHROOT, 176
ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES,	ER_FAIL_SETGID, 176
293	ER_FAIL_SETREGID, 176
ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE,	ER_FAIL_SETREUID, 176
205	ER_FAIL_SETUID, 176
ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE,	ER_FEATURE_DISABLED, 24
205	ER_FEATURE_DISABLED_SEE_DOC, 84
ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY,	ER_FEATURE_NOT_AVAILABLE, 79
291	ER_FEATURE_UNSUPPORTED, 103
ER_FAILED_TO_CREATE_CLONE_HANDLER, 293	ER_FIELD_IN_GROUPING_NOT_GROUP_BY, 96
ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD,	ER_FIELD_IN_ORDER_NOT_SELECT, 74
205	ER_FIELD_NOT_FOUND_PART_ERROR, 37
ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE,	ER_FIELD_SPECIFIED_TWICE, 11
289	ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD,
ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS,	
217	ER_FILEGROUP_OPTION_ONLY_ONCE, 39
ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE,	ER_FILESORT_TERMINATED, 280
204	ER_FILE_CORRUPT, 68

---

---

ER_FILE_EXISTS_DURING_UPGRADE, 262	ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE, 33
ER_FILE_EXISTS_ERROR, 9	ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED, 40
ER_FILE_HAS_OLD_FORMAT, 279	ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO, 56
ER_FILE_NOT_FOUND, 4	ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO, 56
ER_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS, 571	ER_FOREIGN_KEY_ON_PARTITIONED, 38
ER_FILE_TYPE_UNKNOWN, 200	ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT, 139
ER_FILE_USED, 5	ER_FOREIGN_SERVER_DOESNT_EXIST, 36
ER_FILSORT_ABORT, 5	ER_FOREIGN_SERVER_EXISTS, 36
ER_FIREWALL_ACCESS_DENIED, 313	ER_FOUND_MISSING_GTIDS, 388
ER_FIREWALL_DEPRECATED_USER_PROFILE, 601	ER_FOUND_ROWS_WHILE_REPAIRING, 259
ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES, 313	ER_FPARSER_BAD_HEADER, 28
ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGE, 313	ER_FPARSER_EOF_IN_COMMENT, 28
ER_FIREWALL_PFS_TABLE_REGISTER_FAILED, 596	ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER, 28
ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED, 313	ER_FPARSER_ERROR_IN_PARAMETER, 28
ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT, 313	ER_FPARSER_TOO_BIG_FILE, 28
ER_FIREWALL_RELOADING_CACHE, 313	ER_FSEEK_FAIL, 30
ER_FIREWALL_RESET_FOR_USER, 313	ER_FT_BOOL_SYNTAX_INVALID, 171
ER_FIREWALL_SERVICES_NOT_ACQUIRED, 595	ER_FT_MATCHING_KEY_NOT_FOUND, 16
ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE, 313	ER_FULLTEXT_FUNCTIONAL_INDEX, 114
ER_FIREWALL_STATUS_FLUSHED, 314	ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING, 56
ER_FIREWALL_SUSPICIOUS_STMT, 313	ER_FULLTEXT_WITH_ROLLUP, 152
ER_FIREWALL_UDF_REGISTER_FAILED, 596	ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG, 130
ER_FIXING_CLIENT_CHARSET, 176	ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED, 114
ER_FK_CANNOT_CHANGE_ENGINE, 116	ER_FUNCTIONAL_INDEX_ON_FIELD, 114
ER_FK_CANNOT_DROP_PARENT, 110	ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTIONS, 113
ER_FK_CANNOT_OPEN_PARENT, 62	ER_FUNCTIONAL_INDEX_ON_LOB, 114
ER_FK_CANNOT_USE_VIRTUAL_COLUMN, 111	ER_FUNCTIONAL_INDEX_PRIMARY_KEY, 113
ER_FK_COLUMN_CANNOT_CHANGE, 63	ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT, 113
ER_FK_COLUMN_CANNOT_CHANGE_CHILD, 63	ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED, 118
ER_FK_COLUMN_CANNOT_DROP, 62	ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET, 140
ER_FK_COLUMN_CANNOT_DROP_CHILD, 62	ER_FUNCTION_NOT_DEFINED, 12
ER_FK_COLUMN_NOT_NULL, 62	ER_FUNC_INEXISTENT_NAME_COLLISION, 45
ER_FK_DEPTH_EXCEEDED, 69	ER_FUTURE_DATE, 174
ER_FK_DUP_NAME, 62	ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED, 78
ER_FK_FAIL_ADD_SYSTEM, 62	ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED, 114
ER_FK_INCOMPATIBLE_COLUMNS, 116	ER_GENERATED_COLUMN_NON_PRIOR, 79
ER_FK_INCORRECT_OPTION, 62	ER_GENERATED_COLUMN_REF_AUTO_INC, 79
ER_FK_NO_COLUMN_PARENT, 111	ER_GENERATED_COLUMN_ROW_VALUE, 114
ER_FK_NO_INDEX_CHILD, 62	ER_GENERATED_COLUMN_VARIABLES, 114
ER_FK_NO_INDEX_PARENT, 62	
ER_FORBID_SCHEMA_CHANGE, 34	
ER_FORCE_CLOSE_THREAD, 278	
ER_FORCING_CLOSE, 8	
ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST, 33	
ER_FOREIGN_DATA_STRING_INVALID, 33	



---

ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT, 128	ER_GRP_DELAYED_VCLE_LOGGING, 561
ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE, 111	ER_GRP_OPERATION_NOT_ALLOWED_GR_MUST_STOP, 137
ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE, 111	ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_M 370
ER_GET_ERRMSG, 25	ER_GRP_RPL_ADD_GRPSID_TO_GRPGTIDSID_MAP_ERR 344
ER_GET_ERRNO, 5	ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_I 356
ER_GET_ERRNO_FROM_STORAGE_ENGINE, 279	ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID 356
ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER, 69	ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAIL 356
ER_GET_TEMPORARY_ERRMSG, 25	ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FA 356
ER_GIPK_COLUMN_ALTER_NOT_ALLOWED, 156	ER_GRP_RPL_ADD_GTID_TO_GRPGTID_EXECUTED_ERR 344
ER_GIPK_COLUMN_EXISTS, 155	ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXE 345
ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS, 155	ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_M 603
ER_GIS_DATA_WRONG_ENDIANNESS, 73	ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY, 358
ER_GIS_DIFFERENT_SRIDS, 72	ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED, 369
ER_GIS_DIFFERENT_SRIDS_AGGREGATION, 146	ER_GRP_RPL_APPENDING_DATA_TO_INTERNAL_CACHE 362
ER_GIS_INVALID_DATA, 72	ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING, 595
ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED, 81	ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR, 343
ER_GIS_UNKNOWN_ERROR, 72	ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE, 374
ER_GIS_UNKNOWN_EXCEPTION, 72	ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED, 374
ER_GIS_UNSUPPORTED_ARGUMENT, 72	ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE, 374
ER_GLOBAL_CONN_LIMIT, 612	ER_GRP_RPL_APPLIER_INITIALIZED, 370
ER_GLOBAL_VARIABLE, 20	ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TA 371
ER_GLOBSTAT_CHANGE_DURING_QUERY, 131	ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNIN 370
ER_GNO_EXHAUSTED, 57	ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED, 343
ER_GRANT_WRONG_HOST_OR_USER, 13	ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_ 368
ER_GROUPING_ON_TIMESTAMP_IN_DST, 131	ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED, 343
ER_GROUP_REPLICATION_APPLIER_INIT_ERROR, 78	ER_GRP_RPL_APPLIER_THD_KILLED, 342
ER_GROUP_REPLICATION_COMMAND_FAILURE, 103	ER_GRP_RPL_APPLIER_THD_KILLED_BY_SQL_KILL, 643
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_ 78	ER_GRP_RPL_APPLIER_THD_SETUP_ERROR, 353
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_ 78	ER_GRP_RPL_APPLIER_THD_START_ERROR, 353
ER_GROUP_REPLICATION_CONFIGURATION, 78	ER_GRP_RPL_APPLIER_THD_STOP_ERROR, 353
ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_ 157	
ER_GROUP_REPLICATION_MAX_GROUP_SIZE, 86	
ER_GROUP_REPLICATION_PASSWORD_LENGTH, 138	
ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED, 204	
ER_GROUP_REPLICATION_RUNNING, 78	
ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_ 78	
ER_GROUP_REPLICATION_USER_EMPTY_MSG, 138	
ER_GROUP_REPLICATION_USER_MANDATORY_MSG, 138	

---

ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT, 540	ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO, 370
ER_GRP_RPL_AUTO_INC_OFFSET_RESET, 355	ER_GRP_RPL_CONFIGURATION_ACTION_END, 540
ER_GRP_RPL_AUTO_INC_OFFSET_SET, 355	ER_GRP_RPL_CONFIGURATION_ACTION_ERROR, 540
ER_GRP_RPL_AUTO_INC_RESET, 354	ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR, 540
ER_GRP_RPL_AUTO_INC_SET, 355	ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION, 540
ER_GRP_RPL_BINLOG_CHECKSUM_SET, 361	ER_GRP_RPL_CONFIGURATION_ACTION_START, 540
ER_GRP_RPL_BINLOG_DISABLED, 370	ER_GRP_RPL_CONFIG_RECOVERY, 358
ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP, 352	ER_GRP_RPL_CONFLICT_DETECTION_DISABLED, 347
ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED, 363	ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_TEMPORARY, 371
ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG, 377	ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL, 357
ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED, 344	ER_GRP_RPL_CONN_READ_MODE, 357
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE, 361	ER_GRP_RPL_CONTACT_WITH_SRV_FAILED, 356
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_STATE, 361	ER_GRP_RPL_COPY_FROM_EMPTY_STRING, 358
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING, 361	ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR, 343
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING, 361	ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL, 359
ER_GRP_RPL_CANT_GENERATE_GTID, 345	ER_GRP_RPL_CREATE_SESSION_UNABLE, 358
ER_GRP_RPL_CANT_KILL_THREAD, 567	ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM, 350
ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED, 347	ER_GRP_RPL_DEBUG_OPTIONS, 376
ER_GRP_RPL_CANT_READ_GTID, 346	ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_C, 558
ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM, 347	ER_GRP_RPL_DISABLE_READ_ONLY_FAILED, 349
ER_GRP_RPL_CERTIFICATE_SIZE_ERROR, 342	ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED, 348
ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE, 345	ER_GRP_RPL_DONOR_CONN_TERMINATION, 359
ER_GRP_RPL_CERTIFICATION_REC_PROCESS, 364	ER_GRP_RPL_DONOR_SERVER_CONN, 359
ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR, 347	ER_GRP_RPL_DONOR_TRANS_INFO_ERROR, 344
ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATE_FAILED, 643	ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR, 344
ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED, 643	ER_GRP_RPL_ENABLE_READ_ONLY_FAILED, 350
ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED, 643	ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET, 344
ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED, 348	ER_GRP_RPL_ERROR_FETCHING_GTID_SET, 345
ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING, 539	ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO, 342
ER_GRP_RPL_CHECK_STATUS_TABLE, 359	ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION, 343
ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR, 567	ER_GRP_RPL_ERROR_MSG, 320
ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR, 566	ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL, 553
	ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING, 540
	ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG, 343

ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER,	ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE,
611	622
ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER,	ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_E
611	360
ER_GRP_RPL_ERROR_STOPPING_CHANNELS,	ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME,
343	369
ER_GRP_RPL_ERROR_VERIFYING_SIDNO,	ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_U
345	602
ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_DETECTION,	ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_O
363	369
ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR,	ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_O
359	600
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR,	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME
358	363
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR,	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OB
358	368
ER_GRP_RPL_EVENT_HANDLING_ERROR,	ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR
342	362
ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE,	ENGINE_FAILED_TO_SHUTDOWN_REGISTRY_MODU
350	368
ER_GRP_RPL_EXIT_GRP_GCS_ERROR,	ENGINE_FAILED_TO_START_COMMUNICATION_ENO
377	366
ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLER,	ENGINE_FAILED_TO_START_ON_BOOT,
374	369
ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION,	ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WIT
360	366
ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATE_NOTIFICATION,	ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVE
360	369
ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE,	ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL
366	369
ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP,	ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE
367	369
ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE,	ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE
363	600
ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT,	ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE
362	369
ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE,	ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE
368	369
ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE,	ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGAT
366	369
ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET,	ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_E
362	369
ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET,	ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATI
362	369
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP,	ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_D
369	606
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW,	ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_JO
602	606
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER,	ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAL
374	606
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE,	ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY
370	606
ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE,	ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY
366	606
ER_GRP_RPL_FAILED_TO_INIT_HANDLER,	ENGINE_FAILED_TO_REGISTER_MESSAGE_LISTENE
368	606
ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_ARTERIS_CERTIFICATION,	ER_GRP_RPL_FATAL_REC_PROCESS,
550	364

ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED,	ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO_G
355	594
ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED,	ER_GRP_RPL_GRP_NAME_IS_TOO_LONG, 372
355	ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY,
ER_GRP_RPL_FETCH_LOG_EVENT_FAILED, 357	372
ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED,	ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE
355	602
ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED,	ER_GRP_RPL_GTID_ALREADY_USED, 342
355	ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR,
ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED,	351
355	ER_GRP_RPL_GTID_MODE_OFF, 371
ER_GRP_RPL_FETCH_TRANS_DATA_FAILED, 353	ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR,
ER_GRP_RPL_FETCH_TRANS_SIDNO_ERROR,	566
345	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR, 351
ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED,	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOV
356	552
ER_GRP_RPL_FINISHED_AUTO_REJOIN, 558	ER_GRP_RPL_HAS_STARTED, 634
ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED,	ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APP
354	372
ER_GRP_RPL_FLOW_CONTROL_STATS, 378	ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE,
ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN_QUOTAS,	341
373	ER_GRP_RPL_INTERNAL_QUERY, 357
ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA,	ER_GRP_RPL_INVALID_BINLOG_FORMAT, 360
373	ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL,
ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA,	558
373	ER_GRP_RPL_INVALID_DEBUG_OPTIONS, 377
ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY,	ER_GRP_RPL_INVALID_GTID_SET, 346
365	ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING,
ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED,	373
373	ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION_VA
ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING,	371
553	ER_GRP_RPL_IS_STARTING, 582
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET, 377	ER_GRP_RPL_IS_STOPPED, 368
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR,	ER_GRP_RPL_IS_STOPPING, 367
377	ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING
ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT,	539
377	ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING,
ER_GRP_RPL_GCS_GR_ERROR_MSG, 379	539
ER_GRP_RPL_GCS_INTERFACE_ERROR, 377	ER_GRP_RPL_KILLED_FAILED_ID, 357
ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION,	ER_GRP_RPL_KILLED_SESSION_ID, 357
376	ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR,
ER_GRP_RPL_GROUP_NAME_PARSE_ERROR,	352
344	ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET,
ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_UUID,	671
601	ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET,
ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR, 371	351
ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED,	527
376	ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE,
ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONNECTION,	571
374	ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED
ER_GRP_RPL_GRP_MEMBER_OFFLINE, 377	358
ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID,	ER_GRP_RPL_MEMBER_ACTIONS_RESET, 600
372	

---

ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION, 600	ER_GRP_RPL_MEM_UNREACHABLE, 348
ER_GRP_RPL_MEMBER_ACTION_DISABLED, 600	ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR, 570
ER_GRP_RPL_MEMBER_ACTION_ENABLED, 600	ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE, 132
ER_GRP_RPL_MEMBER_ACTION_FAILURE, 599	ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR, 539
ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE, 599	ER_GRP_RPL_MISSING_GRP_RPL_APPLIER, 347
ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE, 599	ER_GRP_RPL_MODULE_TERMINATE_ERROR, 372
ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER, 600	ER_GRP_RPL_MSG_DISCARDED, 347
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER, 600	ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS 360
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE, 599	ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED, 361
ER_GRP_RPL_MEMBER_ACTION_TRIGGERED, 599	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ER 605
ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION, 600	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ER 605
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS, 599	ER_GRP_RPL_NEEDS_INNODB_TABLE, 354
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER_JOIN, 600	ER_GRP_RPL_NEW_PRIMARY_ELECTED, 349
ER_GRP_RPL_MEMBER_ADDED, 349	ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED, 566
ER_GRP_RPL_MEMBER_ALREADY_EXISTS, 350	ER_GRP_RPL_NO_POSSIBLE_RECOVERY, 567
ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP, 352	ER_GRP_RPL_NO_STAGE_SERVICE, 541
ER_GRP_RPL_MEMBER_CHANGE, 349	ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM, 350
ER_GRP_RPL_MEMBER_CONF_INFO, 367	ER_GRP_RPL_NO_VALID_DONOR, 358
ER_GRP_RPL_MEMBER_CONTACT_RESTORED, 348	ER_GRP_RPL_NULL_PACKET, 346
ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR, 349	ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE, 364
ER_GRP_RPL_MEMBER_EXPELLED, 349	ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION, 360
ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST, 641	ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP, 611
ER_GRP_RPL_MEMBER_LEFT_GRP, 349	ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD, 632
ER_GRP_RPL_MEMBER_NOT_FOUND, 358	ER_GRP_RPL_PIPELINE_CREATE_FAILED, 378
ER_GRP_RPL_MEMBER_REMOVED, 349	ER_GRP_RPL_PIPELINE_FLUSH_FAIL, 378
ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP, 366	ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ, 378
ER_GRP_RPL_MEMBER_STATS_INFO, 378	ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE, 378
ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR, 352	ER_GRP_RPL_PLUGIN_ABORT, 536
ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP, 352	ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON 366
ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP, 351	ER_GRP_RPL_PREV_REC_SESSION_RUNNING, 364
ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE, 351	ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR, 540
ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE, 563	ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR, 541
ER_GRP_RPL_MEM_ONLINE, 348	ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED, 354
ER_GRP_RPL_MEM_REACHABLE, 348	ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP, 349
	ER_GRP_RPL_PROCESS_GTID_SET_ERROR, 346

---

ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR,	346	ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT,	380
ER_GRP_RPL_PURGE_APPLIER_LOGS,	352	ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED,	379
ER_GRP_RPL_PURGE_REC,	359	ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN,	379
ER_GRP_RPL_QUERY_FAIL,	358	ER_GRP_RPL_REPLICA_IO_THD_READ_ONLY,	379
ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_READ_ONLY,	365	ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT,	379
ER_GRP_RPL_READ_UNABLE_FOR_SUPER_READ_ONLY,	365	ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED,	379
ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS,	346	ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_SUPPORTED,	372
ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING,	145	ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_MEMBER,	354
ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT,	582	ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN,	354
ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IP,	583	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE,	568
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID,	582	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY_MEMBER,	568
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT,	583	ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_LEAVE,	367
ER_GRP_RPL_RECOVERY_EVAL_ERROR,	567	ER_GRP_RPL_RECOVER_ON_RESET_APPLIER_MODULE_LOGS_ERROR,	353
ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMEOUT,	368	ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER,	353
ER_GRP_RPL_RECOVERY_STRAT_CHOICE,	567	ER_GRP_RPL_SEND_STATS_ERROR,	377
ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED,	567	ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED,	550
ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD,	567	ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED,	552
ER_GRP_RPL_RECOVERY_STRAT_FALLBACK,	567	ER_GRP_RPL_SERVER_ALREADY_LEFT,	367
ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK,	568	ER_GRP_RPL_SERVER_CONN_ERROR,	344
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES_FAILED,	551	ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING,	367
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_REPLICATION_FAILED,	551	ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ERROR,	569
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_EXCLUSIVE_READ,	551	ER_GRP_RPL_SERVER_FAILED_TO_READ_ONLY_DUE_TO_ERROR,	376
ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITER_FAILED,	364	ER_GRP_RPL_SERVER_UDF_ERROR,	541
ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_READER_FAILED,	362	ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY,	365
ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITER_FAILED,	363	ER_GRP_RPL_SESSION_OPEN_FAILED,	349
ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE,	371	ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FAILED,	376
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES_COMMIT_FAILED,	551	ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER,	611
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_SYNC_BEFORE_STARTING_TRANS_ERROR,	552	ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER,	611
ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARED_FAILED,	550	ER_GRP_RPL_SIDNO_FETCH_ERROR,	343
		ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH_U,	372

---

ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTED,	ER_GRP_RPL_START_GRP_RPL_FAILED, 357
346	ER_GRP_RPL_STOPPING_GRP_REC, 359
ER_GRP_RPL_SLAVE_APPLIER_THREAD_ERROR_OUT,	ER_GRP_RPL_STOP_REP_CHANNEL, 378
379	ER_GRP_RPL_SUPER_READ_OFF, 357
ER_GRP_RPL_SLAVE_APPLIER_THREAD_UNBLOCKED,	ER_GRP_RPL_SUPER_READ_ON, 357
379	ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR,
ER_GRP_RPL_SLAVE_IO_THD_PRIMARY_UNKNOWN,	350
353	ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBERS,
ER_GRP_RPL_SLAVE_IO_THREAD_ERROR_OUT,	373
379	ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP,
ER_GRP_RPL_SLAVE_IO_THREAD_UNBLOCKED,	366
379	ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJO,
ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOS,	370
372	ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN,
ER_GRP_RPL_SLAVE_SQL_THD_ON_SECONDARY_MEMBER,	358
354	ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_ON,
ER_GRP_RPL_SLAVE_SQL_THD_PRIMARY_UNKNOWN,	367
354	ER_GRP_RPL_TRANS_GREATER_THAN_GRP, 351
ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_CLONE,	ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP,
568	351
ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_SECONDARY_MEMBER,	ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT, 362
607	ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_S,
ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED,	361
375	ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM,
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CTX,	352
375	ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFT,
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREAD,	350
375	ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HAN,
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY,	351
375	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED,
ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER,	352
376	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED,
ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE,	353
375	ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTING,
ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER,	352
375	ER_GRP_RPL_UDF_ERROR, 131
ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN,	ER_GRP_RPL_UDF_REGISTER_ERROR, 541
376	ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR,
ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE,	541
375	ER_GRP_RPL_UDF_UNREGISTER_ERROR, 541
ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED,	ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS,
375	365
ER_GRP_RPL_SRV_BLOCKED, 348	ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET,
ER_GRP_RPL_SRV_BLOCKED_FOR_SECS, 348	378
ER_GRP_RPL_SRV_GTID_WAIT_ERROR, 561	ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT,
ER_GRP_RPL_SRV_NOT_ONLINE, 347	378
ER_GRP_RPL_SRV_ONLINE, 347	ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC,
ER_GRP_RPL_SRV_PRIMARY_MEM, 350	364
ER_GRP_RPL_SRV_SECONDARY_MEM, 350	ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS,
ER_GRP_RPL_SRV_WAIT_TIME_OUT, 357	364
ER_GRP_RPL_SSL_DISABLED, 370	ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE,
ER_GRP_RPL_STARTED_AUTO_REJOIN, 558	370
ER_GRP_RPL_STARTING_GRP_REC, 359	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_AP,
ER_GRP_RPL_START_FAILED, 351	360

---

ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_ERROR, 360	ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED, 118
ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE, 365	ER_GRP_ELECTED_PRIMARY_GTID_INFORMATION, 574
ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS, 365	ER_GRP_HOLD_KILLED, 116
ER_GRP_RPL_UNBLOCK_WAITING_THD, 343	ER_GRP_HOLD_MEMBER_STATUS_ERROR, 117
ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE, 374	ER_GRP_HOLD_WAIT_TIMEOUT, 116
ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT, 376	ER_GRP_MEMBER_ALREADY_ADDED_BY_USER, 204
ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION, 361	ER_GRP_MEMBER_EXECUTED_WAS_CHANGED, 63
ER_GRP_RPL_UPDATE_GRP_GTID_EXECUTED_ERROR, 344	ER_GRP_MEMBER_EXECUTED_WAS_UPDATED, 279
ER_GRP_RPL_UPDATE_GRP_GTID_VIEW_CHANGE_UUID, 602	ER_GRP_MEMBER_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME, 58
ER_GRP_RPL_UPDATE_GTID_SET_ERROR, 346	ER_GRP_MEMBER_MODE_OFF, 74
ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANS, 345	ER_GRP_MEMBER_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY, 58
ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED, 356	ER_GRP_MEMBER_NEXT_TYPE_UNDEFINED_GROUP, 63
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VER_ERROR, 345	ER_GRP_MEMBER_NEXT_TYPE_UNDEFINED_GTID, 63
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VER_ERROR, 343	ER_GRP_MEMBER_PURGED_WAS_CHANGED, 63
ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP, 602	ER_GRP_MEMBER_PURGED_WAS_UPDATED, 279
ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE, 147	ER_GRP_MEMBER_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPR, 116
ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID, 601	ER_GRP_MEMBER_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_TRANSACTION, 67
ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANOTHER, 601	ER_GRP_MEMBER_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_TRANSACTION, 67
ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR, 602	ER_GRP_MEMBER_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN_TRANSACTION, 58
ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME, 601	ER_GRP_MEMBER_UNSAFE_CREATE_SELECT, 58
ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE, 367	ER_GRP_MEMBER_UNSAFE_DROP_TEMPORARY_TABLE_IN_TRANSACTION, 58
ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED, 551	ER_GRP_MEMBER_UNSAFE_TRANSACTIONAL_TABLE, 58
ER_GRP_RPL_WHILE_SENDING_MSG_REC, 364	ER_GRP_MEMBER_UNSAFE_TRANSACTIONAL_TABLE, 58
ER_GRP_RPL_WHILE_STOPPING_REP_CHANNEL, 364	ER_GRP_MEMBER_UNSAFE_TRANSACTIONAL_TABLE, 58
ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED, 360	ER_GRP_MEMBER_UNSAFE_TRANSACTIONAL_TABLE, 58
ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED, 363	ER_GRP_MEMBER_UNSAFE_TRANSACTIONAL_TABLE, 58
ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED, 363	ER_GRP_MEMBER_UNSAFE_TRANSACTIONAL_TABLE, 58
ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN, 118	ER_GRP_MEMBER_UNSAFE_TRANSACTIONAL_TABLE, 58
ER_GRP_TRX_CONSISTENCY_BEFORE, 118	ER_GRP_MEMBER_UNSAFE_TRANSACTIONAL_TABLE, 58
ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED, 118	ER_GRP_MEMBER_UNSAFE_TRANSACTIONAL_TABLE, 58
	ER_HOSTNAME, 35
	ER_HOSTNAME_DOESNT_RESOLVE_TO, 168
	ER_HOSTNAME_RESEMBLES_IPV4, 168
	ER_HOSTNAME_TOO_LONG, 138
	ER_HOSTNAME_TRUNCATED, 584



---

ER_HOST_IS_BLOCKED, 12	ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLON, 586
ER_HOST_NOT_PRIVILEGED, 12	ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST, 586
ER_HYPERGRAPH_NOT_SUPPORTED_YET, 142	ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY, 586
ER_IB_BUFFER_POOL_FULL, 628	ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATA, 586
ER_IB_BUFFER_POOL_OVERUSE, 628	ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE, 587
ER_IB_BULK_FLUSHER_INFO, 628	ER_IB_ERR_ZLIB_BUF_ERROR, 587
ER_IB_BULK_LOAD_MERGE_FAIL, 631	ER_IB_ERR_ZLIB_DATA_ERROR, 588
ER_IB_BULK_LOAD_SUBTREE_INFO, 628	ER_IB_ERR_ZLIB_MEM_ERROR, 588
ER_IB_BULK_LOAD_THREAD_FAIL, 631	ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED, 587
ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES, 584	ER_IB_ERR_ZLIB_UNKNOWN_ERROR, 588
ER_IB_CLONE_GTID_PERSIST, 406	ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE, 586
ER_IB_CLONE_INTERNAL, 404	ER_IB_HIDDEN_NAME_CONFLICT, 632
ER_IB_CLONE_NON_INNODB_TABLE, 566	ER_IB_INDEX_BUILDER_DONE, 634
ER_IB_CLONE_OPERATION, 566	ER_IB_INDEX_BUILDER_INIT, 634
ER_IB_CLONE_PUNCH_HOLE, 405	ER_IB_INDEX_LOADER_DONE, 633
ER_IB_CLONE_RESTART, 566	ER_IB_INDEX_LOG_VERSION_MISMATCH, 634
ER_IB_CLONE_SQL, 405	ER_IB_INDEX_PART_TOO_LONG, 642
ER_IB_CLONE_START_STOP, 566	ER_IB_INNODB_TBSP_OUT_OF_SPACE, 595
ER_IB_CLONE_STATUS_FILE, 405	ER_IB_LOAD_BULK_CONCURRENCY_REDUCED, 631
ER_IB_CLONE_TIMEOUT, 405	ER_IB_LOB_ROLLBACK_INDEX_LEN, 572
ER_IB_CLONE_USER_DATA, 566	ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION, 585
ER_IB_CLONE_VALIDATE, 405	ER_IB_LONG_AHI_DISABLE_WAIT, 408
ER_IB_DBLWR_BYTES_INFO, 615	ER_IB_MSG_0, 389
ER_IB_DBLWR_DECOMPRESS_FAILED, 591	ER_IB_MSG_1, 389
ER_IB_DBLWR_DECRYPT_FAILED, 591	ER_IB_MSG_10, 390
ER_IB_DBLWR_KEY_MISSING, 591	ER_IB_MSG_100, 399
ER_IB_DDL_CONVERT_HEAP_NOT_FOUND, 640	ER_IB_MSG_1000, 494
ER_IB_DICT_INVALID_COLUMN_POSITION, 632	ER_IB_MSG_1001, 494
ER_IB_DICT_LOG_TABLE_INFO, 633	ER_IB_MSG_1002, 494
ER_IB_DUPLICATE_KEY, 628	ER_IB_MSG_1003, 494
ER_IB_ERR_DDL_LOG_INSERT_FAILURE, 585	ER_IB_MSG_1004, 494
ER_IB_ERR_FOUND_N_DUPLICATE_KEYS, 588	ER_IB_MSG_1005, 494
ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER, 588	ER_IB_MSG_1006, 494
ER_IB_ERR_INDEX_DUPLICATE_KEY, 588	ER_IB_MSG_1007, 495
ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER, 588	ER_IB_MSG_1008, 495
ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW, 587	ER_IB_MSG_1009, 495
ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER, 587	ER_IB_MSG_101, 400
ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED, 604	ER_IB_MSG_1010, 495
ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUFFER, 581	ER_IB_MSG_1011, 495
ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT, 581	ER_IB_MSG_1012, 495
ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED, 581	ER_IB_MSG_1013, 495
ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN, 398	ER_IB_MSG_1014, 495
ER_IB_ERR_PARALLEL_READ_OOM, 588	ER_IB_MSG_1015, 495
ER_IB_ERR_RECOVERY_REDO_DISABLED, 583	ER_IB_MSG_1016, 495
ER_IB_ERR_SCHED_SETAFFINITY_FAILED, 587	ER_IB_MSG_1017, 496
	ER_IB_MSG_1018, 496

---

---

ER\_IB\_MSG\_1019, 496  
ER\_IB\_MSG\_102, 400  
ER\_IB\_MSG\_1020, 496  
ER\_IB\_MSG\_1021, 496  
ER\_IB\_MSG\_1022, 496  
ER\_IB\_MSG\_1023, 496  
ER\_IB\_MSG\_1024, 496  
ER\_IB\_MSG\_1025, 496  
ER\_IB\_MSG\_1026, 496  
ER\_IB\_MSG\_1027, 497  
ER\_IB\_MSG\_1028, 497  
ER\_IB\_MSG\_1029, 497  
ER\_IB\_MSG\_103, 400  
ER\_IB\_MSG\_1030, 497  
ER\_IB\_MSG\_1031, 497  
ER\_IB\_MSG\_1032, 497  
ER\_IB\_MSG\_1033, 497  
ER\_IB\_MSG\_1034, 497  
ER\_IB\_MSG\_1035, 497  
ER\_IB\_MSG\_1036, 497  
ER\_IB\_MSG\_1037, 498  
ER\_IB\_MSG\_1038, 498  
ER\_IB\_MSG\_1039, 498  
ER\_IB\_MSG\_104, 400  
ER\_IB\_MSG\_1040, 498  
ER\_IB\_MSG\_1041, 498  
ER\_IB\_MSG\_1042, 498  
ER\_IB\_MSG\_1043, 498  
ER\_IB\_MSG\_1044, 498  
ER\_IB\_MSG\_1045, 498  
ER\_IB\_MSG\_1046, 498  
ER\_IB\_MSG\_1047, 499  
ER\_IB\_MSG\_1048, 499  
ER\_IB\_MSG\_1049, 499  
ER\_IB\_MSG\_105, 400  
ER\_IB\_MSG\_1050, 499  
ER\_IB\_MSG\_1051, 499  
ER\_IB\_MSG\_1052, 499  
ER\_IB\_MSG\_1053, 499  
ER\_IB\_MSG\_1054, 499  
ER\_IB\_MSG\_1055, 499  
ER\_IB\_MSG\_1056, 500  
ER\_IB\_MSG\_1057, 500  
ER\_IB\_MSG\_1058, 500  
ER\_IB\_MSG\_1059, 500  
ER\_IB\_MSG\_106, 400  
ER\_IB\_MSG\_1060, 500  
ER\_IB\_MSG\_1061, 500  
ER\_IB\_MSG\_1062, 500  
ER\_IB\_MSG\_1063, 500  
ER\_IB\_MSG\_1064, 501  
ER\_IB\_MSG\_1065, 501  
ER\_IB\_MSG\_1066, 501  
ER\_IB\_MSG\_1067, 501

ER\_IB\_MSG\_1068, 501  
ER\_IB\_MSG\_1069, 501  
ER\_IB\_MSG\_107, 400  
ER\_IB\_MSG\_1070, 502  
ER\_IB\_MSG\_1071, 502  
ER\_IB\_MSG\_1072, 502  
ER\_IB\_MSG\_1073, 502  
ER\_IB\_MSG\_1074, 502  
ER\_IB\_MSG\_1075, 502  
ER\_IB\_MSG\_1076, 502  
ER\_IB\_MSG\_1077, 502  
ER\_IB\_MSG\_1078, 502  
ER\_IB\_MSG\_1079, 503  
ER\_IB\_MSG\_108, 400  
ER\_IB\_MSG\_1080, 503  
ER\_IB\_MSG\_1081, 503  
ER\_IB\_MSG\_1082, 503  
ER\_IB\_MSG\_1083, 503  
ER\_IB\_MSG\_1084, 503  
ER\_IB\_MSG\_1085, 503  
ER\_IB\_MSG\_1086, 503  
ER\_IB\_MSG\_1087, 504  
ER\_IB\_MSG\_1088, 504  
ER\_IB\_MSG\_1089, 504  
ER\_IB\_MSG\_109, 400  
ER\_IB\_MSG\_1090, 504  
ER\_IB\_MSG\_1091, 504  
ER\_IB\_MSG\_1092, 504  
ER\_IB\_MSG\_1093, 504  
ER\_IB\_MSG\_1094, 504  
ER\_IB\_MSG\_1095, 504  
ER\_IB\_MSG\_1096, 504  
ER\_IB\_MSG\_1097, 505  
ER\_IB\_MSG\_1098, 505  
ER\_IB\_MSG\_1099, 505  
ER\_IB\_MSG\_11, 390  
ER\_IB\_MSG\_110, 400  
ER\_IB\_MSG\_1100, 505  
ER\_IB\_MSG\_1101, 505  
ER\_IB\_MSG\_1102, 505  
ER\_IB\_MSG\_1103, 505  
ER\_IB\_MSG\_1104, 505  
ER\_IB\_MSG\_1105, 505  
ER\_IB\_MSG\_1106, 505  
ER\_IB\_MSG\_1107, 506  
ER\_IB\_MSG\_1108, 506  
ER\_IB\_MSG\_1109, 506  
ER\_IB\_MSG\_111, 401  
ER\_IB\_MSG\_1110, 506  
ER\_IB\_MSG\_1111, 506  
ER\_IB\_MSG\_1112, 506  
ER\_IB\_MSG\_1113, 506  
ER\_IB\_MSG\_1114, 506  
ER\_IB\_MSG\_1115, 506

---

ER\_IB\_MSG\_1116, 507  
ER\_IB\_MSG\_1117, 507  
ER\_IB\_MSG\_1118, 507  
ER\_IB\_MSG\_1119, 507  
ER\_IB\_MSG\_112, 401  
ER\_IB\_MSG\_1120, 507  
ER\_IB\_MSG\_1121, 507  
ER\_IB\_MSG\_1122, 507  
ER\_IB\_MSG\_1123, 507  
ER\_IB\_MSG\_1124, 507  
ER\_IB\_MSG\_1125, 508  
ER\_IB\_MSG\_1126, 508  
ER\_IB\_MSG\_1127, 508  
ER\_IB\_MSG\_1128, 508  
ER\_IB\_MSG\_1129, 508  
ER\_IB\_MSG\_113, 401  
ER\_IB\_MSG\_1130, 508  
ER\_IB\_MSG\_1131, 508  
ER\_IB\_MSG\_1132, 508  
ER\_IB\_MSG\_1133, 508  
ER\_IB\_MSG\_1134, 509  
ER\_IB\_MSG\_1135, 509  
ER\_IB\_MSG\_1136, 509  
ER\_IB\_MSG\_1137, 509  
ER\_IB\_MSG\_1138, 509  
ER\_IB\_MSG\_1139, 510  
ER\_IB\_MSG\_114, 401  
ER\_IB\_MSG\_1140, 510  
ER\_IB\_MSG\_1141, 510  
ER\_IB\_MSG\_1142, 510  
ER\_IB\_MSG\_1143, 510  
ER\_IB\_MSG\_1144, 510  
ER\_IB\_MSG\_1145, 511  
ER\_IB\_MSG\_1146, 511  
ER\_IB\_MSG\_1147, 511  
ER\_IB\_MSG\_1148, 511  
ER\_IB\_MSG\_1149, 511  
ER\_IB\_MSG\_115, 401  
ER\_IB\_MSG\_1150, 511  
ER\_IB\_MSG\_1151, 511  
ER\_IB\_MSG\_1152, 511  
ER\_IB\_MSG\_1153, 511  
ER\_IB\_MSG\_1154, 512  
ER\_IB\_MSG\_1155, 512  
ER\_IB\_MSG\_1156, 512  
ER\_IB\_MSG\_1157, 512  
ER\_IB\_MSG\_1158, 512  
ER\_IB\_MSG\_1159, 512  
ER\_IB\_MSG\_116, 401  
ER\_IB\_MSG\_1160, 512  
ER\_IB\_MSG\_1161, 512  
ER\_IB\_MSG\_1162, 512  
ER\_IB\_MSG\_1163, 512  
ER\_IB\_MSG\_1164, 513

ER\_IB\_MSG\_1165, 513  
ER\_IB\_MSG\_1166, 513  
ER\_IB\_MSG\_1167, 513  
ER\_IB\_MSG\_1168, 513  
ER\_IB\_MSG\_1169, 513  
ER\_IB\_MSG\_117, 401  
ER\_IB\_MSG\_1170, 513  
ER\_IB\_MSG\_1171, 514  
ER\_IB\_MSG\_1172, 514  
ER\_IB\_MSG\_1173, 514  
ER\_IB\_MSG\_1174, 514  
ER\_IB\_MSG\_1175, 514  
ER\_IB\_MSG\_1176, 514  
ER\_IB\_MSG\_1177, 515  
ER\_IB\_MSG\_1178, 515  
ER\_IB\_MSG\_1179, 515  
ER\_IB\_MSG\_118, 401  
ER\_IB\_MSG\_1180, 515  
ER\_IB\_MSG\_1181, 515  
ER\_IB\_MSG\_1182, 515  
ER\_IB\_MSG\_1183, 515  
ER\_IB\_MSG\_1184, 515  
ER\_IB\_MSG\_1185, 515  
ER\_IB\_MSG\_1186, 515  
ER\_IB\_MSG\_1187, 516  
ER\_IB\_MSG\_1188, 516  
ER\_IB\_MSG\_1189, 516  
ER\_IB\_MSG\_119, 401  
ER\_IB\_MSG\_1190, 516  
ER\_IB\_MSG\_1191, 516  
ER\_IB\_MSG\_1192, 516  
ER\_IB\_MSG\_1193, 516  
ER\_IB\_MSG\_1194, 516  
ER\_IB\_MSG\_1195, 516  
ER\_IB\_MSG\_1196, 517  
ER\_IB\_MSG\_1197, 517  
ER\_IB\_MSG\_1198, 517  
ER\_IB\_MSG\_1199, 517  
ER\_IB\_MSG\_12, 391  
ER\_IB\_MSG\_120, 401  
ER\_IB\_MSG\_1200, 517  
ER\_IB\_MSG\_1201, 517  
ER\_IB\_MSG\_1202, 517  
ER\_IB\_MSG\_1203, 517  
ER\_IB\_MSG\_1204, 517  
ER\_IB\_MSG\_1205, 517  
ER\_IB\_MSG\_1206, 518  
ER\_IB\_MSG\_1207, 518  
ER\_IB\_MSG\_1208, 518  
ER\_IB\_MSG\_1209, 518  
ER\_IB\_MSG\_121, 402  
ER\_IB\_MSG\_1210, 518  
ER\_IB\_MSG\_1211, 518  
ER\_IB\_MSG\_1212, 518

---

ER\_IB\_MSG\_1213, 518  
ER\_IB\_MSG\_1214, 518  
ER\_IB\_MSG\_1215, 518  
ER\_IB\_MSG\_1216, 519  
ER\_IB\_MSG\_1217, 519  
ER\_IB\_MSG\_1218, 519  
ER\_IB\_MSG\_1219, 519  
ER\_IB\_MSG\_122, 402  
ER\_IB\_MSG\_1220, 519  
ER\_IB\_MSG\_1221, 519  
ER\_IB\_MSG\_1222, 519  
ER\_IB\_MSG\_1223, 519  
ER\_IB\_MSG\_1224, 520  
ER\_IB\_MSG\_1225, 520  
ER\_IB\_MSG\_1226, 520  
ER\_IB\_MSG\_1227, 520  
ER\_IB\_MSG\_1228, 520  
ER\_IB\_MSG\_1229, 520  
ER\_IB\_MSG\_123, 402  
ER\_IB\_MSG\_1230, 520  
ER\_IB\_MSG\_1231, 520  
ER\_IB\_MSG\_1232, 520  
ER\_IB\_MSG\_1233, 520  
ER\_IB\_MSG\_1234, 521  
ER\_IB\_MSG\_1235, 521  
ER\_IB\_MSG\_1236, 521  
ER\_IB\_MSG\_1237, 521  
ER\_IB\_MSG\_1238, 521  
ER\_IB\_MSG\_1239, 521  
ER\_IB\_MSG\_124, 402  
ER\_IB\_MSG\_1240, 522  
ER\_IB\_MSG\_1241, 522  
ER\_IB\_MSG\_1242, 522  
ER\_IB\_MSG\_1243, 522  
ER\_IB\_MSG\_1244, 522  
ER\_IB\_MSG\_1245, 522  
ER\_IB\_MSG\_1246, 522  
ER\_IB\_MSG\_1247, 522  
ER\_IB\_MSG\_1248, 523  
ER\_IB\_MSG\_1249, 523  
ER\_IB\_MSG\_125, 402  
ER\_IB\_MSG\_1250, 523  
ER\_IB\_MSG\_1251, 523  
ER\_IB\_MSG\_1252, 523  
ER\_IB\_MSG\_1253, 523  
ER\_IB\_MSG\_1254, 523  
ER\_IB\_MSG\_1255, 523  
ER\_IB\_MSG\_1256, 523  
ER\_IB\_MSG\_1257, 524  
ER\_IB\_MSG\_1258, 524  
ER\_IB\_MSG\_1259, 524  
ER\_IB\_MSG\_126, 402  
ER\_IB\_MSG\_1260, 524  
ER\_IB\_MSG\_1261, 524

ER\_IB\_MSG\_1262, 524  
ER\_IB\_MSG\_1263, 524  
ER\_IB\_MSG\_1264, 524  
ER\_IB\_MSG\_1265, 524  
ER\_IB\_MSG\_1266, 525  
ER\_IB\_MSG\_1267, 525  
ER\_IB\_MSG\_1268, 525  
ER\_IB\_MSG\_1269, 525  
ER\_IB\_MSG\_127, 402  
ER\_IB\_MSG\_1270, 525  
ER\_IB\_MSG\_1271, 535  
ER\_IB\_MSG\_1272, 535  
ER\_IB\_MSG\_1273, 536  
ER\_IB\_MSG\_1274, 537  
ER\_IB\_MSG\_1275, 537  
ER\_IB\_MSG\_1276, 537  
ER\_IB\_MSG\_1277, 538  
ER\_IB\_MSG\_1278, 538  
ER\_IB\_MSG\_1279, 538  
ER\_IB\_MSG\_128, 402  
ER\_IB\_MSG\_1280, 538  
ER\_IB\_MSG\_1281, 538  
ER\_IB\_MSG\_1282, 538  
ER\_IB\_MSG\_1283, 538  
ER\_IB\_MSG\_1284, 538  
ER\_IB\_MSG\_1285, 563  
ER\_IB\_MSG\_129, 402  
ER\_IB\_MSG\_13, 391  
ER\_IB\_MSG\_130, 402  
ER\_IB\_MSG\_131, 403  
ER\_IB\_MSG\_132, 403  
ER\_IB\_MSG\_133, 403  
ER\_IB\_MSG\_134, 403  
ER\_IB\_MSG\_135, 403  
ER\_IB\_MSG\_1357, 585  
ER\_IB\_MSG\_1358, 585  
ER\_IB\_MSG\_1359, 585  
ER\_IB\_MSG\_136, 403  
ER\_IB\_MSG\_137, 403  
ER\_IB\_MSG\_1372, 587  
ER\_IB\_MSG\_1373, 587  
ER\_IB\_MSG\_1374, 587  
ER\_IB\_MSG\_1375, 587  
ER\_IB\_MSG\_138, 403  
ER\_IB\_MSG\_1381, 588  
ER\_IB\_MSG\_139, 403  
ER\_IB\_MSG\_14, 391  
ER\_IB\_MSG\_140, 403  
ER\_IB\_MSG\_141, 404  
ER\_IB\_MSG\_142, 404  
ER\_IB\_MSG\_143, 404  
ER\_IB\_MSG\_144, 404  
ER\_IB\_MSG\_145, 404  
ER\_IB\_MSG\_146, 404

---

ER\_IB\_MSG\_147, 404  
ER\_IB\_MSG\_148, 404  
ER\_IB\_MSG\_149, 404  
ER\_IB\_MSG\_15, 391  
ER\_IB\_MSG\_150, 405  
ER\_IB\_MSG\_151, 405  
ER\_IB\_MSG\_152, 405  
ER\_IB\_MSG\_153, 405  
ER\_IB\_MSG\_154, 405  
ER\_IB\_MSG\_155, 406  
ER\_IB\_MSG\_156, 406  
ER\_IB\_MSG\_157, 406  
ER\_IB\_MSG\_158, 406  
ER\_IB\_MSG\_159, 406  
ER\_IB\_MSG\_16, 391  
ER\_IB\_MSG\_160, 406  
ER\_IB\_MSG\_161, 406  
ER\_IB\_MSG\_162, 406  
ER\_IB\_MSG\_163, 406  
ER\_IB\_MSG\_164, 407  
ER\_IB\_MSG\_165, 407  
ER\_IB\_MSG\_166, 407  
ER\_IB\_MSG\_167, 407  
ER\_IB\_MSG\_168, 407  
ER\_IB\_MSG\_169, 407  
ER\_IB\_MSG\_17, 391  
ER\_IB\_MSG\_170, 407  
ER\_IB\_MSG\_171, 407  
ER\_IB\_MSG\_172, 407  
ER\_IB\_MSG\_173, 407  
ER\_IB\_MSG\_174, 408  
ER\_IB\_MSG\_175, 408  
ER\_IB\_MSG\_176, 408  
ER\_IB\_MSG\_177, 408  
ER\_IB\_MSG\_178, 408  
ER\_IB\_MSG\_179, 408  
ER\_IB\_MSG\_18, 391  
ER\_IB\_MSG\_180, 408  
ER\_IB\_MSG\_181, 408  
ER\_IB\_MSG\_182, 408  
ER\_IB\_MSG\_183, 409  
ER\_IB\_MSG\_184, 409  
ER\_IB\_MSG\_185, 409  
ER\_IB\_MSG\_186, 409  
ER\_IB\_MSG\_187, 409  
ER\_IB\_MSG\_188, 409  
ER\_IB\_MSG\_189, 409  
ER\_IB\_MSG\_19, 391  
ER\_IB\_MSG\_190, 409  
ER\_IB\_MSG\_191, 409  
ER\_IB\_MSG\_192, 409  
ER\_IB\_MSG\_193, 410  
ER\_IB\_MSG\_194, 410  
ER\_IB\_MSG\_195, 410

ER\_IB\_MSG\_196, 410  
ER\_IB\_MSG\_197, 410  
ER\_IB\_MSG\_198, 410  
ER\_IB\_MSG\_199, 410  
ER\_IB\_MSG\_2, 390  
ER\_IB\_MSG\_20, 391  
ER\_IB\_MSG\_200, 410  
ER\_IB\_MSG\_201, 410  
ER\_IB\_MSG\_202, 410  
ER\_IB\_MSG\_203, 411  
ER\_IB\_MSG\_204, 411  
ER\_IB\_MSG\_205, 411  
ER\_IB\_MSG\_206, 411  
ER\_IB\_MSG\_207, 411  
ER\_IB\_MSG\_208, 411  
ER\_IB\_MSG\_209, 411  
ER\_IB\_MSG\_21, 391  
ER\_IB\_MSG\_210, 411  
ER\_IB\_MSG\_211, 411  
ER\_IB\_MSG\_212, 411  
ER\_IB\_MSG\_213, 412  
ER\_IB\_MSG\_214, 412  
ER\_IB\_MSG\_215, 412  
ER\_IB\_MSG\_216, 412  
ER\_IB\_MSG\_217, 412  
ER\_IB\_MSG\_218, 412  
ER\_IB\_MSG\_219, 412  
ER\_IB\_MSG\_22, 392  
ER\_IB\_MSG\_220, 412  
ER\_IB\_MSG\_221, 412  
ER\_IB\_MSG\_222, 412  
ER\_IB\_MSG\_223, 413  
ER\_IB\_MSG\_224, 413  
ER\_IB\_MSG\_225, 413  
ER\_IB\_MSG\_226, 413  
ER\_IB\_MSG\_227, 413  
ER\_IB\_MSG\_228, 413  
ER\_IB\_MSG\_229, 413  
ER\_IB\_MSG\_23, 392  
ER\_IB\_MSG\_230, 413  
ER\_IB\_MSG\_231, 413  
ER\_IB\_MSG\_232, 413  
ER\_IB\_MSG\_233, 414  
ER\_IB\_MSG\_234, 414  
ER\_IB\_MSG\_235, 414  
ER\_IB\_MSG\_236, 414  
ER\_IB\_MSG\_237, 414  
ER\_IB\_MSG\_238, 414  
ER\_IB\_MSG\_239, 414  
ER\_IB\_MSG\_24, 392  
ER\_IB\_MSG\_240, 414  
ER\_IB\_MSG\_241, 414  
ER\_IB\_MSG\_242, 414  
ER\_IB\_MSG\_243, 415

---

ER\_IB\_MSG\_244, 415  
ER\_IB\_MSG\_245, 415  
ER\_IB\_MSG\_246, 415  
ER\_IB\_MSG\_247, 415  
ER\_IB\_MSG\_248, 415  
ER\_IB\_MSG\_249, 415  
ER\_IB\_MSG\_25, 392  
ER\_IB\_MSG\_250, 415  
ER\_IB\_MSG\_251, 415  
ER\_IB\_MSG\_252, 415  
ER\_IB\_MSG\_253, 416  
ER\_IB\_MSG\_254, 416  
ER\_IB\_MSG\_255, 416  
ER\_IB\_MSG\_256, 416  
ER\_IB\_MSG\_257, 416  
ER\_IB\_MSG\_258, 416  
ER\_IB\_MSG\_259, 416  
ER\_IB\_MSG\_26, 392  
ER\_IB\_MSG\_260, 416  
ER\_IB\_MSG\_261, 416  
ER\_IB\_MSG\_262, 416  
ER\_IB\_MSG\_263, 417  
ER\_IB\_MSG\_264, 417  
ER\_IB\_MSG\_265, 417  
ER\_IB\_MSG\_266, 417  
ER\_IB\_MSG\_267, 417  
ER\_IB\_MSG\_268, 417  
ER\_IB\_MSG\_269, 417  
ER\_IB\_MSG\_27, 392  
ER\_IB\_MSG\_270, 417  
ER\_IB\_MSG\_271, 417  
ER\_IB\_MSG\_272, 417  
ER\_IB\_MSG\_273, 418  
ER\_IB\_MSG\_274, 418  
ER\_IB\_MSG\_275, 418  
ER\_IB\_MSG\_276, 418  
ER\_IB\_MSG\_277, 418  
ER\_IB\_MSG\_278, 418  
ER\_IB\_MSG\_279, 418  
ER\_IB\_MSG\_28, 392  
ER\_IB\_MSG\_280, 418  
ER\_IB\_MSG\_281, 418  
ER\_IB\_MSG\_282, 418  
ER\_IB\_MSG\_283, 419  
ER\_IB\_MSG\_284, 419  
ER\_IB\_MSG\_285, 419  
ER\_IB\_MSG\_286, 419  
ER\_IB\_MSG\_287, 419  
ER\_IB\_MSG\_288, 419  
ER\_IB\_MSG\_289, 419  
ER\_IB\_MSG\_29, 392  
ER\_IB\_MSG\_290, 419  
ER\_IB\_MSG\_291, 420  
ER\_IB\_MSG\_292, 420

ER\_IB\_MSG\_293, 420  
ER\_IB\_MSG\_294, 420  
ER\_IB\_MSG\_295, 420  
ER\_IB\_MSG\_296, 420  
ER\_IB\_MSG\_297, 420  
ER\_IB\_MSG\_298, 420  
ER\_IB\_MSG\_299, 420  
ER\_IB\_MSG\_3, 390  
ER\_IB\_MSG\_30, 392  
ER\_IB\_MSG\_300, 421  
ER\_IB\_MSG\_301, 421  
ER\_IB\_MSG\_302, 421  
ER\_IB\_MSG\_303, 421  
ER\_IB\_MSG\_304, 421  
ER\_IB\_MSG\_305, 421  
ER\_IB\_MSG\_306, 421  
ER\_IB\_MSG\_307, 422  
ER\_IB\_MSG\_308, 422  
ER\_IB\_MSG\_309, 422  
ER\_IB\_MSG\_31, 392  
ER\_IB\_MSG\_310, 422  
ER\_IB\_MSG\_311, 422  
ER\_IB\_MSG\_312, 422  
ER\_IB\_MSG\_313, 422  
ER\_IB\_MSG\_314, 422  
ER\_IB\_MSG\_315, 422  
ER\_IB\_MSG\_316, 422  
ER\_IB\_MSG\_317, 423  
ER\_IB\_MSG\_318, 423  
ER\_IB\_MSG\_319, 423  
ER\_IB\_MSG\_32, 393  
ER\_IB\_MSG\_320, 423  
ER\_IB\_MSG\_321, 423  
ER\_IB\_MSG\_322, 423  
ER\_IB\_MSG\_323, 423  
ER\_IB\_MSG\_324, 423  
ER\_IB\_MSG\_325, 423  
ER\_IB\_MSG\_326, 423  
ER\_IB\_MSG\_327, 424  
ER\_IB\_MSG\_328, 424  
ER\_IB\_MSG\_329, 424  
ER\_IB\_MSG\_33, 393  
ER\_IB\_MSG\_330, 424  
ER\_IB\_MSG\_331, 424  
ER\_IB\_MSG\_332, 424  
ER\_IB\_MSG\_333, 424  
ER\_IB\_MSG\_334, 424  
ER\_IB\_MSG\_335, 424  
ER\_IB\_MSG\_336, 424  
ER\_IB\_MSG\_337, 425  
ER\_IB\_MSG\_338, 425  
ER\_IB\_MSG\_339, 425  
ER\_IB\_MSG\_34, 393  
ER\_IB\_MSG\_340, 425

---

ER\_IB\_MSG\_341, 425  
ER\_IB\_MSG\_342, 425  
ER\_IB\_MSG\_343, 425  
ER\_IB\_MSG\_344, 425  
ER\_IB\_MSG\_345, 425  
ER\_IB\_MSG\_346, 425  
ER\_IB\_MSG\_347, 426  
ER\_IB\_MSG\_348, 426  
ER\_IB\_MSG\_349, 426  
ER\_IB\_MSG\_35, 393  
ER\_IB\_MSG\_350, 426  
ER\_IB\_MSG\_351, 426  
ER\_IB\_MSG\_352, 426  
ER\_IB\_MSG\_353, 426  
ER\_IB\_MSG\_354, 426  
ER\_IB\_MSG\_355, 426  
ER\_IB\_MSG\_356, 427  
ER\_IB\_MSG\_357, 427  
ER\_IB\_MSG\_358, 427  
ER\_IB\_MSG\_359, 427  
ER\_IB\_MSG\_36, 393  
ER\_IB\_MSG\_360, 427  
ER\_IB\_MSG\_361, 427  
ER\_IB\_MSG\_362, 427  
ER\_IB\_MSG\_363, 427  
ER\_IB\_MSG\_364, 427  
ER\_IB\_MSG\_365, 427  
ER\_IB\_MSG\_366, 428  
ER\_IB\_MSG\_367, 428  
ER\_IB\_MSG\_368, 428  
ER\_IB\_MSG\_369, 428  
ER\_IB\_MSG\_37, 393  
ER\_IB\_MSG\_370, 428  
ER\_IB\_MSG\_371, 428  
ER\_IB\_MSG\_372, 428  
ER\_IB\_MSG\_373, 428  
ER\_IB\_MSG\_374, 428  
ER\_IB\_MSG\_375, 429  
ER\_IB\_MSG\_376, 429  
ER\_IB\_MSG\_377, 429  
ER\_IB\_MSG\_378, 429  
ER\_IB\_MSG\_379, 429  
ER\_IB\_MSG\_38, 393  
ER\_IB\_MSG\_380, 429  
ER\_IB\_MSG\_381, 429  
ER\_IB\_MSG\_382, 429  
ER\_IB\_MSG\_383, 429  
ER\_IB\_MSG\_384, 429  
ER\_IB\_MSG\_385, 430  
ER\_IB\_MSG\_386, 430  
ER\_IB\_MSG\_387, 430  
ER\_IB\_MSG\_388, 430  
ER\_IB\_MSG\_389, 430  
ER\_IB\_MSG\_39, 393

ER\_IB\_MSG\_390, 430  
ER\_IB\_MSG\_391, 430  
ER\_IB\_MSG\_392, 430  
ER\_IB\_MSG\_393, 431  
ER\_IB\_MSG\_394, 431  
ER\_IB\_MSG\_395, 431  
ER\_IB\_MSG\_396, 431  
ER\_IB\_MSG\_397, 431  
ER\_IB\_MSG\_398, 431  
ER\_IB\_MSG\_399, 431  
ER\_IB\_MSG\_4, 390  
ER\_IB\_MSG\_40, 393  
ER\_IB\_MSG\_400, 431  
ER\_IB\_MSG\_401, 431  
ER\_IB\_MSG\_402, 431  
ER\_IB\_MSG\_403, 432  
ER\_IB\_MSG\_404, 432  
ER\_IB\_MSG\_405, 432  
ER\_IB\_MSG\_406, 432  
ER\_IB\_MSG\_407, 432  
ER\_IB\_MSG\_408, 432  
ER\_IB\_MSG\_409, 432  
ER\_IB\_MSG\_41, 393  
ER\_IB\_MSG\_410, 432  
ER\_IB\_MSG\_411, 432  
ER\_IB\_MSG\_412, 432  
ER\_IB\_MSG\_413, 433  
ER\_IB\_MSG\_414, 433  
ER\_IB\_MSG\_415, 433  
ER\_IB\_MSG\_416, 433  
ER\_IB\_MSG\_417, 433  
ER\_IB\_MSG\_418, 433  
ER\_IB\_MSG\_419, 433  
ER\_IB\_MSG\_42, 394  
ER\_IB\_MSG\_420, 433  
ER\_IB\_MSG\_421, 433  
ER\_IB\_MSG\_422, 433  
ER\_IB\_MSG\_423, 434  
ER\_IB\_MSG\_424, 434  
ER\_IB\_MSG\_425, 434  
ER\_IB\_MSG\_426, 434  
ER\_IB\_MSG\_427, 434  
ER\_IB\_MSG\_428, 434  
ER\_IB\_MSG\_429, 434  
ER\_IB\_MSG\_43, 394  
ER\_IB\_MSG\_430, 434  
ER\_IB\_MSG\_431, 434  
ER\_IB\_MSG\_432, 434  
ER\_IB\_MSG\_433, 435  
ER\_IB\_MSG\_434, 435  
ER\_IB\_MSG\_435, 435  
ER\_IB\_MSG\_436, 435  
ER\_IB\_MSG\_437, 435  
ER\_IB\_MSG\_438, 435

---

ER\_IB\_MSG\_439, 435  
ER\_IB\_MSG\_44, 394  
ER\_IB\_MSG\_440, 435  
ER\_IB\_MSG\_441, 435  
ER\_IB\_MSG\_442, 435  
ER\_IB\_MSG\_443, 436  
ER\_IB\_MSG\_444, 436  
ER\_IB\_MSG\_445, 436  
ER\_IB\_MSG\_446, 436  
ER\_IB\_MSG\_447, 436  
ER\_IB\_MSG\_448, 436  
ER\_IB\_MSG\_449, 436  
ER\_IB\_MSG\_45, 394  
ER\_IB\_MSG\_450, 436  
ER\_IB\_MSG\_451, 436  
ER\_IB\_MSG\_452, 436  
ER\_IB\_MSG\_453, 437  
ER\_IB\_MSG\_454, 437  
ER\_IB\_MSG\_455, 437  
ER\_IB\_MSG\_456, 437  
ER\_IB\_MSG\_457, 437  
ER\_IB\_MSG\_458, 437  
ER\_IB\_MSG\_459, 437  
ER\_IB\_MSG\_46, 394  
ER\_IB\_MSG\_460, 437  
ER\_IB\_MSG\_461, 437  
ER\_IB\_MSG\_462, 437  
ER\_IB\_MSG\_463, 438  
ER\_IB\_MSG\_464, 438  
ER\_IB\_MSG\_465, 438  
ER\_IB\_MSG\_466, 438  
ER\_IB\_MSG\_467, 438  
ER\_IB\_MSG\_468, 438  
ER\_IB\_MSG\_469, 438  
ER\_IB\_MSG\_47, 394  
ER\_IB\_MSG\_470, 438  
ER\_IB\_MSG\_471, 438  
ER\_IB\_MSG\_472, 438  
ER\_IB\_MSG\_473, 439  
ER\_IB\_MSG\_474, 439  
ER\_IB\_MSG\_475, 439  
ER\_IB\_MSG\_476, 439  
ER\_IB\_MSG\_477, 439  
ER\_IB\_MSG\_478, 439  
ER\_IB\_MSG\_479, 439  
ER\_IB\_MSG\_48, 394  
ER\_IB\_MSG\_480, 439  
ER\_IB\_MSG\_481, 439  
ER\_IB\_MSG\_482, 439  
ER\_IB\_MSG\_483, 440  
ER\_IB\_MSG\_484, 440  
ER\_IB\_MSG\_485, 440  
ER\_IB\_MSG\_486, 440  
ER\_IB\_MSG\_487, 440

ER\_IB\_MSG\_488, 440  
ER\_IB\_MSG\_489, 440  
ER\_IB\_MSG\_49, 394  
ER\_IB\_MSG\_490, 440  
ER\_IB\_MSG\_491, 440  
ER\_IB\_MSG\_492, 440  
ER\_IB\_MSG\_493, 441  
ER\_IB\_MSG\_494, 441  
ER\_IB\_MSG\_495, 441  
ER\_IB\_MSG\_496, 441  
ER\_IB\_MSG\_497, 441  
ER\_IB\_MSG\_498, 441  
ER\_IB\_MSG\_499, 441  
ER\_IB\_MSG\_5, 390  
ER\_IB\_MSG\_50, 394  
ER\_IB\_MSG\_500, 441  
ER\_IB\_MSG\_501, 441  
ER\_IB\_MSG\_502, 441  
ER\_IB\_MSG\_503, 442  
ER\_IB\_MSG\_504, 442  
ER\_IB\_MSG\_505, 442  
ER\_IB\_MSG\_506, 442  
ER\_IB\_MSG\_507, 442  
ER\_IB\_MSG\_508, 442  
ER\_IB\_MSG\_509, 442  
ER\_IB\_MSG\_51, 394  
ER\_IB\_MSG\_510, 442  
ER\_IB\_MSG\_511, 442  
ER\_IB\_MSG\_512, 442  
ER\_IB\_MSG\_513, 443  
ER\_IB\_MSG\_514, 443  
ER\_IB\_MSG\_515, 443  
ER\_IB\_MSG\_516, 443  
ER\_IB\_MSG\_517, 443  
ER\_IB\_MSG\_518, 443  
ER\_IB\_MSG\_519, 443  
ER\_IB\_MSG\_52, 395  
ER\_IB\_MSG\_520, 443  
ER\_IB\_MSG\_521, 443  
ER\_IB\_MSG\_522, 443  
ER\_IB\_MSG\_523, 444  
ER\_IB\_MSG\_524, 444  
ER\_IB\_MSG\_525, 444  
ER\_IB\_MSG\_526, 444  
ER\_IB\_MSG\_527, 444  
ER\_IB\_MSG\_528, 444  
ER\_IB\_MSG\_529, 444  
ER\_IB\_MSG\_53, 395  
ER\_IB\_MSG\_530, 444  
ER\_IB\_MSG\_531, 444  
ER\_IB\_MSG\_532, 444  
ER\_IB\_MSG\_533, 445  
ER\_IB\_MSG\_534, 445  
ER\_IB\_MSG\_535, 445



---

ER_IB_MSG_536, 445	ER_IB_MSG_583, 450
ER_IB_MSG_537, 445	ER_IB_MSG_584, 450
ER_IB_MSG_538, 445	ER_IB_MSG_585, 450
ER_IB_MSG_539, 445	ER_IB_MSG_586, 450
ER_IB_MSG_54, 395	ER_IB_MSG_587, 450
ER_IB_MSG_540, 445	ER_IB_MSG_588, 450
ER_IB_MSG_541, 445	ER_IB_MSG_589, 450
ER_IB_MSG_542, 445	ER_IB_MSG_59, 395
ER_IB_MSG_543, 446	ER_IB_MSG_590, 450
ER_IB_MSG_544, 446	ER_IB_MSG_591, 450
ER_IB_MSG_545, 446	ER_IB_MSG_592, 451
ER_IB_MSG_546, 446	ER_IB_MSG_593, 451
ER_IB_MSG_547, 446	ER_IB_MSG_594, 451
ER_IB_MSG_548, 446	ER_IB_MSG_595, 451
ER_IB_MSG_549, 446	ER_IB_MSG_596, 451
ER_IB_MSG_55, 395	ER_IB_MSG_597, 451
ER_IB_MSG_550, 446	ER_IB_MSG_598, 451
ER_IB_MSG_551, 446	ER_IB_MSG_599, 451
ER_IB_MSG_552, 446	ER_IB_MSG_6, 390
ER_IB_MSG_553, 447	ER_IB_MSG_60, 395
ER_IB_MSG_554, 447	ER_IB_MSG_600, 451
ER_IB_MSG_555, 447	ER_IB_MSG_601, 451
ER_IB_MSG_556, 447	ER_IB_MSG_602, 452
ER_IB_MSG_557, 447	ER_IB_MSG_603, 452
ER_IB_MSG_558, 447	ER_IB_MSG_604, 452
ER_IB_MSG_559, 447	ER_IB_MSG_605, 452
ER_IB_MSG_56, 395	ER_IB_MSG_606, 452
ER_IB_MSG_560, 447	ER_IB_MSG_607, 452
ER_IB_MSG_561, 447	ER_IB_MSG_608, 452
ER_IB_MSG_562, 447	ER_IB_MSG_609, 452
ER_IB_MSG_563, 448	ER_IB_MSG_61, 395
ER_IB_MSG_564, 448	ER_IB_MSG_610, 452
ER_IB_MSG_565, 448	ER_IB_MSG_611, 452
ER_IB_MSG_566, 448	ER_IB_MSG_612, 453
ER_IB_MSG_567, 448	ER_IB_MSG_613, 453
ER_IB_MSG_568, 448	ER_IB_MSG_614, 453
ER_IB_MSG_569, 448	ER_IB_MSG_615, 453
ER_IB_MSG_57, 395	ER_IB_MSG_616, 453
ER_IB_MSG_570, 448	ER_IB_MSG_617, 453
ER_IB_MSG_571, 448	ER_IB_MSG_618, 453
ER_IB_MSG_572, 449	ER_IB_MSG_619, 453
ER_IB_MSG_573, 449	ER_IB_MSG_62, 396
ER_IB_MSG_574, 449	ER_IB_MSG_620, 453
ER_IB_MSG_575, 449	ER_IB_MSG_621, 453
ER_IB_MSG_576, 449	ER_IB_MSG_622, 454
ER_IB_MSG_577, 449	ER_IB_MSG_623, 454
ER_IB_MSG_578, 449	ER_IB_MSG_624, 454
ER_IB_MSG_579, 449	ER_IB_MSG_625, 454
ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL, 580	ER_IB_MSG_626, 454
ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL, 576	ER_IB_MSG_627, 454
ER_IB_MSG_58, 395	ER_IB_MSG_628, 454
ER_IB_MSG_580, 449	ER_IB_MSG_629, 454
ER_IB_MSG_581, 449	ER_IB_MSG_63, 396
ER_IB_MSG_582, 450	ER_IB_MSG_630, 454

---

---

ER\_IB\_MSG\_631, 454  
ER\_IB\_MSG\_632, 455  
ER\_IB\_MSG\_633, 455  
ER\_IB\_MSG\_634, 455  
ER\_IB\_MSG\_635, 455  
ER\_IB\_MSG\_636, 455  
ER\_IB\_MSG\_637, 455  
ER\_IB\_MSG\_638, 455  
ER\_IB\_MSG\_639, 455  
ER\_IB\_MSG\_64, 396  
ER\_IB\_MSG\_640, 455  
ER\_IB\_MSG\_641, 456  
ER\_IB\_MSG\_642, 456  
ER\_IB\_MSG\_643, 456  
ER\_IB\_MSG\_644, 456  
ER\_IB\_MSG\_645, 456  
ER\_IB\_MSG\_646, 456  
ER\_IB\_MSG\_647, 456  
ER\_IB\_MSG\_648, 456  
ER\_IB\_MSG\_649, 456  
ER\_IB\_MSG\_65, 396  
ER\_IB\_MSG\_650, 456  
ER\_IB\_MSG\_651, 457  
ER\_IB\_MSG\_652, 457  
ER\_IB\_MSG\_653, 457  
ER\_IB\_MSG\_654, 457  
ER\_IB\_MSG\_655, 457  
ER\_IB\_MSG\_656, 457  
ER\_IB\_MSG\_657, 457  
ER\_IB\_MSG\_658, 457  
ER\_IB\_MSG\_659, 457  
ER\_IB\_MSG\_66, 396  
ER\_IB\_MSG\_660, 458  
ER\_IB\_MSG\_661, 458  
ER\_IB\_MSG\_662, 458  
ER\_IB\_MSG\_663, 458  
ER\_IB\_MSG\_664, 458  
ER\_IB\_MSG\_665, 458  
ER\_IB\_MSG\_666, 458  
ER\_IB\_MSG\_667, 458  
ER\_IB\_MSG\_668, 458  
ER\_IB\_MSG\_669, 459  
ER\_IB\_MSG\_67, 396  
ER\_IB\_MSG\_670, 459  
ER\_IB\_MSG\_671, 459  
ER\_IB\_MSG\_672, 459  
ER\_IB\_MSG\_673, 459  
ER\_IB\_MSG\_674, 459  
ER\_IB\_MSG\_675, 459  
ER\_IB\_MSG\_676, 459  
ER\_IB\_MSG\_677, 459  
ER\_IB\_MSG\_678, 459  
ER\_IB\_MSG\_679, 460  
ER\_IB\_MSG\_68, 396

ER\_IB\_MSG\_680, 460  
ER\_IB\_MSG\_681, 460  
ER\_IB\_MSG\_682, 460  
ER\_IB\_MSG\_683, 460  
ER\_IB\_MSG\_684, 460  
ER\_IB\_MSG\_685, 460  
ER\_IB\_MSG\_686, 460  
ER\_IB\_MSG\_687, 460  
ER\_IB\_MSG\_688, 460  
ER\_IB\_MSG\_689, 461  
ER\_IB\_MSG\_69, 396  
ER\_IB\_MSG\_690, 461  
ER\_IB\_MSG\_691, 461  
ER\_IB\_MSG\_692, 461  
ER\_IB\_MSG\_693, 461  
ER\_IB\_MSG\_694, 461  
ER\_IB\_MSG\_695, 461  
ER\_IB\_MSG\_696, 461  
ER\_IB\_MSG\_697, 461  
ER\_IB\_MSG\_698, 462  
ER\_IB\_MSG\_699, 462  
ER\_IB\_MSG\_7, 390  
ER\_IB\_MSG\_70, 396  
ER\_IB\_MSG\_700, 462  
ER\_IB\_MSG\_701, 462  
ER\_IB\_MSG\_702, 462  
ER\_IB\_MSG\_703, 462  
ER\_IB\_MSG\_704, 463  
ER\_IB\_MSG\_705, 463  
ER\_IB\_MSG\_706, 463  
ER\_IB\_MSG\_707, 463  
ER\_IB\_MSG\_708, 463  
ER\_IB\_MSG\_709, 463  
ER\_IB\_MSG\_71, 396  
ER\_IB\_MSG\_710, 463  
ER\_IB\_MSG\_711, 464  
ER\_IB\_MSG\_712, 464  
ER\_IB\_MSG\_713, 464  
ER\_IB\_MSG\_714, 464  
ER\_IB\_MSG\_715, 464  
ER\_IB\_MSG\_716, 464  
ER\_IB\_MSG\_717, 464  
ER\_IB\_MSG\_718, 464  
ER\_IB\_MSG\_719, 464  
ER\_IB\_MSG\_72, 397  
ER\_IB\_MSG\_720, 464  
ER\_IB\_MSG\_721, 465  
ER\_IB\_MSG\_722, 465  
ER\_IB\_MSG\_723, 465  
ER\_IB\_MSG\_724, 465  
ER\_IB\_MSG\_725, 465  
ER\_IB\_MSG\_726, 465  
ER\_IB\_MSG\_727, 465  
ER\_IB\_MSG\_728, 465

---

ER\_IB\_MSG\_729, 466  
ER\_IB\_MSG\_73, 397  
ER\_IB\_MSG\_730, 466  
ER\_IB\_MSG\_731, 466  
ER\_IB\_MSG\_732, 466  
ER\_IB\_MSG\_733, 466  
ER\_IB\_MSG\_734, 467  
ER\_IB\_MSG\_735, 467  
ER\_IB\_MSG\_736, 467  
ER\_IB\_MSG\_737, 467  
ER\_IB\_MSG\_738, 467  
ER\_IB\_MSG\_739, 468  
ER\_IB\_MSG\_74, 397  
ER\_IB\_MSG\_740, 468  
ER\_IB\_MSG\_741, 468  
ER\_IB\_MSG\_742, 468  
ER\_IB\_MSG\_743, 468  
ER\_IB\_MSG\_744, 468  
ER\_IB\_MSG\_745, 468  
ER\_IB\_MSG\_746, 468  
ER\_IB\_MSG\_747, 468  
ER\_IB\_MSG\_748, 468  
ER\_IB\_MSG\_749, 469  
ER\_IB\_MSG\_75, 397  
ER\_IB\_MSG\_750, 469  
ER\_IB\_MSG\_751, 469  
ER\_IB\_MSG\_752, 469  
ER\_IB\_MSG\_753, 469  
ER\_IB\_MSG\_754, 469  
ER\_IB\_MSG\_755, 469  
ER\_IB\_MSG\_756, 469  
ER\_IB\_MSG\_757, 469  
ER\_IB\_MSG\_758, 469  
ER\_IB\_MSG\_759, 470  
ER\_IB\_MSG\_76, 397  
ER\_IB\_MSG\_760, 470  
ER\_IB\_MSG\_761, 470  
ER\_IB\_MSG\_762, 470  
ER\_IB\_MSG\_763, 470  
ER\_IB\_MSG\_764, 470  
ER\_IB\_MSG\_765, 470  
ER\_IB\_MSG\_766, 470  
ER\_IB\_MSG\_767, 470  
ER\_IB\_MSG\_768, 470  
ER\_IB\_MSG\_769, 471  
ER\_IB\_MSG\_77, 397  
ER\_IB\_MSG\_770, 471  
ER\_IB\_MSG\_771, 471  
ER\_IB\_MSG\_772, 471  
ER\_IB\_MSG\_773, 471  
ER\_IB\_MSG\_774, 471  
ER\_IB\_MSG\_775, 471  
ER\_IB\_MSG\_776, 471  
ER\_IB\_MSG\_777, 471

ER\_IB\_MSG\_778, 471  
ER\_IB\_MSG\_779, 472  
ER\_IB\_MSG\_78, 397  
ER\_IB\_MSG\_780, 472  
ER\_IB\_MSG\_781, 472  
ER\_IB\_MSG\_782, 472  
ER\_IB\_MSG\_783, 472  
ER\_IB\_MSG\_784, 472  
ER\_IB\_MSG\_785, 472  
ER\_IB\_MSG\_786, 472  
ER\_IB\_MSG\_787, 472  
ER\_IB\_MSG\_788, 472  
ER\_IB\_MSG\_789, 473  
ER\_IB\_MSG\_79, 397  
ER\_IB\_MSG\_790, 473  
ER\_IB\_MSG\_791, 473  
ER\_IB\_MSG\_792, 473  
ER\_IB\_MSG\_793, 473  
ER\_IB\_MSG\_794, 473  
ER\_IB\_MSG\_795, 473  
ER\_IB\_MSG\_796, 473  
ER\_IB\_MSG\_797, 473  
ER\_IB\_MSG\_798, 473  
ER\_IB\_MSG\_799, 474  
ER\_IB\_MSG\_8, 390  
ER\_IB\_MSG\_80, 397  
ER\_IB\_MSG\_800, 474  
ER\_IB\_MSG\_801, 474  
ER\_IB\_MSG\_802, 474  
ER\_IB\_MSG\_803, 474  
ER\_IB\_MSG\_804, 474  
ER\_IB\_MSG\_805, 474  
ER\_IB\_MSG\_806, 474  
ER\_IB\_MSG\_807, 474  
ER\_IB\_MSG\_808, 474  
ER\_IB\_MSG\_809, 475  
ER\_IB\_MSG\_81, 397  
ER\_IB\_MSG\_810, 475  
ER\_IB\_MSG\_811, 475  
ER\_IB\_MSG\_812, 475  
ER\_IB\_MSG\_813, 475  
ER\_IB\_MSG\_814, 475  
ER\_IB\_MSG\_815, 475  
ER\_IB\_MSG\_816, 475  
ER\_IB\_MSG\_817, 475  
ER\_IB\_MSG\_818, 475  
ER\_IB\_MSG\_819, 476  
ER\_IB\_MSG\_82, 398  
ER\_IB\_MSG\_820, 476  
ER\_IB\_MSG\_821, 476  
ER\_IB\_MSG\_822, 476  
ER\_IB\_MSG\_823, 476  
ER\_IB\_MSG\_824, 476  
ER\_IB\_MSG\_825, 476

---

ER\_IB\_MSG\_826, 476  
ER\_IB\_MSG\_827, 476  
ER\_IB\_MSG\_828, 476  
ER\_IB\_MSG\_829, 477  
ER\_IB\_MSG\_83, 398  
ER\_IB\_MSG\_830, 477  
ER\_IB\_MSG\_831, 477  
ER\_IB\_MSG\_832, 477  
ER\_IB\_MSG\_833, 477  
ER\_IB\_MSG\_834, 477  
ER\_IB\_MSG\_835, 477  
ER\_IB\_MSG\_836, 477  
ER\_IB\_MSG\_837, 477  
ER\_IB\_MSG\_838, 477  
ER\_IB\_MSG\_839, 478  
ER\_IB\_MSG\_84, 398  
ER\_IB\_MSG\_840, 478  
ER\_IB\_MSG\_841, 478  
ER\_IB\_MSG\_842, 478  
ER\_IB\_MSG\_843, 478  
ER\_IB\_MSG\_844, 478  
ER\_IB\_MSG\_845, 478  
ER\_IB\_MSG\_846, 478  
ER\_IB\_MSG\_847, 479  
ER\_IB\_MSG\_848, 479  
ER\_IB\_MSG\_849, 479  
ER\_IB\_MSG\_85, 398  
ER\_IB\_MSG\_850, 479  
ER\_IB\_MSG\_851, 479  
ER\_IB\_MSG\_852, 479  
ER\_IB\_MSG\_853, 479  
ER\_IB\_MSG\_854, 479  
ER\_IB\_MSG\_855, 479  
ER\_IB\_MSG\_856, 479  
ER\_IB\_MSG\_857, 480  
ER\_IB\_MSG\_858, 480  
ER\_IB\_MSG\_859, 480  
ER\_IB\_MSG\_86, 398  
ER\_IB\_MSG\_860, 480  
ER\_IB\_MSG\_861, 480  
ER\_IB\_MSG\_862, 480  
ER\_IB\_MSG\_863, 480  
ER\_IB\_MSG\_864, 480  
ER\_IB\_MSG\_865, 480  
ER\_IB\_MSG\_866, 480  
ER\_IB\_MSG\_867, 481  
ER\_IB\_MSG\_868, 481  
ER\_IB\_MSG\_869, 481  
ER\_IB\_MSG\_87, 398  
ER\_IB\_MSG\_870, 481  
ER\_IB\_MSG\_871, 481  
ER\_IB\_MSG\_872, 481  
ER\_IB\_MSG\_873, 481  
ER\_IB\_MSG\_874, 481

ER\_IB\_MSG\_875, 481  
ER\_IB\_MSG\_876, 481  
ER\_IB\_MSG\_877, 482  
ER\_IB\_MSG\_878, 482  
ER\_IB\_MSG\_879, 482  
ER\_IB\_MSG\_88, 398  
ER\_IB\_MSG\_880, 482  
ER\_IB\_MSG\_881, 482  
ER\_IB\_MSG\_882, 482  
ER\_IB\_MSG\_883, 482  
ER\_IB\_MSG\_884, 482  
ER\_IB\_MSG\_885, 482  
ER\_IB\_MSG\_886, 482  
ER\_IB\_MSG\_887, 483  
ER\_IB\_MSG\_888, 483  
ER\_IB\_MSG\_889, 483  
ER\_IB\_MSG\_89, 398  
ER\_IB\_MSG\_890, 483  
ER\_IB\_MSG\_891, 483  
ER\_IB\_MSG\_892, 483  
ER\_IB\_MSG\_893, 483  
ER\_IB\_MSG\_894, 483  
ER\_IB\_MSG\_895, 483  
ER\_IB\_MSG\_896, 483  
ER\_IB\_MSG\_897, 484  
ER\_IB\_MSG\_898, 484  
ER\_IB\_MSG\_899, 484  
ER\_IB\_MSG\_9, 390  
ER\_IB\_MSG\_90, 398  
ER\_IB\_MSG\_900, 484  
ER\_IB\_MSG\_901, 484  
ER\_IB\_MSG\_902, 484  
ER\_IB\_MSG\_903, 484  
ER\_IB\_MSG\_904, 484  
ER\_IB\_MSG\_905, 484  
ER\_IB\_MSG\_906, 484  
ER\_IB\_MSG\_907, 485  
ER\_IB\_MSG\_908, 485  
ER\_IB\_MSG\_909, 485  
ER\_IB\_MSG\_91, 399  
ER\_IB\_MSG\_910, 485  
ER\_IB\_MSG\_911, 485  
ER\_IB\_MSG\_912, 485  
ER\_IB\_MSG\_913, 485  
ER\_IB\_MSG\_914, 485  
ER\_IB\_MSG\_915, 485  
ER\_IB\_MSG\_916, 485  
ER\_IB\_MSG\_917, 486  
ER\_IB\_MSG\_918, 486  
ER\_IB\_MSG\_919, 486  
ER\_IB\_MSG\_92, 399  
ER\_IB\_MSG\_920, 486  
ER\_IB\_MSG\_921, 486  
ER\_IB\_MSG\_922, 486

---

ER\_IB\_MSG\_923, 486  
ER\_IB\_MSG\_924, 486  
ER\_IB\_MSG\_925, 486  
ER\_IB\_MSG\_926, 486  
ER\_IB\_MSG\_927, 487  
ER\_IB\_MSG\_928, 487  
ER\_IB\_MSG\_929, 487  
ER\_IB\_MSG\_93, 399  
ER\_IB\_MSG\_930, 487  
ER\_IB\_MSG\_931, 487  
ER\_IB\_MSG\_932, 487  
ER\_IB\_MSG\_933, 487  
ER\_IB\_MSG\_934, 487  
ER\_IB\_MSG\_935, 487  
ER\_IB\_MSG\_936, 487  
ER\_IB\_MSG\_937, 488  
ER\_IB\_MSG\_938, 488  
ER\_IB\_MSG\_939, 488  
ER\_IB\_MSG\_94, 399  
ER\_IB\_MSG\_940, 488  
ER\_IB\_MSG\_941, 488  
ER\_IB\_MSG\_942, 488  
ER\_IB\_MSG\_943, 488  
ER\_IB\_MSG\_944, 488  
ER\_IB\_MSG\_945, 488  
ER\_IB\_MSG\_946, 488  
ER\_IB\_MSG\_947, 489  
ER\_IB\_MSG\_948, 489  
ER\_IB\_MSG\_949, 489  
ER\_IB\_MSG\_95, 399  
ER\_IB\_MSG\_950, 489  
ER\_IB\_MSG\_951, 489  
ER\_IB\_MSG\_952, 489  
ER\_IB\_MSG\_953, 489  
ER\_IB\_MSG\_954, 489  
ER\_IB\_MSG\_955, 489  
ER\_IB\_MSG\_956, 489  
ER\_IB\_MSG\_957, 490  
ER\_IB\_MSG\_958, 490  
ER\_IB\_MSG\_959, 490  
ER\_IB\_MSG\_96, 399  
ER\_IB\_MSG\_960, 490  
ER\_IB\_MSG\_961, 490  
ER\_IB\_MSG\_962, 490  
ER\_IB\_MSG\_963, 490  
ER\_IB\_MSG\_964, 490  
ER\_IB\_MSG\_965, 490  
ER\_IB\_MSG\_966, 490  
ER\_IB\_MSG\_967, 491  
ER\_IB\_MSG\_968, 491  
ER\_IB\_MSG\_969, 491  
ER\_IB\_MSG\_97, 399  
ER\_IB\_MSG\_970, 491  
ER\_IB\_MSG\_971, 491

ER\_IB\_MSG\_972, 491  
ER\_IB\_MSG\_973, 491  
ER\_IB\_MSG\_974, 491  
ER\_IB\_MSG\_975, 491  
ER\_IB\_MSG\_976, 491  
ER\_IB\_MSG\_977, 492  
ER\_IB\_MSG\_978, 492  
ER\_IB\_MSG\_979, 492  
ER\_IB\_MSG\_98, 399  
ER\_IB\_MSG\_980, 492  
ER\_IB\_MSG\_981, 492  
ER\_IB\_MSG\_982, 492  
ER\_IB\_MSG\_983, 492  
ER\_IB\_MSG\_984, 492  
ER\_IB\_MSG\_985, 492  
ER\_IB\_MSG\_986, 492  
ER\_IB\_MSG\_987, 493  
ER\_IB\_MSG\_988, 493  
ER\_IB\_MSG\_989, 493  
ER\_IB\_MSG\_99, 399  
ER\_IB\_MSG\_990, 493  
ER\_IB\_MSG\_991, 493  
ER\_IB\_MSG\_992, 493  
ER\_IB\_MSG\_993, 493  
ER\_IB\_MSG\_994, 493  
ER\_IB\_MSG\_995, 493  
ER\_IB\_MSG\_996, 493  
ER\_IB\_MSG\_997, 494  
ER\_IB\_MSG\_998, 494  
ER\_IB\_MSG\_999, 494  
ER\_IB\_MSG\_ABORTING\_LOG\_ARCHIVER, 643  
ER\_IB\_MSG\_BAD\_DBLWR\_FILE\_NAME, 577  
ER\_IB\_MSG\_BTREE\_LEVEL\_LIMIT\_EXCEEDED,  
566  
ER\_IB\_MSG\_BUF\_PENDING\_IO, 506  
ER\_IB\_MSG\_BUF\_PENDING\_IO\_ON\_SHUTDOWN,  
523  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_CODE\_STATUS,  
627  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_COMPLETE\_CUR\_CODE,  
627  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_PROGRESS\_UPDATE,  
627  
ER\_IB\_MSG\_CANNOT\_FIND\_DD\_UNDO\_SPACE,  
582  
ER\_IB\_MSG\_CANNOT\_OPEN\_57\_UNDO, 503  
ER\_IB\_MSG\_CANT\_DECRYPT\_REDO\_LOG, 478  
ER\_IB\_MSG\_CANT\_ENCRYPT\_REDO\_LOG\_DATA,  
478  
ER\_IB\_MSG\_CLEAR\_INSTANT\_DROP\_COLUMN\_METADATA,  
626  
ER\_IB\_MSG\_CLOCK\_GETTIME\_FAILED, 563  
ER\_IB\_MSG\_CLOCK\_MONOTONIC\_UNSUPPORTED,  
563

---

ER_IB_MSG_CLONE_DDL_APPLY, 607	ER_IB_MSG_DIR_DOES_NOT_EXIST, 546
ER_IB_MSG_CLONE_DDL_INVALIDATE, 607	ER_IB_MSG_DOWNGRADE_PARTITION_FILE, 574
ER_IB_MSG_CLONE_DDL_NTFN, 607	ER_IB_MSG_DROPPED_UNDO_SPACE, 591
ER_IB_MSG_CREATED_UNDO_SPACE, 591	ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE, 544
ER_IB_MSG_CREATE_LOG_FILE, 580	ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR, 544
ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED, 509	ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR, 544
ER_IB_MSG_DBLWR_1285, 576	ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT, 544
ER_IB_MSG_DBLWR_1286, 576	ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE, 545
ER_IB_MSG_DBLWR_1287, 576	ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE, 544
ER_IB_MSG_DBLWR_1288, 576	ER_IB_MSG_FILE_RESIZE, 500
ER_IB_MSG_DBLWR_1290, 576	ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME, 574
ER_IB_MSG_DBLWR_1291, 576	ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH, 574
ER_IB_MSG_DBLWR_1292, 577	ER_IB_MSG_FIL_STATE_MOVED_CORRECTED, 574
ER_IB_MSG_DBLWR_1293, 577	ER_IB_MSG_FIL_STATE_MOVED_PREV, 642
ER_IB_MSG_DBLWR_1294, 577	ER_IB_MSG_FIL_STATE_MOVED_PREV_OR_HAS_DATADIR, 642
ER_IB_MSG_DBLWR_1295, 577	ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY, 574
ER_IB_MSG_DBLWR_1296, 577	ER_IB_MSG_FOUND_WRONG_UNDO_SPACE, 545
ER_IB_MSG_DBLWR_1297, 577	ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR, 430
ER_IB_MSG_DBLWR_1298, 577	ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN, 580
ER_IB_MSG_DBLWR_1300, 577	ER_IB_MSG_IGNORE_SCAN_PATH, 428
ER_IB_MSG_DBLWR_1301, 577	ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR, 430
ER_IB_MSG_DBLWR_1304, 578	ER_IB_MSG_INCORRECT_SIZE, 590
ER_IB_MSG_DBLWR_1305, 578	ER_IB_MSG_INJECT_CRASH, 589
ER_IB_MSG_DBLWR_1306, 578	ER_IB_MSG_INJECT_FAILURE, 589
ER_IB_MSG_DBLWR_1307, 578	ER_IB_MSG_INNODB_END_INITIALIZE, 581
ER_IB_MSG_DBLWR_1308, 578	ER_IB_MSG_INNODB_START_INITIALIZE, 581
ER_IB_MSG_DBLWR_1309, 578	ER_IB_MSG_INVALID_LOCATION_FOR_TABLE, 448
ER_IB_MSG_DBLWR_1310, 578	ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE, 582
ER_IB_MSG_DBLWR_1311, 578	ER_IB_MSG_INVALID_LOCATION_WRONG_DB, 582
ER_IB_MSG_DBLWR_1312, 578	ER_IB_MSG_INVALID_PAGE_TYPE, 628
ER_IB_MSG_DBLWR_1313, 578	ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS, 546
ER_IB_MSG_DBLWR_1314, 579	ER_IB_MSG_LOG_CHECKPOINT_FOUND, 618
ER_IB_MSG_DBLWR_1315, 579	ER_IB_MSG_LOG_CORRUPT, 462
ER_IB_MSG_DBLWR_1316, 579	ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY, 522
ER_IB_MSG_DBLWR_1317, 579	ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED, 619
ER_IB_MSG_DBLWR_1318, 579	ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE, 466
ER_IB_MSG_DBLWR_1319, 579	ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY, 466
ER_IB_MSG_DBLWR_1320, 579	ER_IB_MSG_LOG_FILES_CREATED_BY_MEB, 466
ER_IB_MSG_DBLWR_1321, 579	
ER_IB_MSG_DBLWR_1322, 579	
ER_IB_MSG_DBLWR_1323, 579	
ER_IB_MSG_DBLWR_1324, 580	
ER_IB_MSG_DBLWR_1325, 580	
ER_IB_MSG_DBLWR_1326, 580	
ER_IB_MSG_DBLWR_1327, 580	
ER_IB_MSG_DDL_FAIL_NO_BUILDER, 641	
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK, 457	
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT, 560	
ER_IB_MSG_DDL_LOG_FAIL_POST_DDL, 560	
ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACE, 546	
ER_IB_MSG_DICT_PARTITION_NOT_FOUND, 575	

---

ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY_MODE, 466	ER_IB_MSG_LOG_FILE_TRUNCATE, 621
ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATOR, 620	ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED, 621
ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY_MODE, 501	ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED, 621
ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES, 509	ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED, 621
ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED, 522	ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED, 621
ER_IB_MSG_LOG_FILES_FOUND_MISSING, 620	ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9, 525
ER_IB_MSG_LOG_FILES_INITIALIZED, 501	ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30, 463
ER_IB_MSG_LOG_FILES_INVALID_SET, 509	ER_IB_MSG_LOG_FORMAT_NOT_SUPPORTED, 466
ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED, 619	ER_IB_MSG_LOG_FORMAT_OLD, 466
ER_IB_MSG_LOG_FILES_RESIZE_FINISHED, 619	ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED, 462
ER_IB_MSG_LOG_FILES_RESIZE_ON_START, 519	ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN, 462
ER_IB_MSG_LOG_FILES_RESIZE_ON_START_FAILED, 618	ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN, 462
ER_IB_MSG_LOG_FILES_RESIZE_ON_START_IN_READ_ONLY_MODE, 510	ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED, 616
ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED, 619	ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR, 616
ER_IB_MSG_LOG_FILES_REWRITING, 510	ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE, 616
ER_IB_MSG_LOG_FILES_UPGRADE, 619	ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_UNUSABLE, 525
ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS, 620	ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED, 621
ER_IB_MSG_LOG_FILE_FOREIGN_UUID, 618	ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED, 617
ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW, 620	ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE, 621
ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD, 620	ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED, 617
ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN, 463	ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED, 620
ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM, 524	ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED, 620
ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED, 615	ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0, 620
ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES, 618	ER_IB_MSG_LOG_UPGRADE_CLONED_DB, 617
ER_IB_MSG_LOG_FILE_INVALID_START_LSN, 618	ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED, 617
ER_IB_MSG_LOG_FILE_IS_EMPTY, 615	ER_IB_MSG_LOG_UPGRADE_FLUSH_FAILED__UNEXPECTED, 618
ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED, 621	ER_IB_MSG_LOG_UPGRADE_FORCED_RECV, 617
ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE, 619	ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE, 617
ER_IB_MSG_LOG_FILE_MISSING_FOR_ID, 618	ER_IB_MSG_LOG_UPGRADE_NON_PERSISTED_DD_METADATA, 618
ER_IB_MSG_LOG_FILE_OPEN_FAILED, 502	ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES, 617
ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED, 500	ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER, 521
ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED, 501	ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN, 616
ER_IB_MSG_LOG_FILE_REMOVE_FAILED, 619	
ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED, 619	
ER_IB_MSG_LOG_FILE_RESIZE_FAILED, 501	
ER_IB_MSG_LOG_FILE_SIZE_INVALID, 509	
ER_IB_MSG_LOG_FILE_TOO_BIG, 615	
ER_IB_MSG_LOG_FILE_TOO_SMALL, 615	

---

---

ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN,	ER_IB_MSG_SKIP_HIDDEN_DIR, 572
617	ER_IB_MSG_STATS_SAMPLING_TOO_LARGE, 596
ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE, 521	ER_IB_MSG_THREAD_CONCURRENCY_CHANGED,
ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER,	525
521	ER_IB_MSG_TOO_LONG_PATH, 562
ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER,	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED,
625	516
ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE,	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED,
616	584
ER_IB_MSG_LOG_WRITER_WRITE_FAILED, 616	ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME,
ER_IB_MSG_MADVISE_FAILED, 543	612
ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED,	ER_IB_MSG_UNDO_ALTERED_ACTIVE, 589
543	ER_IB_MSG_UNDO_ALTERED_INACTIVE, 589
ER_IB_MSG_MASTER_KEY_ROTATED, 591	ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED,
ER_IB_MSG_MAX_UNDO_SPACES_REACHED, 544	607
ER_IB_MSG_NOT_END_WITH_IBU, 545	ER_IB_MSG_UNDO_INJECT_CRASH, 589
ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND,	ER_IB_MSG_UNDO_INJECT_FAILURE, 589
538	ER_IB_MSG_UNDO_MARKED_ACTIVE, 588
ER_IB_MSG_NUM_POOLS, 544	ER_IB_MSG_UNDO_MARKED_EMPTY, 589
ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS,	ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE,
581	513
ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION,	ER_IB_MSG_UNDO_TRUNCATE_COMPLETE, 514
625	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE,
ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG,	589
605	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE,
ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG, 605	514
ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER,	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE,
560	514
ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT,	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL,
560	589
ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE,	ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE,
467	513
ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND,	ER_IB_MSG_UNDO_TRUNCATE_START, 513
463	ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN, 582
ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG,	ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING,
616	545
ER_IB_MSG_RECOVERY_CORRUPT, 510	ER_IB_MSG_UNDO_TRUNC_BEFORE_DD_UPDATE,
ER_IB_MSG_RECOVERY_IN_READ_ONLY, 467	545
ER_IB_MSG_RECOVERY_IS_NEEDED, 467	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG,	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
604	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG,	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
604	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE,	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
465	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE,	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
604	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY,	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
604	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
ER_IB_MSG_RESUME_OP_FOR_SPACE, 538	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR,	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
586	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
ER_IB_MSG_SDI_Z_STREAM_ERROR, 544	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
ER_IB_MSG_SDI_Z_UNKNOWN_ERROR, 545	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545



---

ER_IB_RECV_FIRST_REC_GROUP_INVALID, 562	ER_IMP_INCOMPATIBLE_MYSQLD_VERSION, 97
ER_IB_RELOCK_LATCH_ORDER_VIOLATION, 585	ER_IMP_INCOMPATIBLE_SDI_VERSION, 98
ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK, 635	ER_IMP_NO_FILES_MATCHED, 97
ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK, 635	ER_IMP_SCHEMA_DOES_NOT_EXIST, 97
ER_IB_RESURRECT_RECORD_COMPLETE, 636	ER_IMP_TABLE_ALREADY_EXISTS, 97
ER_IB_RESURRECT_RECORD_PROGRESS, 636	ER_INCONSISTENT_ERROR, 528
ER_IB_RESURRECT_TRX_INSERT, 635	ER_INCONSISTENT_PARTITION_INFO_ERROR, 37
ER_IB_RESURRECT_TRX_INSERT_COMPLETE, 636	ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR, 37
ER_IB_RESURRECT_TRX_UPDATE, 635	ER_INCORRECT_CURRENT_PASSWORD, 129
ER_IB_RESURRECT_TRX_UPDATE_COMPLETE, 636	ER_INCORRECT_GLOBAL_LOCAL_VAR, 21
ER_IB_SELECT_COUNT_STAR, 634	ER_INCORRECT_TYPE, 74
ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED, 584	ER_INDEX_COLUMN_TOO_LONG, 51
ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY, 586	ER_INDEX_CORRUPT, 52
ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE, 586	ER_INDEX_OTHER_THAN_PK, 158
ER_IB_WARN_ACCESSING_NONEXISTING_SPACE, 419	ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX, 158
ER_IB_WARN_MANY_NON_LRU_FILES_OPENED, 612	ER_INFORMATION_SCHEMA_VERSION_CHANGE, 641
ER_IB_WARN_OPEN_PARTITION_FILE, 574	ER_INIT_BOOTSTRAP_COMPLETE, 215
ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH, 608	ER_INIT_CANT_OPEN_BOOTSTRAP_FILE, 215
ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE, 598	ER_INIT_CREATING_DD, 215
ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED, 583	ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_OPEN, 215
ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY, 632	ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_OPEN, 215
ER_IB_WRN_OLD_GEOMETRY_TYPE, 599	ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE, 215
ER_IB_WRN_PAGE_ARCH_FLUSH_DATA, 581	ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE, 215
ER_IB_WRN_REDO_DISABLED, 583	ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD, 571
ER_IB_WRN_REDO_ENABLED, 584	ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT, 215
ER_IDENTIFIED_BY_UNSUPPORTED, 149	ER_INIT_ROOT_WITHOUT_PASSWORD, 215
ER_IDENT_CAUSES_TOO_LONG_PATH, 65	ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED, 294
ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE, 568	ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE, 145
ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DIFFERENT_TABLE, 155	ER_INNODB_CANNOT_BE_IGNORED, 107
ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FUNC, 155	ER_INNODB_CANT_CREATE_TABLE, 295
ER_ILLEGAL_GRANT_FOR_TABLE, 13	ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR_DIFFERENT_TABLE, 274
ER_ILLEGAL_HA, 5	ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD, 274
ER_ILLEGAL_HA_CREATE_OPTION, 36	ER_INNODB_CANT_OPEN_TABLE, 274
ER_ILLEGAL_PRIVILEGE_LEVEL, 98	ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK, 274
ER_ILLEGAL_REFERENCE, 21	ER_INNODB_CLUSTERED_INDEX_PRIVATE, 275
ER_ILLEGAL_USER_VAR, 74	ER_INNODB_COMPRESSION_FAILURE, 146
ER_ILLEGAL_VALUE_FOR_TYPE, 29	ER_INNODB_DIFF_IN_REF_LEN, 295
ER_IMPLICIT_COMPARISON_FOR_JSON, 140	ER_INNODB_DIRTY_WATER_MARK_NOT_LOW, 273
ER_IMPOSSIBLE_STRING_CONVERSION, 140	ER_INNODB_ERROR_LOGGER_FATAL_MSG, 297
ER_IMP_INCOMPATIBLE_CFG_VERSION, 135	ER_INNODB_ERROR_LOGGER_MSG, 297
ER_IMP_INCOMPATIBLE_DD_VERSION, 98	

---

---

ER_INNODB_FAILED_TO_FIND_IDX, 294	ER_INNODB_PK_NOT_IN_MYSQL, 275
ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE, 294	ER_INNODB_PK_ONLY_IN_MYSQL, 275
ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO, 294	ER_INNODB_READ_ONLY, 66
ER_INNODB_FILES_SAME, 274	ER_INNODB_REDO_ARCHIVING_ENABLED, 140
ER_INNODB_FORCED_RECOVERY, 67	ER_INNODB_REDO_DISABLED, 140
ER_INNODB_FT_AUX_NOT_HEX_ID, 67	ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE, 124
ER_INNODB_FT_LIMIT, 59	ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID, 123
ER_INNODB_FT_WRONG_DOCID_COLUMN, 59	ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH, 124
ER_INNODB_FT_WRONG_DOCID_INDEX, 60	ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY, 124
ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL, 295	ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS, 124
ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL, 295	ER_INNODB_REDO_LOG_ARCHIVE_FAILED, 124
ER_INNODB_IDX_COLUMN_CNT_DIFF, 295	ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE, 124
ER_INNODB_ILLEGAL_COLON_IN_POOL, 273	ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE, 124
ER_INNODB_IMPORT_ERROR, 61	ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND, 123
ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE, 145	ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR, 124
ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS, 274	ER_INNODB_REDO_LOG_ARCHIVE_SESSION, 124
ER_INNODB_INDEX_CORRUPT, 61	ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH, 123
ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTED, 161	ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT, 123
ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_FILE_SIZE, 161	ER_INNODB_TRX_XLATION_TABLE_OOM, 274
ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_SIZE, 154	ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT, 581
ER_INNODB_INTERNAL_INDEX, 295	ER_INNODB_UNDO_LOG_FULL, 70
ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE, 145	ER_INNODB_UNKNOWN_COLLATION, 273
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY, 273	ER_INNODB_UNREGISTERED_TRX_ACTIVE, 274
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOG_GROUP, 547	ER_INNODB_USE_MONITOR_GROUP_NAME, 295
ER_INNODB_INVALID_LOG_GROUP_HOME_DIR, 273	ER_INSECURE_CHANGE_MASTER, 56
ER_INNODB_INVALID_MONITOR_COUNTER_NAME, 296	ER_INSECURE_CHANGE_SOURCE, 56
ER_INNODB_INVALID_PAGE_SIZE, 273	ER_INSECURE_PLAIN_TEXT, 56
ER_INNODB_IO_CAPACITY_EXCEEDS_MAX, 274	ER_INSERT_INFO, 9
ER_INNODB_IO_WRITE_ERROR_RETRYING, 592	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_DIR, 49
ER_INNODB_IO_WRITE_FAILED, 592	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FLUSH, 49
ER_INNODB_MANDATORY, 171	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG_ENABLED, 50
ER_INNODB_MAX_ROW_VERSION, 153	ER_INSTALL_COMPONENT_SET_NULL_VALUE, 161
ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED, 296	ER_INSTALL_COMPONENT_SET_UNUSED_VALUE, 161
ER_INNODB_MONITOR_IS_ENABLED, 296	ER_INSTALL_PLUGIN_CONFLICT_CLIENT, 148
ER_INNODB_NO_FT_TEMP_TABLE, 59	ER_INSTALL_PLUGIN_CONFLICT_LOG, 603
ER_INNODB_ONLINE_LOG_TOO_BIG, 60	ER_INTERNAL_ERROR, 61
ER_INNODB_OUT_OF_RESOURCES, 575	ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED, 157
ER_INNODB_PARTITION_TABLE_LOWERCASED, 275	

---

ER_INVALID_ADMIN_ADDRESS, 549	ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP, 556
ER_INVALID_ARGUMENT_FOR_LOGARITHM, 70	ER_INVALID_NO_OF_ARGS, 96
ER_INVALID_ASSIGNMENT_TARGET, 148	ER_INVALID_ON_UPDATE, 25
ER_INVALID_AUTHENTICATION_POLICY, 608	ER_INVALID_OPTION_CHARACTERS, 92
ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE, 88	ER_INVALID_OPTION_END_CHARACTER, 92
ER_INVALID_BITWISE_OPERANDS_SIZE, 88	ER_INVALID_OPTION_KEY, 91
ER_INVALID_CAST, 141	ER_INVALID_OPTION_KEY_VALUE_PAIR, 92
ER_INVALID_CAST_POLYGON_RING_DIRECTION, 146	ER_INVALID_OPTION_START_CHARACTER, 92
ER_INVALID_CAST_TO_GEOMETRY, 146	ER_INVALID_OPTION_VALUE, 92
ER_INVALID_CAST_TO_JSON, 82	ER_INVALID_OR_OLD_TABLE_OR_DB_NAME, 223
ER_INVALID_CHARACTER_STRING, 25	ER_INVALID_PARAMETER_USE, 141
ER_INVALID_CHARSET_AND_DEFAULT_IS_MB, 199	ER_INVALID_PLUGIN_FOR_REGISTRATION, 149
ER_INVALID_COLLATION_FOR_CHARSET, 281	ER_INVALID_PROPERTY_KEY, 552
ER_INVALID_DD_OBJECT, 88	ER_INVALID_REPLICATION_TIMESTAMPS, 283
ER_INVALID_DD_OBJECT_ID, 88	ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN, 74
ER_INVALID_DD_OBJECT_NAME, 88	ER_INVALID_SERVER_DOWNGRADE_NOT_PATCH, 640
ER_INVALID_DEFAULT, 8	ER_INVALID_SERVER_UPGRADE_NOT_LTS, 640
ER_INVALID_DEFAULT_UTF8MB4_COLLATION, 109	ER_INVALID_THREAD_ID, 103
ER_INVALID_ENCRYPTION_OPTION, 85	ER_INVALID_THREAD_PRIORITY, 102
ER_INVALID_ENCRYPTION_REQUEST, 121	ER_INVALID_TIME_ZONE_INTERVAL, 141
ER_INVALID_ERROR_LOG_NAME, 182	ER_INVALID_TLS_VERSION, 613
ER_INVALID_FIELD_SIZE, 69	ER_INVALID_TYPE_FOR_JSON, 82
ER_INVALID_GEOJSON CRS_NOT_TOP_LEVEL, 104	ER_INVALID_USER_ATTRIBUTE_JSON, 139
ER_INVALID_GEOJSON_MISSING_MEMBER, 74	ER_INVALID_USER_FOR_REGISTRATION, 150
ER_INVALID_GEOJSON_UNSPECIFIED, 74	ER_INVALID_USE_OF_FORCE_OPTION, 103
ER_INVALID_GEOJSON_WRONG_TYPE, 74	ER_INVALID_USE_OF_NULL, 13
ER_INVALID_GROUP_FUNC_USE, 11	ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY, 166
ER_INVALID_INFO_IN_FRM, 200	ER_INVALID_VALUE_OF_BIND_ADDRESSES, 539
ER_INVALID_INSTRUMENT, 171	ER_INVALID_VCPU_ID, 102
ER_INVALID_JSON_ATTRIBUTE, 139	ER_INVALID_VCPU_RANGE, 102
ER_INVALID_JSON_BINARY_DATA, 82	ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER, 581
ER_INVALID_JSON_CHARSET, 82	ER_INVALID_YEAR_COLUMN_LENGTH, 62
ER_INVALID_JSON_CHARSET_IN_FUNCTION, 82	ER_IO_ERR_LOG_INDEX_READ, 30
ER_INVALID_JSON_DATA, 74	ER_IO_READ_ERROR, 61
ER_INVALID_JSON_PATH, 82	ER_IO_WRITE_ERROR, 61
ER_INVALID_JSON_PATH_ARRAY_CELL, 84	ER_IPSOCK_ERROR, 9
ER_INVALID_JSON_PATH_CHARSET, 82	ER_IS_QUERY_INVALID_CLAUSE, 91
ER_INVALID_JSON_PATH_WILDCARD, 82	ER_I_S_SKIPPED_TABLESPACE, 101
ER_INVALID_JSON_TEXT, 82	ER_JSON_BAD_ONE_OR_ALL_ARG, 83
ER_INVALID_JSON_TEXT_IN_PARAM, 82	ER_JSON_DOCUMENT_NULL_KEY, 83
ER_INVALID_JSON_TYPE, 124	ER_JSON_DOCUMENT_TOO_DEEP, 83
ER_INVALID_JSON_VALUE_FOR_CAST, 83	ER_JSON_KEY_TOO_BIG, 82
ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX, 130	ER_JSON_PARSE_ERROR, 185
ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER, 150	ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILS, 330
ER_INVALID_MFA_PLUGIN_SPECIFIED, 149	ER_JSON_USED_AS_KEY, 83
ER_INVALID_MULTIPLE_CLAUSES, 122	ER_JSON_VACUOUS_PATH, 83
	ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX, 130

---

ER_JSON_VALUE_TOO_BIG, 82	ER_KEYRING_AWS_INVALID_CONF_FILE_PATH,
ER_JT_MAX_NESTED_PATH, 104	339
ER_JT_VALUE_OUT_OF_RANGE, 104	ER_KEYRING_AWS_INVALID_DATA_FILE_PATH,
ER_KERBEROS_CREATE_USER, 148	339
ER_KEYCACHE_OOM, 174	ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER,
ER_KEYRING_ACCESS_DENIED_ERROR, 86	340
ER_KEYRING_AWS_CMK_ID_NOT_SET, 340	ER_KEYRING_AWS_UDF_AWS_KMS_ERROR, 86
ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE,	ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID,
340	332
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE,	ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY,
339	332
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE,	ER_KEYRING_COMPONENT_EXCEPTION, 597
339	ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR,
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE,	340
340	ER_KEYRING_COMPONENT_NOT_INITIALIZED,
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR,	340
339	ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED,
ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS,	337
341	ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED,
ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY,	337
342	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING,
ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY,	338
342	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING,
ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE,	337
341	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING,
ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR,	337
341	ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP,
ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY,	337
341	ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_ERROR,
ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIALS_FROM_CONF_FILE,	338
340	ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE,
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR,	337
340	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR,
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_FAILURE,	338
340	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE,
ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE,	338
339	ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR,
ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE,	338
341	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID,
ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY,	338
342	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG,
ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK,	338
342	ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR,
ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID,	331
338	ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE,
ER_KEYRING_AWS_FAILED_TO_SET_REGION,	332
339	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING,
ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE,	333
341	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP,
ER_KEYRING_AWS_INCORRECT_FILE, 341	333
ER_KEYRING_AWS_INCORRECT_PROXY, 569	ER_KEYRING_FAILED_TO_GENERATE_KEY, 332
ER_KEYRING_AWS_INCORRECT_REGION, 341	ER_KEYRING_FAILED_TO_GET_FILE_STAT, 332
ER_KEYRING_AWS_INIT_FAILURE, 340	ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT,
	333

---

ER_KEYRING_FAILED_TO_REMOVE_FILE, 333	ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY,
ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID,	335
334	ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY,
ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE,	336
332	ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE,
ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA,	336
333	ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE,
ER_KEYRING_FAILED_TO_TRUNCATE_FILE, 333	336
ER_KEYRING_FILE_INIT_FAILED, 331	ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE,
ER_KEYRING_FILE_IO_ERROR, 333	337
ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE,	ER_KEYRING_OKV_FAILED_TO_STORE_KEY, 336
332	ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY,
ER_KEYRING_INCORRECT_FILE, 332	336
ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT,	ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGUR,
331	334
ER_KEYRING_INVALID_KEY_LENGTH, 331	ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_C,
ER_KEYRING_INVALID_KEY_TYPE, 331	334
ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEY,	ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ER,
333	334
ER_KEYRING_LOGGER_ERROR_MSG, 314	ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER,
ER_KEYRING_MIGRATE_FAILED, 527	334
ER_KEYRING_MIGRATION_EXTRA_OPTIONS, 389	ER_KEYRING_OKV_INVALID_KEY_TYPE, 334
ER_KEYRING_MIGRATION_FAILED, 299	ER_KEYRING_OKV_KEY_MISMATCH, 337
ER_KEYRING_MIGRATION_FAILURE, 86	ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEED,
ER_KEYRING_MIGRATION_STATUS, 86	613
ER_KEYRING_MIGRATION_SUCCESSFUL, 299	ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_E,
ER_KEYRING_OCI_HTTP_REQUEST, 627	332
ER_KEYRING_OCI_INVALID_JSON, 627	ER_KEYRING_UDF_KEYRING_SERVICE_ERROR,
ER_KEYRING_OCI_PARSE_JSON, 627	85
ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED,	ER_KEYRING_UNKNOWN_ERROR, 333
335	ER_KEY_COLUMN_DOES_NOT_EXISTS, 8
ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS,	ER_KEY_DOES_NOT_EXISTS, 15
336	ER_KEY_NOT_FOUND, 5
ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE,	ER_KEY_PART_0, 30
335	ER_KEY_REF_DO_NOT_MATCH_TABLE_REF, 21
ER_KEYRING_OKV_FAILED_TO_FETCH_KEY, 336	ER_KILLED_THREADS_OF_PLUGIN, 217
ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY,	ER_KILLING_THREAD, 216
334	ER_KILL_DENIED_ERROR, 10
ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER,	ER_KEYVALUE_OUT_OF_RANGE, 98
335	ER_LCTN_CHANGED, 299
ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY,	ER_LCTN_NOT_FOUND, 527
336	ER_LDAP_AUTH_CERTIFICATE_NAME, 382
ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INVALID_KEY,	ER_LDAP_AUTH_CONNECTION_HOST_INFO,
334	385
ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT, 335	ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER,
ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER,	385
335	ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL,
ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID,	385
335	ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED,
ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE,	385
336	ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER,
ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE,	387
335	ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL,
	385

---

---

ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING, 381	ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL, 382
ER_LDAP_AUTH_CONN_POOL_INITIALIZING, 381	ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO, 554
ER_LDAP_AUTH_CONN_POOL_NOT_CREATED, 381	ER_LDAP_AUTH_INFO_FOR_USER, 381
ER_LDAP_AUTH_CREATE_CONNECTION_KEY, 385	ER_LDAP_AUTH_INIT_FAILED, 386
ER_LDAP_AUTH_CREATING_LDAP_CONNECTION, 384	ER_LDAP_AUTH_LDAPS, 554
ER_LDAP_AUTH_DEINIT_FAILED, 380	ER_LDAP_AUTH_LDAP_INFO_NULL, 384
ER_LDAP_AUTH_DELETING_CONNECTION_KEY, 385	ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT, 384
ER_LDAP_AUTH_DISTINGUISHED_NAME, 386	ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED, 384
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION, 387	ER_LDAP_AUTH_METHOD_TO_CLIENT, 386
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT, 380	ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP, 382
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATOR, 380	ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED, 386
ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION, 380	ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET, 384
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL, 383	ER_LDAP_AUTH_POOLED_CONNECTION_KEY, 385
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECORDING, 383	ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO, 380
ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION, 387	ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION, 387
ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN, 383	ER_LDAP_AUTH_POOL_REINITIALIZING, 381
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT, 383	ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL, 384
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT, 383	ER_LDAP_AUTH_RETURNING_PLUGIN_NOT_READY, 384
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECORDING, 383	ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO, 386
ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT, 383	ER_LDAP_AUTH_SASL_PROCESS_SASL, 386
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN, 387	ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT, 386
ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET, 381	ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME, 382
ER_LDAP_AUTH_FREEING_CONNECTION, 385	ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND, 384
ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL, 384	ER_LDAP_AUTH_SETTING_USERNAME, 381
ER_LDAP_AUTH_GRP_DN_PARSING_FAILED, 554	ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH, 380
ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE, 554	ER_LDAP_AUTH_STARTED_FOR_USER, 386
ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS, 554	ER_LDAP_AUTH_STARTING_TLS, 385
ER_LDAP_AUTH_GRP_IS_FULL_DN, 382	ER_LDAP_AUTH_TLS_CONF, 380
ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE, 554	ER_LDAP_AUTH_TLS_CONNECTION, 380
ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO, 554	ER_LDAP_AUTH_USER_AUTH_DATA, 381
ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL, 553	ER_LDAP_AUTH_USER_BIND_FAILED, 387
	ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS, 382
	ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED, 386
	ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO, 382
	ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND, 542

---

---

ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES, 382	ER_LOCK_DEADLOCK, 18
ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP, 382	ER_LOCK_NOWAIT, 93
ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED, 381	ER_LOCK_ORDER_DEPENDENCIES_SYNTAX, 565
ER_LDAP_EMPTY_USERDN_PASSWORD, 565	ER_LOCK_ORDER_FAILED_READ_FILE, 565
ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE, 555	ER_LOCK_ORDER_FAILED_WRITE_FILE, 565
ER_LDAP_MAPPING_EMPTY_MAPPING, 555	ER_LOCK_ORDER_INIT_FAILED, 563
ER_LDAP_MAPPING_GETTING_NEXT_MAPPING, 556	ER_LOCK_ORDER_MESSAGE, 565
ER_LDAP_MAPPING_GET_USER_PROXY, 554	ER_LOCK_ORDER_SCANNER_SYNTAX, 565
ER_LDAP_MAPPING_INFO, 555	ER_LOCK_OR_ACTIVE_TRANSACTION, 16
ER_LDAP_MAPPING_IS_QUOTE, 556	ER_LOCK_REFUSED_BY_ENGINE, 84
ER_LDAP_MAPPING_NON_DESIRED_STATE, 556	ER_LOCK_TABLE_FULL, 18
ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP, 555	ER_LOCK_WAIT_TIMEOUT, 18
ER_LDAP_MAPPING_PARSING_CURRENT_STATE, 556	ER_LOG_BIN_BETTER_WITH_NAME, 179
ER_LDAP_MAPPING_PARSING_ERROR, 556	ER_LOG_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK, 639
ER_LDAP_MAPPING_PARSING_MAPPING_INFO, 556	ER_LOG_CANNOT_WRITE, 164
ER_LDAP_MAPPING_PROCESS_DELIMITER, 555	ER_LOG_CANNOT_WRITE_EXTENDED, 569
ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA, 555	ER_LOG_COMPONENT_CANNOT_INIT, 592
ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL, 555	ER_LOG_COMPONENT_FLUSH_FAILED, 604
ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA, 555	ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE, 179
ER_LDAP_MAPPING_PROCESS_MAPPING, 555	ER_LOG_FILE_CANNOT_OPEN, 322
ER_LDAP_MAPPING_TRIMMING_SPACES, 556	ER_LOG_FILE_INVALID, 179
ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP, 554	ER_LOG_GENERAL_CANNOT_OPEN, 164
ER_LIMITED_PART_RANGE, 39	ER_LOG_IN_USE, 30
ER_LOAD_BULK_DATA_FAILED, 160	ER_LOG_INVALID_OUTPUT_CONTRADICTION, 178
ER_LOAD_BULK_DATA_UNSORTED, 158	ER_LOG_PRINTF_MSG, 297
ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL, 161	ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NOT_SUPPORTED, 573
ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL_LOG, 631	ER_LOG_PURGE_NO_FILE, 44
ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD, 161	ER_LOG_PURGE_UNKNOWN_ERR, 30
ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD_LOG, 631	ER_LOG_SLOW_CANNOT_OPEN, 163
ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAIT, 185	ER_LOG_SYSLOG_CANNOT_OPEN, 163
ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR, 32	ER_LOG_SYSLOG_FACILITY_FAIL, 163
ER_LOAD_INFO, 9	ER_LONGITUDE_OUT_OF_RANGE, 98
ER_LOCAL_VARIABLE, 20	ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSAFE, 179
ER_LOCKING_SERVICE_DEADLOCK, 81	ER_LOWER_CASE_TABLE_NAMES_USING_0, 179
ER_LOCKING_SERVICE_TIMEOUT, 81	ER_LOWER_CASE_TABLE_NAMES_USING_2, 179
ER_LOCKING_SERVICE_WRONG_NAME, 81	ER_MALFORMED_GTID_SET_ENCODING, 57
ER_LOCK_ABORTED, 50	ER_MALFORMED_GTID_SET_SPECIFICATION, 57
	ER_MALFORMED_GTID_SPECIFICATION, 57
	ER_MALFORMED_PACKET, 63
	ER_MANDATORY_ROLE, 99
	ER_MASTER, 16
	ER_MASTER_DELAY_VALUE_OUT_OF_RANGE, 53
	ER_MASTER_FATAL_ERROR_READING_BINLOG, 20
	ER_MASTER_HAS_PURGED_REQUIRED_GTIDS, 59
	ER_MASTER_INFO, 17
	ER_MASTER_KEY_ROTATION_BINLOG_FAILED, 85

---

---

ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE,	ER_MTA_UPDATED_DBS_GREATER_MAX, 55
85	ER_MTR_MSG_1, 605
ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE,	ER_MTS_CANT_PARALLEL, 55
85	ER_MTS_CHANGE_MASTER_CANT_RUN_WITH_GAPS,
ER_MASTER_NET_READ, 16	60
ER_MASTER_NET_WRITE, 16	ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX,
ER_MAXVALUE_IN_VALUES_IN, 47	65
ER_MAX_PREPARED_STMT_COUNT_REACHED,	ER_MTS_FEATURE_IS_NOT_SUPPORTED, 55
35	ER_MTS_INCONSISTENT_DATA, 55
ER_MDL_OUT_OF_RESOURCES, 140	ER_MTS_RECOVERY_FAILURE, 60
ER_MECAB_CHARSET_LOADED, 303	ER_MTS_RESET_WORKERS, 60
ER_MECAB_CREATE_LATTICE_FAILED, 303	ER_MTS_UPDATED_DBS_GREATER_MAX, 55
ER_MECAB_CREATING_MODEL, 303	ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME,
ER_MECAB_FAILED_TO_CREATE_MODEL, 303	134
ER_MECAB_FAILED_TO_CREATE_TRIGGER, 303	ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR,
ER_MECAB_NOT_SUPPORTED, 303	37
ER_MECAB_NOT_VERIFIED, 303	ER_MULTIPLE INTO CLAUSES, 136
ER_MECAB_OOM_WHILE_PARSING_TEXT, 303	ER_MULTIPLE_JSON_VALUES, 138
ER_MECAB_PARSE_FAILED, 303	ER_MULTIPLE_PRI_KEY, 8
ER_MECAB_UNSUPPORTED_CHARSET, 303	ER_MULTI_UPDATE_KEY_CONFLICT, 51
ER_MESSAGE_AND_STATEMENT, 48	ER_MUST_CHANGE_EXPIRED_PASSWORD, 280
ER_MFA_METHODS_IDENTICAL, 150	ER_MUST_CHANGE_PASSWORD, 62
ER_MFA_METHODS_INVALID_ORDER, 150	ER_MUST_CHANGE_PASSWORD_LOGIN, 65
ER_MFA_METHOD_EXISTS, 149	ER_MYINIT_FAILED, 177
ER_MFA_METHOD_NOT_EXISTS, 149	ER_MYISAM_CHECK_METHOD_ERROR, 296
ER_MFA_PLUGIN_NOT_LOADED, 611	ER_MYISAM_CRASHED_ERROR, 297
ER_MFA_USER_ATTRIBUTES_CORRUPT, 611	ER_MYISAM_CRASHED_ERROR_IN, 188
ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE,	ER_MYISAM_CRASHED_ERROR_IN_THREAD, 187
294	ER_MYSQLBACKUP_CLIENT_MSG, 153
ER_MIGRATE_TABLE_TO_DD_OOM, 576	ER_MYSQLBACKUP_MSG, 570
ER_MISPLACED_INTO, 136	ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD_USE
ER_MISSING_ACL_SYSTEM_TABLE, 285	550
ER_MISSING_CURRENT_PASSWORD, 129	ER_MY_MALLOC_GETPROCADDRESS_FAILED,
ER_MISSING_GRANT_SYSTEM_TABLE, 285	614
ER_MISSING_HA_CREATE_OPTION, 69	ER_MY_MALLOC_LOADLIBRARY_FAILED, 614
ER_MISSING_JSON_TABLE_VALUE, 103	ER_MY_MALLOC_USING_JEMALLOC, 614
ER_MISSING_JSON_VALUE, 137	ER_MY_MALLOC_USING_STD_MALLOC, 614
ER_MISSING_KEY, 68	ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR,
ER_MISSING_SKIP_REPLICA, 24	258
ER_MISSING_SKIP_SLAVE, 23	ER_M_BIGGER_THAN_D, 33
ER_MISSING_TABLESPACE_FILE, 99	ER_NAME_BECOMES_EMPTY, 36
ER_MIXING_NOT_ALLOWED, 19	ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE,
ER_MIX_HANDLER_ERROR, 37	294
ER_MIX_OF_GROUP_FUNC_AND_FIELDS, 13	ER_NATIVE_FCT_NAME_COLLISION, 42
ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2, 77	ER_NDBINFO_NOT_UPGRADING_SCHEMA, 580
ER_MTA_CANT_PARALLEL, 55	ER_NDBINFO_UPGRADING_SCHEMA, 580
ER_MTA_CHANGE_SOURCE_CANT_RUN_WITH_GAPS,	ER_NDBINFO_UPGRADING_SCHEMA_FAIL, 580
60	ER_NDB_BINLOG_BLOB_REQUIRES_PK, 249
ER_MTA_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX,	ER_NDB_BINLOG_CANT_COMMIT_TO_NDB_BINLOG_INDEX,
65	247
ER_MTA_FEATURE_IS_NOT_SUPPORTED, 55	ER_NDB_BINLOG_CANT_CREATE_BLOB, 250
ER_MTA_INCONSISTENT_DATA, 56	ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB,
ER_MTA_RECOVERY_FAILURE, 60	249
ER_MTA_RESET_WORKERS, 60	



---

ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_AND_CANT_DROP,	ER_NDB_BINLOG_GOT_SCHEMA_EVENT, 246
249	ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAILURE,
ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_DROPPED,	247
249	ER_NDB_BINLOG_INJECTOR_DISCARDING_ROW_EVENT,
ER_NDB_BINLOG_CANT_CREATE_PURGE_THD,	251
273	ER_NDB_BINLOG_LATEST_TRX_IN_EPOCH_NOT_IN_BINLOG,
ER_NDB_BINLOG_CANT_DISCOVER_TABLE_FROM_SCHEMA_EVENT,	253
244	ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONTINUE,
ER_NDB_BINLOG_CANT_DROP_EVENT_FROM_DB,	252
250	ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITING,
ER_NDB_BINLOG_CANT_INJECT_APPLY_STATUS_WRITE_ROW,	252
252	ER_NDB_BINLOG_NDBEVENT_EXECUTE_FAILED,
ER_NDB_BINLOG_CANT_LOCK_NDB_BINLOG_INDEX,	250
247	ER_NDB_BINLOG_NDB_LOG_APPLY_STATUS_FORCING_I,
ER_NDB_BINLOG_CANT_RELEASE_SLOCK,	244
248	ER_NDB_BINLOG_NDB_LOG_TRANSACTION_ID_REQUIRE,
ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE,	248
245	ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY,
ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX,	222
247	ER_NDB_BINLOG_NDB_TABLES_WRITABLE, 252
ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS,	ER_NDB_BINLOG_NOT_LOGGING, 249
243	ER_NDB_BINLOG_ONLINE_ALTER_RENAME, 245
ER_NDB_BINLOG_CLUSTER_FAILURE,	250
ER_NDB_BINLOG_CLUSTER_HAS_RECONNECTED,	ER_NDB_BINLOG_ONLINE_ALTER_RENAME_COMPLETE,
251	245
ER_NDB_BINLOG_CLUSTER_RESTARTED_RESET_MASTER,	ER_NDB_BINLOG_OPENING_INDEX, 247
251	ER_NDB_BINLOG_RELEASING_EXTRA_SHARE_REFERENC,
ER_NDB_BINLOG_CREATE_TABLE_EVENT,	220
253	ER_NDB_BINLOG_REMAINING_OPEN_TABLES,
ER_NDB_BINLOG_CREATE_TABLE_EVENT_FAILED,	253
249	ER_NDB_BINLOG_REMAINING_OPEN_TABLE_INFO,
ER_NDB_BINLOG_CREATE_TABLE_EVENT_INFO,	253
249	ER_NDB_BINLOG_RENAME_EVENT, 220
ER_NDB_BINLOG_CREATING_NDBEVENTOPERATION_FAILED,	244
250	ER_NDB_BINLOG_REPLY_TO, 244
ER_NDB_BINLOG_DISCOVER_REUSING_OLD_EVENT_INFO,	ER_NDB_BINLOG_SERVER_SHUTDOWN_DURING_NDB_C,
250	251
ER_NDB_BINLOG_DISCOVER_TABLE_EVENT_INFO,	ER_NDB_BINLOG_SHUTDOWN_DETECTED, 252
249	ER_NDB_BINLOG_SIGNALLING_UNKNOWN_VALUE,
ER_NDB_BINLOG_ERROR_DURING_GCI_COMMIT,	244
253	ER_NDB_BINLOG_SKIPPING_DROP_OF_DB_CONTAINING,
ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK,	246
252	ER_NDB_BINLOG_SKIPPING_DROP_OF_LOCAL_TABLE,
ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT,	245
252	ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE, 245
ER_NDB_BINLOG_ERROR_INFO_FROM_DA,	219
ER_NDB_BINLOG_SKIPPING_OLD_SCHEMA_OPERATION,	246
ER_NDB_BINLOG_FAILED_CREATE_EVENT_OPERATION,	246
220	ER_NDB_BINLOG_SKIPPING_RENAME_OF_LOCAL_TABLE,
ER_NDB_BINLOG_FAILED_CREATE_TABLE_EVENT_OPERATION,	246
220	ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH,
ER_NDB_BINLOG_FAILED_TO_GET_TABLE,	248
252	ER_NDB_BINLOG_UNHANDLED_ERROR_FOR_TABLE,
ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT_TO_TABLE,	250
221	ER_NDB_BINLOG_UNKNOWN_NON_DATA_EVENT,
ER_NDB_BINLOG_GENERIC_MESSAGE,	248
ER_NDB_BINLOG_GOT_DIST_PRIV_EVENT_FLUSHING,	251
246	PRIVILEGES,

---

---

ER_NDB_BINLOG_USING_SERVER_ID_0_SLAVES_WILL_NOT_WRITE, 247	ER_NDB_DISCOVERED_MISSING_DB, 242
ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAILED, 247	ER_NDB_DISCOVERED_REMAINING_DB, 242
ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX, 247	ER_NDB_DISTRIBUTED_INFO, 243
ER_NDB_CANT_ALLOC_GLOBAL_NDB_CLUSTER_CONNECTION, 263	ER_NDB_DISTRIBUTING_ERR, 276
ER_NDB_CANT_ALLOC_GLOBAL_NDB_OBJECT, 264	ER_NDB_DISTRIBUTION_COMPLETE, 244
ER_NDB_CANT_ALLOC_NDB_CLUSTER_CONNECTION, 264	ER_NDB_DUPLICATE_NODEID_IN_NDB_CLUSTER_CONNECTION, 262
ER_NDB_CANT_FIND_TABLE, 245	ER_NDB_EMPTY_NODEID_IN_NDB_CLUSTER_CONNECTION, 262
ER_NDB_CANT_PARSE_NDB_CLUSTER_CONNECTION_FROM_NDBINFO, 263	ER_NDB_ERROR_IN_GET_AUTO_INCREMENT, 220
ER_NDB_CANT_START_CONNECT_THREAD, 264	ER_NDB_ERROR_IN_READAUTOINCREMENTVALUE, 219
ER_NDB_CLEANING_STRAY_TABLES, 242	ER_NDB_FAILED_TO_SET_UP_TABLE, 243
ER_NDB_CLEAR_SLOCK_INFO, 245	ER_NDB_FIELD_INFO, 218
ER_NDB_CLUSTER_FAILURE, 246	ER_NDB_FLUSHING_TABLE_INFO, 242
ER_NDB_CLUSTER_FIND_ALL_DBS_FAIL, 242	ER_NDB_FOUND_UNCOMMITTED_AUTOCOMMIT, 219
ER_NDB_CLUSTER_FIND_ALL_DBS_RETRY, 242	ER_NDB_GENERIC_ERROR, 264
ER_NDB_CLUSTER_FREE_SHARE_INFO, 221	ER_NDB_HANDLE_TRAILING_SHARE_INFO, 221
ER_NDB_CLUSTER_GENERIC_MESSAGE, 207	ER_NDB_IGNOREING_UNKNOWN_EVENT, 246
ER_NDB_CLUSTER_GET_SHARE_INFO, 221	ER_NDB_ILLEGAL_VALUE_FOR_NDB_RECV_THREAD_CPU_MASK, 222
ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROYING_SHARE, 222	ER_NDB_INFO_FAILED_TO_CREATE_NDBINFO, 207
ER_NDB_CLUSTER_MARK_SHARE_DROPPED_INFO, 221	ER_NDB_INFO_FAILED_TO_INIT_NDBINFO, 207
ER_NDB_CLUSTER_OOM_THD_NDB, 222	ER_NDB_INFO_FOUND_UNEXPECTED_FIELD_TYPE, 207
ER_NDB_CLUSTER_REAL_FREE_SHARE_DROP_FAILED, 221	ER_NDB_INITIALIZE_GIVEN_CLUSTER_PLUGIN_DISABLED, 220
ER_NDB_CLUSTER_REAL_FREE_SHARE_INFO, 221	ER_NDB_INVALID_NODEID_IN_NDB_CLUSTER_CONNECTION, 263
ER_NDB_CLUSTER_SCHEMA_INFO, 207	ER_NDB_LOG_ENTRY, 273
ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTION_ARGUMENTS, 207	ER_NDB_LOG_ENTRY_WITH_PREFIX, 273
ER_NDB_COLUMN_DEFAULTS_DIFFER, 218	ER_NDB_MISMATCH_IN_FRM_DISCOVERING, 243
ER_NDB_COLUMN_INFO, 218	ER_NDB_MISSING_FRM_DISCOVERING, 243
ER_NDB_COLUMN_SHOULD_NOT_HAVE_NATIVE_DEFAULT, 218	ER_NDB_MISSING_FRM_DISCOVERING, 243
ER_NDB_CONFLICT_FN_PARSE_ERROR, 248	ER_NDB_NODEID_NOT_FIRST_IN_NDB_CLUSTER_CONNECTION, 263
ER_NDB_CONFLICT_FN_SETUP_ERROR, 248	ER_NDB_NODE_ID_AND_MANAGEMENT_SERVER_INFO, 217
ER_NDB_CONFLICT_GENERIC_MESSAGE, 248	ER_NDB_NODE_INFO, 264
ER_NDB_COULD_NOT_GET_APPLY_STATUS_SHARE, 251	ER_NDB_NOT_WAITING_FOR_DISTRIBUTING, 243
ER_NDB_CPU_MASK_TOO_SHORT, 264	ER_NDB_NUMBER_OF_CHANNELS, 276
ER_NDB_CREATE_EVENT_OPS_LOGGING_INFO, 250	ER_NDB_OOM_GET_NDB_BLOBS_VALUE, 241
ER_NDB_CREATING_SHARE_IN_OPEN, 220	ER_NDB_OOM_IN_FIX_UNIQUE_INDEX_ATTR_ORDER, 218
ER_NDB_CREATING_TABLE, 242	ER_NDB_POOL_SIZE_MUST_MATCH_NDB_CLUSTER_CONNECTION, 263
ER_NDB_DISCARDING_EVENT_ID_VERSION_MISMATCH, 245	ER_NDB_QUERY_FAILED, 216
ER_NDB_DISCARDING_EVENT_NO_OBJ, 245	ER_NDB_REMAINING_OPEN_TABLES, 251
ER_NDB_DISCONNECT_INFO, 218	ER_NDB_REMAINING_OPEN_TABLE_INFO, 251
	ER_NDB_REPLICATION_SCHEMA_ERROR, 45
	ER_NDB_SCHEMA_DISTRIBUTION_FAILED, 244

---

ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_SUBSCRIBED,	244	ER_NDB_UNEXPECTED_RENAME_TYPE, 220
ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_UNSUBSCRIBED,	244	ER_NDB_USING_NODEID, 263
ER_NDB_SCHEMA_GENERIC_MESSAGE, 214		ER_NDB_USING_NODEID_LIST, 264
ER_NDB_SERVER_ID_RESERVED_OR_TOO_LARGE,	248	ER_NDB_UTIL_THREAD_OOM, 222
ER_NDB_SHARE_ALREADY_EXISTS, 221		ER_NDB_WAITING_INFO, 243
ER_NDB_SKIPPING_SETUP_TABLE, 242		ER_NDB_WAITING_INFO_WITH_MAP, 243
ER_NDB_SLAVE_BINLOG_MISSING_INFO_FOR_CONFLICT_DETECTION,	219	ER_NEED_FILE_INSTEAD_OF_DIR, 179
ER_NDB_SLAVE_CANT_ALLOCATE_TABLE_SHARE,	219	ER_NEED_LOG_BIN, 179
ER_NDB_SLAVE_CONFLICT_DETECTION_REQUIRES_TRANSACTION_ID,	219	ER_NEED_REPREPARE, 44
ER_NDB_SLAVE_CONFLICT_FUNCTION_REQUIRES_ROLE,	218	ER_NETWORK_NAMESPACES_NOT_SUPPORTED,
ER_NDB_SLAVE_ERROR_IN_UPDATE_CREATE_INFO,	219	561
ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO, 206		ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG,
ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION, 206		562
ER_NDB_SLAVE_MALFORMED_EVENT_RECEIVED_ON_TABLE,	218	ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WILDCARD,
ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_SET_TO,	217	561
ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN,	217	ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE,
ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN,	206	528
ER_NDB_SLAVE_PARALLEL_WORKERS, 276		ER_NET_ERROR_ON_WRITE, 14
ER_NDB_SLAVE_PREVIOUS_EPOCH_NOT_COMMITTED,	206	ER_NET_FCNTL_ERROR, 14
ER_NDB_SLAVE_SAW_ALREADY_COMMITTED_EPOCH,	206	ER_NET_OK_PACKET_TOO_LARGE, 74
ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS,	206	ER_NET_PACKETS_OUT_OF_ORDER, 14
ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS,	206	ER_NET_PACKET_TOO_LARGE, 14
ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS,	206	ER_NET_READ_ERROR, 14
ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS,	206	ER_NET_READ_ERROR_FROM_PIPE, 14
ER_NDB_SLAVE_TOO_MANY_RETRIES, 219		ER_NET_READ_INTERRUPTED, 14
ER_NDB_STARTING_CONNECT_THREAD, 264		ER_NET_UNCOMPRESS_ERROR, 14
ER_NDB_TABLES_INITIALLY_READ_ONLY_ON_RECONNECT,	246	ER_NET_WAIT_ERROR, 562
ER_NDB_TABLES_NOT_READY, 182		ER_NET_WAIT_ERROR2, 599
ER_NDB_TABLE_IS_NOT_DISTRIBUTED, 242		ER_NET_WRITE_INTERRUPTED, 14
ER_NDB_TABLE_OPENED_READ_ONLY, 220		ER_NEW_ABORTING_CONNECTION, 16
ER_NDB_THREAD_TIMED_OUT, 242		ER_NO, 3
ER_NDB_TIMED_OUT_IN_DROP_TABLE, 250		ER_NONEXISTING_GRANT, 13
ER_NDB_TIMEOUT_WHILE_DISTRIBUTING, 243		ER_NONEXISTING_PROC_GRANT, 31
ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD,	222	ER_NONEXISTING_TABLE_GRANT, 13
ER_NDB_TRAILING_SHARE_RELEASED_BY_CLOSE_CALLBACK,	221	ER_NONPOSITIVE_RADIUS, 108
ER_NDB_TRANS_DEPENDENCY_TRACKER_ERROR,	248	ER_NONUNIQ_TABLE, 8
		ER_NONUNIQ_TABLE_COLUMN, 28
		ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT,
		120
		ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN,
		YES,
		ER_NON_GROUPING_FIELD_USED, 35
		ER_NON_INSERTABLE_TABLE, 36
		ER_NON_RO_SELECT_DISABLE_TIMER, 71
		ER_NON_UNIQ_ERROR, 6
		ER_NON_UPDATABLE_TABLE, 24
		ER_NORMAL_SERVER_SHUTDOWN, 527
		ER_NORMAL_SHUTDOWN, 8
		ER_NORMAL_SERVER_COMPONENT_KEYRING_OCI_MISSING_NAME,
		626
		ER_NORMAL_SERVER_COMPONENT_SLOT_DEREGISTRATION_SUCCESS,
		635
		ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS,
		635

---

ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY, 70	ER_NO_PARTITION_FOR_GIVEN_VALUE, 39
597	ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT, 43
ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY, 597	ER_NO_PATH_FOR_SHARED_LIBRARY, 536
ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE, 597	ER_NO_PERMISSION_TO_CREATE_USER, 18
ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_FAILED, 597	ER_NO_REFERENCED_ROW, 19
ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED, 598	ER_NO_REFERENCED_ROW_2, 34
ER_NOTE_KEYRING_COMPONENT_INITIALIZED, 597	ER_NO_SECURE_TRANSPORTS_CONFIGURED, 83
ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR_FAILED, 598	ER_NO_SESSION_TEMP, 128
ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR_FAILED, 598	ER_NO_SUCH_INDEX, 9
ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR_NO_SUCH_TABLE, 598	ER_NO_SUCH_THREAD, 10
ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND, 598	ER_NO_SUCH_USER, 34
ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED, 598	ER_NO_SUPER_WITHOUT_USER_PLUGIN, 196
ER_NOTE_KEYRING_COMPONENT_STORE_FAILED, 598	ER_NO_SYSTEM_SCHEMA_ACCESS, 91
ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_LENGTH, 598	ER_NO_SYSTEM_TABLESPACE_ACCESS, 91
ER_NOT_ALLOWED_COMMAND, 13	ER_NO_SYSTEM_TABLE_ACCESS, 91
ER_NOT_ALLOWED_WITH_START_TRANSACTION, 139	ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE, 91
ER_NOT_FORM_FILE, 5	ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE, 91
ER_NOT_HINT_UPDATABLE_VARIABLE, 100	ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE, 91
ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS, 107	ER_NO_SYSTEM_VIEW_ACCESS, 98
ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS, 98	ER_NO_TABLES_USED, 10
ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS, 108	ER_NO_THD_NO_UUID, 170
ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS, 322	ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA, 35
ER_NOT_KEYFILE, 5	ER_NO_UNIQUE_LOGFILE, 10
ER_NOT_RIGHT_NOW, 176	ER_NPIPE_CANT_CREATE, 275
ER_NOT_SUPPORTED_AUTH_MODE, 21	ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR, 205
ER_NOT_SUPPORTED_YET, 20	ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR, 205
ER_NOT_VALID_PASSWORD, 62	ER_NPIPE_PIPE_ALREADY_IN_USE, 205
ER_NO_ACCESS_TO_NATIVE_FCT, 92	ER_NULL_COLUMN_IN_INDEX, 12
ER_NO_BINARY_LOGGING, 30	ER_NULL_IN_VALUES_LESS_THAN, 41
ER_NO_BINLOG_ERROR, 39	ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE, 83
ER_NO_CSV_NO_LOG_TABLES, 178	ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION_CHECK, 571
ER_NO_DB_ERROR, 6	ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION, 573
ER_NO_DEFAULT, 20	ER_OLD_FILE_FORMAT, 35
ER_NO_DEFAULT_FOR_FIELD, 29	ER_OLD_KEYFILE, 5
ER_NO_DEFAULT_FOR_VIEW_FIELD, 32	ER_OLD_PASSWORDS_NO_MIDDLE_GROUND, 171
ER_NO_ERROR_LOG_PARSER_CONFIGURED, 591	ER_OLD_TEMPORALS_UPGRADED, 67
ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATE, 43	ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STATE, 53
	ER_NOT_IMPLEMENTED_FOR_SRID_0_AND_4326, 105

---

ER_ONLY_INTEGERS_ALLOWED, 42	ER_PARTITION_WRONG_NO_PART_ERROR, 36
ER_ONLY_ON_RANGE_LIST_PARTITION, 38	ER_PARTITION_WRONG_NO_SUBPART_ERROR, 36
ER_OOM, 176	ER_PARTITION_WRONG_VALUES_ERROR, 36
ER_OOM_SAVE_GTIDS, 527	ER_PART_EXPR_TOO_LONG, 99
ER_OPEN_AS_READONLY, 5	ER_PASSWORD_ANONYMOUS_USER, 12
ER_OPEN_ROLE_TABLES, 89	ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE, 129
ER_OPERAND_COLUMNS, 21	ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTHENTICATION_PLUGIN, 129
ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY, 148	ER_PASSWORD_EXPIRE_ANONYMOUS_USER, 69
ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGE_IS_RUNNING, 154	ER_PASSWORD_FORMAT, 62
ER_OPTION_PREVENTS_STATEMENT, 24	ER_PASSWORD_NOT_ALLOWED, 12
ER_OPT_WRONG_TREE, 163	ER_PASSWORD_NO_MATCH, 12
ER_OUTOFMEMORY, 5	ER_PATH_IN_DATADIR, 100
ER_OUT_OF_RESOURCES, 6	ER_PATH_LENGTH, 49
ER_OUT_OF_SORTMEMORY, 5	ER_PERFORMANCE_SCHEMA_VERSION_CHANGE, 641
ER_PAGE_TRACKING_CANNOT_PURGE, 119	ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP_FAILED, 281
ER_PAGE_TRACKING_NOT_STARTED, 119	ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_FAILED, 281
ER_PAGE_TRACKING_RANGE_NOT_TRACKED, 119	ER_PERFSCHEMA_INIT_FAILED, 180
ER_PARSER_TRACE, 162	ER_PERFSCHEMA_TABLES_INIT_FAILED, 283
ER_PARSE_ERROR, 7	ER_PERSISTED_VARIABLES_DECRYPTION_FAILED, 614
ER_PARSE_ERROR_IN_DIGEST_FN, 104	ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED, 614
ER_PARSING_VIEW, 169	ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED, 613
ER_PARTIAL_REVOKES_EXIST, 129	ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT, 614
ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXIST, 130	ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_RECOVERED, 614
ER_PARTITIONS_MUST_BE_DEFINED_ERROR, 37	ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND, 613
ER_PARTITION_CLAUSE_ON_NONPARTITIONED, 54	ER_PERSISTENT_PRIVILEGES_BOOTSTRAP, 282
ER_PARTITION_COLUMN_LIST_ERROR, 47	ER_PERSIST_ONLY_ACCESS_DENIED_ERROR, 99
ER_PARTITION_CONST_DOMAIN_ERROR, 41	ER_PERSIST_OPTION_HOST_TRUNCATED, 562
ER_PARTITION_ENTRY_ERROR, 37	ER_PERSIST_OPTION_STATUS, 322
ER_PARTITION_EXCHANGE_DIFFERENT_OPTION, 53	ER_PERSIST_OPTION_USER_TRUNCATED, 562
ER_PARTITION_EXCHANGE_FOREIGN_KEY, 54	ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL, 293
ER_PARTITION_EXCHANGE_PART_TABLE, 53	ER_PFS_MALLOC_ARRAY_OOM, 294
ER_PARTITION_EXCHANGE_TEMP_TABLE, 54	ER_PFS_MALLOC_ARRAY_OVERFLOW, 294
ER_PARTITION_FIELDS_TOO_LONG, 47	ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED, 286
ER_PARTITION_FUNCTION_FAILURE, 39	ER_PFS_PATH_LOCATIONS_INACCESSIBLE, 536
ER_PARTITION_FUNCTION_IS_NOT_ALLOWED, 41	ER_PID_FILE_PRIV_DIRECTORY_INSECURE, 388
ER_PARTITION_FUNC_NOT_ALLOWED_ERROR, 37	ER_PK_INDEX_CANT_BE_INVISIBLE, 89
ER_PARTITION_HANDLER_ADMIN_MSG, 296	ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED, 81
ER_PARTITION_INSTEAD_OF_SUBPARTITION, 54	
ER_PARTITION_MAXVALUE_ERROR, 36	
ER_PARTITION_MERGE_ERROR, 41	
ER_PARTITION_MGMT_ON_NONPARTITIONED, 38	
ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_POINTER, 275	
ER_PARTITION_NAME, 45	
ER_PARTITION_NOT_DEFINED_ERROR, 37	
ER_PARTITION_NO_TEMPORARY, 41	
ER_PARTITION_REQUIRES_VALUES_ERROR, 36	

---

ER_PLUGIN_BAD_OPTIONS, 258	ER_PREVENTS_VARIABLE_WITHOUT_RBR, 78
ER_PLUGIN_CANNOT_BE_UNINSTALLED, 67	ER_PRIMARY_CANT_HAVE_NULL, 15
ER_PLUGIN_CANT_LOAD, 257	ER_PRIVILEGE_DEREGISTRATION, 637
ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE, 257	ER_PRIVILEGE_REGISTRATION, 637
ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS, 258	ER_PRIVILEGE_SYSTEM_INIT_FAILED, 282
ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLES, 320	ER_PROCAccess_DENIED_Error, 29
ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE, 320	ER_PROC_AUTO_GRANT_FAIL, 31
ER_PLUGIN_DELETE_BUILTIN, 44	ER_PROC_AUTO_REVOKE_FAIL, 31
ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS, 217	ER_PROTOCOL_COMPRESSION_RESET_LOG, 570
ER_PLUGIN_DISABLED, 258	ER_PS_MANY_PARAM, 30
ER_PLUGIN_EXCEPTION_OPERATION_FAILED, 631	ER_PS_NO_RECURSION, 34
ER_PLUGIN_FAILED_DEINITIALIZATION, 256	ER_QUERY_CACHE_DISABLED, 47
ER_PLUGIN_FAILED_TO_OPEN_TABLE, 533	ER_QUERY_INTERRUPTED, 26
ER_PLUGIN_FAILED_TO_OPEN_TABLES, 533	ER_QUERY_ON_FOREIGN_DATA_SOURCE, 33
ER_PLUGIN_FORCING_SHUTDOWN, 257	ER_QUERY_TIMEOUT, 70
ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES, 258	ER_RANGE_NOT_INCREASING_ERROR, 37
ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION, 256	ER_READING_TABLE_FAILED, 184
ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN, 257	ER_READY, 8
ER_PLUGIN_INIT_FAILED, 184	ER_READ_LOG_EVENT_FAILED, 291
ER_PLUGIN_INSTALL_ERROR, 542	ER_READ_ONLY_MODE, 63
ER_PLUGIN_INVALID_TABLE_DEFINITION, 603	ER_READ_ONLY_TRANSACTION, 18
ER_PLUGIN_IS_NOT_LOADED, 39	ER_RUNNING_AS_ROOT, 175
ER_PLUGIN_IS_PERMANENT, 51	ER_RECORD_FILE_FULL, 11
ER_PLUGIN_LOAD_OPTIONS_IGNORED, 572	ER_RECOVERING_TABLE, 259
ER_PLUGIN_LOAD_PARAMETER_TOO_LONG, 257	ER_REDUCED_DBLWR_FILE_CORRUPTED, 639
ER_PLUGIN_NOT_EARLY, 123	ER_REDUCED_DBLWR_PAGE_FOUND, 639
ER_PLUGIN_NOT_EARLY_DUP, 563	ER_REFERENCED_TRG_DOES_NOT_EXIST, 69
ER_PLUGIN_NO_INSTALL, 52	ER_REGEXP_BAD_ESCAPE_SEQUENCE, 106
ER_PLUGIN_NO_INSTALL_DUP, 563	ER_REGEXP_BAD_INTERVAL, 106
ER_PLUGIN_NO_UNINSTALL, 52	ER_REGEXP_BUFFER_OVERFLOW, 105
ER_PLUGIN_OOM, 258	ER_REGEXP_ERROR, 13
ER_PLUGIN_PARSING_OPTIONS_FAILED, 258	ER_REGEXP_ILLEGAL_ARGUMENT, 105
ER_PLUGIN_REGISTRATION_DONE, 149	ER_REGEXP_INDEX_OUTOFBOUNDS_ERROR, 106
ER_PLUGIN_REGISTRATION_FAILED, 257	ER_REGEXP_INTERNAL_ERROR, 106
ER_PLUGIN_REQUIRES_REGISTRATION, 149	ER_REGEXP_INVALID_BACK_REF, 106
ER_PLUGIN_SHUTTING_DOWN_PLUGIN, 257	ER_REGEXP_INVALID_CAPTURE_GROUP_NAME, 128
ER_PLUGIN_UNINSTALL_ERROR, 542	ER_REGEXP_INVALID_FLAG, 130
ER_PLUGIN_UNKNOWN_VARIABLE_TYPE, 257	ER_REGEXP_INVALID_RANGE, 107
ER_PLUGIN_VARIABLE_MISSING_NAME, 257	ER_REGEXP_LOOK_BEHIND_LIMIT, 106
ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL, 258	ER_REGEXP_MAX_LT_MIN, 106
ER_PLUGIN_VARIABLE_SET_READ_ONLY, 257	ER_REGEXP_MISMATCHED_PAREN, 106
ER_POINTLESS_WITHOUT_SLOWLOG, 171	ER_REGEXP_MISSING_CLOSE_BRACKET, 107
ER_POLYGON_TOO_LARGE, 110	ER_REGEXP_MISSING_FILE, 152
ER_PREPARE_FOR_PRIMARY_ENGINE, 605	ER_REGEXP_MISSING_ICU_DATADIR, 612
ER_PREPARE_FOR_SECONDARY_ENGINE, 556	ER_REGEXP_MISSING_RESOURCE, 152
	ER_REGEXP_PATTERN_TOO_BIG, 107
	ER_REGEXP_RULE_SYNTAX, 106
	ER_REGEXP_STACK_OVERFLOW, 107
	ER_REGEXP_STRING_NOT_TERMINATED, 105
	ER_REGEXP_TIME_OUT, 107
	ER_REGEXP_UNIMPLEMENTED, 106

---

ER_REGEX_NUMBER_TOO_BIG, 142	ER_REPLICA_IGNORE_SERVER_IDS, 46
ER_RELAY_LOG_FAIL, 30	ER_REPLICA_INCIDENT, 529
ER_RELAY_LOG_INIT, 30	ER_REPLICA_KILLED_AFTER_RECONNECT, 292
ER_RELAY_LOG_SPACE_LIMIT_DISABLED, 539	ER_REPLICA_MAX_CHANNELS_EXCEEDED, 76
ER_RELOAD_KEYRING_FAILURE, 146	ER_REPLICA_MULTIPLE_CHANNELS_CMD, 75
ER_REMOVED_SPACES, 35	ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY, 75
ER_RENAMED_NAME, 45	ER_REPLICA_NOT_RUNNING, 17
ER_RENAME_ROLE, 89	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS, 292
ER_REORG_HASH_ONLY_ON_SAME_NO, 38	ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL, 110
ER_REORG_NO_PARAM_ERROR, 38	ER_REPLICA_RECONNECT_FAILED, 292
ER_REORG_OUTSIDE_RANGE, 39	ER_REPLICA_RELAY_LOG_PURGE_FAILED, 284
ER_REORG_PARTITION_NOT_EXIST, 38	ER_REPLICA_RELAY_LOG_READ_FAILURE, 529
ER_REPLACE_INACCESSIBLE_ROWS, 74	ER_REPLICA_RELAY_LOG_TRUNCATE_INFO, 283
ER_REPLICATION_INCOMPATIBLE_TABLE_WITH_GIPK, 629	ER_REPLICA_RELAY_LOG_WRITE_FAILURE, 529
ER_REPLICA_AM_INIT_REPOSITORY, 66	ER_REPLICA_SILENT_RETRY_TRANSACTION, 61
ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_SOURCE, 594	ER_REPLICA_SOURCE_CONNECTION_FAILURE, 529
ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID_AND_GTID_MODE_SOURCE, 594	ER_REPLICA_SQL_THREAD_MUST_STOP, 70
ER_REPLICA_CANT_CREATE_CONVERSION, 49	ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS_RESET, 204
ER_REPLICA_CANT_USE_TEMPDIR, 240	ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_RESET, 203
ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED, 239	ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_RESET, 204
ER_REPLICA_CHANNEL_DOES_NOT_EXIST, 75	ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSING, 204
ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP, 70	ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION, 203
ER_REPLICA_CHANNEL_MUST_STOP, 76	ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION, 203
ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG, 75	ER_REPLICA_THREAD, 18
ER_REPLICA_CHANNEL_NOT_RUNNING, 76	ER_REPLICA_WORKER_STOPPED_PREVIOUS_THD_ERROR, 71
ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED, 82	ER_REQUIRES_PRIMARY_KEY, 15
ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER, 77	ER_REQUIRE_ROW_FORMAT_INVALID_VALUE, 135
ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP, 77	ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE, 161
ER_REPLICA_CHANNEL_WAS_NOT_RUNNING, 76	ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE, 632
ER_REPLICA_CHANNEL_WAS_RUNNING, 76	ER_RESERVED_SYNTAX, 30
ER_REPLICA_CM_INIT_REPOSITORY, 66	ER_RESERVED_TABLESPACE_NAME, 109
ER_REPLICA_CONFIGURATION, 59	ER_RESET_MASTER_TO_VALUE_OUT_OF_RANGE, 92
ER_REPLICA_CORRUPT_EVENT, 44	ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE, 92
ER_REPLICA_CREATE_EVENT_FAILURE, 528	ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER, 46
ER_REPLICA_FATAL_ERROR, 528	ER_RESOURCE_GROUP_BIND_FAILED, 103
ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE, 68	ER_RESOURCE_GROUP_BUSY, 102
ER_REPLICA_HEARTBEAT_FAILURE, 529	ER_RESOURCE_GROUP_DISABLED, 102
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE, 45	ER_RESOURCE_GROUP_EXISTS, 102
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX, 51	ER_RESOURCE_GROUP_IS_DISABLED, 286
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN, 51	
ER_REPLICA_IGNORED_SSL_PARAMS, 23	
ER_REPLICA_IGNORED_TABLE, 20	

---

ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED, 285	ER_ROLE_NOT_GRANTED, 89
ER_RESOURCE_GROUP_NOT_EXISTS, 102	ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG, 291
ER_RESOURCE_GROUP_POST_INIT_FAILED, 282	ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET, 54
ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED, 282	ER_ROW_DOES_NOT_MATCH_PARTITION, 54
ER_RESOURCE_GROUP_VALIDATION_FAILED, 286	ER_ROW_IN_WRONG_PARTITION, 65
ER_RESTART_RECEIVED_INFO, 299	ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR, 187
ER_RESTART_SERVER_FAILED, 108	ER_ROW_IS_REFERENCED, 19
ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT, 287	ER_ROW_IS_REFERENCED_2, 34
ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY, 287	ER_ROW_SINGLE_PARTITION_FIELD_ERROR, 47
ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE, 287	ER_RPL_AM_INIT_INFO_MSG, 296
ER_RES_GRP_FAILED_TO_SWITCH_RESOURCE_GROUP, 625	ER_RPL_ASYNC_CHANNEL_CANT_CONNECT, 592
ER_RES_GRP_FEATURE_NOT_AVAILABLE, 287	ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM, 592
ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED, 287	ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST, 592
ER_RES_GRP_INVALID_THREAD_PRIORITY, 288	ER_RPL_ASYNC_EXECUTING_QUERY, 592
ER_RES_GRP_INVALID_VCPU_ID, 298	ER_RPL_ASYNC_MANAGED_NAME_ADDED, 593
ER_RES_GRP_INVALID_VCPU_RANGE, 298	ER_RPL_ASYNC_MANAGED_NAME_REMOVED, 593
ER_RES_GRP_SET_THREAD_PRIORITY_FAILED, 287	ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED, 633
ER_RES_GRP_SET_THR_AFFINITY_FAILED, 287	ER_RPL_ASYNC_READ_FAILOVER_TABLE, 593
ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED, 287	ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF, 141
ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED, 288	ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE, 590
ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPU_ID_FAILED, 288	ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF, 140
ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_ID_FAILED, 288	ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL, 595
ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_RESOURCE, 626	ER_RPL_ASYNC_SENDER_ADDED, 592
ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_RESOURCE, 626	ER_RPL_ASYNC_SENDER_REMOVED, 592
ER_RES_GRP_SWITCH_FAILED_UNABLE_TO_APPLY_RESOURCE, 626	ER_RPL_BINLOG_FILTERS_OOM, 174
ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED, 287	ER_RPL_BINLOG_MASTER SENDS HEARTBEAT, 216
ER_RETRYING_REPAIR_WITHOUT_QUICK, 258	ER_RPL_BINLOG_MASTER_USES_CHECKSUM_AND_SLAVE_THREAD, 216
ER_RETRYING_REPAIR_WITH_KEYCACHE, 259	ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED, 184
ER_REVOKE_GRANTS, 22	ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO, 216
ER_REWRITER_LOAD_FAILED, 322	ER_RPL_BINLOG_SOURCE SENDS HEARTBEAT, 216
ER_REWRITER_OOM, 322	ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICAS, 216
ER_REWRITER_QUERY_ERROR_MSG, 318	ER_RPL_BINLOG_STARTING_DUMP, 216
ER_REWRITER_QUERY_FAILED, 318	ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED, 184
ER_REWRITER_READ_FAILED, 322	ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED, 184
ER_REWRITER_TABLE_MALFORMED_ERROR, 322	ER_RPL_CANNOT_OPEN_RELAY_LOG, 609
ER_ROLE_GRANTED_TO_ITSELF, 145	



---

ER_RPL_CANT_ADD_DO_TABLE, 177	ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION, 118
ER_RPL_CANT_ADD_IGNORE_TABLE, 177	ER_RPL_ERROR_CHANGING_APPLIER_METADATA_REPO, 210
ER_RPL_CANT_CREATE_REPLICA_THREAD, 227	ER_RPL_ERROR_CHANGING_CONNECTION_METADATA, 209
ER_RPL_CANT_CREATE_SLAVE_THREAD, 227	ER_RPL_ERROR_CHANGING_MASTER_INFO_REPO_TYPE, 209
ER_RPL_CANT_FIND_FOLLOWUP_FILE, 234	ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO_TYPE, 209
ER_RPL_CANT_HAVE_SAME_BASENAME, 278	ER_RPL_ERROR_CHECKING_REPOSITORY, 210
ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO, 241	ER_RPL_ERROR_CREATING_APPLIER_METADATA, 209
ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO, 241	ER_RPL_ERROR_CREATING_CONNECTION_METADATA, 209
ER_RPL_CANT_MAKE_PATHS, 180	ER_RPL_ERROR_CREATING_MASTER_INFO, 208
ER_RPL_CANT_OPEN_INFO_TABLE, 207	ER_RPL_ERROR_CREATING_RELAY_LOG_INFO, 209
ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO, 241	ER_RPL_ERROR_LOOKING_FOR_LOG, 234
ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO, 241	ER_RPL_ERROR_READING_MASTER_CONFIGURATION, 256
ER_RPL_CANT_SCAN_INFO_TABLE, 207	ER_RPL_ERROR_READING_SOURCE_CONFIGURATION, 256
ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP, 125	ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION, 254
ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKUP, 125	ER_RPL_ERROR_READING_SOURCE_CONFIGURATION, 256
ER_RPL_CHANGING_APPLIER_METADATA_REPO_TYPE_FAILED, 209	ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION, 254
ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE_FAILED, 209	ER_RPL_ERROR_READING_SOURCE_CONFIGURATION, 256
ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID, 208	ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION, 254
ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPLICAS, 208	ER_RPL_ERROR_READING_SOURCE_CONFIGURATION, 256
ER_RPL_CORRUPTED_INFO_TABLE, 207	ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION, 254
ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE, 208	ER_RPL_ERROR_READING_SOURCE_CONFIGURATION, 256
ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY, 119	ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION, 254
ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT, 119	ER_RPL_ERROR_READING_SOURCE_CONFIGURATION, 256
ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY, 117	ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE, 212
ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY, 117	ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE, 212
ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY, 117	ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKERS, 210
ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS, 117	ER_RPL_FAILED_TO_DELETE_FROM_SLAVE_WORKERS, 210
ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY, 117	ER_RPL_FAILED_TO_OPEN_INFO_FILE, 212
ER_RPL_ENCRYPTION_HEADER_ERROR, 117	ER_RPL_FAILED_TO_OPEN_RELAY_LOG, 254
ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY, 117	ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_REPO, 210
ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED, 117	ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO_REPO, 210
ER_RPL_ENCRYPTION_KEY_NOT_FOUND, 117	ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX, 240
ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED, 118	ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL, 293
	ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED, 282

---

ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED, 282	ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED, 255
ER_RPL_GTID_LOG_EVENT_IN_STREAM, 213	ER_RPL_MTA_STATISTICS, 231
ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE, 212	ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED, 227
ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY, 278	ER_RPL_MTS_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT, 234
ER_RPL_GTID_TABLE_CANNOT_OPEN, 164	ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO, 234
ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION, 542	ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO_FOR, 233
ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT, 526	ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG, 227
ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE, 526	ER_RPL_MTS_RECOVERY_COMPLETE, 231
ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE, 526	ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDINATOR, 226
ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR, 214	ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR, 226
ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX, 208	ER_RPL_MTS_RECOVERY_SUCCESSFUL, 227
ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX, 208	ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED, 255
ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION, 607	ER_RPL_MTS_STATISTICS, 230
ER_RPL_INFINITY_DENIED, 182	ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORY, 211
ER_RPL_INFINITY_IGNORED, 182	ER_RPL_OPEN_INDEX_FILE_FAILED, 241
ER_RPL_INFO_DATA_TOO_LONG, 54	ER_RPL_PLEASE_USE_OPTION_RELAY_LOG, 241
ER_RPL_IO_THREAD_KILLED, 292	ER_RPL_PLUGIN_FUNCTION_FAILED, 184
ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED, 642	ER_RPL_RECOVERY_ERROR, 225
ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET, 232	ER_RPL_RECOVERY_ERROR_FREEING_IO_CACHE, 225
ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWED_PACKET, 232	ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG, 225
ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_SPACE, 240	ER_RPL_RECOVERY_FILE_MASTER_POS_INFO, 226
ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER, 642	ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO, 226
ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED, 227	ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX, 226
ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT, 234	ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER, 225
ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA, 234	ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE, 225
ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA, 234	ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRED_FOR_WORKER, 226
ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG, 227	ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHANNEL, 225
ER_RPL_MTA_RECOVERY_COMPLETE, 231	ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY, 240
ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR, 226	ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY, 240
ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR, 226	ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY, 613
ER_RPL_MTA_RECOVERY_SUCCESSFUL, 227	ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE, 576

---

ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM_DA, 236	ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE, 276
ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_DISABLED, 224	ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_METADATA, 233
ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA, 229	ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOURCE, 232
ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER, 233	ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED_ERROR, 238
ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION, 231	ER_RPL_REPLICA_IO_THREAD_EXITING, 233
ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL, 224	ER_RPL_REPLICA_IO_THREAD_KILLED, 231
ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL, 225	ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT, 526
ER_RPL_REPLICA_CANT_USE_CHARSET, 238	ER_RPL_REPLICA_IO_THREAD_WAS_KILLED, 228
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICA_FROM_RESERVED, 238	ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING, 593
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_FROM_RESERVED, 633	ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_FAILED, 593
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_FROM_RESERVED_NEW_C_M_NEEDS_REPOS_TYPE_OTHER, 633	ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE, 240
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_FROM_RESERVED_NEXT_LOG_IS_INACTIVE, 633	ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE, 238
ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST, 211	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONNECTION, 237
ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE, 230	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NON_BLOCKING, 573
ER_RPL_REPLICA_ERROR_INFO_FROM_DA, 236	ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE, 237
ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED_LIBRARY, 236	ER_RPL_REPLICA_REPORT_HOST_TOO_LONG, 229
ER_RPL_REPLICA_ERROR_READING_FROM_SERVER, 230	ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG, 229
ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS, 239	ER_RPL_REPLICA_REPORT_USER_TOO_LONG, 229
ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP, 232	ER_RPL_REPLICA_RESET_FILTER_OPTIONS, 284
ER_RPL_REPLICA_ERROR_RETRYING, 230	ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS, 228
ER_RPL_REPLICA_ERROR_RUNNING_QUERY, 237	ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED, 236
ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM_CONNECTION_METADATA, 212	ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST, 633
ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_REPO, 224	ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED, 633
ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA_STRUCTURE, 211	ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANGED, 633
ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_STRUCTURE, 211	ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_ERROR, 573
ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH, 235	ER_RPL_REPLICA_SQL_THREAD_EXITING, 237
ER_RPL_REPLICA_FILTER_CREATE_FAILED, 284	ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT, 235
ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD, 232	ER_RPL_REPLICA_SQL_THREAD_STARTING, 235
ER_RPL_REPLICA_GENERIC_MESSAGE, 210	ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PRIVILEGES, 571
ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED, 284	ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT, 526
ER_RPL_REPLICA_INCORRECT_CHANNEL, 277	

---

ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM, 233	ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_INFO_F 224
ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_ 228	ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCT 211
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED 235	ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE 211
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED 235	ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH, 235
ER_RPL_REPO_HAS_GAPS, 166	ER_RPL_SLAVE_FILTER_CREATE_FAILED, 284
ER_RPL_REPO_SHOULD_BE_TABLE, 208	ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED, 277
ER_RPL_REWRITEDB_EMPTY_FROM, 178	ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD, 232
ER_RPL_REWRITEDB_EMPTY_TO, 178	ER_RPL_SLAVE_GENERIC_MESSAGE, 210
ER_RPL_REWRITEDB_MISSING_ARROW, 178	ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED, 284
ER_RPL_RLI_INIT_INFO_MSG, 296	ER_RPL_SLAVE_INCORRECT_CHANNEL, 277
ER_RPL_SERVER_ID_MISSING, 227	ER_RPL_SLAVE_INVALID_SECURE_CHANGE_MASTER, 276
ER_RPL_SLAVE_ADDITIONAL_ERROR_INFO_FROM_DA 236	ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_RELAY 233
ER_RPL_SLAVE_APPLY_LOG_EVENT_FAILED_INVALID 573	ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MASTER 232
ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE 224	ER_RPL_SLAVE_IO_THREAD_DETECTED_UNEXPECTED_EVENT 238
ER_RPL_SLAVE_CANT_FLUSH_MASTER_INFO_FILE, 229	ER_RPL_SLAVE_IO_THREAD_EXITING, 233
ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER, 233	ER_RPL_SLAVE_IO_THREAD_KILLED, 231
ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION, 231	ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT, 526
ER_RPL_SLAVE_CANT_START_SLAVE_FOR_CHANNEL, 224	ER_RPL_SLAVE_IO_THREAD_WAS_KILLED, 228
ER_RPL_SLAVE_CANT_STOP_SLAVE_FOR_CHANNEL, 225	ER_RPL_SLAVE_MASTER_UUID_HAS_CHANGED, 228
ER_RPL_SLAVE_CANT_USE_CHARSET, 238	ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE, 235
ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION 238	ER_RPL_SLAVE_NEW_MASTER_INFO_NEEDS_REPOS_TYPE 240
ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION 231	ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE, 238
ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST 211	ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE, 238
ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER, 230	ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_CONFIGUR 237
ER_RPL_SLAVE_ERROR_INFO_FROM_DA, 236	ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_NON_ROW 237
ER_RPL_SLAVE_ERROR_LOADING_USER_DEFINED_LIB 236	ER_RPL_SLAVE_READ_INVALID_EVENT_FROM_MASTER, 237
ER_RPL_SLAVE_ERROR_READING_FROM_SERVER, 230	ER_RPL_SLAVE_REPORT_HOST_TOO_LONG, 229
ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENT 239	ER_RPL_SLAVE_REPORT_PASSWORD_TOO_LONG, 229
ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP 232	ER_RPL_SLAVE_REPORT_USER_TOO_LONG, 229
ER_RPL_SLAVE_ERROR_RETRYING, 230	ER_RPL_SLAVE_RESET_FILTER_OPTIONS, 284
ER_RPL_SLAVE_ERROR_RUNNING_QUERY, 237	ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS, 228
ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM 211	ER_RPL_SLAVE_SKIP_COUNTER_EXECUTED, 236
	ER_RPL_SLAVE_SQL_THREAD_DETECTED_UNEXPECTED_EV 573

---

ER_RPL_SLAVE_SQL_THREAD_EXITING, 237	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_F
ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_575	ER_SCHEMA_READ_ONLY, 140
239	ER_SDI_GET_KEYS_INVALID_TABLESPACE, 146
ER_RPL_SLAVE_SQL_THREAD_STARTING, 235	ER_SDI_OPERATION_FAILED, 103
ER_RPL_SLAVE_SQL_THREAD_STARTING_WITH_PRIVILEGE_COPIES, 571	ER_SDI_OPERATION_FAILED_MISSING_RECORD,
ER_RPL_SLAVE_SQL_THREAD_STOP_CMD_EXEC_TIME_100	OUT,
525	ER_SECONDARY_ENGINE, 128
ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM,	ER_SECONDARY_ENGINE_DDL, 129
233	ER_SECONDARY_ENGINE_DDL_FAILED, 639
ER_RPL_SLAVE_USES_CHECKSUM_AND_MASTER_PRI	ER_SECONDARY_ENGINE_PLUGIN, 127
228	ER_SECOND_PASSWORD_CANNOT_BE_EMPTY,
ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_127	227
234	ER_SECURE_AUTH_VALUE_UNSUPPORTED, 171
ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_171	ER_SECURE_TRANSPORT_REQUIRED, 83
235	ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG, 173
ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED	ER_SEC_FILE_PRIV_CANT_ACCESS_DIR, 172
256	ER_SEC_FILE_PRIV_CANT_STAT, 173
ER_RPL_SSL_INFO_IN_MASTER_INFO_IGNORED,	ER_SEC_FILE_PRIV_DIRECTORY_INSECURE, 173
256	ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS,
ER_RPL_TIMESTAMPS_RETURNED_TO_NORMAL,	173
283	ER_SEC_FILE_PRIV_EMPTY, 172
ER_RPL_TRX_DELEGATES_INIT_FAILED, 184	ER_SEC_FILE_PRIV_IGNORED, 172
ER_RPL_UNEXPECTED_BEGIN_IN_STREAM, 214	ER_SEC_FILE_PRIV_NULL, 173
ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_100	ER_SEMI_SYNC_ADD_ACK_TO_SLOT, 308
214	ER_SEMI_SYNC_BINLOG_REPLY_IS_AHEAD, 307
ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM,	ER_SEMI_SYNC_BINLOG_WRITE_OUT_OF_ORDER,
214	307
ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM,	ER_SEMI_SYNC_CLEARED_ACTIVE_TRANSACTION_TILL_F
213	305
ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG,	ER_SEMI_SYNC_CLEARED_ALL_ACTIVE_TRANSACTION_N
255	305
ER_RPL_WORKER_CANT_READ_RELAY_LOG, 254	ER_SEMI_SYNC_DISABLED_ON_MASTER, 306
ER_RPL_WORKER_ID_IS, 208	ER_SEMI_SYNC_DISABLED_ON_SOURCE, 306
ER_RPL_ZOMBIE_ENCOUNTERED, 164	ER_SEMI_SYNC_EXECUTION_FAILED_ON_MASTER,
ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_112	312
ER_RUN_HOOK_ERROR, 78	ER_SEMI_SYNC_EXECUTION_FAILED_ON_SOURCE,
ER_SAME_NAME_PARTITION, 38	312
ER_SAME_NAME_PARTITION_FIELD, 47	ER_SEMI_SYNC_FAILED_REGISTER_REPLICA_TO_RECEIV
ER_SCHEDULER_KILLING, 168	309
ER_SCHEDULER_STARTED, 168	ER_SEMI_SYNC_FAILED_REGISTER_SLAVE_TO_RECEIVER
ER_SCHEDULER_STOPPED, 167	309
ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER_168	ER_SEMI_SYNC_FAILED_TO_ALLOCATE_TRX_NODE,
168	304
ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT,	ER_SEMI_SYNC_FAILED_TO_INSERT_TRX_NODE,
168	308
ER_SCHEDULER_WAITING, 168	ER_SEMI_SYNC_FAILED_TO_START_ACK_RECEIVER_THD
ER_SCHEMA_DIR_CREATE_FAILED, 105	309
ER_SCHEMA_DIR_EXISTS, 105	ER_SEMI_SYNC_FAILED_TO_STOP_ACK_RECEIVER_THD,
ER_SCHEMA_DIR_MISSING, 105	312
ER_SCHEMA_DIR_UNKNOWN, 105	ER_SEMI_SYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET,
ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_309	309
575	ER_SEMI_SYNC_FORCED_SHUTDOWN, 306

---

---

ER_SEMISYNC_FUNCTION_CALLED_TWICE, 305	ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH,
ER_SEMISYNC_INIT_WAIT_POS, 307	308
ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY,	ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS,
304	306
ER_SEMISYNC_MASTER_FAILED_ON_NET_FLUSH,	ER_SEMISYNC_SOURCE_OOM, 306
308	ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS,
ER_SEMISYNC_MASTER_GOT_REPLY_AT_POS,	306
306	ER_SEMISYNC_SOURCE_TRX_WAIT_POS, 307
ER_SEMISYNC_MASTER_OOM, 306	ER_SEMISYNC_STARTING_ACK_RECEIVER_THD,
ER_SEMISYNC_MASTER_SIGNAL_ALL_WAITING_THREADS,	306
306	ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA,
ER_SEMISYNC_MASTER_TRX_WAIT_POS, 307	310
ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT,	ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE,
311	309
ER_SEMISYNC_MOVE_BACK_WAIT_POS, 307	ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD,
ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER,	309
312	ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA,
ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE,	310
312	ER_SEMISYNC_STOP_BINLOG_DUMP_TO_SLAVE,
ER_SEMISYNC_NO_SPACE_IN_THE_PKT, 308	310
ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY,	ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO,
304	308
ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER,	ER_SEMISYNC_TRACE_ENTER_FUNC, 304
308	ER_SEMISYNC_TRACE_EXIT, 304
ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED,	ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE,
311	304
ER_SEMISYNC_REPLICA_REPLY, 311	ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE,
ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO,	304
311	ER_SEMISYNC_TRX_SKIPPED_AT_POS, 308
ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED,	ER_SEMISYNC_UNREGISTERED_REPLICATOR,
312	310
ER_SEMISYNC_REPLICA_SET_FAILED, 312	ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER,
ER_SEMISYNC_REPLICA_START, 311	310
ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE,	ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER,
305	310
ER_SEMISYNC_REPLY_MAGIC_NO_ERROR, 305	ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED,
ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL,	310
305	ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK,
ER_SEMISYNC_RPL_ENABLED_ON_MASTER, 305	309
ER_SEMISYNC_RPL_ENABLED_ON_SOURCE, 305	ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK,
ER_SEMISYNC_RPL_INIT_FOR_TRX, 304	308
ER_SEMISYNC_RPL_SWITCHED_OFF, 307	ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT,
ER_SEMISYNC_RPL_SWITCHED_ON, 307	307
ER_SEMISYNC_SERVER_REPLY, 305	ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TR,
ER_SEMISYNC_SLAVE_NET_FLUSH_REPLY_FAILED,	307
311	ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT,
ER_SEMISYNC_SLAVE_REPLY, 310	307
ER_SEMISYNC_SLAVE_REPLY_WITH_BINLOG_INFO,	ER_SERVERID_TOO_LARGE, 182
311	ER_SERVER_ACL_TABLE_ERROR, 532
ER_SEMISYNC_SLAVE_SEND_REPLY_FAILED,	ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_C,
311	557
ER_SEMISYNC_SLAVE_SET_FAILED, 312	ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CL,
ER_SEMISYNC_SLAVE_START, 311	557
ER_SEMISYNC_SOCKET_FD_TOO_LARGE, 310	

---

---

ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION, 561	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS, 548
ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2, 531	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY, 548
ER_SERVER_CANT_OPEN_FILE, 531	ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR, 548
ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2, 532	ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY, 548
ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2, 532	ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY, 548
ER_SERVER_COST_FAILED_TO_READ, 213	ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED, 548
ER_SERVER_COST_INVALID_COST_CONSTANT, 212	ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND, 547
ER_SERVER_COST_UNKNOWN_COST_CONSTANT, 212	ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERED, 548
ER_SERVER_DISK_FULL_NOWAIT, 531	ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE, 549
ER_SERVER_DOWNGRADE_FROM_VERSION, 640	ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY, 549
ER_SERVER_DOWNGRADE_STATUS, 640	ER_SERVER_SHUTDOWN, 7
ER_SERVER_FILE_NOT_FOUND, 531	ER_SERVER_SHUTDOWN_COMPLETE, 278
ER_SERVER_FILE_USED, 531	ER_SERVER_SHUTDOWN_INFO, 535
ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR, 542	ER_SERVER_SLAVE_CONVERSION_FAILED, 532
ER_SERVER_HANDLER_ERROR, 531	ER_SERVER_SLAVE_IGNORED_TABLE, 533
ER_SERVER_INIT_COMPILED_IN_COMMANDS, 296	ER_SERVER_SLAVE_INIT_QUERY_FAILED, 532
ER_SERVER_ISNT_AVAILABLE, 84	ER_SERVER_SLAVE_MI_INIT_REPOSITORY, 530
ER_SERVER_IS_IN_SECURE_AUTH_MODE, 23	ER_SERVER_SLAVE_RLI_INIT_REPOSITORY, 530
ER_SERVER_MASTER_FATAL_ERROR_READING_BINLOG, 528	ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG, 528
ER_SERVER_NET_PACKET_TOO_LARGE, 530	ER_SERVER_STARTUP_ADMIN_INTERFACE, 549
ER_SERVER_NEW_ABORTING_CONNECTION, 531	ER_SERVER_STARTUP_MSG, 280
ER_SERVER_NOT_FORM_FILE, 531	ER_SERVER_TABLE_CHECK_FAILED, 532
ER_SERVER_NO_SESSION_TO_SEND_TO, 530	ER_SERVER_TEST_MESSAGE, 533
ER_SERVER_NO_SYSTEM_TABLE_ACCESS, 530	ER_SERVER_UNKNOWN_ERROR, 530
ER_SERVER_OFFLINE_MODE, 71	ER_SERVER_UNKNOWN_SYSTEM_VARIABLE, 530
ER_SERVER_OUTOFMEMORY, 281	ER_SERVER_UPGRADE_CHECKING_DB, 560
ER_SERVER_OUT_OF_RESOURCES, 280	ER_SERVER_UPGRADE_EMPTY_SYS, 559
ER_SERVER_OUT_OF_SORTMEMORY, 531	ER_SERVER_UPGRADE_FAILED, 558
ER_SERVER_RECORD_FILE_FULL, 531	ER_SERVER_UPGRADE_FROM_VERSION, 553
ER_SERVER_REPLICA_AM_INIT_REPOSITORY, 530	ER_SERVER_UPGRADE_HELP_TABLE_STATUS, 561
ER_SERVER_REPLICA_CM_INIT_REPOSITORY, 530	ER_SERVER_UPGRADE_INFO_FILE, 559
ER_SERVER_REPLICA_CONVERSION_FAILED, 532	ER_SERVER_UPGRADE_MYSQL_TABLES, 559
ER_SERVER_REPLICA_IGNORED_TABLE, 533	ER_SERVER_UPGRADE_NO_SYS_VERSION, 559
ER_SERVER_REPLICA_INIT_QUERY_FAILED, 532	ER_SERVER_UPGRADE_OFF, 558
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT, 552	ER_SERVER_UPGRADE_PENDING, 558
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY, 547	ER_SERVER_UPGRADE_REPAIR_REQUIRED, 559
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY, 548	ER_SERVER_UPGRADE_REPAIR_STATUS, 559
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY, 548	ER_SERVER_UPGRADE_SKIP, 558
	ER_SERVER_UPGRADE_STATUS, 559
	ER_SERVER_UPGRADE_SYSTEM_TABLES, 559
	ER_SERVER_UPGRADE_SYS_SCHEMA, 559

---

ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNTER, 560	ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG, 75
ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED, 560	ER_SLAVE_CHANNEL_NOT_RUNNING, 76
ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE, 560	ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED, 82
ER_SERVER_UPGRADE_SYS_VERSION_EMPTY, 559	ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER, 77
ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED, 553	ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP, 77
ER_SERVER_WARN_DEPRECATED, 556	ER_SLAVE_CHANNEL_WAS_NOT_RUNNING, 76
ER_SERVER_WRONG_VALUE_FOR_VAR, 541	ER_SLAVE_CHANNEL_WAS_RUNNING, 76
ER_SESSION_WAS_KILLED, 84	ER_SLAVE_CONFIGURATION, 59
ER_SETNS_FAILED, 562	ER_SLAVE_CONVERSION_FAILED, 49
ER_SET_CONSTANTS_ONLY, 18	ER_SLAVE_CORRUPT_EVENT, 43
ER_SET_EVENT_FAILED, 536	ER_SLAVE_CREATE_EVENT_FAILURE, 528
ER_SET_PASSWORD_AUTH_PLUGIN, 50	ER_SLAVE_FATAL_ERROR, 528
ER_SET_PASSWORD_AUTH_PLUGIN_ERROR, 155	ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER, 68
ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION, 57	ER_SLAVE_HEARTBEAT_FAILURE, 529
ER_SE_TYPECODE_CONFLICT, 188	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE, 44
ER_SHA256_PASSWORD_SECOND_PASSWORD_USED, 550	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX, INFORMATION, 51
ER_SHAPE_PREDICTION_UDF, 157	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN, 51
ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE, 543	ER_SLAVE_IGNORED_SSL_PARAMS, 23
ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL, 320	ER_SLAVE_IGNORED_TABLE, 20
ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH, 320	ER_SLAVE_IGNORE_SERVER_IDS, 46
ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING, 319	ER_SLAVE_INCIDENT, 529
ER_SHA_PWD_RSA_KEY_TOO_LONG, 320	ER_SLAVE_KILLED_AFTER_RECONNECT, 292
ER_SHA_PWD_SALT_FOR_USER_CORRUPT, 320	ER_SLAVE_MASTER_COM_FAILURE, 529
ER_SHUTDOWN_COMPLETE, 8	ER_SLAVE_MAX_CHANNELS_EXCEEDED, 76
ER_SHUTTING_DOWN_REPLICA_THREADS, 175	ER_SLAVE_MI_INIT_REPOSITORY, 66
ER_SHUTTING_DOWN_SLAVE_THREADS, 175	ER_SLAVE_MULTIPLE_CHANNELS_CMD, 75
ER_SIGNAL_BAD_CONDITION_TYPE, 46	ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY, 75
ER_SIGNAL_EXCEPTION, 46	ER_SLAVE_NOT_RUNNING, 17
ER_SIGNAL_NOT_FOUND, 46	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS, 292
ER_SIGNAL_WARN, 46	ER_SLAVE_POSSIBLY_DIVERGED_AFTER_DDL, 110
ER_SIZE_OVERFLOW_ERROR, 39	ER_SLAVE_RECONNECT_FAILED, 292
ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE, 291	ER_SLAVE_RELAY_LOG_PURGE_FAILED, 284
ER_SLAVE_ANONYMOUS_TO_GTID_IS_LOCAL_OR_USER_DEFINED, 593	ER_SLAVE_RELAY_LOG_READ_FAILURE, 529
ER_SLAVE_CANT_CREATE_CONVERSION, 49	ER_SLAVE_RELAY_LOG_TRUNCATE_INFO, 283
ER_SLAVE_CANT_USE_TEMPDIR, 240	ER_SLAVE_RELAY_LOG_WRITE_FAILURE, 529
ER_SLAVE_CHANGE_MASTER_TO_EXECUTED, 239	ER_SLAVE_RLI_INIT_REPOSITORY, 66
ER_SLAVE_CHANNEL_DOES_NOT_EXIST, 75	ER_SLAVE_SILENT_RETRY_TRANSACTION, 61
ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP, 70	ER_SLAVE_SQL_THREAD_MUST_STOP, 70
ER_SLAVE_CHANNEL_MUST_STOP, 76	ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED, 204
	ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALREADY_RUNNING, 203
	ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED, 203



---

ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED,	ER_SP_NORETURNEND, 26
204	ER_SP_NOT_VAR_ARG, 32
ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_CONDITION_REACHED,	ER_SP_NO_AGGREGATE, 35
203	ER_SP_NO_DROP_SP, 29
ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED,	ER_SP_NO_RECURSION, 32
203	ER_SP_NO_RECURSIVE_CREATE, 25
ER_SLAVE_THREAD, 17	ER_SP_NO_RESET, 32
ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ERROR,	ER_SP_RECURSION_LIMIT, 35
71	ER_SP_STORE_FAILED, 25
ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING,	ER_SP_SUBSELECT_NYI, 27
118	ER_SP_UNDECLARED_VAR, 27
ER_SOURCE, 16	ER_SP_UNINIT_VAR, 26
ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE, 53	ER_SP_VARCOND_AFTER_CURSHNDLR, 27
ER_SOURCE_FATAL_ERROR_READING_BINLOG,	ER_SP_WRONG_NAME, 35
20	ER_SP_WRONG_NO_OF_ARGS, 26
ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS,	ER_SP_WRONG_NO_OF_FETCH_ARGS, 27
59	ER_SQLTHREAD_WITH_SECURE_REPLICA, 56
ER_SOURCE_NET_READ, 16	ER_SQLTHREAD_WITH_SECURE_SLAVE, 56
ER_SOURCE_NET_WRITE, 16	ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL, 187
ER_SPATIAL_CANT_HAVE_NULL, 21	ER_SQL_HA_READ_FAILED, 184
ER_SPATIAL_FUNCTIONAL_INDEX, 114	ER_SQL_MODE_MERGED, 81
ER_SPATIAL_MUST_HAVE_GEOM_COL, 49	ER_SQL_MODE_MERGED_WITH_STRICT_MODE,
ER_SPATIAL_UNIQUE_INDEX, 110	279
ER_SPECIFIC_ACCESS_DENIED_ERROR, 20	ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_M
ER_SPVAR_NONINTEGER_TYPE, 143	144
ER_SP_ALREADY_EXISTS, 25	ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GT
ER_SP_BADRETURN, 26	65
ER_SP_BADSELECT, 26	ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MOD
ER_SP_BADSTATEMENT, 26	144
ER_SP_BAD_CURSOR_QUERY, 26	ER_SQL_USER_TABLE_ALTER_WARNING, 187
ER_SP_BAD_CURSOR_SELECT, 26	ER_SQL_USER_TABLE_CREATE_WARNING, 187
ER_SP_BAD_SQLSTATE, 31	ER_SRS_ATTRIBUTE_STRING_TOO_LONG, 109
ER_SP_BAD_VAR_SHADOW, 34	ER_SRS_GEOGCS_INVALID_AXES, 111
ER_SP_CANT ALTER, 27	ER_SRS_ID_ALREADY_EXISTS, 108
ER_SP_CANT_SET_AUTOCOMMIT, 34	ER_SRS_INVALID_ANGULAR_UNIT, 111
ER_SP_CASE_NOT_FOUND, 28	ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE,
ER_SP_COND_MISMATCH, 26	109
ER_SP_CURSOR_AFTER_HANDLER, 27	ER_SRS_INVALID_HEIGHT, 157
ER_SP_CURSOR_ALREADY_OPEN, 27	ER_SRS_INVALID_INVERSE_FLATTENING, 111
ER_SP_CURSOR_MISMATCH, 27	ER_SRS_INVALID_LATITUDE_OF_ORIGIN, 155
ER_SP_CURSOR_NOT_OPEN, 27	ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A,
ER_SP_DOES_NOT_EXIST, 25	158
ER_SP_DROP_FAILED, 25	ER_SRS_INVALID_LONGITUDE_OF_ORIGIN, 155
ER_SP_DUP_COND, 27	ER_SRS_INVALID_PRIME_MERIDIAN, 111
ER_SP_DUP_CURS, 27	ER_SRS_INVALID_SCALING, 157
ER_SP_DUP_HANDLER, 32	ER_SRS_INVALID_SEMI_MAJOR_AXIS, 111
ER_SP_DUP_PARAM, 27	ER_SRS_INVALID_ZONE_WIDTH, 157
ER_SP_DUP_VAR, 27	ER_SRS_MISSING_MANDATORY_ATTRIBUTE, 108
ER_SP_FETCH_NO_DATA, 27	ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS,
ER_SP_LABEL_MISMATCH, 26	108
ER_SP_LABEL_REDEFINE, 26	ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE,
ER_SP_LILABEL_MISMATCH, 25	108
ER_SP_LOAD_FAILED, 88	ER_SRS_NOT_CARTESIAN, 89
ER_SP_NORETURN, 26	ER_SRS_NOT_CARTESIAN_UNDEFINED, 89

---

---

ER_SRS_NOT_FOUND, 91	ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT, 41
ER_SRS_NOT_GEOGRAPHIC, 110	ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN, 50
ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITE_SPACE, 108	ER_SUBPARTITION_ERROR, 37
ER_SRS_PARSE_ERROR, 88	ER_SUBPARTITION_NAME, 45
ER_SRS_PROJ_PARAMETER_MISSING, 88	ER_SUBQUERY_NO_1_ROW, 21
ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT, 155	ER_SUBQUERY_TRANSFORM_REJECTED, 138
ER_SR_BOGUS_VALUE, 184	ER_SWITCH_TMP_ENGINE, 94
ER_SR_INVALID_CONTEXT, 184	ER_SYNTAX_ERROR, 14
ER_SSL_FIPS_MODE_ERROR, 322	ER_SYSTEMD_NOTIFY_CONNECT_FAILED, 387
ER_SSL_LIBRARY_ERROR, 170	ER_SYSTEMD_NOTIFY_DEBUG, 625
ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED, 543	ER_SYSTEMD_NOTIFY_PATH_TOO_LONG, 387
ER_SSL_SERVER_CERT_VERIFY_FAILED, 562	ER_SYSTEMD_NOTIFY_WRITE_FAILED, 387
ER_SSL_TRYING_DATADIR_DEFAULTS, 181	ER_SYSTEM_SCHEMA_NOT_FOUND, 164
ER_STACKSIZE_UNEXPECTED, 180	ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE, 280
ER_STACK_BACKTRACE, 627	ER_SYSTEM_TABLE_NOT_TRANSACTIONAL, 255
ER_STACK_OVERRUN, 11	ER_SYSTEM_VIEW_INIT_FAILED, 281
ER_STACK_OVERRUN_NEED_MORE, 33	ER_SYSVAR_CHANGE_DURING_QUERY, 131
ER_STARTING_AS, 174	ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_PERSISTENT, 321
ER_STARTING_INIT, 535	ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE_COMPONENT, 321
ER_STARTING_REPLICA_MONITOR_IO_THREAD, 143	ER_SYS_VAR_COMPONENT_OOM, 321
ER_STARTUP, 31	ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE, 321
ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION, 139	ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY, 321
ER_STD_BAD_ALLOC_ERROR, 72	ER_SYS_VAR_DEREGISTRATION, 637
ER_STD_DOMAIN_ERROR, 72	ER_SYS_VAR_NOT_FOUND, 537
ER_STD_INVALID_ARGUMENT, 73	ER_SYS_VAR_REGISTRATION, 637
ER_STD_LENGTH_ERROR, 73	ER_TABLEACCESS_DENIED_ERROR, 13
ER_STD_LOGIC_ERROR, 73	ER_TABLENAME_NOT_ALLOWED_HERE, 21
ER_STD_OUT_OF_RANGE_ERROR, 73	ER_TABLESPACE_AUTO_EXTEND_ERROR, 39
ER_STD_OVERFLOW_ERROR, 73	ER_TABLESPACE_CANNOT_BE_DECRYPTED, 122
ER_STD_RANGE_ERROR, 73	ER_TABLESPACE_CANNOT_BE_ENCRYPTED, 122
ER_STD_REGEX_ERROR, 124	ER_TABLESPACE_CANNOT_ENCRYPT, 85
ER_STD_RUNTIME_ERROR, 73	ER_TABLESPACE_DISCARDED, 61
ER_STD_UNDERFLOW_ERROR, 73	ER_TABLESPACE_DUP_FILENAME, 97
ER_STD_UNKNOWN_EXCEPTION, 73	ER_TABLESPACE_ENGINE_MISMATCH, 101
ER_STMT_CACHE_FULL, 51	ER_TABLESPACE_EXISTS, 61
ER_STMT_HAS_NO_OPEN_CURSOR, 32	ER_TABLESPACE_IS_NOT_EMPTY, 80
ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG, 27	ER_TABLESPACE_MISSING, 61
ER_STOP_REPLICA_IO_THREAD_DISK_SPACE, 321	ER_TABLESPACE_MISSING_WITH_NAME, 88
ER_STOP_REPLICA_IO_THREAD_TIMEOUT, 67	ER_TABLESPACE_TYPE_UNKNOWN, 122
ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT, 143	ER_TABLES_DIFFERENT_METADATA, 54
ER_STOP_REPLICA_SQL_THREAD_TIMEOUT, 66	ER_TABLE_CANT_HANDLE_AUTO_INCREMENT, 14
ER_STOP_SLAVE_IO_THREAD_DISK_SPACE, 321	ER_TABLE_CANT_HANDLE_BLOB, 14
ER_STOP_SLAVE_IO_THREAD_TIMEOUT, 66	ER_TABLE_CANT_HANDLE_FT, 19
ER_STOP_SLAVE_SQL_THREAD_TIMEOUT, 66	ER_TABLE_CANT_HANDLE_SPKEYS, 35
ER_STORAGE_ENGINE_NOT_LOADED, 68	ER_TABLE_CHECK_INTEGRITY_FAILED, 183
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT, 49	ER_TABLE_CORRUPT, 67

---

---

ER_TABLE_CREATED_WITH_DIFFERENT_VERSION, 200	ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG, 112
ER_TABLE_DEF_CHANGED, 32	ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR, 41
ER_TABLE_EXISTS_ERROR, 6	ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG, 112
ER_TABLE_HAS_NO_FT, 57	ER_TEXTFILE_NOT_READABLE, 9
ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD, 199	ER_TF_FORBIDDEN_JOIN_TYPE, 104
ER_TABLE_INCOMPATIBLE_YEAR_FIELD, 199	ER_TF_MUST_HAVE_ALIAS, 103
ER_TABLE_IN_FK_CHECK, 53	ER_THE_USER_ABIDES, 177
ER_TABLE_IN_SHARED_TABLESPACE, 158	ER_THREAD_HANDLING_OOM, 172
ER_TABLE_IN_SYSTEM_TABLESPACE, 61	ER_THREAD_POOL_ALGORITHM_INVALID, 301
ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN, 146	ER_THREAD_POOL_BUFFER_TOO_SMALL, 302
ER_TABLE_MUST_HAVE_COLUMNS, 11	ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PRIVILEGES, 625
ER_TABLE_NAME, 45	ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA, 301
ER_TABLE_NAME_CAUSES_TOO_LONG_PATH, 131	ER_THREAD_POOL_CONNECTION_REPORT, 639
ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED, 575	ER_THREAD_POOL_CON_HANDLER_INIT_FAILED, 301
ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK, 575	ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID, 615
ER_TABLE_NEEDS_DUMP_UPGRADE, 299	ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT, 302
ER_TABLE_NEEDS_REBUILD, 51	ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER, 302
ER_TABLE_NEEDS_UPGRADE, 35	ER_THREAD_POOL_FAILED_TO_CREATE_POOL, 302
ER_TABLE_NOT_EMPTY, 158	ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH, 302
ER_TABLE_NOT_LOCKED, 10	ER_THREAD_POOL_IDLE_CONNECTION_CLOSED, 632
ER_TABLE_NOT_LOCKED_FOR_WRITE, 10	ER_THREAD_POOL_INIT_FAILED, 301
ER_TABLE_NO_PRIMARY_KEY, 158	ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER, 301
ER_TABLE_REFERENCED, 86	ER_THREAD_POOL_INVALID_STALL_LIMIT, 301
ER_TABLE_SCHEMA_MISMATCH, 61	ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED, 302
ER_TABLE_UPGRADE_REQUIRED, 279	ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID, 302
ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT, 135	ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM, 300
ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS, 135	ER_THREAD_POOL_PFS_TABLES_ADD_FAILED, 301
ER_TABLE_WITHOUT_PK, 113	ER_THREAD_POOL_PFS_TABLES_INIT_FAILED, 547
ER_TABLE_WRONG_KEY_DEFINITION, 199	ER_THREAD_POOL_PLUGIN_STARTED, 615
ER_TARGET_TABLESPACE_UNENCRYPTED, 122	ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID, 627
ER_TARGET_TS_UNENCRYPTED, 537	ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS_THREADS, 628
ER_TC_BAD_MAGIC_IN_TC_LOG, 223	ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS, 302
ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER, 223	ER_THREAD_POOL_SIZE_TOO_HIGH, 301
ER_TC_HEURISTIC_RECOVERY_FAILED, 223	
ER_TC_HEURISTIC_RECOVERY_MODE, 223	
ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY, 223	
ER_TC_RECOVERING_AFTER_CRASH_USING, 223	
ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS, 223	
ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVERY, 224	
ER_TEMPORARY_NAME, 45	
ER_TEMP_FILE_WRITE_FAILURE, 67	

---

---

ER_THREAD_POOL_SIZE_TOO_LOW, 301	ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84, 112
ER_THREAD_POOL_SYSVAR_CHANGE, 627	ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED, 112
ER_THREAD_PRIORITY_IGNORED, 277	ER_TRANSPORTS_WHAT_TRANSPORTS, 175
ER_TLS_CONFIGURATION_REUSED, 584	ER_TRANS_CACHE_FULL, 17
ER_TLS_CONFIGURED_FOR_CHANNEL, 584	ER_TREE_CORRUPT_2_CONSECUTIVE_REDS, 253
ER_TMPDIR_PATH_TOO_LONG, 590	ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT, 254
ER_TMP_SESSION_FOR_VAR, 625	ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT, 253
ER_TOO_BIG_DISPLAYWIDTH, 33	ER_TREE_CORRUPT_RIGHT_IS_LEFT, 254
ER_TOO_BIG_ENUM, 87	ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK, 253
ER_TOO_BIG_FIELDLENGTH, 8	ER_TRG_ALREADY_EXISTS, 29
ER_TOO_BIG_FOR_UNCOMPRESS, 22	ER_TRG_CANT_CHANGE_ROW, 29
ER_TOO_BIG_PRECISION, 33	ER_TRG_CANT_OPEN_TABLE, 43
ER_TOO_BIG_ROW_SIZE, 11	ER_TRG_CANT_PARSE, 183
ER_TOO_BIG_SCALE, 33	ER_TRG_CORRUPTED_FILE, 43
ER_TOO_BIG_SELECT, 10	ER_TRG_CREATION_CTX_NOT_SET, 279
ER_TOO_BIG_SET, 10	ER_TRG_DOES_NOT_EXIST, 29
ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT, 36	ER_TRG_INVALID_CREATION_CTX, 43
ER_TOO_LONG_BODY, 33	ER_TRG_IN_WRONG_SCHEMA, 33
ER_TOO_LONG_FIELD_COMMENT, 45	ER_TRG_NO_CLIENT_CHARSET, 169
ER_TOO_LONG_IDENT, 7	ER_TRG_NO_CREATION_CTX, 43
ER_TOO_LONG_INDEX_COMMENT, 50	ER_TRG_NO_DEFINER, 35
ER_TOO_LONG_KEY, 8	ER_TRG_NO_SUCH_ROW_IN_TRG, 29
ER_TOO_LONG_ROUTINE_COMMENT, 88	ER_TRG_ON_VIEW_OR_TEMP_TABLE, 29
ER_TOO_LONG_SET_ENUM_VALUE, 88	ER_TRG_WITHOUT_DEFINER, 169
ER_TOO_LONG_STRING, 14	ER_TRG_WRONG_ORDER, 553
ER_TOO_LONG_TABLESPACE_COMMENT, 97	ER_TREHEAD_POOL_LOW_LEVEL_INIT_FAILED, 302
ER_TOO_LONG_TABLE_COMMENT, 45	ER_TRIGGER_INVALID_VALUE, 163
ER_TOO_LONG_TABLE_PARTITION_COMMENT, 59	ER_TRUNCATED_WRONG_VALUE, 24
ER_TOO_MANY_CONCURRENT_CLONES, 100	ER_TRUNCATED_WRONG_VALUE_FOR_FIELD, 29
ER_TOO_MANY_CONCURRENT_TRXS, 45	ER_TRUNCATE_ILLEGAL_FK, 50
ER_TOO_MANY_FIELDS, 11	ER_TRX_GTID_COLLECT_REJECT, 187
ER_TOO_MANY_KEYS, 8	ER_TRX_WRITE_SET_OOM, 188
ER_TOO_MANY_KEY_PARTS, 8	ER_TURNING_LOGGING_OFF_FOR_THE_DURATION, 272
ER_TOO_MANY_PARTITIONS_ERROR, 37	ER_TURNING_ON_PARTIAL_REVOKES, 557
ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR, 47	ER_TX_EXTRACTION_ALGORITHM_FOR_BINLOG_TX_DEPED, 283
ER_TOO_MANY_ROWS, 15	ER_TZ_CANT_BUILD_MKTIME_MAP, 202
ER_TOO_MANY_STORAGE_ENGINES, 188	ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE, 201
ER_TOO_MANY_TABLES, 11	ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID, 201
ER_TOO_MANY_USER_CONNECTIONS, 18	ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE, 201
ER_TOO_MANY_VALUES_ERROR, 47	ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE, 201
ER_TOO_MANY_WINDOWS, 153	
ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT, 157	
ER_TRACK_VARIABLES_BOGUS, 178	
ER_TRANSACTION_ROLLBACK_DURING_COMMIT, 78	
ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84, 112	
ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED, 112	

---

---

ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE, 202	ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN, 105
ER_TZ_OOM_INITIALIZING_TIME_ZONES, 200	ER_UNDO_RECORD_TOO_BIG, 52
ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE, 201	ER_UNEXPECTED_GEOMETRY_TYPE, 88
ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION, 202	ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF, 38
ER_TZ_OOM_WHILE_LOADING_TIME_ZONE, 202	ER_UNIT_NOT_FOUND, 130
ER_TZ_OOM_WHILE_SETTING_TIME_ZONE, 203	ER_UNKNOWN_ALTER_ALGORITHM, 60
ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE, 201	ER_UNKNOWN_ALTER_LOCK, 60
ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE, 202	ER_UNKNOWN_AUTHID, 89
ER_TZ_TRANSITION_TABLE_LOAD_ERROR, 202	ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE, 285
ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS, 202	ER_UNKNOWN_CHARACTER_SET, 11
ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEEDS_SPACE, 202	ER_UNKNOWN_COLLATION, 23
ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR, 202	ER_UNKNOWN_COM_ERROR, 6
ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE, 201	ER_UNKNOWN_ERROR, 10
ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE, 201	ER_UNKNOWN_ERROR_DETECTED_IN_SE, 291
ER_UDF_ALREADY_EXISTS, 536	ER_UNKNOWN_ERROR_NUMBER, 185
ER_UDF_CANT_ALLOC_FOR_FUNCTION, 185	ER_UNKNOWN_EXPLAIN_FORMAT, 59
ER_UDF_CANT_ALLOC_FOR_STRUCTURES, 185	ER_UNKNOWN_KEY_CACHE, 24
ER_UDF_CANT_OPEN_FUNCTION_TABLE, 186	ER_UNKNOWN_LOCALE, 46
ER_UDF_DEREGISTRATION, 637	ER_UNKNOWN_NETWORK_NAMESPACE, 561
ER_UDF_DROP_DYNAMICALY_REGISTERED, 99	ER_UNKNOWN_PARTITION, 54
ER_UDF_ERROR, 86	ER_UNKNOWN_PROCEDURE, 10
ER_UDF_EXEC_FAILURE, 637	ER_UNKNOWN_STMT_HANDLER, 21
ER_UDF_EXEC_FAILURE_REASON, 637	ER_UNKNOWN_STORAGE_ENGINE, 24
ER_UDF_EXISTS, 12	ER_UNKNOWN_SYSTEM_VARIABLE, 16
ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE, 186	ER_UNKNOWN_TABLE, 11
ER_UDF_NO_PATHS, 12	ER_UNKNOWN_TABLESPACE_TYPE, 543
ER_UDF_REGISTER_ERROR, 590	ER_UNKNOWN_TABLE_IN_UPGRADE, 568
ER_UDF_REGISTER_SERVICE_ERROR, 590	ER_UNKNOWN_TARGET_BINLOG, 30
ER_UDF_REGISTRATION, 637	ER_UNKNOWN_TIME_ZONE, 25
ER_UDF_UNREGISTER_ERROR, 590	ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE, 170
ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT_AS, 123	ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE, 537
ER_UNABLE_TO_BUILD_HISTOGRAM, 99	ER_UNRESOLVED_HINT_NAME, 80
ER_UNABLE_TO_COLLECT_LOG_STATUS, 109	ER_UNRESOLVED_TABLE_LOCK, 93
ER_UNABLE_TO_DROP_COLUMN_STATISTICS, 99	ER_UNSUPPORTED_LOG_ENGINE, 42
ER_UNABLE_TO_RESOLVE_HOSTNAME, 168	ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATOR, 115
ER_UNABLE_TO_RESOLVE_IP, 168	ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN, 79
ER_UNABLE_TO_SET_OPTION, 110	ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE, 85
ER_UNABLE_TO_STORE_COLUMN_STATISTICS, 99	ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN, 79
ER_UNABLE_TO_STORE_STATISTICS, 91	ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN, 85
ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS, 99	ER_UNSUPPORTED_DATE, 174
	ER_UNSUPPORTED_ENGINE, 53
	ER_UNSUPPORTED_EXTENSION, 11
	ER_UNSUPPORTED_INDEX_ALGORITHM, 87
	ER_UNSUPPORTED_PS, 25
	ER_UNSUPPORTED_SQL_MODE, 130

---

---

ER_UNSUPPORTED_USE_OF_GRANT_AS, 123	ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY,
ER_UNSUPPORT_COMPRESSED_TEMPORARY_TABLE, 318	ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX,
87	318
ER_UNTIL_COND_IGNORED, 24	ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE,
ER_UPDATE_GTID_PURGED_WITH_GR, 131	318
ER_UPDATE_INFO, 12	ER_VALIDATE_PWD_LENGTH_CHANGED, 318
ER_UPDATE_LOG_DEPRECATED_IGNORED, 26	ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED,
ER_UPDATE_LOG_DEPRECATED_TRANSLATED,	388
26	ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED,
ER_UPDATE_TABLE_USED, 9	388
ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE, 15	ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED,
ER_UPDATING_DD_TABLE, 88	388
ER_UPGRADE_NONEXISTENT_SCHEMA, 591	ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED,
ER_UPGRADE_PARSE_ERROR, 542	388
ER_UPGRADE_WITH_PARTITIONED_TABLES_REJECTED,	ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION,
569	389
ER_USAGE_DEPRECATION_COUNTER, 641	ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIF,
ER_USERNAME, 35	389
ER_USERNAME_TRUNCATED, 584	ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED,
ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED,	389
136	ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED,
ER_USER_ALREADY_EXISTS, 83	389
ER_USER_COLUMN_OLD_LENGTH, 85	ER_VALUES_IS_NOT_INT_TYPE_ERROR, 50
ER_USER_DOES_NOT_EXIST, 83	ER_VALUE_OUT_OF_RANGE, 152
ER_USER_LIMIT_REACHED, 19	ER_VARIABLE_IS_NOT_STRUCT, 23
ER_USER_LOCK_DEADLOCK, 74	ER_VARIABLE_IS_READONLY, 44
ER_USER_LOCK_OVERLONG_NAME, 162	ER_VARIABLE_NOT_PERSISTED, 91
ER_USER_LOCK_WRONG_NAME, 73	ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER,
ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INVALID,	57
198	ER_VARIABLE_NOT_SETTABLE_IN_SP, 63
ER_USER_REFERENCED_AS_DEFINER, 142	ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION,
ER_USER_REGISTRATION_FAILED, 150	57
ER_USER_REQUIRES_ROOT, 175	ER_VAR_CANT_BE_READ, 20
ER_USER_WHAT_USER, 175	ER_VIEW_ALREADY_EXISTS, 98
ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTION,	ER_VERBOSE_HINT, 178
144	ER_VERBOSE_REQUIRES_HELP, 171
ER_UUID_INVALID, 170	ER_VIEW_CHECKSUM, 30
ER_UUID_IS, 170	ER_VIEW_CHECK_FAILED, 29
ER_UUID_SALT, 170	ER_VIEW_CREATION_CTX_NOT_SET, 279
ER_UUID_SCRUB, 170	ER_VIEW_DELETE_MERGE_VIEW, 31
ER_VALGRIND_COUNT_LEAKS, 185	ER_VIEW_FRM_NO_USER, 34
ER_VALGRIND_DO_QUICK_LEAK_CHECK, 185	ER_VIEW_INVALID, 29
ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGED,	ER_VIEW_INVALID_CREATION_CTX, 43
162	ER_VIEW_MULTIUPDATE, 30
ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED,	ER_VIEW_NONUPD_CHECK, 29
389	ER_VIEW_NO_CREATION_CTX, 43
ER_VALIDATE_PWD_COULD_BE_NULL, 388	ER_VIEW_NO_EXPLAIN, 28
ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED,	ER_VIEW_NO_INSERT_FIELD_LIST, 31
318	ER_VIEW_OTHER_USER, 34
ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED,	ER_VIEW_PREVENT_UPDATE, 34
317	ER_VIEW_RECURSIVE, 35
ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED,	ER_VIEW_SELECT_CLAUSE, 28
388	ER_VIEW_SELECT_TMPTABLE, 28
ER_VALIDATE_PWD_DICT_FILE_TOO_BIG, 318	

---

---

ER_VIEW_SELECT_VARIABLE, 28	ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES, 154
ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION, 164	ER_WARN_CANT_DROP_DEFAULT_KEYCACHE, 33
ER_VIEW_UNPARSABLE, 200	ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_KEY, 138
ER_VIEW_WRONG_LIST, 28	ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFESTATION, 634
ER_VTOKEN_PLUGIN_TOKEN_MISMATCH, 81	ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFESTATION, 596
ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND, 81	ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEYS, 627
ER_WAITING_FOR_NO_CONNECTIONS, 641	ER_WARN_CONFLICTING_HINT, 80
ER_WAITING_FOR_NO_THDS, 641	ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POSITION, 151
ER_WAITPID_FAILED, 297	ER_WARN_DATA_OUT_OF_RANGE, 22
ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES, 550	ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX, 113
ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID, 549	ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX, 113
ER_WARNING_NOT_COMPLETE_ROLLBACK, 17	ER_WARN_DA_PRIVILEGE_NOT_REGISTERED, 113
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATED_TEMP_TABLE, 55	ER_WARN_DEPRECATED_CHARSET_OPTION, 612
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPED_TEMP_TABLE, 55	ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION, 612
ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID, 101	ER_WARN_DEPRECATED_COLLATION, 152
ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_VOID, 549	ER_WARN_DEPRECATED_COLLATION_OPTION, 612
ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS, 147	ER_WARN_DEPRECATED_DATETIME_DELIMITER, 154
ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS_LOG, 603	ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT, 125
ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATION_SIZE, 147	ER_WARN_DEPRECATED_FLOAT_DIGITS, 125
ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATION_SIZE_DEPRECATED, 603	ER_WARN_DEPRECATED_FLOAT_UNSIGNED, 125
ER_WARN_ALLOWED_PACKET_OVERFLOWED, 25	ER_WARN_DEPRECATED_FOUND_ROWS, 137
ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAME_SPACE, 146	ER_WARN_DEPRECATED_IDENT, 157
ER_WARN_AUDIT_LOG_DISABLED, 612	ER_WARN_DEPRECATED_INNER_INT, 137
ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_OR_ISO_TIMESTAMP, 148	ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH, 125
ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_OR_ISO_TIMESTAMP_DEPRECATED, 605	ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON, 137
ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_KEYS, 572	ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX, 116
ER_WARN_BAD_MAX_EXECUTION_TIME, 80	ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER, 116
ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED, 101	ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER, 116
ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_IMAGES, 101	ER_WARN_DEPRECATED_SQLMODE, 77
ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED, 101	ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS, 137
ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALLOCATED, 635	ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER, 154
ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES, 613	ER_WARN_DEPRECATED_SYNTAX, 24
	ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT, 49

---

ER_WARN_DEPRECATED_SYNTAX_WITH_VER, 40	ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND, 596
ER_WARN_DEPRECATED_SYSVAR_UPDATE, 77	ER_WARN_NO_SERVERID_SPECIFIED, 278
ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL, 601	ER_WARN_NO_SPACE_VERSION_COMMENT, 162
ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL, 147	ER_WARN_NULL_TO_NOTNULL, 22
ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS, 162	ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS, 70
ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS, 634	ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS, 70
ER_WARN_DEPRECATED_USER_SET_EXPR, 116	ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE, 81
ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION, 543	ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO, 70
ER_WARN_DEPRECATED_UTF8MB3_COLLATION, 116	ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR, 80
ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION, 543	ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT, 557
ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION, 543	ER_WARN_PROPERTY_STRING_PARSE_FAILED, 552
ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS, 137	ER_WARN_PURGE_LOG_IN_USE, 65
ER_WARN_DEPRECATED_WITH_NOTE, 162	ER_WARN_PURGE_LOG_IS_ACTIVE, 65
ER_WARN_DEPRECATED_YEAR_UNSIGNED, 136	ER_WARN_QC_RESIZE, 24
ER_WARN_DEPRECATED_ZEROFILL, 126	ER_WARN_REGEX_USING_DEFAULT, 152
ER_WARN_ENGINE_TRANSACTION_ROLLBACK, 44	ER_WARN_REMOVED_SQL_MODE, 544
ER_WARN_FIELD_RESOLVED, 23	ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS 602
ER_WARN_FUNC_INDEX_NOT_APPLICABLE, 131	ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_ON 609
ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET, 603	ER_WARN_RESERVED_SRID_RANGE, 109
ER_WARN_GTID_THRESHOLD_BREACH, 594	ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MA 572
ER_WARN_HOSTNAME_WONT_WORK, 24	ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SO 572
ER_WARN_HYPERGRAPH_EXPERIMENTAL, 142	ER_WARN_SCHEDULED_TASK_RUN_FAILED, 639
ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS, 557	ER_WARN_SF_UDF_NAME_COLLISION, 153
ER_WARN_INDEX_NOT_APPLICABLE, 54	ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED 148
ER_WARN_INVALID_DB_RESTRICTIONS, 557	ER_WARN_SRS_ID_ALREADY_EXISTS, 108
ER_WARN_INVALID_HINT, 98	ER_WARN_SRS_NOT_FOUND, 89
ER_WARN_INVALID_TIMESTAMP, 25	ER_WARN_SRS_NOT_FOUND_AXIS_ORDER, 92
ER_WARN_I_S_SKIPPED_TABLE, 49	ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR, 583
ER_WARN_LEGACY_SYNTAX_CONVERTED, 69	ER_WARN_TOO_FEW_RECORDS, 22
ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_KEY, 582	ER_WARN_TOO_MANY_RECORDS, 22
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPTED, 570	ER_WARN_TRG_ALREADY_EXISTS, 154
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST, 570	ER_WARN_TRIGGER_DOESNT_HAVE_CREATED, 69
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_PERMISSION, 571	ER_WARN_UNKNOWN_KEYRING_AWS_REGION, 570
ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_ALLOWED, 609	ER_WARN_UNKNOWN_QB_NAME, 80
ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING, 613	ER_WARN_UNLOAD_THE_NOT_PERSISTED, 90
	ER_WARN_UNLOAD_THE_NOT_PERSISTED_HINT, 88
	ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME, 80
	ER_WARN_USING_OTHER_HANDLER, 22



---

ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED, 141	ER_WRONG_COUNT_OF_ELEMENTS, 254
ER_WARN_VIEW_MERGE, 28	ER_WRONG_DATETIME_SPEC, 174
ER_WARN_VIEW_WITHOUT_KEY, 29	ER_WRONG_DB_NAME, 10
ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG, 570	ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR, 36
ER_WARN_WRONG_COMPRESSION_LEVEL_LOG, 570	ER_WRONG_FIELD_SPEC, 7
ER_WASTEFUL_NET_BUFFER_SIZE, 171	ER_WRONG_FIELD_TERMINATORS, 9
ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS, 562	ER_WRONG_FIELD_WITH_GROUP, 7
ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH, 94	ER_WRONG_FIELD_WITH_GROUP_V2, 77
ER_WINDOW_DUPLICATE_NAME, 95	ER_WRONG_FILE_NAME, 80
ER_WINDOW_EXPLAIN_JSON, 96	ER_WRONG_FK_DEF, 21
ER_WINDOW_FRAME_END_ILLEGAL, 94	ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN, 79
ER_WINDOW_FRAME_ILLEGAL, 95	ER_WRONG_GROUP_FIELD, 7
ER_WINDOW_FRAME_START_ILLEGAL, 94	ER_WRONG_JSON_TABLE_VALUE, 103
ER_WINDOW_FUNCTION_IGNORES_FRAME, 96	ER_WRONG_KEY_COLUMN, 15
ER_WINDOW_ILLEGAL_ORDER_BY, 95	ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX, 114
ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE, 95	ER_WRONG_LOCK_OF_SYSTEM_TABLE, 33
ER_WINDOW_INVALID_WINDOW_FUNC_USE, 95	ER_WRONG_MRG_TABLE, 15
ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW, 96	ER_WRONG_MVI_VALUE, 130
ER_WINDOW_NO_CHILD_PARTITIONING, 94	ER_WRONG_NAME_FOR_CATALOG, 24
ER_WINDOW_NO_GROUP_ORDER, 96	ER_WRONG_NAME_FOR_INDEX, 24
ER_WINDOW_NO_GROUP_ORDER_UNUSED, 96	ER_WRONG_NATIVE_TABLE_STRUCTURE, 49
ER_WINDOW_NO_INHERIT_FRAME, 94	ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT, 19
ER_WINDOW_NO_REDEFINE_ORDER_BY, 94	ER_WRONG_OBJECT, 28
ER_WINDOW_NO_SUCH_WINDOW, 94	ER_WRONG_OUTER_JOIN, 11
ER_WINDOW_RANGE_BOUND_NOT_CONSTANT, 95	ER_WRONG_OUTER_JOIN_UNUSED, 11
ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE, 95	ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT, 42
ER_WINDOW_RANGE_FRAME_ORDER_TYPE, 95	ER_WRONG_PARAMCOUNT_TO_PROCEDURE, 10
ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE, 95	ER_WRONG_PARAMETERS_TO_NATIVE_FCT, 42
ER_WINDOW_ROWS_INTERVAL_USE, 96	ER_WRONG_PARAMETERS_TO_PROCEDURE, 10
ER_WINDOW_SE_NOT_ACCEPTABLE, 96	ER_WRONG_PARAMETERS_TO_STORED_FCT, 42
ER_WIN_LISTEN_BUT_HOW, 176	ER_WRONG_PARTITION_NAME, 41
ER_WIN_LOAD_LIBRARY_FAILED, 296	ER_WRONG_PERFSHEMA_USAGE, 49
ER_WL9236_NOW_UNUSED, 96	ER_WRONG_SIZE_NUMBER, 39
ER_WRITABLE_CONFIG_REMOVED, 174	ER_WRONG_SPVAR_TYPE_IN_LIMIT, 50
ER_WRITE_ROW_TO_PARTITION_FAILED, 285	ER_WRONG_SRID_FOR_COLUMN, 101
ER_WRITE_SET_EXCEEDS_LIMIT, 87	ER_WRONG_STRING_LENGTH, 36
ER_WRONG_ARGUMENTS, 18	ER_WRONG_SUB_KEY, 9
ER_WRONG_AUTO_KEY, 8	ER_WRONG_SUM_SELECT, 7
ER_WRONG_COLUMN_NAME, 14	ER_WRONG_TABLESPACE_NAME, 80
ER_WRONG_COMPRESSION_ALGORITHM_CLIENT, 132	ER_WRONG_TABLE_NAME, 10
ER_WRONG_COMPRESSION_LEVEL_CLIENT, 132	ER_WRONG_TYPE_COLUMN_VALUE_ERROR, 47
ER_WRONG_COUNT_FOR_KEY, 254	ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD, 295
ER_WRONG_COUNT_FOR_ORIGIN, 254	ER_WRONG_TYPE_FOR_VAR, 20
	ER_WRONG_USAGE, 19
	ER_WRONG_VALUE, 39
	ER_WRONG_VALUE_COUNT, 7
	ER_WRONG_VALUE_COUNT_ON_ROW, 13
	ER_WRONG_VALUE_FOR_TYPE, 32
	ER_WRONG_VALUE_FOR_VAR, 20

---

---

ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART,	ER_XPLUGIN_ERROR_MSG, 319
139	ER_XPLUGIN_ERROR_READING_SOCKET, 327
ER_X509_CANT_CHMOD_KEY, 193	ER_XPLUGIN_ERROR_WRITING_TO_CLIENT, 327
ER_X509_CANT_CREATE_CERT, 194	ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP, 325
ER_X509_CANT_READ_CA_CERT, 194	ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER,
ER_X509_CANT_READ_CA_KEY, 193	325
ER_X509_CANT_WRITE_CERT, 194	ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE,
ER_X509_CANT_WRITE_KEY, 193	328
ER_X509_CIPHERS_MISMATCH, 193	ER_XPLUGIN_FAILED_AT_SSL_CONF, 325
ER_X509_ISSUER_MISMATCH, 193	ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT, 324
ER_X509_NEEDS_RSA_PRIVKEY, 193	ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS,
ER_X509_SUBJECT_MISMATCH, 193	583
ER_XAER_DUPID, 34	ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION,
ER_XAER_INVAL, 31	329
ER_XAER_NOTA, 31	ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN,
ER_XAER_OUTSIDE, 31	326
ER_XAER_RMERR, 31	ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD,
ER_XAER_RMFAIL, 31	329
ER_XA_CANT_CREATE_MDL_BACKUP, 568	ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT,
ER_XA_COMMITTING_XID, 186	330
ER_XA_IGNOREING_XID, 186	ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO,
ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER,	330
186	ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX,
ER_XA_RBDEADLOCK, 44	329
ER_XA_RBROLLBACK, 31	ER_XPLUGIN_FAILED_TO_GET_SYS_VAR, 329
ER_XA_RBTIMEOUT, 44	ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION,
ER_XA_RECOVERY_DONE, 187	326
ER_XA_RECOVER_EXPLANATION, 187	ER_XPLUGIN_FAILED_TO_INTERRUPT_SESSION,
ER_XA_RECOVER_FOUND_TRX_IN_SE, 186	328
ER_XA_RECOVER_FOUND_XA_TRX, 186	ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION,
ER_XA_REPLICATION_FILTERS, 129	330
ER_XA_RETRY, 86	ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES,
ER_XA_ROLLING_BACK_XID, 186	324
ER_XA_STARTING_RECOVERY, 186	ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG,
ER_XA_TEMP_TABLE, 153	331
ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED,	ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT,
326	324
ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED,	ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS,
324	326
ER_XPLUGIN_CAPABILITY_CLIENT_INTERACTIVE_FAILED,	ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG,
331	330
ER_XPLUGIN_CAPABILITY_EXPIRED_PASSWORD,	ER_XPLUGIN_FAILED_TO_STOP_SERVICES, 528
330	ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT,
ER_XPLUGIN_CLIENT_KILL_MSG, 329	330
ER_XPLUGIN_CLIENT_RELEASE_TRIGGERED,	ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX,
328	542
ER_XPLUGIN_CLIENT_SSL_HANDSHAKE_FAILED,	ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX_TO_ROOT,
325	329
ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN,	ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF, 330
326	ER_XPLUGIN_FAILED_TO_USE_SSL_CONF, 319
ER_XPLUGIN_COMPRESSION_ERROR, 570	ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS,
ER_XPLUGIN_DETECTED_HANGING_CLIENTS,	583
324	ER_XPLUGIN_FAIL_TO_GET_RESULT_DATA, 330
ER_XPLUGIN_EMPTY_ADMIN_CMD, 329	ER_XPLUGIN_FORCE_STOP_CLIENT, 323

---

---

ER_XPLUGIN_GET_PEER_ADDRESS_FAILED, 331	ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION, 319
ER_XPLUGIN_INVALID_AUTH_METHOD, 327	ER_XPLUING_NET_STARTUP_FAILED, 325
ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT, 326	ER_YES, 3
ER_XPLUGIN_IPv6_AVAILABLE, 329	ER_ZLIB_Z_BUF_ERROR, 22
ER_XPLUGIN_LISTENER_SETUP_FAILED, 325	ER_ZLIB_Z_DATA_ERROR, 22
ER_XPLUGIN_LISTENER_STATUS_MSG, 328	ER_ZLIB_Z_MEM_ERROR, 22
ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR, 327	WARN_AES_KEY_SIZE, 87
ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED, 323	WARN_COND_ITEM_TRUNCATED, 46
ER_XPLUGIN_MESSAGE_TOO_LONG, 326	WARN_DATA_TRUNCATED, 22
ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING, 327	WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX, 113
ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION, 327	WARN_DISABLED_PIPE_ACCESS_EVERYONE, 68
ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_WRONG_PLUGIN, 319	WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED, 46
ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOCUMENTATION_SECTION, 324	WARN_NO_CONNECTION_METADATA, 44
ER_XPLUGIN_RETRYING_BIND_ON_PORT, 328	WARN_PLUGIN_MASTER_INFO, 44
ER_XPLUGIN_SCHEDULER_STARTED, 327	WARN_ON_BLOCKHOLE_IN_RBR, 66
ER_XPLUGIN_SCHEDULER_STOPPED, 327	WARN_PARTITION_BELOW_LIMIT, 51
ER_XPLUGIN_SERVER_EXITED, 319	WARN_OPTION_IGNORED, 44
ER_XPLUGIN_SERVER_EXITING, 319	WARN_PLUGIN_BUSY, 44
ER_XPLUGIN_SERVER_STARTS_HANDLING_CONNECTIONS, 328	WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB, 121
ER_XPLUGIN_SERVER_STOPPED_HANDLING_CONNECTIONS, 328	WARN_UNSUPPORTED_ACL_TABLES_READ, 143
ER_XPLUGIN_SHUTDOWN_TRIGGERED, 328	WARN_USELESS_SPATIAL_INDEX, 104
ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED, 324	ER_ABORTING error code, 175
ER_XPLUGIN_SSL_HANDSHAKE_WITH_SERVER_FAILED, 325	ER_ABORTING_CONNECTION error code, 14
ER_XPLUGIN_STARTUP_FAILED, 318	ER_ABORTING_USER_CONNECTION error code, 278
ER_XPLUGIN_TASK_SCHEDULING_FAILED, 325	ER_ACCESS_DENIED_CHANGE_USER_ERROR error code, 66
ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION, 326	ER_ACCESS_DENIED_ERROR error code, 6
ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT, 324	ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD error code, 279
ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING_CMD, 325	ER_ACCESS_DENIED_ERROR_WITH_PASSWORD error code, 280
ER_XPLUGIN_UNEXPECTED_MSG_DURING_AUTHENTICATION, 327	ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY error code, 575
ER_XPLUGIN_UNINITIALIZED_MESSAGE, 326	ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED error code, 280
ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED, 329	ER_ACCESS_DENIED_NO_PASSWORD_ERROR error code, 614
ER_XPLUGIN_USER_ACCOUNT_WITH_ALL_PERMISSIONS, 328	ER_ACCESS_DENIED_WITH_EXPIRED_PASSWORD error code, 80
ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX, 319	ER_ACCOUNT_HAS_BEEN_LOCKED error code, 80
ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER, 319	ER_ACCOUNT_WITH_EXPIRED_PASSWORD error code, 614
	ER_ACL_OPERATION_FAILED error code, 87
	ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG error code, 565
	ER_ADDRESSES_FOR_HOSTNAME_HEADER error code, 169
	ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM error code, 169
	ER_ADD_PARTITION_NO_NEW_PARTITION error code, 38

---

---

ER_ADD_PARTITION_SUBPART_ERROR error code, 38	ER_APPLIER_LOG_EVENT_VALIDATION_ERROR error code, 100
ER_ADMIN_WRONG_MRG_TABLE error code, 36	ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUIRE error code, 144
ER_AES_INVALID_IV error code, 67	ER_ATTRIBUTE_IGNORED error code, 103
ER_AES_INVALID_KDF_ITERATIONS error code, 87	ER_AUDIT_API_ABORT error code, 84
ER_AES_INVALID_KDF_NAME error code, 87	ER_AUDIT_CANT_ABORT_COMMAND error code, 276
ER_AES_INVALID_KDF_OPTION_SIZE error code, 87	ER_AUDIT_CANT_ABORT_EVENT error code, 276
ER_AGGREGATE_IN_ORDER_NOT_SELECT error code, 74	ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD error code, 571
ER_AGGREGATE_ORDER_FOR_UNION error code, 71	ER_AUDIT_LOG_CANNOT_READ_PASSWORD error code, 564
ER_AGGREGATE_ORDER_NON_AGG_QUERY error code, 71	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD error code, 564
ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED error code, 134	ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICY error code, 314
ER_ALTER_FILEGROUP_FAILED error code, 39	ER_AUDIT_LOG_CANNOT_STORE_PASSWORD error code, 564
ER_ALTER_INFO error code, 9	ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY error code, 534
ER_ALTER_OPERATION_NOT_SUPPORTED error code, 64	ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING error code, 564
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 64	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE error code, 315
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 64	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION error code, 315
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 64	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPTION error code, 315
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 153	ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED error code, 534
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 64	ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET error code, 534
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 64	ER_AUDIT_LOG_FILE_AUTO_PRUNED error code, 596
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 64	ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSED error code, 564
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 64	ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT error code, 564
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 74	ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING error code, 564
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 64	ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING error code, 564
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 64	ER_AUDIT_LOG_FILE_PRUNE_FAILED error code, 596
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 65	ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_READ error code, 317
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 64	ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE error code, 317
ER_AMBIGUOUS_FIELD_TERM error code, 36	ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ error code, 317
ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDATORY_ROLES error code, 285	ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE error code, 317
ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME error code, 145	ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE error code, 317
ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_ID error code, 147	ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FIELDS error code, 316

---

---

ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE error code, 316	ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED error code, 568
ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY error code, 317	ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST error code, 314
ER_AUDIT_LOG_FILTER_INVALID_COLUMN_COUNT error code, 316	ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED error code, 536
ER_AUDIT_LOG_FILTER_INVALID_COLUMN_DEFINITION error code, 316	ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE error code, 534
ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED error code, 314	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT error code, 569
ER_AUDIT_LOG_FILTER_RESULT_MSG error code, 315	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE error code, 568
ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY error code, 317	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH error code, 569
ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED error code, 569	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH error code, 87
ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER error code, 534	ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHA error code, 535
ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR error code, 314	ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER error code, 534
ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE error code, 131	ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS error code, 315
ER_AUDIT_LOG_INVALID_FILE_CONTENT error code, 564	ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE error code, 315
ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE error code, 639	ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED error code, 315
ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED error code, 533	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED error code, 314
ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST error code, 535	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE error code, 315
ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY error code, 534	ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EV error code, 200
ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR error code, 533	ER_AUDIT_PLUGIN_HAS_INVALID_DATA error code, 200
ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL error code, 316	ER_AUDIT_WARNING error code, 276
ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE error code, 316	ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM error code, 197
ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE error code, 316	ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TAB error code, 197
ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR error code, 316	ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WILL error code, 197
ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY error code, 535	ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME error code, 197
ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID error code, 563	ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE error code, 197
ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED error code, 534	ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAM error code, 585
ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED error code, 314	ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZA error code, 585
ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED error code, 565	ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED error code, 196
ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH error code, 315	ER_AUTHCACHE_PLUGIN_CONFIG error code, 195
	ER_AUTHCACHE_PLUGIN_MISSING error code, 195

---

---

ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_PLUGIN error code, 197	ER_AUTHENTICATION_PLUGIN_OOM error code, 608
ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE error code, 197	ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED error code, 608
ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE error code, 195	ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT error code, 608
ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME error code, 585	ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT error code, 608
ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION error code, 585	ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED error code, 608
ER_AUTHCACHE_ROLE_TABLES_DODGY error code, 195	ER_AUTHENTICATION_POLICY_MISMATCH error code, 149
ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE error code, 198	ER_AUTH_CANT_ACTIVATE_ROLE error code, 193
ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING error code, 197	ER_AUTH_CANT_CREATE_RSA_PAIR error code, 194
ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD error code, 196	ER_AUTH_CANT_SET_DEFAULT_PLUGIN error code, 181
ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD error code, 196	ER_AUTH_CANT_WRITE_PRIVKEY error code, 194
ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN error code, 196	ER_AUTH_CANT_WRITE_PUBKEY error code, 194
ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE error code, 196	ER_AUTH_CERTS_SAVED_TO_DATADIR error code, 194
ER_AUTHCACHE_USER_TABLE_DODGY error code, 196	ER_AUTH_CERT_GENERATION_DISABLED error code, 194
ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY error code, 636	ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLE error code, 557
ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY error code, 609	ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG error code, 603
ER_AUTHENTICATION_OCI_IAM error code, 610	ER_AUTH_KEYS_SAVED_TO_DATADIR error code, 195
ER_AUTHENTICATION_OCI_IMDS error code, 609	ER_AUTH_KEY_GENERATION_DISABLED error code, 195
ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_ERROR error code, 610	ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT error code, 195
ER_AUTHENTICATION_OCI_INVALID_TOKEN error code, 636	ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG error code, 320
ER_AUTHENTICATION_OCI_NONCE error code, 610	ER_AUTH_RSA_CANT_FIND error code, 192
ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND error code, 610	ER_AUTH_RSA_CANT_PARSE error code, 192
ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS error code, 610	ER_AUTH_RSA_CANT_READ error code, 192
ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS_ERROR error code, 637	ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION error code, 195
ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED error code, 609	ER_AUTH_RSA_FILES_NOT_FOUND error code, 193
ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR error code, 609	ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION error code, 194
ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH error code, 636	ER_AUTH_TOKEN_USING_EXISTING_CERTS error code, 194
ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED error code, 636	ER_AUTOINC_READ_FAILED error code, 35
ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT error code, 608	ER_AUTO_CONVERT error code, 21
ER_AUTHENTICATION_PLUGIN_LOG error code, 609	ER_AUTO_INCREMENT_CONFLICT error code, 66
	ER_AUTO_OPTIONS_FAILED error code, 182
	ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF error code, 57
	ER_BACK_IN_TIME error code, 174
	ER_BAD_DB_ERROR error code, 6
	ER_BAD_FIELD_ERROR error code, 7
	ER_BAD_FT_COLUMN error code, 24
	ER_BAD_HOST_ERROR error code, 6
	ER_BAD_LOG_STATEMENT error code, 42

---

---

ER_BAD_NULL_ERROR error code, 6	ER_BINLOG_CANT_OPEN_TMP_INDEX error code, 269
ER_BAD_NULL_ERROR_NOT_IGNORED error code, 104	ER_BINLOG_CANT_RESIZE_CACHE error code, 265
ER_BAD_REPLICA error code, 17	ER_BINLOG_CANT_SET_TMP_INDEX_NAME error code, 268
ER_BAD_REPLICA_AUTO_POSITION error code, 57	ER_BINLOG_CANT_TRIM_CRASHED_BINLOG error code, 272
ER_BAD_REPLICA_UNTIL_COND error code, 23	ER_BINLOG_CANT_USE_FOR_LOGGING error code, 267
ER_BAD_SLAVE error code, 17	ER_BINLOG_CRASHED_BINLOG_TRIMMED error code, 272
ER_BAD_SLAVE_AUTO_POSITION error code, 57	ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED error code, 622
ER_BAD_SLAVE_UNTIL_COND error code, 23	ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS error code, 622
ER_BAD_TABLE_ERROR error code, 6	ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED_SE error code, 622
ER_BAD_TIMESTAMP_FORMAT error code, 157	ER_BINLOG_CRASH_RECOVERY_FAILED error code, 272
ER_BASE64_DECODE_ERROR error code, 42	ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG error code, 622
ER_BASEDIR_SET_TO error code, 282	ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED error code, 623
ER_BEFORE_DML_VALIDATION_ERROR error code, 78	ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED error code, 622
ER_BEG_INITFILE error code, 177	ER_BINLOG_CREATE_ROUTINE_NEED_SUPER error code, 32
ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD error code, 640	ER_BINLOG_END error code, 175
ER_BEYOND_SERVER_UPGRADE_THRESHOLD error code, 640	ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX error code, 269
ER_BINLOG_ATTACHING_THREAD_MEMORY_FINALLY error code, 265	ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG error code, 267
ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX error code, 54	ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG error code, 267
ER_BINLOG_CACHE_SIZE_TOO_LARGE error code, 277	ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA error code, 267
ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX error code, 268	ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO error code, 267
ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG error code, 272	ER_BINLOG_EVENTS_READ_FROM_RELAY_LOG_INFO error code, 267
ER_BINLOG_CANT_CLOSE_TMP_INDEX error code, 269	ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED error code, 283
ER_BINLOG_CANT_COPY_INDEX_TO_TMP error code, 269	ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER error code, 298
ER_BINLOG_CANT_CREATE_CACHE_FOR_LOG error code, 266	ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOGETHER error code, 305
ER_BINLOG_CANT_DELETE_FILE error code, 268	ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILD error code, 268
ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG error code, 271	ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILD error code, 268
ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH error code, 271	ER_BINLOG_FAILED_TO_DELETE_LOG_FILE error code, 271
ER_BINLOG_CANT_FIND_LOG_IN_INDEX error code, 271	ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILD error code, 268
ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME error code, 267	
ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG error code, 268	
ER_BINLOG_CANT_MOVE_TMP_TO_INDEX error code, 269	
ER_BINLOG_CANT_OPEN_CRASHED_BINLOG error code, 271	
ER_BINLOG_CANT_OPEN_FOR_LOGGING error code, 266	
ER_BINLOG_CANT_OPEN_LOG error code, 266	

---

---

ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE error code, 270	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOGS error code, 119
ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE error code, 269	ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE error code, 48
ER_BINLOG_FAILED_TO_READ_REGISTER_FILE error code, 270	ER_BINLOG_NEEDS_SERVERID error code, 180
ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE error code, 270	ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_HEAP error code, 255
ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_FLUSHING error code, 268	ER_BINLOG_PURGE_EMFILE error code, 42
ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK error code, 272	ER_BINLOG_PURGE_FATAL_ERR error code, 30
ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK error code, 272	ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX error code, 269
ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME error code, 270	ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE error code, 269
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE error code, 266	ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE error code, 270
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN error code, 267	ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE error code, 269
ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES error code, 255	ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE error code, 270
ER_BINLOG_FATAL_ERROR error code, 43	ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG error code, 270
ER_BINLOG_FILE_BEING_READ_NOT_PURGED error code, 265	ER_BINLOG_PURGE_PROHIBITED error code, 30
ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED error code, 266	ER_BINLOG_RECOVERING_AFTER_CRASH_USING error code, 271
ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW error code, 266	ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE error code, 47
ER_BINLOG_FILE_NAME_TOO_LONG error code, 266	ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE error code, 48
ER_BINLOG_FILE_OPEN_FAILED error code, 283	ER_BINLOG_ROW_INJECTION_AND_STMT_MODE error code, 48
ER_BINLOG_IO_ERROR_READING_HEADER error code, 266	ER_BINLOG_ROW_LOGGING_FAILED error code, 40
ER_BINLOG_LOGGING_IMPOSSIBLE error code, 43	ER_BINLOG_ROW_MODE_AND_STMT_ENGINE error code, 47
ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS error code, 271	ER_BINLOG_ROW_VALUE_OPTION_IGNORED error code, 526
ER_BINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES error code, 271	ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER_I error code, 527
ER_BINLOG_LOGGING_NOT_POSSIBLE error code, 297	ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX error code, 54
ER_BINLOG_LOGICAL_CORRUPTION error code, 65	ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE error code, 277
ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG error code, 299	ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES error code, 63
ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION error code, 119	ER_BINLOG_STMT_MODE_AND_ROW_ENGINE error code, 48
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP error code, 120	ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY error code, 561
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP error code, 120	ER_BINLOG_UNCLOSED_KEYS_ACL_TABLE_READ_IN_DML_DDL error code, 143
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE error code, 119	ER_BINLOG_UNSAFE_AND_STMT_ENGINE error code, 47
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT error code, 120	ER_BINLOG_UNSAFE_AUTOINC_COLUMNS error code, 48

---



---

ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST error code, 53	ER_BOOST_GEOMETRY_CENTROID_EXCEPTION error code, 72
ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT error code, 52	ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION error code, 72
ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT error code, 52	ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION error code, 80
ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC error code, 53	ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION error code, 72
ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBQUERY error code, 563	ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION error code, 72
ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN error code, 69	ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION error code, 72
ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT error code, 52	ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION error code, 72
ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE error code, 52	ER_BOOTSTRAP_CANT_THREAD error code, 162
ER_BINLOG_UNSAFE_INSERT_TWO_KEYS error code, 53	ER_BUFPOOL_RESIZE_INPROGRESS error code, 84
ER_BINLOG_UNSAFE_LIMIT error code, 48	ER_BUILD_ID error code, 625
ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT error code, 278	ER_BULK_EXECUTOR_ERROR error code, 158
ER_BINLOG_UNSAFE_MIXED_STATEMENT error code, 50	ER_BULK_EXECUTOR_INFO error code, 629
ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF error code, 50	ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVER_BUFFER error code, 159
ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS error code, 48	ER_BULK_LOADER_COMPONENT_ERROR error code, 159
ER_BINLOG_UNSAFE_NOWAIT error code, 93	ER_BULK_LOADER_INFO error code, 629
ER_BINLOG_UNSAFE_REPLACE_SELECT error code, 52	ER_BULK_LOAD_DATA_FAILED error code, 159
ER_BINLOG_UNSAFE_ROUTINE error code, 32	ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED error code, 160
ER_BINLOG_UNSAFE_SKIP_LOCKED error code, 93	ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED_LOG error code, 630
ER_BINLOG_UNSAFE_STATEMENT error code, 43	ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE error code, 160
ER_BINLOG_UNSAFE_SYSTEM_FUNCTION error code, 48	ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE_LOG error code, 631
ER_BINLOG_UNSAFE_SYSTEM_TABLE error code, 48	ER_BULK_PARSER_MISSING_ENCLOSED_BY error code, 159
ER_BINLOG_UNSAFE_SYSTEM_VARIABLE error code, 48	ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG error code, 630
ER_BINLOG_UNSAFE_UDF error code, 48	ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED error code, 159
ER_BINLOG_UNSAFE_UPDATE_IGNORE error code, 52	ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED_LOG error code, 630
ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT error code, 53	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_NAME error code, 160
ER_BINLOG_UNSAFE_XA error code, 86	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_NAME_LOG error code, 631
ER_BINLOG_USE_V1_ROW_EVENTS_IGNORED error code, 527	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_BRACKET error code, 160
ER_BINLOG_WARNING_SUPPRESSED error code, 272	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_BRACKET_LOG error code, 630
ER_BLOBS_AND_NO_TERMINATED error code, 9	
ER_BLOB_CANT_HAVE_DEFAULT error code, 10	
ER_BLOB_FIELD_IN_PART_FUNC_ERROR error code, 37	
ER_BLOB_KEY_WITHOUT_LENGTH error code, 15	
ER_BLOB_USED_AS_KEY error code, 8	

---

---

ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE error code, 160	ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES error code, 613
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE error code, 630	ER_CANNOT_LOAD_FROM_TABLE_V2 error code, 53
ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT error code, 160	ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES error code, 91
ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT_LOG error code, 630	ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID error code, 77
ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR error code, 160	ER_CANNOT_PERSIST_SENSITIVE_VARIABLES error code, 154
ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG error code, 630	ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK error code, 153
ER_BULK_READER_COMMUNICATION_ERROR error code, 159	ER_CANNOT_SET_DATABASE_ENCRYPTION error code, 122
ER_BULK_READER_COMMUNICATION_ERROR_LOG error code, 630	ER_CANNOT_SET_LOG_ERROR_SERVICES error code, 282
ER_BULK_READER_INFO error code, 629	ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_HEADER error code, 553
ER_BULK_READER_LIBCURL_ERROR error code, 159	ER_CANNOT_SET_TABLESPACE_ENCRYPTION error code, 122
ER_BULK_READER_LIBCURL_ERROR_LOG error code, 629	ER_CANNOT_SET_TABLE_ENCRYPTION error code, 122
ER_BULK_READER_LIBCURL_INIT_FAILED error code, 158	ER_CANNOT_USER error code, 31
ER_BULK_READER_LIBCURL_INIT_FAILED_LOG error code, 629	ER_CANNOT_USER_REFERENCED_AS_DEFINER error code, 142
ER_BULK_READER_SERVER_ERROR error code, 159	ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE error code, 145
ER_BULK_READER_SERVER_ERROR_LOG error code, 629	ER_CANNOT_USE_ENCRYPTION_CLAUSE error code, 122
ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_DOES_NOT USE INFORMATION error code, 550	ER_CANT_ACCESS_CAPATH error code, 181
ER_CALL_ME_LOCALHOST error code, 175	ER_CANT_AGGREGATE_2COLLATIONS error code, 22
ER_CANNOT_ADD_FOREIGN error code, 19	ER_CANT_AGGREGATE_3COLLATIONS error code, 22
ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED error code, 86	ER_CANT_AGGREGATE_NCOLLATIONS error code, 23
ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL error code, 84	ER_CANT_ALLOC_TABLE_OBJECT error code, 259
ER_CANNOT_ALTER_SRID_DUE_TO_INDEX error code, 101	ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE error code, 161
ER_CANNOT_CHANGE_TO_ROOT_DIR error code, 282	ER_CANT_CHANGE_TX_CHARACTERISTICS error code, 41
ER_CANNOT_CONVERT_STRING error code, 125	ER_CANT_CHECK_PID_PATH error code, 388
ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT error code, 84	ER_CANT_CHOWN_DATADIR error code, 181
ER_CANNOT_DISCARD_TEMPORARY_TABLE error code, 69	ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTOPOSITION error code, 143
ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX error code, 113	ER_CANT_CREATE_ADMIN_THREAD error code, 549
ER_CANNOT_FIND_KEY_IN_KEYRING error code, 85	ER_CANT_CREATE_CACHE_FOR_DB_OPT error code, 260
ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE_HEADER error code, 553	ER_CANT_CREATE_DB error code, 3
ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER error code, 127	ER_CANT_CREATE_FILE error code, 3
ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE error code, 129	ER_CANT_CREATE_GEOMETRY_OBJECT error code, 32
	ER_CANT_CREATE_HANDLER_FILE error code, 37
	ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE error code, 259

---

---

ER_CANT_CREATE_HANDLE_MGR_THREAD error code, 166	ER_CANT_INIT_SCHEDULER_THREAD error code, 167
ER_CANT_CREATE_INTERRUPT_THREAD error code, 173	ER_CANT_INIT_TC_LOG error code, 167
ER_CANT_CREATE_NAMED_PIPES_THREAD error code, 173	ER_CANT_INIT_TIMER error code, 182
ER_CANT_CREATE_PID_FILE error code, 172	ER_CANT_JOIN_SHUTDOWN_THREAD error code, 181
ER_CANT_CREATE_SCHEDULER_THREAD error code, 167	ER_CANT_LOCK error code, 4
ER_CANT_CREATE_SHM_THREAD error code, 173	ER_CANT_LOCK_LOG_TABLE error code, 40
ER_CANT_CREATE_SHUTDOWN_THREAD error code, 172	ER_CANT_LOCK_TABLE error code, 259
ER_CANT_CREATE_TABLE error code, 3	ER_CANT_LOCK_TABLESPACE error code, 260
ER_CANT_CREATE_TABLE_SHARE_FROM_FRM error code, 259	ER_CANT_MODIFY_SRID_0 error code, 108
ER_CANT_CREATE_TCPIP_THREAD error code, 173	ER_CANT_MODIFY_SRS_USED_BY_COLUMN error code, 109
ER_CANT_CREATE_TEST_FILE error code, 172	ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES error code, 200
ER_CANT_CREATE_THREAD error code, 13	ER_CANT_OPEN_CA error code, 181
ER_CANT_CREATE_USER_WITH_GRANT error code, 32	ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE error code, 262
ER_CANT_CREATE_UUID error code, 170	ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET error code, 260
ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN error code, 217	ER_CANT_OPEN_DIR error code, 262
ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_IS_ON error code, 58	ER_CANT_OPEN_ERROR_LOG error code, 182
ER_CANT_DO_THIS_DURING_AN_TRANSACTION error code, 15	ER_CANT_OPEN_FILE error code, 4
ER_CANT_DROP_FIELD_OR_KEY error code, 9	ER_CANT_OPEN_FRM_FILE error code, 199
ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGONING error code, 79	ER_CANT_OPEN_LIBRARY error code, 12
ER_CANT_EXECUTE_COMMAND_WITH_ASSIGNED_GTID error code, 153	ER_CANT_OPEN_TABLE_MYSQL_PROC error code, 262
ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION error code, 59	ER_CANT_PARSE_STOREED_ROUTINE_BODY error code, 262
ER_CANT_FIND_DL_ENTRY error code, 12	ER_CANT_OPEN_GTID_VIOLATING_TX error code, 572
ER_CANT_FIND_SYSTEM_REC error code, 4	ER_CANT_READ_DIR error code, 4
ER_CANT_FIND_UDF error code, 12	ER_CANT_READ_ERRMSG error code, 178
ER_CANT_GET_STAT error code, 4	ER_CANT_READ_FRM_FILE error code, 200
ER_CANT_HASH_DO_AND_IGNORE_RULES error code, 181	ER_CANT_READ_TABLE_MYSQL_PROC error code, 262
ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT error code, 261	ER_CANT_REMOVE_ALL_FIELDS error code, 9
ER_CANT_INCREASE_MAX_OPEN_FILES error code, 177	ER_CANT_REMOVE_PID_FILE error code, 172
ER_CANT_INITIALIZE_BUILTIN_PLUGINS error code, 180	ER_CANT_RENAME_LOG_TABLE error code, 42
ER_CANT_INITIALIZE_DYNAMIC_PLUGINS error code, 180	ER_CANT_REOPEN_TABLE error code, 13
ER_CANT_INITIALIZE_EARLY_PLUGINS error code, 180	ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION error code, 533
ER_CANT_INITIALIZE_GTID error code, 180	ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_ON error code, 533
ER_CANT_INITIALIZE_UDF error code, 12	ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF error code, 533
ER_CANT_INIT_DBS error code, 178	ER_CANT_RESET_MASTER error code, 85
	ER_CANT_RESET_SOURCE error code, 85
	ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY error code, 162
	ER_CANT_SAVE_GTIDS error code, 181
	ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL error code, 144
	ER_CANT_SET_DATADIR error code, 180

---

---

ER_CANT_SET_DATA_DIR error code, 547	ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING_ error code, 84
ER_CANT_SET_ERROR_LOG_SERVICE error code, 107	ER_CAPACITY_EXCEEDED error code, 84
ER_CANT_SET_ERROR_SUPPRESSION_LIST error code, 111	ER_CAPACITY_EXCEEDED_IN_PARSER error code, 85
ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMANDLINE error code, 539	ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER error code, 84
ER_CANT_SET_GTID_MODE error code, 79	ER_CA_SELF_SIGNED error code, 169
ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_CHANGED error code, 58	ER_CHANGED_MAX_CONNECTIONS error code, 177
ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_CHANGED error code, 58	ER_CHANGED_MAX_OPEN_FILES error code, 177
ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_CHANGED error code, 58	ER_CHANGED_TABLE_OPEN_CACHE error code, 177
ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID error code, 59	ER_CHANGE_MASTER_PASSWORD_LENGTH error code, 73
ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINT error code, 90	ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM error code, 132
ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS_ON error code, 63	ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_L error code, 132
ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS error code, 63	ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT error code, 132
ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE error code, 260	ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID error code, 150
ER_CANT_SET_PATH_FOR error code, 262	ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION error code, 151
ER_CANT_SET_PERSISTED error code, 161	ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POS_WITH error code, 151
ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS error code, 144	ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITH error code, 151
ER_CANT_SET_UP_PERSISTED_VALUES error code, 181	ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORM error code, 150
ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID error code, 81	ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE error code, 151
ER_CANT_START_ERROR_LOG_SERVICE error code, 281	ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE error code, 54
ER_CANT_STAT_DATADIR error code, 181	ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM error code, 147
ER_CANT_STAT_FILE error code, 270	ER_CHANGE_SOURCE_PASSWORD_LENGTH error code, 73
ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT error code, 54	ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM error code, 132
ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG error code, 34	ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_L error code, 132
ER_CANT_UPDATE_WITH_READLOCK error code, 19	ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT error code, 132
ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD error code, 260	ER_CHARACTER_SET_MISMATCH error code, 141
ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE error code, 143	ER_CHECKING_TABLE error code, 259
ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE error code, 79	ER_CHECKREAD error code, 4
ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON error code, 151	ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION error code, 121
ER_CANT_USE_OPTION_HERE error code, 20	ER_CHECK_CONSTRAINT_DUP_NAME error code, 121
ER_CANT_USE_SAME_UUID_AS_GROUP_NAME error code, 145	
ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID error code, 147	

---

---

ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED error code, 120	ER_CLONE_CREATE_HANDLER_FAIL_TRACE error code, 293
ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED error code, 120	ER_CLONE_DDL_IN_PROGRESS error code, 100
ER_CHECK_CONSTRAINT_NOT_FOUND error code, 121	ER_CLONE_DISALLOWED error code, 127
ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENTED error code, 121	ER_CLONE_DISK_SPACE error code, 127
ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN error code, 121	ER_CLONE_DONOR error code, 126
ER_CHECK_CONSTRAINT_ROW_VALUE error code, 121	ER_CLONE_DONOR_TRACE error code, 546
ER_CHECK_CONSTRAINT_VARIABLES error code, 121	ER_CLONE_DONOR_VERSION error code, 126
ER_CHECK_CONSTRAINT_VIOLATED error code, 121	ER_CLONE_ENCRYPTION error code, 127
ER_CHECK_NOT_IMPLEMENTED error code, 15	ER_CLONE_HANDLER_EXISTS error code, 293
ER_CHECK_NO_SUCH_TABLE error code, 15	ER_CLONE_HANDLER_EXIST_TRACE error code, 293
ER_CHECK_TABLE_FUNCTIONS error code, 642	ER_CLONE_INFO_CLIENT error code, 546
ER_CHECK_TABLE_FUNCTIONS_DETAIL error code, 642	ER_CLONE_INFO_SERVER error code, 547
ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET error code, 632	ER_CLONE_IN_PROGRESS error code, 127
ER_CHECK_TABLE_MIN_REC_FLAG_NOT_SET error code, 635	ER_CLONE_LOOPBACK error code, 127
ER_CHECK_TABLE_MIN_REC_FLAG_SET error code, 634	ER_CLONE_NETWORK_PACKET error code, 136
ER_CLIENT_DOES_NOT_SUPPORT error code, 101	ER_CLONE_OS error code, 126
ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECK error code, 156	ER_CLONE_PLATFORM error code, 126
ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRANSACTION error code, 112	ER_CLONE_PLUGIN_MATCH error code, 126
ER_CLIENT_INTERACTION_TIMEOUT error code, 146	ER_CLONE_PLUGIN_NOT_LOADED error code, 293
ER_CLIENT_KEYRING_UDF_KEY_INVALID error code, 133	ER_CLONE_PLUGIN_NOT_LOADED_TRACE error code, 293
ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG error code, 133	ER_CLONE_PROTOCOL error code, 126
ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID error code, 133	ER_CLONE_PROTOCOL_ERROR error code, 546
ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG error code, 133	ER_CLONE_PROTOCOL_TRACE error code, 546
ER_CLIENT_LOCAL_FILES_DISABLED error code, 135	ER_CLONE_REMOTE_ERROR error code, 546
ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_PROMOTED error code, 133	ER_CLONE_SERVER_TRACE error code, 547
ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT error code, 133	ER_CLONE_SHUTDOWN_TRACE error code, 566
ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST error code, 133	ER_CLONE_SYS_CONFIG error code, 126
ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLICAND error code, 133	ER_CLONE_TOO_MANY_CONCURRENT_CLONES error code, 100
ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT error code, 135	ER_CMD_NEED_SUPER error code, 99
ER_CLONE_CHARSET error code, 126	ER_COALESCE_ONLY_ON_HASH_PARTITION error code, 38
ER_CLONE_CLIENT_TRACE error code, 547	ER_COALESCE_PARTITION_NO_PARTITION error code, 38
ER_CLONE_CONFIG error code, 126	ER_COLLATION_CHARSET_MISMATCH error code, 21
	ER_COLUMNACCESS_DENIED_ERROR error code, 13
	ER_COLUMN_CHANGE_SIZE error code, 128
	ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_TABLE error code, 120
	ER_COLUMN_COUNT_DOESNT_MATCH_CORRUPTED_V2 error code, 61
	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE error code, 41
	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2 error code, 69
	ER_CONNECTION_BACKEND_FAILED_TO_FETCH_SECURITY_CONTEXT error code, 156
	ER_COMMAND_SERVICE_BACKEND_FAILED error code, 156
	ER_COMMENT_CONTAINS_INVALID_STRING error code, 153

---

---

ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG error code, 32	ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION error code, 624
ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION error code, 90	ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION error code, 624
ER_COMPONENTS_CANT_LOAD error code, 89	ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE error code, 623
ER_COMPONENTS_CANT_RELEASE_SERVICE error code, 90	ER_COMPONENT_EE_INSUFFICIENT_LENGTH error code, 624
ER_COMPONENTS_CANT_SATISFY_DEPENDENCY error code, 90	ER_COMPONENT_EE_OPENSSL_ERROR error code, 624
ER_COMPONENTS_CANT_UNLOAD error code, 90	ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE error code, 623
ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION error code, 298	ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE error code, 623
ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP error code, 169	ER_COMPONENT_FILTER_CONFUSED error code, 321
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT error code, 596	ER_COMPONENT_FILTER_DIAGNOSTICS error code, 107
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT error code, 596	ER_COMPONENT_FILTER_FLABBERGASTED error code, 98
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN error code, 169	ER_COMPONENT_FILTER_WRONG_VALUE error code, 528
ER_COMPONENTS_LOAD_CANT_INITIALIZE error code, 90	ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY error code, 626
ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION error code, 90	ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE error code, 626
ER_COMPONENTS_NO_SCHEME error code, 89	ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE error code, 626
ER_COMPONENTS_NO_SCHEME_SERVICE error code, 89	ER_COMPONENT_LOCK error code, 638
ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP error code, 169	ER_COMPONENT_MANIPULATE_ROW_FAILED error code, 90
ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE error code, 90	ER_COMPONENT_MASKING_ABI error code, 638
ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE error code, 90	ER_COMPONENT_MASKING_ABI_REASON error code, 638
ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP error code, 90	ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE error code, 638
ER_COMPONENTS_UNLOAD_NOT_LOADED error code, 90	ER_COMPONENT_MASKING_OTHER_ERROR error code, 638
ER_COMPONENT_EE_DATA_DECRYPTION_ERROR error code, 624	ER_COMPONENT_MASKING_RANDOM_CREATE error code, 638
ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR error code, 624	ER_COMPONENT_MASKING_RANDOM_CREATE_REASON error code, 638
ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE error code, 624	ER_COMPONENT_SERVICE_CALL error code, 638
ER_COMPONENT_EE_DATA_SIGN_ERROR error code, 624	ER_COMPONENT_SERVICE_CALL_RESULT error code, 638
ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE error code, 623	ER_COMPONENT_TABLE_INCORRECT error code, 90
ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM error code, 623	ER_COMPONENT_UNLOCK error code, 638
ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENTS error code, 623	ER_CONCURRENT_PROCEDURE_USAGE error code, 152
ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE error code, 623	ER_CONDITIONAL_DEBUG error code, 625
	ER_COND_ITEM_TOO_LONG error code, 46
	ER_CREATE_OPTION_WITHOUT_GROUP error code, 185
	ER_CONFIRMING_THE_FUTURE error code, 174

---

---

ER_CONFLICTING_DECLARATIONS error code, 25	ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT error code, 189
ER_CONFLICT_FN_PARSE_ERROR error code, 45	ER_CONN_TCP_LISTEN_FAIL error code, 190
ER_CONNECTION_ABORTED error code, 527	ER_CONN_TCP_NO_SOCKET error code, 189
ER_CONNECTION_HANDLING_OOM error code, 172	ER_CONN_TCP_RESOLVE_INFO error code, 190
ER_CONNECTION_METADATA error code, 17	ER_CONN_TCP_START_FAIL error code, 190
ER_CONNECT_TO_FOREIGN_DATA_SOURCE error code, 33	ER_CONN_TPC_BIND_FAIL error code, 190
ER_CONNECT_TO_MASTER error code, 19	ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET error code, 190
ER_CONNECT_TO_SOURCE error code, 19	ER_CONN_UNIX_LISTEN_FAILED error code, 191
ER_CONN_ATTR_TRUNCATED error code, 193	ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE error code, 192
ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED error code, 323	ER_CONN_UNIX_LOCK_FILE_CANT_CREATE error code, 191
ER_CONN_CONTROL_ERROR_MSG error code, 320	ER_CONN_UNIX_LOCK_FILE_CANT_DELETE error code, 192
ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED error code, 322	ER_CONN_UNIX_LOCK_FILE_CANT_OPEN error code, 191
ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY error code, 323	ER_CONN_UNIX_LOCK_FILE_CANT_READ error code, 191
ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY error code, 323	ER_CONN_UNIX_LOCK_FILE_CANT_SYNC error code, 191
ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE error code, 323	ER_CONN_UNIX_LOCK_FILE_CANT_WRITE error code, 191
ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED error code, 323	ER_CONN_UNIX_LOCK_FILE_EMPTY error code, 191
ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED error code, 323	ER_CONN_UNIX_LOCK_FILE_FAIL error code, 191
ER_CONN_INIT_CONNECT_IGNORED error code, 322	ER_CONN_UNIX_LOCK_FILE_GIVING_UP error code, 191
ER_CONN_INIT_CONNECT_IGNORED_MFA error code, 639	ER_CONN_UNIX_LOCK_FILE_PIDLESS error code, 192
ER_CONN_LIMIT error code, 612	ER_CONN_UNIX_NO_BIND_NO_START error code, 191
ER_CONN_PER_THREAD_NO_THREAD error code, 189	ER_CONN_UNIX_NO_FD error code, 191
ER_CONN_PIP_CANT_CREATE_EVENT error code, 188	ER_CONN_UNIX_PATH_TOO_LONG error code, 191
ER_CONN_PIP_CANT_CREATE_PIPE error code, 188	ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE error code, 190
ER_CONN_SHM_CANT_CREATE_CONNECTION error code, 188	ER_CONSECUTIVE_REORG_PARTITIONS error code, 39
ER_CONN_SHM_CANT_CREATE_SERVICE error code, 188	ER_CONSTRAINT_NOT_FOUND error code, 134
ER_CONN_SHM_LISTENER error code, 188	ER_CONVERT_MULTI_VALUE error code, 639
ER_CONN_SOCKET_ACCEPT_FAILED error code, 192	ER_CON_COUNT_ERROR error code, 5
ER_CONN_SOCKET_SELECT_FAILED error code, 192	ER_CORE_VALUES error code, 174
ER_CONN_TCP_ADDRESS error code, 189	ER_CORRUPTED_JSON_DIFF error code, 102
ER_CONN_TCP_BIND_FAIL error code, 190	ER_CORRUPT_HELP_DB error code, 21
ER_CONN_TCP_BIND_RETRY error code, 190	ER_COULD_NOT_APPLY_JSON_DIFF error code, 102
ER_CONN_TCP_CANT_RESET_V6ONLY error code, 190	ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY error code, 541
ER_CONN_TCP_CANT_RESOLVE_HOSTNAME error code, 189	ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS error code, 535
ER_CONN_TCP_CREATED error code, 189	ER_CRASHED_ON_REPAIR error code, 17
ER_CONN_TCP_ERROR_WITH_STRERROR error code, 189	ER_CRASHED_ON_USAGE error code, 16
ER_CONN_TCP_IPV6_AVAILABLE error code, 189	ER_CREATED_SYSTEM_WITH_VERSION error code, 291
ER_CONN_TCP_IPV6_UNAVAILABLE error code, 189	ER_CREATE_FILEGROUP_FAILED error code, 39
ER_CONN_TCP_IP_NOT_LOGGED error code, 190	

---

---

ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SCHEMA error code, 156	ER_DA_GRP_RPL_STARTED_AUTO_REJOIN error code, 131
ER_CREATING_NEW_UUID error code, 170	ER_DA_INVALID_CONDITION_NUMBER error code, 56
ER_CREATING_NEW_UUID_FIRST_START error code, 281	ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED error code, 142
ER_CREDENTIALLESS_AUTO_USER_BAD error code, 172	ER_DA_OOM error code, 135
ER_CREDENTIALS_CONTRADICT_TO_HISTORY error code, 100	ER_DA_PLUGIN_INSTALL_ERROR error code, 128
ER_CTE_MAX_RECURSION_DEPTH error code, 100	ER_DA_RPL_GTID_TABLE_CANNOT_OPEN error code, 128
ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER error code, 93	ER_DA_SSL_FIPS_MODE_ERROR error code, 151
ER_CTE_RECURSIVE_FORBIDS_AGGREGATION error code, 93	ER_DA_SSL_LIBRARY_ERROR error code, 128
ER_CTE_RECURSIVE_NOT_UNION error code, 156	ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET error code, 136
ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST error code, 93	ER_DA_UDF_INVALID_CHARSET error code, 134
ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE error code, 94	ER_DA_UDF_INVALID_CHARSET_SPECIFIED error code, 134
ER_CTE_RECURSIVE_REQUIRES_UNION error code, 93	ER_DA_UDF_INVALID_COLLATION error code, 134
ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED error code, 129	ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE error code, 134
ER_CURRENT_PASSWORD_NOT_REQUIRED error code, 129	ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET error code, 136
ER_CUT_VALUE_GROUP_CONCAT error code, 22	ER_DA_UNKNOWN_ERROR_NUMBER error code, 128
ER_CYCLE_TIMER_IS_NOT_AVAILABLE error code, 294	ER_DBACCESS_DENIED_ERROR error code, 6
ER_DATABASE_NAME error code, 45	ER_DEBUG_CHECK_SHARES_DROPPED error code, 223
ER_DATA_DIRECTORY_UNUSABLE error code, 542	ER_DEBUG_CHECK_SHARES_INFO error code, 222
ER_DATA_DIRECTORY_UNUSABLE_DELETABLE error code, 565	ER_DEBUG_CHECK_SHARES_OPEN error code, 222
ER_DATA_OUT_OF_RANGE error code, 50	ER_DB_ACCESS_DENIED error code, 127
ER_DATA_TOO_LONG error code, 31	ER_DB_CREATE_EXISTS error code, 4
ER_DATETIME_FUNCTION_OVERFLOW error code, 34	ER_DB_DROP_EXISTS error code, 4
ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANAGED_USERS error code, 127	ER_DB_DROP_RMDIR error code, 4
ER_DA_CANT_OPEN_ERROR_LOG error code, 142	ER_DB_DROP_RMDIR2 error code, 97
ER_DA_CONN_LIMIT error code, 152	ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET error code, 261
ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED error code, 148	ER_DDL_IN_PROGRESS error code, 100
ER_DA_ERROR_LOG_MULTIPLE_FILTERS error code, 142	ER_DDL_LOG_ERROR error code, 41
ER_DA_ERROR_LOG_TABLE_DISABLED error code, 142	ER_DD_ABORTING_PARTIAL_UPGRADE error code, 198
ER_DA_EXPIRE_LOGS_DAYS_IGNORED error code, 156	ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN error code, 165
ER_DA_GLOBAL_CONN_LIMIT error code, 152	ER_DD_CANT_CREATE_OBJECT_KEY error code, 165
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT error code, 138	ER_DD_CANT_CREATE_SP error code, 260
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID error code, 139	ER_DD_CANT_FETCH_TABLE_DATA error code, 260
	ER_DD_CANT_FIX_SE_DATA error code, 260
	ER_DD_CANT_GET_OBJECT_KEY error code, 165
	ER_DD_CANT_RESOLVE_VIEW error code, 183
	ER_DD_CREATED_FOR_UPGRADE error code, 198
	ER_DD_ERROR_CREATING_ENTRY error code, 260
	ER_DD_FAILSAFE error code, 163
	ER_DD_FRM_EXISTS_FOR_TABLE error code, 198
	ER_DD_INITIALIZE error code, 299
	ER_DD_INITIALIZE_SQL_ERROR error code, 536
	ER_DD_INIT_FAILED error code, 164

---



---

ER_DD_INIT_UPGRADE_FAILED error code, 164	ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_AB error code, 290
ER_DD_METADATA_NOT_FOUND error code, 165	ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_CO error code, 290
ER_DD_MINOR_DOWNGRADE error code, 300	ER_DD_UPGRADE_FOUND_PREPARED_XA_TRANSACTION error code, 575
ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED error code, 300	ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED error code, 290
ER_DD_NO_VERSION_FOUND error code, 300	ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED error code, 289
ER_DD_NO_WRITES_NO_REPOPULATION error code, 163	ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED error code, 289
ER_DD_OBJECT_RELEASER_REMAINS error code, 165	ER_DD_UPGRADE_OFF error code, 300
ER_DD_OBJECT_REMAINS error code, 165	ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED error code, 288
ER_DD_OBJECT_REMAINS_IN_RELEASER error code, 165	ER_DD_UPGRADE_SCHEMA_UNAVAILABLE error code, 300
ER_DD_POPULATING_TABLES_FAILED error code, 165	ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED error code, 291
ER_DD_RESTART error code, 300	ER_DD_UPGRADE_SE_LOGS_FAILED error code, 290
ER_DD_SCHEMA_NOT_FOUND error code, 198	ER_DD_UPGRADE_START error code, 290
ER_DD_SE_INIT_FAILED error code, 198	ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED error code, 289
ER_DD_TABLESPACE_NOT_FOUND error code, 183	ER_DD_UPGRADE_TABLE_INTACT_ERROR error code, 296
ER_DD_TABLE_NOT_FOUND error code, 198	ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED error code, 290
ER_DD_TRG_CANT_ADD error code, 183	ER_DD_UPGRADE_VERSION_NOT_SUPPORTED error code, 300
ER_DD_TRG_CONNECTION_COLLATION_MISSING error code, 183	ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG error code, 299
ER_DD_TRG_DB_COLLATION_MISSING error code, 183	ER_DD_VERSION_FOUND error code, 163
ER_DD_TRG_DEFINER_OOM error code, 183	ER_DD_VERSION_INSTALLED error code, 163
ER_DD_TRG_FILE_UNREADABLE error code, 183	ER_DD_VERSION_UNSUPPORTED error code, 163
ER_DD_UPDATE_DATADIR_FLAG_FAIL error code, 642	ER_DD_VIEW_CANT_ALLOC_CHARSET error code, 164
ER_DD_UPDATING_PLUGIN_MD_FAILED error code, 165	ER_DD_VIEW_CANT_CREATE error code, 165
ER_DD_UPGRADE error code, 300	ER_DD_VIEW_WITHOUT_DEFINER error code, 183
ER_DD_UPGRADE_COMPLETED error code, 562	ER_DEBUG_SYNC_EXECUTED error code, 166
ER_DD_UPGRADE_DD_OPEN_FAILED error code, 288	ER_DEBUG_SYNC_HIT error code, 166
ER_DD_UPGRADE_DD_POPULATED error code, 289	ER_DEBUG_SYNC_HIT_LIMIT error code, 46
ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR error code, 290	ER_DEBUG_SYNC_OOM error code, 167
ER_DD_UPGRADE_FAILED_INIT_DD_SE error code, 290	ER_DEBUG_SYNC_THREAD_MAX error code, 166
ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE error code, 288	ER_DEBUG_SYNC_TIMEOUT error code, 46
ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS error code, 290	ER_DEFAULT_AS_VAL_GENERATED error code, 115
ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS error code, 289	ER_DEFAULT_SE_UNAVAILABLE error code, 182
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES error code, 289	ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED error code, 115
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES error code, 288	ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_NOT_ALLOWED error code, 115
ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE error code, 288	ER_DEFAULT_VAL_GENERATED_NON_PRIOR error code, 115
ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE error code, 299	ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC error code, 115

---

---

ER_DEFAULT_VAL_GENERATED_ROW_VALUE error code, 115	ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT_ORDER error code, 71
ER_DEFAULT_VAL_GENERATED_VARIABLES error code, 115	ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER error code, 71
ER_DEFINITION_CONTAINS_INVALID_STRING error code, 153	ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY error code, 298
ER_DEPART_WITH_GRACE error code, 169	ER_DROP_FILEGROUP_FAILED error code, 39
ER_DEPENDENT_BY_CHECK_CONSTRAINT error code, 137	ER_DROP_INDEX_FK error code, 40
ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE error code, 115	ER_DROP_LAST_PARTITION error code, 38
ER_DEPENDENT_BY_FUNCTIONAL_INDEX error code, 123	ER_DROP_PARTITION_NON_EXISTENT error code, 38
ER_DEPENDENT_BY_GENERATED_COLUMN error code, 79	ER_DROP_PK_COLUMN_TO_DROP_GIPK error code, 156
ER_DEPENDENT_BY_PARTITION_FUNC error code, 125	ER_DUPLICATED_VALUE_IN_TYPE error code, 24
ER_DEPRECATED_NATIONAL error code, 109	ER_DUPLICATE_OPTION_KEY error code, 92
ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS error code, 604	ER_DUPLICATE_SYS_VAR error code, 537
ER_DEPRECATED_SYNTAX_NO_REPLACEMENT error code, 297	ER_DUPLICATE_TABLE_LOCK error code, 93
ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT error code, 297	ER_DUP_ARGUMENT error code, 19
ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS error code, 171	ER_DUP_ENTRY error code, 7
ER_DEPRECATED_TLS_VERSION_SESSION error code, 601	ER_DUP_ENTRY_AUTOINCREMENT_CASE error code, 41
ER_DEPRECATED_UTF8_ALIAS error code, 109	ER_DUP_ENTRY_WITH_KEY_NAME error code, 42
ER_DEPRECATE_MSG_NO_REPLACEMENT error code, 297	ER_DUP_FD_OPEN_FAILED error code, 281
ER_DEPRECATE_MSG_WITH_REPLACEMENT error code, 279	ER_DUP_FIELDNAME error code, 7
ER_DERIVED_MUST_HAVE_ALIAS error code, 21	ER_DUP_INDEX error code, 62
ER_DES_FILE_WRONG_KEY error code, 185	ER_DUP_KEY error code, 4
ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN error code, 217	ER_DUP_KEYNAME error code, 7
ER_DETACHING_SESSION_LEFT_BY_PLUGIN error code, 216	ER_DUP_LIST_ENTRY error code, 71
ER_DIMENSION_UNSUPPORTED error code, 75	ER_DUP_SIGNAL_SET error code, 46
ER_DISABLED_STORAGE_ENGINE error code, 83	ER_DUP_UNIQUE error code, 15
ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT error code, 166	ER_DUP_UNKNOWN_IN_INDEX error code, 65
ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT error code, 141	ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE error code, 107
ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT error code, 141	ER_EMPTY_PRIVILEGE_NAME_IGNORED error code, 590
ER_DISALLOWED_OPERATION error code, 102	ER_EMPTY_QUERY error code, 8
ER_DISCARD_FK_CHECKS_RUNNING error code, 61	ER_ENDING_INIT error code, 535
ER_DISCONNECTING_REMAINING_CLIENTS error code, 175	ER_END_INITFILE error code, 177
ER_DISK_FULL_NOWAIT error code, 104	ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_G error code, 80
ER_DIVISION_BY_ZERO error code, 29	ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED error code, 139
	ER_ENGINE_CANT_DROP_MISSING_TABLE error code, 97
	ER_ENGINE_CANT_DROP_TABLE error code, 97
	ER_ENGINE_COST_FAILED_TO_READ error code, 213
	ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE_AND error code, 213
	ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE error code, 213
	ER_ENGINE_COST_UNKNOWN_COST_CONSTANT error code, 212
	ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE error code, 213

---

---

ER\_ENGINE\_OUT\_OF\_MEMORY error code, 69  
 ER\_ERRMSG\_CANT\_FIND\_FILE error code, 198  
 ER\_ERRMSG\_CANT\_READ error code, 199  
 ER\_ERRMSG\_LOADING\_55\_STYLE error code, 199  
 ER\_ERRMSG\_MISSING\_IN\_FILE error code, 199  
 ER\_ERRMSG\_OOM error code, 199  
 ER\_ERRMSG\_REPLACEMENTS\_FAILED error code, 275  
 ER\_ERRMSG\_REPLACEMENT\_DODGY error code, 275  
 ER\_ERROR\_DURING\_COMMIT error code, 15  
 ER\_ERROR\_DURING\_FLUSH\_LOGS error code, 16  
 ER\_ERROR\_DURING\_FLUSH\_LOG\_COMMIT\_PHASE error code, 298  
 ER\_ERROR\_DURING\_OPTIMIZE\_TABLE error code, 259  
 ER\_ERROR\_DURING\_ROLLBACK error code, 15  
 ER\_ERROR\_ENABLING\_KEYS error code, 259  
 ER\_ERROR\_INFO\_FROM\_DA error code, 532  
 ER\_ERROR\_IN\_TRIGGER\_BODY error code, 52  
 ER\_ERROR\_IN\_UNKNOWN\_TRIGGER\_BODY error code, 52  
 ER\_ERROR\_LOG\_DESTINATION\_NOT\_A\_FILE error code, 591  
 ER\_ERROR\_ON\_MASTER error code, 68  
 ER\_ERROR\_ON\_MODIFYING\_GTID\_EXECUTED\_TABLE error code, 84  
 ER\_ERROR\_ON\_READ error code, 4  
 ER\_ERROR\_ON\_RENAME error code, 5  
 ER\_ERROR\_ON\_SOURCE error code, 68  
 ER\_ERROR\_ON\_WRITE error code, 5  
 ER\_ERROR\_WHEN\_EXECUTING\_COMMAND error code, 19  
 ER\_EVENT\_ALREADY\_EXISTS error code, 40  
 ER\_EVENT\_CANNOT\_ALTER\_IN\_THE\_PAST error code, 42  
 ER\_EVENT\_CANNOT\_CREATE\_IN\_THE\_PAST error code, 42  
 ER\_EVENT\_CANT\_FIND\_TIMEZONE error code, 261  
 ER\_EVENT\_CANT\_GET\_CHARSET error code, 261  
 ER\_EVENT\_CANT\_GET\_COLLATION error code, 261  
 ER\_EVENT\_CANT\_GET\_LOCK\_FOR\_DROPPING\_EVENT error code, 265  
 ER\_EVENT\_CANT\_GET\_TIMEZONE\_FROM\_FIELD error code, 261  
 ER\_EVENT\_CANT\_INIT\_QUEUE error code, 167  
 ER\_EVENT\_CANT\_OPEN\_TABLE\_MYSQL\_EVENT error code, 261  
 ER\_EVENT\_DOES\_NOT\_EXIST error code, 40  
 ER\_EVENT\_DROPPING error code, 214  
 ER\_EVENT\_ENDS\_BEFORE\_STARTS error code, 40  
 ER\_EVENT\_ERROR\_CREATING\_QUERY\_TO\_WRITE\_TO\_BINLOG error code, 264  
 ER\_EVENT\_ERROR\_DURING\_COMPILATION error code, 214  
 ER\_EVENT\_EXECUTION\_FAILED error code, 167  
 ER\_EVENT\_EXECUTION\_FAILED\_CANT\_AUTHENTICATE\_US error code, 214  
 ER\_EVENT\_EXECUTION\_FAILED\_USER\_LOST\_EVEN\_PRIVILEGE error code, 214  
 ER\_EVENT\_EXEC\_TIME\_IN\_THE\_PAST error code, 40  
 ER\_EVENT\_INTERVAL\_NOT\_POSITIVE\_OR\_TOO\_BIG error code, 40  
 ER\_EVENT\_INVALID\_CREATION\_CTX error code, 43  
 ER\_EVENT\_LAST\_EXECUTION error code, 167  
 ER\_EVENT\_MESSAGE\_STACK error code, 167  
 ER\_EVENT\_PURGING\_QUEUE error code, 167  
 ER\_EVENT\_RECURSION\_FORBIDDEN error code, 42  
 ER\_EVENT\_SAME\_NAME error code, 40  
 ER\_EVENT\_SCHEDULER\_ERROR\_GETTING\_EVENT\_OBJECT error code, 265  
 ER\_EVENT\_SCHEDULER\_ERROR\_LOADING\_FROM\_DB error code, 265  
 ER\_EVENT\_SCHEDULER\_GOT\_BAD\_DATA\_FROM\_TABLE error code, 265  
 ER\_EVENT\_SET\_VAR\_ERROR error code, 41  
 ER\_EVENT\_UNABLE\_TO\_DROP\_EVENT error code, 265  
 ER\_EXCEEDED\_MV\_KEYS\_NUM error code, 130  
 ER\_EXCEEDED\_MV\_KEYS\_SPACE error code, 130  
 ER\_EXCEPTIONS\_WRITE\_ERROR error code, 45  
 ER\_EXCESS\_ARGUMENTS error code, 178  
 ER\_EXPIRE\_LOGS\_DAYS\_IGNORED error code, 298  
 ER\_EXPLAIN\_NOT\_SUPPORTED error code, 69  
 ER\_FAILED\_DEFAULT\_ROLES error code, 89  
 ER\_FAILED\_GET\_DD\_PROPERTY error code, 640  
 ER\_FAILED\_READ\_FROM\_PAR\_FILE error code, 50  
 ER\_FAILED\_REVOKE\_ROLE error code, 89  
 ER\_FAILED\_ROLE\_GRANT error code, 89  
 ER\_FAILED\_SET\_DD\_PROPERTY error code, 640  
 ER\_FAILED\_START\_MYSQLD\_DAEMON error code, 282  
 ER\_FAILED\_TO\_ACQUIRE\_LOCK\_ON\_RESOURCE\_GROUP error code, 286  
 ER\_FAILED\_TO\_ADD\_RESOURCE\_GROUP\_TO\_MAP error code, 286  
 ER\_FAILED\_TO\_ADD\_RPL\_FILTER error code, 292  
 ER\_FAILED\_TO\_ALLOCATE\_MEMORY\_FOR\_RESOURCE\_GROUP error code, 286  
 ER\_FAILED\_TO\_ALLOCATE\_MEMORY\_FOR\_RESOURCE\_GROUP error code, 286  
 ER\_FAILED\_TO\_ALLOCATE\_SSL\_BIO error code, 536  
 ER\_FAILED\_TO\_APPLY\_RESOURCE\_GROUP\_CONTROLLER error code, 286  
 ER\_FAILED\_TO\_BINLOG\_DROP\_EVENT error code, 291

---

---

ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES error code, 293	ER_FAILED_TO_START_REPLICA_THREAD error code, 292
ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE error code, 205	ER_FAILED_TO_START_SLAVE_THREAD error code, 291
ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE error code, 205	ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE error code, 289
ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY error code, 291	ER_FAILED_TO_UPDATE_RESOURCE_GROUP error code, 285
ER_FAILED_TO_CREATE_CLONE_HANDLER error code, 293	ER_FAILED_TO_WRITE_TO_FILE error code, 278
ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION error code, 205	ER_FAIL_CHROOT error code, 176
ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE error code, 289	ER_FAIL_SETGID error code, 176
ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS error code, 217	ER_FAIL_SETREGID error code, 176
ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE error code, 204	ER_FAIL_SETREUID error code, 176
ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP error code, 285	ER_FAIL_SETUID error code, 176
ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY error code, 135	ER_FEATURE_DISABLED error code, 24
ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST error code, 135	ER_FEATURE_DISABLED_SEE_DOC error code, 84
ER_FAILED_TO_FIND_COLLATION_NAME error code, 280	ER_FEATURE_NOT_AVAILABLE error code, 79
ER_FAILED_TO_FIND_DL_ENTRY error code, 277	ER_FEATURE_UNSUPPORTED error code, 103
ER_FAILED_TO_FIND_LOCALE_NAME error code, 280	ER_FIELD_IN_GROUPING_NOT_GROUP_BY error code, 96
ER_FAILED_TO_FIND_MYSQLD_STATUS error code, 297	ER_FIELD_IN_ORDER_NOT_SELECT error code, 74
ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE error code, 277	ER_FIELD_NOT_FOUND_PART_ERROR error code, 37
ER_FAILED_TO_GET_ABSOLUTE_PATH error code, 281	ER_FIELD_SPECIFIED_TWICE error code, 11
ER_FAILED_TO_HANDLE_DEFAULTS_FILE error code, 537	ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD error code, 47
ER_FAILED_TO_INIT_SYS_VAR error code, 537	ER_FILEGROUP_OPTION_ONLY_ONCE error code, 39
ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE error code, 205	ER_FILESORT_TERMINATED error code, 280
ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREAD error code, 205	ER_FILE_CORRUPT error code, 68
ER_FAILED_TO_LOCK_MEM error code, 176	ER_FILE_EXISTS_DURING_UPGRADE error code, 262
ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES error code, 213	ER_FILE_EXISTS_ERROR error code, 9
ER_FAILED_TO_OPEN_SHARED_LIBRARY error code, 277	ER_FILE_HAS_OLD_FORMAT error code, 279
ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA error code, 285	ER_FILE_NOT_FOUND error code, 4
ER_FAILED_TO_READ_FILE error code, 278	ER_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS error code, 571
ER_FAILED_TO_REMOVE_TEMP_TABLE error code, 255	ER_FILE_TYPE_UNKNOWN error code, 200
ER_FAILED_TO_REPAIR_TABLE error code, 255	ER_FILE_USED error code, 5
ER_FAILED_TO_SET_PERSISTED_OPTIONS error code, 298	ER_FILSORT_ABORT error code, 5
	ER_INCOMPATIBLE_ACCESS_DENIED error code, 313
	ER_FIREWALL_DEPRECATED_USER_PROFILE error code, 601
	ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES error code, 313
	ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES error code, 313
	ER_FIREWALL_PFS_TABLE_REGISTER_FAILED error code, 596
	ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED error code, 313
	ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT error code, 313
	ER_FIREWALL_RELOADING_CACHE error code, 313
	ER_FIREWALL_RESET_FOR_USER error code, 313
	ER_FIREWALL_SERVICES_NOT_ACQUIRED error code, 595

---

---

ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE error code, 313	ER_FPARSER_ERROR_IN_PARAMETER error code, 28
ER_FIREWALL_STATUS_FLUSHED error code, 314	ER_FPARSER_TOO_BIG_FILE error code, 28
ER_FIREWALL_SUSPICIOUS_STMT error code, 313	ER_FSEEK_FAIL error code, 30
ER_FIREWALL_UDF_REGISTER_FAILED error code, 596	ER_FT_BOOL_SYNTAX_INVALID error code, 171
ER_FIXING_CLIENT_CHARSET error code, 176	ER_FT_MATCHING_KEY_NOT_FOUND error code, 16
ER_FK_CANNOT_CHANGE_ENGINE error code, 116	ER_FULLTEXT_FUNCTIONAL_INDEX error code, 114
ER_FK_CANNOT_DROP_PARENT error code, 110	ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING error code, 56
ER_FK_CANNOT_OPEN_PARENT error code, 62	ER_FULLTEXT_WITH_ROLLUP error code, 152
ER_FK_CANNOT_USE_VIRTUAL_COLUMN error code, 111	ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG error code, 130
ER_FK_COLUMN_CANNOT_CHANGE error code, 63	ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED error code, 114
ER_FK_COLUMN_CANNOT_CHANGE_CHILD error code, 63	ER_FUNCTIONAL_INDEX_ON_FIELD error code, 114
ER_FK_COLUMN_CANNOT_DROP error code, 62	ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNC error code, 113
ER_FK_COLUMN_CANNOT_DROP_CHILD error code, 62	ER_FUNCTIONAL_INDEX_ON_LOB error code, 114
ER_FK_COLUMN_NOT_NULL error code, 62	ER_FUNCTIONAL_INDEX_PRIMARY_KEY error code, 113
ER_FK_DEPTH_EXCEEDED error code, 69	ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT error code, 113
ER_FK_DUP_NAME error code, 62	ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED error code, 118
ER_FK_FAIL_ADD_SYSTEM error code, 62	ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET error code, 140
ER_FK_INCOMPATIBLE_COLUMNS error code, 116	ER_FUNCTION_NOT_DEFINED error code, 12
ER_FK_INCORRECT_OPTION error code, 62	ER_FUNC_INEXISTENT_NAME_COLLISION error code, 45
ER_FK_NO_COLUMN_PARENT error code, 111	ER_FUTURE_DATE error code, 174
ER_FK_NO_INDEX_CHILD error code, 62	ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED error code, 78
ER_FK_NO_INDEX_PARENT error code, 62	ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED error code, 114
ER_FORBID_SCHEMA_CHANGE error code, 34	ER_GENERATED_COLUMN_NON_PRIOR error code, 79
ER_FORCE_CLOSE_THREAD error code, 278	ER_GENERATED_COLUMN_REF_AUTO_INC error code, 79
ER_FORCING_CLOSE error code, 8	ER_GENERATED_COLUMN_ROW_VALUE error code, 114
ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST error code, 33	ER_GENERATED_COLUMN_VARIABLES error code, 114
ER_FOREIGN_DATA_STRING_INVALID error code, 33	ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT error code, 128
ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE error code, 33	ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE error code, 111
ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED error code, 40	ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE error code, 111
ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO error code, 56	ER_GET_ERRMSG error code, 25
ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO error code, 56	ER_GET_ERRNO error code, 5
ER_FOREIGN_KEY_ON_PARTITIONED error code, 38	ER_GET_ERRNO_FROM_STORAGE_ENGINE error code, 279
ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT error code, 139	ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER error code, 69
ER_FOREIGN_SERVER_DOESNT_EXIST error code, 36	
ER_FOREIGN_SERVER_EXISTS error code, 36	
ER_FOUND_MISSING_GTIDS error code, 388	
ER_FOUND_ROWS_WHILE_REPAIRING error code, 259	
ER_FPARSER_BAD_HEADER error code, 28	
ER_FPARSER_EOF_IN_COMMENT error code, 28	
ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER error code, 28	

---

---

ER_GET_TEMPORARY_ERRMSG error code, 25	ER_GRP_RPL_ADD_GRPSID_TO_GRPGTIDSID_MAP_ERROR error code, 344
ER_GIPK_COLUMN_ALTER_NOT_ALLOWED error code, 156	ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED error code, 356
ER_GIPK_COLUMN_EXISTS error code, 155	ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED error code, 356
ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS error code, 155	ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED error code, 356
ER_GIS_DATA_WRONG_ENDIANESS error code, 73	ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED error code, 356
ER_GIS_DIFFERENT_SRIDS error code, 72	ER_GRP_RPL_ADD_GTID_TO_GRPGTID_EXECUTED_ERROR error code, 344
ER_GIS_DIFFERENT_SRIDS_AGGREGATION error code, 146	ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED_ERROR error code, 345
ER_GIS_INVALID_DATA error code, 72	ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP_ERROR error code, 603
ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED error code, 81	ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY error code, 358
ER_GIS_UNKNOWN_ERROR error code, 72	ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED error code, 369
ER_GIS_UNKNOWN_EXCEPTION error code, 72	ER_GRP_RPL_APPENDING_DATA_TO_INTERNAL_CACHE_FAILED error code, 362
ER_GIS_UNSUPPORTED_ARGUMENT error code, 72	ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING error code, 595
ER_GLOBAL_CONN_LIMIT error code, 612	ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR error code, 343
ER_GLOBAL_VARIABLE error code, 20	ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE error code, 374
ER_GLOBSTAT_CHANGE_DURING_QUERY error code, 131	ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED error code, 374
ER_GNO_EXHAUSTED error code, 57	ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE error code, 374
ER_GRANT_WRONG_HOST_OR_USER error code, 13	ER_GRP_RPL_APPLIER_INITIALIZED error code, 370
ER_GROUPING_ON_TIMESTAMP_IN_DST error code, 131	ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TABLE_OR_FILE error code, 371
ER_GROUP_REPLICATION_APPLIER_INIT_ERROR error code, 78	ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING_PRIMARY error code, 370
ER_GROUP_REPLICATION_COMMAND_FAILURE error code, 103	ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED error code, 343
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_ERROR error code, 78	ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN error code, 368
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_ERROR_SESSION_ERROR error code, 78	ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED error code, 343
ER_GROUP_REPLICATION_CONFIGURATION error code, 78	ER_GRP_RPL_APPLIER_THD_KILLED error code, 342
ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE error code, 157	ER_GRP_RPL_APPLIER_THD_KILLED_BY_SQL_KILL error code, 643
ER_GROUP_REPLICATION_MAX_GROUP_SIZE error code, 86	ER_GRP_RPL_APPLIER_THD_SETUP_ERROR error code, 353
ER_GROUP_REPLICATION_PASSWORD_LENGTH error code, 138	ER_GRP_RPL_APPLIER_THD_START_ERROR error code, 353
ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED error code, 204	ER_GRP_RPL_APPLIER_THD_STOP_ERROR error code, 353
ER_GROUP_REPLICATION_RUNNING error code, 78	ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT error code, 540
ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT error code, 78	
ER_GROUP_REPLICATION_USER_EMPTY_MSG error code, 138	
ER_GROUP_REPLICATION_USER_MANDATORY_MSG error code, 138	
ER_GRP_DELAYED_VCLE_LOGGING error code, 561	
ER_GRP_OPERATION_NOT_ALLOWED_GRP_MUST_STOP error code, 137	
ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_MYSQL error code, 370	

---

---

ER_GRP_RPL_AUTO_INC_OFFSET_RESET error code, 355	ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR error code, 567
ER_GRP_RPL_AUTO_INC_OFFSET_SET error code, 355	ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR error code, 566
ER_GRP_RPL_AUTO_INC_RESET error code, 354	ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO error code, 370
ER_GRP_RPL_AUTO_INC_SET error code, 355	ER_GRP_RPL_CONFIGURATION_ACTION_END error code, 540
ER_GRP_RPL_BINLOG_CHECKSUM_SET error code, 361	ER_GRP_RPL_CONFIGURATION_ACTION_ERROR error code, 540
ER_GRP_RPL_BINLOG_DISABLED error code, 370	ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR error code, 540
ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP error code, 352	ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION error code, 540
ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED error code, 363	ER_GRP_RPL_CONFIGURATION_ACTION_START error code, 540
ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG error code, 377	ER_GRP_RPL_CONFIG_RECOVERY error code, 358
ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED error code, 344	ER_GRP_RPL_CONFLICT_DETECTION_DISABLED error code, 347
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STAGE error code, 361	ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_EMPTY error code, 371
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE error code, 361	ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL error code, 357
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECEIVING error code, 361	ER_GRP_RPL_CONTACT_WITH_SRV_FAILED error code, 356
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING error code, 361	ER_GRP_RPL_COPY_FROM_EMPTY_STRING error code, 358
ER_GRP_RPL_CANT_GENERATE_GTID error code, 345	ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR error code, 343
ER_GRP_RPL_CANT_KILL_THREAD error code, 567	ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL error code, 359
ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED error code, 347	ER_GRP_RPL_CREATE_SESSION_UNABLE error code, 358
ER_GRP_RPL_CANT_READ_GTID error code, 346	ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM error code, 350
ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM error code, 347	ER_GRP_RPL_DEBUG_OPTIONS error code, 376
ER_GRP_RPL_CERTIFICATE_SIZE_ERROR error code, 342	ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_MASTER error code, 558
ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE error code, 345	ER_GRP_RPL_DISABLE_READ_ONLY_FAILED error code, 349
ER_GRP_RPL_CERTIFICATION_REC_PROCESS error code, 364	ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED error code, 348
ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR error code, 347	ER_GRP_RPL_DONOR_CONN_TERMINATION error code, 359
ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATE_FAILED error code, 643	ER_GRP_RPL_DONOR_SERVER_CONN error code, 359
ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED error code, 643	ER_GRP_RPL_DONOR_TRANS_INFO_ERROR error code, 344
ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED error code, 643	ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR error code, 508
ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED error code, 348	ER_GRP_RPL_ENABLE_READ_ONLY_FAILED error code, 350
ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING error code, 539	ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET error code, 344
ER_GRP_RPL_CHECK_STATUS_TABLE error code, 359	

---

---

ER_GRP_RPL_ERROR_FETCHING_GTID_SET error code, 345	ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET error code, 362
ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO error code, 342	ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET error code, 362
ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION error code, 539	ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP error code, 369
ER_GRP_RPL_ERROR_MSG error code, 320	ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW_CHANGE error code, 602
ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL error code, 553	ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER error code, 374
ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING error code, 540	ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE error code, 370
ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MESSAGE error code, 343	ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE error code, 366
ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER error code, 611	ER_GRP_RPL_FAILED_TO_INIT_HANDLER error code, 368
ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER error code, 611	ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFTER_COMMIT error code, 550
ER_GRP_RPL_ERROR_STOPPING_CHANNELS error code, 343	ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE error code, 622
ER_GRP_RPL_ERROR_VERIFYING_SIDNO error code, 345	ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT error code, 360
ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_RESOLUTION error code, 363	ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME error code, 369
ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR error code, 359	ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_UUID error code, 602
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR error code, 358	ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER error code, 369
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR error code, 358	ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER error code, 368
ER_GRP_RPL_EVENT_HANDLING_ERROR error code, 342	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION error code, 363
ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE error code, 350	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER error code, 368
ER_GRP_RPL_EXIT_GRP_GCS_ERROR error code, 377	ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_READING_STRUCTURE error code, 362
ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING error code, 374	ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE error code, 358
ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION error code, 360	ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE error code, 366
ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION error code, 360	ER_GRP_RPL_FAILED_TO_START_ON_BOOT error code, 368
ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_MODULE error code, 366	ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC error code, 366
ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP error code, 367	ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID error code, 365
ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE error code, 363	ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL error code, 369
ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT error code, 362	ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER error code, 369
ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE error code, 368	ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER error code, 369
ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE error code, 366	ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER error code, 369

---



---

ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION error code, 148	ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING error code, 553
ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST error code, 606	ER_GRP_RPL_FORCE_MEMBER_VALUE_SET error code, 377
ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION error code, 606	ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR error code, 377
ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE error code, 606	ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT error code, 377
ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_ERROR error code, 606	ER_GRP_RPL_GCS_GR_ERROR_MSG error code, 379
ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAULT_CONFIGURATION error code, 606	ER_GRP_RPL_GCS_INTERFACE_ERROR error code, 377
ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY error code, 607	ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION error code, 376
ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY error code, 606	ER_GRP_RPL_GROUP_NAME_PARSE_ERROR error code, 344
ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER_ERROR error code, 606	ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_UUID error code, 606
ER_GRP_RPL_FATAL_REC_PROCESS error code, 364	ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR error code, 351
ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED error code, 355	ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED error code, 376
ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED error code, 355	ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONF error code, 374
ER_GRP_RPL_FETCH_LOG_EVENT_FAILED error code, 357	ER_GRP_RPL_GRP_MEMBER_OFFLINE error code, 377
ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED error code, 355	ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID error code, 372
ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED error code, 355	ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO error code, 594
ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED error code, 355	ER_GRP_RPL_GRP_NAME_IS_TOO_LONG error code, 372
ER_GRP_RPL_FETCH_TRANS_DATA_FAILED error code, 353	ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY error code, 372
ER_GRP_RPL_FETCH_TRANS_SIDNO_ERROR error code, 345	ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE error code, 602
ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED error code, 356	ER_GRP_RPL_GTID_ALREADY_USED error code, 342
ER_GRP_RPL_FINISHED_AUTO_REJOIN error code, 558	ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR error code, 351
ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED error code, 354	ER_GRP_RPL_GTID_MODE_OFF error code, 371
ER_GRP_RPL_FLOW_CONTROL_STATS error code, 378	ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR error code, 566
ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN error code, 373	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR error code, 351
ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX error code, 373	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY error code, 552
ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX error code, 373	ER_GRP_RPL_HAS_STARTED error code, 634
ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY error code, 365	ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_API error code, 372
ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED error code, 373	ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE error code, 347
	ER_GRP_RPL_INTERNAL_QUERY error code, 357
	ER_GRP_RPL_INVALID_BINLOG_FORMAT error code, 360

---

---

ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL error code, 558	ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS error code, 599
ER_GRP_RPL_INVALID_DEBUG_OPTIONS error code, 377	ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER error code, 600
ER_GRP_RPL_INVALID_GTID_SET error code, 346	ER_GRP_RPL_MEMBER_ADDED error code, 349
ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING error code, 373	ER_GRP_RPL_MEMBER_ALREADY_EXISTS error code, 350
ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION_ERROR error code, 371	ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP_CFG error code, 352
ER_GRP_RPL_IS_STARTING error code, 582	ER_GRP_RPL_MEMBER_CHANGE error code, 349
ER_GRP_RPL_IS_STOPPED error code, 368	ER_GRP_RPL_MEMBER_CONF_INFO error code, 367
ER_GRP_RPL_IS_STOPPING error code, 367	ER_GRP_RPL_MEMBER_CONTACT_RESTORED error code, 349
ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING error code, 539	ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR error code, 349
ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING error code, 539	ER_GRP_RPL_MEMBER_EXPELLED error code, 349
ER_GRP_RPL_KILLED_FAILED_ID error code, 357	ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST error code, 641
ER_GRP_RPL_KILLED_SESSION_ID error code, 357	ER_GRP_RPL_MEMBER_LEFT_GRP error code, 349
ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR error code, 352	ER_GRP_RPL_MEMBER_NOT_FOUND error code, 358
ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET error code, 371	ER_GRP_RPL_MEMBER_REMOVED error code, 349
ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET error code, 371	ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP error code, 366
ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP error code, 527	ER_GRP_RPL_MEMBER_STATS_INFO error code, 378
ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE error code, 371	ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR error code, 352
ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED error code, 358	ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP error code, 352
ER_GRP_RPL_MEMBER_ACTIONS_RESET error code, 600	ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP error code, 351
ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION error code, 600	ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE error code, 351
ER_GRP_RPL_MEMBER_ACTION_DISABLED error code, 600	ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE error code, 563
ER_GRP_RPL_MEMBER_ACTION_ENABLED error code, 600	ER_GRP_RPL_MEM_ONLINE error code, 348
ER_GRP_RPL_MEMBER_ACTION_FAILURE error code, 599	ER_GRP_RPL_MEM_REACHABLE error code, 348
ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE error code, 599	ER_GRP_RPL_MEM_UNREACHABLE error code, 348
ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE error code, 599	ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR error code, 570
ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER error code, 600	ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE error code, 132
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER error code, 600	ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR error code, 539
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVER error code, 599	ER_GRP_RPL_MISSING_GRP_RPL_APPLIER error code, 547
ER_GRP_RPL_MEMBER_ACTION_TRIGGERED error code, 599	ER_GRP_RPL_MODULE_TERMINATE_ERROR error code, 372
ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION error code, 600	ER_GRP_RPL_MSG_DISCARDED error code, 347
	ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_FAILURE error code, 363
	ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED_FOR_CONFIGURATION error code, 361
	ER_GRP_RPL_NETWORK_PROVIDER_CLIENT_ERROR error code, 605

---

---

ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT error code, 605	ER_GRP_RPL_READ_UNABLE_FOR_SUPER_READ_ONLY error code, 365
ER_GRP_RPL_NEEDS_INNOODB_TABLE error code, 354	ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS error code, 346
ER_GRP_RPL_NEW_PRIMARY_ELECTED error code, 349	ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING error code, 145
ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED error code, 356	ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT error code, 582
ER_GRP_RPL_NO_POSSIBLE_RECOVERY error code, 567	ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS error code, 583
ER_GRP_RPL_NO_STAGE_SERVICE error code, 541	ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID error code, 582
ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM error code, 350	ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_EN error code, 583
ER_GRP_RPL_NO_VALID_DONOR error code, 358	ER_GRP_RPL_RECOVERY_EVAL_ERROR error code, 567
ER_GRP_RPL_NULL_PACKET error code, 346	ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMED_OUT error code, 358
ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE error code, 364	ER_GRP_RPL_RECOVERY_STRAT_CHOICE error code, 567
ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION error code, 360	ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED error code, 567
ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GROUP error code, 611	ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD error code, 567
ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_ORDR error code, 632	ER_GRP_RPL_RECOVERY_STRAT_FALLBACK error code, 567
ER_GRP_RPL_PIPELINE_CREATE_FAILED error code, 378	ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK error code, 568
ER_GRP_RPL_PIPELINE_FLUSH_FAIL error code, 378	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCY error code, 551
ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ error code, 378	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PREPARED error code, 551
ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE error code, 378	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE error code, 551
ER_GRP_RPL_PLUGIN_ABORT error code, 536	ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITE_FAILED error code, 364
ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE error code, 366	ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_READ_FAILED error code, 362
ER_GRP_RPL_PREV_REC_SESSION_RUNNING error code, 364	ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITE_FAILED error code, 363
ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR error code, 540	ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE error code, 371
ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR error code, 541	ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCY error code, 551
ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED error code, 354	ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_SYNC error code, 552
ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP error code, 349	ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARED error code, 550
ER_GRP_RPL_PROCESS_GTID_SET_ERROR error code, 346	ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT error code, 380
ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR error code, 346	ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED error code, 379
ER_GRP_RPL_PURGE_APPLIER_LOGS error code, 352	ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY error code, 365
ER_GRP_RPL_PURGE_REC error code, 359	ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN error code, 353
ER_GRP_RPL_QUERY_FAIL error code, 358	
ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER error code, 365	

---

---

ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT error code, 379	ER_GRP_RPL_SLAVE_APPLIER_THREAD_ERROR_OUT error code, 379
ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED error code, 379	ER_GRP_RPL_SLAVE_APPLIER_THREAD_UNBLOCKED error code, 379
ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_SET error code, 372	ER_GRP_RPL_SLAVE_IO_THD_PRIMARY_UNKNOWN error code, 353
ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_MEMBER error code, 354	ER_GRP_RPL_SLAVE_IO_THREAD_ERROR_OUT error code, 379
ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN error code, 354	ER_GRP_RPL_SLAVE_IO_THREAD_UNBLOCKED error code, 379
ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE error code, 568	ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOT_SET error code, 372
ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY_MEMBER error code, 607	ER_GRP_RPL_SLAVE_SQL_THD_ON_SECONDARY_MEMBER error code, 354
ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_LEAVE error code, 367	ER_GRP_RPL_SLAVE_SQL_THD_PRIMARY_UNKNOWN error code, 354
ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR error code, 353	ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_CLONE error code, 568
ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER error code, 353	ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_SECONDARY_MEMBER error code, 607
ER_GRP_RPL_SEND_STATS_ERROR error code, 377	ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED error code, 375
ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED error code, 550	ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CONTEXT error code, 375
ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED error code, 552	ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREADS error code, 375
ER_GRP_RPL_SERVER_ALREADY_LEFT error code, 367	ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY error code, 375
ER_GRP_RPL_SERVER_CONN_ERROR error code, 344	ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER error code, 376
ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING error code, 367	ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION error code, 375
ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ERRORS error code, 569	ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_SESSION error code, 375
ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS error code, 376	ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN error code, 376
ER_GRP_RPL_SERVER_UDF_ERROR error code, 541	ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE error code, 375
ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY error code, 365	ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED error code, 375
ER_GRP_RPL_SESSION_OPEN_FAILED error code, 349	ER_GRP_RPL_SRV_BLOCKED error code, 348
ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOG_ENABLED error code, 376	ER_GRP_RPL_SRV_BLOCKED_FOR_SECS error code, 348
ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER error code, 611	ER_GRP_RPL_SRV_GTID_WAIT_ERROR error code, 561
ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER error code, 611	ER_GRP_RPL_SRV_NOT_ONLINE error code, 347
ER_GRP_RPL_SET_STABLE_TRANS_ERROR error code, 346	ER_GRP_RPL_SRV_ONLINE error code, 347
ER_GRP_RPL_SIDNO_FETCH_ERROR error code, 343	ER_GRP_RPL_SRV_PRIMARY_MEM error code, 350
ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH_UPDATE_EVERYWHERE error code, 372	ER_GRP_RPL_SRV_SECONDARY_MEM error code, 350
ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTED error code, 346	ER_GRP_RPL_SRV_WAIT_TIME_OUT error code, 357
	ER_GRP_RPL_SSL_DISABLED error code, 370
	ER_GRP_RPL_STARTED_AUTO_REJOIN error code, 558

---

---

ER_GRP_RPL_STARTING_GRP_REC error code, 359	ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC error code, 364
ER_GRP_RPL_START_FAILED error code, 351	ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS error code, 364
ER_GRP_RPL_START_GRP_RPL_FAILED error code, 357	ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE error code, 370
ER_GRP_RPL_STOPPING_GRP_REC error code, 359	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPL error code, 360
ER_GRP_RPL_STOP_REP_CHANNEL error code, 378	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAILED error code, 360
ER_GRP_RPL_SUPER_READ_OFF error code, 357	ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE error code, 365
ER_GRP_RPL_SUPER_READ_ON error code, 357	ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS error code, 365
ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR error code, 350	ER_GRP_RPL_UNBLOCK_WAITING_THD error code, 343
ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBER error code, 373	ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_RE error code, 374
ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP error code, 366	ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_M error code, 376
ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN error code, 590	ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION error code, 361
ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN error code, 558	ER_GRP_RPL_UPDATE_GRPGTID_EXECUTED_ERROR error code, 344
ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_ON_GRP error code, 367	ER_GRP_RPL_UPDATE_GRPGTID_VIEW_CHANGE_UUID_EX error code, 602
ER_GRP_RPL_TRANS_GREATER_THAN_GRP error code, 351	ER_GRP_RPL_UPDATE_GTID_SET_ERROR error code, 346
ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP error code, 351	ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANS_ER error code, 345
ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT error code, 362	ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED error code, 356
ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_IN_GRP error code, 361	ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VER_ERROR error code, 345
ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP error code, 352	ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VER_ERROR error code, 343
ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AIR error code, 550	ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP error code, 602
ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLER error code, 551	ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE error code, 147
ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED error code, 552	ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID error code, 601
ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED error code, 551	ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANONYM error code, 601
ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION error code, 552	ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR error code, 602
ER_GRP_RPL_UDF_ERROR error code, 131	ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NA error code, 601
ER_GRP_RPL_UDF_REGISTER_ERROR error code, 541	ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE error code, 367
ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR error code, 541	ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED error code, 551
ER_GRP_RPL_UDF_UNREGISTER_ERROR error code, 541	ER_GRP_RPL_WHILE_SENDING_MSG_REC error code, 364
ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS error code, 365	
ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET error code, 378	
ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT error code, 378	

---

---

ER_GRP_RPL_WHILE_STOPPING_REP_CHANNEL error code, 364	ER_HEALTH_INFO error code, 594
ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED error code, 360	ER_HEALTH_WARNING error code, 594
ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED error code, 363	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1 error code, 595
ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FILE_FAILED error code, 363	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2 error code, 595
ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN error code, 118	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3 error code, 595
ER_GRP_TRX_CONSISTENCY_BEFORE error code, 118	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1 error code, 610
ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED error code, 118	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2 error code, 610
ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED error code, 118	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3 error code, 610
ER_GR_ELECTED_PRIMARY_GTID_INFORMATION error code, 574	ER_HOSTNAME error code, 35
ER_GR_HOLD_KILLED error code, 116	ER_HOSTNAME_DOESNT_RESOLVE_TO error code, 168
ER_GR_HOLD_MEMBER_STATUS_ERROR error code, 117	ER_HOSTNAME_RESEMBLES_IPV4 error code, 168
ER_GR_HOLD_WAIT_TIMEOUT error code, 116	ER_HOSTNAME_TOO_LONG error code, 138
ER_GTID_ALREADY_ADDED_BY_USER error code, 204	ER_HOSTNAME_TRUNCATED error code, 584
ER_GTID_EXECUTED_WAS_CHANGED error code, 63	ER_HOST_IS_BLOCKED error code, 12
ER_GTID_EXECUTED_WAS_UPDATED error code, 279	ER_HOST_NOT_PRIVILEGED error code, 12
ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME error code, 58	ER_HYPERGRAPH_NOT_SUPPORTED_YET error code, 142
ER_GTID_MODE_OFF error code, 74	ER_IB_BUFFER_POOL_FULL error code, 628
ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY error code, 58	ER_IB_BUFFER_POOL_OVERUSE error code, 628
ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_IS NOT NULL error code, 57	ER_IB_BULK_FLUSHER_INFO error code, 628
ER_GTID_NEXT_TYPE_UNDEFINED_GROUP error code, 63	ER_IB_BULK_LOAD_MERGE_FAIL error code, 631
ER_GTID_NEXT_TYPE_UNDEFINED_GTID error code, 63	ER_IB_BULK_LOAD_SUBTREE_INFO error code, 628
ER_GTID_PURGED_WAS_CHANGED error code, 63	ER_IB_BULK_LOAD_THREAD_FAIL error code, 631
ER_GTID_PURGED_WAS_UPDATED error code, 279	ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES error code, 584
ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT error code, 116	ER_IB_CLONE_OUT_PERSIST error code, 406
ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT error code, 67	ER_IB_CLONE_INTERNAL error code, 404
ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT error code, 67	ER_IB_CLONE_NON_INNO_DB_TABLE error code, 566
ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLES IN TRANSACTION error code, 58	ER_IB_CLONE_OPERATION error code, 566
ER_GTID_UNSAFE_CREATE_SELECT error code, 58	ER_IB_CLONE_PUNCH_HOLE error code, 405
ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE error code, 58	ER_IB_CLONE_RESTART error code, 566
ER_HANDLERTON_OOM error code, 188	ER_IB_CLONE_SQL error code, 405
ER_HANDSHAKE_ERROR error code, 6	ER_IB_CLONE_START_STOP error code, 566
ER_HEALTH_ERROR error code, 594	ER_IB_CLONE_STATUS_FILE error code, 405
	ER_IB_CLONE_TIMEOUT error code, 405
	ER_IB_CLONE_UNEXPECTED_DATA error code, 566
	ER_IB_CLONE_VALIDATE error code, 405
	ER_IB_CLONE_VALIDATE_GROUPS_INFO error code, 615
	ER_IB_DBLWR_DECOMPRESS_FAILED error code, 591
	ER_IB_DBLWR_DECRYPT_FAILED error code, 591
	ER_IB_DBLWR_KEY_MISSING error code, 591
	ER_IB_DDL_CONVERT_HEAP_NOT_FOUND error code, 640
	ER_IB_DICT_INVALID_COLUMN_POSITION error code, 632
	ER_IB_DICT_LOG_TABLE_INFO error code, 633

---

---

ER_IB_DUPLICATE_KEY error code, 628	ER_IB_INNODB_TBSP_OUT_OF_SPACE error code, 595
ER_IB_ERR_DDL_LOG_INSERT_FAILURE error code, 585	ER_IB_LOAD_BULK_CONCURRENCY_REDUCED error code, 631
ER_IB_ERR_FOUND_N_DUPLICATE_KEYS error code, 588	ER_IB_LOB_ROLLBACK_INDEX_LEN error code, 572
ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER error code, 588	ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION error code, 585
ER_IB_ERR_INDEX_DUPLICATE_KEY error code, 588	ER_IB_LONG_AHI_DISABLE_WAIT error code, 408
ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER error code, 588	ER_IB_MSG_0 error code, 389
ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW error code, 587	ER_IB_MSG_1 error code, 389
ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER error code, 587	ER_IB_MSG_10 error code, 390
ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED error code, 604	ER_IB_MSG_100 error code, 399
ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUFFER error code, 581	ER_IB_MSG_1000 error code, 494
ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT error code, 581	ER_IB_MSG_1001 error code, 494
ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED error code, 581	ER_IB_MSG_1002 error code, 494
ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN error code, 398	ER_IB_MSG_1003 error code, 494
ER_IB_ERR_PARALLEL_READ_OOM error code, 588	ER_IB_MSG_1004 error code, 494
ER_IB_ERR_RECOVERY_REDO_DISABLED error code, 583	ER_IB_MSG_1005 error code, 494
ER_IB_ERR_SCHED_SETAFFINITY_FAILED error code, 587	ER_IB_MSG_1006 error code, 494
ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMIFILE error code, 586	ER_IB_MSG_1007 error code, 495
ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST error code, 586	ER_IB_MSG_1008 error code, 495
ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY error code, 586	ER_IB_MSG_1009 error code, 495
ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATAFILE error code, 586	ER_IB_MSG_101 error code, 400
ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE error code, 587	ER_IB_MSG_1010 error code, 495
ER_IB_ERR_ZLIB_BUF_ERROR error code, 587	ER_IB_MSG_1011 error code, 495
ER_IB_ERR_ZLIB_DATA_ERROR error code, 588	ER_IB_MSG_1012 error code, 495
ER_IB_ERR_ZLIB_MEM_ERROR error code, 588	ER_IB_MSG_1013 error code, 495
ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED error code, 587	ER_IB_MSG_1014 error code, 495
ER_IB_ERR_ZLIB_UNKNOWN_ERROR error code, 588	ER_IB_MSG_1015 error code, 495
ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE error code, 586	ER_IB_MSG_1016 error code, 495
ER_IB_HIDDEN_NAME_CONFLICT error code, 632	ER_IB_MSG_1017 error code, 496
ER_IB_INDEX_BUILDER_DONE error code, 634	ER_IB_MSG_1018 error code, 496
ER_IB_INDEX_BUILDER_INIT error code, 634	ER_IB_MSG_1019 error code, 496
ER_IB_INDEX_LOADER_DONE error code, 633	ER_IB_MSG_102 error code, 400
ER_IB_INDEX_LOG_VERSION_MISMATCH error code, 634	ER_IB_MSG_1020 error code, 496
ER_IB_INDEX_PART_TOO_LONG error code, 642	ER_IB_MSG_1021 error code, 496
	ER_IB_MSG_1022 error code, 496
	ER_IB_MSG_1023 error code, 496
	ER_IB_MSG_1024 error code, 496
	ER_IB_MSG_1025 error code, 496
	ER_IB_MSG_1026 error code, 496
	ER_IB_MSG_1027 error code, 497
	ER_IB_MSG_1028 error code, 497
	ER_IB_MSG_1029 error code, 497
	ER_IB_MSG_103 error code, 400
	ER_IB_MSG_1030 error code, 497
	ER_IB_MSG_1031 error code, 497
	ER_IB_MSG_1032 error code, 497
	ER_IB_MSG_1033 error code, 497
	ER_IB_MSG_1034 error code, 497
	ER_IB_MSG_1035 error code, 497
	ER_IB_MSG_1036 error code, 497
	ER_IB_MSG_1037 error code, 498
	ER_IB_MSG_1038 error code, 498

---







---

ER\_IB\_MSG\_1233 error code, 520  
ER\_IB\_MSG\_1234 error code, 521  
ER\_IB\_MSG\_1235 error code, 521  
ER\_IB\_MSG\_1236 error code, 521  
ER\_IB\_MSG\_1237 error code, 521  
ER\_IB\_MSG\_1238 error code, 521  
ER\_IB\_MSG\_1239 error code, 521  
ER\_IB\_MSG\_124 error code, 402  
ER\_IB\_MSG\_1240 error code, 522  
ER\_IB\_MSG\_1241 error code, 522  
ER\_IB\_MSG\_1242 error code, 522  
ER\_IB\_MSG\_1243 error code, 522  
ER\_IB\_MSG\_1244 error code, 522  
ER\_IB\_MSG\_1245 error code, 522  
ER\_IB\_MSG\_1246 error code, 522  
ER\_IB\_MSG\_1247 error code, 522  
ER\_IB\_MSG\_1248 error code, 523  
ER\_IB\_MSG\_1249 error code, 523  
ER\_IB\_MSG\_125 error code, 402  
ER\_IB\_MSG\_1250 error code, 523  
ER\_IB\_MSG\_1251 error code, 523  
ER\_IB\_MSG\_1252 error code, 523  
ER\_IB\_MSG\_1253 error code, 523  
ER\_IB\_MSG\_1254 error code, 523  
ER\_IB\_MSG\_1255 error code, 523  
ER\_IB\_MSG\_1256 error code, 523  
ER\_IB\_MSG\_1257 error code, 524  
ER\_IB\_MSG\_1258 error code, 524  
ER\_IB\_MSG\_1259 error code, 524  
ER\_IB\_MSG\_126 error code, 402  
ER\_IB\_MSG\_1260 error code, 524  
ER\_IB\_MSG\_1261 error code, 524  
ER\_IB\_MSG\_1262 error code, 524  
ER\_IB\_MSG\_1263 error code, 524  
ER\_IB\_MSG\_1264 error code, 524  
ER\_IB\_MSG\_1265 error code, 524  
ER\_IB\_MSG\_1266 error code, 525  
ER\_IB\_MSG\_1267 error code, 525  
ER\_IB\_MSG\_1268 error code, 525  
ER\_IB\_MSG\_1269 error code, 525  
ER\_IB\_MSG\_127 error code, 402  
ER\_IB\_MSG\_1270 error code, 525  
ER\_IB\_MSG\_1271 error code, 535  
ER\_IB\_MSG\_1272 error code, 535  
ER\_IB\_MSG\_1273 error code, 536  
ER\_IB\_MSG\_1274 error code, 537  
ER\_IB\_MSG\_1275 error code, 537  
ER\_IB\_MSG\_1276 error code, 537  
ER\_IB\_MSG\_1277 error code, 538  
ER\_IB\_MSG\_1278 error code, 538  
ER\_IB\_MSG\_1279 error code, 538  
ER\_IB\_MSG\_128 error code, 402  
ER\_IB\_MSG\_1280 error code, 538  
ER\_IB\_MSG\_1281 error code, 538

ER\_IB\_MSG\_1282 error code, 538  
ER\_IB\_MSG\_1283 error code, 538  
ER\_IB\_MSG\_1284 error code, 538  
ER\_IB\_MSG\_1285 error code, 563  
ER\_IB\_MSG\_129 error code, 402  
ER\_IB\_MSG\_13 error code, 391  
ER\_IB\_MSG\_130 error code, 402  
ER\_IB\_MSG\_131 error code, 403  
ER\_IB\_MSG\_132 error code, 403  
ER\_IB\_MSG\_133 error code, 403  
ER\_IB\_MSG\_134 error code, 403  
ER\_IB\_MSG\_135 error code, 403  
ER\_IB\_MSG\_1357 error code, 585  
ER\_IB\_MSG\_1358 error code, 585  
ER\_IB\_MSG\_1359 error code, 585  
ER\_IB\_MSG\_136 error code, 403  
ER\_IB\_MSG\_137 error code, 403  
ER\_IB\_MSG\_1372 error code, 587  
ER\_IB\_MSG\_1373 error code, 587  
ER\_IB\_MSG\_1374 error code, 587  
ER\_IB\_MSG\_1375 error code, 587  
ER\_IB\_MSG\_138 error code, 403  
ER\_IB\_MSG\_1381 error code, 588  
ER\_IB\_MSG\_139 error code, 403  
ER\_IB\_MSG\_14 error code, 391  
ER\_IB\_MSG\_140 error code, 403  
ER\_IB\_MSG\_141 error code, 404  
ER\_IB\_MSG\_142 error code, 404  
ER\_IB\_MSG\_143 error code, 404  
ER\_IB\_MSG\_144 error code, 404  
ER\_IB\_MSG\_145 error code, 404  
ER\_IB\_MSG\_146 error code, 404  
ER\_IB\_MSG\_147 error code, 404  
ER\_IB\_MSG\_148 error code, 404  
ER\_IB\_MSG\_149 error code, 404  
ER\_IB\_MSG\_15 error code, 391  
ER\_IB\_MSG\_150 error code, 405  
ER\_IB\_MSG\_151 error code, 405  
ER\_IB\_MSG\_152 error code, 405  
ER\_IB\_MSG\_153 error code, 405  
ER\_IB\_MSG\_154 error code, 405  
ER\_IB\_MSG\_155 error code, 406  
ER\_IB\_MSG\_156 error code, 406  
ER\_IB\_MSG\_157 error code, 406  
ER\_IB\_MSG\_158 error code, 406  
ER\_IB\_MSG\_159 error code, 406  
ER\_IB\_MSG\_16 error code, 391  
ER\_IB\_MSG\_160 error code, 406  
ER\_IB\_MSG\_161 error code, 406  
ER\_IB\_MSG\_162 error code, 406  
ER\_IB\_MSG\_163 error code, 406  
ER\_IB\_MSG\_164 error code, 407  
ER\_IB\_MSG\_165 error code, 407  
ER\_IB\_MSG\_166 error code, 407









---

ER\_IB\_MSG\_556 error code, 447  
ER\_IB\_MSG\_557 error code, 447  
ER\_IB\_MSG\_558 error code, 447  
ER\_IB\_MSG\_559 error code, 447  
ER\_IB\_MSG\_56 error code, 395  
ER\_IB\_MSG\_560 error code, 447  
ER\_IB\_MSG\_561 error code, 447  
ER\_IB\_MSG\_562 error code, 447  
ER\_IB\_MSG\_563 error code, 448  
ER\_IB\_MSG\_564 error code, 448  
ER\_IB\_MSG\_565 error code, 448  
ER\_IB\_MSG\_566 error code, 448  
ER\_IB\_MSG\_567 error code, 448  
ER\_IB\_MSG\_568 error code, 448  
ER\_IB\_MSG\_569 error code, 448  
ER\_IB\_MSG\_57 error code, 395  
ER\_IB\_MSG\_570 error code, 448  
ER\_IB\_MSG\_571 error code, 448  
ER\_IB\_MSG\_572 error code, 449  
ER\_IB\_MSG\_573 error code, 449  
ER\_IB\_MSG\_574 error code, 449  
ER\_IB\_MSG\_575 error code, 449  
ER\_IB\_MSG\_576 error code, 449  
ER\_IB\_MSG\_577 error code, 449  
ER\_IB\_MSG\_578 error code, 449  
ER\_IB\_MSG\_579 error code, 449  
ER\_IB\_MSG\_57\_STAT\_SPACE\_DELETE\_FAIL error  
code, 580  
ER\_IB\_MSG\_57\_UNDO\_SPACE\_DELETE\_FAIL error  
code, 576  
ER\_IB\_MSG\_58 error code, 395  
ER\_IB\_MSG\_580 error code, 449  
ER\_IB\_MSG\_581 error code, 449  
ER\_IB\_MSG\_582 error code, 450  
ER\_IB\_MSG\_583 error code, 450  
ER\_IB\_MSG\_584 error code, 450  
ER\_IB\_MSG\_585 error code, 450  
ER\_IB\_MSG\_586 error code, 450  
ER\_IB\_MSG\_587 error code, 450  
ER\_IB\_MSG\_588 error code, 450  
ER\_IB\_MSG\_589 error code, 450  
ER\_IB\_MSG\_59 error code, 395  
ER\_IB\_MSG\_590 error code, 450  
ER\_IB\_MSG\_591 error code, 450  
ER\_IB\_MSG\_592 error code, 451  
ER\_IB\_MSG\_593 error code, 451  
ER\_IB\_MSG\_594 error code, 451  
ER\_IB\_MSG\_595 error code, 451  
ER\_IB\_MSG\_596 error code, 451  
ER\_IB\_MSG\_597 error code, 451  
ER\_IB\_MSG\_598 error code, 451  
ER\_IB\_MSG\_599 error code, 451  
ER\_IB\_MSG\_6 error code, 390  
ER\_IB\_MSG\_60 error code, 395

ER\_IB\_MSG\_600 error code, 451  
ER\_IB\_MSG\_601 error code, 451  
ER\_IB\_MSG\_602 error code, 452  
ER\_IB\_MSG\_603 error code, 452  
ER\_IB\_MSG\_604 error code, 452  
ER\_IB\_MSG\_605 error code, 452  
ER\_IB\_MSG\_606 error code, 452  
ER\_IB\_MSG\_607 error code, 452  
ER\_IB\_MSG\_608 error code, 452  
ER\_IB\_MSG\_609 error code, 452  
ER\_IB\_MSG\_61 error code, 395  
ER\_IB\_MSG\_610 error code, 452  
ER\_IB\_MSG\_611 error code, 452  
ER\_IB\_MSG\_612 error code, 453  
ER\_IB\_MSG\_613 error code, 453  
ER\_IB\_MSG\_614 error code, 453  
ER\_IB\_MSG\_615 error code, 453  
ER\_IB\_MSG\_616 error code, 453  
ER\_IB\_MSG\_617 error code, 453  
ER\_IB\_MSG\_618 error code, 453  
ER\_IB\_MSG\_619 error code, 453  
ER\_IB\_MSG\_62 error code, 396  
ER\_IB\_MSG\_620 error code, 453  
ER\_IB\_MSG\_621 error code, 453  
ER\_IB\_MSG\_622 error code, 454  
ER\_IB\_MSG\_623 error code, 454  
ER\_IB\_MSG\_624 error code, 454  
ER\_IB\_MSG\_625 error code, 454  
ER\_IB\_MSG\_626 error code, 454  
ER\_IB\_MSG\_627 error code, 454  
ER\_IB\_MSG\_628 error code, 454  
ER\_IB\_MSG\_629 error code, 454  
ER\_IB\_MSG\_63 error code, 396  
ER\_IB\_MSG\_630 error code, 454  
ER\_IB\_MSG\_631 error code, 454  
ER\_IB\_MSG\_632 error code, 455  
ER\_IB\_MSG\_633 error code, 455  
ER\_IB\_MSG\_634 error code, 455  
ER\_IB\_MSG\_635 error code, 455  
ER\_IB\_MSG\_636 error code, 455  
ER\_IB\_MSG\_637 error code, 455  
ER\_IB\_MSG\_638 error code, 455  
ER\_IB\_MSG\_639 error code, 455  
ER\_IB\_MSG\_64 error code, 396  
ER\_IB\_MSG\_640 error code, 455  
ER\_IB\_MSG\_641 error code, 456  
ER\_IB\_MSG\_642 error code, 456  
ER\_IB\_MSG\_643 error code, 456  
ER\_IB\_MSG\_644 error code, 456  
ER\_IB\_MSG\_645 error code, 456  
ER\_IB\_MSG\_646 error code, 456  
ER\_IB\_MSG\_647 error code, 456  
ER\_IB\_MSG\_648 error code, 456  
ER\_IB\_MSG\_649 error code, 456









---

ER\_IB\_MSG\_941 error code, 488  
ER\_IB\_MSG\_942 error code, 488  
ER\_IB\_MSG\_943 error code, 488  
ER\_IB\_MSG\_944 error code, 488  
ER\_IB\_MSG\_945 error code, 488  
ER\_IB\_MSG\_946 error code, 488  
ER\_IB\_MSG\_947 error code, 489  
ER\_IB\_MSG\_948 error code, 489  
ER\_IB\_MSG\_949 error code, 489  
ER\_IB\_MSG\_95 error code, 399  
ER\_IB\_MSG\_950 error code, 489  
ER\_IB\_MSG\_951 error code, 489  
ER\_IB\_MSG\_952 error code, 489  
ER\_IB\_MSG\_953 error code, 489  
ER\_IB\_MSG\_954 error code, 489  
ER\_IB\_MSG\_955 error code, 489  
ER\_IB\_MSG\_956 error code, 489  
ER\_IB\_MSG\_957 error code, 490  
ER\_IB\_MSG\_958 error code, 490  
ER\_IB\_MSG\_959 error code, 490  
ER\_IB\_MSG\_96 error code, 399  
ER\_IB\_MSG\_960 error code, 490  
ER\_IB\_MSG\_961 error code, 490  
ER\_IB\_MSG\_962 error code, 490  
ER\_IB\_MSG\_963 error code, 490  
ER\_IB\_MSG\_964 error code, 490  
ER\_IB\_MSG\_965 error code, 490  
ER\_IB\_MSG\_966 error code, 490  
ER\_IB\_MSG\_967 error code, 491  
ER\_IB\_MSG\_968 error code, 491  
ER\_IB\_MSG\_969 error code, 491  
ER\_IB\_MSG\_97 error code, 399  
ER\_IB\_MSG\_970 error code, 491  
ER\_IB\_MSG\_971 error code, 491  
ER\_IB\_MSG\_972 error code, 491  
ER\_IB\_MSG\_973 error code, 491  
ER\_IB\_MSG\_974 error code, 491  
ER\_IB\_MSG\_975 error code, 491  
ER\_IB\_MSG\_976 error code, 491  
ER\_IB\_MSG\_977 error code, 492  
ER\_IB\_MSG\_978 error code, 492  
ER\_IB\_MSG\_979 error code, 492  
ER\_IB\_MSG\_98 error code, 399  
ER\_IB\_MSG\_980 error code, 492  
ER\_IB\_MSG\_981 error code, 492  
ER\_IB\_MSG\_982 error code, 492  
ER\_IB\_MSG\_983 error code, 492  
ER\_IB\_MSG\_984 error code, 492  
ER\_IB\_MSG\_985 error code, 492  
ER\_IB\_MSG\_986 error code, 492  
ER\_IB\_MSG\_987 error code, 493  
ER\_IB\_MSG\_988 error code, 493  
ER\_IB\_MSG\_989 error code, 493  
ER\_IB\_MSG\_99 error code, 399

ER\_IB\_MSG\_990 error code, 493  
ER\_IB\_MSG\_991 error code, 493  
ER\_IB\_MSG\_992 error code, 493  
ER\_IB\_MSG\_993 error code, 493  
ER\_IB\_MSG\_994 error code, 493  
ER\_IB\_MSG\_995 error code, 493  
ER\_IB\_MSG\_996 error code, 493  
ER\_IB\_MSG\_997 error code, 494  
ER\_IB\_MSG\_998 error code, 494  
ER\_IB\_MSG\_999 error code, 494  
ER\_IB\_MSG\_ABORTING\_LOG\_ARCHIVER error code,  
643  
ER\_IB\_MSG\_BAD\_DBLWR\_FILE\_NAME error code,  
577  
ER\_IB\_MSG\_BTREE\_LEVEL\_LIMIT\_EXCEEDED error  
code, 566  
ER\_IB\_MSG\_BUF\_PENDING\_IO error code, 506  
ER\_IB\_MSG\_BUF\_PENDING\_IO\_ON\_SHUTDOWN  
error code, 523  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_CODE\_STATUS  
error code, 627  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_COMPLETE\_CUR\_CODE  
error code, 627  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_PROGRESS\_UPDATE  
error code, 627  
ER\_IB\_MSG\_CANNOT\_FIND\_DD\_UNDO\_SPACE error  
code, 582  
ER\_IB\_MSG\_CANNOT\_OPEN\_57\_UNDO error code,  
503  
ER\_IB\_MSG\_CANT\_DECRYPT\_REDO\_LOG error  
code, 478  
ER\_IB\_MSG\_CANT\_ENCRYPT\_REDO\_LOG\_DATA  
error code, 478  
ER\_IB\_MSG\_CLEAR\_INSTANT\_DROP\_COLUMN\_METADATA  
error code, 626  
ER\_IB\_MSG\_CLOCK\_GETTIME\_FAILED error code,  
563  
ER\_IB\_MSG\_CLOCK\_MONOTONIC\_UNSUPPORTED  
error code, 563  
ER\_IB\_MSG\_CLONE\_DDL\_APPLY error code, 607  
ER\_IB\_MSG\_CLONE\_DDL\_INVALIDATE error code,  
607  
ER\_IB\_MSG\_CLONE\_DDL\_NTFN error code, 607  
ER\_IB\_MSG\_CREATED\_UNDO\_SPACE error code,  
591  
ER\_IB\_MSG\_CREATE\_LOG\_FILE error code, 580  
ER\_IB\_MSG\_DATA\_DIRECTORY\_NOT\_INITIALIZED\_OR\_COR  
error code, 509  
ER\_IB\_MSG\_DBLWR\_1285 error code, 576  
ER\_IB\_MSG\_DBLWR\_1286 error code, 576  
ER\_IB\_MSG\_DBLWR\_1287 error code, 576  
ER\_IB\_MSG\_DBLWR\_1288 error code, 576  
ER\_IB\_MSG\_DBLWR\_1290 error code, 576  
ER\_IB\_MSG\_DBLWR\_1291 error code, 576

---

ER_IB_MSG_DBLWR_1292 error code, 577	ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR error code, 544
ER_IB_MSG_DBLWR_1293 error code, 577	ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT error code, 544
ER_IB_MSG_DBLWR_1294 error code, 577	ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE error code, 545
ER_IB_MSG_DBLWR_1295 error code, 577	ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE error code, 544
ER_IB_MSG_DBLWR_1296 error code, 577	ER_IB_MSG_FILE_RESIZE error code, 500
ER_IB_MSG_DBLWR_1297 error code, 577	ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME error code, 574
ER_IB_MSG_DBLWR_1298 error code, 577	ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH error code, 574
ER_IB_MSG_DBLWR_1300 error code, 577	ER_IB_MSG_FIL_STATE_MOVED_CORRECTED error code, 574
ER_IB_MSG_DBLWR_1301 error code, 577	ER_IB_MSG_FIL_STATE_MOVED_PREV error code, 642
ER_IB_MSG_DBLWR_1304 error code, 578	ER_IB_MSG_FIL_STATE_MOVED_PREV_OR_HAS_DATADIR error code, 642
ER_IB_MSG_DBLWR_1305 error code, 578	ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY error code, 574
ER_IB_MSG_DBLWR_1306 error code, 578	ER_IB_MSG_FOUND_WRONG_UNDO_SPACE error code, 545
ER_IB_MSG_DBLWR_1307 error code, 578	ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR error code, 430
ER_IB_MSG_DBLWR_1308 error code, 578	ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN error code, 580
ER_IB_MSG_DBLWR_1309 error code, 578	ER_IB_MSG_IGNORE_SCAN_PATH error code, 428
ER_IB_MSG_DBLWR_1310 error code, 578	ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR error code, 430
ER_IB_MSG_DBLWR_1311 error code, 578	ER_IB_MSG_INCORRECT_SIZE error code, 590
ER_IB_MSG_DBLWR_1312 error code, 578	ER_IB_MSG_INJECT_CRASH error code, 589
ER_IB_MSG_DBLWR_1313 error code, 578	ER_IB_MSG_INJECT_FAILURE error code, 589
ER_IB_MSG_DBLWR_1314 error code, 579	ER_IB_MSG_INNODB_END_INITIALIZE error code, 581
ER_IB_MSG_DBLWR_1315 error code, 579	ER_IB_MSG_INNODB_START_INITIALIZE error code, 581
ER_IB_MSG_DBLWR_1316 error code, 579	ER_IB_MSG_INVALID_LOCATION_FOR_TABLE error code, 448
ER_IB_MSG_DBLWR_1317 error code, 579	ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE error code, 582
ER_IB_MSG_DBLWR_1318 error code, 579	ER_IB_MSG_INVALID_LOCATION_WRONG_DB error code, 582
ER_IB_MSG_DBLWR_1319 error code, 579	ER_IB_MSG_INVALID_PAGE_TYPE error code, 628
ER_IB_MSG_DBLWR_1320 error code, 579	ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS error code, 546
ER_IB_MSG_DBLWR_1321 error code, 579	ER_IB_MSG_LOG_CHECKPOINT_FOUND error code, 618
ER_IB_MSG_DBLWR_1322 error code, 579	ER_IB_MSG_LOG_CORRUPT error code, 462
ER_IB_MSG_DBLWR_1323 error code, 579	ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY error code, 522
ER_IB_MSG_DBLWR_1324 error code, 580	ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED error code, 619
ER_IB_MSG_DBLWR_1325 error code, 580	ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE error code, 466
ER_IB_MSG_DBLWR_1326 error code, 580	
ER_IB_MSG_DBLWR_1327 error code, 580	
ER_IB_MSG_DDL_FAIL_NO_BUILDER error code, 641	
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK error code, 457	
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT error code, 560	
ER_IB_MSG_DDL_LOG_FAIL_POST_DDL error code, 560	
ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACE error code, 546	
ER_IB_MSG_DICT_PARTITION_NOT_FOUND error code, 575	
ER_IB_MSG_DIR_DOES_NOT_EXIST error code, 546	
ER_IB_MSG_DOWNGRADE_PARTITION_FILE error code, 574	
ER_IB_MSG_DROPPED_UNDO_SPACE error code, 591	
ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE error code, 544	
ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR error code, 544	

---

---

ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY error code, 616	ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE error code, 619
ER_IB_MSG_LOG_FILES_CREATED_BY_MEB error code, 466	ER_IB_MSG_LOG_FILE_MISSING_FOR_ID error code, 618
ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY error code, 466	ER_IB_MSG_LOG_FILE_OPEN_FAILED error code, 502
ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATE error code, 620	ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED error code, 500
ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY error code, 501	ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED error code, 501
ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES error code, 509	ER_IB_MSG_LOG_FILE_REMOVE_FAILED error code, 619
ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED error code, 522	ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED error code, 619
ER_IB_MSG_LOG_FILES_FOUND_MISSING error code, 620	ER_IB_MSG_LOG_FILE_RESIZE_FAILED error code, 501
ER_IB_MSG_LOG_FILES_INITIALIZED error code, 501	ER_IB_MSG_LOG_FILE_SIZE_INVALID error code, 509
ER_IB_MSG_LOG_FILES_INVALID_SET error code, 509	ER_IB_MSG_LOG_FILE_TOO_BIG error code, 615
ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED error code, 619	ER_IB_MSG_LOG_FILE_TOO_SMALL error code, 615
ER_IB_MSG_LOG_FILES_RESIZE_FINISHED error code, 619	ER_IB_MSG_LOG_FILE_TRUNCATE error code, 621
ER_IB_MSG_LOG_FILES_RESIZE_ON_START error code, 519	ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED error code, 621
ER_IB_MSG_LOG_FILES_RESIZE_ON_START_FAILED error code, 618	ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED error code, 621
ER_IB_MSG_LOG_FILES_RESIZE_ON_START_IN_READ_ONLY error code, 510	ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED error code, 621
ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED error code, 619	ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED error code, 621
ER_IB_MSG_LOG_FILES_REWRITING error code, 510	ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9 error code, 525
ER_IB_MSG_LOG_FILES_UPGRADE error code, 619	ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30 error code, 463
ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS error code, 620	ER_IB_MSG_LOG_FORMAT_NOT_SUPPORTED error code, 466
ER_IB_MSG_LOG_FILE_FOREIGN_UUID error code, 618	ER_IB_MSG_LOG_FORMAT_OLD error code, 466
ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW error code, 620	ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED error code, 462
ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD error code, 620	ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN error code, 462
ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN error code, 463	ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED error code, 616
ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM error code, 524	ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR error code, 616
ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED error code, 615	ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE error code, 616
ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES error code, 618	ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_UNSAFE error code, 525
ER_IB_MSG_LOG_FILE_INVALID_START_LSN error code, 618	ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED error code, 621
ER_IB_MSG_LOG_FILE_IS_EMPTY error code, 615	ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED error code, 617
ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED error code, 621	ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE error code, 621

---

---

ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED error code, 617	ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG error code, 605
ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED error code, 620	ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER error code, 560
ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED error code, 620	ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT error code, 560
ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0 error code, 620	ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE_CLEAN error code, 467
ER_IB_MSG_LOG_UPGRADE_CLONED_DB error code, 617	ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND error code, 463
ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED error code, 617	ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE error code, 616
ER_IB_MSG_LOG_UPGRADE_FLUSH_FAILED__UNEXPECTED error code, 618	ER_IB_MSG_RECOVERY_CORRUPT error code, 510
ER_IB_MSG_LOG_UPGRADE_FORCED_RECV error code, 617	ER_IB_MSG_RECOVERY_IN_READ_ONLY error code, 467
ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE error code, 617	ER_IB_MSG_RECOVERY_IS_NEEDED error code, 467
ER_IB_MSG_LOG_UPGRADE_NON_PERSISTED_DD_METADATA error code, 618	ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__SKIP_IBU error code, 604
ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES error code, 617	ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__UNEXPECTED error code, 604
ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER error code, 521	ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE error code, 465
ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN error code, 616	ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY error code, 604
ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN error code, 617	ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY error code, 604
ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE error code, 521	ER_IB_MSG_RESUME_OP_FOR_SPACE error code, 538
ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER error code, 521	ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR error code, 586
ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER error code, 625	ER_IB_MSG_SDI_Z_STREAM_ERROR error code, 544
ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE error code, 616	ER_IB_MSG_SDI_Z_UNKNOWN_ERROR error code, 545
ER_IB_MSG_LOG_WRITER_WRITE_FAILED error code, 616	ER_IB_MSG_SKIP_HIDDEN_DIR error code, 572
ER_IB_MSG_MADVISE_FAILED error code, 543	ER_IB_MSG_STATS_SAMPLING_TOO_LARGE error code, 596
ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED error code, 543	ER_IB_MSG_THREAD_CONCURRENCY_CHANGED error code, 525
ER_IB_MSG_MASTER_KEY_ROTATED error code, 591	ER_IB_MSG_TOO_LONG_PATH error code, 562
ER_IB_MSG_MAX_UNDO_SPACES_REACHED error code, 544	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED error code, 516
ER_IB_MSG_NOT_END_WITH_IBU error code, 545	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED error code, 584
ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND error code, 538	ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME error code, 612
ER_IB_MSG_NUM_POOLS error code, 544	ER_IB_MSG_UNDO_ALTERED_ACTIVE error code, 589
ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS error code, 581	ER_IB_MSG_UNDO_ALTERED_INACTIVE error code, 589
ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION error code, 625	ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED error code, 607
ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG error code, 605	ER_IB_MSG_UNDO_INJECT_CRASH error code, 589
	ER_IB_MSG_UNDO_INJECT_FAILURE error code, 589
	ER_IB_MSG_UNDO_MARKED_ACTIVE error code, 588

---

---

ER_IB_MSG_UNDO_MARKED_EMPTY error code, 589	ER_IB_RESURRECT_RECORD_COMPLETE error code, 636
ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE error code, 513	ER_IB_RESURRECT_RECORD_PROGRESS error code, 636
ER_IB_MSG_UNDO_TRUNCATE_COMPLETE error code, 514	ER_IB_RESURRECT_TRX_INSERT error code, 635
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE error code, 589	ER_IB_RESURRECT_TRX_INSERT_COMPLETE error code, 636
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE error code, 514	ER_IB_RESURRECT_TRX_UPDATE error code, 635
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE error code, 514	ER_IB_RESURRECT_TRX_UPDATE_COMPLETE error code, 636
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL error code, 589	ER_IB_SELECT_COUNT_STAR error code, 634
ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG error code, 513	ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED error code, 584
ER_IB_MSG_UNDO_TRUNCATE_START error code, 513	ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY error code, 586
ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN error code, 582	ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE error code, 586
ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING error code, 545	ER_IB_WARN_ACCESSING_NONEXISTING_SPACE error code, 419
ER_IB_MSG_UNDO_TRUNC_BEFORE_DD_UPDATE error code, 545	ER_IB_WARN_MANY_NON_LRU_FILES_OPENED error code, 612
ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE error code, 545	ER_IB_WARN_OPEN_PARTITION_FILE error code, 574
ER_IB_MSG_UNDO_TRUNC_BEFORE_RSEG error code, 545	ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH error code, 608
ER_IB_MSG_UNEXPECTED_FILE_EXISTS error code, 421	ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE error code, 598
ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED error code, 426	ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED error code, 583
ER_IB_MSG_UPGRADE_PARTITION_FILE error code, 574	ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY error code, 632
ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT error code, 574	ER_IB_WRN_OLD_GEOMETRY_TYPE error code, 599
ER_IB_MSG_USING_UNDO_SPACE error code, 544	ER_IB_WRN_PAGE_ARCH_FLUSH_DATA error code, 581
ER_IB_MSG_WAITING_ON_LAGGING_REDO_LOG_CONSUMED error code, 643	ER_IB_WRN_REDO_DISABLED error code, 583
ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD error code, 537	ER_IB_WRN_REDO_ENABLED error code, 584
ER_IB_MSG_WRONG_TABLESPACE_DIR error code, 546	ER_IB_WARN_IDENTIFIED_BY_UNSUPPORTED error code, 149
ER_IB_PARALLEL_READER_WORKER_INFO error code, 628	ER_IDENT_CAUSES_TOO_LONG_PATH error code, 65
ER_IB_PRIMARY_KEY_IS_INSTANT error code, 632	ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE error code, 568
ER_IB_RDBLWR_BYTES_INFO error code, 615	ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DIFFERENT_SCHEMA error code, 155
ER_IB_RECV_FIRST_REC_GROUP_INVALID error code, 562	ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FCT_NAME error code, 155
ER_IB_RELOCK_LATCH_ORDER_VIOLATION error code, 585	ER_ILLEGAL_GRANT_FOR_TABLE error code, 13
ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK error code, 635	ER_ILLEGAL_HA error code, 5
ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK error code, 635	ER_ILLEGAL_HA_CREATE_OPTION error code, 36
	ER_ILLEGAL_PRIVILEGE_LEVEL error code, 98
	ER_ILLEGAL_REFERENCE error code, 21
	ER_ILLEGAL_USER_VAR error code, 74
	ER_ILLEGAL_VALUE_FOR_TYPE error code, 29
	ER_IMPLICIT_COMPARISON_FOR_JSON error code, 140

---

---

ER_IMPOSSIBLE_STRING_CONVERSION error code, 140	ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR error code, 274
ER_IMP_INCOMPATIBLE_CFG_VERSION error code, 135	ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD error code, 274
ER_IMP_INCOMPATIBLE_DD_VERSION error code, 98	ER_INNODB_CANT_OPEN_TABLE error code, 274
ER_IMP_INCOMPATIBLE_MYSQLD_VERSION error code, 97	ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK error code, 274
ER_IMP_INCOMPATIBLE_SDI_VERSION error code, 98	ER_INNODB_CLUSTERED_INDEX_PRIVATE error code, 275
ER_IMP_NO_FILES_MATCHED error code, 97	ER_INNODB_COMPRESSION_FAILURE error code, 146
ER_IMP_SCHEMA_DOES_NOT_EXIST error code, 97	ER_INNODB_DIFF_IN_REF_LEN error code, 295
ER_IMP_TABLE_ALREADY_EXISTS error code, 97	ER_INNODB_DIRTY_WATER_MARK_NOT_LOW error code, 273
ER_INCONSISTENT_ERROR error code, 528	ER_INNODB_ERROR_LOGGER_FATAL_MSG error code, 297
ER_INCONSISTENT_PARTITION_INFO_ERROR error code, 37	ER_INNODB_ERROR_LOGGER_MSG error code, 297
ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR error code, 37	ER_INNODB_FAILED_TO_FIND_IDX error code, 294
ER_INCORRECT_CURRENT_PASSWORD error code, 129	ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE error code, 294
ER_INCORRECT_GLOBAL_LOCAL_VAR error code, 21	ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO error code, 294
ER_INCORRECT_TYPE error code, 74	ER_INNODB_FILES_SAME error code, 274
ER_INDEX_COLUMN_TOO_LONG error code, 51	ER_INNODB_FORCED_RECOVERY error code, 67
ER_INDEX_CORRUPT error code, 52	ER_INNODB_FT_AUX_NOT_HEX_ID error code, 67
ER_INDEX_OTHER_THAN_PK error code, 158	ER_INNODB_FT_LIMIT error code, 59
ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX error code, 110	ER_INNODB_FT_WRONG_DOCID_COLUMN error code, 59
ER_INFORMATION_SCHEMA_VERSION_CHANGE error code, 641	ER_INNODB_FT_WRONG_DOCID_INDEX error code, 60
ER_INIT_BOOTSTRAP_COMPLETE error code, 215	ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL error code, 295
ER_INIT_CANT_OPEN_BOOTSTRAP_FILE error code, 215	ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL error code, 295
ER_INIT_CREATING_DD error code, 215	ER_INNODB_INDEX_COLUMN_CNT_DIFF error code, 295
ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE error code, 215	ER_INNODB_ILLEGAL_COLON_IN_POOL error code, 273
ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE error code, 215	ER_INNODB_IMPORT_ERROR error code, 61
ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE error code, 215	ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE error code, 145
ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE error code, 215	ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS error code, 274
ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD error code, 571	ER_INNODB_INDEX_CORRUPT error code, 61
ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT error code, 215	ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTED_MAX_SIZE error code, 161
ER_INIT_ROOT_WITHOUT_PASSWORD error code, 215	ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_FIELDS error code, 161
ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED error code, 294	ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_SIZE error code, 154
ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE error code, 145	ER_INNODB_INTERNAL_INDEX error code, 295
ER_INNODB_CANNOT_BE_IGNORED error code, 107	ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE error code, 145
ER_INNODB_CANNOT_CREATE_TABLE error code, 295	ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY error code, 273

---



---

ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOCATION error code, 547	ER_INNODB_TRX_XLATION_TABLE_OOM error code, 274
ER_INNODB_INVALID_LOG_GROUP_HOME_DIR error code, 273	ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT error code, 581
ER_INNODB_INVALID_MONITOR_COUNTER_NAME error code, 296	ER_INNODB_UNDO_LOG_FULL error code, 70
ER_INNODB_INVALID_PAGE_SIZE error code, 273	ER_INNODB_UNKNOWN_COLLATION error code, 273
ER_INNODB_IO_CAPACITY_EXCEEDS_MAX error code, 274	ER_INNODB_UNREGISTERED_TRX_ACTIVE error code, 274
ER_INNODB_IO_WRITE_ERROR_RETRYING error code, 592	ER_INNODB_USE_MONITOR_GROUP_NAME error code, 295
ER_INNODB_IO_WRITE_FAILED error code, 592	ER_INSECURE_CHANGE_MASTER error code, 56
ER_INNODB_MANDATORY error code, 171	ER_INSECURE_CHANGE_SOURCE error code, 56
ER_INNODB_MAX_ROW_VERSION error code, 153	ER_INSECURE_PLAIN_TEXT error code, 56
ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED error code, 296	ER_INSERT_INFO error code, 9
ER_INNODB_MONITOR_IS_ENABLED error code, 296	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT error code, 49
ER_INNODB_NO_FT_TEMP_TABLE error code, 59	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT error code, 49
ER_INNODB_ONLINE_LOG_TOO_BIG error code, 60	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG_BIN error code, 50
ER_INNODB_OUT_OF_RESOURCES error code, 575	ER_INSTALL_COMPONENT_SET_NULL_VALUE error code, 161
ER_INNODB_PARTITION_TABLE_LOWERCASED error code, 275	ER_INSTALL_COMPONENT_SET_UNUSED_VALUE error code, 161
ER_INNODB_PK_NOT_IN_MYSQL error code, 275	ER_INSTALL_PLUGIN_CONFLICT_CLIENT error code, 148
ER_INNODB_PK_ONLY_IN_MYSQL error code, 275	ER_INSTALL_PLUGIN_CONFLICT_LOG error code, 603
ER_INNODB_READ_ONLY error code, 66	ER_INTERNAL_ERROR error code, 61
ER_INNODB_REDO_ARCHIVING_ENABLED error code, 140	ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED error code, 157
ER_INNODB_REDO_DISABLED error code, 140	ER_INVALID_ADMIN_ADDRESS error code, 549
ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE error code, 124	ER_INVALID_ARGUMENT_FOR_LOGARITHM error code, 70
ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID error code, 123	ER_INVALID_ASSIGNMENT_TARGET error code, 148
ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH error code, 124	ER_INVALID_AUTHENTICATION_POLICY error code, 608
ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY error code, 123	ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE error code, 88
ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS error code, 124	ER_INVALID_BITWISE_OPERANDS_SIZE error code, 88
ER_INNODB_REDO_LOG_ARCHIVE_FAILED error code, 124	ER_INVALID_CAST error code, 141
ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE error code, 124	ER_INVALID_CAST_POLYGON_RING_DIRECTION error code, 146
ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE error code, 124	ER_INVALID_CAST_TO_GEOMETRY error code, 146
ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND error code, 123	ER_INVALID_CAST_TO_JSON error code, 82
ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR error code, 124	ER_INVALID_CHARACTER_STRING error code, 25
ER_INNODB_REDO_LOG_ARCHIVE_SESSION error code, 124	ER_INVALID_CHARSET_AND_DEFAULT_IS_MB error code, 199
ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH error code, 123	ER_INVALID_COLLATION_FOR_CHARSET error code, 281
ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT error code, 123	ER_INVALID_DD_OBJECT error code, 88
	ER_INVALID_DD_OBJECT_ID error code, 88
	ER_INVALID_DD_OBJECT_NAME error code, 88

---

---

ER_INVALID_DEFAULT error code, 8	ER_INVALID_PLUGIN_FOR_REGISTRATION error code, 149
ER_INVALID_DEFAULT_UTF8MB4_COLLATION error code, 109	ER_INVALID_PROPERTY_KEY error code, 552
ER_INVALID_ENCRYPTION_OPTION error code, 85	ER_INVALID_REPLICATION_TIMESTAMPS error code, 283
ER_INVALID_ENCRYPTION_REQUEST error code, 121	ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN error code, 74
ER_INVALID_ERROR_LOG_NAME error code, 182	ER_INVALID_SERVER_DOWNGRADE_NOT_PATCH error code, 640
ER_INVALID_FIELD_SIZE error code, 69	ER_INVALID_SERVER_UPGRADE_NOT_LTS error code, 640
ER_INVALID_GEOJSON_CRS_NOT_TOP_LEVEL error code, 104	ER_INVALID_THREAD_ID error code, 103
ER_INVALID_GEOJSON_MISSING_MEMBER error code, 74	ER_INVALID_THREAD_PRIORITY error code, 102
ER_INVALID_GEOJSON_UNSPECIFIED error code, 74	ER_INVALID_TIME_ZONE_INTERVAL error code, 141
ER_INVALID_GEOJSON_WRONG_TYPE error code, 74	ER_INVALID_TLS_VERSION error code, 613
ER_INVALID_GROUP_FUNC_USE error code, 11	ER_INVALID_TYPE_FOR_JSON error code, 82
ER_INVALID_INFO_IN_FRM error code, 200	ER_INVALID_USER_ATTRIBUTE_JSON error code, 139
ER_INVALID_INSTRUMENT error code, 171	ER_INVALID_USER_FOR_REGISTRATION error code, 150
ER_INVALID_JSON_ATTRIBUTE error code, 139	ER_INVALID_USE_OF_FORCE_OPTION error code, 103
ER_INVALID_JSON_BINARY_DATA error code, 82	ER_INVALID_USE_OF_NULL error code, 13
ER_INVALID_JSON_CHARSET error code, 82	ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY error code, 166
ER_INVALID_JSON_CHARSET_IN_FUNCTION error code, 82	ER_INVALID_VALUE_OF_BIND_ADDRESSES error code, 539
ER_INVALID_JSON_DATA error code, 74	ER_INVALID_VCPU_ID error code, 102
ER_INVALID_JSON_PATH error code, 82	ER_INVALID_VCPU_RANGE error code, 102
ER_INVALID_JSON_PATH_ARRAY_CELL error code, 84	ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER error code, 581
ER_INVALID_JSON_PATH_CHARSET error code, 82	ER_INVALID_YEAR_COLUMN_LENGTH error code, 62
ER_INVALID_JSON_PATH_WILDCARD error code, 82	ER_IO_ERR_LOG_INDEX_READ error code, 30
ER_INVALID_JSON_TEXT error code, 82	ER_IO_ERR_READ_ERROR error code, 61
ER_INVALID_JSON_TEXT_IN_PARAM error code, 82	ER_IO_WRITE_ERROR error code, 61
ER_INVALID_JSON_TYPE error code, 124	ER_IPSOCK_ERROR error code, 9
ER_INVALID_JSON_VALUE_FOR_CAST error code, 83	ER_IS_QUERY_INVALID_CLAUSE error code, 91
ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX error code, 130	ER_I_S_SKIPPED_TABLESPACE error code, 101
ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER error code, 150	ER_JSON_BAD_ONE_OR_ALL_ARG error code, 83
ER_INVALID_MFA_PLUGIN_SPECIFIED error code, 149	ER_JSON_DOCUMENT_NULL_KEY error code, 83
ER_INVALID_MULTIPLE_CLAUSES error code, 122	ER_JSON_DOCUMENT_TOO_DEEP error code, 83
ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP error code, 556	ER_JSON_KEY_TOO_BIG error code, 82
ER_INVALID_NO_OF_ARGS error code, 96	ER_JSON_PARSE_ERROR error code, 185
ER_INVALID_ON_UPDATE error code, 25	ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED_RE error code, 134
ER_INVALID_OPTION_CHARACTERS error code, 92	ER_JSON_USED_AS_KEY error code, 83
ER_INVALID_OPTION_END_CHARACTER error code, 92	ER_JSON_VACUOUS_PATH error code, 83
ER_INVALID_OPTION_KEY error code, 91	ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX error code, 130
ER_INVALID_OPTION_KEY_VALUE_PAIR error code, 92	ER_JSON_VALUE_TOO_BIG error code, 82
ER_INVALID_OPTION_START_CHARACTER error code, 92	ER_JT_MAX_NESTED_PATH error code, 104
ER_INVALID_OPTION_VALUE error code, 92	ER_JT_VALUE_OUT_OF_RANGE error code, 104
ER_INVALID_OR_OLD_TABLE_OR_DB_NAME error code, 223	ER_KERBEROS_CREATE_USER error code, 148
ER_INVALID_PARAMETER_USE error code, 141	ER_KEYCACHE_OOM error code, 174

---

---

ER_KEYRING_ACCESS_DENIED_ERROR error code, 86	ER_KEYRING_AWS_INVALID_CONF_FILE_PATH error code, 339
ER_KEYRING_AWS_CMK_ID_NOT_SET error code, 340	ER_KEYRING_AWS_INVALID_DATA_FILE_PATH error code, 339
ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE error code, 340	ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER error code, 340
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF error code, 339	ER_KEYRING_AWS_UDF_AWS_KMS_ERROR error code, 86
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF error code, 339	ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID error code, 332
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE error code, 340	ER_KEYRING_INVALID_KEY_FAILED_DUE_TO_INVALID_KEY error code, 332
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR error code, 339	ER_KEYRING_INVALID_COMPONENT_EXCEPTION error code, 597
ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS error code, 341	ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR error code, 597
ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY error code, 342	ER_KEYRING_COMPONENT_NOT_INITIALIZED error code, 597
ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY error code, 342	ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED error code, 337
ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE error code, 341	ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED error code, 337
ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_KEYRING_ERROR error code, 341	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING error code, 338
ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY error code, 341	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING error code, 337
ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIALS error code, 340	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING error code, 337
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR error code, 340	ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP error code, 337
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_ERROR error code, 340	ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_INTERNAL_ERROR error code, 338
ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE error code, 339	ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE error code, 337
ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP error code, 341	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR error code, 338
ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY error code, 342	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE error code, 338
ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK error code, 342	ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR error code, 338
ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID error code, 338	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID error code, 338
ER_KEYRING_AWS_FAILED_TO_SET_REGION error code, 339	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG error code, 338
ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE error code, 341	ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR error code, 331
ER_KEYRING_AWS_INCORRECT_FILE error code, 341	ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE error code, 332
ER_KEYRING_AWS_INCORRECT_PROXY error code, 569	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING error code, 333
ER_KEYRING_AWS_INCORRECT_REGION error code, 341	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP error code, 333
ER_KEYRING_AWS_INIT_FAILURE error code, 340	ER_KEYRING_FAILED_TO_GENERATE_KEY error code, 332

---

---

ER_KEYRING_FAILED_TO_GET_FILE_STAT error code, 332	ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT error code, 335
ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT error code, 333	ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER error code, 335
ER_KEYRING_FAILED_TO_REMOVE_FILE error code, 333	ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID error code, 335
ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_KEYRING error code, 334	ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE error code, 336
ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP error code, 332	ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE error code, 335
ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA error code, 333	ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY error code, 335
ER_KEYRING_FAILED_TO_TRUNCATE_FILE error code, 333	ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY error code, 336
ER_KEYRING_FILE_INIT_FAILED error code, 331	ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE error code, 336
ER_KEYRING_FILE_IO_ERROR error code, 333	ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE error code, 336
ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE error code, 332	ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE error code, 337
ER_KEYRING_INCORRECT_FILE error code, 332	ER_KEYRING_OKV_FAILED_TO_STORE_KEY error code, 336
ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT error code, 331	ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY error code, 336
ER_KEYRING_INVALID_KEY_LENGTH error code, 331	ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED error code, 334
ER_KEYRING_INVALID_KEY_TYPE error code, 331	ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONFIG error code, 334
ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEYRING error code, 333	ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR error code, 334
ER_KEYRING_LOGGER_ERROR_MSG error code, 314	ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER error code, 334
ER_KEYRING_MIGRATE_FAILED error code, 527	ER_KEYRING_OKV_INVALID_KEY_TYPE error code, 334
ER_KEYRING_MIGRATION_EXTRA_OPTIONS error code, 389	ER_KEYRING_OKV_KEY_MISMATCH error code, 337
ER_KEYRING_MIGRATION_FAILED error code, 299	ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED error code, 613
ER_KEYRING_MIGRATION_FAILURE error code, 86	ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR error code, 332
ER_KEYRING_MIGRATION_STATUS error code, 86	ER_KEYRING_UDF_KEYRING_SERVICE_ERROR error code, 85
ER_KEYRING_MIGRATION_SUCCESSFUL error code, 299	ER_KEYRING_UNKNOWN_ERROR error code, 333
ER_KEYRING_OCI_HTTP_REQUEST error code, 627	ER_KEY_COLUMN_DOES_NOT_EXISTS error code, 8
ER_KEYRING_OCI_INVALID_JSON error code, 627	ER_KEY_DOES_NOT_EXISTS error code, 15
ER_KEYRING_OCI_PARSE_JSON error code, 627	ER_KEY_NOT_FOUND error code, 5
ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED error code, 335	ER_KEY_PART_0 error code, 30
ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS error code, 336	ER_KEY_REF_DO_NOT_MATCH_TABLE_REF error code, 11
ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE error code, 335	ER_KILLED_THREADS_OF_PLUGIN error code, 217
ER_KEYRING_OKV_FAILED_TO_FETCH_KEY error code, 336	ER_KILLING_THREAD error code, 216
ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY error code, 334	ER_KILL_DENIED_ERROR error code, 10
ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY error code, 335	ER_LCTN_CHANGED error code, 299
ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY error code, 336	ER_LCTN_NOT_FOUND error code, 527
ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR error code, 334	

---

---

ER_LDAP_AUTH_CERTIFICATE_NAME error code, 382	ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET error code, 381
ER_LDAP_AUTH_COMMUNICATION_HOST_INFO error code, 385	ER_LDAP_AUTH_FREEING_CONNECTION error code, 385
ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER error code, 385	ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL error code, 384
ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL error code, 385	ER_LDAP_AUTH_GRP_DN_PARSING_FAILED error code, 554
ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED error code, 383	ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE error code, 554
ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER error code, 387	ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS error code, 554
ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL error code, 385	ER_LDAP_AUTH_GRP_IS_FULL_DN error code, 382
ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING error code, 381	ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE error code, 554
ER_LDAP_AUTH_CONN_POOL_INITIALIZING error code, 381	ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO error code, 554
ER_LDAP_AUTH_CONN_POOL_NOT_CREATED error code, 381	ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL error code, 553
ER_LDAP_AUTH_CREATE_CONNECTION_KEY error code, 385	ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL error code, 382
ER_LDAP_AUTH_CREATING_LDAP_CONNECTION error code, 384	ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO error code, 554
ER_LDAP_AUTH_DEINIT_FAILED error code, 380	ER_LDAP_AUTH_INFO_FOR_USER error code, 381
ER_LDAP_AUTH_DELETING_CONNECTION_KEY error code, 385	ER_LDAP_AUTH_INIT_FAILED error code, 386
ER_LDAP_AUTH_DISTINGUISHED_NAME error code, 386	ER_LDAP_AUTH_LDAPS error code, 554
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION error code, 387	ER_LDAP_AUTH_LDAP_INFO_NULL error code, 384
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT error code, 380	ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT error code, 384
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATOR error code, 380	ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED error code, 384
ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION error code, 380	ER_LDAP_AUTH_METHOD_TO_CLIENT error code, 386
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY error code, 383	ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED error code, 386
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONSTRUCT_STATE error code, 383	ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET error code, 384
ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION error code, 387	ER_LDAP_AUTH_POOLED_CONNECTION_KEY error code, 385
ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN_READY error code, 383	ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO error code, 380
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT_STATE error code, 383	ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION error code, 387
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT_STATE error code, 383	ER_LDAP_AUTH_POOL_REINITIALIZING error code, 381
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCT_STATE error code, 383	ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL error code, 384
ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT error code, 383	ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO error code, 386
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN error code, 387	ER_LDAP_AUTH_SASL_PROCESS_SASL error code, 386

---

---

ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT error code, 386	ER_LDAP_MAPPING_PROCESS_DELIMITER error code, 555
ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME error code, 382	ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA_NOT_FOUND error code, 555
ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND error code, 384	ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL_NOT_FOUND error code, 555
ER_LDAP_AUTH_SETTING_USERNAME error code, 381	ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA error code, 555
ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH error code, 380	ER_LDAP_MAPPING_PROCESS_MAPPING error code, 555
ER_LDAP_AUTH_STARTED_FOR_USER error code, 386	ER_LDAP_MAPPING_TRIMMING_SPACES error code, 556
ER_LDAP_AUTH_STARTING_TLS error code, 385	ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP error code, 554
ER_LDAP_AUTH_TLS_CONF error code, 380	ER_LIMITED_PART_RANGE error code, 39
ER_LDAP_AUTH_TLS_CONNECTION error code, 380	ER_LOAD_BULK_DATA_FAILED error code, 160
ER_LDAP_AUTH_USER_AUTH_DATA error code, 381	ER_LOAD_BULK_DATA_UNSORTED error code, 158
ER_LDAP_AUTH_USER_BIND_FAILED error code, 387	ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL error code, 161
ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRP error code, 382	ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL_LOG error code, 631
ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED error code, 386	ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD error code, 161
ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO error code, 382	ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD_LOG error code, 631
ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND error code, 542	ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAY error code, 185
ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES error code, 382	ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR error code, 32
ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP error code, 382	ER_LOAD_INFO error code, 9
ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED error code, 381	ER_LOCAL_VARIABLE error code, 20
ER_LDAP_EMPTY_USERDN_PASSWORD error code, 565	ER_LOCKING_SERVICE_DEADLOCK error code, 81
ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE error code, 555	ER_LOCKING_SERVICE_TIMEOUT error code, 81
ER_LDAP_MAPPING_EMPTY_MAPPING error code, 555	ER_LOCKING_SERVICE_WRONG_NAME error code, 81
ER_LDAP_MAPPING_GETTING_NEXT_MAPPING error code, 556	ER_LOCK_ABORTED error code, 50
ER_LDAP_MAPPING_GET_USER_PROXY error code, 554	ER_LOCK_DEADLOCK error code, 18
ER_LDAP_MAPPING_INFO error code, 555	ER_LOCK_NOWAIT error code, 93
ER_LDAP_MAPPING_IS_QUOTE error code, 556	ER_LOCK_ORDER_DEPENDENCIES_SYNTAX error code, 565
ER_LDAP_MAPPING_NON_DESIRED_STATE error code, 556	ER_LOCK_ORDER_FAILED_READ_FILE error code, 565
ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP error code, 555	ER_LOCK_ORDER_FAILED_WRITE_FILE error code, 565
ER_LDAP_MAPPING_PARSING_CURRENT_STATE error code, 556	ER_LOCK_ORDER_INIT_FAILED error code, 563
ER_LDAP_MAPPING_PARSING_ERROR error code, 556	ER_LOCK_ORDER_MESSAGE error code, 565
ER_LDAP_MAPPING_PARSING_MAPPING_INFO error code, 556	ER_LOCK_ORDER_SCANNER_SYNTAX error code, 565
	ER_LOCK_OR_ACTIVE_TRANSACTION error code, 16
	ER_LOCK_REFUSED_BY_ENGINE error code, 84
	ER_LOCK_TABLE_FULL error code, 18
	ER_LOCK_WAIT_TIMEOUT error code, 18
	ER_LOG_BIN_BETTER_WITH_NAME error code, 179

---

---

ER\_LOG\_CANNOT\_PURGE\_BINLOG\_WITH\_BACKUP\_LOCK error code, 639  
 ER\_LOG\_CANNOT\_WRITE error code, 164  
 ER\_LOG\_CANNOT\_WRITE\_EXTENDED error code, 569  
 ER\_LOG\_COMPONENT\_CANNOT\_INIT error code, 592  
 ER\_LOG\_COMPONENT\_FLUSH\_FAILED error code, 604  
 ER\_LOG\_FILES\_GIVEN\_LOG\_OUTPUT\_IS\_TABLE error code, 179  
 ER\_LOG\_FILE\_CANNOT\_OPEN error code, 322  
 ER\_LOG\_FILE\_INVALID error code, 179  
 ER\_LOG\_GENERAL\_CANNOT\_OPEN error code, 164  
 ER\_LOG\_IN\_USE error code, 30  
 ER\_LOG\_OUTPUT\_CONTRADICTORY error code, 178  
 ER\_LOG\_PRINTF\_MSG error code, 297  
 ER\_LOG\_PRIV\_CHECKS\_REQUIRE\_ROW\_FORMAT\_NO\_INSET error code, 573  
 ER\_LOG\_PURGE\_NO\_FILE error code, 44  
 ER\_LOG\_PURGE\_UNKNOWN\_ERR error code, 30  
 ER\_LOG\_SLOW\_CANNOT\_OPEN error code, 163  
 ER\_LOG\_SYSLOG\_CANNOT\_OPEN error code, 163  
 ER\_LOG\_SYSLOG\_FACILITY\_FAIL error code, 163  
 ER\_LONGITUDE\_OUT\_OF\_RANGE error code, 98  
 ER\_LOWER\_CASE\_TABLE\_NAMES\_CS\_DD\_ON\_CI\_FS\_UNSUPPORTED error code, 179  
 ER\_LOWER\_CASE\_TABLE\_NAMES\_USING\_0 error code, 179  
 ER\_LOWER\_CASE\_TABLE\_NAMES\_USING\_2 error code, 179  
 ER\_MALFORMED\_GTID\_SET\_ENCODING error code, 57  
 ER\_MALFORMED\_GTID\_SET\_SPECIFICATION error code, 57  
 ER\_MALFORMED\_GTID\_SPECIFICATION error code, 57  
 ER\_MALFORMED\_PACKET error code, 63  
 ER\_MANDATORY\_ROLE error code, 99  
 ER\_MASTER error code, 16  
 ER\_MASTER\_DELAY\_VALUE\_OUT\_OF\_RANGE error code, 53  
 ER\_MASTER\_FATAL\_ERROR\_READING\_BINLOG error code, 20  
 ER\_MASTER\_HAS\_PURGED\_REQUIRED\_GTIDS error code, 59  
 ER\_MASTER\_INFO error code, 17  
 ER\_MASTER\_KEY\_ROTATION\_BINLOG\_FAILED error code, 85  
 ER\_MASTER\_KEY\_ROTATION\_NOT\_SUPPORTED\_BY\_SERVER error code, 85  
 ER\_MASTER\_KEY\_ROTATION\_SE\_UNAVAILABLE error code, 85  
 ER\_MASTER\_NET\_READ error code, 16  
 ER\_MASTER\_NET\_WRITE error code, 16  
 ER\_MAXVALUE\_IN\_VALUES\_IN error code, 47  
 ER\_MAX\_PREPARED\_STMT\_COUNT\_REACHED error code, 35  
 ER\_MDL\_OUT\_OF\_RESOURCES error code, 140  
 ER\_MECAB\_CHARSET\_LOADED error code, 303  
 ER\_MECAB\_CREATE\_LATTICE\_FAILED error code, 303  
 ER\_MECAB\_CREATING\_MODEL error code, 303  
 ER\_MECAB\_FAILED\_TO\_CREATE\_MODEL error code, 303  
 ER\_MECAB\_FAILED\_TO\_CREATE\_TRIGGER error code, 303  
 ER\_MECAB\_NOT\_SUPPORTED error code, 303  
 ER\_MECAB\_NOT\_VERIFIED error code, 303  
 ER\_MECAB\_OOM\_WHILE\_PARSING\_TEXT error code, 303  
 ER\_MECAB\_PARSE\_FAILED error code, 303  
 ER\_MECAB\_UNSUPPORTED\_CHARSET error code, 303  
 ER\_MESSAGE\_AND\_STATEMENT error code, 48  
 ER\_MFA\_METHODS\_IDENTICAL error code, 150  
 ER\_MFA\_METHODS\_INVALID\_ORDER error code, 150  
 ER\_MFA\_METHOD\_EXISTS error code, 149  
 ER\_MFA\_METHOD\_NOT\_EXISTS error code, 149  
 ER\_MFA\_METHOD\_NOT\_LOADED error code, 611  
 ER\_MFA\_USER\_ATTRIBUTES\_CORRUPT error code, 611  
 ER\_MICROSECOND\_TIMER\_IS\_NOT\_AVAILABLE error code, 294  
 ER\_MIGRATE\_TABLE\_TO\_DD\_OOM error code, 576  
 ER\_MISPLACED INTO error code, 136  
 ER\_MISSING\_ACL\_SYSTEM\_TABLE error code, 285  
 ER\_MISSING\_CURRENT\_PASSWORD error code, 129  
 ER\_MISSING\_GRANT\_SYSTEM\_TABLE error code, 285  
 ER\_MISSING\_HA\_CREATE\_OPTION error code, 69  
 ER\_MISSING\_JSON\_TABLE\_VALUE error code, 103  
 ER\_MISSING\_JSON\_VALUE error code, 137  
 ER\_MISSING\_KEY error code, 68  
 ER\_MISSING\_SKIP\_REPLICA error code, 24  
 ER\_MISSING\_SKIP\_SLAVE error code, 23  
 ER\_MISSING\_TABLESPACE\_FILE error code, 99  
 ER\_MIXING\_NOT\_ALLOWED error code, 19  
 ER\_MIX\_HANDLER\_ERROR error code, 37  
 ER\_MIX\_OF\_GROUP\_FUNC\_AND\_FIELDS error code, 13  
 ER\_MIX\_OF\_GROUP\_FUNC\_AND\_FIELDS\_V2 error code, 77  
 ER\_MTA\_CANT\_PARALLEL error code, 55  
 ER\_MTA\_CHANGE\_SOURCE\_CANT\_RUN\_WITH\_GAPS error code, 60  
 ER\_MTA\_EVENT\_BIGGER\_PENDING\_JOBS\_SIZE\_MAX error code, 65

---

---

ER_MTA_FEATURE_IS_NOT_SUPPORTED error code, 55	ER_NAME_BECOMES_EMPTY error code, 36
ER_MTA_INCONSISTENT_DATA error code, 56	ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE error code, 294
ER_MTA_RECOVERY_FAILURE error code, 60	ER_NATIVE_FCT_NAME_COLLISION error code, 42
ER_MTA_RESET_WORKERS error code, 60	ER_NDBINFO_NOT_UPGRADING_SCHEMA error code, 580
ER_MTA_UPDATED_DBS_GREATER_MAX error code, 55	ER_NDBINFO_UPGRADING_SCHEMA error code, 580
ER_MTR_MSG_1 error code, 605	ER_NDBINFO_UPGRADING_SCHEMA_FAIL error code, 580
ER_MTS_CANT_PARALLEL error code, 55	ER_NDB_BINLOG_BLOB_REQUIRES_PK error code, 249
ER_MTS_CHANGE_MASTER_CANT_RUN_WITH_GAPS error code, 60	ER_NDB_BINLOG_CANT_COMMIT_TO_NDB_BINLOG_INDEX error code, 247
ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX error code, 65	ER_NDB_BINLOG_CANT_CREATE_BLOB error code, 250
ER_MTS_FEATURE_IS_NOT_SUPPORTED error code, 55	ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB error code, 249
ER_MTS_INCONSISTENT_DATA error code, 55	ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_AND_CANT_D error code, 249
ER_MTS_RECOVERY_FAILURE error code, 60	ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_DROPPED error code, 249
ER_MTS_RESET_WORKERS error code, 60	ER_NDB_BINLOG_CANT_CREATE_PURGE_THD error code, 273
ER_MTS_UPDATED_DBS_GREATER_MAX error code, 55	ER_NDB_BINLOG_CANT_DISCOVER_TABLE_FROM_SCHEMA_E error code, 244
ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME error code, 134	ER_NDB_BINLOG_CANT_DROP_EVENT_FROM_DB error code, 250
ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR error code, 37	ER_NDB_BINLOG_CANT_INJECT_APPLY_STATUS_WRITE_ROW error code, 252
ER_MULTIPLE_INTO_CLAUSES error code, 136	ER_NDB_BINLOG_CANT_LOCK_NDB_BINLOG_INDEX error code, 247
ER_MULTIPLE_JSON_VALUES error code, 138	ER_NDB_BINLOG_CANT_RELEASE_SLOCK error code, 244
ER_MULTIPLE_PRI_KEY error code, 8	ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE error code, 245
ER_MULTI_UPDATE_KEY_CONFLICT error code, 51	ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX error code, 247
ER_MUST_CHANGE_EXPIRED_PASSWORD error code, 280	ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS error code, 243
ER_MUST_CHANGE_PASSWORD error code, 62	ER_NDB_BINLOG_CLUSTER_FAILURE error code, 250
ER_MUST_CHANGE_PASSWORD_LOGIN error code, 65	ER_NDB_BINLOG_CLUSTER_HAS_RECONNECTED error code, 251
ER_MYINIT_FAILED error code, 177	ER_NDB_BINLOG_CLUSTER_RESTARTED_RESET_MASTER_SU error code, 251
ER_MYISAM_CHECK_METHOD_ERROR error code, 296	ER_NDB_BINLOG_CREATE_TABLE_EVENT error code, 220
ER_MYISAM_CRASHED_ERROR error code, 297	ER_NDB_BINLOG_CREATE_TABLE_EVENT_FAILED error code, 249
ER_MYISAM_CRASHED_ERROR_IN error code, 188	ER_NDB_BINLOG_CREATE_TABLE_EVENT_INFO error code, 249
ER_MYISAM_CRASHED_ERROR_IN_THREAD error code, 187	ER_NDB_BINLOG_CREATING_NDBEVENTOPERATION_FAILED error code, 250
ER_MYSQLBACKUP_CLIENT_MSG error code, 153	ER_NDB_BINLOG_DISCOVER_REUSING_OLD_EVENT_OPS error code, 250
ER_MYSQLBACKUP_MSG error code, 570	
ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD error code, 550	
ER_MY_MALLOC_GETPROCADDRESS_FAILED error code, 614	
ER_MY_MALLOC_LOADLIBRARY_FAILED error code, 614	
ER_MY_MALLOC_USING_JEMALLOC error code, 614	
ER_MY_MALLOC_USING_STD_MALLOC error code, 614	
ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STD error code, 258	
ER_M_BIGGER_THAN_D error code, 33	



---

ER_NDB_BINLOG_DISCOVER_TABLE_EVENT_INFO error code, 249	ER_NDB_BINLOG_REMAINING_OPEN_TABLE_INFO error code, 253
ER_NDB_BINLOG_ERROR_DURING_GCI_COMMIT error code, 253	ER_NDB_BINLOG_RENAME_EVENT error code, 220
ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK error code, 252	ER_NDB_BINLOG_REPLY_TO error code, 244
ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT error code, 252	ER_NDB_BINLOG_SERVER_SHUTDOWN_DURING_NDB_CLUSTER_SHUTDOWN error code, 251
ER_NDB_BINLOG_ERROR_INFO_FROM_DATA_DIRECTORY error code, 219	ER_NDB_BINLOG_SHUTDOWN_DETECTED error code, 252
ER_NDB_BINLOG_FAILED_CREATE_EVENT_OPERATION error code, 220	ER_NDB_BINLOG_SIGNALLING_UNKNOWN_VALUE error code, 244
ER_NDB_BINLOG_FAILED_CREATE_TABLE_EVENT_OPERATION error code, 220	ER_NDB_BINLOG_SKIPPING_DROP_OF_DB_CONTAINING_LOCAL_TABLES error code, 246
ER_NDB_BINLOG_FAILED_TO_GET_TABLE error code, 248	ER_NDB_BINLOG_SKIPPING_DROP_OF_LOCAL_TABLE error code, 245
ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT_TRANSACTION error code, 221	ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE error code, 245
ER_NDB_BINLOG_GENERIC_MESSAGE error code, 248	ER_NDB_BINLOG_SKIPPING_OLD_SCHEMA_OPERATION error code, 246
ER_NDB_BINLOG_GOT_DIST_PRIV_EVENT_FLUSHING error code, 246	ER_NDB_BINLOG_SKIPPING_RENAME_OF_LOCAL_TABLE error code, 246
ER_NDB_BINLOG_GOT_SCHEMA_EVENT error code, 246	ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH error code, 252
ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAILURE error code, 247	ER_NDB_BINLOG_UNHANDLED_ERROR_FOR_TABLE error code, 250
ER_NDB_BINLOG_INJECTOR_DISCARDING_ROW_EVENT error code, 251	ER_NDB_BINLOG_UNKNOWN_NON_DATA_EVENT error code, 251
ER_NDB_BINLOG_LATEST_TRX_IN_EPOCH_NOT_IN_BINLOG error code, 253	ER_NDB_BINLOG_USING_SERVER_ID_0_SLAVES_WILL_NOT_CONNECT error code, 247
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONNECTION error code, 252	ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAILED error code, 247
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITING error code, 252	ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX error code, 247
ER_NDB_BINLOG_NDBEVENT_EXECUTE_FAILED error code, 250	ER_NDB_CANNOT_ALLOC_GLOBAL_NDB_CLUSTER_CONNECTION error code, 263
ER_NDB_BINLOG_NDB_LOG_APPLY_STATUS_FORCING error code, 248	ER_NDB_CANNOT_ALLOC_GLOBAL_NDB_OBJECT error code, 264
ER_NDB_BINLOG_NDB_LOG_TRANSACTION_ID_REQUIRED error code, 248	ER_NDB_CANNOT_WRITE_TO_NDB_CLUSTER_CONNECTION error code, 264
ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY error code, 222	ER_NDB_CANNOT_WRITE_TO_NDB_CLUSTER_CONNECTION error code, 245
ER_NDB_BINLOG_NDB_TABLES_WRITABLE error code, 252	ER_NDB_CANNOT_PARSE_NDB_CLUSTER_CONNECTION_POOL error code, 263
ER_NDB_BINLOG_NOT_LOGGING error code, 249	ER_NDB_CANNOT_START_CONNECT_THREAD error code, 264
ER_NDB_BINLOG_ONLINE ALTER_RENAME error code, 245	ER_NDB_CLEANING_STRAY_TABLES error code, 242
ER_NDB_BINLOG_ONLINE ALTER_RENAME_COMPLETED error code, 245	ER_NDB_CLEAR_SLOCK_INFO error code, 245
ER_NDB_BINLOG_OPENING_INDEX error code, 247	ER_NDB_CLUSTER_FAILURE error code, 246
ER_NDB_BINLOG_RELEASING_EXTRA_SHARE_REFERENCES error code, 253	ER_NDB_CLUSTER_FIND_ALL_DBS_FAIL error code, 242
ER_NDB_BINLOG_REMAINING_OPEN_TABLES error code, 253	ER_NDB_CLUSTER_FIND_ALL_DBS_RETRY error code, 242
	ER_NDB_CLUSTER_FREE_SHARE_INFO error code, 221
	ER_NDB_CLUSTER_GENERIC_MESSAGE error code, 207

---

---

ER_NDB_CLUSTER_GET_SHARE_INFO error code, 221	ER_NDB_FLUSHING_TABLE_INFO error code, 242
ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROYING error code, 222	ER_NDB_FOUND_UNCOMMITTED_AUTOCOMMIT error code, 219
ER_NDB_CLUSTER_MARK_SHARE_DROPPED_INFO error code, 221	ER_NDB_GENERIC_ERROR error code, 264
ER_NDB_CLUSTER_OOM_THD_NDB error code, 222	ER_NDB_HANDLE_TRAILING_SHARE_INFO error code, 221
ER_NDB_CLUSTER_REAL_FREE_SHARE_DROP_FAILED error code, 221	ER_NDB_IGNOREING_UNKNOWN_EVENT error code, 246
ER_NDB_CLUSTER_REAL_FREE_SHARE_INFO error code, 221	ER_NDB_ILLEGAL_VALUE_FOR_NDB_RECV_THREAD_CPU_MASK error code, 222
ER_NDB_CLUSTER_SCHEMA_INFO error code, 207	ER_NDB_INFO_FAILED_TO_CREATE_NDBINFO error code, 207
ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTIONS error code, 207	ER_NDB_INFO_FAILED_TO_INIT_NDBINFO error code, 207
ER_NDB_COLUMN_DEFAULTS_DIFFER error code, 218	ER_NDB_INFO_FOUND_UNEXPECTED_FIELD_TYPE error code, 207
ER_NDB_COLUMN_INFO error code, 218	ER_NDB_INITIALIZE_GIVEN_CLUSTER_PLUGIN_DISABLED error code, 220
ER_NDB_COLUMN_SHOULD_NOT_HAVE_NATIVE_DEFAULT error code, 218	ER_NDB_INVALID_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL error code, 263
ER_NDB_CONFLICT_FN_PARSE_ERROR error code, 248	ER_NDB_LOG_ENTRY error code, 273
ER_NDB_CONFLICT_FN_SETUP_ERROR error code, 248	ER_NDB_LOG_ENTRY_WITH_PREFIX error code, 273
ER_NDB_CONFLICT_GENERIC_MESSAGE error code, 248	ER_NDB_MISMATCH_IN_FRM_DISCOVERING error code, 243
ER_NDB_COULD_NOT_GET_APPLY_STATUS_SHARE error code, 251	ER_NDB_MISSING_FRM_DISCOVERING error code, 243
ER_NDB_CPU_MASK_TOO_SHORT error code, 264	ER_NDB_NODEID_NOT_FIRST_IN_NDB_CLUSTER_CONNECTION_POOL error code, 263
ER_NDB_CREATE_EVENT_OPS_LOGGING_INFO error code, 250	ER_NDB_NODE_ID_AND_MANAGEMENT_SERVER_INFO error code, 217
ER_NDB_CREATING_SHARE_IN_OPEN error code, 220	ER_NDB_NODE_INFO error code, 264
ER_NDB_CREATING_TABLE error code, 242	ER_NDB_NOT_WAITING_FOR_DISTRIBUTING error code, 243
ER_NDB_DISCARDING_EVENT_ID_VERSION_MISMATCH error code, 245	ER_NDB_NUMBER_OF_CHANNELS error code, 276
ER_NDB_DISCARDING_EVENT_NO_OBJ error code, 245	ER_NDB_OOM_GET_NDB_BLOBS_VALUE error code, 241
ER_NDB_DISCONNECT_INFO error code, 218	ER_NDB_OOM_IN_FIX_UNIQUE_INDEX_ATTR_ORDER error code, 218
ER_NDB_DISCOVERED_MISSING_DB error code, 242	ER_NDB_POOL_SIZE_MUST_MATCH_NDB_CLUSTER_CONNECTION_POOL error code, 263
ER_NDB_DISCOVERED_REMAINING_DB error code, 242	ER_NDB_QUERY_FAILED error code, 216
ER_NDB_DISTRIBUTED_INFO error code, 243	ER_NDB_REMAINING_OPEN_TABLES error code, 251
ER_NDB_DISTRIBUTING_ERR error code, 276	ER_NDB_REMAINING_OPEN_TABLE_INFO error code, 251
ER_NDB_DISTRIBUTION_COMPLETE error code, 244	ER_NDB_REPLICATION_SCHEMA_ERROR error code, 45
ER_NDB_DUPLICATE_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL error code, 263	ER_NDB_REPLICATION_SCHEMA_ERROR error code, 45
ER_NDB_EMPTY_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL error code, 262	ER_NDB_SCHEMA_DISTRIBUTION_FAILED error code, 244
ER_NDB_ERROR_IN_GET_AUTO_INCREMENT error code, 220	ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_SUBSCRIBE error code, 244
ER_NDB_ERROR_IN_READAUTOINCREMENTVALUE error code, 219	ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_UNSUBSCRIBE error code, 244
ER_NDB_FAILED_TO_SET_UP_TABLE error code, 243	ER_NDB_SCHEMA_GENERIC_MESSAGE error code, 214
ER_NDB_FIELD_INFO error code, 218	

---

---

ER_NDB_SERVER_ID_RESERVED_OR_TOO_LARGE error code, 248	ER_NDB_TRAILING_SHARE_RELEASED_BY_CLOSE_CACHE error code, 221
ER_NDB_SHARE_ALREADY_EXISTS error code, 221	ER_NDB_TRANS_DEPENDENCY_TRACKER_ERROR error code, 248
ER_NDB_SKIPPING_SETUP_TABLE error code, 242	ER_NDB_UNEXPECTED_RENAME_TYPE error code, 220
ER_NDB_SLAVE_BINLOG_MISSING_INFO_FOR_CONFLICT_DETECTION error code, 219	ER_NDB_USING_NODEID error code, 263
ER_NDB_SLAVE_CANT_ALLOCATE_TABLE_SHARE error code, 219	ER_NDB_USING_NODEID_LIST error code, 264
ER_NDB_SLAVE_CONFLICT_DETECTION_REQUIRES_TRANSACTION_ID error code, 219	ER_NDB_WAITING_INFO error code, 243
ER_NDB_SLAVE_CONFLICT_FUNCTION_REQUIRES_ROLE error code, 218	ER_NDB_WAITING_INFO_WITH_MAP error code, 243
ER_NDB_SLAVE_ERROR_IN_UPDATE_CREATE_INFO error code, 219	ER_NEED_FILE_INSTEAD_OF_DIR error code, 179
ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO error code, 206	ER_NEED_LOG_BIN error code, 179
ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION error code, 206	ER_NEED_REPREPARE error code, 44
ER_NDB_SLAVE_MALFORMED_EVENT_RECEIVED_ON_TABLE error code, 218	ER_NETWORK_NAMESPACES_NOT_SUPPORTED error code, 561
ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_SET_TO error code, 217	ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG error code, 562
ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN error code, 217	ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WILDCARD error code, 561
ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN error code, 206	ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE error code, 528
ER_NDB_SLAVE_PARALLEL_WORKERS error code, 276	ER_NET_ERROR_ON_WRITE error code, 14
ER_NDB_SLAVE_PREVIOUS_EPOCH_NOT_COMMITTED error code, 206	ER_NET_FCNTL_ERROR error code, 14
ER_NDB_SLAVE_SAW_ALREADY_COMMITTED_EPOCH error code, 206	ER_NET_OK_PACKET_TOO_LARGE error code, 74
ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS error code, 206	ER_NET_PACKETS_OUT_OF_ORDER error code, 14
ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS error code, 206	ER_NET_PACKET_TOO_LARGE error code, 14
ER_NDB_SLAVE_TOO_MANY_RETRIES error code, 219	ER_NET_READ_ERROR error code, 14
ER_NDB_STARTING_CONNECT_THREAD error code, 264	ER_NET_READ_ERROR_FROM_PIPE error code, 14
ER_NDB_TABLES_INITIALLY_READ_ONLY_ON_RECONNECT error code, 246	ER_NET_READ_INTERRUPTED error code, 14
ER_NDB_TABLES_NOT_READY error code, 182	ER_NET_UNCOMPRESS_ERROR error code, 14
ER_NDB_TABLE_IS_NOT_DISTRIBUTED error code, 242	ER_NET_WAIT_ERROR error code, 562
ER_NDB_TABLE_OPENED_READ_ONLY error code, 220	ER_NET_WAIT_ERROR2 error code, 599
ER_NDB_THREAD_TIMED_OUT error code, 242	ER_NET_WRITE_INTERRUPTED error code, 14
ER_NDB_TIMED_OUT_IN_DROP_TABLE error code, 250	ER_NO_ERROR error code, 3
ER_NDB_TIMEOUT_WHILE_DISTRIBUTING error code, 243	ER_NO_INSERTING_CONNECTION error code, 16
ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD error code, 222	ER_NO error code, 3
	ER_NONEXISTING_GRANT error code, 13
	ER_NONEXISTING_PROC_GRANT error code, 31
	ER_NONEXISTING_TABLE_GRANT error code, 13
	ER_NONPOSITIVE_RADIUS error code, 108
	ER_NONUNIQ_TABLE error code, 8
	ER_NONUPDATEABLE_COLUMN error code, 28
	ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT error code, 120
	ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN error code, 79
	ER_NON_GROUPING_FIELD_USED error code, 35
	ER_NON_INSERTABLE_TABLE error code, 36
	ER_NON_RO_SELECT_DISABLE_TIMER error code, 71
	ER_NON_UNIQ_ERROR error code, 6
	ER_NON_UPDATABLE_TABLE error code, 24
	ER_NORMAL_SERVER_SHUTDOWN error code, 527
	ER_NORMAL_SHUTDOWN error code, 8

---

---

ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME error code, 626	ER_NO_DEFAULT error code, 20
ER_NOTE_COMPONENT_SLOT_DEREGISTRATION_SUCCESS error code, 635	ER_NO_DEFAULT_FOR_FIELD error code, 29
ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS error code, 635	ER_NO_DEFAULT_FOR_VIEW_FIELD error code, 32
ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIED error code, 597	ER_NO_ERROR_LOG_PARSER_CONFIGURED error code, 591
ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY error code, 597	ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATE error code, 743
ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE error code, 597	ER_NO_FT_MATERIALIZED_SUBQUERY error code, 70
ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR error code, 597	ER_NO_PARTITION_FOR_GIVEN_VALUE error code, 89
ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED error code, 598	ER_NO_BLOCK_SIZE error code, 43
ER_NOTE_KEYRING_COMPONENT_INITIALIZED error code, 597	ER_NO_PARTS_ERROR error code, 38
ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ERROR error code, 598	ER_NO_PATH_FOR_SHARED_LIBRARY error code, 536
ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATION_ERROR error code, 598	ER_NO_PERMISSION_TO_CREATE_USER error code, 18
ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND error code, 598	ER_NO_REFERENCED_ROW error code, 19
ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED error code, 598	ER_NO_REFERENCED_ROW_2 error code, 34
ER_NOTE_KEYRING_COMPONENT_STORE_FAILED error code, 598	ER_NO_SECURE_TRANSPORTS_CONFIGURED error code, 83
ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_SIZE error code, 598	ER_NO_SESSION_TEMP error code, 128
ER_NOT_ALLOWED_COMMAND error code, 13	ER_NO_SUCH_DB error code, 87
ER_NOT_ALLOWED_WITH_START_TRANSACTION error code, 139	ER_NO_SUCH_INDEX error code, 9
ER_NOT_FORM_FILE error code, 5	ER_NO_SUCH_TABLE error code, 13
ER_NOT_HINT_UPDATABLE_VARIABLE error code, 100	ER_NO_SUCH_THREAD error code, 10
ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS error code, 107	ER_NO_SUCH_USER error code, 34
ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS error code, 98	ER_NO_SUPER_WITHOUT_USER_PLUGIN error code, 196
ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS error code, 108	ER_NO_SYSTEM_SCHEMA_ACCESS error code, 91
ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS error code, 322	ER_NO_SYSTEM_TABLESPACE_ACCESS error code, 91
ER_NOT_KEYFILE error code, 5	ER_NO_SYSTEM_TABLE_ACCESS error code, 91
ER_NOT_RIGHT_NOW error code, 176	ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE error code, 91
ER_NOT_SUPPORTED_AUTH_MODE error code, 21	ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE error code, 91
ER_NOT_SUPPORTED_YET error code, 20	ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE error code, 91
ER_NOT_VALID_PASSWORD error code, 62	ER_NO_SYSTEM_VIEW_ACCESS error code, 98
ER_NO_ACCESS_TO_NATIVE_FCT error code, 92	ER_NO_TABLES_USED error code, 10
ER_NO_BINARY_LOGGING error code, 30	ER_NO_THD_NO_UUID error code, 170
ER_NO_BINLOG_ERROR error code, 39	ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA error code, 35
ER_NO_CSV_NO_LOG_TABLES error code, 178	ER_NO_UNIQUE_LOGFILE error code, 10
ER_NO_DB_ERROR error code, 6	ER_NPIPE_CANT_CREATE error code, 275
	ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR error code, 205
	ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR error code, 205
	ER_NPIPE_PIPE_ALREADY_IN_USE error code, 205
	ER_NULL_COLUMN_IN_INDEX error code, 12
	ER_NULL_IN_VALUES_LESS_THAN error code, 41

---

---

ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE error code, 83	ER_PARTITION_EXCHANGE_DIFFERENT_OPTION error code, 53
ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION error code, 571	ER_PARTITION_EXCHANGE_FOREIGN_KEY error code, 54
ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION error code, 573	ER_PARTITION_EXCHANGE_PART_TABLE error code, 53
ER_OLD_FILE_FORMAT error code, 35	ER_PARTITION_EXCHANGE_TEMP_TABLE error code, 54
ER_OLD_KEYFILE error code, 5	ER_PARTITION_FIELDS_TOO_LONG error code, 47
ER_OLD_PASSWORDS_NO_MIDDLE_GROUND error code, 171	ER_PARTITION_FUNCTION_FAILURE error code, 39
ER_OLD_TEMPORALS_UPGRADED error code, 67	ER_PARTITION_FUNCTION_IS_NOT_ALLOWED error code, 37
ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG STATEMENT error code, 53	ER_PARTITION_FUNC_NOT_ALLOWED_ERROR error code, 37
ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326 error code, 105	ER_PARTITION_HANDLER_ADMIN_MSG error code, 296
ER_ONLY_INTEGERS_ALLOWED error code, 42	ER_PARTITION_INSTEAD_OF_SUBPARTITION error code, 54
ER_ONLY_ON_RANGE_LIST_PARTITION error code, 38	ER_PARTITION_MAXVALUE_ERROR error code, 36
ER_OOM error code, 176	ER_PARTITION_MERGE_ERROR error code, 41
ER_OOM_SAVE_GTIDS error code, 527	ER_PARTITION_MGMT_ON_NONPARTITIONED error code, 38
ER_OPEN_AS_READONLY error code, 5	ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE error code, 275
ER_OPEN_ROLE_TABLES error code, 89	ER_PARTITION_NAME error code, 45
ER_OPERAND_COLUMNS error code, 21	ER_PARTITION_NAME_OR_FUNCTION_NOT_DEFINED_ERROR error code, 37
ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY error code, 148	ER_PARTITION_NO_TEMPORARY error code, 41
ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGE_IS_RUNNING error code, 154	ER_PARTITION_REQUIRES_VALUES_ERROR error code, 36
ER_OPTION_PREVENTS_STATEMENT error code, 24	ER_PARTITION_WRONG_NO_PART_ERROR error code, 36
ER_OPT_WRONG_TREE error code, 163	ER_PARTITION_WRONG_NO_SUBPART_ERROR error code, 36
ER_OUTOFMEMORY error code, 5	ER_PARTITION_WRONG_VALUES_ERROR error code, 36
ER_OUT_OF_RESOURCES error code, 6	ER_PART_EXPR_TOO_LONG error code, 99
ER_OUT_OF_SORTMEMORY error code, 5	ER_PASSWORD_ANONYMOUS_USER error code, 12
ER_PAGE_TRACKING_CANNOT_PURGE error code, 119	ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE error code, 129
ER_PAGE_TRACKING_NOT_STARTED error code, 119	ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTHENTICATION error code, 104
ER_PAGE_TRACKING_RANGE_NOT_TRACKED error code, 119	ER_PASSWORD_EXPIRE_ANONYMOUS_USER error code, 69
ER_PARSER_TRACE error code, 162	ER_PASSWORD_FORMAT error code, 62
ER_PARSE_ERROR error code, 7	ER_PASSWORD_NOT_ALLOWED error code, 12
ER_PARSE_ERROR_IN_DIGEST_FN error code, 104	ER_PASSWORD_NO_MATCH error code, 12
ER_PARSING_VIEW error code, 169	ER_PATH_IN_DATADIR error code, 100
ER_PARTIAL_REVOKES_EXIST error code, 129	ER_PATH_LENGTH error code, 49
ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS error code, 130	ER_PERFORMANCE_SCHEMA_VERSION_CHANGE error code, 641
ER_PARTITIONS_MUST_BE_DEFINED_ERROR error code, 37	ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP error code, 281
ER_PARTITION_CLAUSE_ON_NONPARTITIONED error code, 54	
ER_PARTITION_COLUMN_LIST_ERROR error code, 47	
ER_PARTITION_CONST_DOMAIN_ERROR error code, 41	
ER_PARTITION_ENTRY_ERROR error code, 37	

---

---

ER_PERFSHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN error code, 281	ER_PLUGIN_DISABLED error code, 258
ER_PERFSHEMA_INIT_FAILED error code, 180	ER_PLUGIN_EXCEPTION_OPERATION_FAILED error code, 631
ER_PERFSHEMA_TABLES_INIT_FAILED error code, 283	ER_PLUGIN_FAILED_DEINITIALIZATION error code, 256
ER_PERSISTED_VARIABLES_DECRYPTION_FAILED error code, 614	ER_PLUGIN_FAILED_TO_OPEN_TABLE error code, 533
ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED error code, 614	ER_PLUGIN_FAILED_TO_OPEN_TABLES error code, 533
ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED error code, 613	ER_PLUGIN_FORCING_SHUTDOWN error code, 257
ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT error code, 614	ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES error code, 256
ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_GENERATED error code, 614	ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION error code, 256
ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND error code, 613	ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN error code, 257
ER_PERSISTENT_PRIVILEGES_BOOTSTRAP error code, 282	ER_PLUGIN_INIT_FAILED error code, 184
ER_PERSIST_ONLY_ACCESS_DENIED_ERROR error code, 99	ER_PLUGIN_INSTALL_ERROR error code, 542
ER_PERSIST_OPTION_HOST_TRUNCATED error code, 562	ER_PLUGIN_INVALID_TABLE_DEFINITION error code, 603
ER_PERSIST_OPTION_STATUS error code, 322	ER_PLUGIN_IS_NOT_LOADED error code, 39
ER_PERSIST_OPTION_USER_TRUNCATED error code, 562	ER_PLUGIN_IS_PERMANENT error code, 51
ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL error code, 293	ER_PLUGIN_LOAD_OPTIONS_IGNORED error code, 572
ER_PFS_MALLOC_ARRAY_OOM error code, 294	ER_PLUGIN_LOAD_PARAMETER_TOO_LONG error code, 257
ER_PFS_MALLOC_ARRAY_OVERFLOW error code, 294	ER_PLUGIN_NOT_EARLY error code, 123
ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED error code, 286	ER_PLUGIN_NOT_EARLY_DUP error code, 563
ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE error code, 536	ER_PLUGIN_NO_INSTALL error code, 52
ER_PID_FILE_PRIV_DIRECTORY_INSECURE error code, 388	ER_PLUGIN_NO_INSTALL_DUP error code, 563
ER_PK_INDEX_CANT_BE_INVISIBLE error code, 89	ER_PLUGIN_NO_UNINSTALL error code, 52
ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED error code, 81	ER_PLUGIN_OOM error code, 258
ER_PLUGIN_BAD_OPTIONS error code, 258	ER_PLUGIN_PARSING_OPTIONS_FAILED error code, 258
ER_PLUGIN_CANNOT_BE_UNINSTALLED error code, 67	ER_PLUGIN_REGISTRATION_DONE error code, 149
ER_PLUGIN_CANT_LOAD error code, 257	ER_PLUGIN_REGISTRATION_FAILED error code, 257
ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE error code, 257	ER_PLUGIN_REQUIRES_REGISTRATION error code, 149
ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS error code, 258	ER_PLUGIN_SHUTTING_DOWN_PLUGIN error code, 257
ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLE error code, 320	ER_PLUGIN_UNINSTALL_ERROR error code, 542
ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE error code, 320	ER_PLUGIN_UNKNOWN_VARIABLE_TYPE error code, 257
ER_PLUGIN_DELETE_BUILTIN error code, 44	ER_PLUGIN_VARIABLE_MISSING_NAME error code, 257
	ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL error code, 258
	ER_PLUGIN_VARIABLE_SET_READ_ONLY error code, 257
	ER_POINTLESS_WITHOUT_SLOWLOG error code, 171
	ER_POLYGON_TOO_LARGE error code, 110

---

---

ER_PREPARE_FOR_PRIMARY_ENGINE error code, 605	ER_REGEXP_MISMATCHED_PAREN error code, 106
ER_PREPARE_FOR_SECONDARY_ENGINE error code, 556	ER_REGEXP_MISSING_CLOSE_BRACKET error code, 107
ER_PREVENTS_VARIABLE_WITHOUT_RBR error code, 78	ER_REGEXP_MISSING_FILE error code, 152
ER_PRIMARY_CANT_HAVE_NULL error code, 15	ER_REGEXP_MISSING_ICU_DATADIR error code, 612
ER_PRIVILEGE_DEREGISTRATION error code, 637	ER_REGEXP_MISSING_RESOURCE error code, 152
ER_PRIVILEGE_REGISTRATION error code, 637	ER_REGEXP_PATTERN_TOO_BIG error code, 107
ER_PRIVILEGE_SYSTEM_INIT_FAILED error code, 282	ER_REGEXP_RULE_SYNTAX error code, 106
ER_PROCAccess_DENIED_ERROR error code, 29	ER_REGEXP_STACK_OVERFLOW error code, 107
ER_PROC_AUTO_GRANT_FAIL error code, 31	ER_REGEXP_STRING_NOT_TERMINATED error code, 105
ER_PROC_AUTO_REVOKE_FAIL error code, 31	ER_REGEXP_TIME_OUT error code, 107
ER_PROTOCOL_COMPRESSION_RESET_LOG error code, 570	ER_REGEXP_UNIMPLEMENTED error code, 106
ER_PS_MANY_PARAM error code, 30	ER_REGEX_NUMBER_TOO_BIG error code, 142
ER_PS_NO_RECURSION error code, 34	ER_RELAY_LOG_FAIL error code, 30
ER_QUERY_CACHE_DISABLED error code, 47	ER_RELAY_LOG_INIT error code, 30
ER_QUERY_INTERRUPTED error code, 26	ER_RELAY_LOG_SPACE_LIMIT_DISABLED error code, 539
ER_QUERY_ON_FOREIGN_DATA_SOURCE error code, 33	ER_RELOAD_KEYRING_FAILURE error code, 146
ER_QUERY_TIMEOUT error code, 70	ER_REMOVED_SPACES error code, 35
ER_RANGE_NOT_INCREASING_ERROR error code, 37	ER_RENAMED_NAME error code, 45
ER_READING_TABLE_FAILED error code, 184	ER_RENAME_ROLE error code, 89
ER_READY error code, 8	ER_REORG_HASH_ONLY_ON_SAME_NO error code, 38
ER_READ_LOG_EVENT_FAILED error code, 291	ER_REORG_NO_PARAM_ERROR error code, 38
ER_READ_ONLY_MODE error code, 63	ER_REORG_OUTSIDE_RANGE error code, 39
ER_READ_ONLY_TRANSACTION error code, 18	ER_REORG_PARTITION_NOT_EXIST error code, 38
ER REALLY_RUN_AS_ROOT error code, 175	ER_REPLACE_INACCESSIBLE_ROWS error code, 74
ER_RECORD_FILE_FULL error code, 11	ER_REPLICATION_INCOMPATIBLE_TABLE_WITH_GIPK error code, 629
ER_RECOVERING_TABLE error code, 259	ER_REPLICA_AM_INIT_REPOSITORY error code, 66
ER_REDUCED_DBLWR_FILE_CORRUPTED error code, 639	ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_GRO error code, 594
ER_REDUCED_DBLWR_PAGE_FOUND error code, 639	ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID_AND_G error code, 594
ER_REFERENCED_TRG_DOES_NOT_EXIST error code, 69	ER_REPLICA_CANT_CREATE_CONVERSION error code, 49
ER_REGEXP_BAD_ESCAPE_SEQUENCE error code, 106	ER_REPLICA_CANT_USE_TMPDIR error code, 240
ER_REGEXP_BAD_INTERVAL error code, 106	ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED error code, 239
ER_REGEXP_BUFFER_OVERFLOW error code, 105	ER_REPLICA_CHANNEL_DOES_NOT_EXIST error code, 75
ER_REGEXP_ERROR error code, 13	ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP error code, 70
ER_REGEXP_ILLEGAL_ARGUMENT error code, 105	ER_REPLICA_CHANNEL_MUST_STOP error code, 76
ER_REGEXP_INDEX_OUTOFBOUNDS_ERROR error code, 106	ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG error code, 75
ER_REGEXP_INTERNAL_ERROR error code, 106	ER_REPLICA_CHANNEL_NOT_RUNNING error code, 76
ER_REGEXP_INVALID_BACK_REF error code, 106	ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED error code, 82
ER_REGEXP_INVALID_CAPTURE_GROUP_NAME error code, 128	ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER error code, 77
ER_REGEXP_INVALID_FLAG error code, 130	
ER_REGEXP_INVALID_RANGE error code, 107	
ER_REGEXP_LOOK_BEHIND_LIMIT error code, 106	
ER_REGEXP_MAX_LT_MIN error code, 106	

---

ER\_REPLICA\_CHANNEL\_SQL\_THREAD\_MUST\_STOP error code, 77  
 ER\_REPLICA\_CHANNEL\_WAS\_NOT\_RUNNING error code, 76  
 ER\_REPLICA\_CHANNEL\_WAS\_RUNNING error code, 76  
 ER\_REPLICA\_CM\_INIT\_REPOSITORY error code, 66  
 ER\_REPLICA\_CONFIGURATION error code, 59  
 ER\_REPLICA\_CORRUPT\_EVENT error code, 44  
 ER\_REPLICA\_CREATE\_EVENT\_FAILURE error code, 528  
 ER\_REPLICA\_FATAL\_ERROR error code, 528  
 ER\_REPLICA\_HAS\_MORE\_GTIDS\_THAN\_SOURCE error code, 68  
 ER\_REPLICA\_HEARTBEAT\_FAILURE error code, 529  
 ER\_REPLICA\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE error code, 45  
 ER\_REPLICA\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE\_Major error code, 51  
 ER\_REPLICA\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE\_Minor error code, 51  
 ER\_REPLICA\_IGNORED\_SSL\_PARAMS error code, 23  
 ER\_REPLICA\_IGNORED\_TABLE error code, 20  
 ER\_REPLICA\_IGNORE\_SERVER\_IDS error code, 46  
 ER\_REPLICA\_INCIDENT error code, 529  
 ER\_REPLICA\_KILLED\_AFTER\_RECONNECT error code, 292  
 ER\_REPLICA\_MAX\_CHANNELS\_EXCEEDED error code, 76  
 ER\_REPLICA\_MULTIPLE\_CHANNELS\_CMD error code, 75  
 ER\_REPLICA\_NEW\_CHANNEL\_WRONG\_REPOSITORY error code, 75  
 ER\_REPLICA\_NOT\_RUNNING error code, 17  
 ER\_REPLICA\_NOT\_STARTED\_ON\_SOME\_CHANNELS error code, 292  
 ER\_REPLICA\_POSSIBLY\_DIVERGED\_AFTER\_DDL error code, 110  
 ER\_REPLICA\_RECONNECT\_FAILED error code, 292  
 ER\_REPLICA\_RELAY\_LOG\_PURGE\_FAILED error code, 284  
 ER\_REPLICA\_RELAY\_LOG\_READ\_FAILURE error code, 529  
 ER\_REPLICA\_RELAY\_LOG\_TRUNCATE\_INFO error code, 283  
 ER\_REPLICA\_RELAY\_LOG\_WRITE\_FAILURE error code, 529  
 ER\_REPLICA\_SILENT\_RETRY\_TRANSACTION error code, 61  
 ER\_REPLICA\_SOURCE\_COM\_FAILURE error code, 529  
 ER\_REPLICA\_SQL\_THREAD\_MUST\_STOP error code, 70

ER\_REPLICA\_SQL\_THREAD\_STOPPED\_AFTER\_GTIDS\_REACHED error code, 204  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_BEFORE\_GTIDS\_ALREADY error code, 203  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_BEFORE\_GTIDS\_REACHED error code, 204  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_GAP\_TRX\_PROCESSED error code, 204  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_UNTIL\_CONDITION\_BAD error code, 203  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_UNTIL\_POSITION\_REACHED error code, 203  
 ER\_REPLICA\_THREAD error code, 18  
 ER\_REPLICA\_WORKER\_STOPPED\_PREVIOUS\_THD\_ERROR error code, 71  
 ER\_REQUIRES\_PRIMARY\_KEY error code, 15  
 ER\_REQUIRE\_ROW\_FORMAT\_INVALID\_VALUE error code, 135  
 ER\_REQUIRE\_TABLE\_PRIMARY\_KEY\_CHECK\_GENERATE\_WITHOUT error code, 161  
 ER\_REQUIRE\_TABLE\_PRIMARY\_KEY\_CHECK\_GENERATE\_WITHOUT error code, 632  
 ER\_RESERVED\_SYNTAX error code, 30  
 ER\_RESERVED\_TABLESPACE\_NAME error code, 109  
 ER\_RESET\_MASTER\_TO\_VALUE\_OUT\_OF\_RANGE error code, 92  
 ER\_RESET\_SOURCE\_TO\_VALUE\_OUT\_OF\_RANGE error code, 92  
 ER\_RESIGNAL\_WITHOUT\_ACTIVE\_HANDLER error code, 46  
 ER\_RESOURCE\_GROUP\_BIND\_FAILED error code, 103  
 ER\_RESOURCE\_GROUP\_BUSY error code, 102  
 ER\_RESOURCE\_GROUP\_DISABLED error code, 102  
 ER\_RESOURCE\_GROUP\_EXISTS error code, 102  
 ER\_RESOURCE\_GROUP\_IS\_DISABLED error code, 286  
 ER\_RESOURCE\_GROUP\_METADATA\_UPDATE\_SKIPPED error code, 285  
 ER\_RESOURCE\_GROUP\_NOT\_EXISTS error code, 102  
 ER\_RESOURCE\_GROUP\_POST\_INIT\_FAILED error code, 282  
 ER\_RESOURCE\_GROUP\_SUBSYSTEM\_INIT\_FAILED error code, 282  
 ER\_RESOURCE\_GROUP\_VALIDATION\_FAILED error code, 286  
 ER\_RESTART\_RECEIVED\_INFO error code, 299  
 ER\_RESTART\_SERVER\_FAILED error code, 108  
 ER\_RES\_GRP\_FAILED\_DETERMINE\_CPU\_COUNT error code, 287  
 ER\_RES\_GRP\_FAILED\_TO\_DETERMINE\_NICE\_CAPABILITY error code, 287



---

ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE error code, 287	ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR error code, 187
ER_RES_GRP_FAILED_TO_SWITCH_RESOURCE_GROUP error code, 625	ER_ROW_IS_REFERENCED error code, 19
ER_RES_GRP_FEATURE_NOT_AVAILABLE error code, 287	ER_ROW_IS_REFERENCED_2 error code, 34
ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED error code, 287	ER_ROW_SINGLE_PARTITION_FIELD_ERROR error code, 47
ER_RES_GRP_INVALID_THREAD_PRIORITY error code, 288	ER_RPL_AM_INIT_INFO_MSG error code, 296
ER_RES_GRP_INVALID_VCPU_ID error code, 298	ER_RPL_ASYNC_CHANNEL_CANT_CONNECT error code, 592
ER_RES_GRP_INVALID_VCPU_RANGE error code, 298	ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM error code, 592
ER_RES_GRP_SET_THREAD_PRIORITY_FAILED error code, 287	ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST error code, 592
ER_RES_GRP_SET_THR_AFFINITY_FAILED error code, 287	ER_RPL_ASYNC_EXECUTING_QUERY error code, 592
ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED error code, 287	ER_RPL_ASYNC_MANAGED_NAME_ADDED error code, 593
ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED error code, 288	ER_RPL_ASYNC_MANAGED_NAME_REMOVED error code, 593
ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPU_ID error code, 288	ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED error code, 633
ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_ID error code, 288	ER_RPL_ASYNC_READ_FAILOVER_TABLE error code, 593
ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE error code, 626	ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF error code, 141
ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE error code, 626	ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE error code, 590
ER_RES_GRP_SWITCH_FAILED_UNABLE_TO_APPLY_READ error code, 626	ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF error code, 140
ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED error code, 287	ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL error code, 595
ER_RETRYING_REPAIR_WITHOUT_QUICK error code, 258	ER_RPL_ASYNC_SENDER_ADDED error code, 592
ER_RETRYING_REPAIR_WITH_KEYCACHE error code, 259	ER_RPL_ASYNC_SENDER_REMOVED error code, 592
ER_REVOKE_GRANTS error code, 22	ER_RPL_BINLOG_FILTERS_OOM error code, 174
ER_REWRITER_LOAD_FAILED error code, 322	ER_RPL_BINLOG_MASTER_SENDS_HEARTBEAT error code, 216
ER_REWRITER_OOM error code, 322	ER_RPL_BINLOG_MASTER_USES_CHECKSUM_AND_SLAVE error code, 216
ER_REWRITER_QUERY_ERROR_MSG error code, 318	ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED error code, 184
ER_REWRITER_QUERY_FAILED error code, 318	ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO error code, 216
ER_REWRITER_READ_FAILED error code, 322	ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT error code, 216
ER_REWRITER_TABLE_MALFORMED_ERROR error code, 322	ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLIC error code, 216
ER_ROLE_GRANTED_TO_ITSELF error code, 145	ER_RPL_BINLOG_STARTING_DUMP error code, 216
ER_ROLE_NOT_GRANTED error code, 89	ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED error code, 184
ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG error code, 291	ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED error code, 184
ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET error code, 54	ER_RPL_CANNOT_OPEN_RELAY_LOG error code, 609
ER_ROW_DOES_NOT_MATCH_PARTITION error code, 54	ER_RPL_CANT_ADD_DO_TABLE error code, 177
ER_ROW_IN_WRONG_PARTITION error code, 65	ER_RPL_CANT_ADD_IGNORE_TABLE error code, 177

---

---

ER_RPL_CANT_CREATE_REPLICA_THREAD error code, 227	ER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 117
ER_RPL_CANT_CREATE_SLAVE_THREAD error code, 227	ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED error code, 118
ER_RPL_CANT_FIND_FOLLOWUP_FILE error code, 234	ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION error code, 118
ER_RPL_CANT_HAVE_SAME_BASENAME error code, 278	ER_RPL_ERROR_CHANGING_APPLIER_METADATA_REPO_TYPE error code, 210
ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO error code, 241	ER_RPL_ERROR_CHANGING_CONNECTION_METADATA_REPO_TYPE error code, 209
ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO error code, 241	ER_RPL_ERROR_CHANGING_MASTER_INFO_REPO_TYPE error code, 209
ER_RPL_CANT_MAKE_PATHS error code, 180	ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO_TYPE error code, 209
ER_RPL_CANT_OPEN_INFO_TABLE error code, 207	ER_RPL_ERROR_CHECKING_REPOSITORY error code, 210
ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO error code, 241	ER_RPL_ERROR_CREATING_APPLIER_METADATA error code, 209
ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO error code, 241	ER_RPL_ERROR_CREATING_CONNECTION_METADATA error code, 209
ER_RPL_CANT_SCAN_INFO_TABLE error code, 207	ER_RPL_ERROR_CREATING_MASTER_INFO error code, 208
ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP error code, 125	ER_RPL_ERROR_CREATING_RELAY_LOG_INFO error code, 209
ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKUP error code, 125	ER_RPL_ERROR_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE error code, 212
ER_RPL_CHANGING_APPLIER_METADATA_REPO_TYPE error code, 209	ER_RPL_ERROR_FAILED_TO_CREATE_NEW_INFO_FILE error code, 212
ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE error code, 209	ER_RPL_ERROR_FAILED_TO_DELETE_FROM_REPLICA_WORKERS_INFO error code, 210
ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID error code, 208	ER_RPL_ERROR_FAILED_TO_DELETE_FROM_SLAVE_WORKERS_INFO error code, 210
ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPOSITORY error code, 208	ER_RPL_ERROR_FAILED_TO_OPEN_INFO_FILE error code, 212
ER_RPL_CORRUPTED_INFO_TABLE error code, 207	ER_RPL_ERROR_FAILED_TO_OPEN_RELAY_LOG error code, 254
ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE error code, 208	
ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY error code, 119	
ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 119	
ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY error code, 117	
ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 117	
ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 117	
ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS error code, 117	
ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY error code, 117	
ER_RPL_ENCRYPTION_HEADER_ERROR error code, 117	
ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY error code, 117	
ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 117	

---

ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO error code, 210	ER_REPOSITORY_GROUP_RECOVERY_APPLIER_METADATA error code, 234
ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO error code, 210	ER_REPOSITORY_GROUP_RECOVERY_APPLIER_METADATA error code, 234
ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX error code, 240	ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG error code, 227
ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL error code, 293	ER_RPL_MTA_RECOVERY_COMPLETE error code, 231
ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED error code, 282	ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR error code, 226
ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED error code, 282	ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR error code, 226
ER_RPL_GTID_LOG_EVENT_IN_STREAM error code, 213	ER_RPL_MTA_RECOVERY_SUCCESSFUL error code, 227
ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE error code, 212	ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED error code, 255
ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY error code, 278	ER_RPL_MTS_STATISTICS error code, 231
ER_RPL_GTID_TABLE_CANNOT_OPEN error code, 164	ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED error code, 227
ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION error code, 542	ER_RPL_MTS_CHECKPOINT_PERIOD_DIFFERS_FROM_COUNT error code, 231
ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT error code, 526	ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO error code, 234
ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE error code, 526	ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO_FOR_SLAVE error code, 233
ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE error code, 526	ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG error code, 227
ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR error code, 214	ER_RPL_MTS_RECOVERY_COMPLETE error code, 231
ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX error code, 208	ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDINATOR error code, 226
ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX error code, 208	ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR error code, 226
ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION error code, 607	ER_RPL_MTS_RECOVERY_SUCCESSFUL error code, 227
ER_RPL_INFINITY_DENIED error code, 182	ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED error code, 255
ER_RPL_INFINITY_IGNORED error code, 182	ER_RPL_MTS_STATISTICS error code, 230
ER_RPL_INFO_DATA_TOO_LONG error code, 54	ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORY error code, 211
ER_RPL_IO_THREAD_KILLED error code, 292	ER_RPL_OPEN_INDEX_FILE_FAILED error code, 241
ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED error code, 642	ER_RPL_PLEASE_USE_OPTION_RELAY_LOG error code, 225
ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET error code, 232	ER_RPL_PLUGIN_FUNCTION_FAILED error code, 184
ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWED_PACKET error code, 232	ER_RPL_RECOVERY_ERROR error code, 225
ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_ENTRIES error code, 240	ER_RPL_RECOVERY_ERROR_FREEING_IO_CACHE error code, 225
ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER error code, 642	ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG error code, 225
ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED error code, 227	ER_RPL_RECOVERY_FILE_MASTER_POS_INFO error code, 226
ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_COUNT error code, 234	ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO error code, 226

---

ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX error code, 226	ER_RPL_REPLICATION_ERROR_RETRYING error code, 230
ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER error code, 225	ER_RPL_REPLICATION_ERROR_RUNNING_QUERY error code, 237
ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE error code, 225	ER_RPL_REPLICATION_FAILED_TO_CREATE_CHANNEL_FROM_CONNECTION error code, 212
ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRED error code, 226	ER_RPL_REPLICATION_FAILED_TO_CREATE_OR_RECOVER_INFO_FROM_REPOSITORY error code, 224
ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHANNEL error code, 225	ER_RPL_REPLICATION_FAILED_TO_INIT_A_CONNECTION_METADATA error code, 211
ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY error code, 240	ER_RPL_REPLICATION_FAILED_TO_INIT_CONNECTION_METADATA error code, 211
ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY error code, 240	ER_RPL_REPLICATION_FAILED_TO_INIT_PARTITIONS_HASH error code, 235
ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY error code, 613	ER_RPL_REPLICATION_FILTER_CREATE_FAILED error code, 284
ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE error code, 576	ER_RPL_REPLICATION_FORCING_TO_RECONNECT_IO_THREAD error code, 232
ER_RPL_REPLICATION_ADDITIONAL_ERROR_INFO_FROM_SOURCE error code, 236	ER_RPL_REPLICATION_GENERIC_MESSAGE error code, 210
ER_RPL_REPLICATION_AUTO_POSITION_IS_1_AND_GTID_MODE error code, 224	ER_RPL_REPLICATION_GLOBAL_FILTERS_COPY_FAILED error code, 284
ER_RPL_REPLICATION_CANT_FLUSH_CONNECTION_METADATA error code, 229	ER_RPL_REPLICATION_INCORRECT_CHANNEL error code, 277
ER_RPL_REPLICATION_CANT_INITIALIZE_REPLICATION_WORKER error code, 233	ER_RPL_REPLICATION_INSECURE_CHANGE_SOURCE error code, 276
ER_RPL_REPLICATION_CANT_INIT_RELAY_LOG_POSITION error code, 231	ER_RPL_REPLICATION_IO_THREAD_ABORTED_WAITING_FOR_RELAY error code, 233
ER_RPL_REPLICATION_CANT_START_REPLICATION_FOR_CHANNEL error code, 224	ER_RPL_REPLICATION_IO_THREAD_CANT_REGISTER_ON_SOURCE error code, 232
ER_RPL_REPLICATION_CANT_STOP_REPLICATION_FOR_CHANNEL error code, 225	ER_RPL_REPLICATION_IO_THREAD_DETECTED_UNEXPECTED_EVENT error code, 238
ER_RPL_REPLICATION_CANT_USE_CHARSET error code, 238	ER_RPL_REPLICATION_IO_THREAD_EXITING error code, 233
ER_RPL_REPLICATION_CONNECTED_TO_SOURCE_REPLICATION error code, 238	ER_RPL_REPLICATION_IO_THREAD_KILLED error code, 231
ER_RPL_REPLICATION_CONNECTED_TO_SOURCE_REPLICATION_STARTED error code, 633	ER_RPL_REPLICATION_IO_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 526
ER_RPL_REPLICATION_CONNECTED_TO_SOURCE_REPLICATION_STARTED error code, 633	ER_RPL_REPLICATION_IO_THREAD_WAS_KILLED error code, 228
ER_RPL_REPLICATION_COULD_NOT_CREATE_CHANNEL_LIST error code, 211	ER_RPL_REPLICATION_MONITOR_IO_THREAD_EXITING error code, 593
ER_RPL_REPLICATION_DUMP_THREAD_KILLED_BY_SOURCE error code, 230	ER_RPL_REPLICATION_MONITOR_IO_THREAD_RECONNECT_CHANNEL error code, 593
ER_RPL_REPLICATION_ERROR_INFO_FROM_DA error code, 236	ER_RPL_REPLICATION_NEW_C_M_NEEDS_REPOS_TYPE_OTHER_THAN error code, 240
ER_RPL_REPLICATION_ERROR_LOADING_USER_DEFINED_FILTER error code, 236	ER_RPL_REPLICATION_NEXT_LOG_IS_ACTIVE error code, 238
ER_RPL_REPLICATION_ERROR_READING_FROM_SERVER error code, 230	ER_RPL_REPLICATION_NEXT_LOG_IS_INACTIVE error code, 239
ER_RPL_REPLICATION_ERROR_READING_RELAY_LOG_EVENT error code, 239	ER_RPL_REPLICATION_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION error code, 237
ER_RPL_REPLICATION_ERROR_REQUESTING_BINLOG_DUMP error code, 232	ER_RPL_REPLICATION_QUEUE_EVENT_FAILED_INVALID_NON_ROW error code, 573

---

ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE error code, 237	ER_RPL_SLAVE_CANT_FLUSH_MASTER_INFO_FILE error code, 229
ER_RPL_REPLICA_REPORT_HOST_TOO_LONG error code, 229	ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER error code, 233
ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG error code, 229	ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION error code, 231
ER_RPL_REPLICA_REPORT_USER_TOO_LONG error code, 229	ER_RPL_SLAVE_CANT_START_SLAVE_FOR_CHANNEL error code, 224
ER_RPL_REPLICA_RESET_FILTER_OPTIONS error code, 284	ER_RPL_SLAVE_CANT_STOP_SLAVE_FOR_CHANNEL error code, 225
ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS error code, 228	ER_RPL_SLAVE_CANT_USE_CHARSET error code, 238
ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED error code, 236	ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION error code, 238
ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST error code, 633	ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION error code, 231
ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED error code, 633	ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST error code, 211
ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANGED error code, 633	ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER error code, 230
ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_EVENT error code, 573	ER_RPL_SLAVE_ERROR_LOADING_USER_DEFINED_LIBRARIES error code, 236
ER_RPL_REPLICA_SQL_THREAD_EXITING error code, 237	ER_RPL_SLAVE_ERROR_LOADING_USER_DEFINED_LIBRARIES error code, 236
ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT error code, 239	ER_RPL_SLAVE_ERROR_READING_FROM_SERVER error code, 230
ER_RPL_REPLICA_SQL_THREAD_STARTING error code, 235	ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS error code, 239
ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PROTOCOL_CHECK error code, 571	ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP error code, 232
ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 526	ER_RPL_SLAVE_ERROR_RETRYING error code, 230
ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM error code, 233	ER_RPL_SLAVE_ERROR_RUNNING_QUERY error code, 237
ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_PLUGIN error code, 228	ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER error code, 211
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED error code, 235	ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_INFO_FILE error code, 224
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED_WITH_ERROR error code, 235	ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE error code, 211
ER_RPL_REPO_HAS_GAPS error code, 166	ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE error code, 211
ER_RPL_REPO_SHOULD_BE_TABLE error code, 208	ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH error code, 235
ER_RPL_REWRITEDB_EMPTY_FROM error code, 178	ER_RPL_SLAVE_FILTER_CREATE_FAILED error code, 284
ER_RPL_REWRITEDB_EMPTY_TO error code, 178	ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED error code, 277
ER_RPL_REWRITEDB_MISSING_ARROW error code, 178	ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD error code, 232
ER_RPL_RLI_INIT_INFO_MSG error code, 296	ER_RPL_SLAVE_GENERIC_MESSAGE error code, 210
ER_RPL_SERVER_ID_MISSING error code, 227	ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED error code, 284
ER_RPL_SLAVE_ADDITIONAL_ERROR_INFO_FROM_DA error code, 236	ER_RPL_SLAVE_INCORRECT_CHANNEL error code, 277
ER_RPL_SLAVE_APPLY_LOG_EVENT_FAILED_INVALID_FORMAT error code, 573	
ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF error code, 224	

---

---

ER_RPL_SLAVE_INSECURE_CHANGE_MASTER error code, 276	ER_RPL_SLAVE_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 525
ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_ERROR_LOG_SPACE error code, 233	ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM error code, 233
ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MASTER error code, 232	ER_RPL_SLAVE_USES_CHECKSUM_AND_MASTER_PRE_50 error code, 228
ER_RPL_SLAVE_IO_THREAD_DETECTED_UNEXPECTED_EVENTS_SEQUENCE error code, 238	ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED error code, 234
ER_RPL_SLAVE_IO_THREAD_EXITING error code, 233	ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_WITH error code, 235
ER_RPL_SLAVE_IO_THREAD_KILLED error code, 231	ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED error code, 256
ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 526	ER_RPL_SSL_INFO_IN_MASTER_INFO_IGNORED error code, 256
ER_RPL_SLAVE_IO_THREAD_WAS_KILLED error code, 228	ER_RPL_TIMESTAMPS_RETURNED_TO_NORMAL error code, 283
ER_RPL_SLAVE_MASTER_UUID_HAS_CHANGED error code, 228	ER_RPL_TRX_DELEGATES_INIT_FAILED error code, 184
ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE error code, 235	ER_RPL_UNEXPECTED_BEGIN_IN_STREAM error code, 204
ER_RPL_SLAVE_NEW_MASTER_INFO_NEEDS_REPOSITORY error code, 240	ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOG_EVENT error code, 214
ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE error code, 238	ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM error code, 214
ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE error code, 238	ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM error code, 213
ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION error code, 237	ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG error code, 254
ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_NON_ROW_LOG error code, 573	ER_RPL_WORKER_CANT_READ_RELAY_LOG error code, 254
ER_RPL_SLAVE_READ_INVALID_EVENT_FROM_MASTER error code, 237	ER_RPL_WORKER_ID_IS error code, 208
ER_RPL_SLAVE_REPORT_HOST_TOO_LONG error code, 229	ER_RPL_ZOMBIE_ENCOUNTED error code, 164
ER_RPL_SLAVE_REPORT_PASSWORD_TOO_LONG error code, 229	ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG error code, 112
ER_RPL_SLAVE_REPORT_USER_TOO_LONG error code, 229	ER_RUN_HOOK_ERROR error code, 78
ER_RPL_SLAVE_RESET_FILTER_OPTIONS error code, 284	ER_SAME_NAME_PARTITION error code, 38
ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS error code, 228	ER_SAME_NAME_PARTITION_FIELD error code, 47
ER_RPL_SLAVE_SKIP_COUNTER_EXECUTED error code, 236	ER_SCHEDULER_KILLING error code, 168
ER_RPL_SLAVE_SQL_THREAD_DETECTED_UNEXPECTED_EVENTS_SEQUENCE error code, 573	ER_SCHEDULER_STARTED error code, 168
ER_RPL_SLAVE_SQL_THREAD_EXITING error code, 237	ER_SCHEDULER_STOPPED error code, 167
ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_EVENT error code, 239	ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER error code, 168
ER_RPL_SLAVE_SQL_THREAD_STARTING error code, 235	ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT error code, 168
ER_RPL_SLAVE_SQL_THREAD_STARTING_WITH_PRIVILEGES error code, 571	ER_SCHEDULER_WAITING error code, 168
	ER_SCHEMA_DIR_CREATE_FAILED error code, 105
	ER_SCHEMA_DIR_EXISTS error code, 105
	ER_SCHEMA_DIR_MISSING error code, 105
	ER_SCHEMA_DIR_UNKNOWN error code, 105
	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED error code, 575
	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK error code, 575
	ER_SCHEMA_READ_ONLY error code, 140

---

---

ER_SDI_GET_KEYS_INVALID_TABLESPACE error code, 146	ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD error code, 309
ER_SDI_OPERATION_FAILED error code, 103	ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD error code, 312
ER_SDI_OPERATION_FAILED_MISSING_RECORD error code, 136	ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET error code, 309
ER_SECONDARY_ENGINE error code, 128	ER_SEMISYNC_FORCED_SHUTDOWN error code, 306
ER_SECONDARY_ENGINE_DDL error code, 129	ER_SEMISYNC_FUNCTION_CALLED_TWICE error code, 305
ER_SECONDARY_ENGINE_DDL_FAILED error code, 639	ER_SEMISYNC_INIT_WAIT_POS error code, 307
ER_SECONDARY_ENGINE_PLUGIN error code, 127	ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY error code, 304
ER_SECOND_PASSWORD_CANNOT_BE_EMPTY error code, 127	ER_SEMISYNC_MASTER_FAILED_ON_NET_FLUSH error code, 308
ER_SECURE_AUTH_VALUE_UNSUPPORTED error code, 171	ER_SEMISYNC_MASTER_GOT_REPLY_AT_POS error code, 306
ER_SECURE_TRANSPORT_REQUIRED error code, 83	ER_SEMISYNC_MASTER_OOM error code, 306
ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG error code, 173	ER_SEMISYNC_MASTER_SIGNAL_ALL_WAITING_THREADS error code, 306
ER_SEC_FILE_PRIV_CANT_ACCESS_DIR error code, 172	ER_SEMISYNC_MASTER_TRX_WAIT_POS error code, 307
ER_SEC_FILE_PRIV_CANT_STAT error code, 173	ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT error code, 311
ER_SEC_FILE_PRIV_DIRECTORY_INSECURE error code, 173	ER_SEMISYNC_MOVE_BACK_WAIT_POS error code, 307
ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS error code, 173	ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER error code, 312
ER_SEC_FILE_PRIV_EMPTY error code, 172	ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE error code, 312
ER_SEC_FILE_PRIV_IGNORED error code, 172	ER_SEMISYNC_NO_SPACE_IN_THE_PKT error code, 308
ER_SEC_FILE_PRIV_NULL error code, 173	ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY error code, 304
ER_SELECT_REDUCED error code, 21	ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER error code, 308
ER_SEMISYNC_ADD_ACK_TO_SLOT error code, 308	ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED error code, 311
ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD error code, 307	ER_SEMISYNC_REPLICA_REPLY error code, 311
ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER error code, 304	ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO error code, 311
ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TOO_MANY error code, 305	ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED error code, 312
ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_TOO_MANY error code, 305	ER_SEMISYNC_REPLICA_SET_FAILED error code, 312
ER_SEMISYNC_DISABLED_ON_MASTER error code, 306	ER_SEMISYNC_REPLICA_START error code, 311
ER_SEMISYNC_DISABLED_ON_SOURCE error code, 306	ER_SEMISYNC_REPLICA_REPLY_BINLOG_FILE_TOO_LARGE error code, 305
ER_SEMISYNC_EXECUTION_FAILED_ON_MASTER error code, 312	ER_SEMISYNC_REPLICA_REPLY_MAGIC_NO_ERROR error code, 305
ER_SEMISYNC_EXECUTION_FAILED_ON_SOURCE error code, 312	ER_SEMISYNC_REPLICA_PKT_LENGTH_TOO_SMALL error code, 305
ER_SEMISYNC_FAILED_REGISTER_REPLICA_TO_RECEIVER error code, 309	ER_SEMISYNC_RPL_ENABLED_ON_MASTER error code, 305
ER_SEMISYNC_FAILED_REGISTER_SLAVE_TO_RECEIVER error code, 309	
ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE error code, 304	
ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE error code, 308	

---

---

ER_SEMISYNC_RPL_ENABLED_ON_SOURCE error code, 305	ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED error code, 310
ER_SEMISYNC_RPL_INIT_FOR_TRX error code, 304	ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK error code, 309
ER_SEMISYNC_RPL_SWITCHED_OFF error code, 307	ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK error code, 308
ER_SEMISYNC_SERVER_REPLY error code, 305	ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT error code, 307
ER_SEMISYNC_SLAVE_NET_FLUSH_REPLY_FAILED error code, 311	ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TRX error code, 307
ER_SEMISYNC_SLAVE_REPLY error code, 310	ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT error code, 307
ER_SEMISYNC_SLAVE_REPLY_WITH_BINLOG_INFO error code, 311	ER_SERVERID_TOO_LARGE error code, 182
ER_SEMISYNC_SLAVE_SEND_REPLY_FAILED error code, 311	ER_SERVER_ACL_TABLE_ERROR error code, 532
ER_SEMISYNC_SLAVE_SET_FAILED error code, 312	ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COM error code, 557
ER_SEMISYNC_SLAVE_START error code, 311	ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEA error code, 557
ER_SEMISYNC_SOCKET_FD_TOO_LARGE error code, 310	ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION error code, 561
ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH error code, 308	ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2 error code, 531
ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS error code, 306	ER_SERVER_CANT_OPEN_FILE error code, 531
ER_SEMISYNC_SOURCE_OOM error code, 306	ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2 error code, 532
ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS error code, 306	ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE error code, 532
ER_SEMISYNC_SOURCE_TRX_WAIT_POS error code, 307	ER_SERVER_COST_FAILED_TO_READ error code, 213
ER_SEMISYNC_STARTING_ACK_RECEIVER_THD error code, 309	ER_SERVER_COST_INVALID_COST_CONSTANT error code, 212
ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA error code, 310	ER_SERVER_COST_UNKNOWN_COST_CONSTANT error code, 212
ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE error code, 309	ER_SERVER_DISK_FULL_NOWAIT error code, 531
ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD error code, 309	ER_SERVER_DOWNGRADE_FROM_VERSION error code, 640
ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA error code, 310	ER_SERVER_DOWNGRADE_STATUS error code, 640
ER_SEMISYNC_STOP_BINLOG_DUMP_TO_SLAVE error code, 310	ER_SERVER_FILE_NOT_FOUND error code, 531
ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO error code, 308	ER_SERVER_FILE_USED error code, 531
ER_SEMISYNC_TRACE_ENTER_FUNC error code, 304	ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN error code, 542
ER_SEMISYNC_TRACE_EXIT error code, 304	ER_SERVER_HANDLER_ERROR error code, 531
ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE error code, 304	ER_SERVER_INIT_COMPILED_IN_COMMANDS error code, 296
ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE error code, 304	ER_SERVER_ISNT_AVAILABLE error code, 84
ER_SEMISYNC_TRX_SKIPPED_AT_POS error code, 308	ER_SERVER_IS_IN_SECURE_AUTH_MODE error code, 23
ER_SEMISYNC_UNREGISTERED_REPLICATOR error code, 310	ER_SERVER_MASTER_FATAL_ERROR_READING_BINLOG error code, 528
ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER error code, 310	ER_SERVER_NET_PACKET_TOO_LARGE error code, 530
ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER error code, 310	ER_SERVER_NEW_ABORTING_CONNECTION error code, 531
	ER_SERVER_NOT_FORM_FILE error code, 531

---



---

ER_SERVER_NO_SESSION_TO_SEND_TO error code, 530	ER_SERVER_SLAVE_IGNORED_TABLE error code, 533
ER_SERVER_NO_SYSTEM_TABLE_ACCESS error code, 530	ER_SERVER_SLAVE_INIT_QUERY_FAILED error code, 532
ER_SERVER_OFFLINE_MODE error code, 71	ER_SERVER_SLAVE_MI_INIT_REPOSITORY error code, 530
ER_SERVER_OUTOFMEMORY error code, 281	ER_SERVER_SLAVE_RLI_INIT_REPOSITORY error code, 530
ER_SERVER_OUT_OF_RESOURCES error code, 280	ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG error code, 528
ER_SERVER_OUT_OF_SORTMEMORY error code, 531	ER_SERVER_STARTUP_ADMIN_INTERFACE error code, 549
ER_SERVER_RECORD_FILE_FULL error code, 531	ER_SERVER_STARTUP_MSG error code, 280
ER_SERVER_REPLICA_AM_INIT_REPOSITORY error code, 530	ER_SERVER_TABLE_CHECK_FAILED error code, 532
ER_SERVER_REPLICA_CM_INIT_REPOSITORY error code, 530	ER_SERVER_TEST_MESSAGE error code, 533
ER_SERVER_REPLICA_CONVERSION_FAILED error code, 532	ER_SERVER_UNKNOWN_ERROR error code, 530
ER_SERVER_REPLICA_IGNORED_TABLE error code, 533	ER_SERVER_UNKNOWN_SYSTEM_VARIABLE error code, 530
ER_SERVER_REPLICA_INIT_QUERY_FAILED error code, 532	ER_SERVER_UPGRADE_CHECKING_DB error code, 560
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 552	ER_SERVER_UPGRADE_EMPTY_SYS error code, 559
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY error code, 547	ER_SERVER_UPGRADE_FAILED error code, 558
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 548	ER_SERVER_UPGRADE_FROM_VERSION error code, 553
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 548	ER_SERVER_UPGRADE_HELP_TABLE_STATUS error code, 561
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_KEYS error code, 548	ER_SERVER_UPGRADE_INFO_FILE error code, 559
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY error code, 548	ER_SERVER_UPGRADE_MYSQL_TABLES error code, 559
ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR error code, 548	ER_SERVER_UPGRADE_NO_SYS_VERSION error code, 559
ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY error code, 549	ER_SERVER_UPGRADE_OFF error code, 558
ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY error code, 548	ER_SERVER_UPGRADE_PENDING error code, 558
ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 548	ER_SERVER_UPGRADE_REPAIR_REQUIRED error code, 559
ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 547	ER_SERVER_UPGRADE_REPAIR_STATUS error code, 559
ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERED error code, 548	ER_SERVER_UPGRADE_SKIP error code, 558
ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE error code, 549	ER_SERVER_UPGRADE_STATUS error code, 559
ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY error code, 549	ER_SERVER_UPGRADE_SYSTEM_TABLES error code, 559
ER_SERVER_SHUTDOWN error code, 7	ER_SERVER_UPGRADE_SYS_SCHEMA error code, 558
ER_SERVER_SHUTDOWN_COMPLETE error code, 278	ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT error code, 560
ER_SERVER_SHUTDOWN_INFO error code, 535	ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED error code, 560
ER_SERVER_SLAVE_CONVERSION_FAILED error code, 532	ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE error code, 560
	ER_SERVER_UPGRADE_SYS_VERSION_EMPTY error code, 559
	ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED error code, 553
	ER_SERVER_WARN_DEPRECATED error code, 556

---

---

ER_SERVER_WRONG_VALUE_FOR_VAR error code, 541	ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED error code, 82
ER_SESSION_WAS_KILLED error code, 84	ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER error code, 77
ER_SETNS_FAILED error code, 562	ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP error code, 77
ER_SET_CONSTANTS_ONLY error code, 18	ER_SLAVE_CHANNEL_WAS_NOT_RUNNING error code, 76
ER_SET_EVENT_FAILED error code, 536	ER_SLAVE_CHANNEL_WAS_RUNNING error code, 76
ER_SET_PASSWORD_AUTH_PLUGIN error code, 50	ER_SLAVE_CONFIGURATION error code, 59
ER_SET_PASSWORD_AUTH_PLUGIN_ERROR error code, 155	ER_SLAVE_CONVERSION_FAILED error code, 49
ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION error code, 57	ER_SLAVE_CORRUPT_EVENT error code, 43
ER_SE_TYPECODE_CONFLICT error code, 188	ER_SLAVE_CREATE_EVENT_FAILURE error code, 528
ER_SHA256_PASSWORD_SECOND_PASSWORD_USED error code, 550	ER_SLAVE_FATAL_ERROR error code, 528
ER_SHAPE_PREDICTION_UDF error code, 157	ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER error code, 68
ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE error code, 543	ER_SLAVE_HEARTBEAT_FAILURE error code, 529
ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL error code, 320	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE error code, 44
ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH error code, 320	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX error code, 51
ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING error code, 319	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN error code, 51
ER_SHA_PWD_RSA_KEY_TOO_LONG error code, 320	ER_SLAVE_IGNORED_SSL_PARAMS error code, 23
ER_SHA_PWD_SALT_FOR_USER_CORRUPT error code, 320	ER_SLAVE_IGNORED_TABLE error code, 20
ER_SHUTDOWN_COMPLETE error code, 8	ER_SLAVE_IGNORE_SERVER_IDS error code, 46
ER_SHUTTING_DOWN_REPLICA_THREADS error code, 175	ER_SLAVE_INCIDENT error code, 529
ER_SHUTTING_DOWN_SLAVE_THREADS error code, 175	ER_SLAVE_KILLED_AFTER_RECONNECT error code, 292
ER_SIGNAL_BAD_CONDITION_TYPE error code, 46	ER_SLAVE_MASTER_COM_FAILURE error code, 529
ER_SIGNAL_EXCEPTION error code, 46	ER_SLAVE_MAX_CHANNELS_EXCEEDED error code, 76
ER_SIGNAL_NOT_FOUND error code, 46	ER_SLAVE_MI_INIT_REPOSITORY error code, 66
ER_SIGNAL_WARN error code, 46	ER_SLAVE_MULTIPLE_CHANNELS_CMD error code, 75
ER_SIZE_OVERFLOW_ERROR error code, 39	ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY error code, 75
ER_SKIP_UPDATING_METADATA_IN_SE_RDONLY_MODE error code, 291	ER_SLAVE_NOT_RUNNING error code, 17
ER_SLAVE_ANONYMOUS_TO_GTID_IS_LOCAL_OR_UNKNOWN error code, 593	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 292
ER_SLAVE_CANT_CREATE_CONVERSION error code, 49	ER_SLAVE_POSSIBLY_DIVERGED_AFTER_DDL error code, 110
ER_SLAVE_CANT_USE_TEMPDIR error code, 240	ER_SLAVE_RECONNECT_FAILED error code, 292
ER_SLAVE_CHANGE_MASTER_TO_EXECUTED error code, 239	ER_SLAVE_RELAY_LOG_PURGE_FAILED error code, 284
ER_SLAVE_CHANNEL_DOES_NOT_EXIST error code, 75	ER_SLAVE_RELAY_LOG_READ_FAILURE error code, 529
ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP error code, 70	ER_SLAVE_RELAY_LOG_TRUNCATE_INFO error code, 283
ER_SLAVE_CHANNEL_MUST_STOP error code, 76	ER_SLAVE_RELAY_LOG_WRITE_FAILURE error code, 529
ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG error code, 75	ER_SLAVE_RLI_INIT_REPOSITORY error code, 66
ER_SLAVE_CHANNEL_NOT_RUNNING error code, 76	

---

---

ER_SLAVE_SILENT_RETRY_TRANSACTION error code, 61	ER_SP_DROP_FAILED error code, 25
ER_SLAVE_SQL_THREAD_MUST_STOP error code, 70	ER_SP_DUP_COND error code, 27
ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS error code, 204	ER_SP_DUP_CURS error code, 27
ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS error code, 203	ER_SP_DUP_HANDLER error code, 32
ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS error code, 203	ER_SP_DUP_PARAM error code, 27
ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS error code, 203	ER_SP_DUP_VAR error code, 27
ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROCESS error code, 204	ER_SP_FETCH_NO_DATA error code, 27
ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_CONDITION error code, 203	ER_SP_LABEL_MISMATCH error code, 26
ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITION error code, 203	ER_SP_LABEL_REDEFINE error code, 26
ER_SLAVE_THREAD error code, 17	ER_SP_LILABEL_MISMATCH error code, 25
ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ERROR error code, 71	ER_SP_LOAD_FAILED error code, 88
ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING error code, 118	ER_SP_NORETURN error code, 26
ER_SOURCE error code, 16	ER_SP_NORETURNEND error code, 26
ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE error code, 53	ER_SP_NOT_VAR_ARG error code, 32
ER_SOURCE_FATAL_ERROR_READING_BINLOG error code, 20	ER_SP_NO_DROP_SP error code, 29
ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS error code, 59	ER_SP_NO_RECURSION error code, 32
ER_SOURCE_NET_READ error code, 16	ER_SP_NO_RECURSIVE_CREATE error code, 25
ER_SOURCE_NET_WRITE error code, 16	ER_SP_NO_RESET error code, 32
ER_SPATIAL_CANT_HAVE_NULL error code, 21	ER_SP_NO_RECURSION_LIMIT error code, 35
ER_SPATIAL_FUNCTIONAL_INDEX error code, 114	ER_SP_STORE_FAILED error code, 25
ER_SPATIAL_MUST_HAVE_GEOM_COL error code, 49	ER_SP_SUBSELECT_NYI error code, 27
ER_SPATIAL_UNIQUE_INDEX error code, 110	ER_SP_UNDECLARED_VAR error code, 27
ER_SPECIFIC_ACCESS_DENIED_ERROR error code, 20	ER_SP_UNINIT_VAR error code, 26
ER_SPVAR_NONINTEGER_TYPE error code, 143	ER_SP_VARCOND_AFTER_CURSHNDLR error code, 27
ER_SP_ALREADY_EXISTS error code, 25	ER_SP_WRONG_NAME error code, 35
ER_SP_BADRETURN error code, 26	ER_SP_WRONG_NO_OF_ARGS error code, 26
ER_SP_BADSELECT error code, 26	ER_SP_WRONG_NO_OF_FETCH_ARGS error code, 27
ER_SP_BADSTATEMENT error code, 26	ER_SQLTHREAD_WITH_SECURE_REPLICA error code, 56
ER_SP_BAD_CURSOR_QUERY error code, 26	ER_SQLTHREAD_WITH_SECURE_SLAVE error code, 56
ER_SP_BAD_CURSOR_SELECT error code, 26	ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL error code, 187
ER_SP_BAD_SQLSTATE error code, 31	ER_SQL_HA_READ_FAILED error code, 184
ER_SP_BAD_VAR_SHADOW error code, 34	ER_SQL_MODE_MERGED error code, 81
ER_SP_CANT_ALTER error code, 27	ER_SQL_MODE_MERGED_WITH_STRICT_MODE error code, 279
ER_SP_CANT_SET_AUTOCOMMIT error code, 34	ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE error code, 144
ER_SP_CASE_NOT_FOUND error code, 28	ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID_MODE error code, 65
ER_SP_COND_MISMATCH error code, 26	ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE error code, 144
ER_SP_CURSOR_AFTER_HANDLER error code, 27	ER_SQL_USER_TABLE ALTER WARNING error code, 187
ER_SP_CURSOR_ALREADY_OPEN error code, 27	ER_SQL_USER_TABLE_CREATE WARNING error code, 187
ER_SP_CURSOR_MISMATCH error code, 27	ER_SRS_ATTRIBUTE_STRING_TOO_LONG error code, 109
ER_SP_CURSOR_NOT_OPEN error code, 27	ER_SRS_GEOGCS_INVALID_AXES error code, 111
ER_SP_DOES_NOT_EXIST error code, 25	ER_SRS_ID_ALREADY_EXISTS error code, 108

---

---

ER_SRS_INVALID_ANGULAR_UNIT error code, 111	ER_STD_BAD_ALLOC_ERROR error code, 72
ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE error code, 109	ER_STD_DOMAIN_ERROR error code, 72
ER_SRS_INVALID_HEIGHT error code, 157	ER_STD_INVALID_ARGUMENT error code, 73
ER_SRS_INVALID_INVERSE_FLATTENING error code, 111	ER_STD_LENGTH_ERROR error code, 73
ER_SRS_INVALID_LATITUDE_OF_ORIGIN error code, 155	ER_STD_LOGIC_ERROR error code, 73
ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A error code, 158	ER_STD_OUT_OF_RANGE_ERROR error code, 73
ER_SRS_INVALID_LONGITUDE_OF_ORIGIN error code, 155	ER_STD_OVERFLOW_ERROR error code, 73
ER_SRS_INVALID_PRIME_MERIDIAN error code, 111	ER_STD_RANGE_ERROR error code, 73
ER_SRS_INVALID_SCALING error code, 157	ER_STD_REGEX_ERROR error code, 124
ER_SRS_INVALID_SEMI_MAJOR_AXIS error code, 111	ER_STD_RUNTIME_ERROR error code, 73
ER_SRS_INVALID_ZONE_WIDTH error code, 157	ER_STD_UNDERFLOW_ERROR error code, 73
ER_SRS_MISSING_MANDATORY_ATTRIBUTE error code, 108	ER_STD_UNKNOWN_EXCEPTION error code, 73
ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS error code, 108	ER_STMT_CACHE_FULL error code, 51
ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE error code, 108	ER_STMT_HAS_NO_OPEN_CURSOR error code, 32
ER_SRS_NOT_CARTESIAN error code, 89	ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG error code, 27
ER_SRS_NOT_CARTESIAN_UNDEFINED error code, 89	ER_STOP_REPLICA_IO_THREAD_DISK_SPACE error code, 321
ER_SRS_NOT_FOUND error code, 91	ER_STOP_REPLICA_IO_THREAD_TIMEOUT error code, 67
ER_SRS_NOT_GEOGRAPHIC error code, 110	ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT error code, 143
ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE error code, 108	ER_STOP_REPLICA_SQL_THREAD_TIMEOUT error code, 66
ER_SRS_PARSE_ERROR error code, 88	ER_STOP_SLAVE_IO_THREAD_DISK_SPACE error code, 321
ER_SRS_PROJ_PARAMETER_MISSING error code, 88	ER_STOP_SLAVE_IO_THREAD_TIMEOUT error code, 66
ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT error code, 155	ER_STOP_SLAVE_SQL_THREAD_TIMEOUT error code, 66
ER_SR_BOGUS_VALUE error code, 184	ER_STORAGE_ENGINE_NOT_LOADED error code, 68
ER_SR_INVALID_CONTEXT error code, 184	ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_DIRECT error code, 49
ER_SSL_FIPS_MODE_ERROR error code, 322	ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT error code, 41
ER_SSL_LIBRARY_ERROR error code, 170	ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN error code, 50
ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED error code, 543	ER_SUBPARTITION_ERROR error code, 37
ER_SSL_SERVER_CERT_VERIFY_FAILED error code, 562	ER_SUBPARTITION_NAME error code, 45
ER_SSL_TRYING_DATADIR_DEFAULTS error code, 181	ER_SUBQUERY_NO_1_ROW error code, 21
ER_STACKSIZE_UNEXPECTED error code, 180	ER_SUBQUERY_TRANSFORM_REJECTED error code, 138
ER_STACK_BACKTRACE error code, 627	ER_SWITCH_TMP_ENGINE error code, 94
ER_STACK_OVERRUN error code, 11	ER_SYNTAX_ERROR error code, 14
ER_STACK_OVERRUN_NEED_MORE error code, 33	ER_SYSTEMD_NOTIFY_CONNECT_FAILED error code, 387
ER_STARTING_AS error code, 174	ER_SYSTEMD_NOTIFY_DEBUG error code, 625
ER_STARTING_INIT error code, 535	ER_SYSTEMD_NOTIFY_PATH_TOO_LONG error code, 387
ER_STARTING_REPLICA_MONITOR_IO_THREAD error code, 143	ER_SYSTEMD_NOTIFY_WRITE_FAILED error code, 387
ER_STARTUP error code, 31	ER_SYSTEM_SCHEMA_NOT_FOUND error code, 164
ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION error code, 139	ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE error code, 280

---

---

ER_SYSTEM_TABLE_NOT_TRANSACTIONAL error code, 255	ER_TABLE_IN_FK_CHECK error code, 53
ER_SYSTEM_VIEW_INIT_FAILED error code, 281	ER_TABLE_IN_SHARED_TABLESPACE error code, 158
ER_SYSVAR_CHANGE_DURING_QUERY error code, 131	ER_TABLE_IN_SYSTEM_TABLESPACE error code, 61
ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_PERSISTENT error code, 321	ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN error code, 11
ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE_OPTIONS error code, 321	ER_TABLE_MUST_HAVE_COLUMNS error code, 11
ER_SYS_VAR_COMPONENT_OOM error code, 321	ER_TABLE_NAME error code, 45
ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE error code, 321	ER_TABLE_NAME_CAUSES_TOO_LONG_PATH error code, 131
ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY error code, 321	ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED error code, 575
ER_SYS_VAR_DEREGISTRATION error code, 637	ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_F error code, 575
ER_SYS_VAR_NOT_FOUND error code, 537	ER_TABLE_NEEDS_DUMP_UPGRADE error code, 299
ER_SYS_VAR_REGISTRATION error code, 637	ER_TABLE_NEEDS_REBUILD error code, 51
ER_TABLEACCESS_DENIED_ERROR error code, 13	ER_TABLE_NEEDS_UPGRADE error code, 35
ER_TABLENAME_NOT_ALLOWED_HERE error code, 21	ER_TABLE_NOT_EMPTY error code, 158
ER_TABLESPACE_AUTO_EXTEND_ERROR error code, 39	ER_TABLE_NOT_LOCKED error code, 10
ER_TABLESPACE_CANNOT_BE_DECRYPTED error code, 122	ER_TABLE_NOT_LOCKED_FOR_WRITE error code, 10
ER_TABLESPACE_CANNOT_BE_ENCRYPTED error code, 122	ER_TABLE_NO_PRIMARY_KEY error code, 158
ER_TABLESPACE_CANNOT_ENCRYPT error code, 85	ER_TABLE_REFERENCED error code, 86
ER_TABLESPACE_DISCARDED error code, 61	ER_TABLE_SCHEMA_MISMATCH error code, 61
ER_TABLESPACE_DUP_FILENAME error code, 97	ER_TABLE_UPGRADE_REQUIRED error code, 279
ER_TABLESPACE_ENGINE_MISMATCH error code, 101	ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT error code, 135
ER_TABLESPACE_EXISTS error code, 61	ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS error code, 135
ER_TABLESPACE_IS_NOT_EMPTY error code, 80	ER_TABLE_WITHOUT_PK error code, 113
ER_TABLESPACE_MISSING error code, 61	ER_TABLE_WRONG_KEY_DEFINITION error code, 199
ER_TABLESPACE_MISSING_WITH_NAME error code, 88	ER_TARGET_TABLESPACE_UNENCRYPTED error code, 122
ER_TABLESPACE_TYPE_UNKNOWN error code, 122	ER_TARGET_TS_UNENCRYPTED error code, 537
ER_TABLES_DIFFERENT_METADATA error code, 54	ER_TC_BAD_MAGIC_IN_TC_LOG error code, 223
ER_TABLE_CANT_HANDLE_AUTO_INCREMENT error code, 14	ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVERY error code, 223
ER_TABLE_CANT_HANDLE_BLOB error code, 14	ER_TC_HEURISTIC_RECOVERY_FAILED error code, 223
ER_TABLE_CANT_HANDLE_FT error code, 19	ER_TC_HEURISTIC_RECOVERY_MODE error code, 223
ER_TABLE_CANT_HANDLE_SPKEYS error code, 35	ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY error code, 223
ER_TABLE_CHECK_INTACT error code, 183	ER_TC_RECOVERING_AFTER_CRASH_USING error code, 223
ER_TABLE_CORRUPT error code, 67	ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS error code, 223
ER_TABLE_CREATED_WITH_DIFFERENT_VERSION error code, 200	ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER error code, 224
ER_TABLE_DEF_CHANGED error code, 32	ER_TEMPORARY_NAME error code, 45
ER_TABLE_EXISTS_ERROR error code, 6	ER_TEMP_FILE_WRITE_FAILURE error code, 67
ER_TABLE_HAS_NO_FT error code, 57	ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_F error code, 112
ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD error code, 199	ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR error code, 41
ER_TABLE_INCOMPATIBLE_YEAR_FIELD error code, 199	

---

---

ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT error code, 112	ER_THREAD_POOL_SIZE_TOO_HIGH error code, 301
ER_TEXTFILE_NOT_READABLE error code, 9	ER_THREAD_POOL_SIZE_TOO_LOW error code, 301
ER_TF_FORBIDDEN_JOIN_TYPE error code, 104	ER_THREAD_POOL_SYSVAR_CHANGE error code, 627
ER_TF_MUST_HAVE_ALIAS error code, 103	ER_THREAD_PRIORITY_IGNORED error code, 277
ER_THE_USER_ABIDES error code, 177	ER_TLS_CONFIGURATION_REUSED error code, 584
ER_THREAD_HANDLING_OOM error code, 172	ER_TLS_CONFIGURED_FOR_CHANNEL error code, 584
ER_THREAD_POOL_ALGORITHM_INVALID error code, 301	ER_TMPDIR_PATH_TOO_LONG error code, 590
ER_THREAD_POOL_BUFFER_TOO_SMALL error code, 302	ER_TMP_SESSION_FOR_VAR error code, 625
ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PLUGIN error code, 625	ER_TOO_BIG_DISPLAYWIDTH error code, 33
ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA error code, 301	ER_TOO_BIG_ENUM error code, 87
ER_THREAD_POOL_CONNECTION_REPORT error code, 639	ER_TOO_BIG_FIELDLENGTH error code, 8
ER_THREAD_POOL_CON_HANDLER_INIT_FAILED error code, 301	ER_TOO_BIG_FOR_UNCOMPRESS error code, 22
ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID error code, 615	ER_TOO_BIG_PRECISION error code, 33
ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT error code, 302	ER_TOO_BIG_ROWSIZE error code, 11
ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER error code, 302	ER_TOO_BIG_SCALE error code, 33
ER_THREAD_POOL_FAILED_TO_CREATE_POOL error code, 302	ER_TOO_BIG_SELECT error code, 10
ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONNECTION error code, 302	ER_TOO_BIG_SET error code, 10
ER_THREAD_POOL_IDLE_CONNECTION_CLOSED error code, 632	ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT error code, 36
ER_THREAD_POOL_INIT_FAILED error code, 301	ER_TOO_LONG_BODY error code, 33
ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER error code, 301	ER_TOO_LONG_FIELD_COMMENT error code, 45
ER_THREAD_POOL_INVALID_STALL_LIMIT error code, 301	ER_TOO_LONG_IDENT error code, 7
ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED error code, 302	ER_TOO_LONG_INDEX_COMMENT error code, 50
ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID error code, 301	ER_TOO_LONG_KEY error code, 8
ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM error code, 300	ER_TOO_LONG_ROUTINE_COMMENT error code, 88
ER_THREAD_POOL_PFS_TABLES_ADD_FAILED error code, 547	ER_TOO_LONG_SET_ENUM_VALUE error code, 88
ER_THREAD_POOL_PFS_TABLES_INIT_FAILED error code, 547	ER_TOO_LONG_STRING error code, 14
ER_THREAD_POOL_PLUGIN_STARTED error code, 615	ER_TOO_LONG_TABLESPACE_COMMENT error code, 97
ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID error code, 627	ER_TOO_LONG_TABLE_COMMENT error code, 45
ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT error code, 628	ER_TOO_LONG_TABLE_PARTITION_COMMENT error code, 59
ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS error code, 302	ER_TOO_MANY_CONCURRENT_CLONES error code, 100
	ER_TOO_MANY_CONCURRENT_TRXS error code, 45
	ER_TOO_MANY_FIELDS error code, 11
	ER_TOO_MANY_KEYS error code, 8
	ER_TOO_MANY_KEY_PARTS error code, 8
	ER_TOO_MANY_PARTITIONS_ERROR error code, 37
	ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR error code, 47
	ER_TOO_MANY_ROWS error code, 15
	ER_TOO_MANY_STORAGE_ENGINES error code, 188
	ER_TOO_MANY_TABLES error code, 11
	ER_TOO_MANY_USER_CONNECTIONS error code, 18
	ER_TOO_MANY_VALUES_ERROR error code, 47
	ER_TOO_MANY_WINDOWS error code, 153
	ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT error code, 628
	ER_TRACK_VARIABLES_BOGUS error code, 178
	ER_TRANSACTION_ROLLBACK_DURING_COMMIT error code, 78

---

---

ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84 error code, 112	ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID error code, 201
ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED error code, 112	ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE error code, 201
ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84 error code, 112	ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE error code, 201
ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED error code, 112	ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE error code, 202
ER_TRANSPORTS_WHAT_TRANSPORTS error code, 175	ER_TZ_OOM_INITIALIZING_TIME_ZONES error code, 200
ER_TRANS_CACHE_FULL error code, 17	ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE error code, 201
ER_TREE_CORRUPT_2_CONSECUTIVE_REDS error code, 253	ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION error code, 202
ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT error code, 254	ER_TZ_OOM_WHILE_LOADING_TIME_ZONE error code, 202
ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT error code, 253	ER_TZ_OOM_WHILE_SETTING_TIME_ZONE error code, 203
ER_TREE_CORRUPT_RIGHT_IS_LEFT error code, 254	ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE error code, 201
ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK error code, 253	ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE error code, 202
ER_TRG_ALREADY_EXISTS error code, 29	ER_TZ_TRANSITION_TABLE_LOAD_ERROR error code, 202
ER_TRG_CANT_CHANGE_ROW error code, 29	ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS error code, 202
ER_TRG_CANT_OPEN_TABLE error code, 43	ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEEDED error code, 202
ER_TRG_CANT_PARSE error code, 183	ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR error code, 202
ER_TRG_CORRUPTED_FILE error code, 43	ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE error code, 201
ER_TRG_CREATION_CTX_NOT_SET error code, 279	ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE error code, 201
ER_TRG_DOES_NOT_EXIST error code, 29	ER_UDF_ALREADY_EXISTS error code, 536
ER_TRG_INVALID_CREATION_CTX error code, 43	ER_UDF_CANT_ALLOC_FOR_FUNCTION error code, 185
ER_TRG_IN_WRONG_SCHEMA error code, 33	ER_UDF_CANT_ALLOC_FOR_STRUCTURES error code, 185
ER_TRG_NO_CLIENT_CHARSET error code, 169	ER_UDF_CANT_OPEN_FUNCTION_TABLE error code, 186
ER_TRG_NO_CREATION_CTX error code, 43	ER_UDF_DEREGISTRATION error code, 637
ER_TRG_NO_DEFINER error code, 35	ER_UDF_DROP_DYNAMICALLY_REGISTERED error code, 99
ER_TRG_NO_SUCH_ROW_IN_TRG error code, 29	ER_UDF_ERROR error code, 86
ER_TRG_ON_VIEW_OR_TEMP_TABLE error code, 29	ER_UDF_EXEC_FAILURE error code, 637
ER_TRG_WITHOUT_DEFINER error code, 169	ER_UDF_EXEC_FAILURE_REASON error code, 637
ER_TRG_WRONG_ORDER error code, 553	ER_UDF_EXISTS error code, 12
ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED error code, 302	ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE error code, 186
ER_TRIGGER_INVALID_VALUE error code, 163	ER_UDF_NO_PATHS error code, 12
ER_TRUNCATED_WRONG_VALUE error code, 24	ER_UDF_REGISTER_ERROR error code, 590
ER_TRUNCATED_WRONG_VALUE_FOR_FIELD error code, 29	ER_UDF_REGISTER_SERVICE_ERROR error code, 590
ER_TRUNCATE_ILLEGAL_FK error code, 50	
ER_TRX_GTID_COLLECT_REJECT error code, 187	
ER_TRX_WRITE_SET_OOM error code, 188	
ER_TURNING_LOGGING_OFF_FOR_THE_DURATION error code, 272	
ER_TURNING_ON_PARTIAL_REVOKES error code, 557	
ER_TX_EXTRACTION_ALGORITHM_FOR_BINLOG_TX_DENIED error code, 283	
ER_TZ_CANT_BUILD_MKTIME_MAP error code, 202	
ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE error code, 201	

---

---

ER_UDF_REGISTRATION error code, 637	ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE error code, 537
ER_UDF_UNREGISTER_ERROR error code, 590	ER_UNRESOLVED_HINT_NAME error code, 80
ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT error code, 123	ER_UNRESOLVED_TABLE_LOCK error code, 93
ER_UNABLE_TO_BUILD_HISTOGRAM error code, 99	ER_UNSUPPORTED_LOG_ENGINE error code, 42
ER_UNABLE_TO_COLLECT_LOG_STATUS error code, 109	ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATED error code, 115
ER_UNABLE_TO_DROP_COLUMN_STATISTICS error code, 99	ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN error code, 79
ER_UNABLE_TO_RESOLVE_HOSTNAME error code, 168	ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE error code, 85
ER_UNABLE_TO_RESOLVE_IP error code, 168	ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN error code, 79
ER_UNABLE_TO_SET_OPTION error code, 110	ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN error code, 85
ER_UNABLE_TO_STORE_COLUMN_STATISTICS error code, 99	ER_UNSUPPORTED_DATE error code, 174
ER_UNABLE_TO_STORE_STATISTICS error code, 91	ER_UNSUPPORTED_ENGINE error code, 53
ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS error code, 99	ER_UNSUPPORTED_EXTENSION error code, 11
ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN error code, 105	ER_UNSUPPORTED_INDEX_ALGORITHM error code, 87
ER_UNDO_RECORD_TOO_BIG error code, 52	ER_UNSUPPORTED_PS error code, 25
ER_UNEXPECTED_GEOMETRY_TYPE error code, 88	ER_UNSUPPORTED_SQL_MODE error code, 130
ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF error code, 38	ER_UNSUPPORTED_USE_OF_GRANT_AS error code, 123
ER_UNIT_NOT_FOUND error code, 130	ER_UNSUPPORT_COMPRESSED_TEMPORARY_TABLE error code, 87
ER_UNKNOWN_ALTER_ALGORITHM error code, 60	ER_UNTIL_COND_IGNORED error code, 24
ER_UNKNOWN_ALTER_LOCK error code, 60	ER_UPDATE_GTID_PURGED_WITH_GR error code, 131
ER_UNKNOWN_AUTHID error code, 89	ER_UPDATE_INFO error code, 12
ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE error code, 285	ER_UPDATE_LOG_DEPRECATED_IGNORED error code, 26
ER_UNKNOWN_CHARACTER_SET error code, 11	ER_UPDATE_LOG_DEPRECATED_TRANSLATED error code, 26
ER_UNKNOWN_COLLATION error code, 23	ER_UPDATE_TABLE_USED error code, 9
ER_UNKNOWN_COM_ERROR error code, 6	ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE error code, 15
ER_UNKNOWN_ERROR error code, 10	ER_UPDATING_DD_TABLE error code, 88
ER_UNKNOWN_ERROR_DETECTED_IN_SE error code, 291	ER_UPGRADE_NONEXISTENT_SCHEMA error code, 591
ER_UNKNOWN_ERROR_NUMBER error code, 185	ER_UPGRADE_PARSE_ERROR error code, 542
ER_UNKNOWN_EXPLAIN_FORMAT error code, 59	ER_UPGRADE_WITH_PARTITIONED_TABLES_REJECTED error code, 569
ER_UNKNOWN_KEY_CACHE error code, 24	ER_USAGE_DEPRECATION_COUNTER error code, 641
ER_UNKNOWN_LOCALE error code, 46	ER_USERNAME error code, 35
ER_UNKNOWN_NETWORK_NAMESPACE error code, 561	ER_USERNAME_TRUNCATED error code, 584
ER_UNKNOWN_PARTITION error code, 54	ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED error code, 136
ER_UNKNOWN_PROCEDURE error code, 10	ER_USER_ALREADY_EXISTS error code, 83
ER_UNKNOWN_STMT_HANDLER error code, 21	ER_USER_COLUMN_OLD_LENGTH error code, 85
ER_UNKNOWN_STORAGE_ENGINE error code, 24	ER_USER_DOES_NOT_EXIST error code, 83
ER_UNKNOWN_SYSTEM_VARIABLE error code, 16	ER_USER_LIMIT_REACHED error code, 19
ER_UNKNOWN_TABLE error code, 11	ER_USER_LOCK_DEADLOCK error code, 74
ER_UNKNOWN_TABLESPACE_TYPE error code, 543	
ER_UNKNOWN_TABLE_IN_UPGRADE error code, 568	
ER_UNKNOWN_TARGET_BINLOG error code, 30	
ER_UNKNOWN_TIME_ZONE error code, 25	
ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE error code, 170	



ER_USER_LOCK_OVERLONG_NAME error code, 162	ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED error code, 389
ER_USER_LOCK_WRONG_NAME error code, 73	ER_INVALID_TIMESTAMP error code, 198
ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPLETE error code, 198	ER_INVALID_TIMESTAMP_NOT_INT_TYPE_ERROR error code, 50
ER_USER_REFERENCED_AS_DEFINER error code, 142	ER_VALUE_OUT_OF_RANGE error code, 152
ER_USER_REGISTRATION_FAILED error code, 150	ER_VARIABLE_IS_NOT_STRUCT error code, 23
ER_USER_REQUIRES_ROOT error code, 175	ER_VARIABLE_IS_READONLY error code, 44
ER_USER_WHAT_USER error code, 175	ER_VARIABLE_NOT_PERSISTED error code, 91
ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTION error code, 144	ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER error code, 57
ER_UUID_INVALID error code, 170	ER_VARIABLE_NOT_SETTABLE_IN_SP error code, 63
ER_UUID_IS error code, 170	ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION error code, 57
ER_UUID_SALT error code, 170	ER_VAR_CANT_BE_READ error code, 20
ER_UUID_SCRUB error code, 170	ER_VAR_DOES_NOT_EXIST error code, 98
ER_VALGRIND_COUNT_LEAKS error code, 185	ER_VERBOSE_HINT error code, 178
ER_VALGRIND_DO_QUICK_LEAK_CHECK error code, 185	ER_VERBOSE_REQUIRES_HELP error code, 171
ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGED error code, 162	ER_VIEW_CHECKSUM error code, 30
ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED error code, 389	ER_VIEW_CHECK_FAILED error code, 29
ER_VALIDATE_PWD_COULD_BE_NULL error code, 388	ER_VIEW_CREATION_CTX_NOT_SET error code, 279
ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED error code, 318	ER_VIEW_DELETE_MERGE_VIEW error code, 31
ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED error code, 317	ER_VIEW_FRM_NO_USER error code, 34
ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED error code, 388	ER_VIEW_INVALID error code, 29
ER_VALIDATE_PWD_DICT_FILE_TOO_BIG error code, 318	ER_VIEW_INVALID_CREATION_CTX error code, 43
ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX error code, 318	ER_VIEW_MULTIUPDATE error code, 30
ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX error code, 318	ER_VIEW_NONUPD_CHECK error code, 29
ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE error code, 318	ER_VIEW_NO_CREATION_CTX error code, 43
ER_VALIDATE_PWD_LENGTH_CHANGED error code, 318	ER_VIEW_NO_EXPLAIN error code, 28
ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED error code, 388	ER_VIEW_NO_INSERT_FIELD_LIST error code, 31
ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED error code, 388	ER_VIEW_OTHER_USER error code, 34
ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED error code, 388	ER_VIEW_PREVENT_UPDATE error code, 34
ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED error code, 388	ER_VIEW_RECURSIVE error code, 35
ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED error code, 389	ER_VIEW_SELECT_CLAUSE error code, 28
ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED error code, 389	ER_VIEW_SELECT_TMPTABLE error code, 28
ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED error code, 389	ER_VIEW_SELECT_VARIABLE error code, 28
	ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION error code, 164
	ER_VIEW_UNPARSABLE error code, 200
	ER_VIEW_WRONG_LIST error code, 28
	ER_VTOKEN_PLUGIN_TOKEN_MISMATCH error code, 150
	ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND error code, 150
	ER_WAITING_FOR_NO_CONNECTIONS error code, 601
	ER_WAITING_FOR_NO_THDS error code, 641
	ER_WAITPID_FAILED error code, 297
	ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES error code, 150
	ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID error code, 549
	ER_WARNING_NOT_COMPLETE_ROLLBACK error code, 17

---

ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATE_TEMPORARY TABLE error code, 22	ER_WARN_DATA_OUT_OF_RANGE error code, 22
error code, 55	ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX error code, 113
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROP_TEMPORARY TABLE error code, 113	ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX error code, 113
error code, 55	ER_WARN_DA_PRIVILEGE_NOT_REGISTERED error code, 113
ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID error code, 101	ER_WARN_DEPRECATED_CHARSET_OPTION error code, 612
error code, 101	ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION error code, 158
ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSES_VOID error code, 549	ER_WARN_DEPRECATED_COLLATION error code, 150
error code, 549	ER_WARN_DEPRECATED_COLLATION_OPTION error code, 603
ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS error code, 147	ER_WARN_DEPRECATED_DATETIME_DELIMITER error code, 154
error code, 147	ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT error code, 125
ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS error code, 603	ER_WARN_DEPRECATED_FLOAT_DIGITS error code, 125
error code, 603	ER_WARN_DEPRECATED_FLOAT_UNSIGNED error code, 125
ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATION_SIZE error code, 147	ER_WARN_DEPRECATED_FOUND_ROWS error code, 137
error code, 147	ER_WARN_DEPRECATED_IDENT error code, 157
ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATION_SIZE error code, 603	ER_WARN_DEPRECATED_INNER_INTO error code, 137
error code, 603	ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH error code, 125
ER_WARN_ALLOWED_PACKET_OVERFLOWED error code, 25	ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_EMPTY error code, 137
code, 25	ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX error code, 116
ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAME_ERROR error code, 146	ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER error code, 641
error code, 146	ER_WARN_DEPRECATED_SQLMODE error code, 77
ER_WARN_AUDIT_LOG_DISABLED error code, 612	ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS error code, 137
error code, 612	ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER error code, 154
ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_OR_ISO_TIMESTAMP error code, 148	ER_WARN_DEPRECATED_SYNTAX error code, 24
error code, 148	ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT error code, 49
ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_OR_ISO_TIMESTAMP error code, 605	ER_WARN_DEPRECATED_SYNTAX_WITH_VER error code, 40
error code, 605	ER_WARN_DEPRECATED_SYSVAR_UPDATE error code, 7
ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROWS error code, 572	ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL error code, 601
error code, 572	ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL_CLI error code, 147
ER_WARN_BAD_MAX_EXECUTION_TIME error code, 80	ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS error code, 162
error code, 80	
ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED error code, 101	
error code, 101	
ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_UPDATES error code, 101	
error code, 101	
ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED error code, 101	
error code, 101	
ER_WARN_CANNOT_FREE_COMPONENT_DATA DEALLOCATION FAILED error code, 635	
error code, 635	
ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES error code, 613	
error code, 613	
ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES error code, 154	
error code, 154	
ER_WARN_CANT_DROP_DEFAULT_KEYCACHE error code, 33	
code, 33	
ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_ERROR error code, 138	
error code, 138	
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFESTATION error code, 634	
error code, 634	
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFESTATION error code, 596	
error code, 596	
ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY error code, 627	
error code, 627	
ER_WARN_CONFLICTING_HINT error code, 80	
error code, 80	
ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POSITION error code, 151	
error code, 151	

---

---

ER_WARN_DEPRECATED_USER_DEFINED_COLLATION error code, 634	ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND error code, 596
ER_WARN_DEPRECATED_USER_SET_EXPR error code, 116	ER_WARN_NO_SERVERID_SPECIFIED error code, 278
ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION error code, 543	ER_WARN_NO_SPACE_VERSION_COMMENT error code, 162
ER_WARN_DEPRECATED_UTF8MB3_COLLATION error code, 116	ER_WARN_NULL_TO_NOTNULL error code, 22
ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION error code, 543	ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS error code, 70
ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION error code, 543	ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS error code, 70
ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS error code, 137	ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE error code, 81
ER_WARN_DEPRECATED_WITH_NOTE error code, 162	ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO error code, 70
ER_WARN_DEPRECATED_YEAR_UNSIGNED error code, 136	ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR error code, 80
ER_WARN_DEPRECATED_ZEROFILL error code, 126	ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT error code, 557
ER_WARN_ENGINE_TRANSACTION_ROLLBACK error code, 44	ER_WARN_PROPERTY_STRING_PARSE_FAILED error code, 552
ER_WARN_FIELD_RESOLVED error code, 23	ER_WARN_PURGE_LOG_IN_USE error code, 65
ER_WARN_FUNC_INDEX_NOT_APPLICABLE error code, 131	ER_WARN_PURGE_LOG_IS_ACTIVE error code, 65
ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET error code, 603	ER_WARN_QC_RESIZE error code, 24
ER_WARN_GTID_THRESHOLD_BREACH error code, 594	ER_WARN_REGEXP_USING_DEFAULT error code, 152
ER_WARN_HOSTNAME_WONT_WORK error code, 24	ER_WARN_REMOVED_SQL_MODE error code, 544
ER_WARN_HYPERGRAPH_EXPERIMENTAL error code, 142	ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME error code, 602
ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS error code, 557	ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_O error code, 609
ER_WARN_INDEX_NOT_APPLICABLE error code, 54	ER_WARN_RESERVED_SRID_RANGE error code, 109
ER_WARN_INVALID_DB_RESTRICTIONS error code, 557	ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_M error code, 572
ER_WARN_INVALID_HINT error code, 98	ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_S error code, 572
ER_WARN_INVALID_TIMESTAMP error code, 25	ER_WARN_SCHEDULED_TASK_RUN_FAILED error code, 639
ER_WARN_I_S_SKIPPED_TABLE error code, 49	ER_WARN_SF_UDF_NAME_COLLISION error code, 153
ER_WARN_LEGACY_SYNTAX_CONVERTED error code, 69	ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATE error code, 148
ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_KEY error code, 582	ER_WARN_SRS_ID_ALREADY_EXISTS error code, 108
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT error code, 570	ER_WARN_SRS_NOT_FOUND error code, 89
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST error code, 570	ER_WARN_SRS_NOT_FOUND_AXIS_ORDER error code, 92
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_PERMISSION error code, 571	ER_WARN_SSL_BROKEN_CHANNEL_INITIALIZATION_ERROR error code, 583
ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_NOT_SUPPORTED error code, 609	ER_WARN_TOO_MANY_RECORDS error code, 22
ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING error code, 613	ER_WARN_TOO_MANY_RECORDS error code, 22
	ER_WARN_TRG_ALREADY_EXISTS error code, 154
	ER_WARN_TRIGGER_DOESNT_HAVE_CREATED error code, 69

---

---

ER_WARN_UNKNOWN_KEYRING_AWS_REGION error code, 570	ER_WINDOW_SE_NOT_ACCEPTABLE error code, 96
ER_WARN_UNKNOWN_QB_NAME error code, 80	ER_WIN_LISTEN_BUT_HOW error code, 176
ER_WARN_UNLOAD_THE_NOT_PERSISTED error code, 90	ER_WIN_LOAD_LIBRARY_FAILED error code, 296
ER_WARN_UNSUPPORTED_HINT error code, 88	ER_WL9236_NOW_UNUSED error code, 96
ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME error code, 80	ER_WRITABLE_CONFIG_REMOVED error code, 174
ER_WARN_USING_OTHER_HANDLER error code, 22	ER_WRITE_ROW_TO_PARTITION_FAILED error code, 285
ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED error code, 141	ER_WRITE_SET_EXCEEDS_LIMIT error code, 87
ER_WARN_VIEW_MERGE error code, 28	ER_WRONG_ARGUMENTS error code, 18
ER_WARN_VIEW_WITHOUT_KEY error code, 29	ER_WRONG_AUTO_KEY error code, 8
ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOGGER_WRONG_COMPRESSION_LEVEL_CLIENT error code, 570	ER_WRONG_COLUMN_NAME error code, 14
ER_WARN_WRONG_COMPRESSION_LEVEL_LOG error code, 570	ER_WRONG_COMPRESSION_ALGORITHM_CLIENT error code, 132
ER_WASTEFUL_NET_BUFFER_SIZE error code, 171	ER_WRONG_COMPRESSION_LEVEL_CLIENT error code, 132
ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS error code, 562	ER_WRONG_COUNT_FOR_KEY error code, 254
ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH error code, 94	ER_WRONG_COUNT_FOR_ORIGIN error code, 254
ER_WINDOW_DUPLICATE_NAME error code, 95	ER_WRONG_COUNT_OF_ELEMENTS error code, 254
ER_WINDOW_EXPLAIN_JSON error code, 96	ER_WRONG_DATETIME_SPEC error code, 174
ER_WINDOW_FRAME_END_ILLEGAL error code, 94	ER_WRONG_DB_NAME error code, 10
ER_WINDOW_FRAME_ILLEGAL error code, 95	ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR error code, 36
ER_WINDOW_FRAME_START_ILLEGAL error code, 94	ER_WRONG_FIELD_SPEC error code, 7
ER_WINDOW_FUNCTION_IGNORES_FRAME error code, 96	ER_WRONG_FIELD_TERMINATORS error code, 9
ER_WINDOW_ILLEGAL_ORDER_BY error code, 95	ER_WRONG_FIELD_WITH_GROUP error code, 7
ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE error code, 95	ER_WRONG_FIELD_WITH_GROUP_V2 error code, 77
ER_WINDOW_INVALID_WINDOW_FUNC_USE error code, 95	ER_WRONG_FILE_NAME error code, 80
ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SPEC error code, 114	ER_WRONG_FK_DEF error code, 21
ER_WINDOW_NO_CHILD_PARTITIONING error code, 94	ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN error code, 79
ER_WINDOW_NO_GROUP_ORDER error code, 96	ER_WRONG_GROUP_FIELD error code, 7
ER_WINDOW_NO_GROUP_ORDER_UNUSED error code, 96	ER_WRONG_JSON_TABLE_VALUE error code, 103
ER_WINDOW_NO_INHERIT_FRAME error code, 94	ER_WRONG_KEY_COLUMN error code, 15
ER_WINDOW_NO_REDEFINE_ORDER_BY error code, 94	ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX error code, 114
ER_WINDOW_NO_SUCH_WINDOW error code, 94	ER_WRONG_LOCK_OF_SYSTEM_TABLE error code, 33
ER_WINDOW_RANGE_BOUND_NOT_CONSTANT error code, 95	ER_WRONG_MRG_TABLE error code, 15
ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE error code, 95	ER_WRONG_MVI_VALUE error code, 130
ER_WINDOW_RANGE_FRAME_ORDER_TYPE error code, 95	ER_WRONG_NAME_FOR_CATALOG error code, 24
ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE error code, 95	ER_WRONG_NAME_FOR_INDEX error code, 24
ER_WINDOW_ROWS_INTERVAL_USE error code, 96	ER_WRONG_NATIVE_TABLE_STRUCTURE error code, 49
	ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT error code, 19
	ER_WRONG_OBJECT error code, 28
	ER_WRONG_OUTER_JOIN error code, 11
	ER_WRONG_OUTER_JOIN_UNUSED error code, 11
	ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT error code, 42
	ER_WRONG_PARAMCOUNT_TO_PROCEDURE error code, 10
	ER_WRONG_PARAMETERS_TO_NATIVE_FCT error code, 42

---

---

ER_WRONG_PARAMETERS_TO_PROCEDURE error code, 10	ER_XA_RECOVER_FOUND_TRX_IN_SE error code, 186
ER_WRONG_PARAMETERS_TO_STORED_FCT error code, 42	ER_XA_RECOVER_FOUND_XA_TRX error code, 186
ER_WRONG_PARTITION_NAME error code, 41	ER_XA_REPLICATION_FILTERS error code, 129
ER_WRONG_PERFSCHEMA_USAGE error code, 49	ER_XA_RETRY error code, 86
ER_WRONG_SIZE_NUMBER error code, 39	ER_XA_ROLLING_BACK_XID error code, 186
ER_WRONG_SPVAR_TYPE_IN_LIMIT error code, 50	ER_XA_STARTING_RECOVERY error code, 186
ER_WRONG_SRID_FOR_COLUMN error code, 101	ER_XA_TEMP_TABLE error code, 153
ER_WRONG_STRING_LENGTH error code, 36	ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED error code, 326
ER_WRONG_SUB_KEY error code, 9	ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED error code, 324
ER_WRONG_SUM_SELECT error code, 7	ER_XPLUGIN_CAPABILITY_CLIENT_INTERACTIVE_FAILED error code, 331
ER_WRONG_TABLESPACE_NAME error code, 80	ER_XPLUGIN_CAPABILITY_EXPIRED_PASSWORD error code, 330
ER_WRONG_TABLE_NAME error code, 10	ER_XPLUGIN_CLIENT_KILL_MSG error code, 329
ER_WRONG_TYPE_COLUMN_VALUE_ERROR error code, 47	ER_XPLUGIN_CLIENT_RELEASE_TRIGGERED error code, 328
ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD error code, 295	ER_XPLUGIN_CLIENT_SSL_HANDSHAKE_FAILED error code, 325
ER_WRONG_TYPE_FOR_VAR error code, 20	ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN error code, 326
ER_WRONG_USAGE error code, 19	ER_XPLUGIN_COMPRESSION_ERROR error code, 570
ER_WRONG_VALUE error code, 39	ER_XPLUGIN_DETECTED_HANGING_CLIENTS error code, 324
ER_WRONG_VALUE_COUNT error code, 7	ER_XPLUGIN_EMPTY_ADMIN_CMD error code, 329
ER_WRONG_VALUE_COUNT_ON_ROW error code, 13	ER_XPLUGIN_ERROR_MSG error code, 319
ER_WRONG_VALUE_FOR_TYPE error code, 32	ER_XPLUGIN_ERROR_READING_SOCKET error code, 327
ER_WRONG_VALUE_FOR_VAR error code, 20	ER_XPLUGIN_ERROR_WRITING_TO_CLIENT error code, 327
ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART error code, 139	ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP error code, 325
ER_X509_CANT_CHMOD_KEY error code, 193	ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER error code, 325
ER_X509_CANT_CREATE_CERT error code, 194	ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE error code, 328
ER_X509_CANT_READ_CA_CERT error code, 194	ER_XPLUGIN_FAILED_AT_SSL_CONF error code, 325
ER_X509_CANT_READ_CA_KEY error code, 193	ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT error code, 324
ER_X509_CANT_WRITE_CERT error code, 194	ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS error code, 583
ER_X509_CANT_WRITE_KEY error code, 193	ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION error code, 329
ER_X509_CIPHERS_MISMATCH error code, 193	ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN error code, 326
ER_X509_ISSUER_MISMATCH error code, 193	ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD error code, 329
ER_X509_NEEDS_RSA_PRIVKEY error code, 193	ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT error code, 330
ER_X509_SUBJECT_MISMATCH error code, 193	ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO error code, 330
ER_XAER_DUPID error code, 34	
ER_XAER_INVALID error code, 31	
ER_XAER_NOTA error code, 31	
ER_XAER_OUTSIDE error code, 31	
ER_XAER_RMERR error code, 31	
ER_XAER_RMFAIL error code, 31	
ER_XA_CANT_CREATE_MDL_BACKUP error code, 568	
ER_XA_COMMITTING_XID error code, 186	
ER_XA_IGNOREING_XID error code, 186	
ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER error code, 186	
ER_XA_RBDEADLOCK error code, 44	
ER_XA_RBROLLBACK error code, 31	
ER_XA_RBTIMEOUT error code, 44	
ER_XA_RECOVERY_DONE error code, 187	
ER_XA_RECOVER_EXPLANATION error code, 187	

---

---

ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX error code, 329	ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG_B error code, 327
ER_XPLUGIN_FAILED_TO_GET_SYS_VAR error code, 329	ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION error code, 327
ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION error code, 326	ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XPLUGIN error code, 319
ER_XPLUGIN_FAILED_TO_INTERRUPT_SESSION error code, 328	ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOC_SECTIO error code, 324
ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION error code, 330	ER_XPLUGIN_RETRYING_BIND_ON_PORT error code, 328
ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES error code, 324	ER_XPLUGIN_SCHEDULER_STARTED error code, 327
ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG error code, 331	ER_XPLUGIN_SCHEDULER_STOPPED error code, 327
ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT error code, 324	ER_XPLUGIN_SERVER_EXITED error code, 319
ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS error code, 326	ER_XPLUGIN_SERVER_EXITING error code, 319
ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG error code, 330	ER_XPLUGIN_SERVER_STARTS_HANDLING_CONNECTIONS error code, 328
ER_XPLUGIN_FAILED_TO_STOP_SERVICES error code, 528	ER_XPLUGIN_SERVER_STOPPED_HANDLING_CONNECTIONS error code, 328
ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT error code, 330	ER_XPLUGIN_SHUTDOWN_TRIGGERED error code, 328
ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX error code, 542	ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED error code, 324
ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX_TO error code, 329	ER_XPLUGIN_SSL_HANDSHAKE_WITH_SERVER_FAILED error code, 325
ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF error code, 330	ER_XPLUGIN_STARTUP_FAILED error code, 318
ER_XPLUGIN_FAILED_TO_USE_SSL_CONF error code, 319	ER_XPLUGIN_TASK_SCHEDULING_FAILED error code, 325
ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS error code, 583	ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION error code, 326
ER_XPLUGIN_FAIL_TO_GET_RESULT_DATA error code, 330	ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT error code, 324
ER_XPLUGIN_FORCE_STOP_CLIENT error code, 323	ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING_CMD error code, 325
ER_XPLUGIN_GET_PEER_ADDRESS_FAILED error code, 331	ER_XPLUGIN_UNEXPECTED_MSG_DURING_AUTHENTICATION error code, 327
ER_XPLUGIN_INVALID_AUTH_METHOD error code, 327	ER_XPLUGIN_UNINITIALIZED_MESSAGE error code, 326
ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT error code, 326	ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED error code, 329
ER_XPLUGIN_IPv6_AVAILABLE error code, 329	ER_XPLUGIN_USER_ACCOUNT_WITH_ALL_PERMISSIONS error code, 328
ER_XPLUGIN_LISTENER_SETUP_FAILED error code, 325	ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX error code, 319
ER_XPLUGIN_LISTENER_STATUS_MSG error code, 328	ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER error code, 319
ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR error code, 327	ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION error code, 319
ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED error code, 323	ER_XPLUING_NET_STARTUP_FAILED error code, 325
ER_XPLUGIN_MESSAGE_TOO_LONG error code, 326	ER_YES error code, 3
	ER_ZLIB_Z_BUF_ERROR error code, 22
	ER_ZLIB_Z_DATA_ERROR error code, 22
	ER_ZLIB_Z_MEM_ERROR error code, 22

---

---

## W

WARN\_AES\_KEY\_SIZE error code, 87  
WARN\_COND\_ITEM\_TRUNCATED error code, 46  
WARN\_DATA\_TRUNCATED error code, 22  
WARN\_DATA\_TRUNCATED\_FUNCTIONAL\_INDEX  
error code, 113  
WARN\_NAMED\_PIPE\_ACCESS\_EVERYONE error  
code, 68  
WARN\_NON\_ASCII\_SEPARATOR\_NOT\_IMPLEMENTED  
error code, 46  
WARN\_NO\_CONNECTION\_METADATA error code, 44  
WARN\_NO\_MASTER\_INFO error code, 44  
WARN\_ON\_BLOCKHOLE\_IN\_RBR error code, 66  
WARN\_OPTION\_BELOW\_LIMIT error code, 51  
WARN\_OPTION\_IGNORED error code, 44  
WARN\_PLUGIN\_BUSY error code, 44  
WARN\_UNENCRYPTED\_TABLE\_IN\_ENCRYPTED\_DB  
error code, 121  
WARN\_UNSUPPORTED\_ACL\_TABLES\_READ error  
code, 143  
WARN\_USELESS\_SPATIAL\_INDEX error code, 104

