



Chapter 1: Making the Case for Docker Enterprise





- Best where applications are a stack of application dedicated services
- Development is application focused
- Typical 3 – Tier applications
- Lift and shift legacy web applications

-- Bottom line --

- Swarm is NOT dead – significant enhancements 18.09
- Easier to build, manage and secure
- Monolithic Service deployment
- Production Support for Windows with near Linux Parity





kubernetes


- Best where applications are composed from a network of long running services
- Development teams are service focused
- Large scale microservices applications
- Bottom-up, multi layer API services for enterprise or 3rd party consumption

-- Bottom line --


- Management plane as a Service (AKS/EKS/GKE) with large echo-system modules
- Modular Service deployment
- Beta, limited Windows capabilities
- Vendor lock-in with many supported versions


Chapter 2: Docker Enterprise - an Architectural Overview








Phased, Agile Adoption













Chapter 3: Getting Started - Docker Enterprise Proof of Concept



 docker store

Search for great content (e.g., mysql)

ExplorePublishFeedback

 nvisiantc

Setup Instructions

 1 Month Trial | Tue 09/26/2018

Get Docker EE on Ubuntu

Go to <https://docs.docker.com/engine/installation/linux/ubuntu/> for detailed install instructions, and be sure to use your custom Docker EE repository URL where a repository is mentioned.

Getting Started with Docker Enterprise Edition

Install on Linux servers

Follow [these instructions](#) to install:

- Docker Enterprise Edition container engine
- Docker Universal Control Plane (UCP)
- Docker Trusted Registry (DTR)

Setup Security Scanning

Resources

Expires 11/24/2018

[License Key](#)

[Download CVE Vulnerability Database for DTR version 2.2.5 or lower](#)

[Download CVE Vulnerability Database for DTR version 2.2.6 or higher](#)

[Getting Started](#)

[User Guide](#)

Copy and paste this URL to download your Edition:

<https://storebits.docker.com/ee/ubuntu/sub-a>

The screenshot shows the Visual Studio Code interface with a file named 'Install-EE-Engine-notes.md' open. The editor displays a markdown document with instructions for installing Docker Engine on Ubuntu. The code is as follows:

```
4
5 Docker Engine Install Docs - https://docs.docker.com/ee/supported-platforms/
6
7 ## Ubuntu Docker Engine Install
8 This page walks through the process described here
9 https://docs.docker.com/install/linux/docker-ee/ubuntu/
10
11 On each linux node, update the package manager.
12 ~~~
13 sudo apt-get update
14 ~~~
15
16 Now oEnable apt over HTTPS...
17 ~~~
18 sudo apt-get install -y \
19     apt-transport-https \
20     ca-certificates \
21     curl \
22     software-properties-common
23 ~~~
24 Set up temp environmental variables
25 ~~~
```

Below the code editor, the 'TERMINAL' tab is active, showing a bash prompt: `ubuntu@ip-172-31-0-99:~$`. The status bar at the bottom indicates the file is on line 3, column 114, using UTF-8 encoding with LF line endings.

```
ubuntu@ip-172-31-0-170:~$ sudo docker info
Containers: 0
  Running: 0
  Paused: 0
  Stopped: 0
Images: 0
Server Version: 18.09.0-rc1
Storage Driver: overlay2
  Backing Filesystem: extfs
  Supports d_type: true
  Native Overlay Diff: true
Logging Driver: json-file
Cgroup Driver: cgroupfs
Plugins:
  Volume: local
  Network: bridge host macvlan null overlay
  Log: awslogs fluentd gcplogs gelf journald json-file local logentries splunk syslog
Swarm: inactive
Runtimes: runc
Default Runtime: runc
Init Binary: docker-init
containerd version: 99fc40fd6088baebe3c18b8f8093cd50d58815d6 (expected: 468a545b9edcd5932818eb9de8e72413e616e86e)
runc version: 4fc53a81fb7c994640722ac585fa9ca548971871 (expected: 69663f0bd4b60df09991c08812a60108003fa340)
init version: fec3683
Security Options:
  apparmor
  seccomp
  Profile: default
Kernel Version: 4.4.0-1067-aws
Operating System: Ubuntu 16.04.5 LTS
OSType: linux
Architecture: x86_64
CPUs: 2
Total Memory: 7.795GiB
```



```
Administrator: Windows PowerShell
PS C:\Users\Administrator> docker info
Containers: 0
  Running: 0
  Paused: 0
  Stopped: 0
Images: 0
Server Version: 18.09.0-beta3
Storage Driver: windowsfilter
  Windows:
Logging Driver: json-file
Plugins:
  Volume: local
  Network: ics l2bridge l2tunnel nat null overlay transparent
  Log: awslogs etwlogs fluentd gelf json-file local logentries splunk syslog
Swarm: inactive
Default Isolation: process
Kernel Version: 10.0 14393 (14393.2551.amd64fre.rs1_release.181004-1309)
Operating System: Windows Server 2016 Datacenter Version 1607 (OS Build 14393.2551)
OSType: windows
Architecture: x86_64
CPUs: 2
Total Memory: 8GiB
Name: EC2AMAZ-SNCEIC7
ID: VZIV:QABT:63VB:KUOW:4FOR:BTTB:QULZ:U7KS:CIZK:QWTU:63SI:65EG
Docker Root Dir: C:\ProgramData\docker
Debug Mode (client): false
Debug Mode (server): false
Registry: https://index.docker.io/v1/
Labels:
  com.docker.security.fips=enabled
Experimental: false
Insecure Registries:
  127.0.0.0/8
Live Restore Enabled: false
PS C:\Users\Administrator> _
```

Docker Enterprise

Universal Control Plane
v3.1.0-beta3

Access Control

Shared Resources

Collections

Stacks

Containers

Images

Nodes

Docs

Kubernetes API Docs

Live API

1 Node(s)

Add Node

STATUS	NAME	TYPE	ROLE	ADDRESS	ENGINE	OS/ARCH	CPU
	ip-172-31-C	mixed	mana...	172.31.0.1...	18.09.0-r...	linux/x8...	8.18

Add Node

Node Type*

WINDOWS

LINUX

Node Role* ?

MANAGER

WORKER

☐ Use a custom listen address ?

☐ Use a custom advertise address ?

Nodes are added to the cluster by using Docker's 'swarm join' command. Use the following command on the engine you want to connect to the cluster.

```
docker swarm join --token SWMTKN-1-3ggoagvdn7jm27pf1ayqj3z7zmyl272fix6jqv0vrh4g1v9785-806uco0sh7qpuzp3c6zgbwk17172.31.0.170:2377
```

Add Node

Default Orchestrator Type

The default orchestrator type for new nodes created is swarm. To change the orchestrator type, as an admin, go to [Settings -> Scheduler page](#)

Node Type*

WINDOWS

LINUX

*Windows nodes can only be added as worker nodes

Step 1

Adding Windows nodes to UCP

If you're deploying windows nodes, please follow the steps in the Documentation

View The Docs

Step 2

☒ I have followed the instructions and I'm ready to join my windows node.

☐ Use a custom listen address ?

☐ Use a custom advertise address ?

Nodes are added to the cluster by using Docker's 'swarm join' command. Use the following command on the engine you want to connect to the cluster.

```
docker swarm join --token SWMTKN-1-52gmoem4bupp74ozji2983jtuo2co19oyt4a01sxcj0nigw4wn-23g13ty0hnnvisfwnwjmvvx8w10.10.1.40:2377
```

[15]

 **Docker Enterprise**

Universal Control Plane

v3.1.0-beta3

admin

Dashboard

Access Control

Shared Resources

Collections

Stacks

Containers

Images

Nodes

Kubernetes

Docs


Kubernetes API Docs


Live API


4 Node(s)


Add Node

STATUS	NAME	TYPE	ROLE	ADDRESS	ENGINE	OS/ARCH	CPU	MEMORY	DISK
●	ip-172-31-0	mixed	mana...	172.31.0.1...	18.09.0-r...	linux/x8...	7.29%	17.17%	49.93%
●	EC2AMAZ-7	swarm	worker	172.31.0.1...	18.09.0-b...	window...	0%	1.49%	-
●	ip-172-31-0	swarm	worker	172.31.0.49	18.09.0-r...	linux/x8...	1.16%	2.47%	30.42%
●	ip-172-31-0	swarm	worker	172.31.0.7	18.09.0-r...	linux/x8...	3.45%	2.49%	30.42%











```
graph TD; A["microsoft/dotnet-framework:3.5-sdk<br/><Official Image>"] --> B["mta-dev-web-builder:3.5<br/><Base-Image>"]; B --> C["App-Image:v1<br/><Application Image>"]
```

microsoft/dotnet-framework:3.5-sdk
<Official Image>

mta-dev-web-builder:3.5
<Base-Image>

App-Image:v1
<Application Image>





 **Docker Enterprise**
Trusted Registry
2.6.0-beta3

 admin ▼

 Search

 **Repositories**

 Organizations

 Users

 System

API

Docs

Repositories

Filter by

All namespaces × ▼

New repository

Repository


app-dev / app-image Private [View details](#)

app-dev / db-image Private [View details](#)

<

>

[23]






Woah!


Something's wrong. We're looking into it.


© 2018 - Company, Inc.



Chapter 4: Preparing the Docker Enterprise Pilot Cluster




















Chapter 5: Prepare and Deploy a Docker Enterprise Pilot Application





FULL CONTROL:

- Exec
- Namespaces
- Custom Kernel Capabilities
- Host Bind Mounts
- Privileged Mode

SCHEDULER

- Node Schedule
- Node View



Node permissions

⚠ No Node Permissions

RESTRICTED CONTROL:

- Create
- Run
- Restart
- Stop
- Delete


⚠ No Node Permissions



VIEW ONLY:


⚠ No Node Permissions



- Inspect
- View

NONE
















Chapter 6: Design and Pilot a Docker Enterprise CI Pipeline









DockerEEBook > Projects

DockerEEBook projects:

New project

DockerEEBook / atsea-web

6.5 MB

Members

Edit

Remove

DockerEEBook / atsea-db

533 KB

Members

Edit

Remove

DockerEEBook / atsea-deploy

1.1 MB

Members

Edit

Remove

DockerEEBook / atsea-reverse_proxy

265 KB

Members

Edit

Remove

DockerEEBook / atsea-payment

297 KB

Members

Edit

Remove

GitLab

Projects ▾

Groups ▾

Activity

Milestones

Snippets



D

DockerEEBook



Overview



Issues0



Merge Requests0



Kubernetes



Members



Settings

General

Projects

CI / CD

Webhooks

Billing

To start serving your jobs you can add Runners to your group

Group Runners

GitLab Group Runners can execute code for all the projects in this group. They can be managed using the Runners API.

Set up a group Runner manually

1. Install [GitLab Runner](#)
2. Specify the following URL during the Runner setup: `https://gitlab.com/`
3. Use the following registration token during setup: `DUdA7V-y`

Reset runners registration token

4. Start the Runner!

Available group Runners : 1.

DUdA7V-y

docker-iscsi-runner

#670581

Pause

Remove Runner

docker

ntc

[45]

dev / atsea-db_build

Private

Info

Permissions

Tags

Webhooks

Promotions

Pruning

Mirrors

Settings

Activity

Is source

Is target

New promotion policy

Promote To Target If...

Tag name

starts with RC-

Critical Vulnerabilities

equals 0

Add filter

TARGET REPOSITORY

test / atsea-db_build

Tag Name In Target

RC-test

Variables for new tag name:
%n - tag name
%a - weekday (Sun, Mon, Tue)
%d - day of the month (01, 02, 31)
%b - month (Jan, Feb)
%m - month (01, 12)
%y - year (16, 17)
[See all variables](#)

Cancel Save Save & Apply

Docker Enterprise

Trusted Registry

2.6.0

admin

Profile

Account

Logout

Search

Repositories

Organizations

Organizations / dev / Members

dev

Org Members

Teams

Create a team to give users more repository permissions.

Members

Repositories


Settings

Add user

Username	Full Name		
admin	No name	Org Owner	x
oopsmanager	Otto OpsManager	Org Owner	x
builder	CI Build Account	Org Owner	x

PreviousNextItems per page 10 25 50 100

[46]



Docker Enterprise
Trusted Registry
2.6.0

admin

Search

Repositories

Organizations

Users

System

Repositories / dev / atsea-payment_build / Tags

dev / atsea-payment_build

Private

InfoPermissions**Tags**WebhooksPromotions

☐	Image	Os/Arch	Image ID	Size (Compressed)
☐	RC-DEV	linux / amd64	4e4bbbef7d49	2.11 MB
☐	master	linux / amd64	4e4bbbef7d49	2.11 MB

GitLab

Projects

Groups

Activity

Milestones

Snippets

A atsea-db

Project

Repository

Issues0

Merge Requests0

CI / CD

Pipelines

DockerEEBook > atsea-db > Pipelines

All14

Pending0

Running0

Finished14

Branches

Tags

Status	Pipeline	Commit	Stages
passed	#46121337 by latest	master -> bd29e042 Clean up...	✓ ✓ ✓
passed	#46074572 by	master -> a771c3e8 Final cleanup	✓ ✓ ✓

Docker Enterprise

Trusted Registry

2.6.2

admin

Search

Repositories

Organizations

Users

System

API

Repositories / test / atsea-db_build / Tags

test / atsea-db_build

Private

Info

Permissions

Tags

Webhooks

Promotions

Pruning

Mirrors

Settings

Act

☐	Image	Os/Arch	Image ID	Size (Compressed)	Signed	Last Pushed	Vulnerabilities
☐	RC-test (Promoted)	linux / amd64	77edfb0f774a	116.87 MB		21 minutes ago by builder	6 Critical 24 Major 18 Minor View details
☐	kv1	linux / amd64	77edfb0f774a	116.87 MB		5 days ago by admin	Scan out of date. Rescan View details

<

>

```
$ docker container run --network atsea-web-${CI_PIPELINE_ID}_front-tier --name 1
driver:${CI_PIPELINE_ID}
Running after script...
$ docker stack rm atsea-web-${CI_PIPELINE_ID}
Removing service atsea-web-46142493_appserver
Removing service atsea-web-46142493_database
Removing service atsea-web-46142493_payment_gateway
Removing secret atsea-web-46142493_postgres_password
Removing secret atsea-web-46142493_payment_token
Removing network atsea-web-46142493_front-tier
Removing network atsea-web-46142493_payment
Removing network atsea-web-46142493_back-tier
$ docker container rm -f local-test-driver-container-${CI_PIPELINE_ID}
local-test-driver-container-46142493
$ docker image rm local-test-driver:${CI_PIPELINE_ID}
Untagged: local-test-driver:46142493
Deleted: sha256:5e461fa057d3cdb2314a3867f8239334b7b19c0ad1dffad2de01ba1f42dee23
Deleted: sha256:0a80c51bcaab25cd7f6c1488d486625415d2d25fc00f4fb0c6e7f32d83e1986
Deleted: sha256:75b67a25798e2382ecaa5b66e6adec06ea9ba1cdcd5292f7461e82ada7e224
Deleted: sha256:942acb39c5c1fbcd1f14e44e1f7934c3bc3c5953ede45235541078cb0fe6fc6
Deleted: sha256:23bc8b904a9fcb795183696a0783f402e6dc419816c69ac6f8717c3f6036f45
ERROR: Job failed: exit code 1
```

```

$ docker container run --network atsea-web-${CI_PIPELINE_ID}_front-tier -
driver:${CI_PIPELINE_ID}
Running after script...
$ docker stack rm atsea-web-${CI_PIPELINE_ID}
Removing service atsea-web-46142789_appserver
Removing service atsea-web-46142789_database
Removing service atsea-web-46142789_payment_gateway
Removing secret atsea-web-46142789_payment_token
Removing secret atsea-web-46142789_postgres_password
Removing network atsea-web-46142789_back-tier
Removing network atsea-web-46142789_payment
Removing network atsea-web-46142789_front-tier
$ docker container rm -f local-test-driver-container-${CI_PIPELINE_ID}
local-test-driver-container-46142789
$ docker image rm local-test-driver:${CI_PIPELINE_ID}
Untagged: local-test-driver:46142789
Job succeeded

```


Docker Enterprise
 Universal Control Plane
 v3.1.3

- admin
- Dashboard
- Access Control
- Shared Resources
 - Collections
 - Stacks**
 - Containers
 - Images
 - Nodes
- Kubernetes

< Stacks


atsea-deployer-test


Overview Services Networks Volumes Secrets







☐	STATUS	NAME ↕	IMAGE ▾
☒	2/2	atsea-deployer-test_	dtr.nvisia.io/test/atsea-web_build:RC-test@sha256:c946d0...
☒	1/1	atsea-deployer-test_	dtr.nvisia.io/test/atsea-payment_build:RC-test@sha256:41a...
☒	1/1	atsea-deployer-test_	dtr.nvisia.io/test/atsea-db_build:RC-test@sha256:156d94e...


Chapter 7: Pilot Docker Enterprise Platform Monitoring and Logging















Wiki Service is Down

One or more Swarm services are down

 High ▼

1 Define

a Select entity to monitor ?

Alert if any ▼ ×
 ▼ is down.

b Scope ?

▼ is ▼ ▼
 ▼

c Trigger ?

If entity is down for the last minute ▼ for % of the time

Prod Worker Is Down

Insert alert description

 High ▼

1 Define

(a) Select entity to monitor ?

Alert if any host.hostName ▼ ×
Select a label... ▼ is down.

(b) Scope ?

swarm.node.label.com.nvisia... ▼ is ▼ prod ▼
Select a label... ▼

(c) Trigger ?

If entity is down for the last 2 minute ▼ for 100 % of the time

3 Act

Activate Sysdig Capture 

Storage Sysdig Monitor Storage ▼ (Go to [Sysdig Storage](#) to review setting)

File Name alert-capture.scap

Time frame 15 seconds

Filter Sysdig Capture Filter

[Swarm] Task with No Containers Running

No running containers available for one or more Swarm services

 Medium ▼

1 Define

a Metric ?

Average ▼ of swarm.service.task.running ▼ ↕

b Scope ?

everywhere ▼


c Trigger ?

If metric < ▼ 0.8 for the last 3 minute ▼ on average ▼

Multiple Alerts ▼

Trigger a separate alert for each **segment**: swarm.service.name ▼ ×
Select a label... ▼

Chapter 8: First Application in Production with Docker Enterprise



 **Docker Enterprise**
Trusted Registry
2.6.0

admin

Search

Repositories

Organizations

Users

System

Repositories / qa / atsea-web_stage / Mirrors / New

qa / atsea-web_stage

Private

Mirror direction

 **Push to remote registry**
Images will push from this registry to the remote registry

 **Pull from remote registry**
Images will pull from the remote registry to this registry

Connect to a remote repository

Registry type

Docker Trusted Registry

Registry URL

https://

http://

dtr.p1p1d.mydomain.com

Username

prod-stager

Password or access token

.....

Repository

staging / atsea-web

Triggers

Copy image to remote repository if it has...

Tag name
starts with v

Add criteria:

Tag name

Component name

All vulnerabilities

Critical vulnerabilities

Major vulnerabilities

Minor vulnerabilities

License name

Last updated at

Mirrored image's tag

%n

Variables for tag name:

%n = tag name

%d = day of the month (01, 02, 31)

%m = month (01, 02)



%a = weekday (Sun, Mon, Tue)

%b = month (Jan, Feb)

%y = year (16, 17)

[See all variables](#)

[61]



 Docker Enterprise

Trusted Registry

2.6.0

admin

Search

Repositories

Organizations

Users

System

API

Docs

Repositories / test / atsea-payment_build / RC-test / Components

test / atsea-payment_build : RC-test

Private

linux / amd640367cd2eeab42.63 MBPushed 14 days ago by builder2 majorAll layers already scanned

DeletePromoteScan

LayersComponents

busybox1.29.3-r11 Major

busybox1.29.3-r121 Major

apk-tools2.10.3-r1Clean

openssl1.1.1a-r1Clean

busybox

Version: 1.29.3-r10

License: GPL

Vulnerabilities	Severity	Description
CVE-2018-20679	5	An issue was discovered in BusyBox before 1.30.0. An out of bounds read in udhcp components (consumed by the DHCP server, client, and relay) allows a remote attacker to leak sensitive information from the stack by sending a crafted DHCP message. This is related to verification in udhcp_get_option() in networking/udhcp/common.c that 4-byte options are indeed 4 bytes.

Show layers affected

 Docker Enterprise

Universal Control Plane

v3.1.3

admin

My Profile

Admin Settings

Support Dump

About

Sign Out

Dashboard

Access Control

Shared Resources

Stacks

Containers

Images

Nodes

Kubernetes

Swarm

Docs


< Stacks


atsea-deployer-test

OverviewServicesNetworksVolumesSecrets

Actions

	STATUS	NAME ^	IMAGE ^	VULNERABILITIES	MODE	UPDATED AT	LAST I
	2/2	atsea-deplc	dtr.nvisia.io/test/atsea-web_build...	29 Critical51 Major1 Minor	Replicated	29 minutes ...	
	1/1	atsea-deplc	dtr.nvisia.io/test/atsea-db_build:R...	5 Critical20 Major4 Minor	Replicated	29 minutes ...	
	1/1	atsea-deplc	dtr.nvisia.io/test/atsea-payment_...	0 Critical2 Major0 Minor	Replicated	29 minutes ...	





Admin Settings

X
Esc

Swarm

Certificates

Layer 7 Routing

Cluster Configuration

Authentication & Authorization

Logs

Audit Logs

License

Docker Trusted Registry

Docker Content Trust

Usage

Scheduler

Upgrade

Upgrade UCP

Current UCP Version: Universal Control Plane 3.1.3

You are currently using the latest version of UCP.

Cancel

Save

 Docker Enterprise

Trusted Registry

2.6.0

admin

Search

Repositories

Organizations

Users

System

API

Docs

Universal Control Plane

System / General

General

Storage

Security

Garbage collection

Job Logs

Updates

Your current Trusted Registry version is out of date. [Click here to read the release notes for upgrade information.](#) [View release notes](#)

Version

2.6.0

Check for updates

☒

License

Tier

 Advanced

Expires

November 20, 2019 8:47 AM


License Id

Auto refresh license

☐

Apply new license

Chapter 9: Important Docker Enterprise Production Topics



Docker Enterprise
Universal Control Plane
v3.1.3

Stacks

Containers

Images

Nodes

Kubernetes

+ Create

Namespaces

All Namespaces

Service Accounts

Controllers

Load Balancers

Pods

Configurations

Storage

Swarm

Services

Volumes

Networks

Secrets

Docs

Kubernetes API Docs

< Services

atsea-deployer-test_appserver

2 / 2 Last Updated an hour ago / Last Error: --

OverviewMetrics

Vulnerabilities: image was not in DTR scanning data response

UPDATE CONFIGURATION

Failure action

rollback

Max failure ratio

0

Parallelism

1

Order

stop-first

LIMITS

CPUs

1

Memory

1.5 GB



RESERVATIONS


CPUs



1

Memory

1.5 GB







Server Hostname

atsea. [REDACTED]

Check SSL

- ✓ atsea. [REDACTED] resolves to 38.140.113.29
- ✓ Server Type: Apache/2.2.15 (CentOS)
- ✓ The certificate should be trusted by all major web browsers (all the correct intermediate certificates are installed).
- ✓ The certificate was issued by DigiCert. [Write review of DigiCert](#)
- ✓ The certificate will expire in 273 days. [Remind me](#)
- ✓ The hostname (atsea. [REDACTED]) is correctly listed in the certificate.



Common name: * [REDACTED]
SANs: * [REDACTED]
Valid from November 20, 2018 to November 21, 2019
Serial Number: 0e274b7af77ebd961af056452af0e2d9
Signature Algorithm: sha256WithRSAEncryption
Issuer: RapidSSL RSA CA 2018



Common name: RapidSSL RSA CA 2018
Organization: DigiCert Inc **Org. Unit:** www.digicert.com
Location: US
Valid from November 6, 2017 to November 6, 2027
Serial Number: 08a5a246cd4b5c8c83d702b4bbab5349
Signature Algorithm: sha256WithRSAEncryption
Issuer: DigiCert Global Root CA

POLICY EVENTS

POLICIES

COMMANDS AUDIT

CAPTURES

COMPLIANCE

IMAGE SCANNING

Policy Events

1f6e38e4c330
in ntc-wrk-3.nvisia.io

LIST

Search

EXPORT

Browse By Sysdig Monitor Explo...

ntc-dtr-3.nvisia.io0

ntc-iscsi-1.nvisia.io0

3fd38f8334040

b71943074cfb0

ntc-lb1.nvisia.io0

ntc-ucp-1.nvisia.io0

ntc-ucp-2.nvisia.io0

ntc-ucp-3.nvisia.io0

ntc-wrk-1.nvisia.io1

ntc-wrk-2.nvisia.io0

ntc-wrk-3.nvisia.io1

170ba84b62c50

1f6e38e4c3301

54140b1e871d0

58b1368448340

7821d5dfe6800

a2b3c99888af0

a95fd01b05dc0

b43463843aac0

Terminal shell in container

ntc-wrk-3.nvisia.io > 1f6e38...

About 10 minutes

Policy Event Details

When
2/20/2019 10:20:32.427 pm (15 minutes ago)

Related Resources

Capture and commands will cover 10 minutes around the time of the event.

VIEW CAPTURES 1

VIEW COMMANDS 2

Severity

Medium

Triggered Policy

Terminal shell in container

Filter: Add Remove

Triggered Rule Type

Fa Ico

Scope

1. host.hostname: ntc-wrk-3.nvisia.io

2. container.id: 1f6e38e4c330

Host

Hostname: ntc-wrk-3.nvisia.io

MAC: 78:e3:b5:1b:12:58

Container

ID: 1f6e38e4c330

Name: nvisia-wiki_postgres.1.y6n0g5s2mw84ylmoawi5kgnin

Image: dtr.nvisia.io/pilot/postgres:v1.0.1@sha256:50c1dfdcbabb04767278f8e807f937cf...

COMMANDS AUDIT

POLICIES

CAPTURES

COMPLIANCE

IMAGE SCANNING

Commands Audit

1f6e38e4c330
in ntc-wrk-3.nvisia.io

Search

Browse By Sysdig Monitor ...

Entire infrastructure

ntc-dtr-...nvisia.io141

ntc-dtr-...nvisia.io101

ntc-dtr-...nvisia.io141

ntc-iscsi...nvisia.io0

ntc-lb1.nvisia.io0

ntc-... nvisia.io1.13 K


ntc-... nvisia.io1.14 K

ntc-... nvisia.io1.16 K

ntc-wr... nvisia.io121

ntc-wr... nvisia.io124

	Time	Shell	Command line	Scope
	02/20/19 10:20:32.369 pm	22287	sh	ntc-wrk-3.nvisia.io > 1f6e38e4c330
	02/20/19 10:20:24.718 pm	19115	ls	ntc-wrk-3.nvisia.io > 1f6e38e4c330



COMPLIANCE

Results > Docker Node Compliance

Download CSV

HIGH RISK

0

38

66

Fail

Warn

Pass

Completed on

Feb 18, 2019 - 12:00 am

Host Mac

b4:b5:2f:65:f0:8c

1. Host Configuration

2. Docker daemon configuration

3. Docker daemon configuration files

4. Container Images and Build File

5. Container Runtime

6. Docker Security Operations

7. Docker Swarm Configuration

5. Container Runtime

5.1

Ensure AppArmor Profile is enabled

Containers with no AppArmorProfile:
- sysdig-agent
- gitlab-runner

5.2

Ensure SELinux security options are set, if applicable

Containers with no SecurityOptions:
- gitlab-runner

5.3

Ensure Linux Kernel Capabilities are restricted within containers

5.4

Ensure privileged containers are not used

Containers running in privileged mode:
- sysdig-agent

5.5


Ensure sensitive host system directories are not mounted on containers


5.6

Ensure ssh is not run within containers

[76]

Chapter 10: More on Kubernetes with Docker Enterprise





ClusterRole: system:aggregate-to-view

Created 3 months ago

Overview

RULES

API Groups
N/A

Resources
configmaps, endpoints, persistentvolumeclaims, pods, replicationcontrollers, replicationcontrollers/scale, serviceaccounts, services

Verbs
get, list, watch

API Groups
N/A

Resources
bindings, events, limitranges, namespaces/status, pods/log, pods/status, replicationcontrollers/status, resourcequotas, resourcequotas/status

Verbs
get, list, watch

API Groups
N/A


Resources
namespaces


Verbs
get, list, watch

API Groups
apps

Resources
daemonsets, deployments, deployments/scale, replicaset, replicaset/scale, statefulsets, statefulsets/scale

Verbs
get, list, watch





Settings

General

Shared Drives

Advanced

Network

Proxies

Daemon

Kubernetes

Reset

Docker is running

Kubernetes is running

Kubernetes

Configure and manage the Kubernetes cluster



☒ Enable Kubernetes

Starts a Kubernetes single-node cluster when starting Docker Desktop.


☐ Deploy Docker Stacks to Kubernetes by default



Make Kubernetes the default orchestrator for `docker stack` commands (changes `~/.docker/config.json`)

☐ Show system containers (advanced)

Show kubernetes internal containers when using Docker commands.

Apply





4 Namespace(s)

Set context for all namespaces ☐

Actions

Create

☐	NAME	NODES COLLECTION
	atsea-test	
	default	
	kube-public	
	kube-system	

Create User

Details

Newly added users will automatically be added to the "docker-datacenter" organization; this organization has restricted privileges. These users will have restricted control to their own private collections.

Username

mpanthofer

Password

.....

Full Name

Mark Panthofer (no-admin)

☐ Is a Docker Enterprise admin

Create Role Binding

✕
Esc

A grant defines who (subject) has a specific access (role or cluster role) to a resource set (Kubernetes namespace).

✓ 1. Subject

User
mpanthofer

Edit

✓ 2. Resource Set

Namespace
atsea-test

Edit

3. Role

Role Type

ROLECLUSTER ROLE

Select Cluster Role

admin

Cancel

Create

```
mpanthofer@xps-bash::cli-mpanthofer-no-admin$ kubectl get all
Error from server (Forbidden): pods is forbidden: User "2177a148-729b-4aa2-aa28-eeeb1e701c55" cannot list pods in the namespace "default": access denied
Error from server (Forbidden): replicationcontrollers is forbidden: User "2177a148-729b-4aa2-aa28-eeeb1e701c55" cannot get replicationcontrollers in the namespace "default": access denied
Error from server (Forbidden): services is forbidden: User "2177a148-729b-4aa2-aa28-eeeb1e701c55" cannot get services in the namespace "default": access denied
Error from server (Forbidden): daemonsets.apps is forbidden: User "2177a148-729b-4aa2-aa28-eeeb1e701c55" cannot get daemonsets in the namespace "default": access denied
Error from server (Forbidden): deployments.apps is forbidden: User "2177a148-729b-4aa2-aa28-eeeb1e701c55" cannot get deployments in the namespace "default": access denied
Error from server (Forbidden): replicasetsets.apps is forbidden: User "2177a148-729b-4aa2-aa28-eeeb1e701c55" cannot get replicasetsets in the namespace "default": access denied
Error from server (Forbidden): statefulsets.apps is forbidden: User "2177a148-729b-4aa2-aa28-eeeb1e701c55" cannot get statefulsets in the namespace "default": access denied
Error from server (Forbidden): horizontalpodautoscalers.autoscaling is forbidden: User "2177a148-729b-4aa2-aa28-eeeb1e701c55" cannot get horizontalpodautoscalers in the namespace "default": access denied
Error from server (Forbidden): jobs.batch is forbidden: User "2177a148-729b-4aa2-aa28-eeeb1e701c55" cannot get jobs in the namespace "default": access denied
Error from server (Forbidden): cronjobs.batch is forbidden: User "2177a148-729b-4aa2-aa28-eeeb1e701c55" cannot get cronjobs in the namespace "default": access denied
mpanthofer@xps-bash::cli-mpanthofer-no-admin$ kubectl -n atsea-test get all
No resources found.
mpanthofer@xps-bash::cli-mpanthofer-no-admin$
```

IP: 10.60.38.134 HOST: 69c5ea9b8a82

[Create User](#)

[Sign in](#)

IP: 192.168.220.137 HOST: atsea-web-59774bc8c9-6trcl

[Create User](#)

[Sign in](#)

Docker Enterprise
 Universal Control Plane
 v3.1.3

admin

Dashboard

Access Control

Orgs & Teams

Users

Roles

Grants

Shared Resources

Kubernetes


+ Create

3 Storage & Volumes

Actions

Create

☐	NAME ↕	STATUS	TYPE ↕
	pvc-eb937812-3767-11e9-88f4-0242ac110007	Bound	PersistentVolume
	nfs-claim	Bound	PersistentVolumeClaim
	nfs-client	-	StorageClass



 **Docker Enterprise**
Universal Control Plane
v3.1.3

admin

Dashboard

Access Control

Shared Resources

Kubernetes

+ Create

Namespaces

All Namespaces

2 Pod(s)

Actions

Create

☐	STATE	STATUS	NAME	NAMESPACE	VULNERABILITIES	NODE	CREATED
☐		Running	my-nginx-nginx-ir	default	?	ntc-wrk-3.nvisi...	Today at 4:34 AM
☐		Running	my-nginx-nginx-ir	default	?	ntc-wrk-2.nvisi...	Today at 4:34 AM

 **PuTTY Reconfiguration**

Category:

Session

Logging

Terminal

Keyboard

Bell

Features

Window

Appearance

Behaviour

Translation

Selection

Colours

Connection

SSH

Kex

Host keys

Cipher

Tunnels

Options controlling SSH port forwarding

Port forwarding

☐ Local ports accept connections from other hosts

☐ Remote ports do the same (SSH-2 only)

Forwarded ports:

Remove

L8888 10.10.1.39:33394

Add new forwarded port:

Source port

Destination

☒ Local

☒ Auto

☐ Remote

☐ IPv4


☐ Dynamic

☐ IPv6

Add

Apply

Cancel



Chapter 11: Taking the Docker Enterprise Platform into the Future

